
**HP Integrity Superdome Enterprise Server
using
HP-UX 11.i V2 64-bit
and
Oracle 10g Database Enterprise Edition with
Partitioning**

TPC Benchmark™ H Full Disclosure Report

First Edition

January 5, 2004



First Edition - January 5, 2004

Hewlett-Packard Company, the sponsor of this benchmark test, believes that the information in this document is accurate as of the publication date. The information in this document is subject to change without notice. The sponsors assume no responsibility for any errors that may appear in this document. The pricing information in this document is believed to accurately reflect the current prices as of the publication date. However, the sponsors provide no warranty of the pricing information in this document.

Benchmark results are highly dependent upon workload, specific application requirements, and system design and implementation. Relative system performance will vary as a result of these and other factors. Therefore, TPC Benchmark H should not be used as a substitute for a specific customer application benchmark when critical capacity planning and/or product evaluation decisions are contemplated.

All performance data contained in this report was obtained in a rigorously controlled environment. Results obtained in other operating environments may vary significantly. No warranty of system performance or price/performance is expressed or implied in this report.

© Copyright Hewlett-Packard Company, 2004.

All rights reserved. Permission is hereby granted to reproduce this document in whole or in part provided the copyright notice printed above is set forth in full text on the title page of each item reproduced.

Printed in U.S.A., January 5, 2004.

HP, HP-UX, HP C/HP-UX, HP 9000 are registered trademarks of Hewlett-Packard Company.

ORACLE 10g, SQL*DBA, SQL*Loader, SQL*Net, SQL*Plus, Pro *C, and PL/SQL are trademarks of the Oracle Corporation

UNIX is a registered trademark in the United States, and other countries, licensed exclusively through X/Open Company Limited.

TPC Benchmark and TPC-H are registered trademarks of the Transaction Processing Performance Council.

All other brand or product names mentioned herein must be considered trademarks or registered trademarks of their respective owners.

Overview

This report documents the methodology and results of the TPC Benchmark™ H test conducted on the HP Integrity Superdome Enterprise Server, in conformance with the requirements of the TPC Benchmark™ H Standard Specification, Revision 2.1.0. The operating system used for the benchmark was HP-UX 11.i V2 64-bit; the DBMS was Oracle 10g.

Standard and Executive Summary Statements

The pages following this preface contain the Executive Summary and Numerical Quantities Summary of the benchmark results.

Auditor

The benchmark configuration, environment and methodology used to produce and validate the test results and the pricing model used to calculate the cost per QphH was audited by Francois Raab, InfoSizing, to verify compliance with the relevant TPC specifications.

TPC Benchmark H Overview

The TPC Benchmark™ H (TPC-H) is a decision support benchmark. It consists of a suite of business oriented ad-hoc queries and concurrent data modifications. The queries and the data populating the database have been chosen to have broad industry-wide relevance while maintaining a sufficient degree of ease of implementation. This benchmark illustrates decision support systems that

- Examine large volumes of data;
- Execute queries with a high degree of complexity;
- Give answers to critical business questions.

TPC-H evaluates the performance of various decision support systems by the execution of sets of queries against a standard database under controlled conditions. The TPC-H queries:

- Give answers to real-world business questions;
- Simulate generated ad-hoc queries(e.g., via a point and click GUI interface);
- Are far more complex than most OLTP transactions;
- Include a rich breadth of operators and selectivity constraints;
- Generate intensive activity on the part of the database server component of the system under test;
- Are executed against a database complying to specific population and scaling requirements;
- Are implemented with constraints derived from staying closely synchronized with an on-line production database.

The TPC-H operations are modeled as follows:

- The database is continuously available 24 hours a day, 7 days a week, for ad-hoc queries from multiple end users and updates against all tables, except possibly during infrequent (e.g., once a month) maintenance sessions;
- The TPC-H database tracks, possibly with some delay, the state of the OLTP database through ongoing updates which batch together a number of modifications impacting some part of the decision support database;
- Due to the world-wide nature of the business data stored in the TPC-H database, the queries and the updates may be executed against the database at any time, especially in relation to each other. In addition, this mix of queries and updates is subject to specific ACIDity requirements, since queries and updates may execute concurrently;

- To achieve the optimal compromise between performance and operational requirements the database administrator can set, once and for all, the locking levels and the concurrent scheduling rules for queries and updates.

The minimum database required to run the benchmark holds business data from 10,000 suppliers. It contains almost ten million rows representing a raw storage capacity of about 1 GB. Compliant benchmark implementations may also use one of the larger permissible database populations (e.g. 10000 GB), as defined in Clause 4.1.3.

The performance metrics reported by TPC-H measure multiple aspects of the capability of the system to process queries. The TPC-H metric at the selected size (QphH@Size) is the performance metric. To be compliant with the TPC-H standard, all references to TPC-H results for a given configuration must include all required reporting components (see Clause 5.4.7). The TPC believes that comparisons of TPC-H results measured against different database sizes are misleading and discourages such comparisons.

The TPC-H database must be implemented using a commercially available database management system (DBMS), and the queries executed via an interface using dynamic SQL. The specification provides for variants of SQL, as implementers are not required to have implemented a specific SQL standard in full. TPC-D uses terminology and metrics that are similar to other benchmarks, originated by the TPC and others. Such similarity in terminology does not in any way imply that TPC-H results are comparable to other benchmarks. The only benchmark results comparable to TPC-H are other TPC-H results compliant with the same revision.

Despite the fact that this benchmark offers a rich environment representative of many decision support systems, this benchmark does not reflect the entire range of decision support requirements. In addition, the extent to which a customer can achieve the results reported by a vendor is highly dependent on how closely TPC-H approximates the customer application. The relative performance of systems derived from this benchmark does not necessarily hold for other workloads or environments. Extrapolations to any other environment are not recommended.

Benchmark results are highly dependent upon workload, specific application requirements, and systems design and implementation. Relative system performance will vary as a result of these and other factors. Therefore, TPC-H should not be used as a substitute for a specific customer application benchmarking when critical capacity planning and/or product evaluation decisions are contemplated.


Benchmark sponsors are permitted several possible system designs, provided that they adhere to the model described in Clause 6. A full disclosure report (FDR) of the implementation details, as specified in Clause 8, must be made available along with the reported results.

General Implementation Guidelines

The purpose of TPC benchmarks is to provide relevant, objective performance data to industry users. To achieve that purpose, TPC benchmark specifications require that benchmark tests be implemented with systems, products, technologies and pricing that:

- Are generally available to users;
- Are relevant to the market segment that the individual TPC benchmark models or represents (e.g. TPC-H models and represents complex, high data volume, decision support environments);
- Would plausibly be implemented by a significant number of users in the market segment the benchmark models or represents.

Hewlett-Packard Company does not warrant or represent that a user can or will achieve performance similar to the benchmark results contained in this report. No warranty of system performance or price/performance is expressed or implied by this report

	HP Integrity Superdome Enterprise Server	TPC-H Rev 2.1.0										
		Report Date: January 5, 2004										
Total System Cost	Composite Query per Hour Metric	Price/Performance										
\$5,800,675	49,104.5 QphH@10000GB	\$118 QphH@10000GB										
Database Size	Database Manager	Operating System										
10000 GB*	Oracle 10g Database Enterprise Edition with Partitioning	HP-UX 11.i V2 64-bit										
		Other Software										
		Availability Date										
		None										
		March 25, 2004										
 <p>Query times in seconds</p> <table border="1"> <tr> <td>Database Load Time = 12:32:00</td> <td>Load Includes Backup: N</td> <td>Total Data Storage/Database Size = 10.53</td> </tr> <tr> <td>RAID (Base Tables Only): N</td> <td>RAID (Base Tables and Auxiliary Data Structures): N</td> <td>RAID (All): Y</td> </tr> </table>			Database Load Time = 12:32:00	Load Includes Backup: N	Total Data Storage/Database Size = 10.53	RAID (Base Tables Only): N	RAID (Base Tables and Auxiliary Data Structures): N	RAID (All): Y				
Database Load Time = 12:32:00	Load Includes Backup: N	Total Data Storage/Database Size = 10.53										
RAID (Base Tables Only): N	RAID (Base Tables and Auxiliary Data Structures): N	RAID (All): Y										
System Configuration <table> <tr> <td>Processors:</td> <td>64 Itanium2 1.5GHz, 6MB L3 Cache</td> </tr> <tr> <td>Memory:</td> <td>256 GB</td> </tr> <tr> <td>Disk Drives:</td> <td>1 HP Surestore Disk System 2100 with 4 - 36GB 1-36GB LP 10K LVD SE U320 HDD disks and 96 HP Surestore VA7110 (with a total of 1440 73GB 15K RPM LVD disks)</td> </tr> <tr> <td>Total Disk Storage</td> <td>105264GB (In this calculation one GB is defined as 1024*1024*1024 bytes)</td> </tr> <tr> <td>Lan Controllers</td> <td>1 HP 10/100 Base-T Lan Adapter</td> </tr> </table> <p>*Database Size includes only raw data (e.g. no temp, index, redundant storage space, etc.)</p>			Processors:	64 Itanium2 1.5GHz, 6MB L3 Cache	Memory:	256 GB	Disk Drives:	1 HP Surestore Disk System 2100 with 4 - 36GB 1-36GB LP 10K LVD SE U320 HDD disks and 96 HP Surestore VA7110 (with a total of 1440 73GB 15K RPM LVD disks)	Total Disk Storage	105264GB (In this calculation one GB is defined as 1024*1024*1024 bytes)	Lan Controllers	1 HP 10/100 Base-T Lan Adapter
Processors:	64 Itanium2 1.5GHz, 6MB L3 Cache											
Memory:	256 GB											
Disk Drives:	1 HP Surestore Disk System 2100 with 4 - 36GB 1-36GB LP 10K LVD SE U320 HDD disks and 96 HP Surestore VA7110 (with a total of 1440 73GB 15K RPM LVD disks)											
Total Disk Storage	105264GB (In this calculation one GB is defined as 1024*1024*1024 bytes)											
Lan Controllers	1 HP 10/100 Base-T Lan Adapter											



HP Integrity Superdome Enterprise Server

TPC-H Rev 2.1.0

Report Date: January 5, 2004

Description	Part Number	Source	Reference Price	Qty	Extended Price	3 yr. Maint. Price
Server Hardware						
Superdome left chassis	A5201A, Opt. 429	1	205,840	1	205,840	
Superdome right chassis	A5202A, Opt. 429	1	218,435	1	218,435	
IPF Superdome Cell Board (sx1000)	A6866A	1	16,000	16	256,000	
3 Year Svc & Support Price (Hardware and Software)						838,197
4GB SDRAM (4x1GB DIMMS)	A6863A	1	17,750	64	1,136,000	
PCI-x I/O chassis	A6864A	1	16,805	12	201,660	
Core I/O Card	A6865A	1	1,045	1	1,045	
CPU Itanium 2, 1.5GHz w/6MB iL3 cache (2 CPUs)	A6924A	1	40,000	32	1,280,000	
PCI 1000BT Lan Adapter	A6847A, Opt. 0D1	1	2,135	1	2,135	
I/O chassis enclosure for PCI chassis	A5862A	1	25,725	2	51,450	
Graphite I/O expansion power subsystem	A5861D	1	34,860	1	34,860	
PCI 2GB Fibre Channel Adapter	A6795A	1	2,240	96	215,040	
PCI Ultra160 SCSI Adapter	A6828A	1	1,323	1	1,323	
HP Surestore Disk System 2100	A5675A	1	700	1	700	
1-36GB LP 10K LVD SE U320 HDD	A6571A	1	720	4	2,880	
TA5300 Enclosure for DAT tape	C7508AZ	1	1,395	1	1,395	
DDS 4 tape	C5687B	1	1,450	1	1,450	
DVD Rom drive	C7499A	1	688	1	688	
SCSI Terminator LVD/SE HDTS68 Multimedia	C2364A	1	100	1	100	
HP Tape Array PSU/Fan Kit	C7496A	1	425	1	425	
SCSI Cable 10m VHDTS68/DHTS68 M/M Multimed	C2363B	1	335	1	335	
SCSI Cable 0.5m HDTS68 M/M Multimedia	C2978B	1	99	1	99	
SMS for HP Integrity Superdome Tower	A9801A	1	5,140	1	5,140	
				Subtotal	3,617,000	838,197
Server Software						
Oracle Database 10g Enterprise Edition for 3 years, Named User Plus		2	10,000	64	640,000	
Partitioning for 3 years, Named User Plus		2	2,500	64	160,000	
Oracle Database Server Support Package for 3 years:		2	6,000	1		6,000
HPUX 11i, V2 Foundation Operating Environment	B9429AC	1	2,370	64	151,680	
				Subtotal	951,680	6,000
Storage						
16 meter Fibre Optic Cable	A7525A	1	260	96	24,960	
HP Surestore VA 7110 w/ dual controller, 1024MB r A7294A		1	25,440	96	2,442,240	
*(large quantity discount)						
3 Year Support Price						364,224
73GB 15K RPM FC HDD (10% sparing included)*	A7288A, Opt 0D1	1	1,702	1584	2,696,522	138,240
*(large quantity discount)						
HP Rack System/E, 41U, Quartz Color	A4902A	1	1,910	8	15,280	
HP Rear Door for 41U Quartz Rack	A5213AZ	1	334	8	2,672	
Modular Power Dist.	A5137AZ	1	145	32	4,640	
200-240 Volts Power Option	A5137AZ, Opt AW4	1	94	32	3,008	
				Subtotal	5,189,322	502,464
				Total	9,758,002	1,346,661
Oracle Mandatory E-Business Discount on (Licenses and Support)						
Large Configuration Discount and Support Prepayment*						
					(161,200)	
					(4,503,976)	(638,813)
				Grand Total	5,092,827	707,848
Source: 1=HP,					3-yr Cost of Ownership:	5,800,675
2=Oracle (Pricing Contact: MaryBeth Pierantoni;					QphH@10000GB:	49,104.5
email: mary.beth.pierantoni@oracle.com; phone number: 650-506-2118)					\$/QphH@10000GB: \$	118
*All discounts are based on US list prices and for similar quantities and configurations						
Audited By: Francois Raab for InfoSizing (www.sizing.com)						

Prices used in TPC benchmarks reflect actual prices a customer would pay for a one-time purchase of the stated components. Individually negotiated discounts are not permitted. Special prices based on assumptions about past or future purchases are not permitted. All discounts reselect standard pricing policies for the listed components. For complete details, see the pricing sections of the TPC benchmark specifications. If you find the stated prices are not available according to these terms, please inform the TPC at pricing@tpc.org. Thank you.



HP Integrity Superdome Enterprise Server

TPC-H Rev 2.1.0

Report Date: January 5, 2004

Measurement Results

Database Scaling (SF/size)	10000
Total Data Storage/Database Size	10.53
Start of Database Load Time	2003-12-05 06:20:16
End of Database Load Time	2003-12-05 18:51:44
Database Load Time	12:32:00
Query Streams for Throughput Test (S)	9
TPC-H Power	64,248.7
TPC-H Throughput	37,530.0
TPC-H Composite Query-per-Hour Metric (QphH@10000GB)	49,104.5
Total System Price Over 3 Years	\$5,800,676
TPC-H Price/Performance Metric (\$/QphH@10000GB)	\$118

Measurement Intervals

Measurement Interval in Throughput Test (Ts)	189,928
--	---------

Duration of Stream Execution:

	SEED	Start Date/Time	End Date/Time	Duration
Stream 00	1205185144	12/5/03 19:28:14	12/6/03 01:39:03	6:10:49
Stream 01	1205185145	12/6/03 01:41:37	12/8/03 03:01:18	49:19:41
Stream 02	1205185146	12/6/03 01:41:37	12/8/03 02:17:05	48:35:28
Stream 03	1205185147	12/6/03 01:41:37	12/8/03 01:30:59	47:49:22
Stream 04	1205185148	12/6/03 01:41:37	12/8/03 00:46:38	47:05:01
Stream 05	1205185149	12/6/03 01:41:37	12/8/03 04:16:33	50:34:56
Stream 06	1205185150	12/6/03 01:41:37	12/8/03 00:37:07	46:55:30
Stream 07	1205185151	12/6/03 01:41:37	12/8/03 01:21:21	47:39:44
Stream 08	1205185152	12/6/03 01:41:37	12/8/03 01:39:51	47:58:14
Stream 09	1205185153	12/6/03 01:41:37	12/8/03 00:55:22	47:13:45
Refresh		12/6/03 04:16:33	12/8/03 06:27:05	50:10:32



HP Integrity Superdome Enterprise Server

TPC-H Rev 2.1.0

Report Date January 5, 2004

TPC-H Timing Intervals (in seconds)

Duration of stream execution:

Stream ID	Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12
Stream 00	1917.5	291.5	166.5	146.5	681.0	137.4	834.6	496.6	2355.8	316.0	448.7	591.4
Stream 01	1955.0	9513.2	1575.3	149.3	5898.2	404.3	9532.3	5243.2	21860.8	2009.0	1797.9	2550.9
Stream 02	9094.2	5048.9	1933.6	1409.7	7229.3	428.5	8234.3	2328.1	22918.6	2657.5	2224.5	3232.5
Stream 03	8367.6	6366.5	1419.2	1180.5	10609.0	276.7	8150.9	3502.2	20025.3	2925.5	2139.9	2982.1
Stream 04	8015.5	5394.4	1952.2	955.8	3351.0	377.1	9773.3	2357.9	24095.7	2092.4	1732.2	3463.6
Stream 05	7817.6	7359.4	1191.5	1131.2	7590.1	285.4	12179.5	3977.8	10642.8	1632.6	2032.6	3032.3
Stream 06	7815.9	6437.1	2519.0	1027.0	8148.8	242.9	11659.5	4105.1	17397.7	853.2	1755.8	5270.8
Stream 07	7739.7	4957.3	1878.8	918.6	8397.2	230.8	9470.2	2657.9	14563.7	2306.3	2551.5	1312.6
Stream 08	8101.0	5957.1	1282.6	932.4	6250.4	384.1	11660.7	2829.4	17133.7	1942.1	948.7	5035.6
Stream 09	7787.2	6770.0	1096.3	1368.5	6801.4	245.7	11403.6	4340.4	23512.2	2161.3	1873.0	6140.5
Minimum	1955.0	4957.3	1096.3	149.3	3351.0	230.8	8150.9	2328.1	10642.8	853.2	948.7	1312.6
Average	7410.4	6379.2	1719.0	963.0	7184.2	328.7	10082.6	3375.2	18579.8	2052.3	1897.9	3360.0
Maximum	9094.2	9513.2	2519.0	1409.7	10609.0	428.5	12179.5	5243.2	24095.7	2925.5	2551.5	6140.5

Stream ID	Q13	Q14	Q15a	Q16	Q17	Q18	Q19	Q20	Q21	Q22	RF1	RF2
Stream 00	2270.6	101.6	217.5	401.8	951.2	4185.5	948.6	375.9	2996.7	452.8	553.7	409.0
Stream 01	7212.7	1321.8	1816.3	2565.1	3491.0	49691.0	5373.9	4754.6	38336.0	528.0	490.6	391.5
Stream 02	9207.5	1442.0	1712.9	4267.1	7483.0	53081.1	6627.0	1890.6	19830.2	2645.9	458.5	414.9
Stream 03	10534.3	551.6	2752.6	2810.6	5896.7	47076.6	3897.6	4432.7	23840.0	2422.4	459.2	395.4
Stream 04	10242.7	802.4	1410.8	2473.5	3809.7	56715.0	4655.5	2472.4	20902.9	2453.9	457.1	411.3
Stream 05	8253.6	1237.3	1759.2	2693.3	6276.8	52263.1	3726.9	1762.0	42105.6	3144.2	457.6	417.6
Stream 06	8012.2	720.9	2395.3	2569.5	6432.0	47291.7	5607.4	5993.1	19824.1	2850.3	499.5	404.8
Stream 07	9554.9	607.5	941.6	2164.2	3715.2	70047.4	4660.8	1511.4	18790.1	2605.7	464.5	396.1
Stream 08	9323.3	778.3	986.9	2031.1	4744.4	61322.3	8327.3	2465.6	18062.9	2193.4	453.0	412.1
Stream 09	8288.3	631.2	2492.1	1963.7	5605.7	47915.9	3887.6	3293.7	18371.4	4074.7	453.9	394.1
Minimum	7212.7	551.6	941.6	1963.7	3491.0	47076.6	3726.9	1511.4	18062.9	528.0	453.0	391.5
Average	9042.6	932.7	1722.0	2696.8	5231.1	54686.0	5359.6	3160.3	25211.5	2355.5	467.5	405.5
Maximum	10534.3	1442.0	2752.6	4267.1	7483.0	70047.4	8327.3	5993.1	42105.6	4074.7	499.5	417.6



Benchmark Sponsors:	Juergen Mueller Performance Engineer Hewlett Packard Company 19111 Pruneridge Avenue Cupertino CA 95014	Ray Glasstone Manager, DSS Performance Oracle Corporation 100 Oracle Parkway Redwood Shores, CA 94065
---------------------	---	---

December 18, 2003

I verified the TPC Benchmark™ H performance of the following configuration:

Platform:	HP Integrity Superdome Enterprise Server
Database Manager:	Oracle 10g Database Enterprise Edition with Partitioning
Operating System:	HP-UX 11.i 64-bit

The results were:

CPU (Speed)	Memory	Disks	Appendix A: Qph H@10,000GB
Appendix B: HP 9000 Superdome Enterprise Server			
64 x Itanium 2 (1.5 GHz)	6MB L3 cache per CPU 255 GB Main	1440 x 73 GB 4 x 36 GB	49,104.5

In my opinion, this performance result was produced in compliance with the TPC's requirements for the benchmark. The following verification items were given special attention:

- The database records were defined with the proper layout and size
- The database population was generated using DBGEN
- The database was properly scaled to 10000GB and populated accordingly

- The compliance of the database auxiliary data structures was verified
- The database load time was correctly measured and reported
- The required ACID properties were verified and met
- The query input variables were generated by QGEN
- The query text was produced using minor modifications and one variant
- The execution of the queries against the SF1 database produced compliant answers
- A compliant implementation specific layer was used to drive the tests
- The throughput tests involved 9 query streams
- The ratio between the longest and the shortest query was such that no query timing was adjusted
- The execution times for queries and refresh functions were correctly measured and reported
- The repeatability of the measured results was verified
- The required amount of database log was configured
- The system pricing was verified for major components and maintenance
- The major pages from the FDR were verified for accuracy

Additional Audit Notes:

The measured system contained 4 9.1GB Ultra2-SCSI disks that were substituted by 4 36GB U320 SCSI disks. Based on the specifications of these disks and on additional performance data collected on these disks, it is my opinion that this substitution does not have a material effect on the reported performance.

Respectfully Yours,



François Raab, President



Bradley J. Askins, Auditor

Overview.....	ii
TPC Benchmark H Overview.....	ii
General Implementation Guidelines	iii
1 General Items	1
1.1 Benchmark Sponsor.....	1
1.2 Parameter Settings.....	1
1.3 Configuration Diagrams	1
2 Clause 1 Logical Database Design Related Items	3
2.1 Database Definition Statements	3
2.2 Physical Organization.....	3
2.3 Horizontal Partitioning	3
2.4 Replication	3
3 Clause 2 Queries and Refresh Functions	4
3.1 Query Language.....	4
3.2 Verifying Method for Random Number Generation	4
3.3 Generating Values for Substitution Parameters	4
3.4 Query Text and Output Data from Qualification Database.....	4
3.5 Query Substitution Parameters and Seeds Used.....	4
3.6 Query Isolation Level	4
3.7 Source Code of Refresh Functions.....	4
4 Clause 3 Database System Properties	5
4.1 ACID Properties	5
4.2 Atomicity	5
4.3 Consistency.....	5
4.4 Isolation.....	6
4.5 Durability	7
5 Clause 4 Scaling and Database Population.....	8
5.1 Ending Cardinality of Tables.....	8
5.2 Distribution of Tables and Logs Across Media.....	8
5.3 Database Partition/Replication Mapping.....	9
5.4 RAID Feature	9
5.5 DBGEN Modification.....	9
5.6 Database Load Time	9
5.7 Data Storage Ratio	9
5.8 Database Load Mechanism Details and Illustration	9
5.9 Qualification Database Configuration	9
6 Clause 5 Performance Metrics and Execution-Rules	11
6.1 System Activity Between Load and Performance Tests.....	11
6.2 Steps in the Power Test.....	11
6.3 Timing Intervals for Each Query and Refresh Functions.....	11
6.4 Number of Streams for the Throughput Test.....	11
6.5 Start and End Date/Time of Each Query Stream	11
6.6 Total Elapsed Time of the Measurement Interval.....	11
6.7 Refresh Function Start Date/Time and Finish Date/Time	11
6.8 Timing Intervals for Each Query and Each Refresh Function for Each Stream.....	12
6.9 Performance Metrics	12

6.10	The Performance Metric and Numerical Quantities from Both Runs	12
6.11	System Activity Between Performance Tests.....	12
7	Clause 6 SUT and Driver Implementation Related Items	13
7.1	Driver.....	13
7.2	Implementation-Specific Layer (ISL)	13
7.3	Profile -Directed Optimization.....	13
8	Clause 7 Pricing.....	14
8.1	Hardware and Software Used in the Priced System.....	14
8.2	Total Three Year Price	14
8.3	Availability Date.....	14
9	Clause 8 Auditor's Information and Attestation Letter.....	15
9.1	Auditor's Report.....	15
10	Report Availability	16
Appendix A	Parameter Settings.....	17
A.1	10TB-run.ora	17
A.2	system.....	17
A.3	env.....	18
Appendix B.	Build Programs and Scripts	20
B.1	10TB.DAT	20
B.2	bumpx.pl	96
Appendix C Acid Scripts		146
C.1	a_query.sql.....	146
C.2	a_query2.sql	146
C.3	atom.sh	146
C.4	atranspl.c	147
C.5	atranspl.h	152
C.6	ckpt.sh.....	154
C.7	cnt_hist.sql.....	154
C.8	consist.sh	154
C.9	consist.sql	155
C.10	count_tx.sh.....	156
C.11	d_hist.sql	156
C.12	end_acid.sh	157
C.13	iso.sh.....	157
C.14	iso1.sh.....	157
C.15	iso2.sh.....	158
C.16	iso3.sh.....	159
C.17	iso4.sh.....	160
C.18	iso5.sh.....	161
C.19	iso6.sh.....	162
C.20	randkey.c	163
C.21	randpsup.c	165
C.22	sample.sh	166
C.23	sample.sql	166
C.24	atrans.sql	166
C.27	prepare4acid.sh	168
C.28	q21.sql	168
Appendix D	Query text and Output.....	170

D.1	qryqual.....	170
Appendix E	Seed and Input Parameters	187
Appendix F Benchmark Scripts		190
F. 1	dbtables.sql.....	190
F. 2	gen_seed.sh.....	191
F. 3	gtime.c	191
F. 4	qexecpl.c	191
F. 5	qexecpl.h	198
F. 6	runTPCHall.....	200
F. 7	runTPCHpt.....	201
F. 8	runTPCHus.....	203
F. 9	runuf1.sh	204
F. 10	runuf2.sh	205
F. 11	tstart	206
F. 12	tshut.....	206
F. 13	set_queue.....	206
Appendix G Price Quotes.....		207

1 General Items

1.1 Benchmark Sponsor

A statement identifying the benchmark sponsor(s) and other participating companies must be provided.

Hewlett-Packard Company is the test sponsor of this TPC Benchmark H benchmark.

1.2 Parameter Settings

Settings must be provided for all customer-tunable parameters and options which have been changed from the defaults found in actual products, including but not limited to:

Database Tuning Options

Optimizer/Query execution options

Query processing tool/language configuration parameters

Recovery/commit options

Consistency/locking options

Operating system and configuration parameters

Configuration parameters and options for any other software component incorporated into the pricing structure;

Compiler optimization options.

Appendix A contains the HP-UX and Oracle 10g Database Enterprise Edition with Partitioning parameters used in this benchmark.

1.3 Configuration Diagrams

Diagrams of both measured and priced configurations must be provided, accompanied by a description of the differences.

Measured Configuration:


- 64 1.5GHz Itanium2 CPUs each with 6MB L3 Cache.
- 256 GB Memory
- 96 PCI Fibre Channel 2X Cards
- 1 I/O Expansion Cabinet
- 1 HP 1000 BaseSX PCI Lan Adapter
- 96 HP Surestore VA7110 (with a total of 1440 73GB Disks)
- 1 High Availability Storage System (with a total of 4 9 GB 1-36GB LP 10K LVD SE U320 HDD Disks)
- 1 DVD ROM
- 1 SCSI Card

Priced Configuration:

- 64 1.5GHz Itanium2 CPUs each with 6MB L3 Cache.
- 256 GB Memory
- 96 PCI Fibre Channel 2X Card
- 1 I/O Expansion Cabinet
- 1 HP 1000 BaseSX PCI Lan Adapter


- 96 HP Surestore VA7110 (with a total of 1440 73GB Disks)
- 1 HP Surestore Disk System 2100 (with a total of 4 36 GB 1-36GB LP 10K LVD SE U320 HDD Disks)
- 1 DVD ROM
- 1 SCSI Card

The difference between measured and priced is a High Availability Storage System for the root disk which currently is obsolete. For the priced system we used a Surestore Disk System 2100 was substituted.



Terminal

Keyboard




Measured Configuration

96 HP Surestore Virtual Array 7110

- 1440 73GB 15K RPM Disk Drives

96 Fiber Channel Adapters






Terminal

Keyboard




Priced Configuration



96 HP Surestore Virtual Array 7110

- 1440 73GB 15K RPM Disk Drives

96 Fiber Channel Adapters



2 Clause 1 Logical Database Design Related Items

2.1 Database Definition Statements

Listings must be provided for all table definition statements and all other statements used to set up the test and qualification databases.

Appendix B describes the scripts that define, create, and analyze the tables and indices for the TPC-H database.

2.2 Physical Organization

The physical organization of tables and indices, within the test and qualification databases, must be disclosed. If the column ordering of any table is different from that specified in Clause 1.4, it must be noted.

No record clustering or index clustering was used. Columns were reordered in the tables – please refer to the table create statements for the ordering.

2.3 Horizontal Partitioning

Horizontal partitioning of tables and rows in the test and qualification databases (see Clause 1.5.4) must be disclosed.

Horizontal partitioning was used for all base and index tables except NATION and REGION. The details of this partitioning can be understood by examining the syntax of the table and index definition statements in Appendix B. Similar partitioning was used in the qualification database size.

Section 5.2 describes the distribution of tables and logs across all media.

2.4 Replication

Any replication of physical objects must be disclosed and must conform to the requirements of Clause 1.5.6.

No replication was used.

3 Clause 2 Queries and Refresh Functions

3.1 Query Language

The query language used to implement the queries must be identified.

SQL was the query language used to implement all queries.

3.2 Verifying Method for Random Number Generation

The method of verification for the random number generation must be described unless the supplied DBGEN and QGEN were used.

TPC supplied versions 1.3.0 of DBGEN and QGEN were used for this TPC-H benchmark.

3.3 Generating Values for Substitution Parameters

The method used to generate values for substitution parameters must be disclosed. If QGEN is not used for this purpose, then the source code of any non-commercial tool used must be disclosed. If QGEN is used, the version number, release number, modification number, and patch level of QGEN must be disclosed.

QGEN version 1.3.0 was used to generate the substitution parameters.

3.4 Query Text and Output Data from Qualification Database

The executable query text used for query validation must be disclosed along with the corresponding output data generated during the execution of the query text against the qualification database. If minor modifications (see Clause 2.2.3) have been applied to any functional query definition or approved variants in order to obtain executable query text, these modifications must be disclosed and justified. The justification for a particular minor query modification can apply collectively to all queries for which it has been used. The output data for the power and throughput tests must be made available electronically upon request.

- Appendix C contains the actual query text and query output.

3.5 Query Substitution Parameters and Seeds Used

The query substitution parameters used for all performance tests must be disclosed in tabular format, along with the seeds used to generate these parameters.

Appendix E contains the seed and query substitution parameters.

3.6 Query Isolation Level

The isolation level used to run the queries must be disclosed. If the isolation level does not map closely to the levels defined in Clause 3.4, additional descriptive detail must be provided.

The queries and transactions were run with the isolation level set to "Level 3" (repeatable read).

3.7 Source Code of Refresh Functions

The details of how the refresh functions were implemented must be disclosed (including source code of any non-commercial program used).

The refresh function is part of the implementation-specific layer/driver code included in Appendix F.

4 Clause 3 Database System Properties

4.1 ACID Properties

The ACID (Atomicity, Consistency, Isolation, and Durability) properties of transaction processing systems must be supported by the system under test during the timed portion of this benchmark. Since TPC-H is not a transaction processing benchmark, the ACID properties must be evaluated outside the timed portion of the test.

Source code for ACID test is included in Appendix C.

4.2 Atomicity

The system under test must guarantee that transactions are atomic; the system will either perform all individual operations on the data, or will assure that no partially completed operations leave any effects on the data.

Completed Transaction

Perform the ACID Transaction for a randomly selected set of input data and verify that the appropriate rows have been changed in the ORDERS, LINEITEM, and HISTORY tables.

1. The total price from the ORDERS table and the extended price from the LINEITEM table were retrieved for a randomly selected order key.
2. The ACID Transaction was performed using the order key from step 1.
3. The ACID Transaction committed.
4. The total price from the ORDERS table and the extended price from the LINEITEM table were retrieved for the same order key. It was verified that the appropriate rows had been changed.

Aborted Transaction

Perform the ACID Transaction for a randomly selected set of input data, substituting a ROLLBACK of the transaction for the COMMIT of the transaction. Verify that the appropriate rows have not been changed in the ORDERS, LINEITEM, and HISTORY tables.

1. The total price from the ORDERS table and the extended price from the LINEITEM table were retrieved for a randomly selected order key.
2. The ACID Transaction was performed using the order key from step 1. The transaction was stopped prior to the commit.
3. The ACID Transaction was ROLLED BACK.
4. The total price from the ORDERS table and the extended price from the LINEITEM table were retrieved for the same order key. It was verified that the appropriate rows had not been changed.

4.3 Consistency

Consistency is the property of the application that requires any execution of transactions to take the database from one consistent state to another.

Consistency Test

Verify that ORDERS and LINEITEM tables are initially consistent, submit the prescribed number of ACID Transactions with randomly selected input parameters, and re-verify the consistency of the ORDERS and LINEITEM.

1. The consistency of the ORDERS and LINEITEM tables was verified based on a sample of order keys.
2. 100 ACID Transactions were submitted from each of 9 execution streams.
3. The consistency of the ORDERS and LINEITEM tables was re-verified.

4.4 Isolation

Operations of concurrent transactions must yield results, which are indistinguishable from the results, which would be obtained by forcing each transaction to be serially executed to completion in some order.

Read-Write Conflict with Commit

Demonstrate isolation for the read-write conflict of a read-write transaction and a read-only transaction when the read-write transaction is committed.

1. An ACID Transaction was started for a randomly selected O_KEY, L_KEY, and DELTA. The ACID Transaction was suspended prior to COMMIT.
2. An ACID Query was started for the same O_KEY used in step 1. The ACID Query blocked and did not see any uncommitted changes made by the ACID Transaction.
3. The ACID Transaction was resumed, and COMMITTED.
4. The ACID Query completed. It returned the data as committed by the ACID Transaction.

Read-Write Conflict with Rollback

Demonstrate isolation for the read-write conflict of a read-write transaction and a read-only transaction when the read-write transaction is rolled back.

1. An ACID Transaction was started for a randomly selected O_KEY, L_KEY, and DELTA. The ACID Transaction was suspended prior to ROLLBACK.
2. An ACID Query was started for the same O_KEY used in step 1. The ACID Query did not see the uncommitted changes made by the ACID Transaction.
3. The ACID Transaction was ROLLED BACK.
4. The ACID Query completed.

Write-Write Conflict with Commit

Demonstrate isolation for the write-write conflict of two update transactions when the first transaction is committed.

1. An ACID Transaction, T1, was started for a randomly selected O_KEY, L_KEY, and DELTA. The ACID transaction T1 was suspended prior to COMMIT.
2. Another ACID Transaction, T2, was started using the same O_KEY and L_KEY and a randomly selected DELTA.
3. T2 waited.
4. T1 was allowed to COMMIT and T2 completed.
5. It was verified that $T2.L_EXTENDEDPRICE = T1.L_EXTENDEDPRICE + (DELTA1 * (T1.L_EXTENDEDPRICE / T1.L_QUANTITY))$

Write-Write Conflict with Rollback

Demonstrate isolation for the write-write conflict of two update transactions when the first transaction is rolled back.

1. An ACID Transaction, T1, was started for a randomly selected O_KEY, L_KEY, and DELTA. The ACID transaction T1 was suspended prior to ROLLBACK.
2. Another ACID Transaction, T2, was started using the same O_KEY and L_KEY and a randomly selected DELTA.
3. T2 waited.
4. T1 was allowed to ROLLBACK and T2 completed.
5. It was verified that $T2.L_EXTENDEDPRICE = T1.L_EXTENDEDPRICE$.

Concurrent Progress of Read and Write on Different Tables

Demonstrate the ability of read and write transactions affecting different database tables to make progress concurrently.

1. An ACID Transaction, T1, was started for a randomly selected O_KEY, L_KEY, and DELTA. T1 was suspended prior to COMMIT.

2. Another ACID transaction, T2 was started using random values for PS_PARTKEY and PS_SUPPKEY, all columns of the PARTSUPP table for which PS_PARTKEY and PS_SUPPKEY are equal are returned.
3. ACID Transaction T2 completed.
4. T1 was allowed to COMMIT.
5. It was verified that the appropriate rows in the ORDER, LINEITEM, and HISTORY tables have been changed.

Read-Only Query Conflict with Update Transactions

Demonstrates that the continuous submission of arbitrary (read-only) queries against one or more tables of the database does not indefinitely delay update transactions affecting those tables from making progress.

1. A Transaction, T1, was started which executed Q21 against the qualification database, was started using a randomly selected DELTA.
2. An ACID Transaction, T2, was started for a randomly selected O_KEY, L_KEY and DELTA.
3. T2 completed and appropriate rows in the ORDERS, LINEITEM and HISTORY tables had been changed.
4. Transaction T1 completed executing Q21.

4.5 Durability

The tested system must guarantee durability: the ability to preserve the effects of committed transactions and insure database consistency after recovery from any one of the failures listed in Clause 3.5.3.

Failure of a Durable Medium

Guarantee the database and committed updates are preserved across a permanent irrecoverable failure of any single durable medium containing TPC-H database tables or recovery log tables.

The disks containing TPC-H tables and log files were on RAID 1/0 protected disk groups. During the durability test, one disk was removed from each RAID group containing the data and the log. The test continued uninterrupted, because of the RAID protection.

System Crash

Guarantee the database and committed updates are preserved across an instantaneous interruption (system crash/system hang) in processing which requires the system to reboot to recover.

The system crash and memory failure tests were combined. Power to the servers was turned off during the durability test. When power was restored, the system rebooted and the database was restarted. The durability success file and the HISTORY table were compared and the counts matched.

Memory Failure

Guarantee the database and committed updates are preserved across failure of all or part of memory (loss of contents).

See the previous section.

5 Clause 4 Scaling and Database Population

5.1 Ending Cardinality of Tables

The cardinality (e.g., the number of rows) of each table of the test database, as it existed at the completion of the database load (see clause 4.2.5) must be disclosed.

Table	Cardinality
ORDER	15,000,000,000
LINEITEM	59,999,994,267
CUSTOMER	1,500,000,000
PART	2,000,000,000
SUPPLIER	100,000,000
PARTSUPP	8,000,000,000
NATION	25
REGION	5

5.2 Distribution of Tables and Logs Across Media

On each VA7110 array, several LUNs were created in RAID 1/0 mode.

These LUNs were for:

- flat-files
- swap
- lineitem + orders table
- part, supp, partsupp, nation, region tables and all indexes
- temp
- misc (logs/sys/default, etc).

24 logical volumes were created across the 96 arrays with 4 LUNs in each volume group. Each of these volume groups was divided into 28 lvols. For lineitem table, 14 of these lvols from each of the 24 volume groups was used as an independent Oracle tablespace (336 in all). Similarly, for orders table, 14 of these lvols from each of the 24 volume groups was used as an independent oracle tablespace (336 in all).

32 logical volumes were created across 96 arrays with 3 LUNs in each volume group. The other tables and indexes were created evenly across these logical volumes.

12 logical volumes were created across 96 arrays with 8 LUNs in each volume group. The temp files were created evenly across these logical volumes.

A single volume group was created across all 96 arrays and sys/default/undo/logs were created in this volume group.

Another single volume group was created across all 96 arrays for use as swap.

OS root disk was configured on one disk from the JBOD array.

5.3 Database Partition/Replication Mapping

The mapping of database partitions/replications must be explicitly described.

Horizontal partitioning was used for all base and index tables except NATION and REGION. The details of this partitioning can be understood by examining the syntax of the table and index definition statements in Appendix B. Similar partitioning was used in the qualification database size.

Section 5.2 describes the distribution of tables and logs across all media..

5.4 RAID Feature

Implementation may use some form of RAID to ensure high availability. If used for data, auxiliary storage (e.g. indexes) or temporary space, the level of RAID must be disclosed for each device.

RAID1/0 was used for log, data, temp , index, and all storage disks.

5.5 DBGEN Modification

Any modifications to the DBGEN (see clause 4.2.1) source code must be disclosed. In the event that a program other than DBGEN was used to populate the database, it must be disclosed in its entirety.

The supplied DBGEN version 1.3.0 was not modified to generate the database population for this benchmark.

5.6 Database Load Time

The database load time for the test database (see clause 4.3) must be disclosed.

The database load time was 12:32:00

5.7 Data Storage Ratio

The data storage ratio must be disclosed. It is computed as the ratio between the total amount of priced disk space, and the chosen test database size as defined in Clause 4.1.3.

The data storage ratio is computed from the following information:

Type	Quantity	Disk Size	Total
1 HP Surestore Disk System 2100	4	36	144
96 HP Surestore VA7110	1440	73	105,120.0
TOTAL			105,264.0
Scale Factor			10,000
Storage Ratio			10.53

5.8 Database Load Mechanism Details and Illustration


The details of the database load must be described, including a block diagram illustrating the overall process.

The database was loaded using data generation stored on the flat files all on the tested and priced configuration

5.9 Qualification Database Configuration

Any differences between the configuration of the qualification database and the test database must be disclosed.

The qualification database used identical scripts to create and load the data with changes to adjust for the database scale factor.



6 Clause 5 Performance Metrics and Execution-Rules

6.1 System Activity Between Load and Performance Tests

Any system activity on the SUT that takes place between the conclusion of the load test and the beginning of the performance test must be fully disclosed.

A script was run to display the hardware configurations of the SUT.

Auditor requested queries were run against the database to verify the correctness of the database load.

The database was restarted.

All scripts and queries used are included in Appendix E.

6.2 Steps in the Power Test

The details of the steps followed to implement the power test (e.g., system boot, database restart, etc.) must be disclosed.

The following steps were used to implement the power test:

1. Database started
2. RF1 Refresh Transaction
3. Stream 00 Execution
4. RF2 Refresh Transaction

6.3 Timing Intervals for Each Query and Refresh Functions

The timing intervals for each query for both refresh functions must be reported for the power test.

The timing intervals for each query and both update functions are given in the Numerical Quantities Summary earlier in this document.

6.4 Number of Streams for the Throughput Test

The number of execution streams used for the throughput test must be disclosed.

9 streams were used for the throughput test.

6.5 Start and End Date/Time of Each Query Stream

The start time and finish time for each query stream must be reported for the throughput test.

The throughput test start time and finish time for each stream are given in the Numerical Quantities Summary earlier in this document.

6.6 Total Elapsed Time of the Measurement Interval

The total elapsed time of the measurement interval must be reported for the throughput test.

The total elapsed time of the throughput test is given in the Numerical Quantities Summary earlier in this document.

6.7 Refresh Function Start Date/Time and Finish Date/Time

Start and finish time for each update function in the update stream must be reported for the throughput test.

The start and finish time for each refresh function in the refresh stream are given in the Numerical Quantities Summary earlier in this document.

6.8 Timing Intervals for Each Query and Each Refresh Function for Each Stream

The timing intervals for each query of each stream and for each refresh function must be reported for the throughput test.

The timing intervals for each query and each update function are given in the Numerical Quantities Summary earlier in this document.

6.9 Performance Metrics

The computed performance metric, related numerical quantities and price performance metric must be reported.

The performance metrics, and the numbers, on which they are based, is given in the Numerical Quantities Summary earlier in this document.

6.10 The Performance Metric and Numerical Quantities from Both Runs

The performance metric and numerical quantities from both runs must be disclosed.

Performance results from the first two executions of the TPC-H benchmark indicated the following percent difference for the metric points:

	QppH@10000GB	QthH@10000GB	QphH@10000GB
Reported Run	64,248.7	37,530.0	49,104.5
Reproducibility Run	64,255.1	37,700.9	49,218.6
% Difference	0.0%	0.5%	0.2%

6.11 System Activity Between Performance Tests

Any activity on the SUT that takes place between the conclusion of the Reported Run and the beginning of Reproducibility Run must be disclosed.

The database was restarted between the two runs.

7 Clause 6 SUT and Driver Implementation Related Items

7.1 Driver

A detailed description of how the driver performs its functions must be supplied, including any related source code or scripts. This description should allow an independent reconstruction of the driver.

All stream executions are performed by a single script. QGEN is used to produce query text.

For each power-test run:

- The SQL for RF1 is submitted to the database
- Then the queries as generated by QGEN are submitted in the order defined by Clause 5.3.5.4
- The SQL for RF2 is submitted to the database.

7.2 Implementation-Specific Layer (ISL)

If an implementation specific layer is used, then a detailed description of how it performs its functions must be provided. All related source code, scripts and configuration files must be disclosed. The information provided should be sufficient for an independent reconstruction of the implementation specific layer.

The source code for the "qexec" utility can be found in Appendix E.

7.3 Profile-Directed Optimization

If profile-directed optimization as described in Clause 5.2. is used, such use must be disclosed..

Profile -directed optimization subject to the requirements of 5.2.9 and 5.2.10 was not used.

8 Clause 7 Pricing

8.1 Hardware and Software Used in the Priced System

A detailed list of hardware and software used in the priced system must be reported. Each item must have vendor part number, description, and release/revision level, and either general availability status or committed delivery date. If package pricing is used, contents of the package must be disclosed. Pricing source(s) and effective date(s) of price(s) must also be reported.

A detailed list of hardware and software used in the priced system is included in the pricing sheet in the executive summary. All prices are currently effective.

8.2 Total Three Year Price

The total 3-year price of the entire configuration must be reported including: hardware, software, and maintenance charges. Separate component pricing is recommended. The basis of all discounts used must be disclosed.

A detailed pricing sheet of all the hardware and software used in this configuration and the 3-year maintenance costs, demonstrating the computation of the total 3-year price of the configuration, is included in the executive summary at the beginning of this document.

8.3 Availability Date

The committed delivery date for general availability of products used in the priced calculations must be reported. When the priced system includes products with different availability dates, the reported availability date for the priced system must be the date at which all components are committed to be available.

Availability Dates:

Server Hardware	Now
Server Software	Now
Storage	Available Now
Database Manager (Oracle 10g Database Enterprise Edition with Partitioning)	March 25, 2004

9 Clause 8 Auditor's Information and Attestation Letter

9.1 Auditor's Report

The auditor's agency name, address, phone number, and Attestation letter with a brief audit summary report indicating compliance must be included in the full disclosure report. A statement should be included specifying who to contact in order to obtain further information regarding the audit process.

This implementation of the TPC Benchmark H was audited by Francois Raab for InfoSizing. Further information regarding the audit process may be obtained from:

Francois Raab
InfoSizing
1373 N. Franklin Street
Colorado Springs, CO 80903
(719) 473-7555
(719) 473-7554

The auditor's attestation letter is included at the front of this report.

10 Report Availability

Requests for this TPC Benchmark H Full Disclosure Report should be sent to:

Appendix A Parameter Settings

A.1 10TB-run.ora

```
hpux_sched_noage      = 180
statistics_level      = BASIC
aq_tm_processes       = 0
audit_trail           = FALSE
compatible            = 10.0.0.0
control_files          =
(/oracle/dbs/control1,/oracle/dbs/control2)
db_block_checksum     = false
db_block_size          = 8192
db_cache_size          = 12g
db_file_multiblock_read_count = 256
db_files               = 1200
db_name                = 10tb
db_writer_processes    = 8
dml_locks              = 40000
enqueue_resources      = 40000
global_names            = FALSE
instance_name           = tpch
large_pool_size         = 3g
log_buffer              = 33554432
log_checkpoints_to_alert = true
max_dump_file_size     = unlimited
nls_date_format        = YYYY-MM-DD
open_cursors             = 1024
optimizer_features_enable = 10.0.0.1
optimizer_mode           = CHOOSE
parallel_adaptive_multi_user = true
parallel_executio n_message_size = 16384
parallel_max_servers     = 1024
parallel_min_servers     = 1024
pga_aggregate_target    = 100g
processes               = 5000
query_rewrite_enabled   = true
recovery_parallelism     = 32
replication_dependency_tracking = false
shared_pool_size         = 1073741824
transactions             = 10
undo_management          = auto
undo_retention           = 200000
```

A.2 system

```
*
* Created on Sat Sep 13 22:27:47 2003
*
version 1
configuration nextboot "imported from system_tpch" [3f63fc4f]
*
* Module entries
*
module ipf loaded 0.1.0
module mpt best [3F1DCA3B]
module vols best [3F1DAFDA]
module vol best [3F1DAFDA]
module vxdump best [3F1DAFD9]
module vxvm best [3F1DAFDA]
module lv best [3F237870]
module lvm best [3F237870]
module vxportal best [3F237870]
```

```
module vxfs best [3F237870]
module pfil auto 0.1.0
module igelan best [3F17DABC]
module iether best [3F17DC0F]
module gelan best [3F17D80A]
module fddi4 best [3F16C8EB]
module td best [3F1D1375]
module cifs best [3F1C3A86]
module pkct best [3F237870]
module ptm best [3F237870]
module pts best [3F237870]
module ptm best [3F237870]
module ldterm best [3F237870]
module ffs best [3F237870]
module pipemod best [3F237870]
module pipedev best [3F237870]
module tirdwr best [3F237870]
module timod best [3F237870]
module sc best [3F237870]
module echo best [3F237870]
module sad best [3F237870]
module strlog best [3F237870]
module clone best [3F237870]
module hpstreams best [3F237870]
module cachefsc best [3F237870]
module autofsc best [3F237870]
module rpcmod best [3F237870]
module nfsm best [3F237870]
module nfs_client best [3F237870]
module nfs_server best [3F237870]
module nfs_core best [3F237870]
module nms best [3F237870]
module netdiag1 best [3F237870]
module token_arp best [3F237870]
module dlpi best [3F237870]
module intl100 best [3F237870]
module btlan best [3F237870]
module tels best [3F237870]
module telm best [3F237870]
module tun best [3F237870]
module uipc best [3F237870]
module inet best [3F237870]
module rng loaded 0.1.0
module cdfs best 0.1.0
module dev_config best [3F237870]
module dmem best [3F237870]
module diag2 best [3F237870]
module c8xx best [3F237870]
module pdh best [3F237870]
module lion_psm best [3F237870]
module ia64_psm best [3F237870]
module wxb_hp best [3F237870]
module sac best [3F237870]
module acpi_node best [3F237870]
module LCentIf best [3F237870]
module ipmi best [3F237870]
module pty1 best [3F237870]
module pty0 best [3F237870]
module azusa_psm best [3F237870]
module sctl best [3F237870]
module sdisk best [3F237870]
module tgt best [3F237870]
module asio0 best [3F237870]
module lba best [3F237870]
module sba best [3F237870]
module cell best [3F237870]
module root best [3F237870]
*
* Swap entries
*
```

```

*
* Dump entries
*
dump lvol
*
* Driver binding entries
*
*
* Tunables entries
*
tunable unlockable_mem 1
tunable timezone 480
tunable maxswapchunks 65536
tunable swchunk 65536
tunable nhtbl_scale 1
tunable max_async_ports 2048
tunable maxusers 32
tunable eqmemsize 512
tunable buffpages 50000
tunable maxtsiz_64bit 4294967296
tunable maxssiz_64bit 1073741824
tunable maxdsiz_64bit 0x80000000
tunable maxdsiz 0x40000000
tunable shmmmax 0x40000000000
tunable semvmtx 32768
tunable nproc 4096
tunable nfile 500000
tunable msgmni 512
tunable maxfiles_lim 4096
tunable maxfiles 4096
tunable swapmem_on 0
tunable vx_fancyra_enable 1
tunable vxfs_max_ra_kbytes 1024
tunable vxfs_ra_per_disk 1024
tunable dbc_max_pct 3
tunable dbc_min_pct 3
tunable vps_ceiling 64
tunable STRMSGSZ 65535
tunable shmseg 512
tunable shmmni 2048
tunable semume 512
tunable semmnu 4092
tunable semmns 8192
tunable semmmni 4096
tunable nswapdev 25
tunable npty 200
tunable ninode 120000
tunable msgtql 5120
tunable msgsz 128
tunable msgseg 20480
tunable msgmnb 65536
tunable msgmax 32768
tunable msgmap 5122
tunable maxvgs 99
tunable maxupr 3277
tunable maxtsiz 1073741824
tunable maxssiz 0x10000000
tunable max_thread_proc 2048
tunable hfs_revra_per_disk 256
tunable hfs_ra_per_disk 256
tunable hfs_max_revra_blocks 20
tunable hfs_max_ra_blocks 20
tunable create_fastlinks 1
tunable nstrpty 200
tunable vxfs_ifree_timelag 3600000

```

A.3 env

```

#####
##### MACHINE PARAMETERS #####
#####
#export RAC_NODES="mach1 mach2 mach3 mach4"
#####
##### PATHS #####
export KIT_DIR=/dbms/oracle10i/kit
export SCHEMA_DIR=$KIT_DIR/schema
export PERL=/opt/perl/bin/perl
export BUMPX_DIR=$KIT_DIR/bumpx
export BUMPX_OUT=$KIT_DIR/bumpx
export UTILS=$KIT_DIR/utils
export TEST_DB=/tmp
export QUAL_DB=$TEST_DB
export DBGEN=$KIT_DIR/dbgen
export ACID_DIR=$KIT_DIR/acid
export QEXEC=$KIT_DIR/utils
export QUERIES=$KIT_DIR/queries
export ANSWERS=$KIT_DIR/answers
export ANS2VAL=/dbms/oracle10i/kit/acid/answers2validate
export ACID_OUT=$KIT_DIR/out
export DSS_CONFIG=$DBGEN
export DSS_QUERY=$KIT_DIR/queries
export DSS_PATH=$ADE_VIEW_ROOT
export MAINT=$KIT_DIR/maintenance
export CC=/opt/ansic/bin/cc
export FRAME=$KIT_DIR/frame
export REGR_TEST=$KIT_DIR/internal/regression_test
export SCALE_FACTOR=10000
export UPDATE_1_DOP=32
export UPDATE_2_DOP=128
#####
##### FRAME STUFF #####
export FRAME_PATH=$KIT_DIR/frame

#export ORACORE3INCL=/vobs/oracore3/include
#export ORACORE3PUBL=/vobs/oracore3/public
export ORACORE3INCL=$ORACLE_HOME/rdbms/demo
export ORACORE3PUBL=$ORACLE_HOME/rdbms/public
#export RDBMSPUBL=/vobs/rdbms/public
export RDBMSPUBL=$ORACLE_HOME/rdbms/public
#export NETWORKPUBL=/vobs/network_src/public
export NETWORKPUBL=$ORACLE_HOME/network/public
export RDBMSDEMO=$ORACLE_HOME/rdbms/demo
export PLSQLDEMO=$ORACLE_HOME/plsql/demo
export PLSQLPUBL=$ORACLE_HOME/plsql/public
export O=$ORACLE_HOME
export
PATH=./:$BUMPX_DIR:$UTILS:$DBGEN:$MAINT:$ACID_DIR:$FRAME/bin:$FRAME/bin:$REGR_TEST:$PATH
#
#####
##### ENVIRONMENT VARIABLES #####
#####
export WORKLOAD=TPCH
export HOST=
#export OPTLEVEL=X02
export GETOPT=DSTDLIB_HAS_GETOPT
export PLATFORM=
#export INITORA=$KIT_DIR/schema/test_db/testdb.ora
#export INITORA=$KIT_DIR/schema/test_db/sf100.ora

#####
##### ALIASES #####
#####

#####
##### RULES - do not change these #####
case "$SCALE_FACTOR" in
    1) export NUM_STREAMS=2;;
    10) export NUM_STREAMS=3;;
    100) export NUM_STREAMS=4;;
esac

```

```
300) export NUM_STREAMS=6;;
1000) export NUM_STREAMS=7;;
3000) export NUM_STREAMS=8;;
10000) export NUM_STREAMS=9;;
```

```
esac
DATABASE_USER=tpch/tpch
```

Appendix C Appendix B. Build Programs and Scripts

B.1 10TB.DAT

```
#####
## preprocessing-like directives
%b-preproc

*sql
\echo "{}" > script*getenv(BUMPX_CTR).sql
\sqlplus /NOLOG <<!
\set echo on;
\set timing on;
\set termout on;
\connect / as sysdba;
\select to_char(sysdate, 'MM-DD-YYYY HH24:MI:SS') now from dual;
@\script*getenv(BUMPX_CTR).sql;
\select to_char(sysdate, 'MM-DD-YYYY HH24:MI:SS') now from dual;
\exit;
!\
/bin/rm script*getenv(BUMPX_CTR).sql;

*load1
\sqlldr {}

*mknod
\mknod {}

*dbggen
\dbggen {}

*sh
\{

%e-preproc
%b-dbcrc
*bgon=1
#####
# Database Creation Phase
*sql
{
shutdown abort;
}
*wait
# creating database and undo tablespace
*sql
{
startup pfile=/oracle/dbs/10TB_run.ora nomount;
create database
controlfile reuse
logfile '/dbms/links/log_1' size 32000m reuse,
'/dbms/links/log_2' size 32000m reuse
datafile '/dbms/links/sys_1' size 2000m reuse
sysaux datafile '/dbms/links/aux' size 2000m reuse
undo tablespace ts_undo
    datafile '/dbms/links/undo_1' size 22000m reuse
default temporary tablespace ts_temp
    tempfile '/dbms/links/temp_1' size 32000m reuse
    extent management local uniform size 5m
maxdatafiles 1000

maxinstances 1
;
}
*wait
# building data dictionary
*sql
{
set termout off
set echo off
spool /tmp/cat
@?/rdbms/admin/catalog.sql;
@?/rdbms/admin/catparr.sql;
@?/rdbms/admin/catproc.sql;
connect system/manager
@?/rdbms/admin/utlxplan.sql;
@?/sqlplus/admin/pupbld.sql;
spool off
}
*wait
*bgoff
%e-dbcrc
%b-sctso
*bgon=64
#####
#####
# Schema Creation Phase - datafiles only (no tables or users)
# creating data tablespaces, datafiles
*sql
{
--drop tablespace ts_default including contents;
create tablespace ts_default
datafile '/dbms/links/default_1' size 4000m reuse
extent management local
autoallocate
;
}
*sql
{
--drop tablespace ts_11 including contents;
create tablespace ts_11
datafile '/dbms/links/line_1' size 30800m reuse
extent management dictionary default storage (initial 1050m next 20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_12 including contents;
create tablespace ts_12
datafile '/dbms/links/line_2' size 30800m reuse
extent management dictionary default storage (initial 1050m next 20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_13 including contents;
create tablespace ts_13
datafile '/dbms/links/line_3' size 30800m reuse
extent management dictionary default storage (initial 1050m next 20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_14 including contents;
create tablespace ts_14
datafile '/dbms/links/line_4' size 30800m reuse
extent management dictionary default storage (initial 1050m next 20m maxextents unlimited pctincrease 0)
;
```

```

;
}
/*sql
{
--drop tablespace ts_15 including contents;
create tablespace ts_15
datafile '/dbms/links/line_5' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
/*sql
{
--drop tablespace ts_16 including contents;
create tablespace ts_16
datafile '/dbms/links/line_6' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
/*sql
{
--drop tablespace ts_17 including contents;
create tablespace ts_17
datafile '/dbms/links/line_7' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
/*sql
{
--drop tablespace ts_18 including contents;
create tablespace ts_18
datafile '/dbms/links/line_8' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
/*sql
{
--drop tablespace ts_19 including contents;
create tablespace ts_19
datafile '/dbms/links/line_9' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
/*sql
{
--drop tablespace ts_110 including contents;
create tablespace ts_110
datafile '/dbms/links/line_10' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
/*sql
{
--drop tablespace ts_111 including contents;
create tablespace ts_111
datafile '/dbms/links/line_11' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
/*sql
{
--drop tablespace ts_112 including contents;
create tablespace ts_112
datafile '/dbms/links/line_12' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
/*sql
{
--drop tablespace ts_113 including contents;
create tablespace ts_113
datafile '/dbms/links/line_13' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
/*sql
{
--drop tablespace ts_114 including contents;
create tablespace ts_114
datafile '/dbms/links/line_14' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
/*sql
{
--drop tablespace ts_115 including contents;
create tablespace ts_115
datafile '/dbms/links/line_15' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
/*sql
{
--drop tablespace ts_116 including contents;
create tablespace ts_116
datafile '/dbms/links/line_16' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
/*sql
{
--drop tablespace ts_117 including contents;
create tablespace ts_117
datafile '/dbms/links/line_17' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
/*sql
{
--drop tablespace ts_118 including contents;
create tablespace ts_118
datafile '/dbms/links/line_18' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
/*sql
{
--drop tablespace ts_119 including contents;
create tablespace ts_119
datafile '/dbms/links/line_19' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
/*sql
{
--drop tablespace ts_120 including contents;

```

```

create tablespace ts_120
datafile '/dbms/links/line_20' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_121 including contents;
create tablespace ts_121
datafile '/dbms/links/line_21' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_122 including contents;
create tablespace ts_122
datafile '/dbms/links/line_22' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_123 including contents;
create tablespace ts_123
datafile '/dbms/links/line_23' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_124 including contents;
create tablespace ts_124
datafile '/dbms/links/line_24' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_125 including contents;
create tablespace ts_125
datafile '/dbms/links/line_25' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_126 including contents;
create tablespace ts_126
datafile '/dbms/links/line_26' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_127 including contents;
create tablespace ts_127
datafile '/dbms/links/line_27' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_128 including contents;
create tablespace ts_128
datafile '/dbms/links/line_28' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_129 including contents;
create tablespace ts_129
datafile '/dbms/links/line_29' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_130 including contents;
create tablespace ts_130
datafile '/dbms/links/line_30' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_131 including contents;
create tablespace ts_131
datafile '/dbms/links/line_31' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_132 including contents;
create tablespace ts_132
datafile '/dbms/links/line_32' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_133 including contents;
create tablespace ts_133
datafile '/dbms/links/line_33' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_134 including contents;
create tablespace ts_134
datafile '/dbms/links/line_34' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_135 including contents;
create tablespace ts_135
datafile '/dbms/links/line_35' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}

```

```

}
*sql
{
--drop tablespace ts_l36 including contents;
create tablespace ts_l36
datafile '/dbms/links/line_36' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l37 including contents;
create tablespace ts_l37
datafile '/dbms/links/line_37' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l38 including contents;
create tablespace ts_l38
datafile '/dbms/links/line_38' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l39 including contents;
create tablespace ts_l39
datafile '/dbms/links/line_39' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l40 including contents;
create tablespace ts_l40
datafile '/dbms/links/line_40' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l41 including contents;
create tablespace ts_l41
datafile '/dbms/links/line_41' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l42 including contents;
create tablespace ts_l42
datafile '/dbms/links/line_42' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l43 including contents;
create tablespace ts_l43
datafile '/dbms/links/line_43' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l44 including contents;
create tablespace ts_l44
datafile '/dbms/links/line_44' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l45 including contents;
create tablespace ts_l45
datafile '/dbms/links/line_45' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l46 including contents;
create tablespace ts_l46
datafile '/dbms/links/line_46' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l47 including contents;
create tablespace ts_l47
datafile '/dbms/links/line_47' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l48 including contents;
create tablespace ts_l48
datafile '/dbms/links/line_48' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l49 including contents;
create tablespace ts_l49
datafile '/dbms/links/line_49' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l50 including contents;
create tablespace ts_l50
datafile '/dbms/links/line_50' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l51 including contents;

```

```

create tablespace ts_151
datafile '/dbms/links/line_51' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_152 including contents;
create tablespace ts_152
datafile '/dbms/links/line_52' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_153 including contents;
create tablespace ts_153
datafile '/dbms/links/line_53' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_154 including contents;
create tablespace ts_154
datafile '/dbms/links/line_54' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_155 including contents;
create tablespace ts_155
datafile '/dbms/links/line_55' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_156 including contents;
create tablespace ts_156
datafile '/dbms/links/line_56' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_157 including contents;
create tablespace ts_157
datafile '/dbms/links/line_57' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_158 including contents;
create tablespace ts_158
datafile '/dbms/links/line_58' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_159 including contents;
create tablespace ts_159
datafile '/dbms/links/line_59' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_160 including contents;
create tablespace ts_160
datafile '/dbms/links/line_60' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_161 including contents;
create tablespace ts_161
datafile '/dbms/links/line_61' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_162 including contents;
create tablespace ts_162
datafile '/dbms/links/line_62' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_163 including contents;
create tablespace ts_163
datafile '/dbms/links/line_63' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_164 including contents;
create tablespace ts_164
datafile '/dbms/links/line_64' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_165 including contents;
create tablespace ts_165
datafile '/dbms/links/line_65' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_166 including contents;
create tablespace ts_166
datafile '/dbms/links/line_66' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}

```

```

}
*sql
{
--drop tablespace ts_167 including contents;
create tablespace ts_167
datafile '/dbms/links/line_67' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_168 including contents;
create tablespace ts_168
datafile '/dbms/links/line_68' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_169 including contents;
create tablespace ts_169
datafile '/dbms/links/line_69' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_170 including contents;
create tablespace ts_170
datafile '/dbms/links/line_70' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_171 including contents;
create tablespace ts_171
datafile '/dbms/links/line_71' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_172 including contents;
create tablespace ts_172
datafile '/dbms/links/line_72' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_173 including contents;
create tablespace ts_173
datafile '/dbms/links/line_73' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_174 including contents;
create tablespace ts_174
datafile '/dbms/links/line_74' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_175 including contents;
create tablespace ts_175
datafile '/dbms/links/line_75' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_176 including contents;
create tablespace ts_176
datafile '/dbms/links/line_76' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_177 including contents;
create tablespace ts_177
datafile '/dbms/links/line_77' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_178 including contents;
create tablespace ts_178
datafile '/dbms/links/line_78' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_179 including contents;
create tablespace ts_179
datafile '/dbms/links/line_79' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_180 including contents;
create tablespace ts_180
datafile '/dbms/links/line_80' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_181 including contents;
create tablespace ts_181
datafile '/dbms/links/line_81' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_182 including contents;

```

```

create tablespace ts_182
datafile '/dbms/links/line_82' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_183 including contents;
create tablespace ts_183
datafile '/dbms/links/line_83' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_184 including contents;
create tablespace ts_184
datafile '/dbms/links/line_84' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_185 including contents;
create tablespace ts_185
datafile '/dbms/links/line_85' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_186 including contents;
create tablespace ts_186
datafile '/dbms/links/line_86' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_187 including contents;
create tablespace ts_187
datafile '/dbms/links/line_87' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_188 including contents;
create tablespace ts_188
datafile '/dbms/links/line_88' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_189 including contents;
create tablespace ts_189
datafile '/dbms/links/line_89' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_190 including contents;
create tablespace ts_190
datafile '/dbms/links/line_90' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_191 including contents;
create tablespace ts_191
datafile '/dbms/links/line_91' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_192 including contents;
create tablespace ts_192
datafile '/dbms/links/line_92' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_193 including contents;
create tablespace ts_193
datafile '/dbms/links/line_93' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_194 including contents;
create tablespace ts_194
datafile '/dbms/links/line_94' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_195 including contents;
create tablespace ts_195
datafile '/dbms/links/line_95' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_196 including contents;
create tablespace ts_196
datafile '/dbms/links/line_96' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_197 including contents;
create tablespace ts_197
datafile '/dbms/links/line_97' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}

```

```

}
*sql
{
--drop tablespace ts_198 including contents;
create tablespace ts_198
datafile '/dbms/links/line_98' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_199 including contents;
create tablespace ts_199
datafile '/dbms/links/line_99' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1100 including contents;
create tablespace ts_1100
datafile '/dbms/links/line_100' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1101 including contents;
create tablespace ts_1101
datafile '/dbms/links/line_101' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1102 including contents;
create tablespace ts_1102
datafile '/dbms/links/line_102' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1103 including contents;
create tablespace ts_1103
datafile '/dbms/links/line_103' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1104 including contents;
create tablespace ts_1104
datafile '/dbms/links/line_104' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1105 including contents;
create tablespace ts_1105
datafile '/dbms/links/line_105' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1106 including contents;
create tablespace ts_1106
datafile '/dbms/links/line_106' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1107 including contents;
create tablespace ts_1107
datafile '/dbms/links/line_107' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1108 including contents;
create tablespace ts_1108
datafile '/dbms/links/line_108' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1109 including contents;
create tablespace ts_1109
datafile '/dbms/links/line_109' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1110 including contents;
create tablespace ts_1110
datafile '/dbms/links/line_110' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1111 including contents;
create tablespace ts_1111
datafile '/dbms/links/line_111' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1112 including contents;
create tablespace ts_1112
datafile '/dbms/links/line_112' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1113 including contents;

```

```

create tablespace ts_1113
datafile '/dbms/links/line_113' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1114 including contents;
create tablespace ts_1114
datafile '/dbms/links/line_114' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1115 including contents;
create tablespace ts_1115
datafile '/dbms/links/line_115' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1116 including contents;
create tablespace ts_1116
datafile '/dbms/links/line_116' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1117 including contents;
create tablespace ts_1117
datafile '/dbms/links/line_117' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1118 including contents;
create tablespace ts_1118
datafile '/dbms/links/line_118' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1119 including contents;
create tablespace ts_1119
datafile '/dbms/links/line_119' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1120 including contents;
create tablespace ts_1120
datafile '/dbms/links/line_120' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1121 including contents;
create tablespace ts_1121
datafile '/dbms/links/line_121' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1122 including contents;
create tablespace ts_1122
datafile '/dbms/links/line_122' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1123 including contents;
create tablespace ts_1123
datafile '/dbms/links/line_123' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1124 including contents;
create tablespace ts_1124
datafile '/dbms/links/line_124' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1125 including contents;
create tablespace ts_1125
datafile '/dbms/links/line_125' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1126 including contents;
create tablespace ts_1126
datafile '/dbms/links/line_126' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1127 including contents;
create tablespace ts_1127
datafile '/dbms/links/line_127' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1128 including contents;
create tablespace ts_1128
datafile '/dbms/links/line_128' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}

```

```

}
*sql
{
--drop tablespace ts_1129 including contents;
create tablespace ts_1129
datafile '/dbms/links/line_129' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1130 including contents;
create tablespace ts_1130
datafile '/dbms/links/line_130' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1131 including contents;
create tablespace ts_1131
datafile '/dbms/links/line_131' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1132 including contents;
create tablespace ts_1132
datafile '/dbms/links/line_132' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1133 including contents;
create tablespace ts_1133
datafile '/dbms/links/line_133' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1134 including contents;
create tablespace ts_1134
datafile '/dbms/links/line_134' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1135 including contents;
create tablespace ts_1135
datafile '/dbms/links/line_135' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1136 including contents;
create tablespace ts_1136
datafile '/dbms/links/line_136' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1137 including contents;
create tablespace ts_1137
datafile '/dbms/links/line_137' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1138 including contents;
create tablespace ts_1138
datafile '/dbms/links/line_138' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1139 including contents;
create tablespace ts_1139
datafile '/dbms/links/line_139' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1140 including contents;
create tablespace ts_1140
datafile '/dbms/links/line_140' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1141 including contents;
create tablespace ts_1141
datafile '/dbms/links/line_141' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1142 including contents;
create tablespace ts_1142
datafile '/dbms/links/line_142' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1143 including contents;
create tablespace ts_1143
datafile '/dbms/links/line_143' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1144 including contents;

```

```

create tablespace ts_1144
datafile '/dbms/links/line_144' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1145 including contents;
create tablespace ts_1145
datafile '/dbms/links/line_145' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1146 including contents;
create tablespace ts_1146
datafile '/dbms/links/line_146' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1147 including contents;
create tablespace ts_1147
datafile '/dbms/links/line_147' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1148 including contents;
create tablespace ts_1148
datafile '/dbms/links/line_148' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1149 including contents;
create tablespace ts_1149
datafile '/dbms/links/line_149' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1150 including contents;
create tablespace ts_1150
datafile '/dbms/links/line_150' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1151 including contents;
create tablespace ts_1151
datafile '/dbms/links/line_151' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1152 including contents;
create tablespace ts_1152
datafile '/dbms/links/line_152' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1153 including contents;
create tablespace ts_1153
datafile '/dbms/links/line_153' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1154 including contents;
create tablespace ts_1154
datafile '/dbms/links/line_154' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1155 including contents;
create tablespace ts_1155
datafile '/dbms/links/line_155' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1156 including contents;
create tablespace ts_1156
datafile '/dbms/links/line_156' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1157 including contents;
create tablespace ts_1157
datafile '/dbms/links/line_157' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1158 including contents;
create tablespace ts_1158
datafile '/dbms/links/line_158' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1159 including contents;
create tablespace ts_1159
datafile '/dbms/links/line_159' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}

```

```

}
*sql
{
--drop tablespace ts_1160 including contents;
create tablespace ts_1160
datafile '/dbms/links/line_160' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1161 including contents;
create tablespace ts_1161
datafile '/dbms/links/line_161' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1162 including contents;
create tablespace ts_1162
datafile '/dbms/links/line_162' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1163 including contents;
create tablespace ts_1163
datafile '/dbms/links/line_163' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1164 including contents;
create tablespace ts_1164
datafile '/dbms/links/line_164' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1165 including contents;
create tablespace ts_1165
datafile '/dbms/links/line_165' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1166 including contents;
create tablespace ts_1166
datafile '/dbms/links/line_166' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1167 including contents;
create tablespace ts_1167
datafile '/dbms/links/line_167' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1168 including contents;
create tablespace ts_1168
datafile '/dbms/links/line_168' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1169 including contents;
create tablespace ts_1169
datafile '/dbms/links/line_169' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1170 including contents;
create tablespace ts_1170
datafile '/dbms/links/line_170' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1171 including contents;
create tablespace ts_1171
datafile '/dbms/links/line_171' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1172 including contents;
create tablespace ts_1172
datafile '/dbms/links/line_172' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1173 including contents;
create tablespace ts_1173
datafile '/dbms/links/line_173' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1174 including contents;
create tablespace ts_1174
datafile '/dbms/links/line_174' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1175 including contents;

```

```

create tablespace ts_1175
datafile '/dbms/links/line_175' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1176 including contents;
create tablespace ts_1176
datafile '/dbms/links/line_176' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1177 including contents;
create tablespace ts_1177
datafile '/dbms/links/line_177' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1178 including contents;
create tablespace ts_1178
datafile '/dbms/links/line_178' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1179 including contents;
create tablespace ts_1179
datafile '/dbms/links/line_179' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1180 including contents;
create tablespace ts_1180
datafile '/dbms/links/line_180' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1181 including contents;
create tablespace ts_1181
datafile '/dbms/links/line_181' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1182 including contents;
create tablespace ts_1182
datafile '/dbms/links/line_182' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1183 including contents;
create tablespace ts_1183
datafile '/dbms/links/line_183' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1184 including contents;
create tablespace ts_1184
datafile '/dbms/links/line_184' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1185 including contents;
create tablespace ts_1185
datafile '/dbms/links/line_185' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1186 including contents;
create tablespace ts_1186
datafile '/dbms/links/line_186' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1187 including contents;
create tablespace ts_1187
datafile '/dbms/links/line_187' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1188 including contents;
create tablespace ts_1188
datafile '/dbms/links/line_188' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1189 including contents;
create tablespace ts_1189
datafile '/dbms/links/line_189' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1190 including contents;
create tablespace ts_1190
datafile '/dbms/links/line_190' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}

```

```

}
*sql
{
--drop tablespace ts_1191 including contents;
create tablespace ts_1191
datafile '/dbms/links/line_191' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1192 including contents;
create tablespace ts_1192
datafile '/dbms/links/line_192' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1193 including contents;
create tablespace ts_1193
datafile '/dbms/links/line_193' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1194 including contents;
create tablespace ts_1194
datafile '/dbms/links/line_194' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1195 including contents;
create tablespace ts_1195
datafile '/dbms/links/line_195' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1196 including contents;
create tablespace ts_1196
datafile '/dbms/links/line_196' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1197 including contents;
create tablespace ts_1197
datafile '/dbms/links/line_197' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1198 including contents;
create tablespace ts_1198
datafile '/dbms/links/line_198' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1199 including contents;
create tablespace ts_1199
datafile '/dbms/links/line_199' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1200 including contents;
create tablespace ts_1200
datafile '/dbms/links/line_200' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1201 including contents;
create tablespace ts_1201
datafile '/dbms/links/line_201' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1202 including contents;
create tablespace ts_1202
datafile '/dbms/links/line_202' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1203 including contents;
create tablespace ts_1203
datafile '/dbms/links/line_203' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1204 including contents;
create tablespace ts_1204
datafile '/dbms/links/line_204' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1205 including contents;
create tablespace ts_1205
datafile '/dbms/links/line_205' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_1206 including contents;

```

```

create tablespace ts_l206
datafile '/dbms/links/line_206' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l207 including contents;
create tablespace ts_l207
datafile '/dbms/links/line_207' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l208 including contents;
create tablespace ts_l208
datafile '/dbms/links/line_208' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l209 including contents;
create tablespace ts_l209
datafile '/dbms/links/line_209' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l210 including contents;
create tablespace ts_l210
datafile '/dbms/links/line_210' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l211 including contents;
create tablespace ts_l211
datafile '/dbms/links/line_211' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l212 including contents;
create tablespace ts_l212
datafile '/dbms/links/line_212' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l213 including contents;
create tablespace ts_l213
datafile '/dbms/links/line_213' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l214 including contents;
create tablespace ts_l214
datafile '/dbms/links/line_214' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l215 including contents;
create tablespace ts_l215
datafile '/dbms/links/line_215' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l216 including contents;
create tablespace ts_l216
datafile '/dbms/links/line_216' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l217 including contents;
create tablespace ts_l217
datafile '/dbms/links/line_217' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l218 including contents;
create tablespace ts_l218
datafile '/dbms/links/line_218' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l219 including contents;
create tablespace ts_l219
datafile '/dbms/links/line_219' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l220 including contents;
create tablespace ts_l220
datafile '/dbms/links/line_220' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l221 including contents;
create tablespace ts_l221
datafile '/dbms/links/line_221' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}

```

```

}
*sql
{
--drop tablespace ts_l222 including contents;
create tablespace ts_l222
datafile '/dbms/links/line_222' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l223 including contents;
create tablespace ts_l223
datafile '/dbms/links/line_223' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l224 including contents;
create tablespace ts_l224
datafile '/dbms/links/line_224' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l225 including contents;
create tablespace ts_l225
datafile '/dbms/links/line_225' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l226 including contents;
create tablespace ts_l226
datafile '/dbms/links/line_226' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l227 including contents;
create tablespace ts_l227
datafile '/dbms/links/line_227' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l228 including contents;
create tablespace ts_l228
datafile '/dbms/links/line_228' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l229 including contents;
create tablespace ts_l229
datafile '/dbms/links/line_229' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l230 including contents;
create tablespace ts_l230
datafile '/dbms/links/line_230' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l231 including contents;
create tablespace ts_l231
datafile '/dbms/links/line_231' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l232 including contents;
create tablespace ts_l232
datafile '/dbms/links/line_232' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l233 including contents;
create tablespace ts_l233
datafile '/dbms/links/line_233' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l234 including contents;
create tablespace ts_l234
datafile '/dbms/links/line_234' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l235 including contents;
create tablespace ts_l235
datafile '/dbms/links/line_235' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l236 including contents;
create tablespace ts_l236
datafile '/dbms/links/line_236' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l237 including contents;

```

```

create tablespace ts_l237
datafile '/dbms/links/line_237' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l238 including contents;
create tablespace ts_l238
datafile '/dbms/links/line_238' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m max extents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l239 including contents;
create tablespace ts_l239
datafile '/dbms/links/line_239' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l240 including contents;
create tablespace ts_l240
datafile '/dbms/links/line_240' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l241 including contents;
create tablespace ts_l241
datafile '/dbms/links/line_241' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l242 including contents;
create tablespace ts_l242
datafile '/dbms/links/line_242' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l243 in cluding contents;
create tablespace ts_l243
datafile '/dbms/links/line_243' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l244 including contents;
create tablespace ts_l244
datafile '/dbms/links/line_244' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l245 including contents;
create tablespace ts_l245
datafile '/dbms/links/line_245' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l246 including contents;
create tablespace ts_l246
datafile '/dbms/links/line_246' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l247 including contents;
create tablespace ts_l247
datafile '/dbms/links/line_247' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l248 including contents;
create tablespace ts_l248
datafile '/dbms/links/line_248' size 30800m re use
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l249 including contents;
create tablespace ts_l249
datafile '/dbms/links/line_249' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l250 including contents;
create tablespace ts_l250
datafile '/dbms/links/line_250' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l251 including contents;
create tablespace ts_l251
datafile '/dbms/links/line_251' size 30800m reuse
extent management dictionary default storage (init ial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l252 including contents;
create tablespace ts_l252
datafile '/dbms/links/line_252' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}

```

```

}
*sql
{
--drop tablespace ts_l253 including contents;
create tablespace ts_l253
datafile '/dbms/links/line_253' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l254 including contents;
create tablespace ts_l254
datafile '/dbms/links/line_254' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l255 including contents;
create tablespace ts_l255
datafile '/dbms/links/line_255' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l256 including contents;
create tablespace ts_l256
datafile '/dbms/links/line_256' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l257 including contents;
create tablespace ts_l257
datafile '/dbms/links/line_257' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l258 including contents;
create tablespace ts_l258
datafile '/dbms/links/line_258' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l259 including contents;
create tablespace ts_l259
datafile '/dbms/links/line_259' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l260 including contents;
create tablespace ts_l260
datafile '/dbms/links/line_260' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l261 including contents;
create tablespace ts_l261
datafile '/dbms/links/line_261' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l262 including contents;
create tablespace ts_l262
datafile '/dbms/links/line_262' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l263 including contents;
create tablespace ts_l263
datafile '/dbms/links/line_263' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l264 including contents;
create tablespace ts_l264
datafile '/dbms/links/line_264' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l265 including contents;
create tablespace ts_l265
datafile '/dbms/links/line_265' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l266 including contents;
create tablespace ts_l266
datafile '/dbms/links/line_266' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l267 including contents;
create tablespace ts_l267
datafile '/dbms/links/line_267' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l268 including contents;

```

```

create tablespace ts_l268
datafile '/dbms/links/line_268' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l269 including contents;
create tablespace ts_l269
datafile '/dbms/links/line_269' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l270 including contents;
create tablespace ts_l270
datafile '/dbms/links/line_270' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l271 including contents;
create tablespace ts_l271
datafile '/dbms/links/line_271' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l272 including contents;
create tablespace ts_l272
datafile '/dbms/links/line_272' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l273 including contents;
create tablespace ts_l273
datafile '/dbms/links/line_273' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l274 including contents;
create tablespace ts_l274
datafile '/dbms/links/line_274' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l275 including contents;
create tablespace ts_l275
datafile '/dbms/links/line_275' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l276 including contents;
create tablespace ts_l276
datafile '/dbms/links/line_276' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l277 including contents;
create tablespace ts_l277
datafile '/dbms/links/line_277' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l278 including contents;
create tablespace ts_l278
datafile '/dbms/links/line_278' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l279 including contents;
create tablespace ts_l279
datafile '/dbms/links/line_279' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l280 including contents;
create tablespace ts_l280
datafile '/dbms/links/line_280' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l281 including contents;
create tablespace ts_l281
datafile '/dbms/links/line_281' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l282 including contents;
create tablespace ts_l282
datafile '/dbms/links/line_282' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l283 including contents;
create tablespace ts_l283
datafile '/dbms/links/line_283' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}

```

```

}
*sql
{
--drop tablespace ts_l284 including contents;
create tablespace ts_l284
datafile '/dbms/links/line_284' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l285 including contents;
create tablespace ts_l285
datafile '/dbms/links/line_285' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l286 including contents;
create tablespace ts_l286
datafile '/dbms/links/line_286' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l287 including contents;
create tablespace ts_l287
datafile '/dbms/links/line_287' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l288 including contents;
create tablespace ts_l288
datafile '/dbms/links/line_288' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l289 including contents;
create tablespace ts_l289
datafile '/dbms/links/line_289' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l290 including contents;
create tablespace ts_l290
datafile '/dbms/links/line_290' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l291 including contents;
create tablespace ts_l291
datafile '/dbms/links/line_291' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l292 including contents;
create tablespace ts_l292
datafile '/dbms/links/line_292' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l293 including contents;
create tablespace ts_l293
datafile '/dbms/links/line_293' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l294 including contents;
create tablespace ts_l294
datafile '/dbms/links/line_294' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l295 including contents;
create tablespace ts_l295
datafile '/dbms/links/line_295' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l296 including contents;
create tablespace ts_l296
datafile '/dbms/links/line_296' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l297 including contents;
create tablespace ts_l297
datafile '/dbms/links/line_297' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l298 including contents;
create tablespace ts_l298
datafile '/dbms/links/line_298' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l299 including contents;

```

```

create tablespace ts_l299
datafile '/dbms/links/line_299' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l300 including contents;
create tablespace ts_l300
datafile '/dbms/links/line_300' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l301 including contents;
create tablespace ts_l301
datafile '/dbms/links/line_301' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l302 including contents;
create tablespace ts_l302
datafile '/dbms/links/line_302' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l303 including contents;
create tablespace ts_l303
datafile '/dbms/links/line_303' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l304 including contents;
create tablespace ts_l304
datafile '/dbms/links/line_304' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l305 including contents;
create tablespace ts_l305
datafile '/dbms/links/line_305' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l306 including contents;
create tablespace ts_l306
datafile '/dbms/links/line_306' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l307 including contents;
create tablespace ts_l307
datafile '/dbms/links/line_307' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l308 including contents;
create tablespace ts_l308
datafile '/dbms/links/line_308' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l309 including contents;
create tablespace ts_l309
datafile '/dbms/links/line_309' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l310 including contents;
create tablespace ts_l310
datafile '/dbms/links/line_310' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l311 including contents;
create tablespace ts_l311
datafile '/dbms/links/line_311' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l312 including contents;
create tablespace ts_l312
datafile '/dbms/links/line_312' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l313 including contents;
create tablespace ts_l313
datafile '/dbms/links/line_313' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l314 including contents;
create tablespace ts_l314
datafile '/dbms/links/line_314' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}

```

```

}
*sql
{
--drop tablespace ts_l315 including contents;
create tablespace ts_l315
datafile '/dbms/links/line_315' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l316 including contents;
create tablespace ts_l316
datafile '/dbms/links/line_316' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l317 including contents;
create tablespace ts_l317
datafile '/dbms/links/line_317' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l318 including contents;
create tablespace ts_l318
datafile '/dbms/links/line_318' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l319 including contents;
create tablespace ts_l319
datafile '/dbms/links/line_319' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l320 including contents;
create tablespace ts_l320
datafile '/dbms/links/line_320' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l321 including contents;
create tablespace ts_l321
datafile '/dbms/links/line_321' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l322 including contents;
create tablespace ts_l322
datafile '/dbms/links/line_322' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l323 including contents;
create tablespace ts_l323
datafile '/dbms/links/line_323' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l324 including contents;
create tablespace ts_l324
datafile '/dbms/links/line_324' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l325 including contents;
create tablespace ts_l325
datafile '/dbms/links/line_325' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l326 including contents;
create tablespace ts_l326
datafile '/dbms/links/line_326' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l327 including contents;
create tablespace ts_l327
datafile '/dbms/links/line_327' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_B28 including contents;
create tablespace ts_l328
datafile '/dbms/links/line_328' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l329 including contents;
create tablespace ts_l329
datafile '/dbms/links/line_329' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l330 including contents;

```

```

create tablespace ts_l330
datafile '/dbms/links/line_330' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l331 including contents;
create tablespace ts_l331
datafile '/dbms/links/line_331' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l332 including contents;
create tablespace ts_l332
datafile '/dbms/links/line_332' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l333 including contents;
create tablespace ts_l333
datafile '/dbms/links/line_333' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l334 including contents;
create tablespace ts_l334
datafile '/dbms/links/line_334' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l335 including contents;
create tablespace ts_l335
datafile '/dbms/links/line_335' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_l336 including contents;
create tablespace ts_l336
datafile '/dbms/links/line_336' size 30800m reuse
extent management dictionary default storage (initial 1050m next
20m maxextents unlimited pctincrease 0)
;
}
*wait
*sql
{
--drop tablespace ts_o1 including contents;
create tablespace ts_o1
datafile '/dbms/links/ord_1' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}

*sql
{
--drop tablespace ts_o2 including contents;
create tablespace ts_o2
datafile '/dbms/links/ord_2' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o3 including contents;
create tablespace ts_o3
datafile '/dbms/links/ord_3' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o4 including contents;
create tablespace ts_o4
datafile '/dbms/links/ord_4' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o5 including contents;
create tablespace ts_o5
datafile '/dbms/links/ord_5' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o6 including contents;
create tablespace ts_o6
datafile '/dbms/links/ord_6' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o7 including contents;
create tablespace ts_o7
datafile '/dbms/links/ord_7' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o8 including contents;
create tablespace ts_o8
datafile '/dbms/links/ord_8' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o9 including contents;
create tablespace ts_o9
datafile '/dbms/links/ord_9' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}

```

```

;
}
*sql
{
--drop tablespace ts_o10 including contents;
create tablespace ts_o10
datafile '/dbms/links/ord_10' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o11 including contents;
create tablespace ts_o11
datafile '/dbms/links/ord_11' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o12 including contents;
create tablespace ts_o12
datafile '/dbms/links/ord_12' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o13 including contents;
create tablespace ts_o13
datafile '/dbms/links/ord_13' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o14 including contents;
create tablespace ts_o14
datafile '/dbms/links/ord_14' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o15 including contents;
create tablespace ts_o15
datafile '/dbms/links/ord_15' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o16 including contents;
create tablespace ts_o16
datafile '/dbms/links/ord_16' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o17 including contents;
create tablespace ts_o17
datafile '/dbms/links/ord_17' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o18 including contents;
create tablespace ts_o18
datafile '/dbms/links/ord_18' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o19 including contents;
create tablespace ts_o19
datafile '/dbms/links/ord_19' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o20 including contents;
create tablespace ts_o20
datafile '/dbms/links/ord_20' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o21 including contents;
create tablespace ts_o21
datafile '/dbms/links/ord_21' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o22 including contents;
create tablespace ts_o22
datafile '/dbms/links/ord_22' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o23 including contents;
create tablespace ts_o23
datafile '/dbms/links/ord_23' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o24 including contents;
create tablespace ts_o24
datafile '/dbms/links/ord_24' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o25 including contents;

```

```

create tablespace ts_o25
datafile '/dbms/links/ord_25' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o26 including contents;
create tablespace ts_o26
datafile '/dbms/links/ord_26' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o27 including contents;
create tablespace ts_o27
datafile '/dbms/links/ord_27' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o28 including contents;
create tablespace ts_o28
datafile '/dbms/links/ord_28' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o29 including contents;
create tablespace ts_o29
datafile '/dbms/links/ord_29' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o30 including contents;
create tablespace ts_o30
datafile '/dbms/links/ord_30' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o31 including contents;
create tablespace ts_o31
datafile '/dbms/links/ord_31' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o32 including contents;
create tablespace ts_o32
datafile '/dbms/links/ord_32' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o33 including contents;
create tablespace ts_o33
datafile '/dbms/links/ord_33' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o34 including contents;
create tablespace ts_o34
datafile '/dbms/links/ord_34' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o35 including contents;
create tablespace ts_o35
datafile '/dbms/links/ord_35' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o36 including contents;
create tablespace ts_o36
datafile '/dbms/links/ord_36' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o37 including contents;
create tablespace ts_o37
datafile '/dbms/links/ord_37' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o38 including contents;
create tablespace ts_o38
datafile '/dbms/links/ord_38' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o39 including contents;
create tablespace ts_o39
datafile '/dbms/links/ord_39' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o40 including contents;
create tablespace ts_o40
datafile '/dbms/links/ord_40' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}

```

```

}
*sql
{
--drop tablespace ts_o41 including contents;
create tablespace ts_o41
datafile '/dbms/links/ord_41' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o42 including contents;
create tablespace ts_o42
datafile '/dbms/links/ord_42' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o43 including contents;
create tablespace ts_o43
datafile '/dbms/links/ord_43' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o44 including contents;
create tablespace ts_o44
datafile '/dbms/links/ord_44' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o45 including contents;
create tablespace ts_o45
datafile '/dbms/links/ord_45' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o46 including contents;
create tablespace ts_o46
datafile '/dbms/links/ord_46' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o47 including contents;
create tablespace ts_o47
datafile '/dbms/links/ord_47' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o48 including contents;
create tablespace ts_o48
datafile '/dbms/links/ord_48' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o49 including contents;
create tablespace ts_o49
datafile '/dbms/links/ord_49' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o50 including contents;
create tablespace ts_o50
datafile '/dbms/links/ord_50' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o51 including contents;
create tablespace ts_o51
datafile '/dbms/links/ord_51' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o52 including contents;
create tablespace ts_o52
datafile '/dbms/links/ord_52' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o53 including contents;
create tablespace ts_o53
datafile '/dbms/links/ord_53' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o54 including contents;
create tablespace ts_o54
datafile '/dbms/links/ord_54' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o55 including contents;
create tablespace ts_o55
datafile '/dbms/links/ord_55' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o56 including contents;

```

```

create tablespace ts_056
datafile '/dbms/links/ord_56' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_057 including contents;
create tablespace ts_057
datafile '/dbms/links/ord_57' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_058 including contents;
create tablespace ts_058
datafile '/dbms/links/ord_58' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_059 including contents;
create tablespace ts_059
datafile '/dbms/links/ord_59' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_060 including contents;
create tablespace ts_060
datafile '/dbms/links/ord_60' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_061 including contents;
create tablespace ts_061
datafile '/dbms/links/ord_61' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_062 including contents;
create tablespace ts_062
datafile '/dbms/links/ord_62' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_063 including contents;
create tablespace ts_063
datafile '/dbms/links/ord_63' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_064 including contents;
create tablespace ts_064
datafile '/dbms/links/ord_64' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_065 including contents;
create tablespace ts_065
datafile '/dbms/links/ord_65' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_066 including contents;
create tablespace ts_066
datafile '/dbms/links/ord_66' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_067 including contents;
create tablespace ts_067
datafile '/dbms/links/ord_67' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_068 including contents;
create tablespace ts_068
datafile '/dbms/links/ord_68' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_069 including contents;
create tablespace ts_069
datafile '/dbms/links/ord_69' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_070 including contents;
create tablespace ts_070
datafile '/dbms/links/ord_70' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_071 including contents;
create tablespace ts_071
datafile '/dbms/links/ord_71' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}

```

```

}
*sql
{
--drop tablespace ts_o72 including contents;
create tablespace ts_o72
datafile '/dbms/links/ord_72' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o73 including contents;
create tablespace ts_o73
datafile '/dbms/links/ord_73' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o74 including contents;
create tablespace ts_o74
datafile '/dbms/links/ord_74' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o75 including contents;
create tablespace ts_o75
datafile '/dbms/links/ord_75' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o76 including contents;
create tablespace ts_o76
datafile '/dbms/links/ord_76' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o77 including contents;
create tablespace ts_o77
datafile '/dbms/links/ord_77' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o78 including contents;
create tablespace ts_o78
datafile '/dbms/links/ord_78' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o79 including contents;
create tablespace ts_o79
datafile '/dbms/links/ord_79' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o80 including contents;
create tablespace ts_o80
datafile '/dbms/links/ord_80' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o81 including contents;
create tablespace ts_o81
datafile '/dbms/links/ord_81' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o82 including contents;
create tablespace ts_o82
datafile '/dbms/links/ord_82' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o83 including contents;
create tablespace ts_o83
datafile '/dbms/links/ord_83' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o84 including contents;
create tablespace ts_o84
datafile '/dbms/links/ord_84' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o85 including contents;
create tablespace ts_o85
datafile '/dbms/links/ord_85' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o86 including contents;
create tablespace ts_o86
datafile '/dbms/links/ord_86' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o87 including contents;

```

```

create tablespace ts_o87
datafile '/dbms/links/ord_87' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o88 including contents;
create tablespace ts_o88
datafile '/dbms/links/ord_88' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o89 including contents;
create tablespace ts_o89
datafile '/dbms/links/ord_89' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o90 including contents;
create tablespace ts_o90
datafile '/dbms/links/ord_90' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o91 including contents;
create tablespace ts_o91
datafile '/dbms/links/ord_91' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o92 including contents;
create tablespace ts_o92
datafile '/dbms/links/ord_92' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o93 including contents;
create tablespace ts_o93
datafile '/dbms/links/ord_93' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o94 including contents;
create tablespace ts_o94
datafile '/dbms/links/ord_94' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o95 including contents;
create tablespace ts_o95
datafile '/dbms/links/ord_95' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o96 including contents;
create tablespace ts_o96
datafile '/dbms/links/ord_96' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o97 including contents;
create tablespace ts_o97
datafile '/dbms/links/ord_97' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o98 including contents;
create tablespace ts_o98
datafile '/dbms/links/ord_98' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o99 including contents;
create tablespace ts_o99
datafile '/dbms/links/ord_99' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o100 including contents;
create tablespace ts_o100
datafile '/dbms/links/ord_100' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o101 including contents;
create tablespace ts_o101
datafile '/dbms/links/ord_101' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o102 including contents;
create tablespace ts_o102
datafile '/dbms/links/ord_102' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}

```

```

}
*sql
{
--drop tablespace ts_o103 including contents;
create tablespace ts_o103
datafile '/dbms/links/ord_103' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o104 including contents;
create tablespace ts_o104
datafile '/dbms/links/ord_104' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o105 including contents;
create tablespace ts_o105
datafile '/dbms/links/ord_105' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o106 including contents;
create tablespace ts_o106
datafile '/dbms/links/ord_106' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o107 including contents;
create tablespace ts_o107
datafile '/dbms/links/ord_107' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o108 including contents;
create tablespace ts_o108
datafile '/dbms/links/ord_108' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o109 including contents;
create tablespace ts_o109
datafile '/dbms/links/ord_109' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o110 including contents;
create tablespace ts_o110
datafile '/dbms/links/ord_110' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o111 including contents;
create tablespace ts_o111
datafile '/dbms/links/ord_111' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o112 including contents;
create tablespace ts_o112
datafile '/dbms/links/ord_112' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o113 including contents;
create tablespace ts_o113
datafile '/dbms/links/ord_113' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o114 including contents;
create tablespace ts_o114
datafile '/dbms/links/ord_114' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o115 including contents;
create tablespace ts_o115
datafile '/dbms/links/ord_115' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o116 including contents;
create tablespace ts_o116
datafile '/dbms/links/ord_116' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o117 including contents;
create tablespace ts_o117
datafile '/dbms/links/ord_117' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o118 including contents;

```

```

create tablespace ts_o118
datafile '/dbms/links/ord_118' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o119 including contents;
create tablespace ts_o119
datafile '/dbms/links/ord_119' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o120 including contents;
create tablespace ts_o120
datafile '/dbms/links/ord_120' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o121 including contents;
create tablespace ts_o121
datafile '/dbms/links/ord_121' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o122 including contents;
create tablespace ts_o122
datafile '/dbms/links/ord_122' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o123 including contents;
create tablespace ts_o123
datafile '/dbms/links/ord_123' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o124 including contents;
create tablespace ts_o124
datafile '/dbms/links/ord_124' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o125 including contents;
create tablespace ts_o125
datafile '/dbms/links/ord_125' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o126 including contents;
create tablespace ts_o126
datafile '/dbms/links/ord_126' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o127 including contents;
create tablespace ts_o127
datafile '/dbms/links/ord_127' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o128 including contents;
create tablespace ts_o128
datafile '/dbms/links/ord_128' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o129 including contents;
create tablespace ts_o129
datafile '/dbms/links/ord_129' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o130 including contents;
create tablespace ts_o130
datafile '/dbms/links/ord_130' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o131 including contents;
create tablespace ts_o131
datafile '/dbms/links/ord_131' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o132 including contents;
create tablespace ts_o132
datafile '/dbms/links/ord_132' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o133 including contents;
create tablespace ts_o133
datafile '/dbms/links/ord_133' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}

```

```

}
*sql
{
--drop tablespace ts_o134 including contents;
create tablespace ts_o134
datafile '/dbms/links/ord_134' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o135 including contents;
create tablespace ts_o135
datafile '/dbms/links/ord_135' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o136 including contents;
create tablespace ts_o136
datafile '/dbms/links/ord_136' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o137 including contents;
create tablespace ts_o137
datafile '/dbms/links/ord_137' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o138 including contents;
create tablespace ts_o138
datafile '/dbms/links/ord_138' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o139 including contents;
create tablespace ts_o139
datafile '/dbms/links/ord_139' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o140 including contents;
create tablespace ts_o140
datafile '/dbms/links/ord_140' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o141 including contents;
create tablespace ts_o141
datafile '/dbms/links/ord_141' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o142 including contents;
create tablespace ts_o142
datafile '/dbms/links/ord_142' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o143 including contents;
create tablespace ts_o143
datafile '/dbms/links/ord_143' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o144 including contents;
create tablespace ts_o144
datafile '/dbms/links/ord_144' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o145 including contents;
create tablespace ts_o145
datafile '/dbms/links/ord_145' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o146 including contents;
create tablespace ts_o146
datafile '/dbms/links/ord_146' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o147 including contents;
create tablespace ts_o147
datafile '/dbms/links/ord_147' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o148 including contents;
create tablespace ts_o148
datafile '/dbms/links/ord_148' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o149 including contents;

```

```

create tablespace ts_o149
datafile '/dbms/links/ord_149' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o150 including contents;
create tablespace ts_o150
datafile '/dbms/links/ord_150' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o151 including contents;
create tablespace ts_o151
datafile '/dbms/links/ord_151' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o152 including contents;
create tablespace ts_o152
datafile '/dbms/links/ord_152' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o153 including contents;
create tablespace ts_o153
datafile '/dbms/links/ord_153' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o154 including contents;
create tablespace ts_o154
datafile '/dbms/links/ord_154' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o155 including contents;
create tablespace ts_o155
datafile '/dbms/links/ord_155' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o156 including contents;
create tablespace ts_o156
datafile '/dbms/links/ord_156' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o157 including contents;
create tablespace ts_o157
datafile '/dbms/links/ord_157' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o158 including contents;
create tablespace ts_o158
datafile '/dbms/links/ord_158' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o159 including contents;
create tablespace ts_o159
datafile '/dbms/links/ord_159' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o160 including contents;
create tablespace ts_o160
datafile '/dbms/links/ord_160' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o161 including contents;
create tablespace ts_o161
datafile '/dbms/links/ord_161' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o162 including contents;
create tablespace ts_o162
datafile '/dbms/links/ord_162' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o163 including contents;
create tablespace ts_o163
datafile '/dbms/links/ord_163' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o164 including contents;
create tablespace ts_o164
datafile '/dbms/links/ord_164' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}

```

```

}
*sql
{
--drop tablespace ts_o165 including contents;
create tablespace ts_o165
datafile '/dbms/links/ord_165' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o166 including contents;
create tablespace ts_o166
datafile '/dbms/links/ord_166' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o167 including contents;
create tablespace ts_o167
datafile '/dbms/links/ord_167' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o168 including contents;
create tablespace ts_o168
datafile '/dbms/links/ord_168' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o169 including contents;
create tablespace ts_o169
datafile '/dbms/links/ord_169' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o170 including contents;
create tablespace ts_o170
datafile '/dbms/links/ord_170' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o171 including contents;
create tablespace ts_o171
datafile '/dbms/links/ord_171' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o172 including contents;
create tablespace ts_o172
datafile '/dbms/links/ord_172' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o173 including contents;
create tablespace ts_o173
datafile '/dbms/links/ord_173' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o174 including contents;
create tablespace ts_o174
datafile '/dbms/links/ord_174' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o175 including contents;
create tablespace ts_o175
datafile '/dbms/links/ord_175' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o176 including contents;
create tablespace ts_o176
datafile '/dbms/links/ord_176' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o177 including contents;
create tablespace ts_o177
datafile '/dbms/links/ord_177' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o178 including contents;
create tablespace ts_o178
datafile '/dbms/links/ord_178' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o179 including contents;
create tablespace ts_o179
datafile '/dbms/links/ord_179' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o180 including contents;

```

```

create tablespace ts_o180
datafile '/dbms/links/ord_180' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o181 including contents;
create tablespace ts_o181
datafile '/dbms/links/ord_181' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o182 including contents;
create tablespace ts_o182
datafile '/dbms/links/ord_182' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o183 including contents;
create tablespace ts_o183
datafile '/dbms/links/ord_183' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o184 including contents;
create tablespace ts_o184
datafile '/dbms/links/ord_184' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o185 including contents;
create tablespace ts_o185
datafile '/dbms/links/ord_185' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o186 including contents;
create tablespace ts_o186
datafile '/dbms/links/ord_186' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o187 including contents;
create tablespace ts_o187
datafile '/dbms/links/ord_187' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o188 including contents;
create tablespace ts_o188
datafile '/dbms/links/ord_188' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o189 including contents;
create tablespace ts_o189
datafile '/dbms/links/ord_189' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o190 including contents;
create tablespace ts_o190
datafile '/dbms/links/ord_190' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o191 including contents;
create tablespace ts_o191
datafile '/dbms/links/ord_191' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o192 including contents;
create tablespace ts_o192
datafile '/dbms/links/ord_192' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o193 including contents;
create tablespace ts_o193
datafile '/dbms/links/ord_193' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o194 including contents;
create tablespace ts_o194
datafile '/dbms/links/ord_194' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o195 including contents;
create tablespace ts_o195
datafile '/dbms/links/ord_195' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}

```

```

}
*sql
{
--drop tablespace ts_o196 including contents;
create tablespace ts_o196
datafile '/dbms/links/ord_196' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o197 including contents;
create tablespace ts_o197
datafile '/dbms/links/ord_197' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o198 including contents;
create tablespace ts_o198
datafile '/dbms/links/ord_198' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o199 including contents;
create tablespace ts_o199
datafile '/dbms/links/ord_199' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o200 including contents;
create tablespace ts_o200
datafile '/dbms/links/ord_200' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o201 including contents;
create tablespace ts_o201
datafile '/dbms/links/ord_201' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o202 including contents;
create tablespace ts_o202
datafile '/dbms/links/ord_202' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o203 including contents;
create tablespace ts_o203
datafile '/dbms/links/ord_203' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o204 including contents;
create tablespace ts_o204
datafile '/dbms/links/ord_204' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o205 including contents;
create tablespace ts_o205
datafile '/dbms/links/ord_205' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o206 including contents;
create tablespace ts_o206
datafile '/dbms/links/ord_206' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o207 including contents;
create tablespace ts_o207
datafile '/dbms/links/ord_207' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o208 including contents;
create tablespace ts_o208
datafile '/dbms/links/ord_208' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o209 including contents;
create tablespace ts_o209
datafile '/dbms/links/ord_209' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o210 including contents;
create tablespace ts_o210
datafile '/dbms/links/ord_210' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o211 including contents;

```

```

create tablespace ts_o211
datafile '/dbms/links/ord_211' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o212 including contents;
create tablespace ts_o212
datafile '/dbms/links/ord_212' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o213 including contents;
create tablespace ts_o213
datafile '/dbms/links/ord_213' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o214 including contents;
create tablespace ts_o214
datafile '/dbms/links/ord_214' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o215 including contents;
create tablespace ts_o215
datafile '/dbms/links/ord_215' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o216 including contents;
create tablespace ts_o216
datafile '/dbms/links/ord_216' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o217 including contents;
create tablespace ts_o217
datafile '/dbms/links/ord_217' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o218 including contents;
create tablespace ts_o218
datafile '/dbms/links/ord_218' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o219 including contents;
create tablespace ts_o219
datafile '/dbms/links/ord_219' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o220 including contents;
create tablespace ts_o220
datafile '/dbms/links/ord_220' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o221 including contents;
create tablespace ts_o221
datafile '/dbms/links/ord_221' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o222 including contents;
create tablespace ts_o222
datafile '/dbms/links/ord_222' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o223 including contents;
create tablespace ts_o223
datafile '/dbms/links/ord_223' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o224 including contents;
create tablespace ts_o224
datafile '/dbms/links/ord_224' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o225 including contents;
create tablespace ts_o225
datafile '/dbms/links/ord_225' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o226 including contents;
create tablespace ts_o226
datafile '/dbms/links/ord_226' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}

```

```

}
*sql
{
--drop tablespace ts_o227 including contents;
create tablespace ts_o227
datafile '/dbms/links/ord_227' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o228 including contents;
create tablespace ts_o228
datafile '/dbms/links/ord_228' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o229 including contents;
create tablespace ts_o229
datafile '/dbms/links/ord_229' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o230 including contents;
create tablespace ts_o230
datafile '/dbms/links/ord_230' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o231 including contents;
create tablespace ts_o231
datafile '/dbms/links/ord_231' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pct increase 0)
;
}
*sql
{
--drop tablespace ts_o232 including contents;
create tablespace ts_o232
datafile '/dbms/links/ord_232' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o233 including contents;
create tablespace ts_o233
datafile '/dbms/links/ord_233' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o234 including contents;
create tablespace ts_o234
datafile '/dbms/links/ord_234' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o235 including contents;
create tablespace ts_o235
datafile '/dbms/links/ord_235' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o236 including contents;
create tablespace ts_o236
datafile '/dbms/links/ord_236' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o237 including contents;
create tablespace ts_o237
datafile '/dbms/links/ord_237' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o238 including contents;
create tablespace ts_o238
datafile '/dbms/links/ord_238' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o239 including contents;
create tablespace ts_o239
datafile '/dbms/links/ord_239' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o240 including contents;
create tablespace ts_o240
datafile '/dbms/links/ord_240' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o241 including contents;
create tablespace ts_o241
datafile '/dbms/links/ord_241' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o242 including contents;

```

```

create tablespace ts_o242
datafile '/dbms/links/ord_242' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o243 including contents;
create tablespace ts_o243
datafile '/dbms/links/ord_243' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o244 including contents;
create tablespace ts_o244
datafile '/dbms/links/ord_244' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o245 including contents;
create tablespace ts_o245
datafile '/dbms/links/ord_245' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o246 including contents;
create tablespace ts_o246
datafile '/dbms/links/ord_246' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o247 including contents;
create tablespace ts_o247
datafile '/dbms/links/ord_247' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o248 including contents;
create tablespace ts_o248
datafile '/dbms/links/ord_248' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o249 including contents;
create tablespace ts_o249
datafile '/dbms/links/ord_249' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o250 including contents;
create tablespace ts_o250
datafile '/dbms/links/ord_250' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o251 including contents;
create tablespace ts_o251
datafile '/dbms/links/ord_251' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o252 including contents;
create tablespace ts_o252
datafile '/dbms/links/ord_252' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o253 including contents;
create tablespace ts_o253
datafile '/dbms/links/ord_253' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o254 including contents;
create tablespace ts_o254
datafile '/dbms/links/ord_254' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o255 including contents;
create tablespace ts_o255
datafile '/dbms/links/ord_255' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o256 including contents;
create tablespace ts_o256
datafile '/dbms/links/ord_256' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o257 including contents;
create tablespace ts_o257
datafile '/dbms/links/ord_257' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}

```

```

}
*sql
{
--drop tablespace ts_o258 including contents;
create tablespace ts_o258
datafile '/dbms/links/ord_258' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o259 including contents;
create tablespace ts_o259
datafile '/dbms/links/ord_259' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o260 including contents;
create tablespace ts_o260
datafile '/dbms/links/ord_260' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o261 including contents;
create tablespace ts_o261
datafile '/dbms/links/ord_261' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o262 including contents;
create tablespace ts_o262
datafile '/dbms/links/ord_262' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o263 including contents;
create tablespace ts_o263
datafile '/dbms/links/ord_263' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o264 including contents;
create tablespace ts_o264
datafile '/dbms/links/ord_264' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o265 including contents;
create tablespace ts_o265
datafile '/dbms/links/ord_265' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o266 including contents;
create tablespace ts_o266
datafile '/dbms/links/ord_266' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o267 including contents;
create tablespace ts_o267
datafile '/dbms/links/ord_267' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o268 including contents;
create tablespace ts_o268
datafile '/dbms/links/ord_268' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o269 including contents;
create tablespace ts_o269
datafile '/dbms/links/ord_269' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o270 including contents;
create tablespace ts_o270
datafile '/dbms/links/ord_270' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o271 including contents;
create tablespace ts_o271
datafile '/dbms/links/ord_271' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o272 including contents;
create tablespace ts_o272
datafile '/dbms/links/ord_272' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o273 including contents;

```

```

create tablespace ts_o273
datafile '/dbms/links/ord_273' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o274 including contents;
create tablespace ts_o274
datafile '/dbms/links/ord_274' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o275 including contents;
create tablespace ts_o275
datafile '/dbms/links/ord_275' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o276 including contents;
create tablespace ts_o276
datafile '/dbms/links/ord_276' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o277 including contents;
create tablespace ts_o277
datafile '/dbms/links/ord_277' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o278 including contents;
create tablespace ts_o278
datafile '/dbms/links/ord_278' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o279 including contents;
create tablespace ts_o279
datafile '/dbms/links/ord_279' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o280 including contents;
create tablespace ts_o280
datafile '/dbms/links/ord_280' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o281 including contents;
create tablespace ts_o281
datafile '/dbms/links/ord_281' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o282 including contents;
create tablespace ts_o282
datafile '/dbms/links/ord_282' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o283 including contents;
create tablespace ts_o283
datafile '/dbms/links/ord_283' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o284 including contents;
create tablespace ts_o284
datafile '/dbms/links/ord_284' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o285 including contents;
create tablespace ts_o285
datafile '/dbms/links/ord_285' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o286 including contents;
create tablespace ts_o286
datafile '/dbms/links/ord_286' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o287 including contents;
create tablespace ts_o287
datafile '/dbms/links/ord_287' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o288 including contents;
create tablespace ts_o288
datafile '/dbms/links/ord_288' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}

```

```

}
*sql
{
--drop tablespace ts_o289 including contents;
create tablespace ts_o289
datafile '/dbms/links/ord_289' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o290 including contents;
create tablespace ts_o290
datafile '/dbms/links/ord_290' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o291 including contents;
create tablespace ts_o291
datafile '/dbms/links/ord_291' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o292 including contents;
create tablespace ts_o292
datafile '/dbms/links/ord_292' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o293 including contents;
create tablespace ts_o293
datafile '/dbms/links/ord_293' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o294 including contents;
create tablespace ts_o294
datafile '/dbms/links/ord_294' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o295 including contents;
create tablespace ts_o295
datafile '/dbms/links/ord_295' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o296 including contents;
create tablespace ts_o296
datafile '/dbms/links/ord_296' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o297 including contents;
create tablespace ts_o297
datafile '/dbms/links/ord_297' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o298 including contents;
create tablespace ts_o298
datafile '/dbms/links/ord_298' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o299 including contents;
create tablespace ts_o299
datafile '/dbms/links/ord_299' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o300 including contents;
create tablespace ts_o300
datafile '/dbms/links/ord_300' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o301 including contents;
create tablespace ts_o301
datafile '/dbms/links/ord_301' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o302 including contents;
create tablespace ts_o302
datafile '/dbms/links/ord_302' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o303 including contents;
create tablespace ts_o303
datafile '/dbms/links/ord_303' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o304 including contents;

```

```

create tablespace ts_o304
datafile '/dbms/links/ord_304' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o305 including contents;
create tablespace ts_o305
datafile '/dbms/links/ord_305' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o306 including contents;
create tablespace ts_o306
datafile '/dbms/links/ord_306' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o307 including contents;
create tablespace ts_o307
datafile '/dbms/links/ord_307' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o308 including contents;
create tablespace ts_o308
datafile '/dbms/links/ord_308' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o309 including contents;
create tablespace ts_o309
datafile '/dbms/links/ord_309' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o310 including contents;
create tablespace ts_o310
datafile '/dbms/links/ord_310' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o311 including contents;
create tablespace ts_o311
datafile '/dbms/links/ord_311' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o312 including contents;
create tablespace ts_o312
datafile '/dbms/links/ord_312' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o313 including contents;
create tablespace ts_o313
datafile '/dbms/links/ord_313' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o314 including contents;
create tablespace ts_o314
datafile '/dbms/links/ord_314' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o315 including contents;
create tablespace ts_o315
datafile '/dbms/links/ord_315' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o316 including contents;
create tablespace ts_o316
datafile '/dbms/links/ord_316' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o317 including contents;
create tablespace ts_o317
datafile '/dbms/links/ord_317' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o318 including contents;
create tablespace ts_o318
datafile '/dbms/links/ord_318' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o319 including contents;
create tablespace ts_o319
datafile '/dbms/links/ord_319' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}

```

```

}
*sql
{
--drop tablespace ts_o320 including contents;
create tablespace ts_o320
datafile '/dbms/links/ord_320' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o321 including contents;
create tablespace ts_o321
datafile '/dbms/links/ord_321' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o322 including contents;
create tablespace ts_o322
datafile '/dbms/links/ord_322' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o323 including contents;
create tablespace ts_o323
datafile '/dbms/links/ord_323' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o324 including contents;
create tablespace ts_o324
datafile '/dbms/links/ord_324' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o325 including contents;
create tablespace ts_o325
datafile '/dbms/links/ord_325' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o326 including contents;
create tablespace ts_o326
datafile '/dbms/links/ord_326' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o327 including contents;
create tablespace ts_o327
datafile '/dbms/links/ord_327' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o328 including contents;
create tablespace ts_o328
datafile '/dbms/links/ord_328' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o329 including contents;
create tablespace ts_o329
datafile '/dbms/links/ord_329' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o330 including contents;
create tablespace ts_o330
datafile '/dbms/links/ord_330' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o331 including contents;
create tablespace ts_o331
datafile '/dbms/links/ord_331' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o332 including contents;
create tablespace ts_o332
datafile '/dbms/links/ord_332' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o333 including contents;
create tablespace ts_o333
datafile '/dbms/links/ord_333' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o334 including contents;
create tablespace ts_o334
datafile '/dbms/links/ord_334' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o335 including contents;

```

```

create tablespace ts_o335
datafile '/dbms/links/ord_335' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_o336 including contents;
create tablespace ts_o336
datafile '/dbms/links/ord_336' size 7000m reuse
extent management dictionary default storage (initial 450m next 10m
maxextents unlimited pctincrease 0)
;
}
*wait
*sql
{
--drop tablespace ts_small1 including contents;
create tablespace ts_small1
datafile '/dbms/links/small_1' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small2 including contents;
create tablespace ts_small2
datafile '/dbms/links/small_2' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small3 including contents;
create tablespace ts_small3
datafile '/dbms/links/small_3' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small4 including contents;
create tablespace ts_small4
datafile '/dbms/links/small_4' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small5 including contents;
create tablespace ts_small5
datafile '/dbms/links/small_5' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small6 including contents;
create tablespace ts_small6
datafile '/dbms/links/small_6' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}

*sql
{
--drop tablespace ts_small7 including contents;
create tablespace ts_small7
datafile '/dbms/links/small_7' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small8 including contents;
create tablespace ts_small8
datafile '/dbms/links/small_8' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small9 including contents;
create tablespace ts_small9
datafile '/dbms/links/small_9' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small10 including contents;
create tablespace ts_small10
datafile '/dbms/links/small_10' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small11 including contents;
create tablespace ts_small11
datafile '/dbms/links/small_11' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small12 including contents;
create tablespace ts_small12
datafile '/dbms/links/small_12' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small13 including contents;
create tablespace ts_small13
datafile '/dbms/links/small_13' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small14 including contents;
create tablespace ts_small14
datafile '/dbms/links/small_14' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}

```

```

;
}
*sql
{
--drop tablespace ts_small15 including contents;
create tablespace ts_small15
datafile '/dbms/links/small_15' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small16 including contents;
create tablespace ts_small16
datafile '/dbms/links/small_16' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small17 including contents;
create tablespace ts_small17
datafile '/dbms/links/small_17' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small18 including contents;
create tablespace ts_small18
datafile '/dbms/links/small_18' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small19 including contents;
create tablespace ts_small19
datafile '/dbms/links/small_19' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small20 including contents;
create tablespace ts_small20
datafile '/dbms/links/small_20' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small21 including contents;
create tablespace ts_small21
datafile '/dbms/links/small_21' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small22 including contents;
create tablespace ts_small22
datafile '/dbms/links/small_22' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small23 including contents;
create tablespace ts_small23
datafile '/dbms/links/small_23' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small24 including contents;
create tablespace ts_small24
datafile '/dbms/links/small_24' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small25 including contents;
create tablespace ts_small25
datafile '/dbms/links/small_25' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small26 including contents;
create tablespace ts_small26
datafile '/dbms/links/small_26' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small27 including contents;
create tablespace ts_small27
datafile '/dbms/links/small_27' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small28 including contents;
create tablespace ts_small28
datafile '/dbms/links/small_28' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small29 including contents;
create tablespace ts_small29
datafile '/dbms/links/small_29' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small30 including contents;

```

```

create tablespace ts_small30
datafile '/dbms/links/small_30' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small31 including contents;
create tablespace ts_small31
datafile '/dbms/links/small_31' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_small32 including contents;
create tablespace ts_small32
datafile '/dbms/links/small_32' size 25000m reuse
extent management dictionary default storage (initial 450m next 20m
maxextents unlimited pctincrease 0)
;
}
*sql
{
--drop tablespace ts_okey including contents;
create tablespace ts_okey
datafile '/dbms/links/okey_1' size 14000m reuse
extent management local
autoallocate
;
}
*sql
{
--drop tablespace ts_custkey including contents;
create tablespace ts_custkey
datafile '/dbms/links/custkey_1' size 1500m reuse
extent management local
uniform size 30M
;
}
*sql
{
--drop tablespace ts_lokey including contents;
create tablespace ts_lokey
datafile '/dbms/links/lokey_1' size 16000m reuse
extent management local
autoallocate
;
}
*sql
{
--drop tablespace ts_pspp1 including contents;
create tablespace ts_pspp1
datafile '/dbms/links/psupp_1' size 26400m reuse
extent management dictionary default storage (initial 1100m next
50m maxextents unlimited pctincrease 0)
;
}
# creating tpch's ts_temp tablespace
##sql
#{
--drop tablespace ts_temp including contents;
#create temporary tablespace ts_temp
#rem tempfile '/dbms/links/temp_1' size 32000m reuse
#rem extent management local
#rem uniform size 5M
#;
#}

*wait
# adding tablespace datafiles
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_2' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_3' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_4' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_5' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_6' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_7' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_8' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_9' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_10' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_11' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_12' size 26400m reuse
;
}
*sql
{

```

```

alter tablespace ts_pspp1
add datafile '/dbms/links/pspp_13' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/pspp_14' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/pspp_15' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/pspp_16' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/pspp_17' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/pspp_18' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/pspp_19' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/pspp_20' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/pspp_21' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/pspp_22' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/pspp_23' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/pspp_24' size 26400m reuse
;
}

*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/pspp_25' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/pspp_26' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/pspp_27' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/pspp_28' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/pspp_29' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/pspp_30' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/pspp_31' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/pspp_32' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/pspp_33' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/pspp_34' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/pspp_35' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/pspp_36' size 26400m reuse
;
}

```

```

;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_37' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_38' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_39' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_40' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_41' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_42' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_43' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_44' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_45' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_46' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_47' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_48' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_49' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_50' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_51' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_52' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_53' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_54' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_55' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_56' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_57' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_58' size 26400m reuse
;
}
*sql
{
alter tablespace ts_pspp1
add datafile '/dbms/links/psupp_59' size 26400m reuse
;
}

```

```

*sql
{
alter tablespace ts_psupp1
add datafile '/dbms/links/psupp_60' size 26400m reuse
;
}
*sql
{
alter tablespace ts_psupp1
add datafile '/dbms/links/psupp_61' size 26400m reuse
;
}
*sql
{
alter tablespace ts_psupp1
add datafile '/dbms/links/psupp_62' size 26400m reuse
;
}
*sql
{
alter tablespace ts_psupp1
add datafile '/dbms/links/psupp_63' size 26400m reuse
;
}
*sql
{
alter tablespace ts_psupp1
add datafile '/dbms/links/psupp_64' size 26400m reuse
;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_2' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_3' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_4' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_5' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_6' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_7' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_8' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_9' size 14000m reuse;
}

*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_10' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_11' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_12' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_13' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_14' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_15' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_16' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_17' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_18' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_19' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_20' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_21' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_22' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_23' size 14000m reuse;
}

```

```

*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_24' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_25' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_26' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_27' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_28' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_29' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_30' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_31' size 14000m reuse;
}
*sql
{
alter tablespace ts_okey
  add datafile '/dbms/links/okey_32' size 14000m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_2' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_3' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_4' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_5' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_6' size 1500m reuse;
}

*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_7' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_8' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_9' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_10' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_11' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_12' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_13' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_14' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_15' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_16' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_17' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_18' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_19' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_20' size 1500m reuse;
}

```

```

*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_21' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_22' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_23' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_24' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_25' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_26' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_27' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_28' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_29' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_30' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_31' size 1500m reuse;
}
*sql
{
alter tablespace ts_custkey
  add datafile '/dbms/links/custkey_32' size 1500m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_2' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_3' size 16000m reuse;
}

*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_4' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_5' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_6' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_7' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_8' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_9' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_10' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_11' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_12' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_13' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_14' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_15' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_16' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_17' size 16000m reuse;
}

```

```

*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_18' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_19' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_20' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_21' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_22' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_23' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_24' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_25' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_26' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_27' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_28' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_29' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_30' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_31' size 16000m reuse;
}

*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_32' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_33' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_34' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_35' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_36' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_37' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_38' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_39' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_40' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_41' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_42' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_43' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_44' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_45' size 16000m reuse;
}

```

```

*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_46' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_47' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_48' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_49' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_50' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_51' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_52' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_53' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_54' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_55' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_56' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_57' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_58' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_59' size 16000m reuse;
}

*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_60' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_61' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_62' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_63' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_64' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_65' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_66' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_67' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_68' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_69' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_70' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_71' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_72' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_73' size 16000m reuse;
}

```

```

*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_74' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_75' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_76' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_77' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_78' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_79' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_80' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_81' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_82' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_83' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_84' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_85' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_86' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_87' size 16000m reuse;
}

*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_88' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_89' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_90' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_91' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_92' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_93' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_94' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_95' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_96' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_97' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_98' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_99' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_100' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_101' size 16000m reuse;
}

```

```

*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_102' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_103' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_104' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_105' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_106' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_107' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_108' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_109' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_110' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_111' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_112' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_113' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_114' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_115' size 16000m reuse;
}

*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_116' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_117' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_118' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_119' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_120' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_121' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_122' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_123' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_124' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_125' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_126' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_127' size 16000m reuse;
}
*sql
{
alter tablespace ts_lokey
  add datafile '/dbms/links/lokey_128' size 16000m reuse;
}
*wait
#adding tpch's ts_temp add datafiles
*sql
{
alter tablespace ts_temp

```

```

add tempfile '/dbms/links/temp_2' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_3' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_4' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_5' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_6' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_7' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_8' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_9' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_10' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_11' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_12' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_13' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_14' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_15' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_16' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_17' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_18' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_19' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_20' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_21' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_22' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_23' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_24' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_25' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_26' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_27' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_28' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_29' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp

```

```

add tempfile '/dbms/links/temp_30' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_31' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_32' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_33' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_34' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_35' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_36' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_37' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_38' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_39' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_40' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_41' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_42' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_43' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_44' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_45' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_46' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_47' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_48' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_49' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_50' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_51' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_52' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_53' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_54' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_55' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_56' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_57' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp

```

```

add tempfile '/dbms/links/temp_58' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_59' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_60' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_61' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_62' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_63' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_64' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_65' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_66' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_67' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_68' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_69' size 32000m reuse;
}
sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_70' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_71' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_72' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_73' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_74' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_75' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_76' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_77' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_78' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_79' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_80' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_81' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_82' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_83' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_84' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_85' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp

```

```

add tempfile '/dbms/links/temp_86' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_87' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_88' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_89' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_90' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_91' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_92' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_93' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_94' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_95' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_96' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_97' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_98' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_99' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_100' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_101' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_102' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_103' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_104' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_105' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_106' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_107' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_108' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_109' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_110' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_111' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_112' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_113' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp

```

```

add tempfile '/dbms/links/temp_114' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_115' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_116' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_117' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_118' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_119' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_120' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_121' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_122' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_123' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_124' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_125' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_126' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_127' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_128' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_129' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_130' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_131' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_132' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_133' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_134' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_135' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_136' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_137' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_138' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_139' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_140' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_141' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp

```

```

add tempfile '/dbms/links/temp_142' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_143' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_144' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_145' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_146' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_147' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_148' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_149' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_150' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_151' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_152' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_153' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_154' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_155' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_156' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_157' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_158' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_159' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_160' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_161' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_162' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_163' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_164' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_165' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_166' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_167' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_168' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_169' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp

```

```

add tempfile '/dbms/links/temp_170' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_171' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_172' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_173' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_174' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_175' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_176' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_177' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_178' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_179' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_180' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_181' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_182' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_183' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_184' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_185' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_186' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_187' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_188' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_189' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_190' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_191' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_192' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_193' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_194' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_195' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_196' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_197' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp

```

```

add tempfile '/dbms/links/temp_198' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_199' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_200' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_201' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_202' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_203' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_204' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_205' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_206' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_207' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_208' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_209' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_210' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_211' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_212' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_213' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_214' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_215' size 32000m reuse;
}
*sql
{
alter tablespace ts_temp
add tempfile '/dbms/links/temp_216' size 32000m reuse;
}
*wait
#adding tpch's ts_undo add datafiles
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_2' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_3' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_4' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_5' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_6' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_7' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_8' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_9' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_10' size 22000m reuse;
}
*sql

```

```

{
alter tablespace ts_undo
add datafile '/dbms/links/undo_11' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_12' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_13' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_14' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_15' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_16' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_17' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_18' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_19' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_20' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_21' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_22' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_23' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_24' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_25' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_26' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_27' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_28' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_29' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_30' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_31' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_32' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_33' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_34' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_35' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_36' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_37' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_38' size 22000m reuse;
}
*sql

```

```

{
alter tablespace ts_undo
add datafile '/dbms/links/undo_39' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_40' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_41' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_42' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_43' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_44' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_45' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_46' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_47' size 22000m reuse;
}
*sql
{
alter tablespace ts_undo
add datafile '/dbms/links/undo_48' size 22000m reuse;
}
*wait
*sql
{
shutdown ;
}
*wait
*bgoff
%e-sctso
%b-dapop
*bgon=1
#####
##### Schema Creation Phase - User and Tables
##### AND Database Population Phase
#
# creating tpch user
*sql
{
#drop user tpch cascade;
grant DBA
to tpch identified by tpch;
}

}
*wait
*sql
{
connect tpch/tpch;
drop directory data_dir;
create directory data_dir as '/dbms/flat';
}
*sql
{
connect tpch/tpch;
drop table l_et;
create table l_et(
l_orderkey      number ,
l_partkey       number ,
l_suppkey       number ,
l_linenumber    number ,
l_quantity      number ,
l_extendedprice number ,
l_discount      number ,
l_tax           number ,
l_returnflag    char(1),
l_linestatus    char(1),
l_shipdate      date ,
l_commitdate    date ,
l_receiptdate   date ,
l_shipinstruct  char(25),
l_shipmode      char(10),
l_comment       varchar(44)
)
organization external (
type ORACLE_LOADER
default directory data_dir
access parameters
(
records delimited by newline
badfile 'l_et.bad'
logfile 'l_et.log'
fields terminated by '|'
missing field values are null
)
location (
'lineitem.tbl.1',
'lineitem.tbl.2',
'lineitem.tbl.3',
'lineitem.tbl.4',
'lineitem.tbl.5',
'lineitem.tbl.6',
'lineitem.tbl.7',
'lineitem.tbl.8',
'lineitem.tbl.9',
'lineitem.tbl.10',
'lineitem.tbl.11',
'lineitem.tbl.12',
'lineitem.tbl.13',
'lineitem.tbl.14',
'lineitem.tbl.15',
'lineitem.tbl.16',
'lineitem.tbl.17',
'lineitem.tbl.18',
'lineitem.tbl.19',
'lineitem.tbl.20',
'lineitem.tbl.21',
'lineitem.tbl.22',
'lineitem.tbl.23',
'lineitem.tbl.24',
'lineitem.tbl.25',
'lineitem.tbl.26',
'lineitem.tbl.27',
'lineitem.tbl.28',
)
)

```

```

'lineitem.tbl.29',
'lineitem.tbl.30',
'lineitem.tbl.31',
'lineitem.tbl.32',
'lineitem.tbl.33',
'lineitem.tbl.34',
'lineitem.tbl.35',
'lineitem.tbl.36',
'lineitem.tbl.37',
'lineitem.tbl.38',
'lineitem.tbl.39',
'lineitem.tbl.40',
'lineitem.tbl.41',
'lineitem.tbl.42',
'lineitem.tbl.43',
'lineitem.tbl.44',
'lineitem.tbl.45',
'lineitem.tbl.46',
'lineitem.tbl.47',
'lineitem.tbl.48',
'lineitem.tbl.49',
'lineitem.tbl.50',
'lineitem.tbl.51',
'lineitem.tbl.52',
'lineitem.tbl.53',
'lineitem.tbl.54',
'lineitem.tbl.55',
'lineitem.tbl.56',
'lineitem.tbl.57',
'lineitem.tbl.58',
'lineitem.tbl.59',
'lineitem.tbl.60',
'lineitem.tbl.61',
'lineitem.tbl.62',
'lineitem.tbl.63',
'lineitem.tbl.64',
'lineitem.tbl.65',
'lineitem.tbl.66',
'lineitem.tbl.67',
'lineitem.tbl.68',
'lineitem.tbl.69',
'lineitem.tbl.70',
'lineitem.tbl.71',
'lineitem.tbl.72',
'lineitemtbl.73',
'lineitemtbl.74',
'lineitemtbl.75',
'lineitemtbl.76',
'lineitemtbl.77',
'lineitemtbl.78',
'lineitemtbl.79',
'lineitemtbl.80',
'lineitemtbl.81',
'lineitemtbl.82',
'lineitemtbl.83',
'lineitemtbl.84'
))
reject limit unlimited;
}
*sql
{
connect tpch/tpch;
drop table o_et;
create table o_et(
    o_orderkey      number ,
    o_custkey       number ,
    o_orderstatus   char(1) ,
    o_totalprice    number ,
    o_orderdate     date ,
    o_orderpriority char(15) ,
    o_clerk         char(15) ,
    o_shippriority  number ,
    o_comment        varchar(79)
)
organization external (
    type ORACLE_LOADER
    default directory data_dir
    access parameters
    (
        records delimited by newline
        badfile 'o_et.bad'
        logfile 'o_et.log'
        fields terminated by '|'
        missing field values are null
    )
    location (
        'orders.tbl.1',
        'orders.tbl.2',
        'orders.tbl.3',
        'orders.tbl.4',
        'orders.tbl.5',
        'orders.tbl.6',
        'orders.tbl.7',
        'orders.tbl.8',
        'orders.tbl.9',
        'orders.tbl.10',
        'orders.tbl.11',
        'orders.tbl.12',
        'orders.tbl.13',
        'orders.tbl.14',
        'orders.tbl.15',
        'orders.tbl.16',
        'orders.tbl.17',
        'orders.tbl.18',
        'orders.tbl.19',
        'orders.tbl.20',
        'orders.tbl.21',
        'orders.tbl.22',
        'orders.tbl.23',
        'orders.tbl.24',
        'orders.tbl.25',
        'orders.tbl.26',
        'orders.tbl.27',
        'orders.tbl.28',
        'orders.tbl.29',
        'orders.tbl.30',
        'orders.tbl.31',
        'orders.tbl.32',
        'orders.tbl.33',
        'orders.tbl.34',
        'orders.tbl.35',
        'orders.tbl.36',
        'orders.tbl.37',
        'orders.tbl.38',
        'orders.tbl.39',
        'orders.tbl.40',
        'orders.tbl.41',
        'orders.tbl.42',
        'orders.tbl.43',
        'orders.tbl.44',
        'orders.tbl.45',
        'orders.tbl.46',
        'orders.tbl.47',
        'orders.tbl.48',
        'orders.tbl.49',
        'orders.tbl.50',
        'orders.tbl.51',
        'orders.tbl.52',
        'orders.tbl.53',
        'orders.tbl.54',
        'orderstbl.55',
        'orderstbl.56',
        'orderstbl.57',
        'orderstbl.58',
        'orderstbl.59',
        'orderstbl.60',
        'orderstbl.61',
        'orderstbl.62',
        'orderstbl.63',
        'orderstbl.64',
        'orderstbl.65',
        'orderstbl.66',
        'orderstbl.67',
        'orderstbl.68',
        'orderstbl.69',
        'orderstbl.70',
        'orderstbl.71',
        'orderstbl.72',
        'orderstbl.73',
        'orderstbl.74',
        'orderstbl.75',
        'orderstbl.76',
        'orderstbl.77',
        'orderstbl.78',
        'orderstbl.79',
        'orderstbl.80',
        'orderstbl.81',
        'orderstbl.82',
        'orderstbl.83',
        'orderstbl.84',
        'orderstbl.85',
        'orderstbl.86',
        'orderstbl.87',
        'orderstbl.88',
        'orderstbl.89',
        'orderstbl.90',
        'orderstbl.91',
        'orderstbl.92',
        'orderstbl.93',
        'orderstbl.94',
        'orderstbl.95',
        'orderstbl.96',
        'orderstbl.97',
        'orderstbl.98',
        'orderstbl.99',
        'orderstbl.100'
    )
)

```

```

'orders.tbl.55',
'orders.tbl.56',
'orders.tbl.57',
'orders.tbl.58',
'orders.tbl.59',
'orders.tbl.60',
'orders.tbl.61',
'orders.tbl.62',
'orders.tbl.63',
'orders.tbl.64',
'orders.tbl.65',
'orders.tbl.66',
'orders.tbl.67',
'orders.tbl.68',
'orders.tbl.69',
'orders.tbl.70',
'orders.tbl.71',
'orders.tbl.72',
'orders.tbl.73',
'orders.tbl.74',
'orders.tbl.75',
'orders.tbl.76',
'orders.tbl.77',
'orders.tbl.78',
'orders.tbl.79',
'orders.tbl.80',
'orders.tbl.81',
'orders.tbl.82',
'orders.tbl.83',
'orders.tbl.84'
))
reject limit unlimited;
}
*sql
{
connect tpch/tpch;
drop table ps_et;
create table ps_et(
    ps_partkey      number ,
    ps_suppkey      number ,
    ps_availqty     number ,
    ps_supplycost   number ,
    ps_comment       varchar(199)
)
organization external (
type ORACLE_LOADER
default directory data_dir
access parameters
(
    records delimited by newline
    badfile 'ps_et.bad'
    logfile 'ps_et.log'
    fields terminated by '|'
    missing field values are null
)
location (
'partsupp.tbl.1',
'partsupp.tbl.2',
'partsupp.tbl.3',
'partsupp.tbl.4',
'partsupp.tbl.5',
'partsupp.tbl.6',
'partsupp.tbl.7',
'partsupp.tbl.8',
'partsupp.tbl.9',
'partsupp.tbl.10',
'partsupp.tbl.11',
'partsupp.tbl.12',
'partsupp.tbl.13',
'partsupp.tbl.14',
'partsupp.tbl.15',
'partsupp.tbl.16',
'partsupp.tbl.17',
'partsupp.tbl.18',
'partsupp.tbl.19',
'partsupp.tbl.20',
'partsupp.tbl.21',
'partsupp.tbl.22',
'partsupp.tbl.23',
'partsupp.tbl.24',
'partsupp.tbl.25',
'partsupp.tbl.26',
'partsupp.tbl.27',
'partsupp.tbl.28',
'partsupp.tbl.29',
'partsupp.tbl.30',
'partsupp.tbl.31',
'partsupp.tbl.32',
'partsupp.tbl.33',
'partsupp.tbl.34',
'partsupp.tbl.35',
'partsupp.tbl.36',
'partsupp.tbl.37',
'partsupp.tbl.38',
'partsupp.tbl.39',
'part supp.tbl.40',
'partsupp.tbl.41',
'partsupp.tbl.42',
'partsupp.tbl.43',
'partsupp.tbl.44',
'partsupp.tbl.45',
'partsupp.tbl.46',
'partsupp.tbl.47',
'partsupp.tbl.48',
'partsupp.tbl.49',
'partsupp.tbl.50',
'partsupp.tbl.51',
'partsupp.tbl.52',
'partsupp.tbl.53',
'partsupp.tbl.54',
'partsupp.tbl.55',
'partsupp.tbl.56',
'partsupp.tbl.57',
'partsupp.tbl.58',
'partsupp.tbl.59',
'partsupp.tbl.60',
'partsupp.tbl.61',
'partsupp.tbl.62',
'partsupp.tbl.63',
'partsupp.tbl.64'))
reject limit unlimited;
}
*sql
{
connect tpch/tpch;
drop table p_et;
create table p_et(
    p_partkey      number ,
    p_name         varchar(55) ,
    p_mfgr         char(25) ,
    p_brand        char(10) ,
    p_type         varchar(25) ,
    p_size         number ,
    p_container    char(10) ,
    p_retailprice  number ,
    p_comment      varchar(23)
)
organization external (
type ORACLE_LOADER
default directory data_dir

```

```

access parameters
(
    records delimited by newline
    badfile 'p_et.bad'
    logfile 'p_et.log'
    fields terminated by '|'
    missing field values are null
)
location (
'part.tbl.1',
'part.tbl.2',
'part.tbl.3',
'part.tbl.4',
'part.tbl.5',
'part.tbl.6',
'part.tbl.7',
'part.tbl.8',
'part.tbl.9',
'part.tbl.10',
'part.tbl.11',
'part.tbl.12',
'part.tbl.13',
'part.tbl.14',
'part.tbl.15',
'part.tbl.16'
))
reject limit unlimited;
}
*sql
{
connect tpch/tpch;
drop table c_et;
create table c_et(
    c_custkey      number ,
    c_name         varchar(25) ,
    c_address      varchar(40) ,
    c_nationkey    number ,
    c_phone        char(15) ,
    c_acctbal     number ,
    c_mktsegment   char(10) ,
    c_comment       varchar(117)
)
organization external (
type ORACLE_LOADER
default directory data_dir
access parameters
(
    records delimited by newline
    badfile 'c_et.bad'
    logfile 'c_et.log'
    fields terminated by '|'
    missing field values are null
)
location (
'customer.tbl.1',
'customer.tbl.2',
'customer.tbl.3',
'customer.tbl.4',
'customer.tbl.5',
'customer.tbl.6',
'customer.tbl.7',
'customer.tbl.8',
'customer.tbl.9',
'customer.tbl.10',
'customer.tbl.11',
'customer.tbl.12',
'customer.tbl.13',
'customer.tbl.14',
'customer.tbl.15',
'customer.tbl.16'
))
reject limit unlimited;
}
*sql
{
connect tpch/tpch;
drop table s_et;
create table s_et(
    s_suppkey      number ,
    s_name          char(25) ,
    s_address       varchar(40) ,
    s_nationkey    number ,
    s_phone         char(15) ,
    s_acctbal      number ,
    s_comment       varchar(101)
)
organization external (
type ORACLE_LOADER
default directory data_dir
access parameters
(
    records delimited by newline
    badfile 's_et.bad'
    logfile 's_et.log'
    fields terminated by '|'
    missing field values are null
)
location (
'supplier.tbl'
))
reject limit unlimited;
}
*sql
{
connect tpch/tpch;
drop table n_et;
create table n_et(
    n_nationkey    number ,
    n_name          char(25) ,
    n_regionkey    number ,
    n_comment       varchar(152)
)
organization external (
type ORACLE_LOADER
default directory data_dir
access parameters
(
    records delimited by newline
    badfile 'n_et.bad'
    logfile 'n_et.log'
    fields terminated by '|'
    missing field values are null
)
location (
'nation.tbl'))
reject limit unlimited;
}
*sql
{
connect tpch/tpch;
drop table r_et;
create table r_et(
    r_regionkey    number ,
    r_name          char(25) ,
    r_comment       varchar(152)
)
organization external (
type ORACLE_LOADER
default directory data_dir
access parameters
(

```

```

(
    records delimited by newline
    badfile 'r_et.bad'
    logfile 'r_et.log'
    fields terminated by '|'
    missing field values are null
)
location (
    'region.tbl')
reject limit unlimited;
}
*sql
{
connect tpch/tpch;
alter table l_et parallel;
alter table o_et parallel;
alter table ps_et parallel;
alter table p_et parallel;
alter table c_et parallel;
alter table s_et parallel;
}
# altering tpch's default and temporary tablespace
*sql
{
alter user tpch default tablespace ts_default;
alter user tpch temporary tablespace ts_temp;
}
*sql
{
connect tpch/tpch
@?/rdbms/admin/utlxplan.sql;
}
*wait
*sql
{
set timing on
set echo on
!date
connect tpch/tpch;
connect tpch/tpch;
rem drop table lineitem;
create table lineitem(
    l_shipdate      ,
    l_orderkey     NOT NULL,
    l_discount      NOT NULL,
    l_extendedprice NOT NULL,
    l_suppkey       NOT NULL,
    l_quantity      NOT NULL,
    l_returnflag    ,
    l_partkey       NOT NULL,
    l_linestatus    ,
    l_tax           NOT NULL,
    l_commitdate   ,
    l_receiptdate  ,
    l_shipmode      ,
    l_linenumber    NOT NULL,
    l_shipinstruct  ,
    l_comment       )
)
pctfree 1
pctused 99
initrans 10
storage (initial 835m next 835m freelist groups 4 freelists 99)
parallel
nologging
partition by range (l_shipdate)
subpartition by hash(l_partkey)
subpartitions 16
(
    partition item1 values less than (to_date('1992-01-01','YYYY-MM-DD'))
    store in (ts_l1,ts_l2,ts_l3,ts_l4)
    ,
    partition item2 values less than (to_date('1992-02-01','YYYY-MM-DD'))
    store in (ts_l5,ts_l6,ts_l7,ts_l8)
    ,
    partition item3 values less than (to_date('1992-03-01','YYYY-MM-DD'))
    store in (ts_l9,ts_l10,ts_l11,ts_l12)
    ,
    partition item4 values less than (to_date('1992-04-01','YYYY-MM-DD'))
    store in (ts_l13,ts_l14,ts_l15,ts_l16)
    ,
    partition item5 values less than (to_date('1992-05-01','YYYY-MM-DD'))
    store in (ts_l17,ts_l18,ts_l19,ts_l20)
    ,
    partition item6 values less than (to_date('1992-06-01','YYYY-MM-DD'))
    store in (ts_l21,ts_l22,ts_l23,ts_l24)
    ,
    partition item7 values less than (to_date('1992-07-01','YYYY-MM-DD'))
    store in (ts_l25,ts_l26,ts_l27,ts_l28)
    ,
    partition item8 values less than (to_date('1992-08-01','YYYY-MM-DD'))
    store in (ts_l29,ts_l30,ts_l31,ts_l32)
    ,
    partition item9 values less than (to_date('1992-09-01','YYYY-MM-DD'))
    store in (ts_l33,ts_l34,ts_l35,ts_l36)
    ,
    partition item10 values less than (to_date('1992-10-01','YYYY-MM-DD'))
    store in (ts_l37,ts_l38,ts_l39,ts_l40)
    ,
    partition item11 values less than (to_date('1992-11-01','YYYY-MM-DD'))
    store in (ts_l41,ts_l42,ts_l43,ts_l44)
    ,
    partition item12 values less than (to_date('1992-12-01','YYYY-MM-DD'))
    store in (ts_l45,ts_l46,ts_l47,ts_l48)
    ,
    partition item13 values less than (to_date('1993-01-01','YYYY-MM-DD'))
    store in (ts_l49,ts_l50,ts_l51,ts_l52)
    ,
    partition item14 values less than (to_date('1993-02-01','YYYY-MM-DD'))
    store in (ts_l53,ts_l54,ts_l55,ts_l56)
    ,
    partition item15 values less than (to_date('1993-03-01','YYYY-MM-DD'))
    store in (ts_l57,ts_l58,ts_l59,ts_l60)
    ,
    partition item16 values less than (to_date('1993-04-01','YYYY-MM-DD'))
    store in (ts_l61,ts_l62,ts_l63,ts_l64)
    ,
    partition item17 values less than (to_date('1993-05-01','YYYY-MM-DD'))
    store in (ts_l65,ts_l66,ts_l67,ts_l68)
    ,
    partition item18 values less than (to_date('1993-06-01','YYYY-MM-DD'))
)

```

```

store in (ts_l69,ts_l70,ts_l71,ts_l72)
,
partition item19 values less than (to_date('1993-07-01','YYYY-MM-DD'))
store in (ts_l73,ts_l74,ts_l75,ts_l76)
,
partition item20 values less than (to_date('1993-08-01','YYYY-MM-DD'))
store in (ts_l77,ts_l78,ts_l79,ts_l80)
,
partition item21 values less than (to_date('1993-09-01','YYYY-MM-DD'))
store in (ts_l81,ts_l82,ts_l83,ts_l84)
,
partition item22 values less than (to_date('1993-10-01','YYYY-MM-DD'))
store in (ts_l85,ts_l86,ts_l87,ts_l88)
,
partition item23 values less than (to_date('1993-11-01','YYYY-MM-DD'))
store in (ts_l89,ts_l90,ts_l91,ts_l92)
,
partition item24 values less than (to_date('1993-12-01','YYYY-MM-DD'))
store in (ts_l93,ts_l94,ts_l95,ts_l96)
,
partition item25 values less than (to_date('1994-01-01','YYYY-MM-DD'))
store in (ts_l97,ts_l98,ts_l99,ts_l100)
,
partition item26 values less than (to_date('1994-02-01','YYYY-MM-DD'))
store in (ts_l101,ts_l102,ts_l103,ts_l104)
,
partition item27 values less than (to_date('1994-03-01','YYYY-MM-DD'))
store in (ts_l105,ts_l106,ts_l107,ts_l108)
,
partition item28 values less than (to_date('1994-04-01','YYYY-MM-DD'))
store in (ts_l109,ts_l110,ts_l111,ts_l112)
,
partition item29 values less than (to_date('1994-05-01','YYYY-MM-DD'))
store in (ts_l113,ts_l114,ts_l115,ts_l116)
,
partition item30 values less than (to_date('1994-06-01','YYYY-MM-DD'))
store in (ts_l117,ts_l118,ts_l119,ts_l120)
,
partition item31 values less than (to_date('1994-07-01','YYYY-MM-DD'))
store in (ts_l121,ts_l122,ts_l123,ts_l124)
,
partition item32 values less than (to_date('1994-08-01','YYYY-MM-DD'))
store in (ts_l125,ts_l126,ts_l127,ts_l128)
,
partition item33 values less than (to_date('1994-09-01','YYYY-MM-DD'))
store in (ts_l129,ts_l130,ts_l131,ts_l132)
,
partition item34 values less than (to_date('1994-10-01','YYYY-MM-DD'))
store in (ts_l133,ts_l134,ts_l135,ts_l136)
,
partition item35 values less than (to_date('1994-11-01','YYYY-MM-DD'))
store in (ts_l137,ts_l138,ts_l139,ts_l140)
,

```

```

partition item36 values less than (to_date('1994-12-01','YYYY-MM-DD'))
store in (ts_l141,ts_l142,ts_l143,ts_l144)
,
partition item37 values less than (to_date('1995-01-01','YYYY-MM-DD'))
store in (ts_l145,ts_l146,ts_l147,ts_l148)
,
partition item38 values less than (to_date('1995-02-01','YYYY-MM-DD'))
store in (ts_l149,ts_l150,ts_l151,ts_l152)
,
partition item39 values less than (to_date('1995-03-01','YYYY-MM-DD'))
store in (ts_l153,ts_l154,ts_l155,ts_l156)
,
partition item40 values less than (to_date('1995-04-01','YYYY-MM-DD'))
store in (ts_l157,ts_l158,ts_l159,ts_l160)
,
partition item41 values less than (to_date('1995-05-01','YYYY-MM-DD'))
store in (ts_l161,ts_l162,ts_l163,ts_l164)
,
partition item42 values less than (to_date('1995-06-01','YYYY-MM-DD'))
store in (ts_l165,ts_l166,ts_l167,ts_l168)
,
partition item43 values less than (to_date('1995-07-01','YYYY-MM-DD'))
store in (ts_l169,ts_l170,ts_l171,ts_l172)
,
partition item44 values less than (to_date('1995-08-01','YYYY-MM-DD'))
store in (ts_l173,ts_l174,ts_l175,ts_l176)
,
partition item45 values less than (to_date('1995-09-01','YYYY-MM-DD'))
store in (ts_l177,ts_l178,ts_l179,ts_l180)
,
partition item46 values less than (to_date('1995-10-01','YYYY-MM-DD'))
store in (ts_l181,ts_l182,ts_l183,ts_l184)
,
partition item47 values less than (to_date('1995-11-01','YYYY-MM-DD'))
store in (ts_l185,ts_l186,ts_l187,ts_l188)
,
partition item48 values less than (to_date('1995-12-01','YYYY-MM-DD'))
store in (ts_l189,ts_l190,ts_l191,ts_l192)
,
partition item49 values less than (to_date('1996-01-01','YYYY-MM-DD'))
store in (ts_l193,ts_l194,ts_l195,ts_l196)
,
partition item50 values less than (to_date('1996-02-01','YYYY-MM-DD'))
store in (ts_l197,ts_l198,ts_l199,ts_l200)
,
partition item51 values less than (to_date('1996-03-01','YYYY-MM-DD'))
store in (ts_l201,ts_l202,ts_l203,ts_l204)
,
partition item52 values less than (to_date('1996-04-01','YYYY-MM-DD'))
store in (ts_l205,ts_l206,ts_l207,ts_l208)
,
partition item53 values less than (to_date('1996-05-01','YYYY-MM-DD'))

```

```

store in (ts_l209,ts_l210,ts_l211,ts_l212)
,
partition item54 values less than (to_date('1996-06-01','YYYY-MM-DD'))
store in (ts_l213,ts_l214,ts_l215,ts_l216)
,
partition item55 values less than (to_date('1996-07-01','YYYY-MM-DD'))
store in (ts_l217,ts_l218,ts_l219,ts_l220)
,
partition item56 values less than (to_date('1996-08-01','YYYY-MM-DD'))
store in (ts_l221,ts_l222,ts_l223,ts_l224)
,
partition item57 values less than (to_date('1996-09-01','YYYY-MM-DD'))
store in (ts_l225,ts_l226,ts_l227,ts_l228)
,
partition item58 values less than (to_date('1996-10-01','YYYY-MM-DD'))
store in (ts_l229,ts_l230,ts_l231,ts_l232)
,
partition item59 values less than (to_date('1996-11-01','YYYY-MM-DD'))
store in (ts_l233,ts_l234,ts_l235,ts_l236)
,
partition item60 values less than (to_date('1996-12-01','YYYY-MM-DD'))
store in (ts_l237,ts_l238,ts_l239,ts_l240)
,
partition item61 values less than (to_date('1997-01-01','YYYY-MM-DD'))
store in (ts_l241,ts_l242,ts_l243,ts_l244)
,
partition item62 values less than (to_date('1997-02-01','YYYY-MM-DD'))
store in (ts_l245,ts_l246,ts_l247,ts_l248)
,
partition item63 values less than (to_date('1997-03-01','YYYY-MM-DD'))
store in (ts_l249,ts_l250,ts_l251,ts_l252)
,
partition item64 values less than (to_date('1997-04-01','YYYY-MM-DD'))
store in (ts_l253,ts_l254,ts_l255,ts_l256)
,
partition item65 values less than (to_date('1997-05-01','YYYY-MM-DD'))
store in (ts_l257,ts_l258,ts_l259,ts_l260)
,
partition item66 values less than (to_date('1997-06-01','YYYY-MM-DD'))
store in (ts_l261,ts_l262,ts_l263,ts_l264)
,
partition item67 values less than (to_date('1997-07-01','YYYY-MM-DD'))
store in (ts_l265,ts_l266,ts_l267,ts_l268)
,
partition item68 values less than (to_date('1997-08-01','YYYY-MM-DD'))
store in (ts_l269,ts_l270,ts_l271,ts_l272)
,
partition item69 values less than (to_date('1997-09-01','YYYY-MM-DD'))
store in (ts_l273,ts_l274,ts_l275,ts_l276)
,
partition item70 values less than (to_date('1997-10-01','YYYY-MM-DD'))
store in (ts_l277,ts_l278,ts_l279,ts_l280)
,
partition item71 values less than (to_date('1997-11-01','YYYY-MM-DD'))
store in (ts_l281,ts_l282,ts_l283,ts_l284)
,
partition item72 values less than (to_date('1997-12-01','YYYY-MM-DD'))
store in (ts_l285,ts_l286,ts_l287,ts_l288)
,
partition item73 values less than (to_date('1998-01-01','YYYY-MM-DD'))
store in (ts_l289,ts_l290,ts_l291,ts_l292)
,
partition item74 values less than (to_date('1998-02-01','YYYY-MM-DD'))
store in (ts_l293,ts_l294,ts_l295,ts_l296)
,
partition item75 values less than (to_date('1998-03-01','YYYY-MM-DD'))
store in (ts_l297,ts_l298,ts_l299,ts_l300)
,
partition item76 values less than (to_date('1998-04-01','YYYY-MM-DD'))
store in (ts_l301,ts_l302,ts_l303,ts_l304)
,
partition item77 values less than (to_date('1998-05-01','YYYY-MM-DD'))
store in (ts_l305,ts_l306,ts_l307,ts_l308)
,
partition item78 values less than (to_date('1998-06-01','YYYY-MM-DD'))
store in (ts_l309,ts_l310,ts_l311,ts_l312)
,
partition item79 values less than (to_date('1998-07-01','YYYY-MM-DD'))
store in (ts_l313,ts_l314,ts_l315,ts_l316)
,
partition item80 values less than (to_date('1998-08-01','YYYY-MM-DD'))
store in (ts_l317,ts_l318,ts_l319,ts_l320)
,
partition item81 values less than (to_date('1998-09-01','YYYY-MM-DD'))
store in (ts_l321,ts_l322,ts_l323,ts_l324)
,
partition item82 values less than (to_date('1998-10-01','YYYY-MM-DD'))
store in (ts_l325,ts_l326,ts_l327,ts_l328)
,
partition item83 values less than (to_date('1998-11-01','YYYY-MM-DD'))
store in (ts_l329,ts_l330,ts_l331,ts_l332)
,
partition item84 values less than (MAXVALUE)
store in (ts_l333,ts_l334,ts_l335,ts_l336) )
as select
    l_shipdate      ,
    l_orderkey      ,
    l_discount       ,
    l_extendedprice  ,
    l_suppkey        ,
    l_quantity       ,
    l_returnflag     ,
    l_partkey        ,
    l_linenstatus   ,
    l_tax            ,
    l_commitdate     ,
    l_receiptdate    ,
    l_shipmode       ,
    l_linenumber     ,
    l_shipinstruct   ,

```

```

l_comment
from l_et;
!date
}
*wait
*sql
{
connect tpch/tpch;
set timing on
set echo on
!date

rem drop table orders;
create table orders(
    o_orderdate      ,
    o_orderkey       NOT NULL,
    o_custkey        NOT NULL,
    o_orderpriority  ,
    o_shipppriority  ,
    o_clerk          ,
    o_orderstatus    ,
    o_totalprice     ,
    o_comment         )
)
pctfree 1
pctused 99
initrans 10
storage (initial 410m next 410m freelist groups 4 freelists 99)
parallel
nologging
partition by range (o_orderdate)
subpartition by hash(o_custkey)
subpartitions 16
(
partition ord1 values less than (to_date('1992-01-01','YYYY-MM-DD'))
store in (ts_o1,ts_o2,ts_o3,ts_o4)
,
partition ord2 values less than (to_date('1992-02-01','YYYY-MM-DD'))
store in (ts_o5,ts_o6,ts_o7,ts_o8)
,
partition ord3 values less than (to_date('1992-03-01','YYYY-MM-DD'))
store in (ts_o9,ts_o10,ts_o11,ts_o12)
,
partition ord4 values less than (to_date('1992-04-01','YYYY-MM-DD'))
store in (ts_o13,ts_o14,ts_o15,ts_o16)
,
partition ord5 values less than (to_date('1992-05-01','YYYY-MM-DD'))
store in (ts_o17,ts_o18,ts_o19,ts_o20)
,
partition ord6 values less than (to_date('1992-06-01','YYYY-MM-DD'))
store in (ts_o21,ts_o22,ts_o23,ts_o24)
,
partition ord7 values less than (to_date('1992-07-01','YYYY-MM-DD'))
store in (ts_o25,ts_o26,ts_o27,ts_o28)
,
partition ord8 values less than (to_date('1992-08-01','YYYY-MM-DD'))
store in (ts_o29,ts_o30,ts_o31,ts_o32)
,
partition ord9 values less than (to_date('1992-09-01','YYYY-MM-DD'))
store in (ts_o33,ts_o34,ts_o35,ts_o36)
,
partition ord10 values less than (to_date('1992-10-01','YYYY-MM-DD'))
store in (ts_o37,ts_o38,ts_o39,ts_o40)
,
partition ord11 values less than (to_date('1992-11-01','YYYY-MM-DD'))
store in (ts_o41,ts_o42,ts_o43,ts_o44)
,
partition ord12 values less than (to_date('1992-12-01','YYYY-MM-DD'))
store in (ts_o45,ts_o46,ts_o47,ts_o48)
,
partition ord13 values less than (to_date('1993-01-01','YYYY-MM-DD'))
store in (ts_o49,ts_o50,ts_o51,ts_o52)
,
partition ord14 values less than (to_date('1993-02-01','YYYY-MM-DD'))
store in (ts_o53,ts_o54,ts_o55,ts_o56)
,
partition ord15 values less than (to_date('1993-03-01','YYYY-MM-DD'))
store in (ts_o57,ts_o58,ts_o59,ts_o60)
,
partition ord16 values less than (to_date('1993-04-01','YYYY-MM-DD'))
store in (ts_o61,ts_o62,ts_o63,ts_o64)
,
partition ord17 values less than (to_date('1993-05-01','YYYY-MM-DD'))
store in (ts_o65,ts_o66,ts_o67,ts_o68)
,
partition ord18 values less than (to_date('1993-06-01','YYYY-MM-DD'))
store in (ts_o69,ts_o70,ts_o71,ts_o72)
,
partition ord19 values less than (to_date('1993-07-01','YYYY-MM-DD'))
store in (ts_o73,ts_o74,ts_o75,ts_o76)
,
partition ord20 values less than (to_date('1993-08-01','YYYY-MM-DD'))
store in (ts_o77,ts_o78,ts_o79,ts_o80)
,
partition ord21 values less than (to_date('1993-09-01','YYYY-MM-DD'))
store in (ts_o81,ts_o82,ts_o83,ts_o84)
,
partition ord22 values less than (to_date('1993-10-01','YYYY-MM-DD'))
store in (ts_o85,ts_o86,ts_o87,ts_o88)
,
partition ord23 values less than (to_date('1993-11-01','YYYY-MM-DD'))
store in (ts_o89,ts_o90,ts_o91,ts_o92)
,
partition ord24 values less than (to_date('1993-12-01','YYYY-MM-DD'))
store in (ts_o93,ts_o94,ts_o95,ts_o96)
,
partition ord25 values less than (to_date('1994-01-01','YYYY-MM-DD'))
store in (ts_o97,ts_o98,ts_o99,ts_o100)
,
partition ord26 values less than (to_date('1994-02-01','YYYY-MM-DD'))
store in (ts_o101,ts_o102,ts_o103,ts_o104)
,
partition ord27 values less than (to_date('1994-03-01','YYYY-MM-DD'))

```

```

store in (ts_o105,ts_o106,ts_o107,ts_o108)
,
partition ord28 values less than (to_date('1994-04-01','YYYY-MM-DD'))
store in (ts_o109,ts_o110,ts_o111,ts_o112)
,
partition ord29 values less than (to_date('1994-05-01','YYYY-MM-DD'))
store in (ts_o113,ts_o114,ts_o115,ts_o116)
,
partition ord30 values less than (to_date('1994-06-01','YYYY-MM-DD'))
store in (ts_o117,ts_o118,ts_o119,ts_o120)
,
partition ord31 values less than (to_date('1994-07-01','YYYY-MM-DD'))
store in (ts_o121,ts_o122,ts_o123,ts_o124)
,
partition ord32 values less than (to_date('1994-08-01','YYYY-MM-DD'))
store in (ts_o125,ts_o126,ts_o127,ts_o128)
,
partition ord33 values less than (to_date('1994-09-01','YYYY-MM-DD'))
store in (ts_o129,ts_o130,ts_o131,ts_o132)
,
partition ord34 values less than (to_date('1994-10-01','YYYY-MM-DD'))
store in (ts_o133,ts_o134,ts_o135,ts_o136)
,
partition ord35 values less than (to_date('1994-11-01','YYYY-MM-DD'))
store in (ts_o137,ts_o138,ts_o139,ts_o140)
,
partition ord36 values less than (to_date('1994-12-01','YYYY-MM-DD'))
store in (ts_o141,ts_o142,ts_o143,ts_o144)
,
partition ord37 values less than (to_date('1995-01-01','YYYY-MM-DD'))
store in (ts_o145,ts_o146,ts_o147,ts_o148)
,
partition ord38 values less than (to_date('1995-02-01','YYYY-MM-DD'))
store in (ts_o149,ts_o150,ts_o151,ts_o152)
,
partition ord39 values less than (to_date('1995-03-01','YYYY-MM-DD'))
store in (ts_o153,ts_o154,ts_o155,ts_o156)
,
partition ord40 values less than (to_date('1995-04-01','YYYY-MM-DD'))
store in (ts_o157,ts_o158,ts_o159,ts_o160)
,
partition ord41 values less than (to_date('1995-05-01','YYYY-MM-DD'))
store in (ts_o161,ts_o162,ts_o163,ts_o164)
,
partition ord42 values less than (to_date('1995-06-01','YYYY-MM-DD'))
store in (ts_o165,ts_o166,ts_o167,ts_o168)
,
partition ord43 values less than (to_date('1995-07-01','YYYY-MM-DD'))
store in (ts_o169,ts_o170,ts_o171,ts_o172)
,
partition ord44 values less than (to_date('1995-08-01','YYYY-MM-DD'))
store in (ts_o173,ts_o174,ts_o175,ts_o176)
,
partition ord45 values less than (to_date('1995-09-01','YYYY-MM-DD'))
store in (ts_o177,ts_o178,ts_o179,ts_o180)
,
partition ord46 values less than (to_date('1995-10-01','YYYY-MM-DD'))
store in (ts_o181,ts_o182,ts_o183,ts_o184)
,
partition ord47 values less than (to_date('1995-11-01','YYYY-MM-DD'))
store in (ts_o185,ts_o186,ts_o187,ts_o188)
,
partition ord48 values less than (to_date('1995-12-01','YYYY-MM-DD'))
store in (ts_o189,ts_o190,ts_o191,ts_o192)
,
partition ord49 values less than (to_date('1996-01-01','YYYY-MM-DD'))
store in (ts_o193,ts_o194,ts_o195,ts_o196)
,
partition ord50 values less than (to_date('1996-02-01','YYYY-MM-DD'))
store in (ts_o197,ts_o198,ts_o199,ts_o200)
,
partition ord51 values less than (to_date('1996-03-01','YYYY-MM-DD'))
store in (ts_o201,ts_o202,ts_o203,ts_o204)
,
partition ord52 values less than (to_date('1996-04-01','YYYY-MM-DD'))
store in (ts_o205,ts_o206,ts_o207,ts_o208)
,
partition ord53 values less than (to_date('1996-05-01','YYYY-MM-DD'))
store in (ts_o209,ts_o210,ts_o211,ts_o212)
,
partition ord54 values less than (to_date('1996-06-01','YYYY-MM-DD'))
store in (ts_o213,ts_o214,ts_o215,ts_o216)
,
partition ord55 values less than (to_date('1996-07-01','YYYY-MM-DD'))
store in (ts_o217,ts_o218,ts_o219,ts_o220)
,
partition ord56 values less than (to_date('1996-08-01','YYYY-MM-DD'))
store in (ts_o221,ts_o222,ts_o223,ts_o224)
,
partition ord57 values less than (to_date('1996-09-01','YYYY-MM-DD'))
store in (ts_o225,ts_o226,ts_o227,ts_o228)
,
partition ord58 values less than (to_date('1996-10-01','YYYY-MM-DD'))
store in (ts_o229,ts_o230,ts_o231,ts_o232)
,
partition ord59 values less than (to_date('1996-11-01','YYYY-MM-DD'))
store in (ts_o233,ts_o234,ts_o235,ts_o236)
,
partition ord60 values less than (to_date('1996-12-01','YYYY-MM-DD'))
store in (ts_o237,ts_o238,ts_o239,ts_o240)
,
partition ord61 values less than (to_date('1997-01-01','YYYY-MM-DD'))
store in (ts_o241,ts_o242,ts_o243,ts_o244)
,
partition ord62 values less than (to_date('1997-02-01','YYYY-MM-DD'))

```

```

store in (ts_o245,ts_o246,ts_o247,ts_o248)
,
partition ord63 values less than (to_date('1997-03-01','YYYY-MM-
DD'))
store in (ts_o249,ts_o250,ts_o251,ts_o252)
,
partition ord64 values less than (to_date('1997-04-01','YYYY-MM-
DD'))
store in (ts_o253,ts_o254,ts_o255,ts_o256)
,
partition ord65 values less than (to_date('1997-05-01','YYYY-MM-
DD'))
store in (ts_o257,ts_o258,ts_o259,ts_o260)
,
partition ord66 values less than (to_date('1997-06-01','YYYY-MM-
DD'))
store in (ts_o261,ts_o262,ts_o263,ts_o264)
,
partition ord67 values less than (to_date('1997-07-01','YYYY-MM-
DD'))
store in (ts_o265,ts_o266,ts_o267,ts_o268)
,
partition ord68 values less than (to_date('1997-08-01','YYYY-MM-
DD'))
store in (ts_o269,ts_o270,ts_o271,ts_o272)
,
partition ord69 values less than (to_date('1997-09-01','YYYY-MM-
DD'))
store in (ts_o273,ts_o274,ts_o275,ts_o276)
,
partition ord70 values less than (to_date('1997-10-01','YYYY-MM-
DD'))
store in (ts_o277,ts_o278,ts_o279,ts_o280)
,
partition ord71 values less than (to_date('1997-11-01','YYYY-MM-
DD'))
store in (ts_o281,ts_o282,ts_o283,ts_o284)
,
partition ord72 values less than (to_date('1997-12-01','YYYY-MM-
DD'))
store in (ts_o285,ts_o286,ts_o287,ts_o288)
,
partition ord73 values less than (to_date('1998-01-01','YYYY-MM-
DD'))
store in (ts_o289,ts_o290,ts_o291,ts_o292)
,
partition ord74 values less than (to_date('1998-02-01','YYYY-MM-
DD'))
store in (ts_o293,ts_o294,ts_o295,ts_o296)
,
partition ord75 values less than (to_date('1998-03-01','YYYY-MM-
DD'))
store in (ts_o297,ts_o298,ts_o299,ts_o300)
,
partition ord76 values less than (to_date('1998-04-01','YYYY-MM-
DD'))
store in (ts_o301,ts_o302,ts_o303,ts_o304)
,
partition ord77 values less than (to_date('1998-05-01','YYYY-MM-
DD'))
store in (ts_o305,ts_o306,ts_o307,ts_o308)
,
partition ord78 values less than (to_date('1998-06-01','YYYY-MM-
DD'))
store in (ts_o309,ts_o310,ts_o311,ts_o312)
,
partition ord79 values less than (to_date('1998-07-01','YYYY-MM-
DD'))
store in (ts_o313,ts_o314,ts_o315,ts_o316)
,
partition ord80 values less than (to_date('1998-08-01','YYYY-MM-
DD'))
store in (ts_o317,ts_o318,ts_o319,ts_o320)
,
partition ord81 values less than (to_date('1998-09-01','YYYY-MM-
DD'))
store in (ts_o321,ts_o322,ts_o323,ts_o324)
,
partition ord82 values less than (to_date('1998-10-01','YYYY-MM-
DD'))
store in (ts_o325,ts_o326,ts_o327,ts_o328)
,
partition ord83 values less than (to_date('1998-11-01','YYYY-MM-
DD'))
store in (ts_o329,ts_o330,ts_o331,ts_o332)
,
partition ord84 values less than (MAXVALUE)
store in (ts_o333,ts_o334,ts_o335,ts_o336) )
as select
    o_orderdate      ,
    o_orderkey       ,
    o_custkey        ,
    o_orderpriority  ,
    o_shipppriority  ,
    o_clerk          ,
    o_orderstatus    ,
    o_totalprice     ,
    o_comment        ,
from o_et;
!date
}
*wait
*sql
{
connect tpch/tpch
set timing on
set echo on

!date

rem drop table partsupp;
create table partsupp(
    ps_partkey      NOT NULL,
    ps_suppkey      NOT NULL,
    ps_supplycost   NOT NULL,
    ps_availqty     ,
    ps_comment      ,
constraint pk_partkey_suppkey_1 primary key(ps_partkey,
ps_suppkey)
)
organization index
partition by hash(ps_partkey)
partitions 128
storage (initial 1200m next 1200m)
parallel
nologging
pctthreshold 50
tablespace ts_pspp1
as select
    ps_partkey      ,
    ps_suppkey      ,
    ps_supplycost   ,
    ps_availqty     ,
    ps_comment      ,
from ps_et;
!date
}
*wait
*sql
{

```

```

connect tpch/tpch
set timing on
set echo on

!date
rem drop table customer;
create table customer(
    c_custkey      NOT NULL,
    c_mktsegment   ,
    c_nationkey    ,
    c_name         ,
    c_address      ,
    c_phone        ,
    c_acctbal      ,
    c_comment       )
) pctfree 0
pctused 99
parallel
nologging
storage (initial 265m next 265m)
partition by hash (c_custkey)
partitions 128
store in
(ts_small1,ts_small2,ts_small3,ts_small4,ts_small5,ts_small6,ts_ma
ll7,ts_small8,ts_small9,ts_small10,ts_small11,ts_small12,ts_small13
,ts_small14,ts_small15,ts_small16,ts_small17,ts_small18,ts_small19
,ts_small20,ts_small21,ts_small22,ts_small23,ts_small24,ts_small25
,ts_small26,ts_small27,ts_small28,ts_small29,ts_small30,ts_small31
,ts_small32)
as select
    p_partkey      ,
    p_type         ,
    p_size         ,
    p_brand        ,
    p_name         ,
    p_container    ,
    p_mfgr         ,
    p_retailprice  ,
    p_comment       from p_et;
!date
}
*wait
*sql
{
connect tpch/tpch;
set timing on
set echo on
rem drop table supplier;
create table supplier(
    s_suppkey      NOT NULL,
    s_nationkey    ,
    s_comment       ,
    s_name         ,
    s_address      ,
    s_phone        ,
    s_acctbal      )
) pctfree 0
pctused 99
parallel
nologging
storage (initial 120m next 5m)
partition by hash (s_suppkey)
partitions 128
store in
(ts_small1,ts_sm all2,ts_small3,ts_small4,ts_small5,ts_small6,ts_ma
ll7,ts_small8,ts_small9,ts_small10,ts_small11,ts_small12,ts_small13
,ts_small14,ts_small15,ts_small16,ts_small17,ts_small18,ts_small19
,ts_small20,ts_small21,ts_small22,ts_small23,ts_small24,ts_small25
,ts_small26,ts_small27,ts_small28,ts_small29,ts_small30,ts_small31
,ts_small32)
as select
    s_suppkey      ,
    s_nationkey    ,
    s_comment       ,
    s_name         ,
    s_address      ,
    s_phone        ,
    s_acctbal      from s_et;
}
*wait
*sql
{
connect tpch/tpch;
set echo on
set timing on
rem drop table nation;
create table nation(
    n_nationkey    NOT NULL,
)

```

```

n_name      ,
n_regionkey ,
n_comment   )
tablespace ts_default
as select * from n_et;

rem drop table region;
create table region(
  r_regionkey ,
  r_name      ,
  r_comment   )
tablespace ts_default
as select * from r_et;
}

*wait
*bgoff
%e-scuto

*sql
{
connect tpch/tpch
set timing on
set echo on

!date
drop table l_et;
drop table o_et;
drop table ps_et;
drop table p_et;
drop table c_et;
drop table s_et;
drop table n_et;
drop table r_et;
}
*bgoff
%e-dapop
%b-ixcre
*bgon=1
#####
# Index Creation Phase
*sql
{
connect tpch/tpch;
!date
set echo on
set timing on
rem drop index i_l_orderkey;
create index i_l_orderkey
on lineitem (l_orderkey)
global partition by hash (l_orderkey)
partitions 128
pctfree 5
intrans 10
tablespace ts_lokey
storage (freelist groups 4 freelists 99)
parallel
compute statistics
nologging;
}
*sql
{
connect tpch/tpch;
!date
set echo on
set timing on
rem drop index i_o_orderkey;
create unique index i_o_orderkey
on orders (o_orderkey)
}

global partition by hash (o_orderkey)
partitions 128
pctfree 2
intrans 10
tablespace ts_okey
storage (freelist groups 4 freelists 99 )
parallel
compute statistics
nologging;
}
*sql
{
connect tpch/tpch;
!date
set echo on
set timing on

rem drop index i_c_custkey;
create unique index i_c_custkey
on customer (c_custkey)
pctfree 2
intrans 10
tablespace ts_custkey
storage (freelists 99)
parallel
compute statistics
nologging;
}
*wait
*bgoff
%e-ixcre
%b-analyz
*bgon=1
#####
# Analyze Phase
*sql
{
connect tpch/tpch;
!date
set timing on
execute dbms_stats.gather_schema_stats('TPCH', estimate_percent
=> 1, degree => 128, granularity => 'GLOBAL');
connect / as sysdba
execute dbms_stats.gather_system_stats;
alter system switch logfile;
!date
}
*wait
*bgoff
%e-analyz

```

B.2 bumpx.pl

```

#!/usr/contrib/bin/perl
#
# $Header: bumpx.pl 13-feb-2001.14:35:03 mpoess Exp $
#
# bumpx.pl
#
# Copyright (c) Oracle Corporation 1999, 2000. All Rights
# Reserved.
#
# NAME
#   bumpx.pl - <one-line expansion of the name>
#
# DESCRIPTION

```

```

# <short description of component this file declares/defines>
#
# NOTES
# <other useful comments, qualifications, etc.>
#
# MODIFIED (MM/DD/YY)
# mpoess 02/13/01 - make global range index possible for
o_orderkey
# mpoess 01/31/00 - fix bug with undo
# mpoess 01/21/00 - fix bugs for partitioned tablespaces
# mpoess 01/20/00 - add OPS load one partition from one node
support
# mpoess 01/07/00 - add support for flatfile distribution
# mpoess 01/06/00 - add controlfile generation performance
improvement
# mpoess 12/16/99 - add partitioning support for control files
# mpoess 10/28/99 - adjust bumpx to fixed dbgen (84
partitioning)
# mpoess 08/17/99 - change column definition of base tables
# mpoess 08/13/99 - add support for reporting files
# mpoess 08/08/99 - change file attributes
# mpoess 07/12/99 - add setpath for dbgen
# mpoess 07/12/99 - disable -o option for dbgen
# mpoess 07/07/99 - fix dbgen phase
# mpoess 07/06/99 - change path to perl
# mpoess 07/02/99 - add environment variable support for conf
file
# mpoess 06/28/99 - add pathname for param.txt file
# mpoess 06/28/99 - Copy from TPCD
# mpoess 06/28/99 - Creation
# MODIFIED (MM/DD/YY)
# mpoess 11/18/98 - add undo rollback segment support for
OPS systems
# mpoess 11/18/98 - add control log etc. keywords in SQLLDR
call
# mpoess 11/06/98 - fix bug in print_as_select
# mpoess 11/05/98 - change name of BUMPC_CTR variable
# mpoess 11/04/98 - delete default startup before index creation
# mpoess 11/04/98 - adopt Barry Perkins changes to dbgen
# mpoess 11/03/98 - change as select handling
# mpoess 11/02/98 - change background process handling for
NT
# mpoess 10/26/98 - modify dapop so that multiple partitions
can be lo
# mpoess 10/23/98 - take *waits out from flat file generation
# mpoess 10/20/98 - add sdgen, dbgen and dapop description
# mpoess 10/12/98 - fix bug in constraint creation
# mpoess 10/12/98 - add support for non partitioned tables
# mpoess 10/08/98 - add -including new values- clause in view
log defin
# mpoess 09/27/98 - update links,param2html
# mpoess 09/25/98 - adding new features
# akarasik 07/29/98 -
# akarasik 07/29/98 - Checking in
# kwong 05/22/98 - add change storage for tables and indexes in
# chdop
# kwong 05/21/98 - fix load pipe
# kwong 05/21/98 - add some more default values in init.ora
# kwong 05/20/98 - add parameter nt_port
# kwong 05/19/98 - fix control file generation
# kwong 05/18/98 - run utlxplan.sql after created user
# kwong 05/18/98 - add "dbgen" phase
# kwong 05/15/98 - calculate partition values for l_orderkey
# and l_partkey
# kwong 05/13/98 - add phase "chdop" for modifying dop as
the
# end of the build
# kwong 05/13/98 - fix the order of create tablespaces and add
datafiles
# pswong 04/15/97 - fix pipeline load

```

```

@keys = keys %params;
while ($#keys >=0)
{
    $key = pop(@keys);
    if (($defpar cmp "") ==0)
    {
        print $key, "=", $params{$key}, "\n";
    }
    else
    {
        print $key, "=", $params{$key}, "\n" if ($key
=~ /$defpar/);
    }
}
exit(0);

if ($arg =~ /-a/)
{
    $infile = "$ENV{'BUMPX_DIR'}/bumpx.conf" if
!defined $infile;
    $infile = $infile;
    &readfile;
    &defaults;
    @keys = keys %params;
    while ($#keys >=0)
    {
        $key = pop(@keys);
        print $key, "=", $params{$key}, "\n";
    }
    exit(0);
}

$dorecreate = 0 if !defined $dorecreate;
$doexecute = 0 if !defined $doexecute;
if (!$dorecreate || !$doexecute)
{
    $error = "*** Error: Must specify either -c or -x or both\n";
    &usage;
}
$infile = "$ENV{'BUMPX_DIR'}/bumpx.conf" if !defined $infile;
$outfile = "$ENV{'BUMPX_DIR'}/bumpx.dat" if !defined $outfile;
if ($nt) {
    $listdir = $filedir."list";
    if (!-e $listfile) {
        system ("mkdir $listdir");
    }
}
if ($os cmp "nt") == 0
{
    ## NT Port (Use tmpfile to buffer commands and nruntpb to
    synchronize them)
    $tmpfile = "tmp.txt";
    $tmpfile = $filedir.$tmpfile;
    $runtpb = "nruntpb.exe";
}
## NT End

if ((!-e $infile) && !$doexecute && $dorecreate)
{
    $error = "*** Error: -i file, $infile, does not exist\n";
    &usage;
}
if ((!-e $outfile) && !$dorecreate)
{
    $error = "*** Error: -o file, $outfile, does not exist\n";
    &usage;
}
$phaselst = $defphases if !defined $phaselst;
@phases = split(/,/, $phaselst);

if ($dorecreate)
{
    open (OUTFILE, ">$outfile") if $dorecreate;
    &readfile;
    &defaults;
    &dorecreate;
    close (OUTFILE);
}

## NT Port (Use tmpfile to buffer commands for nruntpb)
open (TMPFILE, ">$tmpfile") if ( ($os cmp "nt") == 0) &&
$doexecute;
## NT End

&doexecute if $doexecute;

## NT Port
close(TMPFILE) if ( ($os cmp "nt") == 0) && $doexecute;
## NT End

exit(0);

sub readfile
{
    $matchon = 0;
    $contin = 0;
    $pkey = "";
    $pval = "";
    open (INFILE, "$infile");
    WLOOP:
    while ($line = <INFILE>)
    {
        $line = $line."\n" if $line !~ /\n/;
        study $line;
        if ($line =~ /^$matchon)
        {
            $matchon = 1;
            next WLOOP;
        }
        if ($line =~ /^$matchoff/)
        {
            $matchon = 0;
            next WLOOP;
        }
        if ($matchon == 1)
        {
            &dump0($line) if $dorecreate;
            next WLOOP;
        }
    }
    next WLOOP if $line =~ /\s*\#/;
    next WLOOP if $line =~ /\s*\n/;
    if ($contin)
    {
        if ($line =~ /(.*)\&|\s*\n/) # still continuing (changed \ to &)
        {
            $pval = $pval . $1 . "\n";
            $pval = $pval . $1;
            next WLOOP;
        }
        $line =~ /(.*)\s*\n/; # reached the end
        $pval = $pval . $1;
        $pval =~ s/\?/$ENV{'ORACLE_HOME'}/g;
        &key_exists($pkey);
        if ($result!=1)
        {
            print "Parameter $pkey does not
exist.\nBailing out!\n";
            exit (0);
        }
    }
}

```

```

        }
        $params{$pkey} = $pval;
    $contin = 0;
    $pkey = "";
    $pval = "";
    next WLOOP;
}
else
{
    if ($line =~ /\s*(\$+)\s*=\$*(.*)\&\s*\n/)
    {
        $pkey = $1;
        $pval = $2 . "\n";
        $pval = $2;
        $contin = 1;
        next WLOOP;
    }
    if ($line =~ /\s*(\$+)\s*=\$*\n/)
    {
        undef($params{$1});
        next WLOOP;
    }
    if ($line !~ /\s*(\$+)\s*=\$*((\$+)(\$+.*\$+))\s*\n/)
    {
        print "Bad line: $line";
        next WLOOP;
    }
    $tkey = $1;
    $tval = $2;
    $tval =~ s/^\$ENV{'ORACLE_HOME'}/g;
    if ($tval =~ /\$/) { # a $ sign at the beginning of the
contents
                                # of the parameter value results in
a environment
                                # variable lookup and substitution
        $tenv = $tval;
        $tval =~ s/\$///g;
        if ($unix) {
            $tenv =~ s/(.*)_\\(.*)\\(.*)\\\$2/g;
        }
        $tenvval = `echo $tenv`;
        $tenv =~ s/\$/g;
        chop($tenvval);
        if ($tenvval =~ /\n/) {
            print "bumpx error: Environment variable
$tval not defined!\n";
            exit(1);
        }
        $tval =~ s/$tenv/$tenvval/g;
    }

    &key_exists($tkey);
    if ($result!=1)
    {
        print "Parameter $tkey does not
exists.\nBailing out!\n";
        exit (0);
    }
    $params{$tkey} = $tval;
}
close (INFILE);
}

sub docreate
{
    print "Creation pass begun." if $verbose;
    @phases_tmp = @phases; # because I will eat the elements
    while ($phase=shift(@phases_tmp))
    {
        if ($allphases =~ /$phase/)
        {
            $nextphase = shift(@phases_tmp);
            unshift (@phases_tmp,$nextphase) if ($nextphase);
            print "\n Creating phase '$phase'" if $verbose;
            &dump0("%b-$phase\n");
            &prepmulti();
            &dump0("*bgon=$params{$phase.'_max_bg'}");
            eval (&$phase);
            &dump0("*wait");
            &dump0("*bgoff");
            &dump0("%e-$phase\n");
        }
        else
        {
            print "\n Phase '$phase' not built in...assuming a /*match
block being used";
        }
    }
    print "\nCreation pass complete.\n" if $verbose;
}

sub doexecute
{
# First, do preprocessing stuff
    print "Execution pass begun." if $verbose;
    open (INFILE, $outfile);
    WLOOP1:
    while ($line = <INFILE>)
    {
        study $line;
        next WLOOP1 if $line =~ /^|\s*#/;
        next WLOOP1 if $line =~ /^|\s*\n/;
        if ($line =~ /^%b-preproc/)
        {
            $insection = 1;
            next WLOOP1;
        }
        next WLOOP1 if ($insection != 1);
        if ($line =~ /^%e-preproc/)
        {
            $insection = 0;
            $Commands{$shortcmd} = $longcmd if defined $shortcmd;
            last WLOOP1;
        }
        if ($line =~ /%/)
        {
            $Commands{$shortcmd} = $longcmd if defined $shortcmd;
            $line =~ /(^.*\$+)\s*\$"/;
            $shortcmd = $1;
            $longcmd = "";
            next WLOOP1;
        }
        if ($line =~ /%/)
        {
            $line =~ /\(\.*\n/;
            $longcmd = $longcmd . $1;
            next WLOOP1;
        }
        print "Illegal entry in preproc stage:\n $line";
    }
    close (INFILE);
}

# Then, do all of the requested phases
$execctr = 0;
foreach $phase (@phases)
{
    $phase_cmd_num = 0;
    print "\n Executing phase '$phase'" if $verbose;
    $bg = 0;
}

```

```

open (INFILE, $outfile);
WLOOP2:
while ($line = <INFILE>)
{
    study $line;
    next WLOOP2 if $line =~ /^$#/;
    next WLOOP2 if $line =~ /^$#\n/;
    if ($line =~ /^.*ignore/)
    {
        $signon = 1;
        next WLOOP2;
    }
    if ($line =~ /^.*ignoff/)
    {
        $signon = 0;
        next WLOOP2;
    }
    next WLOOP2 if ($signon == 1);
    if ($line =~ /^%b-$phase/)
    {
        $insection = 1;
        $execcmd = "";
        next WLOOP2;
    }
    next WLOOP2 if ($insection != 1);
    if ($line =~ /^%e-$phase/)
    {
        $insection = 0;
        &execute ($execcmd);
        last WLOOP2;
    }
    if ($line =~ /^(.*)/)
    {
        &execute ($execcmd);
        if (($1 =~ /bgo/) || ($1 =~ /wait/) || ($1 =~ /ignore/))
        {
            $execcmd = $line;
            next WLOOP2;
        }
        $line =~ /(^.*\S+)\s*\n$/;
        $execcmd = $commands{$1};
        next WLOOP2;
    }
    if ($line =~ /^{(.*)}/)
    {
        $insert = "";
        $insert = $1;
        $execcmd =~ s/\{/$insert/;
        next WLOOP2;
    }
    if ($line =~ /^{(.*)$}/)
    {
        $insubsection = 1;
        $insert = "";
        $insert = $1;
        next WLOOP2;
    }
    if ($line =~ /^{(.*)\}/)
    {
        $insubsection = 0;
        $insert = $insert . $1;
## NT Port (Ignore '\n')
        if (($os cmp "nt") == 0)
        {
            $insert =~ /(.*\n)/s;
            $insert = $1;
        }
## NT End
        $execcmd =~ s/\{/$insert/;
        next WLOOP2;
    }
}
}

}
$insert = $insert . $line if ($insubsection == 1);
}
close (INFILE);
}
print "\nExecution pass complete.\n" if $verbose;
}

sub execute
{
    $cmd = shift(@_);
    if ($cmd)
    {
        return if ($cmd =~ /^.*ignore/);
        if ($cmd =~ /^bgon=(.*)/)
        {
            $bgmax = $1;
            $bg = 1;
            $bgrun = 0;
            return;
        }
        if ($cmd =~ /^bgoff/)
        {
            $bg = 0;
            return;
        }
        if ($cmd =~ /^time=(.*)/) ##NT only
        {
            print $1 . "\n";
            print localtime(time) . "\n";
            return;
        }
        if ($cmd =~ /copy (.*)/) ## NT only
        {
            system($cmd);
## Quit if failed
            if ($?) {
                print "system copy command
failed:\n$cmd\nreason: $? ($!)\n";
                exit(1);
            }
            return;
        }
        if ($cmd =~ /del (.*)/) ## NT only
        {
            system($cmd);
## Quit if failed
            if ($?) {
                print "system del command
failed:\n$cmd\nreason: $? ($!)\n";
                exit(1);
            }
            return;
        }
        if ($cmd =~ /^wait/) ## This deals with main
differences between NT and UNIX
        {
            if (($os cmp "unix") == 0)
            {
                while ($fpid = shift(@wpids))
                {
                    waitpid($fpid, 0);
                }
            }
            else
            {
## NT Port (Start background tasks if any. nruntb
will wait until all tasks are done)
                if ($bgrun >= 1)

```

```

        {
            close(TMPFILE);
            system("cat $tmpfile >>
system("vi $tmpfile") if $debug;
system("$nruntpb -p < $tmpfile") if
!$debug;
            if ($?)
            {
                print "system command
failed:\n$nruntpb < $tmpfile\n";
                print "reason: $? ($!)\n";
                print "Please check the contents in
the input file.\n";
                exit(-1);
            }
            open(TMPFILE, ">$tmpfile");
        }
        $bgrun = 0;
        return;
    }

    if ($cmd =~ /(s|g)etenv/)
    {
        @lines = split(/\n/, $cmd);
        $cmd = "";
        foreach $line (@lines)
        {
            while (1)
            {
                last if ($line !~ /getenv/);
                $line =~ /(.*)(\^)(getenv\(([^\(\)]*)\))(.*/);
                $line = $1 . $ENV{$2} . $3;
            }
            if ($line =~ /jo/o/) #we do not want to use this for now
            {
                $line =~ /setenv\($+\)\$+(\$+)/;
                $ENV{$1} = $2;
            }
            else
            {
                $cmd = $cmd . $line. "\n";
            }
        }
        return if ($cmd !~ /\$/); # return if nothing left to execute
    }

    $execctr++;
    $ENV{'BUMPIX_CTR'} = $$.'-'.$execctr;

    if (($os cmp "unix") == 0)
    {
        if ($bg == 1)
        {
            print "." if $verbose;
            $fpid = fork;
            if ($fpid == 0)
            {
                exec ($cmd);
                print "exec\b command
failed:\n$cmd\nreason: $!\n";
                exit(-1);
            }
            unshift (@wpids, $fpid);
            $bgrun = $bgrun + 1;
            &execute ("*wait") if (($bgrun >= $bgmax)
&& ($bgmax >= 0));
        }
        else
    }

    {
        system ($cmd);
        print "system\b command
failed:\n$cmd\nreason: $? ($!)\n" if $?;
    }
    else ## NT support
    {
        ## NT Port (Submit background tasks if there are bgmax of
them, otherwise write to tmpfile)
        if ($bg == 1)
        {
            print "." if $verbose;
            if ($bgrun < $bgmax)
            {
                $cmd =~
s/phase\#.lst/$listdir$phase\_$.phase_cmd_num.lst/;
                ++$phase_cmd_num;
                print TMPFILE $cmd;
                $bgrun = $bgrun + 1;
            }
            else
            {
                close(TMPFILE);
                system("cat $tmpfile >>
$listdir$phase.lst");
                system("$nruntpb -p < $tmpfile");
                if ($?) {
                    print "system command
failed:\n$nruntpb < $tmpfile\nreason: $? ($!)\n";
                    print "Please check the contents in
the input file.\n";
                    exit(-1);
                }
                open(TMPFILE, ">$tmpfile");
                $cmd =~
s/phase\#.lst/$listdir$phase\_$.phase_cmd_num.lst/;
                ++$phase_cmd_num;
                print TMPFILE $cmd;
                $bgrun = 1;
            }
            else
            {
                $cmd =~
s/phase\#.lst/$listdir$phase\_$.phase_cmd_num.lst/;
                ++$phase_cmd_num;
                print TMPFILE $cmd;
                close(TMPFILE);
                system("cat $tmpfile >> $listdir$phase.lst");
                system ("sh $tmpfile");
                if ($?) {
                    print "system\b command failed:\n$!
$tmpfile\nreason: $? ($!)\n";
                    print "Please check the contents in the shell
script.\n";
                    exit(-1);
                }
                open(TMPFILE, ">$tmpfile");
            }
        } ## NT support End
    }
}

sub usage
{
    print "Usage:\n";
    print " $0 [-c] [-x] [-i infile] [-o outfile] [-p phaselst] [-t type]\n";
    print " -c : create intermediary file (needed for execution)\n";
    print " -x : execute intermediary file\n";
}

```

```

print " -i : configuration file to be used\n";
print "     defaults to bumpx.conf in \$BUMPX_DIR or
\$CWD\n";
print " -o : intermediary file to be created and/or used\n";
print "     defaults to bumpx.dat in \$BUMPX_DIR or
\$CWD\n";
print " -p : list of phases to create/execute\n";
print "     phaselst is a comma separated list of phases in
order\n";
print "     possible phases are:\n";
print "         sgen = seed file generation\n";
print "         dbgen = data flat file generation\n";
print "         plcre = NT raw partition and links creation\n";
print "         dbcre = database creation\n";
print "         shutd = shutdown database (on all instances)\n";
print "         start = startup database (on all instances)\n";
print "         scre = schema creation\n";
print "         sctso = schema creation (tablespaces only)\n";
print "         scuto = schema creation (user and tables only)\n";
print "         scovo = schema creation (views only)\n";
print "         dapop = data population\n";
print "         ixcre = index creation (including constraints)\n";
print "         anlyz = analyze objects\n";
print "         chob = change parameters of objects\n";
print "         expln = create explain plans\n";
print "         query = run and time queries\n";
print "         defaults to \$defphases\n";
print " -t : type of benchmark\n";
print "     enables benchmark-specific defaults\n";
print "     current possiblities are: \$allbmtypes\n";
print "     defaults to tpcd\n";
print " -s : run silent (no parameter checking is done)\n";
print "\n";
print "Examples:\n";
print "$0 -c -o file.out\n";
print " This will create an intermediary file named file.out for the
default\n";
print " phases using bumpx.conf which can be executed in the
future.\n";
print "$0 -x -p dapop\n";
print " Executes data population phase of intermediary file
bumpx.dat\n";
print "$0 -cx -p dbcre,dapop\n";
print " This will create an intermediary file, bumpx.dat, using
configuration\n";
print " file, bumpx.conf, for both the database creation phase and
the data\n";
print " population phase, and then execute that file.\n";
print "\n";
print "$error\n";
exit(-1);
}

#####
# All Known Phases
#####
#####

sub dbcre
{
&dump0("#####
#####");
&dump0("# Database Creation Phase");
&time0("Begin database creation");

# Shut down anything that may have been running
&shutdb();

# Create database (system tablespace/datafile, redo logs, rollback
segments)
@sys_files = split (//, $params{'ts_sys_datafiles'});
$sys_file = shift(@sys_files);
@log_files = split (//, $params{'ts_log_datafiles'});
&dump0("# creating database and initial rollback segment");
$cmd := "startup pfile= $params{'startupfile_dbcre'} nomount\n";
$cmd := "create database\n";
$cmd := " controlfile reuse\n" if !($params{'db_ctreuse'}) =~
/false/;
for ($i = 0; $i < $params{'ts_log_files_pt'}; $i++)
{
    ($i == 0) ? ($addname = "logfile") : ($addname = "      ");
    (($i+1) == $params{'ts_log_files_pt'}) ? ($addcomma = "") :
($addcomma = ",");
    $log_file = shift(@log_files);
    if ($os cmp "unix") == 0
    {
        $cmd .= " $addname $params{'ts_log_area'}$log_file"
size $params{'ts_log_size'}
$params{'ts_log_options'}$addcomma\n";
    }
    else
    {
        $cmd .= " $addname (
$params{'ts_log_area'}$log_file) size $params{'ts_log_size'}
$params{'ts_log_options'}$addcomma\n";
    }
}
$cmd .= " maxlogfiles $params{'db_maxlogfiles'}\n" if defined
$params{'db_maxlogfiles'};
$cmd .= " maxlogmembers $params{'db_maxlogmembers'}\n" if
defined $params{'db_maxlogmembers'};
$cmd .= " maxloghistory $params{'db_maxloghistory'}\n" if
defined $params{'db_maxloghistory'};
$cmd .= " datafile '$params{'ts_sys_area'}$sys_file' size
$params{'ts_sys_size'} $params{'ts_sys_options'}\n";
$cmd .= " maxdatafiles $params{'db_maxdat afiles'}\n" if defined
$params{'db_maxdatafiles'};
$cmd .= " maxinstances $params{'db_maxinstances'}\n" if
defined $params{'db_maxinstances'};
$cmd .= " maxarchlogs $params{'db_maxarchlogs'}\n" if defined
$params{'db_maxarchlogs'};
$cmd .= " archivelog\n" if defined $params{'db_archivelog'};
$cmd .= " character set $params{'db_charset'}\n" if defined
$params{'db_charset'};
$cmd .= "\n";
$cmd .= "\n";
$cmd .= "create public rollback segment t_rs1 ";
$cmd .= " storage $params{'ts_undo_rs_storage'}" if defined
$params{'ts_undo_rs_storage'};
$cmd .= "\n";
$cmd .= "\n";
$cmd .= "alter rollback segment t_rs1 online;\n";
$cmd .= "\n";
$cmd .= "shutdown\n"; #^sd
&dump1("*sql");
&dump0("*wait");

# This startup is in its own session because of some weird bug I've
been
# seeing on the SP2; otherwise, it's in the previous session
#^su
# $cmd = "";
# $cmd = "startup pfile=$iofname[1];\n";
# &dump1("*sql");
}

```

```

# &dump0("*wait");
startdb("dbcrc");
&dump0("*wait");
@ops_nodes = split(./,$params{'ops_nodes'});
if (defined $params{'ops_nodes'}) {
    foreach $ops_node (@ops_nodes)
    {
        if ($ops_node =~ /undo/)
        {
            $ts_undo = 'undo';
        }
        else {
            $ts_undo = 'undo_'.$ops_node;
        }
        if ($params{'skip_ts'} !~ /$ts_undo/)
        {
            &add_ts_rollback ($ts_undo);
        }
    }
} else {
    $ts_undo = 'undo';
}

# currently set up for the foreground - maybe should be changed
&dump0("# creating extra logfile threads");
for ($i = 1; $i < $params{'ts_log_#threads'}; $i++)
{
    $thrno = $i + 1;
    $cmd .= "alter database add logfile thread $thrno\n";
    for ($j = 0; $j < $params{'ts_log_#files_pt'}; $j++)
    {
        (($j+1) == $params{'ts_log_#files_pt'}) ? ($addcomma = ";") :
        ($addcomma = ",");
        $log_file = shift(@log_files);
        $cmd .= " '$params{'ts_log_area'}$log_file' size
$params{'ts_log_size'} $params{'ts_log_options'}$addcomma\n";
    }
    $cmd .= "alter database enable public thread $thrno;\n";
}
&dump1("*sql");
&dump0("*wait");

# Build data dictionary
&dump0("# building data dictionary");
$cmd .= "set termout off\n";
$cmd .= "set echo off\n";
$cmd .= '@'. "$params{'dd_sql_area}' . "catalog.sql;\n";
$cmd .= '@'. "$params{'dd_sql_area}' . "catparr.sql;\n";
$cmd .= '@'. "$params{'dd_sql_area}' . "catproc.sql;\n";
$cmd .= "connect system/manager\n";
$cmd .= '@'. "$params{'dd_sql_area}' . "utlxplan.sql;\n";
$cmd .= '@'. "$params{'dd_sqlplus_area}' . "pupbld.sql;\n";
&dump1("*sql");
&dump0("*wait");
&time0("Done database creation");

# prepare for multi-user
#^>sd
$cmd .= "shutdown;\n";
&dump1("*sql");
&dump0("*wait");
&startdb("dbcrc");
} # end dbcrc

sub shutd
{
    &dump0("#####
#####");
}

sub start
{
    &dump0("# Shutdown Database - All Instances");
    &shutdb();
    &time0("Done database shutdown - all instances");
}

sub sdgen
{
    &dump0("#####
#####");
    &dump0("# Data (Seed File) Generation Phase");
    &time0("Begin creating seed files");
    @load_tablelist = split(./, $params{'load_tables'});
    foreach $table (@load_tablelist)
    {
        $bgopt = "";
        $dbgprc = $params{'load_dbgen_.$table._option_C'};
        if (! $seen{$dbgprc}++) {
            $dbgopt = $verbose ? "-v" : "";
            $dbgopt .= "-O s -s ";
        }
        $params{'scale_factor'};
        $cmd .= $dbgopt . " -C ". $dbgprc;
        $cmd .= sprintf(" 2>> dbgen_seed_%d.log",
$dbgprc) if $log_output;
        $cmd .= "\n";
        &dump1("*dbgen");
        &time0("Done creating seed files for degree
$dbgprc");
    }
    &dump0("*wait");
    &time0("Done creating seed files");
    &dump0("*wait");
} # end of sdgen

sub dbgen
{
    &dump0("#####
#####");
    &dump0("# Data (Flat File) Generation Phase");
    &time0("Begin creating flat files");

# change DSS_PATH
$cmd = "setenv DSS_PATH $params{'load_flatfile_area'}";
&dump1("*sh");

$cur_inst = 1 if $multi; # for possible locality on SP2
($params{'load_type'} =~ /delim/) ? ($ud = 1) : ($ud = 0);
$params{'load_tables'} = $params{'tab_tables'} if !defined
$params{'load_tables'};
@load_tablelist = split(./, $params{'load_tables'});

foreach $table (@load_tablelist)
{
    $load_flatfile_area_list = split(./,
$params{'load_flatfile_area_.$table'}) if (defined
$params{'load_flatfile_area_.$table'});
    $curts = $params{'tab_.$table._ts'};
    $usels = 0;
}

```

```

$lfexist = 0;
$bfexist = 0;
$dafexist = 0;
$difexist = 0;
$ffexist = 0;

# see if we are using pipes
$up = $params{'load_use_pipes'} =~ /$table/ ? 1 : 0;

$dsp = $params{'tab_.$table._load_degar'};;
$dgp = ($params{'load_dbgen_partition'}) =~ /$table/ ? 1 : 0;
$dbgpar = $params{'load_dbgen_.$table._option_C'};

# create all of the "executable" load sections
# These variables will hold for all loaders for a given table
$upwd = "";
$parboot = "";
$dirboot = "";
$silent = "";
$dismax = "";
$file = "";
$errors = "";
$rows = "";
$bsize = "";
$load = "";
$skip = "";
$dbgopt = "";
$dbgtab = "";

if ($table =~ /lineitem/)
{
    $dbgtab = "L";
}
elsif ($table =~ /orders/)
{
    $dbgtab = "O";
}
elsif ($table =~ /partsupp/)
{
    $dbgtab = "S";
}
elsif ($table =~ /part/)
{
    $dbgtab = "P";
}
elsif ($table =~ /customer/)
{
    $dbgtab = "c";
}
elsif ($table =~ /supplier/)
{
    $dbgtab = "s";
}
elsif ($table =~ /nation/)
{
    $dbgtab = "n";
}
elsif ($table =~ /region/)
{
    $dbgtab = "r";
}

$dbgopt .= "-T ".$dbgtab." ";
$dbgopt .= "-s ". $params{'scale_factor'} . " ";
$dbgopt .= "-C ";
$dbgopt .= $params{'load_dbgen_.$table._option_C'};
# if using pipes, create the pipes
$nperset = 1;

```

```

if ($dgp && $dp > 1)
{
    $nset = ($params{'tab_.$table._#part'} > $dp) ? 1
        : int($dp / $params{'tab_.$table._#part'});
    $nperset = int($dbgpar / $nset);
}
if (defined @load_flatfile_area_list) {
    $number_of_flatfile_areas = @load_flatfile_area_list;
    if ($number_of_flatfile_areas < $dbgpar) {
        print "load_flatfile_area_list has to few entries\n";
        print "set it to at least ". $dbgpar." elements\n";
        print "baling out ...\n";
    }
}
for ($i=0;$i<$dbgpar;$i++)
{
    # create script to generate flat files for each dbgpar
    $cmd = sprintf("%s -S %d", $dbgopt, ($i + 1));
    if (defined $params{'load_flatfile_area_.$table'}) {
        $fpre =
            @load_flatfile_area_list[$i].$params{'load_dbgen_.$table._output_prefix'};
    }
    else {
        $fpre =
            $params{'load_flatfile_area'}. $params{'load_dbgen_.$table._output_prefix'};
    }
    if ($dgp)
    {
        # create script to generate partitioned flat files
        # if the output prefix name is specified with #
        # divide output file names into $dp/#numpart
        sets
        if ($fpre =~ /\#/)
        {
            $snum = 1;
            $snum = (int($i/$nperset) + 1) if ($dp > 1);
            $fpre =~ s/\#/\$snum/g;
        }
        # I commented this out to enable support for
        fixed dbgen (fixed to 84 partitions)
        $cmd .= "-p -I ";
        $cmd .=
            $params{'load_dbgen_.$table._input_params'};
            $cmd.= sprintf(" -o %s_%d ", $fpre,($i + 1));
            # the following is the new stuff
            #$cmd = "-D ". $cmd;
    }
    else
    {
        # $cmd .= sprintf(" -o $fpre"); this is only
        temporary
    }
    $cmd = $verbose ? "-v -f " . $cmd : "-f " . $cmd;
    $cmd .= " & ";
    $cmd .= "\n";
    &dump1("*dbgen");
}
&dump0("*wait");
&time0("Done creating flat files for table $table");
}
&dump0("*wait");
&time0("Done creating flat files");
} # end of dbgen

sub dbgen_old
{

```

```

&dump0("#####
#####");
    &dump0("# Data (Flat File) Generation Phase");
    &time0("Begin creating flat files");

$cur_inst = 1 if $multi; # for possible locality on SP2
($params{'load_type'} =~ /delim/) ? ($ud = 1) : ($ud = 0);
$params{'load_tables'} = $params{'tab_tables'} if !defined
$params{'load_tables'};

@load_tablelist = split(//, $params{'load_tables'});
foreach $table (@load_tablelist)
{
    $dbgprc = $params{'load_dbgen_.$table._option_C'};
    $curts = $params{'tab_.$table._ts'};
    $dp = $params{'tab_.$table._load_degar'};
    $usels = 0;
    $lfexist = 0;
    $bfexist = 0;
    $dafexist = 0;
    $difexist = 0;
    $ffexist = 0;

    # see if we are using pipes
    $up = $params{'load_use_pipes'} =~ /$table/ ? 1 : 0;

    $dgp = ($params{'load_dbgen_partition'} =~ /$table/) ? 1
: 0;
    $dbgpar = $params{'load_dbgen_.$table._option_C'};

# create all of the "executable" load sections
# These variables will hold for all loaders for a given table
    $upwd = "";
    $parbool = "";
    $dirbool = "";
    $silent = "";
    $dismax = "";
    $file = "";
    $errors = "";
    $rows = "";
    $bsize = "";
    $load = "";
    $skip = "";
    $dbgopt = "";
    $dbgtab = "";

    if ($table =~ /lineitem/)
    {
        $dbgtab = "L";
    }
    elsif ($table =~ /orders/)
    {
        $dbgtab = "O";
    }
    elsif ($table =~ /partsupp/)
    {
        $dbgtab = "S";
    }
    elsif ($table =~ /part/)
    {
        $dbgtab = "P";
    }
    elsif ($table =~ /customer/)
    {
        $dbgtab = "c";
    }
    elsif ($table =~ /supplier/)
    {
        $dbgtab = "s";
    }

    elsif ($table =~ /nation/)
    {
        $dbgtab = "n";
    }
    elsif ($table =~ /region/)
    {
        $dbgtab = "r";
    }

    $dbgopt .= "-T ".$dbgtab." ";
    $dbgopt .= "-s ".$params{'scale_factor'} . " ";
    $dbgopt .= "-C ";
    $dbgopt .= ((defined
$params{'load_dbgen_.$table._option_C'}) ?
$params{'load_dbgen_.$table._option_C'} :
$params{'load_dbgen_def_option_C'}));
    if ($dgp)
    {
        $dbgopt .= "-p -i ";
        $dbgopt .= (defined
$params{'load_dbgen_.$table._input_params'}) ?
$params{'load_dbgen_.$table._input_params'} :
$params{'load_dbgen_def_input_params'});
    }

    # Start - Barry N. Perkins 8/27/1998      #
    # included the following lines to copy flat files#
    # from default location to backup location   #
    # Defined a new variable for backup location  #
    $fbkp = (defined
$params{'load_dbgen_flatfile_backup'}) ?
$params{'load_dbgen_flatfile_backup'} :
0;
    $bpref = (defined
$params{'load_dbgen_backup_.$table._prefix'}) ?
$params{'load_dbgen_backup_.$table._prefix'} :
$params{'load_dbgen_backup_area'} . $table;
    # End - Barry N. Perkins 8/27/1998      #
    # if using pipes, create the pipes
    if($dgp)
    {
        # create script to generate partitioned flat files for each
        $dbgpar
        $nperset = 1;

        if ($dgp && $dp > 1)
        {
            $nset = ($params{'tab_.$table._#part'} > $dp)
? 1 : int($dp / $params{'tab_.$table._#part'});
            $nperset = int($dbgpar / $nset);
        }

        for ($i=0;$i<$dbgpar;$i++)
        {
            $cmd = sprintf("%s -S %d", $dbgopt, ($i +
1));
            if ($dgp)
            {
                # if the output prefix name is specified with
                # $dp/#numpart sets
                $fpre = (defined
$params{'load_dbgen_.$table._output_prefix'}) ?
$params{'load_dbgen_.$table._output_prefix'} :
$params{'load_flatfile_area'} . $table;
                if ($fpre =~ /\#/)

```

```

{
    $snum = 1;
    $snum = (int($i/$nperset) + 1) if
($dp > 1);
    $fpre =~ s/#/$snum/g;
}
$cmt .= sprintf(" -o %s_%d ", $fpre, ($i +
1));
}
$cmt = $verbose ? "-v -f " . $cmt : "-f " .
$cmt;
$cmt .= sprintf(" 2>> %s_%d.log", $table, ($i +
1)) if $log_output;
#
$cmt .= "& ";
$cmt .= "\n";
&dump1("*dbgen");
}
&dump0("*wait");
}
else
{
    $cmt = $verbose ? "-v " : "";
    $cmt .= "-f " . $dbgopt;
    $cmt .= sprintf(" 2>> %s.log", $table) if $verbose;
    $cmt .= "\n";
    &dump1("*dbgen");
}
# Start - Barry N. Perkins 8/27/1998      #
# Included the following lines to copy flat files#
# from default location to backup location   #
# Copy from default location to backup location #
if ($fbkp) {
    $cmt = sprintf("copy %s%*.* %s*.*\n", $fpre,
$table, $pre);
    &dump1("*sh");
    &dump0("*wait");
}
# End - Barry N. Perkins 8/27/1998      #
&time0("Done creating flat files for table $table");
}
&dump0("*wait");
&time0("Done creating flat files");
} # end of dbgen

sub dbgen_my_split_version # I will delete this and dbgen_nt and
dbgen_unix as soon as new dbgen is fully tested
{
    if (($os cmp "unix") == 0)
    {
        &dbgen_unix();
    }
    else
    {
        &dbgen_nt();
    }
}

sub dbgen_nt
{

&dump0("#####
#####");
    &dump0("# Data (Flat File) Generation Phase");
    &time0("Begin creating flat files");

$cur_inst = 1 if $multi; # for possible locality on SP2
($params{'load_type'} =~ /delim/) ? ($ud = 1) : ($ud = 0);
$params{'load_tables'} = $params{'tab_tables'} if !defined
$params{'load_tables'};
@load_tablelist = split(//, $params{'load_tables'});

foreach $table (@load_tablelist)
{
    $curts = $params{'tab_.$table._ts'};
    $dp = $params{'tab_.$table._load_degpar'};
    $usels = 0;
    $lfexist = 0;
    $bfexist = 0;
    $dafexist = 0;
    $difexist = 0;
    $ffexist = 0;
    $up = 0;
    $dgp = 0;
    $dbgpar = 1;

    # see if we are using pipes
    $up = 1 if ($params{'load_use_pipes'} =~ /$table/);
    $dgp = 1 if ($params{'load_dbgen_partition'} =~
/$table/);
    $dbgpar = $params{'load_dbgen_def_option_C'} if
defined $params{'load_dbgen_def_option_C'};
    $dbgpar = $params{'load_dbgen_.$table._option_C'} if
defined $params{'load_dbgen_.$table._option_C'};

    # create all of the "executable" load sections
    # These variables will hold for all loaders for a given table
    $upwd = "";
    $parbool = "";
    $dirbool = "";
    $silent = "";
    $dismax = "";
    $file = "";
    $errors = "";
    $rows = "";
    $bsize = "";
    $load = "";
    $skip = "";
    $dbgopt = "";
    $dbgtab = "";

    if ($table =~ /lineitem/)
    {
        $dbgtab = "L";
    }
    elsif ($table =~ /orders/)
    {
        $dbgtab = "O";
    }
    elsif ($table =~ /partsupp/)
    {
        $dbgtab = "S";
    }
    elsif ($table =~ /part/)
    {
        $dbgtab = "P";
    }
    elsif ($table =~ /customer/)
    {
        $dbgtab = "c";
    }
    elsif ($table =~ /supplier/)
    {
        $dbgtab = "s";
    }
    elsif ($table =~ /nation/)
    {
        $dbgtab = "n";
    }
}

```

```

        elseif ($table =~ /region/)
        {
            $dbgtab = "r";
        }

        if ($up) {
            $dbgopt .= "-T ".$dbgtab." ";
            $dbgopt .= "-s ".$params{'scale_factor'} . " ";
            $dbgopt .= "-C ";
            $dbgopt .= ((defined
$params{'load_dbgen_.$table._option_C'}) ?
$params{'load_dbgen_.$table._option_C'} :
$params{'load_dbgen_def_option_C'});
            if ($dgp) {
                $dbgopt .= "-p -i ";
                $dbgopt .=((defined
$params{'load_dbgen_.$table._input_params'}) ?
$params{'load_dbgen_.$table._input_params'} :
$params{'load_dbgen_def_input_params'});
            }
            else
            {
                $dbgopt .= "-T ".$dbgtab." ";
                $dbgopt .= "-s ".$params{'scale_factor'} . " ";
                $dbgopt .= "-C ";
                $dbgopt .= ((defined
$params{'load_dbgen_.$table._option_C'}) ?
$params{'load_dbgen_.$table._option_C'} :
$params{'load_dbgen_def_option_C'});
                # if using pipes, create the pipes
                if($up)
                {
                    # create script to generate partitioned flat files for each
                    $nperset = 1;
                    if ($dgp && $dp > 1) {
                        $nset = int($dp /
$params{'tab_.$table._#part'});
                        $nperset = int($dbgpar / $nset);
                    }
                    for ($i=0;$i<$dbgpar;$i++) {
                        $cmd = sprintf("%s -S %d", $dbgopt, ($i +
1));
                        if ($dgp) {
                            # if the output prefix name is specified with
                            # divide output file names into
                            $dp/#numpart sets
                            $fpre = (defined $params{'load_dbgen_'.
$table._output_prefix'}) ?
$params{'load_dbgen_.$table._output_prefix'} :
$params{'load_dbgen_def_output_prefix'};
                            if ($fpre =~ /\#/) {
                                $snum = 1;
                                $snum = (int($i/$nperset) + 1) if
($dp > 1);
                                $fpre =~ s/#/$snum/g;
                            }
                            $cmd .= sprintf(" -o %s_%d ", $fpre, ($i +
1));
                            $cmd = "#!/bin/sh\n$cmd\n";
                            $cmd .= "#\n";
                            $cmd .= "&dump1(*dbgen");
                            $cmd .= "&dump0(*wait");
                            $cmd .= "# create script to concatenate partitioned flat files for each
dbgpar into partitioned flat files by partitions and number of
partitioned files in each partition
                            if ($dgp) {
                                $nptn = $params{'tab_.$table._#part'};
                                for ($i=0;$i<$dbgpar;$i++) {
                                    # if the output prefix name is specified with
                                    # divide output file names into
                                    $dp/#numpart sets
                                    $fpre = (defined $params{'load_dbgen_'.
$table._output_prefix'}) ?
$params{'load_dbgen_.$table._output_prefix'} :
$params{'load_dbgen_def_output_prefix'};
                                    if ($fpre =~ /\#/) {
                                        $snum = 1;
                                        $snum = (int($i/$nperset) + 1) if
($dp > 1);
                                        $fpre =~ s/#/$snum/g;
                                    }
                                    $cmd = sprintf("copy %s_*.%d %s.%d\n",
$fpre, $nptn, $fpre, $nptn);
                                    $cmd .= "&dump1(*sh");
                                    $cmd .= "&dump0(*wait");
                                    $cmd = sprintf("del %s_*.%d\n", $fpre,
$nptn);
                                    $cmd .= "&dump1(*sh");
                                    $cmd .= "&dump0(*wait");
                                }
                            }
                            else
                            {
                                $cmd = "-f ". $dbgopt;
                                $cmd .= "#\n";
                                $cmd .= "&dump1(*dbgen");
                            }
                            $cmd .= "&dump0(*wait");
                            &time0("Done creating flat files for table $table");
                            &dump0(*wait");
                            &time0("Done creating flat files");
                        } # dbgen_nt
                    }
                }
            }
        }
    }
}

```

```

$params{'load_tables'} = $params{'tab_tables'} if !defined
$params{'load_tables'};
@load_tablelist = split(//, $params{'load_tables'});
foreach $table (@load_tablelist)
{
    $curts = $params{'tab_.$table._ts'};
    $dp = $params{'tab_.$table._load_degpar'};
    $usels = 0;
    $lfexist = 0;
    $bfexist = 0;
    $dafexist = 0;
    $difexist = 0;
    $ffexist = 0;
    $up = 0;
    $dgp = 0;
    $dbgpar = 1;

    # see if we are using pipes

    $up = 1 if ($params{'load_use_pipes'} =~ /$table/);
    # <bug> parts/partsupp can be confused
    $dgp = 1 if ($params{'load_dbgen_partition'} =~
    /$table/);
    $dbgpar = $params{'load_dbgen_def_option_C'} if
    defined $params{'load_dbgen_def_option_C'};
    $dbgpar = $params{'load_dbgen_.$table._option_C'} if
    defined $params{'load_dbgen_.$table._option_C'};

    $params{'tab_.$table._load_ctlf'} = $table.'.ctl' if !defined
$params{'tab_.$table._load_ctlf'};
    @ctlf = split(//, $params{'tab_.$table._load_ctlf'});
    $err = "ctl" if ((@ctlf > 1) && (@ctlf != $dp));
    @logf = split(//, $params{'tab_.$table._load_logf'});
    $err = "log" if ((@logf > 1) && (@logf != $dp));
    $lfexist = 1 if (@logf > 0);
    @badf = split(//, $params{'tab_.$table._load_badf'});
    $err = "bad" if ((@badf > 1) && (@badf != $dp));
    $bfexist = 1 if (@badf > 0);
    @datf = split(//, $params{'tab_.$table._load_datf'});
    $err = "dat" if ((@datf > 1) && (@datf != $dp));
    $dafexist = 1 if (@datf > 0);
    @disf = split(//, $params{'tab_.$table._load_disf'});
    $err = "dis" if ((@disf > 1) && (@disf != $dp));
    $difexist = 1 if (@disf > 0);

    @filf = 0;
    # $params{'tab_.$table._load_filf'} =
$params{$curts.'_datafiles'} if ($params{'tab_.$table._load_filf'} =~
    /alltsdatafiles/);
    if ($params{'tab_.$table._load_filf'} =~ /alltsdatafiles/)
    {
        $params{'tab_.$table._load_filf'} =
$params{$curts.'_datafiles'}
    }
    @filf = split(//, $params{'tab_.$table._load_filf'}) if defined
$params{'tab_.$table._load_filf'};
        # relax the requirement a little bit by allowing round
robining
        $numfil = @filf;
        # if (($numfil > 1) && ($numfil < $dp) && (($dp %
$numfil) == 0)) {
            if (($numfil > 1) && ($numfil < $dp)) {
#                $p = $dp / $numfil;
                $fil = "";
                for ($i = 0; $i < $dp; $i++)
                {
                    if ($i == 0) {
                        $fil = $params{'tab_.$table._load_filf'};
                    } else {
                        $fil =
join(',',$fil,$params{'tab_.$table._load_filf'});
```

```

                }
            }
            $err = "fil" if (((@filf > 1) && ($dp != @filf)));
            $ffexist = 1 if (@filf > 0;
            if ($err)
            {
                print "Error with load parameters for table $table\n";
                print " degree is $dp, $err list has bad number of
elements\n";
                return;
            }
            $usels = 1 if (((@dp > 1) && (@datf == 1) &&
$params{'tab_.$table._load_datf'} !~ /\#/));
# expand all of the xxxf arrays to arrays of size $dp
@ff = ();
for ($i=0; $i < $dp; $i++)
{
    $iplus = $i + 1;
    if (@ctlf > 1)
    {
        @cf[$i] = @ctlf[$i];
    }
    else
    {
        @cf[$i] = @ctlf[0];
        @cf[$i] =~ s/\#/$/iplus/g;
    }
    if (@logf > 1)
    {
        @lf[$i] = @logf[$i];
    }
    else
    {
        @lf[$i] = @logf[0];
        @lf[$i] =~ s/\#/$/iplus/g;
    }
    if (@badf > 1)
    {
        @bf[$i] = @badf[$i];
    }
    else
    {
        @bf[$i] = @badf[0];
        @bf[$i] =~ s/\#/$/iplus/g;
    }
    if (@datf > 1)
    {
        @daf[$i] = @datf[$i];
    }
    else
    {
        @daf[$i] = @datf[0];
    }
}
# if load_degpar is larger than the number
partitions
# and we are using pipes,
# then load_degpar has to be a multiple of the
number
# of partition and load_degpar/#partitions sets
of
# pipes will be setup.
# The goal is to maintain only one pipe/flatfile
per
# sqldr.

if (($params{'tab_.$table._#part'} > 0) &&
($dp > $params{'tab_.$table._#part'})) {
    if ($dp % $params{'tab_.$table._#part'} ==
```

0) {

```

        if (@datf[0] =~ /#.*/#) {
            # set number

$num=int($i/$params{'tab_'.\$table.'_'.$part'}) + 1;
            # partiton number

$pnum=$i%$params{'tab_'.\$table.'_'.$part'} + 1;
            @daf[$i] = @datf[0];
            @daf[$i] =~ s#/$/num/;
            @daf[$i] =~ s#/$/pnum/;

        } else {
            @daf[$i] = @datf[0];
            @daf[$i] =~ s#/$/iplus/g;
        }
    }
else
{
    print "Error: #partitons for table
$table does not divide load_degar for the table.\n";
    print "degree is $dp, number of
partitions is $params{'tab_'.\$table.'_'.$part'}.\\n";
    return;
}
else
{
    # assign
    @daf[$i] = @datf[0];
    @daf[$i] =~ s#/$/iplus/g;
}

if (@disf > 1)
{
    @dif[$i] = @disf[$i];
}
else
{
    @dif[$i] = @disf[0];
    @dif[$i] =~ s#/$/iplus/g;
}
if (@filf > 1)
{
    @ff[$i] = @filf[$i];
}
else
{
    # round robining - temp fix
    @ff[$i] = @filf[0] if (@filf);
    if (defined $params{$params{'tab_'.\$table.'_.ts'}.'_#files'}})
    {
        $numfil =
$params{$params{'tab_'.\$table.'_.ts'}.'_#files'}};
        $filnum = $i % $numfil + 1;
        @ff[$i] =~ s#/$/filnum/g;
    } else {
        @ff[$i] =~ s#/$/iplus/g;
    }
}

$control = sprintf ("%s%s", $params{'load_controlfile_area'}, @cf[0]);
$control =~ s/^?/$ENV{'ORACLE_HOME'}/g;

$ff_path = $params{'load_dbgen_'.\$table.'_.output_prefix'};
$numchild = $params{'load_dbgen_'.\$table.'_.option_C'};
$pname = $params{'tab_'.\$table.'_.partnames'};
@pname = split(//, $pname);

# create the controlfiles (fixed-length fields or delimited records)
#   if ($params{'skip_mk_ldctifs'} !~ /$table/)
#
#      {
#          $npart = (defined $params{'tab_'.\$table.'_'.$part'}) ?
$params{'t ab_'.\$table.'_'.$part'} : 1;
        for ($ictl=1; $ictl<=$npart; $ictl++) {
            open (CTLFILE, ">$control");
            print CTLFILE "---\\n";
            print CTLFILE " --- $table.ctl for delimited records\\n" if
($ud == 1);
            print CTLFILE " --- $table.ctl for fixed-length fields\\n" if
($ud == 0);
            print CTLFILE " ---\\n\\n";
            if (!($pre72) && defined
$params{'tab_'.\$table.'_.loadextent'})
            {
                print CTLFILE "options\\n";
                print CTLFILE "(\\n";
                print CTLFILE "storage = (initial
$params{'tab_'.\$table.'_.loadextent'} next
$params{'tab_'.\$table.'_.loadextent'})\\n";
                print CTLFILE ")\\n";
            }
            print CTLFILE "unrecoverable\\n" if
($params{'load_unrecoverable'} =~ /[tT][rR][uU][eE]/);
            print CTLFILE "load\\n";
            print CTLFILE " - This is where INFILE should go.\\n";
            if ((!($up)) && ($dbgpar)) {
                for ($jpart=1;$jpart<=$numchild;$jpart++) {
                    print CTLFILE "INFILE ".$ff_path.$jpart.".".Sctl."\n";
                }
            }
            print CTLFILE "$params{'load_insert_type'}\\n";
            print CTLFILE "into table $table\\n";
            if ($dgp) {
                print CTLFILE "partition ($pname[$ictl-1])\\n";
            }
            print CTLFILE "$params{'load_insert_type'}\\n";
            print CTLFILE "fields terminated by
$params{'load_field_terminator'}\\n" if ($ud == 1);
            print CTLFILE "(\\n";
            @tab_collist = split(//, $params{'tab_'.\$table.'_.columns'});
            while ($col = shift(@tab_collist))
            {
                (@tab_collist == 0) ? ($addcomma = "") : ($addcomma =
",");
                $pos = "";
                $pos = sprintf ("position
(%s)", $params{'tab_'.\$table.'_.Scol.'_.pos'}) if ($ud == 0);
                $ctlline = sprintf (" %-20s %s %s$addcomma", $col, $pos,
$params{'tab_'.\$table.'_.Scol.'_.loadcolx'});
                print CTLFILE "$ctlline\\n";
            }
            print CTLFILE "\\n";
            close (CTLFILE);
            if ($npart > 1) {
                $newi=$ictl+1;
                $control =~ s/$table$ictl/$table$newi/;
            }
        }
    }
}

# create all of the "executable" load sections
# These variables will hold for all loaders for a given table
$upwd = "";
$parbool = "";
$dirbool = "";
$silent = "";
$dismax = "";
$file = "";
$errors = "";
$rows = "";

```

```

$bsize = "";
$load = "";
$skip = "";
$dbgopt = "";
$dbgtab = "";

if ($up) {
    if ($table =~ /lineitem/)
    {
        $dbgtab = "L";
    }
    elsif ($table =~ /orders/)
    {
        $dbgtab = "O";
    }
    elsif ($table =~ /partsupp/)
    {
        $dbgtab = "S";
    }
    elsif ($table =~ /part/)
    {
        $dbgtab = "P";
    }
    elsif ($table =~ /customer/)
    {
        $dbgtab = "c";
    }
    elsif ($table =~ /supplier/)
    {
        $dbgtab = "s";
    }
    elsif ($table =~ /nation/)
    {
        $dbgtab = "n";
    }
    elsif ($table =~ /region/)
    {
        $dbgtab = "r";
    }
    $dbgopt .= "-T ".$dbgtab." ";
    $dbgopt .= "-s ".$params{'scale_factor'} . " ";
    $dbgopt .= "-C ";
    $dbgopt .= ((defined
$params{'load_dbgen_.$table._option_C'}) ?
$params{'load_dbgen_.$table._option_C'} :
$params{'load_dbgen_def_option_C'});
    if ($dgp) {
        $dbgopt .= "-p -i ";
        $dbgopt .= (defined
$params{'load_dbgen_.$table._input_params'}) ?
$params{'load_dbgen_.$table._input_params'} :
$params{'load_dbgen_def_input_params'};
    }
}

$upwd = "$params{'user'}/$params{'passwd'}";
$parbool = "parallel=true" if
(($params{'tab_.$table._load_parallel'} =~ /true/) || ($dp > 1));
$dirbool = "direct=true" if
(($params{'tab_.$table._load_direct'} =~ /[Tt][Rr][Uu][Ee]/) ||
$parbool);
$silent = "silent=$params{'tab_.$table._load_silent'}" if
defined $params{'tab_.$table._load_silent'};
$dismax = "";
$dismax= $params{'tab_.$table._load_dismax'}" if defined
$params{'tab_.$table._load_dismax'};
$errors = "errors=$params{'tab_.$table._load_errors'}" if
defined $params{'tab_.$table._load_errors'};

$rows = "rows=$params{'tab_.$table._load_rows'}" if defined
$params{'tab_.$table._load_rows'};
$bsize = "bindsize=$params{'tab_.$table._load_bsize'}" if
defined $params{'tab_.$table._load_bsize'};

if ($usels)
{
    $split = int($params{'tab_.$table._#rows'} / $dp);
    $extra = int($params{'tab_.$table._#rows'} % $dp);
    $loadval = $split;
    $skipval = 0;
}

# if using pipes, create the pipes

if($up)
{
    for ($i=0;$i<$dp;$i++)
    {
        $cmd = sprintf("rm -f %s%s\nmknode %s%s
p\n",$params{'load_flatfile_area'},@daff[$i],$params{'load_flatfile_a
rea'},@daff[$i]);
        #
        $cmd = sprintf("%s%s
p\n",$params{'load_flatfile_area'},@daf[$i]);
        &dump1("*sh");
    }
    &dump0("*wait");
}

# start the dbgens

if ($dgp)
{
    $nset = int($dp /
$params{'tab_.$table._#part'});
    $nperset = int($dbgpar / $nset);
}

for ($i=0;$i<$dbgpar;$i++)
{
    $cmd = $params{'load_flatfile_area'} . "\n";
    $cmd2 = sprintf("-f %s -S %d", $dbgopt, ($i +
1));
    if ($dgp)
        # if the output prefix name is specified with
#
        # divide output file names into
$dp/#numpart sets
    $fpre = (defined $params{'load_dbgen_.
$table._output_prefix'}) ?
$params{'load_dbgen_.$table._output_prefix'} :
$params{'load_dbgen_def_output_prefix'};
    if ($fpre =~ /\//)
        if ($fpre =~ /\#/)
            $snum = int($i/$nperset) + 1;
            $fpre =~ s/#/$snum/g;
        }
        $cmd2 .= sprintf(" -o %s ", $fpre);
    }
    $cmd2 .= "\n";
    &dump2("*dbgen");
}

$control = "";
$log = "";
$bad = "";
$data = "";
$discard = "";
$file = "";
$load = "";
$loadval = "";
$skip = "";

for ($i=0; $i < $dp; $i++)

```

```

{
    &advmulti();

    $control = sprintf (" control=%s%s",
$params{'load_controlfile_area'}, @cf[$i]);
    $control = sprintf (" control=/host%s%s",
$params{'load_controlfile_area'}, @cf[$i]) if
($params{'special_machine'} eq 'ncube');
    $log = sprintf (" log=%s%s", $params{'load_otherfile_area'},
@lf[$i]) if !$fexist;
    $bad = sprintf (" bad=%s%s",
$params{'load_otherfile_area'}, @bf[$i]) if $bfexist;
    $data = sprintf (" data=%s%s", $params{'load_flatfile_area'},
@daf[$i]) if $dafexist;
    $discard = sprintf (" discard=%s%s",
$params{'load_otherfile_area'}, @dif[$i]) if $difexist;
    $file = sprintf (" file=%s%s", $params{$curts._area},
@ff[$i]) if $ffexist;

    if ($usels)
    {
        $loadval = $loadval + 1 if ($extra > $i);
        $load = sprintf (" load=%d", $loadval);
        $skip = sprintf (" skip=%d", $skipval);
        $skipval = $skipval + $loadval;
        $loadval = $split;
    }
    if ($up)
    {
        $load = " load=99999999";
    }

    $cmd = sprintf
("%s%s%s%s%s%s%s%s%s%s%s%s%s%s%s%s%s%s%s%s%s%s\n",
$upwd,$contr
ol,$log,$bad,$data,$discard,$dismax,$skip,$load,$errors,$rows,$bsiz
e,$silent,$dirbool,$parbool,$file);
    &dump1("*load");
    &dump0("*wait") if ((!$parbool) && (!defined
$params{'load_no_waits'}));
}
&dump0("*wait") if !defined $params{'load_no_waits'};

if($up)
{
    for ($i=0;$i<$dp;$i++) {
        $cmd = sprintf("rm -f
%$s\n",
$params{'load_flatfile_area'}, @daf[$i]);
        &dump1("*sh");
    }
}
}

sub plcre
{
    &dump0("#####
#####");
    &dump0("# NT Raw Partition and Setlink Creation Phase");
    &time0("Begin NT Raw Partition and Setlink creation");

# create NT Raw Partition and Setlink input files
    $lnksfile = $params{'plcre_setlinks_input_file'};
    open (LNKSFILE, ">$lnksfile");
    $drvenum = $params{'plcre_drivenums'};
    $md = $drvenum =~ tr/,/./;
    @drvenum = split(//,$params{'plcre_drivenums'});

    if ($params{'plcre_recreate_extended_partitions' =~
/[tT][rR][uU][eE]/})
    {
        foreach $drvenum (@drvenum)
        {
            &recreate_drive_extended_part;
        }
        if (defined $params{'plcre_log_drivenum'})
        {
            &recreate_drive_extended_part;
        }
    }
    $io_control_files = $params{'io_control_files'};
    $io_control_files =~ s/[\\\"\\\\.\\/]*/g;
    @io_control_files = split(//,$io_control_files);
    $d = 0;
    foreach $file (@io_control_files)
    {
        $size = $params{'plcre_control_file_size'};
        $size =~ s/[Mm]/g;
        &create_drive_part_file;
    }
    foreach $ts_entry (@ts_all)
    {
        &create_drive_part("$ts_entry") if ($ts_entry =~ /ts_sys/
|| $ts_entry =~ /ts_log/);
    }
    $d = 0;
    foreach $ts_entry (@ts_most)
    {
        &create_drive_part("$ts_entry");
    }
    close (LNKSFILE);
    &dump0("*wait");
    &time0("Done NT Raw Partition creation");
    $cmd = "setlinks /F: . $lnksfile . "\n";
    &dump1("*sh");
    &dump0("*wait");
    &time0("Done Setlink links creation");
    &time0("Done NT Raw Partition and Setlink creation");
} # end of plcre

sub sccre
{
    &dump0("#####
#####");
    &dump0("# Schema Creation Phase");
    &time0("Begin schema creation");

# Create user
    if ($params{'skip_create_user'} !~ /true/)
    {
        &dump0("# creating $params{'user'} user");
        $cmd .= "drop user $params{'user'} cascade;\n";
        $cmd .= "grant $params{'privileges'}\n";
        $cmd .= " to $params{'user'} identified by
$params{'passwd'};\n";
        $cmd .= "@?/rdbms/admin/utlxplan;\n" if (($os cmp "unix") ==
0);
        &dump1("*sql");
    }
    &dump0("*wait");

# Create data tablespaces (including datafiles and tables)
    &dump0("# creating data tablespaces, datafiles, and tables");
}

```

```

# create tablespaces with initial datafile
foreach $ts_entry (@ts_data)
{
    &create_ts("$ts_entry");
}
foreach $ts_entry (@ts_index)
{
    &create_ts("$ts_entry");
}
foreach $ts_entry (@ts_temp)
{
    $ts_temporary = "temporary" if !$pre73;
    &create_ts("$ts_entry");
}
&dump0("*wait");

# create remaining datafiles for the tablespaces
foreach $ts_entry (@ts_data)
{
    &add_dfs("$ts_entry");
}
foreach $ts_entry (@ts_index)
{
    &add_dfs("$ts_entry");
}
if ($params{'skip_ts'} !~ /temp/)
{
    foreach $ts_entry (@ts_temp)
    {
        &add_dfs("$ts_entry");
    }
}
&dump0("*wait");

if ($params{'skip_create_tables'} !~ /true/)
{
    &create_clusters();
    &dump0("*wait");
    &create_objects('tab',@tab_list) if defined(@tab_list);
    &dump0("*wait");
}

if ($params{'skip_ts'} !~ /temp/)
{
# Alter user's temporary tablespace
    &dump0("# altering $params{'user'}'s temporary tablespace");
    $ts_entry = shift (@ts_temp);
    $cmd = "alter user $params{'user'} temporary tablespace
$ts_entry;\n";
    &dump1("*sql");
    &dump0("*wait");
}
if ($params{'skip_ts'} !~ /data/)
{
# Alter user's default tablespace
    &dump0("# altering $params{'user'}'s default tablespace");
    $ts_entry = shift (@ts_data);
    $cmd = "alter user $params{'user'} default tablespace
$ts_entry;\n";
    &dump1("*sql");
    &dump0("*wait");
}
&time0("Done schema creation");
}

sub sctso
{
    if ($phaselist !~ /sccre/)
    {
        &dump0("#####
#####");
        &dump0("# Schema Creation Phase - datafiles only (no
tables or users)");
    }

    # Create data tablespaces (including datafiles)
    &dump0("# creating data tablespaces, datafiles");

    # create tablespaces with initial datafile
    foreach $ts_entry (@ts_data)
    {
        &create_ts("$ts_entry");
    }
    foreach $ts_entry (@ts_index)
    {
        &create_ts("$ts_entry");
    }
    foreach $ts_entry (@ts_temp)
    {
        $ts_temporary = "temporary" if !$pre73;
        &create_ts("$ts_entry");
    }
    &dump0("*wait");

    # create remaining datafiles for the tablespaces
    foreach $ts_entry (@ts_data)
    {
        &add_dfs("$ts_entry");
    }
    foreach $ts_entry (@ts_index)
    {
        &add_dfs("$ts_entry");
    }
    if ($params{'skip_ts'} !~ /temp/)
    {
        foreach $ts_entry (@ts_temp)
        {
            &add_dfs("$ts_entry");
        }
    }
    &dump0("*wait");

    if ($params{'skip_ts'} !~ /temp/)
    {
# Alter user's temporary tablespace
        &dump0("# altering $params{'user'}'s temporary
tablespace");
#        $ts_entry = shift (@ts_temp);
#        $cmd = "alter user $params{'user'} temporary
tablespace $ts_entry;\n";
#        &dump1("*sql");
#        &dump0("*wait");
    }
}

sub scuto
{
    if ($phaselist !~ /sccre/)
    {
        &dump0("#####
#####");
        &dump0("# Schema Creation Phase - User and Tables ONLY
(no datafiles)");
        &time0("Begin creating user and tables (no datafiles)");
    }
}

```

```

if ($params{'skip_create_user'} !~ /true/)
{
    &dump0("# creating $params{'user'} user");
    $cmd .= "drop user $params{'user'} cascade;\n";
    $cmd .= "grant $params{'privileges'}\n";
    $cmd .= " to $params{'user'} identified by
$params{'passwd'};\n";
    &dump1("*sql");
}
&dump0("*wait");

&create_clusters();
&dump0("*wait");
&create_objects('tab',@tab_list) if defined(@tab_list);
&dump0("*wait");

if ($params{'skip_ts'} !~ /temp/)
{
# Alter user's temporary tablespace
    &dump0("# altering $params{'user'}'s temp tablespace");
    $ts_entry = shift (@ts_temp);
    $cmd = "alter user $params{'user'} temporary tablespace
$ts_entry;\n";
    &dump1("*sql");
    &dump0("*wait");
}
# Alter user's default tablespace
if ($params{'skip_ts'} !~ /data/)
{
    &dump0("# altering $params{'user'}'s default tablespace");
    $ts_entry = shift (@ts_data);
    $cmd = "alter user $params{'user'} default tablespace
$ts_entry;\n";
    &dump1("*sql");
    &dump0("*wait");
}
$cmd .= "connect tpcd/tpcd\n";
$cmd .= '@' . "$params{'dd_sql_area'}".
"utlxplan.sql;\n";
    &dump1("*sql");
    &dump0("*wait");
    &time0("Done creating user and tables (no datafiles)");
}

sub scuvo
{
    if ($phaselist =~ /scuvo/)
    {

&dump0("#####
#####");
        &dump0("# Schema Creation Phase - Views ONLY (no
datafiles)");

        if (defined(@tablelog_list))
        {

&dump0("#####
#####");
            &dump0("# First I will create the materialized log for
the base tables");
            &create_objects('viewlog',@tablelog_list);
            &dump0("*wait");
        }

&dump0("#####
#####");
    }
}

&dump0("#####
#####");
    &dump0("# Now I can create the views with the corresponding
materialized logs");
    $cmd .= "connect
$params{'user'}$/params{'passwd'};\n";
    foreach $view (@view_list)
    {
        @viewlogs =
split(//,$params{'view_'. $view.'_viewlogs'});
        foreach $viewlog (@viewlogs)
        {
            $ob_type = 'viewlog';
            $object = $viewlog;
            if (!defined $params{'created_.$object'})
            {
                $params{'created_.$object'} = $object;
                &create_object;
            }
        }
        $ob_type = 'view';
        $object = $view;
        &create_object;
    }
    &dump1("*sql");
}

#     &create_objects('view',@view_list) if defined(@view_list);
#         &create_objects('viewlog',@viewlog_list) if
defined(@tablelog_list);

&dump0("*wait")
}
}

sub dsffs
{
    &dump0("#####
#####");
    &dump0("# Flatfile Distribution Phase");
    &time0("Begin data population");

    # &recycle_db() if ($params{'startup_db_dapop'});

    $cur_inst = 1 if $multi; # for possible locality on SP2
    ($params{'load_type'} =~ /delim/) ? ($ud = 1) : ($ud = 0);
}

sub dapop # Meikel's version
{
    &dump0("#####
#####");
    &dump0("# Database Population Phase");
    &time0("Begin data population");

    # &recycle_db() if ($params{'startup_db_dapop'});

    # find out how many nodes we have
    if (!defined(@ops_nodes)) {
        $nnodes=1
    } else {
        $nnodes= ($#ops_nodes + 1);
    }
    $cur_inst = 1 if $multi; # for possible locality on SP2
}

```

```

($params{'load_type'} =~ /delim/) ? ($ud = 1) : ($ud = 0);
$params{'load_tables'} = $params{'tab_tables'} if !defined
$params{'load_tables'};
@load_tablelist = split(//, $params{'load_tables'});
foreach $table (@load_tablelist)
{
    &time0("Begin $table load");
    $curts = $params{'tab_.$table._ts'};

# see if we are using pipes
$up = $params{'load_use_pipes'} =~ /$table/ ? 1 : 0;

$dsp = $params{'tab_.$table._load_degrpar'};
$dgp = ($params{'load_dbgen_partition'} =~ /$table/) ? 1
: 0;
$dbgpar = $params{'load_dbgen_.$table._option_C'};

# These variables will hold for all loaders for a given table
$upwd = "";
$parbool = "";
$dirbool = "";
$silent = "";
$dismax = "";
$errors = "";
$rows = "";
$bsize = "";
$load = "";
$skip = "";
$dbgopt = "";
$dbgtab = "";

$upwd = "$params{'user'}/$params{'passwd'}";
$parbool = "parallel=true" if
(($params{'tab_.$table._load_parallel'} =~ /true/) || ($dp > 1));
$dirbool = "direct=true" if
(($params{'tab_.$table._load_direct'} =~ /[Tt][Rr][Uu][Ee]/) ||
$parbool);
$silent = "silent=$params{'tab_.$table._load_silent'}" if
defined $params{'tab_.$table._load_silent'};
$dismax = ""
discardmax=$params{'tab_.$table._load_dismax'}" if defined
$params{'tab_.$table._load_dismax'};
$errors = "errors=$params{'tab_.$table._load_errors'}" if
defined $params{'tab_.$table._load_errors'};
$rows = "rows=$params{'tab_.$table._load_rows'}" if defined
$params{'tab_.$table._load_rows'};
$bsize = "bindsize=$params{'tab_.$table._load_bsize'}" if
defined $params{'tab_.$table._load_bsize'};

$ff_path =
$params{'load_flatfile_area'}.$params{'load_dbgen_.$table._output
_prefix'};

$pname = $params{'tab_.$table._partnames'};
$pname =~ s/#//g;
print $pname."--"@pname;
@pname = split(//,$pname);
$npart = ((defined $params{'tab_.$table._#part'}) &&
$dgp) ?
    $params{'tab_.$table._#part'} : 1;
$ctlarea = $params{'load_controlfile_area'};
$logarea = $params{'load_otherfile_area'};

if ($dbgpar*$npart <= $dp)
{
    $dpmax = $dbgpar*$npart;
    $numchild = 1;
    $remchild = 0;
}
else
{
    &time0("Begin $table load");
    $curts = $params{'tab_.$table._ts'};

# see if we are using pipes
$up = $params{'load_use_pipes'} =~ /$table/ ? 1 : 0;

$dsp = $params{'tab_.$table._load_degrpar'};
$dgp = ($params{'load_dbgen_partition'} =~ /$table/) ? 1
: 0;
$dbgpar = $params{'load_dbgen_.$table._option_C'};

# These variables will hold for all loaders for a given table
$upwd = "";
$parbool = "";
$dirbool = "";
$silent = "";
$dismax = "";
$errors = "";
$rows = "";
$bsize = "";
$load = "";
$skip = "";
$dbgopt = "";
$dbgtab = "";

$upwd = "$params{'user'}/$params{'passwd'}";
$parbool = "parallel=true" if
(($params{'tab_.$table._load_parallel'} =~ /true/) || ($dp > 1));
$dirbool = "direct=true" if
(($params{'tab_.$table._load_direct'} =~ /[Tt][Rr][Uu][Ee]/) ||
$parbool);
$silent = "silent=$params{'tab_.$table._load_silent'}" if
defined $params{'tab_.$table._load_silent'};
$dismax = ""
discardmax=$params{'tab_.$table._load_dismax'}" if defined
$params{'tab_.$table._load_dismax'};
$errors = "errors=$params{'tab_.$table._load_errors'}" if
defined $params{'tab_.$table._load_errors'};
$rows = "rows=$params{'tab_.$table._load_rows'}" if defined
$params{'tab_.$table._load_rows'};
$bsize = "bindsize=$params{'tab_.$table._load_bsize'}" if
defined $params{'tab_.$table._load_bsize'};

$ff_path =
$params{'load_flatfile_area'}.$params{'load_dbgen_.$table._output
_prefix'};

$pname = $params{'tab_.$table._partnames'};
$pname =~ s/#//g;
print $pname."--"@pname;
@pname = split(//,$pname);
$npart = ((defined $params{'tab_.$table._#part'}) &&
$dgp) ?
    $params{'tab_.$table._#part'} : 1;
$ctlarea = $params{'load_controlfile_area'};
$logarea = $params{'load_otherfile_area'};

if ($dbgpar*$npart <= $dp)
{
    $dpmax = $dbgpar*$npart;
    $numchild = 1;
    $remchild = 0;
}
else
{
    &time0("Begin $table load");
    $curts = $params{'tab_.$table._ts'};

# see if we are using pipes
$up = $params{'load_use_pipes'} =~ /$table/ ? 1 : 0;

$dsp = $params{'tab_.$table._load_degrpar'};
$dgp = ($params{'load_dbgen_partition'} =~ /$table/) ? 1
: 0;
$dbgpar = $params{'load_dbgen_.$table._option_C'};

{
    $dpmax = $dp;
    $numchild = int(($dbgpar*$npart)/$dp); # numchild is
the number of infiles of one loader
    $remchild = ($dbgpar*$npart) - ($numchild * $dp);
    #print "dp numchild remchild ".$dp." ".$numchild." ".
    ".$remchild."\n";
    $loaders_p_part=$dp/$npart;
    #print "dp npart loaders per partition
    ".$loaders_p_part." ".$dp." ".$npart."\n";
    $ninfile= int($dbgpar/$loaders_p_part);
    $ninfile_last=$ninfile+$dbgpar-($ninfile *
$loaders_p_part);
    #print "infiles lastloader ".$ninfile." ".
    ".$ninfile_last."\n";
}

# if we load on an ops we want to load each partition only
on one node

$npartitions_per_node = int($npart / $nnodes); #
partition/#nodes
$rempartitions = $npart - ($npartitions_per_node * $nnodes); #reminder of the partitions
    print "$nnodes $nnodes $npart $npart $table $table
npartitions_per_node $npartitions_per_node $rempartitions
$rempartitions\n";

$node = 0;
$idbgpar = 0;
$ipart=1;
$iipart=1;
if ($dp > $npart) {
    print "$dp $npart\n";
    $sqlldr_per_partition = int ($dp / $npart); #
load_degrpar / #partitions
    print "*** dp $dp npart $npart sqlldr_per_partition
$sqlldr_per_partition\n";
    $ninfile_per_sqlldr = int ($dbgpar /
$sqlldr_per_partition); #_C / sqlldr_per_partition
    $sqlldr_per_partition_rest = $dbgpar -
$sqlldr_per_partition * $ninfile_per_sqlldr;
    print "*** dbgpar $dbgpar sqlldr_per_partition
$sqlldr_per_partition\n";
    print "*** sqlldr_per_partition $sqlldr_per_partition
sqlldr_per_partition_rest $sqlldr_per_partition_rest
ninfile_per_sqlldr $ninfile_per_sqlldr\n";
}
else{
    $sqlldr_per_partition = 1;
    $ninfile_per_sqlldr = int ($dbgpar / $sqlldr_per_partition );
#_C / sqlldr_per_partition
}

$partcount = 1;
if (defined(@ops_nodes)){
    &sqlldr_ctl_ops; # this is a special controlfile
generation for OPS
}
else {
for ($idp=1; $idp<=$dpmax; $idp++)
{
    if ($partcount > $sqlldr_per_partition) {
        $partcount = 1;
    }
    if (defined(@ops_nodes)){
        $node = $node + 1;
        if ($node > $#ops_nodes+1) {
            $node = 1;
        }
    }
}

```

```

        }
    else {
        $node = "";
    }
    #$dbgpar = 0;
# create all of the "executable" load sections
#Sipart= int(((idp-1)*$numchild)/$dbgpar)+1; # this
is the first partition of the new series
    &admulti();
    $ctlfile = $params{'tab_.$table._load_ctlf'};
    $ctlfile =~ s/#/$/idp/g;
    $control = $ctlarea.$ctlfile;
    if ($dgp) # load this table in partition mode
    {
        #$control = sprintf (" %s%s_%d_%d.ctl",
$ctlarea,$table,$idp,$ipart);
        $log = sprintf (" %s%s_%d_%d.log",
$logarea,$table,$idp,$ipart);
    }
    else
    {
        if ($dbgpar == 1) #dbgpar is option _C for this
table
        {
            #$control = sprintf (" %s%.ctl",$ctlarea,
$table);
            $log = sprintf (" %s%.log",$logarea,
$table);
        }
        else
        {
            #$control = sprintf (" %s%s_%d.ctl",
$ctlarea,$table,$idp);
            $log = sprintf (" %s%s_%d.log",$logarea,
$table,$idp);
        }
    }
    $cmd = sprintf ("%s control=%s%s%s
log=%s%s%s%s%s%s%n",
$upwd,$control,$skip,$load,$log,$errors,$rows,
$bsize,$silent,$dirbool,$parbool);
    &dump1(*$load$node");
    &dump0(*$wait") if ((!$parbool) && (!defined
$params{'load_no_waits'}));

# create the controlfiles (fixed-length fields or delimited records)
    if ($params{'skip_mk_ldctlf'} !~ /$table/)
    {
        &load_ctl_head;
        $infiles = 0;
        $badfiles = 0;
        $discardfiles = 0;
        $intopartitions = "BEGINNING"; # this will
collect the partition numbers that will be served.
        if ($dp < $npart) {
            if ($idp <=$remchild)
                $nchild = $numchild+1;
            }else{
                $nchild = $numchild;
            }
        }else{
            if ($partcount <=
$sqlldr_per_partition_rest) {
                $nchild = $infiles_per_sqlldr+1;
            }else{
                $nchild = $infiles_per_sqlldr;
            }
        }
for ($jpart=1; $jpart<=$nchild; $jpart++)
{
    #print "ipart $ipart\n";
    $dbgpar = 0 if $idbgpar >= $dbgpar;
    $ipart = int(((idp-
1)*$nchild+$jpart)/$dbgpar);
    #$ipart = $ipart+1 if (((idp-
1)*$nchild+$jpart)$ipart*$dbgpar)>0;
    if ($dgp)
    {
        $pn=@ipart[$node];
        $partitionname = $pname.$pn;
        if (!$intopartitions ==

$partitionname)) {
/BEGINNING/
$partitionname;
        }
        if ($intopartitions =~
".*$partitionname;")
        {
            $intopartitions =
".*$partitionname";
        }
        else {
            $intopartitions .=
".*$partitionname";
        }
        @infile[$infiles++] = "" . $ff_path
"._" . $ipart . "";
        @badfile[$badfiles++] = "" .
"._" . $ipart . ".bad";
        @discardfile[$discardfiles++] = "" .
"._" . $ipart . ".dsc";
        #if ($remchild- > 0)
        #{

@infile[$infiles++] = "" .
".*$ipart . ";
        # @badfile[$badfiles++] = "" .
".*$ipart . ".bad";
        # @discardfile[$discardfiles++] = "" .
".*$ipart . ".dsc";
        }
        elsif ($dbgpar == 1)
        {
            @infile[$infiles++] = "" . $ff_path
".tbl";
            $ff_path . "_" . $dbgpar . ".bad";
            $ff_path . "_" . $dbgpar . ".dsc";
        }
        else
        {
            @infile[$infiles++] = "" . $ff_path
".tbl" . ++$idbgpar . "";
            $ff_path . "_" . $dbgpar . ".bad";
            $ff_path . "_" . $dbgpar . ".dsc";
            if ($remchild- > 0)
            {
                @infile[$infiles++] = "" .
$ff_path . ".tbl" . ++$idbgpar . "";
                @badfile[$badfiles++] = "" .
$ff_path . ".tbl" . ++$idbgpar . ".bad";
                @discardfile[$discardfiles++] = "" .
$ff_path . ".tbl" . ++$idbgpar . ".dsc";
            }
            $ff_path . "_" . $dbgpar . "";
            if ($remchild- > 0)
            {
                @infile[$infiles++] = "" .
$ff_path . ".tbl" . ++$idbgpar . "";
                @badfile[$badfiles++] = "" .
$ff_path . ".tbl" . ++$idbgpar . ".bad";
                @discardfile[$discardfiles++] = "" .
$ff_path . ".tbl" . ++$idbgpar . ".dsc";
            }
        }
    }
}

```

```

        @discardfile[$discardfiles++] =
"" . $ff_path . "_" . $dbgpar .
                                ".dsc";
    }
}
#print "vorher jpart $jpart ipart $ipart iipart
$iipart dbgpar $dbgpar\n";
if ($iipart >= $dbgpar){
    $iipart=0;
    $ipart=$iipart+1;
}
$ipart=$iipart+1;
#print "nacher jpart $jpart ipart $ipart iipart
$iipart dbgpar $dbgpar\n";
}
--$infiles;
if ($up)
{
    print CTLFILE "INFILE ";
    for ($fpart=0; $fpart<=$infiles; $fpart++)
    {
        print CTLFILE @infile[$fpart] . ",";
        print CTLFILE @infile[$fpart] . "
    " if $fpart < $infiles;
    " if $fpart == $infiles;
    }
    print CTLFILE "BADFILE " . @badfile[0]
. " ";
    print CTLFILE "DISCARDFILE " .
@discardfile[0] . "\n";
}
else
{
    for ($fpart=0; $fpart<=$infiles; $fpart++)
    {
        print CTLFILE "INFILE " .
@infile[$fpart] . "";
        print CTLFILE "BADFILE " .
@badfile[$fpart] . "";
        print CTLFILE "DISCARDFILE " .
@discardfile[$fpart] . "\n";
    }
    print CTLFILE
"$params{'load_insert_type'}\n";
    print CTLFILE "into table $table\n";
    if ($dgp)
    {
        #print CTLFILE "partition
($pname$ipart)\n" if !($params{'tab_.$table._parttype'} =~ /hash/);
        print CTLFILE "partition
($intopartitions)\n" if !($params{'tab_.$table._parttype'} =~ /hash/);
        &load_ctl_tail;
    }
    $partcount = $partcount + 1;
}
&& $dgp;
&time0("End of load for Partition: $part for Table:
$table") if ($dgp);

&dump0("*wait") if !defined $params{'load_no_waits'};
} & time0("End $table load");
} & dump0("*wait");
&time0("Done data population");
} # end of dapop
}

sub sqlldr_ctl_ops
{
    $controlfiles_per_node = $dpmax / $nnodes;
    print "controlfiles_per_node $controlfiles_per_node nnodes
$nnodes\n";
    for ($i=1; $i<=$nnodes; $i++){
        @ipart[$i] = (($i-1)*$npartitions_per_node)+1;
        @ipart[$i] = 1;
        print "Offset for node $i is: @ipart[$i]\n";
    }
    for ($idpp=1; $idpp<=$controlfiles_per_node; $idpp++) {
        for ($node=1; $node<=$nnodes; $node++)
        {
            print "idpp $idpp node $node infiles_per_sqlldr
$infiles_per_sqlldr\n";
            $idp = ($node-1)*$controlfiles_per_node + $idpp;
            if ($partcount > $sqlldr_per_partition) {
                $partcount = 1;
            }
            #if (defined(@ops_nodes)){
            #    $node = $node + 1;
            #    if ($node > $#ops_nodes+1) {
            #        $node = 1;
            #    }
            #}
            #else {
            #    $node = "";
            #}
            #$dbgpar = 0;
            # create all of the "executable" load sections
            #@@ipart[$node]= int((($idp-1)*$numchild)/$dbgpar)+1;
            # this is the first partition of the new series
            &admulti();
            $ctlfile = $params{'tab_.$table._load_ctlf'};
            $ctlfile =~ s/#/Idp/g;
            $control = $ctlarea.$ctlfile;
            if ($dgp) # load this table in partition mode
            {
                $control = sprintf (" %s%s_%d_%d.ctl", $ctlarea,
$table, $idp, @ipart[$node]);
                $log = sprintf (" %s%s_%d_%d.log", $logarea, $table,
$idp, @ipart[$node]);
            }
            else
            {
                if ($dbgpar == 1) #dbgpar is option _C for this table
                {
                    $control = sprintf (" %s%s.ctl", $ctlarea,
$table);
                    $log = sprintf (" %s%s.log", $logarea, $table);
                }
                else
                {
                    $control = sprintf (" %s%s_%d.ctl", $ctlarea,
$table, $idp);
                    $log = sprintf (" %s%s_%d.log", $logarea,
$table, $idp);
                }
            }
            $cmd = sprintf ("%s control=%s%s%s
log=%s%s%s%s%s%s%s\n",
$upwd,$control,$skip,$load,$log,$errors,$rows,
$bsize,$silent,$dirbool,$parpool);
            &dump1("*load$node");
            &dump0("*wait") if (!$parpool) && (!defined
$params{'load_no_waits'});
        }
        # create the controlfiles (fixed-length fields or delimited records)
        if ($params{'skip_mk_ldctlf'}) !~ /$table/
}

```

```

{
    &load_ctl_head;
    $infiles = 0;
    $badfiles = 0;
    $discardfiles = 0;
    $intopartitions = "BEGINNING"; # this will collect the
partition numbers that will be served.
    if ($dp < $npart) {
        if ($idp <= $remchild) {
            $nchild = $numchild+1;
        }else{
            $nchild = $numchild;
        }
    }else{
        if ($partcount <= $sqlldr_per_partition_rest) {
            $nchild = $infiles_per_sqlldr+1;
        }else{
            $nchild = $infiles_per_sqlldr;
        }
    }
    for ($jpart=1; $jpart<=$nchild; $jpart++)
    {
        #print "ipart @ipart[$node]\n";
        $idbgpar = 0 if $idbgpar >= $dbgpar;
        #@ipart[$node] = int((($idp-
1)*$nchild+$jpart)/$dbgpar);
        #@ipart[$node] = @ipart[$node]+1 if
((((($idp -1)*$nchild+$jpart)-@ipart[$node]*$dbgpar)>0);
        if ($dgp) # load in partition mode
        {
            print @ipart."\n";
            $pn=@ipart[$node];
            $partitionname = $pname.$pn;
            if (!($intopartitions =~~/ partitionname/)) {
                if ($intopartitions =~~
/BEGINNING/)
                    {
                        $intopartitions =
                    }
                else {
                    $intopartitions .=
                }
            }
            @infile[$infiles++] = "" . $ff_path . "_" .
++$idbgpar .
"._" . @ipart[$node] . "";
            @badfile[$badfiles++] = "" . $ff_path . "_" .
$ff_path . "_" . $idbgpar .
"._" . @ipart[$node] . ".dsc";
            #if ($remchild- > 0)
            #{
            #    @infile[$infiles++] = "" . $ff_path . "_" .
#            # @badfile[$badfiles++] = "" . $ff_path .
"_" . $idbgpar .
"._" . @ipart[$node] . ".bad";
            #    @discardfile[$discardfiles++] = "" .
$ff_path . "_" . $idbgpar .
"._" . @ipart[$node] . ".dsc";
            #
            #    "# @discardfile[$discardfiles++] = "" .
$ff_path . "_" . $idbgpar .
"._" . @ipart[$node] . ".dsc";
            #
        }
        elsif ($dbgpar == 1)
        {
            @infile[$infiles++] = "" . $ff_path . ".tbl";
            @badfile[$badfiles++] = "" . $ff_path . ".tbl" . ".bad";
            @discardfile[$discardfiles++] = "" .
$ff_path . "_" . $idbgpar .
".tbl";
            @infile[$infiles++] = "" . $ff_path . ".tbl" . ".dsc";
            @badfile[$badfiles++] = "" . $ff_path . "_" .
$ff_path . "_" . $idbgpar .
".tbl" . ".bad";
            @discardfile[$discardfiles++] = "" .
$ff_path . "_" . $idbgpar .
".tbl" . ".dsc";
            if ($remchild-- > 0)
            {
                @infile[$infiles++] = "" . $ff_path . ".tbl" . ".dsc";
                @badfile[$badfiles++] = "" . $ff_path . "_" .
$ff_path . "_" . $idbgpar .
".tbl" . ".bad";
                @discardfile[$discardfiles++] = "" .
$ff_path . "_" . $idbgpar .
".tbl" . ".dsc";
            }
            #print "vorher jpart $jpart ipart @ipart[$node]
iipart @iipart[$node] dbgpar $dbgpar\n";
            if (@iipart[$node] >= $dbgpar){
                @iipart[$node]=0;
                @ipart[$node]=@ipart[$node]+1;
            }
            @iipart[$node]=@ipart[$node]+1;
            #print "nacher jpart $jpart ipart @ipart[$node]
iipart @iipart[$node] dbgpar $dbgpar\n";
            }
            -$infiles;
            if ($up)
            {
                print CTLFILE "INFILE ";
                for ($fpart=0; $fpart<=$infiles; $fpart++)
                {
                    print CTLFILE @infile[$fpart] . " " if
$part < $infiles;
                    print CTLFILE @infile[$fpart] . " " if
$part == $infiles;
                }
                print CTLFILE "BADFILE " . @badfile[0] . " ";
                print CTLFILE "DISCARDFILE " .
@discardfile[0] . "\n";
            }
            else
            {
                for ($fpart=0; $fpart<=$infiles; $fpart++)
                {
                    print CTLFILE "INFILE " . @infile[$fpart] .
" ";
                    print CTLFILE "BADFILE " .
@badfile[$fpart] . " ";
                    print CTLFILE "DISCARDFILE " .
@discardfile[$fpart] . "\n";
                }
                print CTLFILE "$params{'load_insert_type'}\n";
                print CTLFILE "into table $table\n";
                if ($dgp)
                {
                    #print CTLFILE "partition
($pname@ipart[$node])\n" if !($params{'tab_.$table._parttype'} =~
/hash/);
                }
            }
        }
    }
}

```

```

        print CTLFILE "partition ($intopartitions)\n"
if !($params{'tab_.$table._parttype'} =~ /hash/);
    }
    &load_ctl_tail;
}
$partcount = $partcount + 1;
}
&dump0("*wait") if !defined $params{'load_no_waits'} &&
$dgp;
&time0("End of load for Partition: @ipart[$node] for Table:
$table") if ($dgp);

&dump0("*wait") if !defined $params{'load_no_waits'};
&time0("End $table load");
}

sub dpop_frank ## copied from Frank's version
{
    &dump0("#####
#####
# Database Population Phase");
    &time0("Begin data population");

$cur_inst = 1 if $multi; # for possible locality on SP2
($params{'load_type'} =~ /delim/) ? ($ud = 1) : ($ud = 0);
$params{'load_tables'} = $params{'tab_tables'} if !defined
$params{'load_tables'};
@load_tablelist = split(//, $params{'load_tables'});
foreach $table (@load_tablelist)
{
    &time0("Begin $table load");

$curts = $params{'tab_.$table._ts'};
$dsp = $params{'tab_.$table._load_degar'};;
$usels = 0;
$lfexist = 0;
$bfexist = 0;
$dfexist = 0;
$ffexist = 0;
$up = 0;
$dgp = 0;
$dbgpar = 1;

# see if we are using pipes

$up = 1 if ($params{'load_use_pipes'} =~ /$table/);
$dgp = 1 if ($params{'load_dbgen_partition'} =~
/$table/);
$dbgpar = $params{'load_dbgen_def_option_C'} if
defined $params{'load_dbgen_def_option_C'};
$dbgpar = $params{'load_dbgen_'.$table.'_option_C'} if
defined $params{'load_dbgen_'.$table.'_option_C'};

$params{'tab_.$table._load_ctlf'} = $table.'.ctl' if !defined
$params{'tab_.$table._load_ctlf'};
@ctlf = split(//, $params{'tab_.$table._load_ctlf'});
$err = "ctl" if ((@ctlf > 1) && (@ctlf != $dp));
@logf = split(//, $params{'tab_.$table._load_logf'});
$err = "log" if ((@logf > 1) && (@logf != $dp));
$lfexist = 1 if @logf > 0;
@badf = split(//, $params{'tab_.$table._load_badf'});
$err = "bad" if ((@badf > 1) && (@badf != $dp));
$bfexist = 1 if @badf > 0;
@datf = split(//, $params{'tab_.$table._load_datf'});
$err = "dat" if ((@datf > 1) && (@datf != $dp));

$dfexist = 1 if @datf > 0;
@disf = split(//, $params{'tab_.$table._load_disf'});
$err = "dis" if ((@disf > 1) && (@disf != $dp));
$dfexist = 1 if @diff > 0;
@filf = ();

## NT Port
## expnd all files for all partitions
if ($params{'tab_.$table._load_filf'} =~ /alltsdatafiles/)
{
    if ($params{'tab_.$table._part_ts'} =~ '/^(.*).#$/ &&
$dgp == 1)
    {
        $curts = "";
        $params{'tab_.$table._part_ts'} =~ '/^(.*).#$/';
        $tsnam = $1;
        $params{'tab_.$table._load_filf'} = "";
        $numts = $params{'tab_.$table._#part'};
        $numfil =
$params{$params{'tab_.$table._ts'}._#files'};

for ($j = 1; $j <= $numts; $j++)
{
    $tspnam = sprintf("%s%d",$tsnam,$j);
    if (defined $params{$tspnam._areas})
    {
        $tsareas =
$params{$tspnam._area} . "," . $params{$tspnam._areas};
    }
    else
    {
        $tsareas =
$params{$tspnam._area};
        for ($i = 1; $i < $numfil; $i++)
        {
            $tsareas = $tsareas . ",";
        }
    }
    $tsarea[$j] = [ split(//, $tsareas) ];
}
for ($i = 1; $i <= $numfil; $i++)
{
    for ($j = 1; $j <= $numts; $j++)
    {
        $tspnam = sprintf("%s%d",$tsnam,$j);
        if ($i == $numfil) && ($j ==
$numts) ?
            ($addcomma = "") :
            ($addcomma = ",");
        if ($tsarea[$j][$i-1] !~ /\|\|.\|/)
        {
            $nextfile =
sprintf("%s%s_s_%d.dbf%s",$tsarea[$j][$i-1],$tspnam,$i,$addcomma);
        }
        else
        {
# Temporay workaround for 804 & SQLLDR bugs
# $nextfile =
sprintf("%s%s_s_%d%s",$tsarea[$j][$i-1],$tspnam,$i,$addcomma);
        if (defined
$params{'tab_.$table._part_lfn'})
        {
            $nextfile =
sprintf("\|\|\|\|\|.\|\|\%s%d_%d%s",$params{'tab_.$table._part_lfn'},$j,$i,$addcomma);
        }
        else
        {

```

```

        $nextfile =
sprintf("|||||||.||||%s_%d%s",$stpname,$i,$addcomma);
    }
}
$params{'tab_.$table._load_filf'} .=
$nextfile;
}
}
else
{
    $params{'tab_.$table._load_filf'} =
$params{$curts._datafiles'};
}
}
elsif ($params{'tab_.$table._load_filf'} =~ /(^.*#\$/)
{
    $curts = "";
    $params{'tab_.$table._load_filf'} =~
/^(\.*#\$/;
    $tsnam = $1;
    $params{'tab_.$table._load_filf'} = "";
    $tsareas = $params{$tsnam.'area'} . "," .
$params{$tsnam.'areas'};
    @tsarea = split(/,/, $tsareas);
    $numfil = @tsarea;
    @dfile = split(/,/, $params{$tsnam.'datafiles'});
    $numfil = @dfile if ($numfil < @dfile);
    for ($i = 0; $i < $numfil; $i++)
    {
        ($i == $numfil - 1) ? ($addcomma = "") :
($addcomma = ",");
        if (@tsarea[0] !~ /\||\|) ||\|
        {
            $nextfile =
 sprintf("%s%s.dbf%s",@tsarea[$i],$dfile[$i],$addcomma);
        }
        else
        {
# Temporay workaround of 804 and SQLLDR bugs
#           $nextfile =
 sprintf("%s%s%s",@tsarea[$i],$dfile[$i],$addcomma);
           $nextfile =
 sprintf("|||||||.||||%s%s",$dfile[$i],$addcomma);

        }
        $params{'tab_.$table._load_filf'} .=
$nextfile;
    }
}
## NT End

@filf = split(/,/, $params{'tab_.$table._load_filf'}) if defined
$params{'tab_.$table._load_filf'};
# relax the requirement a little bit by allowing round
robining
$numfil = @filf;
## NT Port (fix the case for partition tables which has only one file
in each partition
##
##-
##  if (($numfil > 1) && ($numfil < $dp) && (($dp % $numfil)
== 0)) {
##      $p = $dp / $numfil;
##-
if (((($numfil > 1) && ($numfil < $dp) && (($dp %
$numfil) == 0)) ||
     (($dgp == 1) && ($dp == 1)))
{
$p = 1;
$p = ($dp / $numfil) if ($dp > 1);
## NT End
$fil = "";
for ($i = 0; $i < $p; $i++)
{
    if ($i == 0) {
        $fil = $params{'tab_.$table._load_filf'};
    } else {
        $fil =
join(',',$fil,$params{'tab_.$table._bad_filf'});
    }
}
@filf = split(/,/, $fil);
}

$perr = "fil" if ((@filf > 1) && ($dp != @filf) && ($dp != 1));
$ffexist = 1 if @filf > 0;
if ($err)
{
    print "Error with load parameters for table $table\n";
    print " degree is $dp, $err list has bad number of
elements\n";
    return;
}
$usels = 1 if (((($dp > 1) && (@datf == 1) &&
$params{'tab_.$table._load_datf'} !~ /\#/));
# expand all of the xxxf arrays to arrays of size $dp
@ff = ();
$dp = @filf if (($dp == 1) && ($dgp == 1));
for ($i=0; $i < $dp; $i++)
{
    $iplus = $i + 1;
    if (@ctlf > 1)
    {
        @cf[$i] = @ctlf[$i];
    }
    else
    {
        @cf[$i] = @ctlf[0];
        @cf[$i] =~ s/\#//$iplus/g;
    }
    if (@logf > 1)
    {
        @lf[$i] = @logf[$i];
    }
    else
    {
        @lf[$i] = @logf[0];
        @lf[$i] =~ s/\#//$iplus/g;
    }
    if (@badf > 1)
    {
        @bf[$i] = @badf[$i];
    }
    else
    {
        @bf[$i] = @badf[0];
        @bf[$i] =~ s/\#//$iplus/g;
    }
    if (@datf > 1)
    {
        @daf[$i] = @datf[$i];
    }
    else
    {

```

```

partitions          # if load_degpar is larger than the number
                   # and we are using pipes,
                   # then load_degpar has to be a multiple of the
number            # of partition and load_degpar/#partitions sets
of               # pipes will be setup.
per              # The goal is to maintain only one pipe/flatfile
               # sqldr.

0) {
    if (($params{'tab_.$table._#part'} > 0) &&
        ($dp > $params{'tab_.$table._#part'})) {
        if ($dp % $params{'tab_.$table._#part'} ==
0) {
            if (@datf[0] =~ /#.*/#/)
                # set number
$snump=int($i/$params{'tab_.$table._#part'}) + 1;
                # partiton number
$pnum=$i%$params{'tab_.$table._#part'} + 1;
                @daff[$i] = @datf[0];
                @daff[$i] =~ s/#/$/snump/;
                @daff[$i] =~ s/#/$/pnum/;
            } else {
                @daff[$i] = @datf[0];
                @daff[$i] =~ s/#/$/iplus/g;
            }
        } else
        {
            print "Error: #partitons for table
$table does not divide load_degpar for the table.\n";
            print "degree is $dp, number of
partitions is $params{'tab_.$table._#part'}.\\n";
            return;
        }
    } else
    {
        # assign
        @daff[$i] = @datf[0];
        @daff[$i] =~ s/#/$/iplus/g;
    }
} if (@disf > 1)
{
    @dif[$i] = @disf[$i];
}
else
{
    @dif[$i] = @disf[0];
    @dif[$i] =~ s/#/$/iplus/g;
}
if (@filf > 1)
{
    @ff[$i] = @filf[$i];
}
else
{
    # round robinning - temp fix
    @ff[$i] = @filf[0] if (@filf);
    if (defined $params{$params{'tab_.$table._ts'}._#files'})
{
    $numfil =
$params{$params{'tab_.$table._ts'}._#files};
#MP           print "$table \\n";
#MP           print "#MP
print
"$params{$params{'tab_.$table._ts'}._#files'}\\n";
$filnum = $i % $numfil + 1;
@ff[$i] =~ s/#/$/filnum/g;
} else {
    @ff[$i] =~ s/#/$/iplus/g;
}
}
}
$control = sprintf ("%s%s", $params{'load_controlfile_area'},
@cfl[0]);
$control =~ s/?/$ENV{'ORACLE_HOME'}/g;
# add code to create head and tail of control files
$controlh = sprintf ("%s%s.s.head",
$params{'load_controlfile_area'}, $table);
$controlh =~ s/?/$ENV{'ORACLE_HOME'}/g;
$controlt = sprintf ("%s%s.s.tail",
$params{'load_controlfile_area'}, $table);
$controlt =~ s/?/$ENV{'ORACLE_HOME'}/g;
open (CTLFILEH, ">$controlh");
open (CTLFILET, ">$controlt");
print CTLFILEH "----\\n";
if (!$pre72) && defined
$params{'tab_.$table._loadextent'}
{
    print CTLFILEH "options\\n";
    print CTLFILEH "(\\n";
    print CTLFILEH "storage = (initial
$params{'tab_.$table._loadextent'} next
$params{'tab_.$table._loadextent'})\\n";
    print CTLFILEH ")\\n";
}
#    print CTLFILE "unrecoverable\\n" if
($params{'load_unrecoverable'} =~ /[tT][rR][uU][eE]/);
    print CTLFILEH "unrecoverable\\n" if
($params{'load_unrecoverable'} =~ /[tT][rR][uU][eE]/);
    print CTLFILEH "load\\n";
    print CTLFILEH "-- This is where INFILE should go.\\n";
#    print CTLFILEH "$params{'load_insert_type'}\\n";
    print CTLFILEH "into table $table\\n";
}
print CTLFILET "-- This is where PARTITION is
specified.\\n";
print CTLFILET "$params{'load_insert_type'}\\n";
print CTLFILET "fields terminated by
$params{'load_field_terminator'}\\n" if ($ud == 1);
print CTLFILET "(\\n";
@tab_collist = split('/', $params{'tab_.$table._columns'});
while ($col = shift(@tab_collist))
{
    (@tab_collist == 0) ? ($addcomma = "") :
    ($addcomma = ",");
    $pos = "";
    $pos = sprintf ("position
(%s)", $params{'tab_.$table._$col._pos'}) if ($ud == 0);
    $ctline = sprintf (" % -20s %s %s$addcomma", $col,
$pos, $params{'tab_.$table._$col._loadcolx'});
    print CTLFILET "$ctline\\n";
}
print CTLFILET ")\\n";

```

```

close (CTLFILEH);
close (CTLFILET);

# create the controlfiles (fixed-length fields or delimited records)
if ($params{'skip_mk_ldctlf'} !~ /$table/)
{
    #print "control $control\n";
    open (CTLFILE, ">$control");
    print CTLFILE "--\n";
    print CTLFILE "--- $table.ctl for delimited records\n" if
($ud == 1);
    print CTLFILE "--- $table.ctl for fixed-length fields\n" if
($ud == 0);
    print CTLFILE "--\n\n";
    if (!($pre72) && defined
$params{'tab_.$table._loadextent'})
    {
        print CTLFILE "options\n";
        print CTLFILE "(\n";
        print CTLFILE "storage = (initial
$params{'tab_.$table._loadextent'} next
$params{'tab_.$table._loadextent'})\n";
        print CTLFILE ")\n";
    }
    print CTLFILE "unrecoverable\n" if
($params{'load_unrecoverable'} =~ /[tT][rR][uU][eE]/);
    print CTLFILE "load\n";
#    print CTLFILE "$params{'load_insert_type'}\n";
    print CTLFILE "into table $table\n";

    print CTLFILE "$params{'load_insert_type'}\n";
    print CTLFILE "fields terminated by
$params{'load_field_terminator'}\n" if ($ud == 1);
    print CTLFILE "(\n";
    @tab_collist = split(./, $params{'tab_.$table._columns'});
    while ($col = shift(@tab_collist))
    {
        (@tab_collist == 0) ? ($addcomma = "") : ($addcomma =
",");
        $pos = "";
        $pos = sprintf ("position
(%s)", $params{'tab_.$table._$col._pos'}) if ($ud == 0);
        $ctline = sprintf (" %20s %s %$addcomma", $col,
$pos, $params{'tab_.$table._$col._loadcolx'});
        print CTLFILE "$ctline\n";
    }
    print CTLFILE ")\n";
    close (CTLFILE);
}

# create all of the "executable" load sections
# These variables will hold for all loaders for a given table
$upwd = "";
$parbool = "";
$dirbool = "";
$silent = "";
$dismax = "";
$file = "";
$errors = "";
$rows = "";
$bsize = "";
$load = "";
$skip = "";
$dbgopt = "";
$dbgtab = "";

if ($up) {
    if ($table =~ /lineitem/)
    {
        $dbgtab = "L";
    }
}
else
{
    $dbgtab = "O";
}
if ($table =~ /orders/)
{
    $dbgtab = "S";
}
if ($table =~ /partsupp/)
{
    $dbgtab = "P";
}
if ($table =~ /part/)
{
    $dbgtab = "c";
}
if ($table =~ /customer/)
{
    $dbgtab = "n";
}
if ($table =~ /supplier/)
{
    $dbgtab = "s";
}
if ($table =~ /nation/)
{
    $dbgtab = "r";
}
if ($table =~ /region/)
{
    $dbgopt .= "-T ".$dbgtab." ";
    $dbgopt .= "-s ".$params{'scale_factor'} . " ";
    $dbgopt .= "-C ";
    $dbgopt .= ((defined
$params{'load_dbgen_.$table._option_C'}) ?
$params{'load_dbgen_.$table._option_C'}) :
$params{'load_dbgen_.$table._option_C'} : $params{'load_dbgen_def_option_C'});
    if ($dgp)
    {
        $dbgopt .= "-p -i ";
        $dbgopt .= (defined
$params{'load_dbgen_.$table._input_params'}) ?
$params{'load_dbgen_.$table._input_params'} :
$params{'load_dbgen_def_input_params'});
    }
}
$upwd = "$params{'user'}/$params{'passwd'}";
$parbool = "parallel=true" if
(($params{'tab_.$table._load_parallel'} =~ /true/) || ($dp > 1));
$dirbool = "direct=true" if
(($params{'tab_.$table._load_direct'} =~ /[Tt][Rr][Uu][Ee]/) ||
$parbool);
$silent = " silent=$params{'tab_.$table._load_silent'}" if
defined $params{'tab_.$table._load_silent'};
$dismax = " discardmax=$params{'tab_.$table._load_dismax'}" if defined
$params{'tab_.$table._load_dismax'};
$errors = " errors=$params{'tab_.$table._load_errors'}" if
defined $params{'tab_.$table._load_errors'};
$rows = " rows=$params{'tab_.$table._load_rows'}" if defined
$params{'tab_.$table._load_rows'};
$bsize = " bindsizes=$params{'tab_.$table._load_bsizes'}" if
defined $params{'tab_.$table._load_bsizes'};
if ($usels)
{
    $split = int($params{'tab_.$table._#rows'} / $dp);
    $extra = int($params{'tab_.$table._#rows'} % $dp);
    $loadval = $split;
}

```

```

$skipval = 0;
}

## NT Port (use dbgen to create flat files)
##
##      # if using pipes, create the pipes
##
##      if($up)
##      {
##          for ($i=0;$i<$dp;$i++) {
##              $cmd = sprintf("%s%s
$p\n",$params{'load_flatfile_area'},@daf[$i]);
##              &dump1("*mknod");
##
##          }
##          &dump0("*wait");
##
##      # start the dbgens
##
##      if ($dgp) {
##          $nset = int($dp /
$params{'tab_.$table._#part'});
##          $nperset = int($dbgpar / $nset);
##      }
##
##      for ($i=0;$i<$dbgpar;$i++) {
##          $cmd = $params{'load_flatfile_area'} . "\n";
##          $cmd2 = sprintf("%s -S %d", $dbgopt, ($i +
1));
##
##          if ($dgp) {
##              # if the output prefix name is specified with
#
##              # divide output file names into
$dp/#numpart sets
##              $fpre = (defined $params{'load_dbgen_'.
$stable._output_prefix'}) ?
$params{'load_dbgen_.$stable._output_prefix'} :
$params{'load_dbgen_def_output_prefix'};
##              if ($fpre =~ ^/#/) {
##                  $nnum = int($i/$nperset) + 1;
##                  $fpre =~ s/^#/${nnum}/g;
##
##              }
##              $cmd2 .= sprintf(" -o %s ", $fpre);
##          }
##
### Added 4/28? - Ari
### need to force in case pipe still there, and need to kick
### off in the background from here
##          $cmd2 = " -f " . $cmd2;
##          $cmd2 .= " & ";
##
##          $cmd2 .= "\n";
##          &dump2("*dbgen");
##
##      }
##
##      &dump0("*wait");
## NT End

for ($i=0; $i < $dp; $i++)
{
    &advmulti();
    $control = "";
    $log = "";
    $bad = "";
    $data = "";
    $discard = "";

    $control = sprintf (" control=%s%s",
$params{'load_controlfile_area'}, @cff[$i]);
}

```

```

$control = sprintf (" control=/host%s%s",
$params{'load_controlfile_area'}, @cff[$i]) if
($params{'special_machine'} eq 'ncube');

$log = sprintf (" log=%s%s", $params{'load_otherfile_area'},
@lf[$i]) if ($lfexist == 1);
$bad = sprintf (" bad=%s%s",
$params{'load_otherfile_area'}, @bf[$i]) if ($bfexist == 1);
$data = sprintf (" data=%s%s", $params{'load_flatfile_area'},
@daf[$i]) if ($dafexist== 1);
$discard = sprintf (" discard=%s%s",
$params{'load_otherfile_area'}, @dif[$i]) if ($difexist== 1);
if ($ffexist ==1)
{
    if ($curts == "")
    {
        $file = sprintf (" file=%s", @ff[$i]);
    }
    else
    {
        $file = sprintf (" file=%s%s", $params{$curts._area},
@ff[$i]);
    }
}
## NT Port
## Change to UPPER case string as a workaround for SQLLDR
$file =~ tr/a-z/A-Z/;

## NT End
if ($usels)
{
    $loadval = $loadval + 1 if ($extra > $i);
    $load = sprintf (" load=%d", $loadval);
    $skip = sprintf (" skip=%d", $skipval);
    $skipval = $skipval + $loadval;
    $loadval = $split;
}
##      if ($up)
##      {
##          $load = " load=99999999";
##      }

$cmd = sprintf
("%s%s%s%s%s%s%s%s%s%s%s%s%s%s%s%s%s%s%s%s%s\n",
$upwd,$contr
ol,$log,$bad,$dat,a,$discard,$dismax,$skip,$load,$errors,$rows,$bsiz
e,$silent,$dirbool,$parbool,$file);
&dump1("*load");
&dump0("*wait") if (!($parbool) && (!defined
$params{'load_no_waits'}));
}
&dump0("*wait") if !defined $params{'load_no_waits'};

##--      if($up)
##      {
##          for ($i=0;$i<$dp;$i++) {
##              $cmd = sprintf("rm -f
%$s\n",$params{'load_flatfile_area'},@daf[$i]);
##              &dump1("*sh");
##
##              &dump0("*wait");
##          }
##          &time0("End $table load");
##      }

$cmd = "shutdown\n"; #^^sd
&dump1("*sql");
&dump0("*wait");
&time0("Done data population");
}

```

```

sub ixcre
{
    &dump0("#####
#####");
    &dump0("# Index Creation Phase");
    &time0("Begin index creation");
    foreach $index (@indexlist)
    {
        if (defined $params{'ind_.$index._table'})
        {
            $ob_type = 'table';
            $ob_stype = 'tab';
        }
        else
        {
            $ob_type = 'view';
            $ob_stype = 'view';
        }

        &time0("Begin creating index $index");
        &advmulti();
        $cmd .= "connect $params{'user'}$/params{'passwd'};\n";
        $cmd .= "drop index $index;\n";
        $cmd .= "create ";
        if ($params{'ind_.$index._unique'} =~
/[tT][rR][uU][eE]/)
        {
            $cmd .= "unique ";
        } elsif ($params{'ind_.$index._bitmap'} =~
/[tT][rR][uU][eE]/)
        {
            $cmd .= "bitmap ";
        }
        $cmd .= "index $index\n";
        if (defined $params{'ind_.$index._$ob_type'})
        {
            $cmd .= "on $params{'ind_.$index._$ob_type}";
            ($params{'ind_.$index._$ob_stype.cols'})\n";
            $indtab = $params{'ind_.$index._$ob_type'};
        }
        else
        {
            $cmd .= "on cluster $params{'ind_.$index._cluster'}\n";
        }
        $cmd .= "pctfree $params{'ind_.$index._%f'}\n" if defined
$params{'ind_.$index._%f'};
        $cmd .= "initrans $params{'ind_.$index._it'}\n" if defined
$params{'ind_.$index._it'};
        $cmd .= "maxtrans $params{'ind_.$index._mt'}\n" if defined
$params{'ind_.$index._mt'};
        if ($params{'compatible'} =~ /7/)
        {
            $cmd .= "unrecoverable\n" if
($params{'ind_.$index._unrecoverable'} =~ /[tT][rR][uU][eE]/);
        } elsif ($params{'compatible'} =~ /8/)
        {
            $cmd .= "nologging\n" if
($params{'ind_.$index._nolg'} =~ /[tT][rR][uU][eE]/);
        }
        $cmd .= "compute statistics\n" if
($params{'ind_.$index._compstats'} =~ /[tT][rR][uU][eE]/);
        $cmd .= "tablespace $params{'ind_.$index._ts'}\n" if ((defined
$params{'ind_.$index._ts'}) && (& ($params{'skip_ts'} !~/ /index/)));
        $cmd .= "storage $params{'ind_.$index._storage'}\n" if
defined $params{'ind_.$index._storage'};
        $cmd .= "reverse\n" if ($params{'ind_.$index._reverse'}
=~ /[tT][rR][uU][eE]/);
        $cmd .= "nosort\n" if ($params{'ind_.$index._nosort'} =~
/[tT][rR][uU][eE]/);
    }
}

if ((defined $params{'ind_.$index._pardeg'}) || (defined
$params{'ind_.$index._parinst'}))
{
    $cmd .= "parallel";
    if ($params{'ind_.$index._pardeg'} =~/[dD][eE][fF][aA][uU][lL]/)
    {
        $cmd .= "\n";
    }
    else
    {
        $cmd .= "(degree
$params{'ind_.$index._pardeg'})"
        if defined $params{'ind_.$index._pardeg'};
        $cmd .= "instances
$params{'ind_.$index._parinst'}"
        if defined $params{'ind_.$index._parinst'};
        $cmd = $cmd . ")\\n";
    }
}

# deal with partitioning

if ($params{'ind_.$index._partition'} =~
/[lL][oO][cC][aA][lL]/)
{
    $numpart = $params{$ob_stype.'_'.$indtab._#part};
    $cmd .= "local";
    if (defined $params{'ind_.$indtab._partnames'})
    {
        &exp_ind_part_l;
    }
    else
    {
        $cmd .= "\\n";
    }
} elsif ($params{'ind_.$index._partition'} =~
/[gG][lL][oO][bB][aA][lL]/)
{
    $numpart = $params{'ind_.$index._#part'};
    $cmd .= "global partition by range (";
    &exp_ind_part_g;
}
$cmd .= "\\n";
&dump1("*sql");
}

# Constraints which are enabled after the load
foreach $const (@constlist)
{
    &time0("Begin creating constraint $const");
    &advmulti();

    $cmd .= "connect $params{'user'}$/params{'passwd'};\n";
    if ($params{'con_.$const._constraint'} =~ /null/)
    {
        @collist = split(/,/, $params{'con_.$const._columns'});
        $cmd .= "alter table $params{'con_.$const._table'} ";
        $cmd .= "modify ";
        while ($col = shift(@collist))
        {
            (@collist == 0) ? ($addcomma = "") : ($addcomma = ",");
            $cmd .= "$col
$params{'con_.$const._constraint'}$addcomma";
        }
        $cmd .= ");\\n";
    }
    else
    {

```

```

$cmd .= "alter table $params{'con_.$const._table'} drop
constraint $const;\n";
$cmd .= "alter table $params{'con_.$const._table'} ";
$cmd .= "add constraint $const\n";
$cmd .= " $params{'con_.$const._constraint'} key
($params{'con_.$const._columns'}) ";
if ($params{'con_.$const._has_index'} =~
/[Tt][Rr][Uu][Ee]/) {
    $cmd .= "using index";
}
if ($params{'con_.$const._disable'} =~
/[Tt][Rr][Uu][Ee]/) {
    $cmd .= "disable;\n";
} else {
    $cmd .= ";\n";
}
if ($params{'con_.$const._constraint'} =~ /foreign/) {
    $cmd .= "alter table
$params{'con_.$const._table'} ";
    $cmd .= "enable novalidate primary key;\n";
}
if ($params{'con_.$const._constraint'} =~ /foreign/) {
    $cmd .= "alter table
$params{'con_.$const._table'} ";
    $cmd .= "enable primary key";
}
if ($params{'con_.$const._has_index'} =~
/[Tt][Rr][Uu][Ee]/) {
    $cmd .= "";
} else {
    $cmd .= "using index\n";
    $cmd .= "pctfree
$params{'con_.$const._%f'}\n" if defined
$params{'con_.$const._%f'};
    $cmd .= "intrans
$params{'con_.$const._it'}\n" if defined
$params{'con_.$const._it'};
    $cmd .= "maxtrans
$params{'con_.$const._mt'}\n" if defined
$params{'con_.$const._mt'};
    $cmd .= "tablespace
$params{'con_.$const._ts'}\n" if ((defined
$params{'con_.$const._ts'}) && ($params{'skip_ts'} !~/index/));
    $cmd .= "storage
$params{'con_.$const._storage'}\n" if defined
$params{'con_.$const._storage'};
    $cmd .= "nosort\n" if
($params{'con_.$const._nosort'} =~ /true/);
    $cmd .= ";\n";
}
&dump1("*sql");
&dump0("*wait") if (($os cmp "nt") ==0);
&time0("Done creating constraint $const");
}

# Alter DOP of indexes (NT support)
if (($os cmp "nt") ==0)
{
    &dump0("*wait");
    &time0("Alter DOP of indexes");
    $cmd = "connect
$params{'user'}/$params{'passwd'};\n";
    foreach $index (@indexlist)
    {
        &advmulti();
        if (defined $params{'ind_.$index._pardeg_alter'})
        {
            $cmd .= "alter index $index parallel";
            $cmd .= " (degree
$params{'ind_.$index._pardeg_alter'});
            $cmd .= " instances
$params{'ind_.$index._parinst'});\n";
        }
        &dump1("*sql");
        &dump0("*wait");
        &time0("Done altering DOP of indexes");
        &time0("Done index creation");
    }
} # end of ixcre

sub exp_ind_part_1
{
    @ind_partnames = ();
    $params{'ind_.$index._#part'} =
        $params{$ob_stype.'_'.$params{'ind_.$index._$ob_typ
e'}._#part'};

    if (!defined $params{'ind_.$index._partnames'})
    {
        # if no partnames are specified, use a default part name
        for ($i = 1; $i <= $params{'ind_.$index._#part'}; $i++)
        {
            ($i == $params{'ind_.$index._#part'}) ? ($addcomma = "") :
                ($addcomma = ",");
            $nextfile = sprintf("%s%s%d%s", $index, "_p", $i,
$addcomma);
            $params{'ind_.$index._partnames'} =
                $params{'ind_.$index._partnames'} . $nextfile;
        }
    }

    @ind_partnames = split('/', $params{'ind_.$index._partnames'});
    if ($ind_partnames[0] =~ /\#/)
    {
        $filenn = shift(@ind_partnames);
        $savename = $filenn;
        $params{'ind_.$index._partnames'} = "";
        # indtab defined in ixcre
        for ($i = 1; $i <= $numpart; $i++)
        {
            $filenn =~ s/\#/$/g;
            ($i == $numpart) ? ($addcomma = "") : ($addcomma =
",");
            $params{'ind_.$index._partnames'} =
                $params{'ind_.$index._partnames'} . $filenn
            . $addcomma;
            $filenn = $savename;
        }
        @ind_partnames =
            split('/', $params{'ind_.$index._partnames'});
        print "Expanded $savename
to:\n$params{'ind_.$index._partnames'}\n" if $verbose;
    } else {
        if (@ind_partnames != $numpart)
        {
            print "number of partitions $numpart from the base
table $indtab does not equal to the number of partition names
defined in ind_.$index._partnames.\n";
            exit(-1);
        }
    }
    &process_ind_part_ts;

    # complete the local partition index statement
    if ($numpart >0)

```

```

{
    $cmd .= "(\n";
    for ($i=0; $i < $numpart; $i++)
    {
        $cmd .= "partition ";
        $cmd .= $ind_partnames[$i] . "\n" if @ind_partnames;
        &process_part_params('ind','%f','pctfree',$index,
            (@ind_partnames) ?
                (@ind_partnames) ?
                    $ind_partnames[$i] : ""
                );
        &process_part_params('ind','%u','pctused',$index,
            (@ind_partnames) ?
                $ind_partnames[$i] : ""
            );
        &process_part_params('ind','it','intrans',$index,
            (@ind_partnames) ?
                $ind_partnames[$i] : ""
            );
        &process_part_params('ind','mt','maxtrans',$index,
            (@ind_partnames) ?
                $ind_partnames[$i] : ""
            );
        if ((@ind_partnames) &&
            (defined
            $params{'ind_.$index.'_'.$ind_partnames[$i].'_ts'}))
        {
            $cmd .= 'tablespace '.

$params{'ind_.$index.'_'.$ind_partnames[$i].'_ts'} . "\n";
            &process_part_storage('ind',$index,$ind_partnames[$i]);
            } elsif ((@ind_partnames) &&
                defined $params{'ind_.$index.'._part_ts'})
            {
                $cmd .= 'tablespace ' . $ind_part_ts[$i] . "\n";
            &process_part_storage('ind',$index,$ind_partnames[$i]);
            } if (@ind_partnames &&
                defined
$params{'ind_.$index.'_'.$ind_partnames[$i].'_nolg'})
            {
                $cmd .= "nologging\n"
                if
($params{'ind_.$index.'_'.$ind_partnames[$i].'_nolg'}
            =~ /[tT][rR][uU][eE]/);
            } elsif (defined
$params{'ind_.$table.'._part_def_nolg'}) {
                $cmd .= "nologging\n"
                if ($params{'ind_.$index.'._part_def_nolg'}
            =~ /[tT][rR][uU][eE]/);
            }
            $cmd .= ")n";
    } # end of exp_ind_part_l

sub exp_ind_part_g
{
    @ind_partnames = ();
    @pcollist = split(//, $params{'ind_.$index.'._partcol'});
    $cmd .= "$params{'ind_.$index.'._partcol'})\n(\n";
    if (!defined $params{'ind_.$index.'._partnames'})
    {
        # if no partnames are specified, use a default part name
        for ($i = 1; $i <= $params{'ind_.$index.'._#part'}; $i++)
        {
            ($i == $params{'ind_.$index.'._#part'}) ? ($addcomma = "") :
                ($addcomma = ",");
            $nextfile = sprintf("%s%s%d%s", $index, "_p", $i,
                $addcomma);
            $params{'ind_.$index.'._partnames'} =
                $params{'ind_.$index.'._partnames'} . $nextfile;
        }
        @ind_partnames = split(//, $params{'ind_.$index.'._partnames'});
        if ($ind_partnames[0] =~ /\#/)
        {
            $filennm = $ind_partnames[0];
            $savename = $filennm;
            $params{'ind_.$index.'._partnames'} = "";
            # indtab defined in ixcre
            for ($i = 1; $i <= $numpart; $i++)
            {
                $filennm =~ s/\#/$/g;
                ($i == $numpart) ? ($addcomma = "") : ($addcomma =
",");
                $params{'ind_.$index.'._partnames'} =
                    $params{'ind_.$index.'._partnames'} . $filennm
                . $addcomma;
                $filennm = $savename;
            }
            @ind_partnames =
                split(//, $params{'ind_.$index.'._partnames'});
            print "Expanded $savename
to:\n$params{'ind_.$index.'._partnames'}\n\n" if $verbose;
        } else {
            if (@ind_partnames != $numpart)
            {
                print "number of partitions $numpart from the base
table $indtab does not equal to the number of partition names
defined in ind_.$index._partnames.\n";
                exit(-1);
            }
        }
        # process boundaries and tablespaces
        &process_ind_part_brys;
        &process_ind_part_ts;
        # complete the local partition index statement
        for ($i=0; $i < $numpart; $i++)
        {
            $cmd .= "partition " . $ind_partnames[$i] . " values less
than ";
            if ($i===$params{'ind_.$table.'._#part'}-1) {
                $cmd .= "(MAXVALUE)\n";
            } else {
                $cmd .= "(" . $ind_part_vals[$i] . ")\n";
            }
            &process_part_params('ind','%f','pctfree',$index,$ind_partnames[$i]);
            &process_part_params('ind','%u','pctused',$index,$ind_partnames[$i]);
            &process_part_params('ind','it','intrans',$index,$ind_partnames[$i]);
            &process_part_params('ind','mt','maxtrans',$index,$ind_partnames[$i]);
            if (defined
$params{'ind_.$index.'_'.$ind_partnames[$i].'_ts'})
            {

```

```

$cmd .= 'tablespace ';
$params{'ind_.$index.'_'.$ind_partnames[$i].'_ts'} . "\n";
&process_part_storage('ind','$index,$ind_partnames[$i]);
} elsif (defined $params{'ind_.$index.'._part_ts'}) {
{
    $cmd .= 'tablespace ' . $ind_part_ts[$i] . "\n";
}

&process_part_storage('ind','$index,$ind_partnames[$i]);
}
if (defined
$params{'ind_.$index.'_'.$ind_partnames[$i].'_nolg'})
{
    $cmd .= "nologging\n"
    if
($params{'ind_.$index.'_'.$ind_partnames[$i].'_nolg'}
    =~ /[tT][rR][uU][eE]/);
} elsif (defined $params{'ind_.$table.'._part_def_nolg'})
{
    $cmd .= "nologging\n"
    if ($params{'ind_.$index.'._part_def_nolg'}
        =~ /[tT][rR][uU][eE]/);
}
$cmd .= ((($i+1) == $numpart) ? "" : ",\n";
}
$cmd .= ")";
}

} # end of exp_ind_part_g

sub process_ind_part_ts
{
# is ind_<name>_part_ts is in the form of XXXX#, expand it
# else treat it as a comma separated list of ts names
if (defined $params{'ind_.$index.'._part_ts'})
{
    @ind_part_ts = split(//,$params{'ind_.$index.'._part_ts'});
    if ($ind_part_ts[0] =~ /\#/)
    {
        $filenm = shift(@ind_part_ts);
        $savename = $filenm;
        $params{'ind_.$index.'._part_ts'} = "";
        for ($i = 1; $i <= $numpart; $i++)
        {
            $filenm =~ s/\#/$/i/g;
            ($i == $numpart) ? ($addcomma = "") : ($addcomma =
",");
            $params{'ind_.$index.'._part_ts'} =
            $params{'ind_.$index.'._part_ts'} . $filenm .
$addcomma;
            $filenm = $savename;
        }
        @ind_part_ts = split(//,$params{'ind_.$index.'._part_ts'});
    } else {
        if (@ind_part_ts != $numpart)
        {
            $numpart = @ind_part_ts;
            if (($numpart % $numfil) == 0) {
                $p = $numpart / $numfil;
                $fil = "";
                for ($i = 0; $i < $p; $i++)
                {
                    if ($i == 0) {
                        $fil =
$params{'ind_.$index.'._part_ts'};
                    } else {
                        $fil =
join(',',$fil,$params{'ind_.$index.'._part_ts'});
                }
            }
        }
    }
}

```

```

for ($i=0; $i < $numpart-1; $i++) {
    $pval = $pval + $incre;
    push(@ind_part_col, $pval);
}
push(@ind_part_col, 'MAXVALUE');
}
else
{
    @ind_part_col =
split(//,$params{'ind_'.index.'_'.$col.'_partvals'});
}
}

if (@ind_part_col != $params{'ind_'.index.'#part'})
{
    printf "Number of partition boundary values %d for column
$col in global index $index doesn't match the number of partitions
($params{'ind_'.index.'#part'}) of the index\n", (#ind_part_col +
1);
    exit(1);
}
for ($i=0; $i < $params{'ind_'.index.'#part'}; $i++)
{
    ($cnt == $#pcollist) ? ($addcomma = "") : ($addcomma =
",");
    if ($ind_part_col[$i] =~
/[Mm][Aa][Xx][Vv][Aa][Ll][Uu][Ee]/) {
        $addquote = "";
    }
    if ($params{$ob_stype.'_'.$indtab.'_'.$col.'_type'} =~
/[dD][aA][tT][eE]/)
    {
        if ($i == $params{'ind_'.index.'#part'} - 1)
        {
            $ind_part_vals[$i] .= "MAXVALUE";
        } else {
            $nls_format = (defined
$params{$ob_stype.'_'.$indtab.'_'.$col.'_date_format'}) ?
$params{$ob_stype.'_'.$indtab.'_'.$col.'_date_format'} : "YYYY-
MM-DD";
            $ind_part_vals[$i] .= "to_date(\".$ind_part_col[$i].\";\";
            $ind_part_vals[$i] .= $nls_format."".$addcomma;
        }
    }
    elsif (!($params{$ob_stype.'_'.$indtab.'_'.$col.'_type'} =~
/[iI][nN][tT][eE][gG][eE][rR]/ ||
$params{$ob_stype.'_'.$indtab.'_'.$col.'_type'} =~
/[nN][uU][mM][Bb][eE][rR]/))
    {
        if ($index=~/l_ored/)
        print "Before:$ind_part_vals[$i]";
        }
        $ind_part_vals[$i] = $ind_part_vals[$i] . $addquote.
        $ind_part_col[$i] . $addquote . $addcomma ;
        if ($index=~/l_ored/)
        print "After:$ind_part_vals[$i]\n";
    }
    else {
        $ind_part_vals[$i] = $ind_part_col[$i] . $addcomma ;
    }
}
$cnt++;
}

} # end of process_ind_part_brys

sub anlyz
{
    &dump0("#####
#####");
    &dump0("# Analyze Phase");
    &time0("Begin anlyze");

    if ($params{'analyze_type'} =~ /via package dbms.stats/)
    {
        &time0("Begin via package dbms.stats analyzing");
        foreach $object (@anlyzlist)
        {
            $cmd = "connect
$params{'user'}/$params{'passwd'};\n";
            $phead="anl_ ".$object;
            $type = $params{$phead.'_object_type'};
            $type = "table" if ($params{$phead.'_object_type'} =~
/view/);
            $type = "table" if ($params{$phead.'_object_type'} =~
/viewlog/);
            $objectname = $object;
            $objectname = "MLOG\\\$_" . $object if
($params{$phead.'_object_type'} =~ /viewlog/);
            $cmd .= "execute
dbms_stats.$params{$phead.'_anl_type'}_" . $type . "_stats('$params{'
user'}')";
            $cmd .= " , estimate_percent =>
$params{$phead.'_percent}'" if (defined
$params{$phead.'_percent'});
            $cmd .= " , degree => $params{$phead.'_degree}'" if
(defined $params{$phead.'_degree'});
            $cmd .= " , granularity =>
$params{$phead.'_granularity}'" if (defined
$params{$phead.'_granularity'});
            $cmd .= " , block_sample =>
$params{$phead.'_block_sample}'" if (defined
$params{$phead.'_block_sample'});
            $cmd .= " , \"$objectname.\"" if (!$object =~
/schema/);
            $cmd .= ";\n";
            &dump1("*sql");
            &dump0("*wait") if ($object =~ /schema/);
        }
        &time0("End per schema analyzing");
    }
    else
    {
        foreach $object (@anlyzlist)
        {
            &time0("Begin analyzing $object");
            &advmulti();
            if ((($params{'anl_'.object'_type'} =~ /table/) &&
                ($params{'tab_'.object'_#part'} > 1)) {
                $tab_entry = 'tab_'.object;
                if (!defined
$params{$tab_entry.'_partnames'})
                {
                    # if no partnames are specified, use a
default part name
                    for ($i = 1; $i <=
$params{$tab_entry.'_#part'}; $i++)
                    {
                        ($i ==
$params{$tab_entry.'_#part'}) ? ($addcomma = "") :
                        ($addcomma = ",");
                        $nextfile = sprintf("%s%s%d%s",
$table."_p",
$i,
$addcomma );
                    }
                    $params{$tab_entry.'_partnames'} =
                }
            }
        }
    }
}

```

```

$params{$tab_entry.'_partnames'} . $nextfile;
}
}
@tab_partnames =
split(//,$params{$tab_entry.'_partnames'});
# if partnames is specified as XXXX#, then
expand
if ($tab_partnames[0] =~ /\#/)
{
    $filenm = shift(@tab_partnames);
    $savename = $filenm;
    $params{$tab_entry.'_partnames'} = "";
    for ($i = 1; $i <=
$params{$tab_entry.'_#part'}; $i++)
    {
        $filenm =~ s/\#/$/i/g;
        ($i ==
$params{$tab_entry.'_#part'}) ? ($addcomma = "") :
            ($addcomma = ",");

$params{$tab_entry.'_partnames'}
=
$params{$tab_entry.'_partnames'} . $filenm . $addcomma;
$filenm = $savename;
}
@tab_partnames =
split(//,$params{$tab_entry.'_partnames'});
printf("Expanded $savename
to:\n$params{$tab_entry.'_partnames'}\n") if $verbose;
} else {
    if (@tab_partnames !=

$params{$tab_entry.'_#part'})
    {
        print "Number of partitions
$params{$tab_entry.'_#part'} for $table doesn't match\n _partnames
parameter for $params{$tab_entry.'_partnames'}\n";
        exit(-1);
    }
}
@tab_partnames =
split(//,$params{'tab_'.${object}'._partnames'});
foreach $partname (@tab_partnames)
{
    $cmd = "connect
$params{'user'}/$params{'passwd'};\n";
    $cmd .= "analyze
$params{'anl_'.${object}'._type'} ${object}";
    $cmd .= "partition ($partname) ";
    if (defined
$params{'anl_'.${object}'._estimate'})
    {
        $cmd .= "estimate statistics
$params{'anl_'.${object}'._estimate'};\n";
    }
    else
    {
        $cmd .= "compute statistics;\n";
    }
    &dump1("*sql");
}
else {
    if (($params{'anl_'.${object}'._type'} =~ /index/)

&&
        (defined
$params{'ind_'.${object}'._partition'}))
    {
        $ind_entry = 'ind_'.${object};
        if ($params{'ind_'.${object}'._partition'} =~
/[IL][oO][cC][aA][IL]/) {
            $params{$ind_entry.'_#part'} =
$params{'tab_'.${params{$ind_entry.'_table'}}.'_#part'};
        }
        if (!defined
$params{$ind_entry.'_partnames'})
        {
            # if no partnames are specified, use
a default part name
            for ($i = 1; $i <=
$params{$ind_entry.'_#part'}; $i++)
            {
                ($i ==
$params{$ind_entry.'_#part'}) ?
                    ($addcomma = "") :
($addcomma = ",");
                $nextfile =
sprintf("%s%s%s%d%s",$object,"_p",
$i, $addcomma );
}
$params{$ind_entry.'_partnames'} =
$params{$ind_entry.'_partnames'} . $nextfile;
}
}
}
@ind_partnames =
split(//,$params{$ind_entry.'_partnames'});
# if partnames is specified as XXXX#, then
expand
if ($ind_partnames[0] =~ /\#/)
{
    $filenm = shift(@ind_partnames);
    $savename = $filenm;
    $params{$ind_entry.'_partnames'} =
"";

for ($i = 1; $i <=
$params{$ind_entry.'_#part'}; $i++)
{
    $filenm =~ s/\#/$/i/g;
    ($i==$params{$ind_entry.'_#part'}) ? ($addcomma = "") :
            ($addcomma = ",");

$params{$ind_entry.'_partnames'} =
$params{$ind_entry.'_partnames'} . $filenm . $addcomma;
$filenm = $savename;
}
@tab_partnames=split(//,$params{$ind_entry.'_partnames'});
printf("Expanded $savename
to:\n$params{$ind_entry.'_partnames'}\n") if $verbose;
} else {
    if (@ind_partnames !=

$params{$ind_entry.'_#part'})
    {
        print "Number of partitions
$params{$ind_entry.'_#part'} for $table doesn't match\n _partnames
parameter for $params{$ind_entry.'_partnames'}\n";
        exit(-1);
    }
}
@ind_partnames =
split(//,$params{'ind_'.${object}'._partnames'});
foreach $partname (@ind_partnames)

```

```

        {
            $cmd = "connect
$params{'user'}$/params{'passwd'};\n";
            $cmd .= "analyze
$params{'anl_.$object._type'} $object ";
            $cmd .= "partition ($partname) ";
            if (defined
$params{'anl_.$object._estimate'})
            {
                $cmd .= "estimate statistics
$params{'anl_.$object._estimate'};\n";
            }
            else
            {
                $cmd .= "compute statistics;\n";
            }
            &dump1("*sql");
        }
    } else {
        $cmd = "connect
$params{'user'}$/params{'passwd'};\n";
#      $cmd .= "analyze $params{'anl_.$object._type'} $object ";
#      $cmd .= "delete statistics;\n";
        $cmd .= "analyze
$params{'anl_.$object._type'} $object ";
        if (defined
$params{'anl_.$object._estimate'})
        {
            $cmd .= "estimate statistics
$params{'anl_.$object._estimate'};\n";
        }
        else
        {
            $cmd .= "compute statistics;\n";
        }
        &dump1("*sql");
    }
    &time0("Done analyzing $object");
}
&time0("End analyze");
}

sub chdop_old
{
    &dump0("#####
#####");
    &dump0("# Make DOP Phase");

    if (@chdolist)
        $cmd = "connect $params{'user'}$/params{'passwd'};\n";
    foreach $object (@chdolist)
    {
        if ($params{'chdop_.$object._type'} =~ /table/) {
            $cmd .= "alter table $object parallel (degree
$chdolist{$object} instances 1);\n";
        }
        else {
            $cmd .= "alter index $object parallel (degree
$chdolist{$object} instances 1);\n";
        }
    }
    foreach $object (@chstorlist)
    {
        if ($params{'chstor_.$object._type'} =~ /table/) {
            $cmd .= "alter table $object storage (next $chstorlist{$object}
pctincrease 0);\n";
        }
    }
    else {
        $cmd .= "alter index $object storage (next $chstorlist{$object}
pctincrease 0);\n";
    }
}
else {
    $cmd .= "alter index $object storage (next $chstorlist{$object}
pctincrease 0);\n";
}
}
&dump1("*sql");
}

sub chob
{
    &dump0("#####
#####");
    &dump0("# Make CHOB Phase");

    if (@choblist)
        $cmd = "connect $params{'user'}$/params{'passwd'};\n";
}
FLOOP:
while (@choblist)
{
    $object = shift(@choblist);
    if ((defined $params{'chob_tab_.$object._degpar'}) ||
        (defined $params{'chob_tab_.$object._storage'}))
        { $objecttype = 'table'; $objecttypes =
        'tab';$objectn=$object; }
    elsif ((defined $params{'chob_ind_.$object._degpar'}) ||
        (defined $params{'chob_ind_.$object._storage'}))
        { $objecttype = 'index'; $objecttypes =
        'ind';$objectn=$object; }
    elsif ((defined
$params{'chob_viewlog_.$object._degpar'}) || (defined
$params{'chob_viewlog_.$object._storage'}))
        { $objecttype = 'table'; $objecttypes =
        'viewlog';$objectn="MLOG\\$_.$object" }
    else
        {next FLOOP; }
    if (defined
$params{'chob_.$objecttypes.'_. $object._degpar'})
    {
        $cmd .= "alter $objecttype $objectn";
        if ($params{'chob_.$objecttypes.'_. $object._degpar'} =~ /[dD][eE][fF][aA][uU][lL][tT]/)
        {
            $cmd .= " parallel";
        }
        elsif
        ($params{'chob_.$objecttypes.'_. $object._degpar'} =~ /[nN][oO][pP][aA][rR][aA][lL][iI][eE][lL]/)
        {
            $cmd .= " nowrap";
        }
        else
        {
            $cmd .= " parallel
$params{'chob_.$objecttypes.'_. $object._degpar'}"
            if (defined
$params{'chob_.$objecttypes.'_. $object._degpar'});
            }
        $cmd .= ";\n";
    }
    if (defined
$params{'chob_.$objecttypes.'_. $object._storage'})
    {
        $cmd .= "alter $objecttype $objectn";
        if (defined
$params{'chob_.$objecttypes.'_. $object._storage'});
        }
}

```

```

$cmd .= " storage
$params{'chob_'.\$objecttypes.'_'.$object.'_storage'});\\n";
    }
}
if ($objecttypes eq 'tab')
{
    delete $params{'chob_tab_'.\$object.'_degpar'};
    delete $params{'chob_tab'."\$object.'_storage'};
    push (@choblist,$object);
}
}
&dump1("*sql");
}

sub expln
{
&dump0("#####
#####
# Explain Plan Phase");

$params{'qry_explain_queries'} = $params{'qry_all_queries'} if
!defined $params{'qry_explain_queries'};
if ($params{'qry_explain_queries'})
{
    $astr = "2_1";
    $astr = "2_" . $params{'db_maxinstances'} if defined
$params{'db_maxinstances'};
    &alttabs($astr);
    @qrynames = split(//, $params{'qry_explain_queries'});
    foreach $qname (@qrynames)
    {
        $cmd = "";
        $cmd .= "$params{'qry_area'}expl." . $qname . "\\n";
        $cmd2 = "";
        $cmd2 = $cmd2 . "connect
$params{'user'}/$params{'passwd'};\\n";
        $cmd2 = $cmd2 . "set longwidth 360\\n";
        if (defined $params{'qry_'.\$qname.'_text'})
        {
            $cmd2 = $cmd2 . "drop table plan_table;\\n";
            $cmd2 = $cmd2 . '@' . "$params{'dd_sql_area'}".
"utlxplan.sql\\n";
            $cmd2 = $cmd2 . "explain plan for\\n";
            $cmd2 = $cmd2 . "$params{'qry_'.\$qname.'_text'}\\n";
            $cmd2 = $cmd2 . "select level, rpad(lpad('' ,2*(level-1)) ||
operation || '' || object_name || '' || options || '(' || object_node || ',' ||
cost || ',' || cardinality || ')',68)\\n";
            $cmd2 = $cmd2 . "from plan_table\\n";
            $cmd2 = $cmd2 . "connect by parent_id=prior id start
with id=0;\\n";
            $cmd2 = $cmd2 . "select level, lpad('' ,2*(level-1)) ||
operation || '' || object_name || '' || options || '(' || object_node || ')',\\n";
            $cmd2 = $cmd2 . "other_tag, other\\n";
            $cmd2 = $cmd2 . "from plan_table\\n";
            $cmd2 = $cmd2 . "connect by parent_id=prior id start
with id=0;\\n";
            $cmd2 = $cmd2 . "select level, lpad('' ,2*(level-1)) ||
operation || '' || object_name || '' || options || '(' || object_node || ')',\\n";
            $cmd2 = $cmd2 . "other_tag, other\\n";
            $cmd2 = $cmd2 . "from plan_table\\n";
            $cmd2 = $cmd2 . "connect by parent_id=prior id start
with id=0;\\n";
        }
    }
}
else
{
    if (defined $params{'qry_'.\$qname.'_texte'})
    {
        @expln_texts = split(//,
$params{'qry_'.\$qname.'_texte'});
        $text_index = 1;
        while ($expln_next = shift (@expln_texts))
        {
EXPLNLOOP:
            while ($expln_next ne ('text'."\$text_index"))
            {
                if (!defined
$params{'qry_'.\$qname.'_text'."\$text_index"})
                {
                    print "\\n** Missing text for $qname:
$text_index\\n";
                    last EXPLNLOOP;
                }
                $cmd2 = $cmd2 . "
drop table plan_table;\\n";
                $cmd2 = $cmd2 . '@' . "$params{'dd_sql_area'}".
"utlxplan.sql\\n";
                $cmd2 = $cmd2 . "explain plan for\\n";
                $sqltext = 'qry_'.\$qname.'_'.$expln_next;
                $cmd2 = $cmd2 . "$params{$sqltext}\\n";
                $cmd2 = $cmd2 . "select level, rpad(lpad('' ,2*(level-1)) ||
operation || '' || object_name || '' || options || '(' || object_node || ',' ||
cost || ',' || cardinality || ')',68)\\n";
                $cmd2 = $cmd2 . "from plan_table\\n";
                $cmd2 = $cmd2 . "connect by parent_id=prior id start
with id=0;\\n";
                $cmd2 = $cmd2 . "select level, lpad('' ,2*(level-1)) ||
operation || '' || object_name || '' || options || '(' || object_node || ')',\\n";
                $cmd2 = $cmd2 . "other_tag, other\\n";
                $cmd2 = $cmd2 . "from plan_table\\n";
                $cmd2 = $cmd2 . "connect by parent_id=prior id start
with id=0;\\n";
                $text_index++;
            }
            while (defined
$params{'qry_'.\$qname.'_text'."\$text_index"})
            {
                $cmd2 = $cmd2 . "
$params{'qry_'.\$qname.'_text'."\$text_index}\\n";
                $text_index++;
            }
            else
            {
                print "\\n** No sql text or texte corresponding to
$qname\\n";
            }
        }
        &dump2("*sql2");
    }
}
}

sub query
{
&dump0("#####
#####
# Query Phase");

$params{'qry_run_queries'} = $params{'qry_all_queries'} if
!defined $params{'qry_run_queries'};
if ($params{'qry_run_queries'})
{
    $params{'qry_config'} = "1_1" if !defined
$params{'qry_config'};
    @qconfs = split(//, $params{'qry_config'});
    foreach $qconf (@qconfs)
    {
        &alttabs($qconf);
}
}

```

```

if ($params{'qry_separate_queries'} !~ /true/)
{
    $cmd = "";
    $cmd .= "$params{'qry_area'}qry.all." . $qconf . "\n";
    $cmd2 = "";
    $cmd2 = $cmd2 . "set timing on\n";
    $cmd2 = $cmd2 . "connect
$params{'user'}/$params{'passwd'};\n";
}
@qrynames = split(//, $params{'qry_run_queries'});
foreach $qname (@qrynames)
{
    if ($params{'qry_separate_queries'} =~ /true/)
    {
        $cmd = "";
        $cmd .= "$params{'qry_area'}qry." . $qname . ":" .
$qconf . "\n";
        $cmd2 = "";
        $cmd2 = $cmd2 . "set timing on\n";
        $cmd2 = $cmd2 . "connect
$params{'user'}/$params{'passwd'};\n";
    }
    for ($i = 0; $i < $params{'qry_number_trials'}; $i++)
    {
        if (defined $params{'qry_'.$qname.'_text'})
        {
            $cmd2 = $cmd2 . "$params{'qry_'.$qname.'_text'}\n";
        }
        else
        {
            $text_index = 1;
            WTLLOOP:
            while(1)
            {
                if (defined
$params{'qry_'.$qname.'_text'$text_index})
                {
                    $cmd2 = $cmd2 . "
$params{'qry_'.$qname.'_text'$text_index}\n";
                    $text_index++;
                }
                else
                {
                    print "No sql text corresponding to $qname\n" if
($text_index == 1);
                    last WTLLOOP;
                }
            }
            if ($params{'qry_separate_queries'} =~ /true/)
            {
                &dump2("*sql2");
            }
        }
        if ($params{'qry_separate_queries'} !~ /true/)
        {
            &dump2("*sql2");
        }
    }
}
#*****
#*****
#*****
# Utility Functions
#*****
#*****

```

```

*****  

*****  

*****  

*****  

*****  

sub premulti
{
# Some multi-instance stuff
$num_inst = $params{$phase->{'_num_inst'}};  

if ($num_inst > 1)
{
    $multi = 1;
    $cur_inst = 1;
    &advmulti(); # Make sure it's set to some appropriate value
}
else
{
    $multi = 0;
}
}  

sub advmulti
{
if ($multi)
{
    &setinst($cur_inst);
    $cur_inst = ($cur_inst % $num_inst) + 1;
}
}  

sub startdb #does not work for OPS systems!!
# if you have an OPS system use startdb_old
{
    $initora=$params{'startupfile'.'$_[0]'};  

    $mounttype=$_[1];
    $cmd = "startup pfile=$initora $mounttype\n";
    &dump1("*sql");
}
sub startdb_old
{
# Get init.oras for startup/shutdown
$checkios = 0;
$ofile = sprintf ("%s%s", $params{'dbs_area'},  

"init_".$params{'oracle_sid'}.ora");
$checkios = 1 if (! -e $ofile);
for ($j = 1; $j <= $num_inst; $j++)
{
    $iofname[$j] = sprintf ("%s%s", $params{'dbs_area'},  

"init".'$j'."_".$params{'oracle_sid'}.ora");
    $iofname[$j] = sprintf ("host% s", $iofname[$j])
        if ($params{'special_machine'} eq 'ncube');
    $iofname[$j] =~ s/\?/$ENV{'ORACLE_HOME'}/g;
    $checkios = 1 if (! -e $iofname[$j]);
}
&createios() if $checkios;  

# startup exclusive/shared single-instance/multi-instance
if ($multi)
{
    for ($loop = 1; $loop <= $num_inst; $loop++)
    {
        &setinst($loop);
        $cmd = "startup shared pfile=$iofname[$loop];\n";
        &dump1("*sql");
        &dump0("*wait") if ($params{'sync_startup'} =~ /true/);
    }
}
else
{
    $cmd = "startup pfile=$iofname[1];\n";
    &dump1("*sql");
}
}
```

```

    &dump0("*wait");
}

sub shutdb
{
# shutdown whatever might be running
if ($multi)
{
    for ($loop = $num_inst; $loop >= 1; $loop--)
    {
        &setinst($loop);
        $cmd = "shutdown $params{'shutdown_level'};\n";
        &dump1("*sql");
    }
}
else
{
    $cmd = "shutdown $params{'shutdown_level'};\n";
    &dump1("*sql");
}
&dump0("*wait");
}

sub create_ts
{
    $tsname = shift(@_);
    # 1. parameter is the list of
    # tablespaces

    &dump0("# creating $params{'user'}'s $tsname tablespace");
    &advmulti();
    @ts_datafiles = split(//, $params{$tsname.'_datafiles'});
    $ts_datafile = shift (@ts_datafiles);

    if ($params{$tsname.'_managed'} =~ /[uU][sS][eE][rR]/)
    {
        # user managed
        temporary tablespace
        if ($params{$tsname.'_temporary'} =~
/[tT][rR][uU][eE]/)
        {
            # temporary tablespace
            $cmd .= "drop tablespace $tsname including
contents;\n";
            $cmd .= "create tablespace $tsname
temporary\n";
        }
        else
            # user managed permanent
        tablespace
        {
            $cmd .= "drop tablespace $tsname including
contents;\n";
            $cmd .= "create tablespace $tsname\n";
        }
        $cmd .= "datafile '$params{$tsname.'_area'}$ts_datafile'
size $params{$tsname.'_first_size'} $params{$tsname.'_options'}\n";
        $cmd .= "default storage $params{$tsname.'_storage'}\n";
    if defined $params{$tsname.'_storage'};
    }
    else
        # system managed temporary tablespace
    {
        if ($params{$tsname.'_temporary'} =~
/[tT][rR][uU][eE]/)
        {
            # temporary tablespace
            $cmd .= "drop tablespace $tsname including
contents;\n";
            $cmd .= "create temporary tablespace
$tsname\n";
            $cmd .= "tempfile
'$params{$tsname.'_area'}$ts_datafile' size
$params{$tsname.'_first_size'} $params{$tsname.'_options'}\n";
            $cmd .= "extent management local\n";
        }
        if (defined ($params{$tsname.'_extent_size'}) ||
&& ($params{$tsname.'_extent_size'} =~
/[aA][uU][Tt][oO][aA][iL][iL][oO][cC][aA][tT][eE]/))
        {
            $cmd .= "autoallocate\n";
        }
        elsif (defined
($params{$tsname.'_extent_size'}) &&
!($params{$tsname.'_extent_size'} =~
/[aA][uU][Tt][oO][aA][iL][iL][oO][cC][aA][tT][eE]/))
        {
            $cmd .= "uniform size
".$params{$tsname.'_extent_size'}."\n";
        }
        else
        {
            $cmd .= "uniform";
        }
    }
    else
        # system managed permanent
    tablespace
    {
        $cmd .= "drop tablespace $tsname including
contents;\n";
        $cmd .= "create tablespace $tsname\n";
        $cmd .= "datafile
'$params{$tsname.'_area'}$ts_datafile' size
$params{$tsname.'_first_size'} $params{$tsname.'_options'}\n";
        $cmd .= "extent management local\n";
        if (defined ($params{$tsname.'_extent_size'}) &&
($params{$tsname.'_extent_size'} =~
/[aA][uU][Tt][oO][aA][iL][iL][oO][cC][aA][tT][eE]/))
        {
            $cmd .= "autoallocate\n";
        }
        elsif (defined ($params{$tsname.'_extent_size'}) &&
!($params{$tsname.'_extent_size'} =~
/[aA][uU][Tt][oO][aA][iL][iL][oO][cC][aA][tT][eE]/))
        {
            $cmd .= "uniform size
".$params{$tsname.'_extent_size'}."\n";
        }
        else
        {
            $cmd .= "uniform";
        }
    }
    $cmd .= "nologging" if ($params{$tsname.'_nolg'} =~
/[tT][rR][uU][eE]/);
    $cmd .= "\n";
    &dump1("*sql");
}
}

sub add_ts_rollback
{
    $ts_undo_l = $_[0];
    @ts_datafiles = split(//, $params{'ts_'.$ts_undo_l.'_datafiles'});
    $ts_datafile = shift (@ts_datafiles);
    $cmd .= "create tablespace ts_.$ts_undo_l.\n";
    $cmd .= "datafile '$params{'ts_undo_area'}$ts_datafile' size
$params{'ts_'.$ts_undo_l.'_first_size'}
$params{'ts_'.$ts_undo_l.'_options'}\n";
    &dump1("*sql");
    &dump0("*wait");
    &add_dfs("ts_.$ts_undo_l");
}

# currently set up for the foreground - maybe should be changed
&dump0("# creating extra rollback segments");
for ($i = 1; $i <= $params{'ts_'.$ts_undo_l.'_rs'}; $i++)

```

```

{
    $cmd .= "create public rollback segment
$params{'ts_.$ts_undo_l._rs_prefix'}$!";
    $cmd .= " storage $params{'ts_undo_rs_storage'}" if defined
$params{'ts_.$ts_undo_l._rs_storage'};
    $cmd .= " tablespace ts_.$ts_undo_l" if ($params{'skip_ts'} !~
/$ts_undo_l/);
    $cmd .= "\n";
}
&dump1(*sql");
&dump0(*wait");

}

sub add_dfs
{
    $tsname = shift(@_);
    &dump0("# adding $params{'user'}'s $tsname datafiles");
    @ts_datafiles = split(/ /, $params{$tsname.'_datafiles'});
    $ts_datafile = shift (@ts_datafiles); # drop first one
    $cur_inst = 2 if $multi; # for possible locality on SP2
    for ($i = 1; $i < $params{$tsname.'_#files'}; $i++)
    {
        $ts_datafile = shift (@ts_datafiles);
        &advmulti();
        $cmd .= "alter tablespace $tsname\n";
        if ($params{$tsname.'_managed'} =~ /[uU][sS][eE][rR]/)
        {
            # user managed temporary tablespace
            $cmd .= " add datafile ";
        }
        else
        {
            # system managed temporary tablespace
            if ($params{$tsname.'_temporary'} =~ /true/)
            {
                $cmd .= " add tempfile ";
            }
            else
            {
                $cmd .= " add datafile ";
            }
        }
        $cmd .= "$params{$tsname.'_area'}$ts_datafile' size
$params{$tsname.'_size'} $params{$tsname.'_options'};\n";
        &dump1(*sql");
    }
}

sub createios
{
    push (@iokv, "db_name=$params{'oracle_sid'}");
    push (@iokv, "control_files=$params{'io_control_files'}");
    push (@iokv, "db_block_buffers=1000");
    push (@iokv, "shared_pool_size=35000000");
    push (@iokv, "parallel_max_servers=144");
    push (@iokv, "parallel_min_servers=0");
    push (@iokv, "max_dump_file_size=5000");
    push (@iokv, "audit_trail=FALSE");
    push (@iokv, "global_names=FALSE");
    # push (@iokv, "commit_point_strength=1");
    # push (@iokv, "dblink_encrypt_login=true");
    # push (@iokv, "db_block_size=16384");
    push (@iokv, "db_block_size=8192");
    push (@iokv, "db_file_multiblock_read_count=32");
    push (@iokv, "processes=256");
    push (@iokv, "sessions=256");
    push (@iokv, "transactions=512");
    push (@iokv, "transactions_per_rollback_segment=20");
    push (@iokv, "max_rollback_segments=256");
    push (@iokv, "distributed_transactions=0");
    push (@iokv, "nls_date_format=YYYY-MM-DD");
}

push (@iokv, "db_files=1023");
push (@iokv, "open_cursors=1024");
push (@iokv, "optimizer_mode=CHOOSE");
push (@iokv, "optimizer_percent_parallel=100");
push (@iokv, "sort_area_size=3000000");
push (@iokv, "always_semi_join=HASH");
push (@iokv, "parallel_broadcast_enabled=TRUE");
push (@iokv, "optimizer_features_enable=8.0.4");
push (@iokv, "compatible=8.0.4");
push (@iokv, "hash_multiblock_io_count=64");
push (@iokv, "always_anti_join=HASH");

$fdata = sprintf ("%s%s", $params{'dbs_area'},
"init_$params{'oracle_sid'.ora}");
$fdata =~ s/^\?/$ENV{'ORACLE_HOME'}/g;
if ($params{'skip_mk_initoras'} !~/include/)
{
    open (IOFILE, ">$ofile");
    print IOFILE "# Init.ora include file created by bumpx.pl\n";
    while ($kv = shift(@iokv))
    {
        $kv =~ /(.*)=(.*)/;
        $entry = sprintf ("%25s = %s\n", $1, $2);
        print IOFILE $entry;
    }
    if (defined $params{'io_ifile'})
    {
        $entry = sprintf ("%25s = %s\n", "ifile",
$params{'io_ifile'});
        print IOFILE $entry;
    }
    close (IOFILE);
}

for ($j = 1; $j <= $num_inst; $j++)
{
    $ofname[$j] = sprintf ("%s%s", $params{'dbs_area'},
"init_$j.$params{'oracle_sid'.ora}");
    $ofname_opn = $ofname[$j];
    $ofname_opn =~ s/^\?/$ENV{'ORACLE_HOME'}/g;
    if ($params{'skip_mk_initoras'} !~/instance/)
    {
        open (IOFILE, ">$ofname_opn");
        print IOFILE "# Init.ora for instance $j created by
bumpx.pl\n";
        print IOFILE "thread = $j\n";
        if ($params{'special_machine'} ne 'ncube');
        print IOFILE "ifile = $ofile\n";
        close (IOFILE);
    }
    $ofname[$j] = sprintf ("/host%s", $ofname[$j])
        if ($params{'special_machine'} eq 'ncube');
}
}

sub create_objects
{
    $obj_type = shift(@_);
    @obj_objectlist = @_;
    $cmd .= "connect $params{'user'}/$params{'passwd'};\n";
    foreach $object (@obj_objectlist)
    {
        &create_object;
    }
    &dump1(*sql");
}

```

```

sub create_object
{
    # this routine only creates one object
    # need it because of the creation of materialized views

    $ob_entry = $ob_type.'_'.$object;
    if (($ob_type cmp 'tab') == 0) # we are creating a table
    {
        $cmd .= "drop table $object;\n";
        $cmd .= "create table $object";
    }
    elsif (($ob_type cmp 'view') == 0) # we are creating a view
    {
        if ($params{$ob_entry.'_creation_type'} =~
            /[dD][iI][rR][eE][cC][tT]/) # direct
        {
            $cmd .= "drop materialized view $object;\n";
            $cmd .= "create materialized view $object";
        }
        else # with table
        {
            $cmd .= "drop table $object;\n";
            $cmd .= "create table $object";
        }
    }
    if (($ob_type cmp 'viewlog') == 0) # we have a viewlog
    {
        $cmd .= "drop materialized view log on $object;\n";
        $cmd .= "create materialized view log ";
        $cmd .= "on $object\n";
    }
    elsif (!$ob_type eq 'view') ||
           (($ob_type eq 'view') &&
            ($params{$ob_entry.'_creation_type'} =~
                /[wW][iI][tT][hH][s][tT][aA][bB][iL][eE]/))
    {
        $cmd .= "(\n";
        $cmd .= "$params{$ob_entry.'_cons'}\n" if defined
        $params{$ob_entry.'_cons'};
        @ob_collist = split(//, $params{$ob_entry.'_columns'});
        &add_columns; # the list of columns are in
        @ob_collist
        $cmd .= ")\n";
    }
    else
    {
        $cmd .= "\n";
    }
    if (defined $params{$ob_entry.'_cluster'})
    {
        $cmd .= "cluster $params{$ob_entry.'_cluster'}\n";
        ($params{$ob_entry.'_clucols'})\n";
    }
    else
    {
        # add organization and pctthreshold for index only tables
        $cmd .= "organization $params{$ob_entry.'_org'}\n" if
        defined $params{$ob_entry.'_org'};
        $cmd .= "pctthreshold $params{$ob_entry.'_%t'}\n" if
        defined $params{$ob_entry.'_%t'};
        $cmd .= "pctfree $params{$ob_entry.'_%f'}\n" if defined
        $params{$ob_entry.'_%f'};
        $cmd .= "pctused $params{$ob_entry.'_%u'}\n" if
        defined $params{$ob_entry.'_%u'};
        $cmd .= "intrans $params{$ob_entry.'_it'}\n" if defined
        $params{$ob_entry.'_it'};
    }
}

$cmd .= "maxtrans $params{$ob_entry.'_mt'}\n" if
defined $params{$ob_entry.'_mt'};
$cmd .= "tablespace $params{$ob_entry.'_ts'}\n" if
defined $params{$ob_entry.'_ts'};
$cmd .= "storage $params{$ob_entry.'_storage'}\n" if
defined $params{$ob_entry.'_storage'};
if (defined $params{$ob_entry.'_of_ts'})
{
    # overflow tablespace specs
    $cmd .= "overflow ";
    $cmd .= "pctfree $params{$ob_entry.'_of_%f'} " if
defined $params{$ob_entry.'_of_%f'};
    $cmd .= "pctused $params{$ob_entry.'_of_%u'} " if
defined $params{$ob_entry.'_of_%u'};
    $cmd .= "intrans $params{$ob_entry.'_of_it'} " if
defined $params{$ob_entry.'_of_it'};
    $cmd .= "maxtrans $params{$ob_entry.'_of_mt'} " if
defined $params{$ob_entry.'_of_mt'};
    $cmd .= "tablespace $params{$ob_entry.'_of_ts'} " if
defined $params{$ob_entry.'_of_ts'};
    $cmd .= "storage $params{$ob_entry.'_of_storage'}\n"
if defined $params{$ob_entry.'_of_storage'};
}
if ((defined $params{$ob_entry.'_pardeg'}) || (defined
$params{$ob_entry.'_parinst'}))
{
    $cmd .= "parallel";
    if ((defined $params{$ob_entry.'_pardeg'}) &&
        ($params{$ob_entry.'_pardeg'} =~
            /[dD][eE][fF][aA][uU][iL][tT]/))
    {
        $cmd .= "\n";
    }
    else
    {
        $cmd .= "(degree $params{$ob_entry.'_pardeg'} " if
defined $params{$ob_entry.'_pardeg'};
        $cmd .= "instances $params{$ob_entry.'_parinst'} " if
defined $params{$ob_entry.'_parinst'};
        $cmd .= ")")\n";
    }
    $cmd .= "nologging\n" if ($params{$ob_entry.'_nolg'} =~
        /[tT][rR][uU][eE]/);
    $cmd .= "cache\n" if ($params{$ob_entry.'_cache'} =~
        /[tT][rR][uU][eE]/);

    # add partition support
    if (defined $params{$ob_entry.'_#part'} &&
        ($params{$ob_entry.'_#part'} > 1))
    {
        &expand_partitions ($ob_entry,$object,$ob_type);
        # no partitioning
    }
}

if (($ob_type cmp 'view') == 0)
{
    $cmd .= "enable row movement\n" if
defined($params{$ob_entry.'_partype'});
        if ($params{$ob_entry.'_creation_type'} =~
            /[dD][iI][rR][eE][cC][tT]/)
    {
        $cmd .= "BUILD
".$params{$ob_entry.'_build_when'}."\n" if (defined
$params{$ob_entry.'_build_when'});
        &add_refresh_clause($ob_entry);
    }
}

```

```

if ($params{$ob_entry.'_rewrite'} =~ /[tT][rR][uU][eE]/)
{
    $cmd .= "enable query rewrite\n";
}
elsif ($params{$ob_entry.'_rewrite'} =~
/[fF][aA][lL][sS][eE]/)
{
    $cmd .= "disable query rewrite\n";
}
}

if (defined $params{$ob_entry.'_as_select'}) # as select (here I
only copy a variable called <viewname>_define_as_select
{
    &print_as_select_stm($params{$ob_entry.'_as_select'});
    $cmd .= "\n";
}

if (($ob_type cmp 'viewlog') == 0)
{
    $cmd .= "with rowid\n";
    if (defined $params{$ob_entry.'_columns'})
    {
        $cmd .= "(\n";
        @ob_collist = split(/,/
$params{$ob_entry.'_columns'});
        $add_columns; # the list of columns are in
@ob_collist
        $cmd .= ")\n";
    }
    $cmd .= "including new values\n";
}

if ($params{$ob_entry'_creation_type'} =~
/[wW][iI][tT][hH][sS][tT][aA][bB][lL][eE]/)
{
    $cmd .= ";ndrop materialized view $object;\n";
    $cmd .= "create materialized view $object\n";
    $cmd .= "BUILD
".$params{$ob_entry'_build_when'}. "\n" if (defined
$params{$ob_entry'_build_when'});
    $cmd .= "on prebuilt table \n";
#    if (defined $params{$ob_entry'_precision'})
#
#        ($params{$ob_entry'_precision'} =~
/[rR][eE][dD][uU][cC][eE][dD]/) ?
#            $cmd .= "WITH REDUCED PRECISION \n"
#            : $cmd .= "WITHOUT REDUCED PRECISION \n";
#
}

&add_refresh_clause($ob_entry);

if ((defined $params{$ob_entry'_rewrite'}) &&
($params{$ob_entry'_rewrite'} =~ /[tT][rR][uU][eE]/))
{
    $cmd .= "enable query rewrite\n";
}
elsif ($params{$ob_entry'_rewrite'} =~
/[fF][aA][lL][sS][eE]/)
{
    $cmd .= "disable query rewrite\n";
}

$cmd .= "refresh " . $params{$ob_entry'_refresh'} . "\n"
if (defined $params{$ob_entry'_refresh'});
    $cmd .= $params{$ob_entry'_queryrw'} . "\n" if (defined
$params{$ob_entry'_queryrw'});
        &print_as_select_stm($params{$ob_entry'_as_select'});
}
}

$cmd .= "\n";
}

sub add_columns
{
    while ($col = shift(@ob_collist))
    {
        (@ob_collist == 0) ? ($addcomma = "") : ($addcomma =
",");
        if (($ob_type cmp 'tab') == 0 )
        {
            $columntype = $params{$ob_entry.'_'. $col.'_type'};
        }
        else
        {
            $columntype = "";
        }
        $nextline = sprintf (" % -20s %s %s$addcomma\n",
$col, $columntype, $params{$ob_entry.'_'. $col.'_cons'});
        $cmd .= $nextline;
    }
}

sub add_refresh_clause
{
    $ob_entry = $_[0];
    if (defined $params{$ob_entry'_refresh_how'})
    {
        $cmd .= "REFRESH
".$params{$ob_entry'_refresh_how'}. "\n";
        $cmd .= "ON
".$params{$ob_entry'_refresh_when'}. "\n" if (defined
$params{$ob_entry'_refresh_when'});
    }
}

sub print_as_select_stm
{
    if ($_[0] =~ /\/*/)
    {
        ($beforehint,$rest)=split(/\/*/,$_[0]);
        ($hint,$as_select)=split(/\*\//,$rest);
    }
    else
    {
        $as_select = $_[0];
        $hint="^";
    }
    $as_select =~ s/(, )|(|\t)/\n /g;
    $as_select =~ s/from|FROM/nFROM\n/g;
    $as_select =~ s/select|SELECT/SELECT\n/g;
    $as_select =~ s/where|WHERE/nWHERE\n/g;
    $as_select =~ s/group by|GROUP BY/nGROUP BY\n/g;
    $as_select =~ s/ and | AND \n AND \n/g;
    $as_select =~ s/ or | OR \n OR \n/g;
    $cmd .= "as select \n";
    $cmd .= "$hint$hint$hint" if ($hint !~ /^/);
    $cmd .= $as_select;
}

sub create_clusters
{
    $cmd .= "connect $params{'user'}/$params{'passwd'};\n";
    foreach $cluster (@clulist)
    {
        $cmd .= "drop cluster $cluster including tables;\n";
        $cmd .= "create cluster $cluster (\n";
        @clu_collist = split(/,/, $params{'clu_'. $cluster.'_columns'});
        while ($col = shift(@clu_collist))
        {
}
}
}

```

```

{
    (@clu_collist == 0) ? ($addcomma = "") : ($addcomma =
",");

    $nextline = sprintf ("  %-20s %s$addcomma\n", $col,
$params{'clu_.$cluster.'.$col.'_type'});
    $cmd .= $nextline;
}

$cmd .= "\n";
$cmd .= "pcffree $params{'clu_.$cluster.'%f'}\n" if defined
$params{'clu_.$cluster.'%f'};

$cmd .= "pcusred $params{'clu_.$cluster.'%u'}\n" if defined
$params{'clu_.$cluster.'%u'};

$cmd .= "intrans $params{'clu_.$cluster.'it'}\n" if defined
$params{'clu_.$cluster.'it'};

$cmd .= "maxtrans $params{'clu_.$cluster.'mt'}\n" if defined
$params{'clu_.$cluster.'mt'};

$cmd .= "size $params{'clu_.$cluster.'size'}\n" if defined
$params{'clu_.$cluster.'size'};

$cmd .= "tablespace $params{'clu_.$cluster.'ts'}\n" if defined
$params{'clu_.$cluster.'ts'};

$cmd .= "storage $params{'clu_.$cluster.'storage'}\n" if
defined $params{'clu_.$cluster.'storage'};

$cmd .= "index\n" if ($params{'clu_.$cluster.'index'} =~
true);

if (defined $params{'clu_.$cluster.'hashkeys'})
{
    $cmd .= "hash is $params{'clu_.$cluster.'hashcol'} " if
defined $params{'clu_.$cluster.'hashcol'};
    $cmd .= "hashkeys $params{'clu_.$cluster.'hashkeys'}\n";
}

if ((defined $params{'clu_.$cluster.'pardeg'}) || (defined
$params{'clu_.$cluster.'parinst'}))
{
    $cmd .= "parallel ";
    $cmd .= "degree $params{'clu_.$cluster.'pardeg'} " if
defined $params{'clu_.$cluster.'pardeg'};

    $cmd .= "instances $params{'clu_.$cluster.'parinst'}" if
defined $params{'clu_.$cluster.'parinst'};
    $cmd .= "\n";
}

$cmd .= "cache\n" if $params{'clu_.$cluster.'cache'} =~
>true/;

$cmd .= "\n";
# Now, create the cluster index, if necessary
if ($params{'clu_.$cluster.'index'} =~ true)
{
    $cluindex = "ind_.$cluster";
    $cmd .= "drop index $cluindex;\n";
    $cmd .= "create index $cluindex on cluster $cluster;\n";
}
}

&dump1("*sql");
}

sub expand_partitions
{
    # *MP* parameterize procedure: changed $tab_entry into $ob_entry
    1. parameter $_[0]
    #           $table into $ob          2. parameter $_[1]
    #           introduced $ob_type      3. parameter $_[2]

    {
        $ob_entry = $_[0];
        $ob = $_[1];
        $ob_type = $_[2];

        if ($params{$ob_entry.'_parttype'} =~ /[rR][aA][nN][gG][eE]/)
        {
            $cmd .= "partition by range (" .
$params{$ob_entry.'_partcol'} . ")\\n\\n";
            &expand_partitions_doit($ob_entry,$ob,$ob_type);
        }
        elsif ($params{$ob_entry.'_parttype'} =~ /[hH][aA][sS][hH]/)
        {
            $cmd .= "partition by hash (" .
$params{$ob_entry.'_partcol'} . ")\\n";
            $cmd .= "partitions ". $params{$ob_entry.'_#part'} . "\\n";
        }
        elsif ($params{$ob_entry.'_parttype'} =~
/[cC][oO][mM][pP][oO][sS][iI][tT][eE]/)
        {
            $cmd .= "partition by range (" .
$params{$ob_entry.'_partcol'} . ")\\n";
            $cmd .= "subpartition by hash(" .
$params{$ob_entry.'_subpartcol'} . ")\\n";
            $cmd .= "subpartitions ";
            $params{$ob_entry.'_#subpart'} . "\\n\\n";
            &expand_partitions_doit($ob_entry,$ob,$ob_type);
        }
    }
    # no partitioning
}

sub expand_partitions_doit
{
    # *MP* parameterize procedure: changed $tab_entry into $ob_entry
    1. parameter $_[0]
    #           $table into $ob          2. parameter $_[1]
    #           introduced $ob_type      3. parameter $_[2]

    {
        $ob_entry = $_[0];
        $ob = $_[1];
        $ob_type = $_[2];

        @pcollist = split(//, $params{$ob_entry.'_partcol'});
        if (!defined $params{$ob_entry.'_partnames'})
        {
            # if no partnames are specified, use a default part name
            for ($i = 1; $i <= $params{$ob_entry.'_#part'}; $i++)
            {
                ($i == $params{$ob_entry.'_#part'}) ? ($addcomma =
"") :
                    ($addcomma = ",");
                $nextfile = sprintf("%s%s%d%s", $ob, "_p", $i,
$addcomma);
                $params{$ob_entry.'_partnames'} =
                    $params{$ob_entry.'_partnames'} . $nextfile;
            }
        }

        @ob_partnames = split(//,$params{$ob_entry.'_partnames'});

        # if partnames is specified as XXXX#, then expand
        if ($ob_partnames[0] =~ /\#/)
        {
            $filennm = shift(@ob_partnames);
            $savename = $filennm;
            $params{$ob_entry.'_partnames'} = "";
            for ($i = 1; $i <= $params{$ob_entry.'_#part'}; $i++)
            {
                $filennm =~ s/\#/\\$i/g;
                ($i == $params{$ob_entry.'_#part'}) ? ($addcomma =
"") :
                    ($addcomma = ",");
                $params{$ob_entry.'_partnames'} =
                    $params{$ob_entry.'_partnames'} . $filennm . $addcomma;
                $filennm = $savename;
            }
        }
    }
}

```

```

        }
        @ob_partnames =
split(//,$params{$ob_entry.'_partnames'});
        printf("Expanded $savename
to:\n$params{$ob_entry.'_partnames'}\n\n") if $verbose;
    } else {
        if (@ob_partnames != $params{$ob_entry.'_#part'})
        {
            print "Number of partitions
$params{$ob_entry.'_#part'} for $ob doesn't match\n _partnames
parameter for $params{$ob_entry.'_partnames'}\n";
            exit(-1);
        }
    }
    # now process the partition boundary

&process_part_brys ($ob_entry,$ob);
&process_part_ts ($ob_entry,$ob);

# complete the partition statement

for ($i=0; $i < $params{$ob_entry.'_#part'}; $i++)
{
    $cmd .= "partition " . $ob_partnames[$i] . " values less
than ";
    if ($i==$params{$ob_entry.'_#part'}-1) {
        $cmd .= "(MAXVALUE)\n";
    }
    else {
        $cmd .= "(" . $ob_part_vals[$i] . ")\n";
    }
    &process_part_params($ob_type,'%f','pctfree',$ob,$ob_p
artnames[$i]);
    &process_part_params($ob_type,'it','intrans',$ob,$ob_pa
rtnames[$i]);
    &process_part_params($ob_type,'mt','maxtrans',$ob,$ob_
partnames[$i]);

    if (defined
$params{$ob_entry.'_$.ob_partnames[$i]'. '_ts'})
    {
        $cmd .= 'tablespace ' .
$params{$ob_entry.'_$.ob_partnames[$i]'. '_ts'} . "\n";
    }
    &process_part_storage($ob_type,$ob,$ob_partnames[$i]);
    } elsif (defined $params{$ob_entry.'_part_ts'}) {
        $cmd .= 'tablespace ' . $ob_part_ts[$i] . "\n";
    }
    &process_part_storage($ob_type,$ob,$ob_partnames[$i]);
    if (defined
$params{$ob_entry.'_$.ob_partnames[$i]'. '_nolg'})
    {
        $cmd .= "nologging\n" if
($params{$ob_entry.'_$.ob_partnames[$i]'. '_nolg'} =~
/[tT][rR][uU][eE]/);
        } elsif (defined $params{$ob_entry.'_part_def_nolg'}) {
            $cmd .= "nologging\n" if
($params{$ob_entry.'_part_def_nolg'} =~ /[tT][rR][uU][eE]/);
        }
        $cmd .= (($i+1) == $params{$ob_entry.'_#part'}) ? "" :
",\n";
    }
    $cmd .= ")\n";
} #end expand_partitions_doit

sub process_part_storage
{
    local($type,$name,$pname) = @_;
    if (defined $params{$type.'_'.$name.'_'.$pname.'_storage'})
    {
        $cmd .= 'storage
'.$params{$type.'_'.$name.'_'.$pname.'_storage'}."\n";
    } elsif (defined $params{$type.'_'.$name.'_part_def_storage'}) {
        $cmd .= 'storage
'.$params{$type.'_'.$name.'_part_def_storage'}."\n";
    }
}

sub process_part_params
{
    local($type,$p1,$p2,$name,$pname) = @_;
    if (defined $params{$type.'_'.$name.'_'.$pname.'_'.$p1}) {
        $cmd .= $p2 . " ";
    }
    $params{$type.'_'.$name.'_'.$pname.'_'.$p1}."\n";
    } elsif (defined $params{$type.'_'.$name.'_part_def_'.$p1}) {
        $cmd .= $p2 . " ";
    }
    $params{$type.'_'.$name.'_part_def_'.$p1} . "\n";
}

sub process_part_ts
{
    # *MP* parameterize procedure: changed 'tab'$table into
    $ob_entry 1. parameter $_[0] (same as $__entry in expand_partition)
    #           $table into $ob_          2. parameter $_[1]
    (same as $ob in expand_partition)

    {
        $ob_entry = $_[0];
        $ob_ = $_[1];
        # is objecttype_<name>_part_ts is in the form of XXXX#, expand
        it
        # else treat it as a comma separated list of ts names
        if (defined $params{$ob_entry.'_part_ts'}) {
            $nts=$params{$ob_entry.'_part_ts'};
            $nts=~s/#//;
            $nts=$params{$nts."_instances"};
            @ob_part_ts = split(//,$params{$ob_entry.'_part_ts'});
            if ($ob_part_ts[0] =~ /\#/)
            {
                $filenm = shift(@ob_part_ts);
                $savename = $filenm;
                $params{$ob_entry.'_part_ts'} = "";
                $its = 0;
                for ($i = 1; $i <= $params{$ob_entry.'_#part'}; $i++)
                {
                    $its = $its + 1;
                    if ($its > $nts) {
                        $its=1;
                    }
                    $filenm =~ s/#/$its/g;
                    ($i == $params{$ob_entry.'_#part'}) ?
($addcomma = "") :
                    ($addcomma = ",");
                    $params{$ob_entry.'_part_ts'} =
                    $params{$ob_entry.'_part_ts'} . $filenm .
$addcomma;
                    $filenm = $savename;
                }
                @ob_part_ts =
split(//,$params{$ob_entry.'_part_ts'});
            } else {
                if (@ob_part_ts != $params{$ob_entry.'_#part'})
                {

```

```

if (($params{$ob_entry.'#part'} % @ob_part_ts) == 0) {
    $numfil = @ob_part_ts;
    $p = $params{$ob_entry.'#part'} /
$numfil;
    $fil = "";
    for ($i = 0; $i < $p; $i++)
    {
        if ($i == 0) {
            $fil =
$params{$ob_entry.'_part_ts'};
        } else {
            $fil =
join(',',$fil,$params{$ob_entry.'_part_ts'});
        }
        @ob_part_ts = split(//,$fil);
    } else {
        print "Number of partitions
$params{$ob_entry.'#part'} for object $ob_¶ doesn't match
$table_part_ts parameter.\n";
        exit (-1);
    }
}
} # end of process_part_ts

sub process_part_brys
{
# *MP* parameterize procedure: changed 'tab'.$table into
$ob_entry 1. parameter $_[0] (same as $ob_entry in
expand_partition)
# $table into $ob_ 2. parameter $_[1]
(same as $ob in expand_partition)

{
    $ob_entry = $_[0];
    $ob_ = $_[1];

    $cnt = 0;
    @ob_part_vals = ();

    foreach $col (@pcollist)
    {
        # add quotes for character strings and dates

        if (($params{$ob_entry.'$.col.'_type'} =~ /cC|hH|aA|rR/) ||
            ($params{$ob_entry.'$.col.'_type'} =~ /dD|aA|tT|eE/))
        {
            $addquote = "";
        } else {
            $addquote = "'";
        }

        @ob_part_col =
split(//,$params{$ob_entry.'$.col.'_partvals'});
        if (@ob_part_col != $params{$ob_entry.'#part'})
        {
            printf "Number of partition boundary values %d for
column $col in object $ob_ doesn't match the number of partitions
($params{$ob_entry.'#part'}) of the object\n", (#ob_part_col +
1);
            exit(-1);
        }
    }
}

for ($i=0; $i < $params{$ob_entry.'#part'}; $i++)
{
    ($cnt == $#pcollist) ? ($addcomma = "") :
    ($addcomma = ",");
    if ($ob_part_col[$i] =~ /[Mm][Aa][Xx][Vv][Aa][Ll][Uu][Ee]/) {
        $addquote = "";
    } else {
        if ($params{$ob_entry.'$.col.'_type'} =~ /dD|aA|tT|eE/)
        {
            if ($i == $params{$ob_entry.'#part'} - 1)
            {
                $ob_part_vals[$i] = "MAXVALUE";
            } else {
                $nls_format = (defined
$params{$ob_entry.'$.col.'_date_format'}) ?
$params{$ob_entry.'$.col.'_date_format} : "YYYY-MM-DD";
                $ob_part_vals[$i] .=
"to_date(\".$ob_part_col[$i].\",'";
                $ob_part_vals[$i] .=
$nls_format.")".$addcomma;
            }
        } else {
            $ob_part_vals[$i] = $ob_part_vals[$i] .
$addquote.
$ob_part_col[$i] . $addquote . $addcomma
;
        }
    }
    $cnt++;
}
} # end of process_part_brys

sub alttabs
{
    $di = shift(@_);
    $di =~ /(d*)_(\d*)/;
    $cmd = "";
    $cmd .= "connect $params{'user'}/$params{'passwd'};\n";
    $params{'alter_tables'} = $params{'tab_tables'} if !defined
$params{'alter_tables'};
    @atabs = split(//, $params{'alter_tables'});
    foreach $atab (@atabs)
    {
        $cmd .= "alter table $atab parallel (degree $1 instances $2);\n";
    }
    &dump1("*sql");
    &dump0("*wait");
}

sub setinst
{
    $inum = shift(@_);
    &dump0("*inst");
    &dump0("{$inum}");
}

sub dump2
{
    $value = shift(@_);
    &dump0($value);
    &dump0("{}");
    print OUTFILE $cmd;
    &dump0("{}");
    &dump0("{}");
    print OUTFILE $cmd2;
    &dump0("{}");
    $cmd = "";
    $cmd2 = "";
}

```

```

    print "." if $verbose;
}

sub dump1
{
    $value = shift(@_);
    &dump0($value);
    &dump0("(");
    print OUTFILE $cmd;
    &dump0(")");
    $cmd = "";
    print "." if $verbose;
}

sub dump0
{
    $value = shift (@_);
    $value = $value . "\n" if ($value =~ /.*/\n$/);
    print OUTFILE "$value";
}

sub recreate_drive_extended_part
{
    $cmd = "crepart -d PhysicalDrive" . $drivenum . "\n";
    &dump1("*sh");
    $cmd = "Deleted partitions on PhysicalDrive" . $drivenum;
    &time0($cmd);
    $cmd = "crepart -x PhysicalDrive" . $drivenum . "\n";
    &dump1("*sh");
    $cmd = "Created extended partition on PhysicalDrive" .
$drivenum;
    &time0($cmd);
}

sub create_drive_part
{
    $numfiles = $params{'$ts_entry._#files'}-1;
    if ($d == 0)
    {
        $size = (defined $params{$ts_entry._first_size}) ?
            $params{$ts_entry._first_size} :
            $params{$ts_entry._size};
    }
    else
    {
        $size = $params{$ts_entry._size};
    }
    $size =~ s/[Mm]//g;
    @files = split(//,$params{$ts_entry._datafiles'});
    foreach $file (@files)
    {
        &create_drive_part_file;
    }
}

sub create_drive_part_file
{
    # add 1MB to nt partition size to prevent writing data to cyl 0
    $psize = $size+1;
    $drivenum = $file =~ /log/ ? $params{'plcre_log_drivenum'} :
        @drivenum[$d];
    $cmd = "crepart -l PhysicalDrive";
    $cmd .= $drivenum . " " . $psize . "\n";
    &dump1("*sh");
    $cmd = $file . "\device\PhysicalDrive" . $drivenum;
    $cmd .= "\partition" . ++$partnum{$drivenum} . "\n";
    &time0($cmd);
    print LNKSFILE $cmd;
    if ($file =~ /sys/ || $file =~ /cntr/)
    {
        $d = $d < $md ? ++$d : 0;
    }
    elsif ($file =~ !/^log/)
    {
        $d = ($d < $md) && ($d < $numfiles) ? ++$d : 0;
    }
}

sub load_ctl_head
{
    print "control $control\n";
    open (CTLFILE, ">$control");
    print CTLFILE "---\n";
    print CTLFILE " --- $tablectl for delimited records\n" if ($ud ==
1);
    print CTLFILE " --- $tablectl for fixed-length fields\n" if ($ud ==
0);
    print CTLFILE " ---\n\n";
    if (!($pre72) && defined $params{'tab_.$table._loadextent'})
    {
        print CTLFILE "options\n";
        print CTLFILE "(\n";
        print CTLFILE "storage = (initial
$params{'tab_.$table._loadextent'}) next
$params{'tab_.$table._loadextent'})\n";
        print CTLFILE ")\n";
    }
    print CTLFILE "unrecoverable\n" if
($params{'load_unrecoverable'} =~ /[tT][rR][uU][eE]/);
    print CTLFILE "load\n";
    print CTLFILE "- This is where INFILe should go.\n";
}

sub load_ctl_tail
{
    print CTLFILE "$params{'load_insert_type'}\n";
    print CTLFILE "fields terminated by
$params{'load_field_terminator'}\n" if ($ud == 1);
    print CTLFILE "(\n";
    @tab_collist = split(//, $params{'tab_.$table._columns'});
    while ($col = shift(@tab_collist))
    {
        (@tab_collist == 0) ? ($addcomma = "") : ($addcomma =
",");
        $pos = "";
        $pos = sprintf ("position
(%s)", $params{'tab_.$table._$col._pos'}) if ($ud == 0);
        $ctlline = sprintf (" % -20s % $s$addcomma", $col,
$pos, $params{'tab_.$table._$col._loadcolx'});
        print CTLFILE "$ctlline\n";
    }
    print CTLFILE ")\n";
    close (CTLFILE);
}

#####
#####
#####
# Assigning Defaults
#####
#####
#####

sub defaults
{
    # defaults for the params associative array
    if (defined $bmtpe)

```

```

{
    eval(&{$bmttype});
    &assigndefs;
}
&auxdefaults;
&assigndefs;

$params{'dd_sql_area'}="$ENV{'ORACLE_HOME'}/rdbms/admin/
" if !(defined $params{'dd_sql_area'});

$params{'dd_sqlplus_area'}="$ENV{'ORACLE_HOME'}/sqlplus/a
dmin/" if !(defined $params{'dd_sqlplus_area'});

if (defined $params{'compatible'})
{
    $pre72 = 1 if $params{'compatible'} ==~/7\,(0|1)/;
    $pre73 = 1 if $params{'compatible'} ==~/7\,(0|1|2)/;
}
$params{'dbs_area'} =~ s/\?/$ENV{'ORACLE_HOME'}/g;
$params{'load_tables'} = $params{'tab_tables'} if !defined
$params{'load_tables'};
foreach $phase (@phases)
{
    $params{$phase.'_num_inst'} = $params{'def_num_inst'} if
!defined $params{$phase.'_num_inst'};
    $params{$phase.'_max_bg'} = $params{'max_bg'} if !defined
$params{$phase.'_max_bg'};
    $params{'startupfile_.$phase'} = $params{'io_ifile'} if
!defined($params{'startupfile_.$phase'});
    $params{'startupfile_.$phase'} = sprintf ("$/host%$",
$params{'startupfile_.$phase'});
        if ($params{'special_machine'} eq 'ncube');
        #Params{'startupfile_.$phase'} =~
s/\?/$ENV{'ORACLE_HOME'}/g;
    }
$params{'ops_nodes'} = 'undo' if !defined($params{'ops_nodes'});
    @ops_nodes = split(//,$params{'ops_nodes'}) if defined
$params{'ops_nodes'};
    $params{'db_maxinstances'} = @ops_nodes if !defined
$params{'db_maxinstances'};

#----- undo tablespace definition -----
$params{'ts_undo_#rs'} = $params{'def_num_inst'} if !defined
$params{'ts_undo_#rs'};
    $params{'ts_undo_area'} = $params{'dbs_area'} if !defined
$params{'ts_undo_area'};
    $params{'ts_undo_rs_prefix'} = 'r' if !defined
$params{'ts_undo_rs_prefix'};
    $save_datafiles = $params{'ts_undo_datafiles'};

&expand_filename('ts_undo_datafiles',$params{'ts_undo_#files'});

if (@ops_nodes > 1)
{
    foreach $node (@ops_nodes)
    {
        $params{'ts_undo_.$node._#files'} =
$params{'ts_undo_#files'}
            if !defined($params{'ts_undo_.$node._#files'});
        $df= $save_datafiles.'_'.$node;
        $params{'ts_undo_.$node._datafiles'} = $df
            if
!defined($params{'ts_undo_.$node._datafiles'});
    &expand_filename('ts_undo_.$node._datafiles',$params{'ts_undo_'.
$node._#files'});
}

```

\$params{'ts_undo_.\$node._first_size'} =
\$params{'ts_undo_first_size'}
 if !defined(\$params{'ts_undo_.\$node._first_size'});

 \$params{'ts_undo_.\$node._#rs'} =
\$params{'ts_undo_#rs'}
 if !defined(\$params{'ts_undo_.\$node._#rs'});

 \$params{'ts_undo_.\$node._rs_storage'} =
\$params{'ts_undo_rs_storage'}
 if !defined(\$params{'ts_undo_.\$node._rs_storage'});

 \$pr = \$params{'ts_undo_rs_prefix'}. \$node;
 \$params{'ts_undo_.\$node._rs_prefix'} = \$pr
 if
!defined(\$params{'ts_undo_.\$node._rs_prefix'});
}

\$params{'ts_log_#files'} = \$params{'ts_log_#threads'} *
\$params{'ts_log_#files_pt'};

\$params{'ts_def_area'} = \$params{'dbs_area'} if !defined
\$params{'ts_def_area'};
 \$params{'load_flatfile_area'} = \$params{'ts_def_area'} if !defined
\$params{'load_flatfile_area'};
 \$params{'load_controlfile_area'} = \$params{'ts_def_area'} if
!defined \$params{'load_controlfile_area'};
 \$params{'load_otherfile_area'} = \$params{'ts_def_area'} if
!defined \$params{'load_otherfile_area'};

\$params{'ts_index_names'} = "ts_index" if ((!defined
\$params{'ts_index_names'}) && (\$params{'skip_ts'} !~ /index/));
 \$params{'ts_temp_names'} = "ts_temp" if ((!defined
\$params{'ts_temp_names'}) && (\$params{'skip_ts'} !~ /temp/));
 \$params{'ts_data_names'} = "ts_data" if ((!defined
\$params{'ts_data_names'}) && (\$params{'skip_ts'} !~ /data/));

expand ts_data groups

if (defined \$params{'ts_data_groups'})
{
 @ts_data_group = split(//,\$params{'ts_data_groups'});
 foreach \$gname (@ts_data_group)
 {
 \$nts = \$params{\$gname.'_group_#ts'};
 for (\$i=0;\$i<\$nts;\$i++)
 {
 \$tsn = sprintf("%s%d",\$gname,(\$i+1));
 \$params{'ts_data_names'} .= ", ".\$tsn;
 \$params{\$tsn.'_datafiles'} = \$tsn."_#";
 \$params{\$tsn.'_#files'} =
\$params{\$gname.'_group_#files'} if defined
\$params{\$gname.'_group_#files'};
 \$params{\$tsn.'_option'} =
\$params{\$gname.'_group_option'} if defined
\$params{\$gname.'_group_option'};
 \$params{\$tsn.'_area'} =
\$params{\$gname.'_group_area'} if defined
\$params{\$gname.'_group_area'};
 \$params{\$tsn.'_storage'} =
\$params{\$gname.'_group_storage'} if defined
\$params{\$gname.'_group_storage'};
 \$params{\$tsn.'_first_size'} =
\$params{\$gname.'_group_first_size'} if defined
\$params{\$gname.'_group_first_size'};
 \$params{\$tsn.'_size'} =
\$params{\$gname.'_group_size'} if defined
\$params{\$gname.'_group_size'};

```

$params{$tsn.'_nolg'} =
$params{$gname.'_nolg'} if defined $params{$gname.'_nolg'};
}
}

@ts_data = split(//, $params{'ts_data_names'});
@ts_index = split(//, $params{'ts_index_names'});
@ts_temp = split(//, $params{'ts_temp_names'});

# expand tablespaces
@ts_data_new =();
$ts_data_names="@@";
foreach $ts_entry (@ts_data)
{
    if (defined($params{$ts_entry.'_instances'})){
        for ($i = $params{$ts_entry.'_instances'}; $i > 0; $i -)
    {
        $ts_new_entry = $ts_entry.$i;
        $params{$ts_new_entry.'_size'}=$params{$ts_entry.'_size'};
        $params{$ts_new_entry.'_datafiles'}=$params{$ts_entry.'_datafiles'};
        $params{$ts_new_entry.'_datafiles'}=~s/#/$i/;
        $params{$ts_new_entry.'_#files'}=$params{$ts_entry.'_#files'};
        $params{$ts_new_entry.'_storage'}=$params{$ts_entry.'_storage'};
        unshift (@ts_data_new, $ts_new_entry);
        $ts_data_names=$ts_data_names.".$ts_new_entry;
    }
    else {
        unshift (@ts_data_new, $ts_entry);
        $ts_data_names=$ts_data_names.".$ts_entry;
    }
}
$ts_data_names=~s/@@@//;
#print "ts_data_names: $ts_data_names\n";
@ts_data = @ts_data_new;
#print "ts_all before substitution @ts_all\n";
#print "ts_all_new before substitution @ts_all_new\n";
#while (@ts_data) {
#    $ts = shift (@ts_data);
#    #unshift (@ts_data_new,$ts);
#}
#foreach $ts_entry (@ts_data)
#{
#    print "ts_entry: $ts_entry\n";
#    print "size: $params{$ts_entry.'_size'}\n";
#    print "datafiles: $params{$ts_entry.'_datafiles'}\n";
#    print "#files: $params{$ts_entry.'_#files'}\n";
#    print "storage: $params{$ts_entry.'_storage'}\n";
#}

#print "ts_all after substitution @ts_all\n";
#print "$ts_list\n";
#exit(0);
$mostts =
$params{'ts_temp_names'}.$ts_data_names.$params{'ts_index_names'}";
$allts =
"ts_sys,ts_log,$params{'ts_undo'},$params{'ts_temp_names'},$ts_da
ta_names,$params{'ts_index_names'}";
@ts_most = split(//, $mostts);
@ts_all = split(//, $allts);

foreach $ts_entry (@ts_most)
{
    $params{$ts_entry.'_#files'} = $params{'ts_def_#files'} if
!defined $params{$ts_entry.'_#files'};
    $params{$ts_entry.'_size'} = $params{'ts_def_size'} if !defined
$params{$ts_entry.'_size'};
    $params{$ts_entry.'_storage'} = $params{'ts_def_storage'} if
!defined $params{$ts_entry.'_storage'};
}

#rint "ts_all: @ts_all\n";
foreach $ts_entry (@ts_all)
{
    print "ts_entry $ts_entry\n";
    $params{$ts_entry.'_area'} = $params{'ts_def_area'} if !defined
$params{$ts_entry.'_area'};
    $params{$ts_entry.'_options'} = $params{'ts_def_options'} if
!defined $params{$ts_entry.'_options'};
    $params{$ts_entry.'_first_size'} = $params{$ts_entry.'_size'} if
!defined $params{$ts_entry.'_first_size'};
    $params{$ts_entry.'_temporary'} = "false" if !defined
$params{$ts_entry.'_temporary'};
    $params{$ts_entry.'_managed'} = "user" if !defined
$params{$ts_entry.'_managed'};
    if (!defined $params{$ts_entry.'_datafiles'})
    {
        for ($i = 0; $i < $params{$ts_entry.'_#files'}; $i++)
        {
            (($i+1) == $params{$ts_entry.'_#files'}) ? ($addcomma =
 "") : ($addcomma = ",");
            $nextfile = sprintf ("%s%d.%s", $ts_entry, $i+1,
$addcomma);
            $params{$ts_entry.'_datafiles'} =
$params{$ts_entry.'_datafiles'} . $nextfile;
        }
        @ts_datafiles = split(//, $params{$ts_entry.'_datafiles'});
        $cntr = 1;
        if ($ts_datafiles[0] =~ /\#/) # we want to replace all #'s
{
            $filenm = shift(@ts_datafiles);
            $savename = $filenm;
            $params{$ts_entry.'_datafiles'} = "";
            for ($i = 0; $i < $params{$ts_entry.'_#files'}; $i++)
{
                $filenm =~ s/\#//$cntr/g;
                $cntr++;
                (($i+1) == $params{$ts_entry.'_#files'}) ? ($addcomma =
 "") : ($addcomma = ",");
                $params{$ts_entry.'_datafiles'} =
$params{$ts_entry.'_datafiles'} .
$filenm . $addcomma;
                $filenm = $savename;
            }
            printf ("Expanded $savename
to:\n$params{$ts_entry.'_datafiles'}\n\n") if $verbose;
        }
        else
{
            if (@ts_datafiles != $params{$ts_entry.'_#files'})
{
                print "Number of files ($params{$ts_entry.'_#files'}) for
$ts_entry doesn't match\n_datafile parameter
$params{$ts_entry.'_datafiles'}\n";
                exit(-1);
}
}
}
}

```

```

        }
    }
$params{'io_control_files'} = $params{'ts_sys_area'}.t_cf1.f if
!defined $params{'io_control_files'};

@tab_list = split(//, $params{'tab_tables'});
foreach $table (@tab_list)
{
    $params{'load_dbgen_.$table._option_C'} =
$params{'load_dbgen_def_option_C'} if !defined
$params{'load_dbgen_.$table._option_C'};

    $params{'tab_.$table._ts'} = "ts_data" if !defined
$params{'tab_.$table._ts'};
        if (defined($params{'load_deg_parallel'})) {
            $params{'tab_.$table._load_degpar'} =
$params{'load_deg_parallel'} if !defined
$params{'tab_.$table._load_degpar'};
        } else {
            $params{'tab_.$table._load_degpar'} = 1 if !defined
$params{'tab_.$table._load_degpar'};
        }

    ##$params{'load_dbgen_.$table._output_prefix'} =
"$table.tbl" if !defined
$params{'load_dbgen_.$table._output_prefix'};

    $params{'tab_.$table._load_datf'} = "$table.tbl" if
!defined $params{'tab_.$table._load_datf'};

    $params{'tab_.$table._load_badf'} = "$table.badf" if
!defined $params{'tab_.$table._load_badf'};

    $params{'tab_.$table._load_ctlf'} = "$table.ctl" if
!defined $params{'tab_.$table._load_ctlf'};

    $params{'tab_.$table._load_logf'} = "$table.log" if
!defined $params{'tab_.$table._load_logf'};

    $params{'tab_.$table._load_direct'} = "true" if !defined
$params{'tab_.$table._load_direct'};

    $params{'tab_.$table._rows'} *=
$params{'scale_factor'};

}

@view_list = split(//, $params{'view_views'});
foreach $view (@view_list)
{
    $params{'view_.$view._ts'} = "ts_data" if !defined
$params{'view_.$view._ts'};
    $params{'view_.$view._load_degpar'} =
$params{'load_deg_parallel'} if !defined
$params{'view_.$view._load_degpar'};
        $params{'view_.$view._#rows'} *= $params{'scale_factor'};
        $params{$ob_entry._rewrite} = "" if !defined
$params{$ob_entry._rewrite};
}

@tablelog_list = split(//, $params{'tablelog_list'});

@clulist = split(//, $params{'clu_clusters'});
foreach $cluster (@clulist)
{
    $params{'clu_.$cluster._ts'} = "ts_data" if !defined
$params{'clu_.$cluster._ts'};
}

@constlist = split(//, $params{'con_constraints'});
foreach $const (@constlist)

{
    $params{'con_.$const._ts'} = "ts_index" if ((!defined
$params{'con_.$const._ts'}) && ($params{'skip_ts'} !~/index/));
}

@indexlist = split(//, $params{'ind_indices'});
foreach $index (@indexlist)
{
    $params{'ind_.$index._ts'} = "ts_index" if ((!defined
$params{'ind_.$index._ts'}) && ($params{'skip_ts'} !~/index/));
}

$params{'analyze_type'} = "via package dbms.stats" if
!defined($params{'analyze_type'});
@anlyzlist = split(//, $params{'anl_objects'});
@anlyzlist = "schema" if (@anlyzlist == 0);
foreach $object (@anlyzlist)
{
    $params{'anl_.$object._object_type'} = "schema" if
($object =~ /schema/);
    $params{'anl_.$object._object_type'} = "table" if !defined
$params{'anl_.$object._object_type'};
    $params{'anl_.$object._anl_type'} = "gather" if !defined
$params{'anl_.$object._anl_type'};
}

@choblist = split(//, $params{'chob_objects'});
# foreach $object (@choblist)
#
#   $choblist{$object} = $params{'chob_.$object._pardeg'};
#
# @chstorlist = split(//, $params{'chstor_objects'});
foreach $object (@chstorlist)
{
    $chstorlist{$object} = $params{'chstor_.$object._next'};
}
if ((defined $params{'verbose'}) && (($params{'verbose'} =~
/[tT][rR][uU][eE]/) || ($params{'verbose'} =~ 1))){
    $verbose=1;
}
else {
    $verbose=0;
}
if ((defined $params{'log_output'}) && (($params{'log_output'} =~
/[tT][rR][uU][eE]/) || ($params{'log_output'} =~ 1))){
    $log_output=1;
}
else {
    $log_output=0;
}
$params{'plcre_recreate_extended_partitions'} = "false" if
!defined ($params{'plcre_recreate_extended_partitions'});
}

sub assigndefs
{
    while ($onedef = shift(@defparams))
    {
        $onedef =~ /^(.*)=(.*)$/;
        $key = $1;
        $value = $2;
        $params{$key} = $value if !defined $params{$key};
    }
}

sub auxdefaults
{
    @defparams = ();
    push (@defparams, 'scale_factor=0.1');
    push (@defparams, 'dbs_area=?/dbs/');
    push (@defparams, 'dbs_area=/tmp');
    push (@defparams, 'dd_sql_area=?/rdbms/admin/');
    push (@defparams, 'max_bg=-1');
    push (@defparams, 'user=bmuser');
    push (@defparams, 'passwd=bmpasswd');
    push (@defparams, 'load_type=delim');
}

```

```

push (@defparams, 'load_field_terminator=whitespace');
push (@defparams, 'ts_def_#files=1');
push (@defparams, 'ts_def_options=reuse');
push (@defparams, 'ts_def_first_size=1m');
push (@defparams, 'ts_def_size=1m');
push (@defparams, 'ts_sys_#files=1');
push (@defparams, 'ts_log_#threads=1');
push (@defparams, 'ts_log_#files_pt=2');
push (@defparams, 'ts_undo_#files=1');
push (@defparams, 'ts_sys_size=25m');
push (@defparams, 'ts_log_size=2m');
push (@defparams, 'ts_undo_size=10m');
# push (@defparams, 'ts_data_names=ts_data');
push (@defparams, 'load_insert_type=append');
push (@defparams, 'load_deg_parallel=1');
push (@defparams, 'special_machine=');
push (@defparams, 'shutdown_level=abort');
push (@defparams, 'def_num_inst=1');
# push (@defparams, 'privileges=resource,unlimited
tablespace,connect');
#push (@defparams, 'privileges=DBA,query rewrite,global query
rewrite');
push (@defparams, 'privileges=DBA');
push (@defparams, 'qry_number_trials=1');
}

sub tpcd
{
    @defparams = ();
    push (@defparams, 'user=tpcd');
    push (@defparams, 'passwd=tpcd');
    push (@defparams,
'tab_tables=lineitem,orders,partsupp,part,customer,supplier,nation,re
gion');
    push (@defparams, 'view_views=mav_li,mv_locs');
    push (@defparams, 'viewlog_list=lineitem,orders');
    push (@defparams,
'mav_li_columns=count_p_group,l_shipdate,l_returnflag,l_linenumber
,sum_qty,sum_base_price,sum_disc_price
,sum_disc_price,sum_charge,
count_charge,count_qty,count_price,sum_disc,count_disc,count_ord
er');
    push (@defparams,
'tab_lineitem_columns=l_orderkey,l_partkey,l_suppkey,l_linenumber
,l_quantity,l_extendedprice,l_discount,l_tax,l_returnflag,l_linenumber
,l_shipdate,l_commitdate,l_receiptdate,l_shipinstruct,l_shipmode,l_c
omment');
    push (@defparams,
'tab_orders_columns=o_orderkey,o_custkey,o_orderstatus,o_totalpri
ce,o_orderdate,o_orderpriority,o_clerk,o_shipppriority,o_comment');
    push (@defparams,
'tab_partsupp_columns=ps_partkey,ps_suppkey,ps_availqty,ps_supp
lycost,ps_comment');
    push (@defparams,
'tab_part_columns=p_partkey,p_name,p_mfgr,p_brand,p_type,p_siz
e,p_container,p_retailprice,p_comment');
    push (@defparams,
'tab_customer_columns=c_custkey,c_name,c_address,c_nationkey,c
_phone,c_acctbal,c_mktsegment,c_comment');
    push (@defparams,
'tab_supplier_columns=s_suppkey,s_name,s_address,s_nationkey,s_
phone,s_acctbal,s_comment');
    push (@defparams,
'tab_nation_columns=n_nationkey,n_name,n_regionkey,n_comment');
    push (@defparams,
'tab_region_columns=r_regionkey,r_name,r_comment');
    push (@defparams, 'tab_lineitem_#rows=6100000'); # Somewhat
of a random value
    push (@defparams, 'tab_orders_#rows=1500000');

    push (@defparams, 'tab_partsupp_#rows=800000');
    push (@defparams, 'tab_part_#rows=200000');
    push (@defparams, 'tab_customer_#rows=150000');
    push (@defparams, 'tab_supplier_#rows=10000');
    push (@defparams, 'tab_nation_#rows=0');
    push (@defparams, 'tab_region_#rows=0');
    push (@defparams, 'tab_lineitem_parttype=range');
    push (@defparams, 'tab_lineitem_l_orderkey_type=number');
    push (@defparams, 'tab_lineitem_l_partkey_type=number');
    push (@defparams, 'tab_lineitem_l_suppkey_type=number');
    push (@defparams, 'tab_lineitem_l_linenumber_type=number');
    push (@defparams, 'tab_lineitem_l_quantity_type=number');
    push (@defparams,
'tab_lineitem_l_extendedprice_type=number');
    push (@defparams, 'tab_lineitem_l_discount_type=number');
    push (@defparams, 'tab_lineitem_l_tax_type=number');
    push (@defparams, 'tab_lineitem_l_returnflag_type=char(1)');
    push (@defparams, 'tab_lineitem_l_linenumber_type=char(1)');
    push (@defparams, 'tab_lineitem_l_shipdate_type=date');
    push (@defparams, 'tab_lineitem_l_commitdate_type=date');
    push (@defparams, 'tab_lineitem_l_receiptdate_type=date');
    push (@defparams, 'tab_lineitem_l_shipinstruct_type=char(25)');
    push (@defparams, 'tab_lineitem_l_shipmode_type=char(10)');
    push (@defparams, 'tab_lineitem_l_comment_type=varchar(44)');
    push (@defparams, 'tab_lineitem_l_orderkey_pos=13:24');
    push (@defparams, 'tab_lineitem_l_partkey_pos=25:36');
    push (@defparams, 'tab_lineitem_l_suppkey_pos=37:48');
    push (@defparams, 'tab_lineitem_l_linenumber_pos=49:60');
    push (@defparams, 'tab_lineitem_l_quantity_pos=61:72');
    push (@defparams, 'tab_lineitem_l_extendedprice_pos=73:87');
    push (@defparams, 'tab_lineitem_l_discount_pos=88:102');
    push (@defparams, 'tab_lineitem_l_tax_pos=103:117');
    push (@defparams, 'tab_lineitem_l_returnflag_pos=118:118');
    push (@defparams, 'tab_lineitem_l_linenumber_pos=120:120');
    push (@defparams, 'tab_lineitem_l_shipdate_pos=122:131');
    push (@defparams, 'tab_lineitem_l_commitdate_pos=135:144');
    push (@defparams, 'tab_lineitem_l_receiptdate_pos=148:157');
    push (@defparams, 'tab_lineitem_l_shipinstruct_pos=161:185');
    push (@defparams, 'tab_lineitem_l_shipmode_pos=186:195');
    push (@defparams, 'tab_lineitem_l_comment_pos=196:239');
    push (@defparams, 'tab_lineitem_l_shipdate_loadcolx=date
"yyyy-mm-dd"');
    push (@defparams, 'tab_lineitem_l_commitdate_loadcolx=date
"yyyy-mm-dd"');
    push (@defparams, 'tab_lineitem_l_receiptdate_loadcolx=date
"yyyy-mm-dd"');
    push (@defparams, 'tab_orders_parttype=range');
    push (@defparams, 'tab_orders_o_orderkey_type=number');
    push (@defparams, 'tab_orders_o_custkey_type=number');
    push (@defparams, 'tab_orders_o_orderstatus_type=char(1)');
    push (@defparams, 'tab_orders_o_totalprice_type=number');
    push (@defparams, 'tab_orders_o_orderdate_type=date');
    push (@defparams, 'tab_orders_o_orderpriority_type=char(15)');
    push (@defparams, 'tab_orders_o_clerk_type=char(15)');
    push (@defparams, 'tab_orders_o_shipppriority_type=number');
    push (@defparams, 'tab_orders_o_comment_type=varchar(79)');
    push (@defparams, 'tab_orders_o_orderkey_pos=13:24');
    push (@defparams, 'tab_orders_o_custkey_pos=25:36');
    push (@defparams, 'tab_orders_o_orderstatus_pos=37:37');
    push (@defparams, 'tab_orders_o_totalprice_pos=39:53');
    push (@defparams, 'tab_orders_o_orderdate_pos=54:63');
    push (@defparams, 'tab_orders_o_orderpriority_pos=67:81');
    push (@defparams, 'tab_orders_o_clerk_pos=82:96');
    push (@defparams, 'tab_orders_o_shipppriority_pos=97:108');
    push (@defparams, 'tab_orders_o_comment_pos=109:187');
    push (@defparams, 'tab_orders_o_orderdate_loadcolx=date
"yyyy-mm-dd"');
    push (@defparams, 'tab_partsupp_parttype=range');
    push (@defparams, 'tab_partsupp_ps_partkey_type=number');
    push (@defparams, 'tab_partsupp_ps_suppkey_type=number');
}

```

```

push (@defparams, 'tab_partsupp_ps_availqty_type=number');
push (@defparams, 'tab_partsupp_ps_supplycost_type=number');
push (@defparams,
'tab_partsupp_ps_comment_type=varchar(199)');
push (@defparams, 'tab_partsupp_ps_partkey_pos=1:12');
push (@defparams, 'tab_partsupp_ps_suppkey_pos=13:24');
push (@defparams, 'tab_partsupp_ps_availqty_pos=25:36');
push (@defparams, 'tab_partsupp_ps_supplycost_pos=37:51');
push (@defparams, 'tab_partsupp_ps_comment_pos=52:250');
push (@defparams, 'tab_part_parttype=range');
push (@defparams, 'tab_part_p_partkey_type=number');
push (@defparams, 'tab_part_p_name_type=varchar(55)');
push (@defparams, 'tab_part_p_mfgr_type=char(25)');
push (@defparams, 'tab_part_p_brand_type=char(10)');
push (@defparams, 'tab_part_p_type_type=varchar(25)');
push (@defparams, 'tab_part_p_size_type=number');
push (@defparams, 'tab_part_p_container_type=char(10)');
push (@defparams, 'tab_part_p_retailprice_type=number');
push (@defparams, 'tab_part_p_comment_type=varchar(23)');
push (@defparams, 'tab_part_p_partkey_pos=1:12');
push (@defparams, 'tab_part_p_name_pos=13:67');
push (@defparams, 'tab_part_p_mfgr_pos=68:92');
push (@defparams, 'tab_part_p_brand_pos=93:102');
push (@defparams, 'tab_part_p_type_pos=103:127');
push (@defparams, 'tab_part_p_size_pos=128:139');
push (@defparams, 'tab_part_p_container_pos=140:149');
push (@defparams, 'tab_part_p_retailprice_pos=150:164');
push (@defparams, 'tab_part_p_comment_pos=165:187');
push (@defparams, 'tab_customer_parttype=range');
push (@defparams, 'tab_customer_c_custkey_type=number');
push (@defparams, 'tab_customer_c_name_type=varchar(25)');
push (@defparams, 'tab_customer_c_address_type=varchar(40)');
push (@defparams, 'tab_customer_c_nationkey_type=number');
push (@defparams, 'tab_customer_c_phone_type=char(15)');
push (@defparams, 'tab_customer_c_acctbal_type=number');
push (@defparams,
'tab_customer_c_mktsegment_type=char(10)');
push (@defparams,
'tab_customer_c_comment_type=varchar(117)');
push (@defparams, 'tab_customer_c_custkey_pos=1:12');
push (@defparams, 'tab_customer_c_name_pos=13:30');
push (@defparams, 'tab_customer_c_address_pos=31:70');
push (@defparams, 'tab_customer_c_nationkey_pos=71:82');
push (@defparams, 'tab_customer_c_phone_pos=83:97');
push (@defparams, 'tab_customer_c_acctbal_pos=98:112');
push (@defparams, 'tab_customer_c_mktsegment_pos=113:122');
push (@defparams, 'tab_customer_c_comment_pos=123:239');
push (@defparams, 'tab_supplier_parttype=range');
push (@defparams, 'tab_supplier_s_suppkey_type=number');
push (@defparams, 'tab_supplier_s_name_type=char(25)');
push (@defparams, 'tab_supplier_s_address_type=varchar(40)');
push (@defparams, 'tab_supplier_s_nationkey_type=number');
push (@defparams, 'tab_supplier_s_phone_type=char(15)');
push (@defparams, 'tab_supplier_s_acctbal_type=number');
push (@defparams,
'tab_supplier_s_comment_type=varchar(101)');
push (@defparams, 'tab_supplier_s_suppkey_pos=1:12');
push (@defparams, 'tab_supplier_s_name_pos=13:37');
push (@defparams, 'tab_supplier_s_address_pos=38:77');
push (@defparams, 'tab_supplier_s_nationkey_pos=78:89');
push (@defparams, 'tab_supplier_s_phone_pos=90:104');
push (@defparams, 'tab_supplier_s_acctbal_pos=105:119');
push (@defparams, 'tab_supplier_s_comment_pos=120:220');
push (@defparams, 'tab_nation_parttype=range');
push (@defparams, 'tab_nation_n_nationkey_type=number');
push (@defparams, 'tab_nation_n_name_type=char(25)');
push (@defparams, 'tab_nation_n_regionkey_type=number');
push (@defparams, 'tab_nation_n_comment_type=varchar(152)');
push (@defparams, 'tab_nation_n_nationkey_pos=1:12');
push (@defparams, 'tab_nation_n_name_pos=13:37');

push (@defparams, 'tab_nation_n_regionkey_pos=38:49');
push (@defparams, 'tab_nation_n_comment_pos=50:164');
push (@defparams, 'tab_region_r_regionkey_type=number');
push (@defparams, 'tab_region_r_name_type=char(25)');
push (@defparams, 'tab_region_r_comment_type=varchar(152)');
push (@defparams, 'tab_region_r_regionkey_pos=1:12');
push (@defparams, 'tab_region_r_name_pos=13:37');
push (@defparams, 'tab_region_r_comment_pos=38:152');
push (@defparams,
'load_dbgen_lineitem_output_prefix=.lineitem');
push (@defparams, 'load_dbgen_orders_output_prefix=.orders');
push (@defparams,
'load_dbgen_customer_output_prefix=.customer');
push (@defparams, 'load_dbgen_part_output_prefix=.part');
push (@defparams,
'load_dbgen_partsupp_output_prefix=.partsupp');
push (@defparams,
'load_dbgen_supplier_output_prefix=.supplier');
push (@defparams, 'load_dbgen_nation_output_prefix=.nation');
push (@defparams, 'load_dbgen_region_output_prefix=.region');
push (@defparams, 'load_type=fixed');
}

sub wisc
{
    @defparams = ();
    push (@defparams, 'user=wisc');
    push (@defparams, 'passwd=wisc');
    push (@defparams, 'tab_tables=wisc');
    push (@defparams, 'load_field_terminator=whitespace');
    push (@defparams,
'tab_wisc_columns=unique1,unique2,two,four,ten,twenty,hundred,th
ousand,fivethous,tenthous,odd100,even100,string1,string2,string4'
);
    push (@defparams, 'tab_wisc_#rows=1000000');
    push (@defparams, 'tab_wisc_unique1_type=number');
    push (@defparams, 'tab_wisc_unique2_type=number');
    push (@defparams, 'tab_wisc_two_type=number');
    push (@defparams, 'tab_wisc_four_type=number');
    push (@defparams, 'tab_wisc_ten_type=number');
    push (@defparams, 'tab_wisc_twenty_type=number');
    push (@defparams, 'tab_wisc_hundred_type=number');
    push (@defparams, 'tab_wisc_thousand_type=number');
    push (@defparams, 'tab_wisc_fivethous_type=number');
    push (@defparams, 'tab_wisc_tenthous_type=number');
    push (@defparams, 'tab_wisc_odd100_type=number');
    push (@defparams, 'tab_wisc_even100_type=number');
    push (@defparams, 'tab_wisc_string1_type=varchar(52)');
    push (@defparams, 'tab_wisc_string2_type=varchar(52)');
    push (@defparams, 'tab_wisc_string4_type=varchar(52)');
    push (@defparams, 'tab_wisc_unique1_loadcolx=integer
external');
    push (@defparams, 'tab_wisc_unique2_loadcolx=integer
external');
    push (@defparams, 'tab_wisc_two_loadcolx=integer external');
    push (@defparams, 'tab_wisc_four_loadcolx=integer external');
    push (@defparams, 'tab_wisc_ten_loadcolx=integer external');
    push (@defparams, 'tab_wisc_twenty_loadcolx=integer external');
    push (@defparams, 'tab_wisc_hundred_loadcolx=integer
external');
    push (@defparams, 'tab_wisc_thousand_loadcolx=integer
external');
    push (@defparams, 'tab_wisc_fivethous_loadcolx=integer
external');
    push (@defparams, 'tab_wisc_tenthous_loadcolx=integer
external');
    push (@defparams, 'tab_wisc_odd100_loadcolx=integer
external');
}

```

```

push (@defparams, 'tab_wisc_even100_loadcolx=integer
external');
push (@defparams, 'tab_wisc_stringu1_loadcolx=char(52)');
push (@defparams, 'tab_wisc_stringu2_loadcolx=char(52)');
push (@defparams, 'tab_wisc_string4_loadcolx=char(52)');
}

sub expand_filename
{
    # 1. parameter: name of datafiles in associative array (params)
    # 2. parameter: number of files the name should be expanded to
    @tsdf = split('/', $params{$_[0]});
    $no_files = $_[1];
    $cntr = 1;
    if ($tsdf[0] =~ /\#/) # we want to replace all #'s
    {
        $filenm = shift(@tsdf);
        $savename = $filenm;
        $params{$_[0]} = "";
        for ($i = 0; $i < $no_files; $i++)
        {
            $filenm =~ s/#/$cntr/g;
            $cntr++;
            if ($i+1 == $no_files) {($addcomma = "") : ($addcomma = ",")};
            $params{$_[0]} .= $filenm . $addcomma;
            $filenm = $savename;
        }
        printf ("Expanded $savename to:\n$params{$_[1]}\n\n");
    }
    if $verbose;
    }
    else
    {
        if (@tsdf != $no_files)
        {
            print "Number of files (@ts_datafiles) for $_[1] doesn't
match\n _datafile parameter $no_files}\n";
            exit(-1);
        }
    }
}

sub time0
{
    if (($os cmp "nt") == 0)
    {
        $value = shift @_;
        $value = "*time=" . $value;
        $value = $value . "\n" if ($value !~ /\.*\n$/);
        print OUTFILE "$value";
        $value = "";
    }
}

sub read_parameter_description
{
    @paramdesc = ();
    stat ("$pdfile");
    if (-e _)
    {
        open (PDFILE, "$pdfile");
        while (<PDFILE>)
        {
            ($key,$desc)=split (/:/,$_,2);
            $key = shift(@l);
            $key =~ s/(\w*)(\w*)>(\w*)/$1\\$2\\$3/g;
            $paramdesc{$key} = $desc;
        }
    }
    else
    {
        print "Parameterfile: $pdfile does not exist \n will
continue without ... \n";
    }
}

sub key_exists
{
    $result = 1;
    return if ($runsilent == 1);
    @keys = keys %paramdesc;
    $p = $_[0]!"!";
    while ($#keys >=0)
    {
        $key = pop(@keys);
        $key = $key!"!";
        return if ($p =~ /$key/);
    }
    $result = -1;
}

```

Appendix C Acid Scripts

C.1 a_query.sql

```
Rem
Rem $Header: a_query.sql 06-aug-99.10:51:10 mpoess Exp $
Rem
Rem a_query.sql
Rem
Rem Copyright (c) Oracle Corporation 1999. All Rights Reserved.
Rem
Rem NAME
Rem a_query.sql - <one-line expansion of the name>
Rem
rem DESCRIPTION
Rem Performs ACID Query for TPC-D benchmark.
Rem Asks user to input values for o_key
Rem The range of okey is 1 to 600000
Rem
=====
=====

Rem
Rem Usage: sqlplus tpcd/tpcd @a_query <o_key>
Rem
Rem
Rem MODIFIED (MM/DD/YY)
Rem mpoess 08/06/99 - Creation
Rem mpoess 08/06/99 - Created
Rem

set serverout on;

select
'BEFORE ACID QUERY' as STAGE,
substr(TO_CHAR(sysdate,'YYYY-MM-DD HH:MI:SS'),1,20) as
CURRENT_TIME
from dual;

select SUM(trunc(trunc(l_extendedprice * (1-l_discount),2) *
(1+l_tax),2)) AS RESULT
from lineitem
where l_orderkey = &&1;

select
'AFTER ACID QUERY' as STAGE,
substr(TO_CHAR(sysdate,'YYYY-MM-DD HH:MI:SS'),1,20) as
CURRENT_TIME
from dual;

exit;
```

C.2 a_query2.sql

```
Rem
Rem $Header: aquery2.sql 07-aug-99.23:54:47 mpoess Exp $
Rem
Rem aquery2.sql
Rem
Rem Copyright (c) Oracle Corporation 1999. All Rights Reserved.
Rem
Rem NAME
Rem aquery2.sql - <one-line expansion of the name>
Rem
Rem DESCRIPTION
Rem Performs query on PARTSUPP for TPC-D benchmark
```

```
Rem Isolation Test 5.
Rem Asks user to input values for ps_partkey and ps_suppkey
Rem The range for ps_partkey is 1 to 20000
Rem The range for ps_suppkey is 1 to 1000
Rem A valid combination is 46 and 47
Rem Usage: sqlplus tpcd/tpcd @a_query2 <ps_partkey>
<ps_suppkey>
Rem
Rem MODIFIED (MM/DD/YY)
Rem mpoess 08/07/99 - Creation
Rem mpoess 08/07/99 - Created
Rem
rem DESCRIPTION
rem Performs query on PARTSUPP for TPC-D benchmark
rem Isolation Test 5.
rem Asks user to input values for ps_partkey and ps_suppkey
rem The range for ps_partkey is 1 to 20000
rem The range for ps_suppkey is 1 to 1000
rem A valid combination is 46 and 47

set serverout on;

select
'BEFORE PARTSUPP QUERY' as STAGE,
substr(TO_CHAR(sysdate,'YYYY-MM-DD HH:MI:SS'),1,20) as
CURRENT_TIME
from dual;

select *
from partsupp
where ps_partkey = &&1
and ps_suppkey = &&2;

select
'AFTER PARTSUPP QUERY' as STAGE,
substr(TO_CHAR(sysdate,'YYYY-MM-DD HH:MI:SS'),1,20) as
CURRENT_TIME
from dual;

exit;
```

C.3 atom.sh

```
#!/bin/ksh
#
# $Header: atom.sh 08-aug-99.13:48:02 mpoess Exp $
#
# atom.sh
#
# Copyright (c) Oracle Corporation 1999. All Rights Reserved.
#
# NAME
# atom.sh - <one-line expansion of the name>
#
# DESCRIPTION
# Performs atomicity tests.
# Usage: atom.sh [-n iter] [-p prog] [-u usr/pwd] -h
#
# Options: See usage below
#
# NOTES
# <other useful comments, qualifications, etc.>
#
# MODIFIED (MM/DD/YY)
# mpoess 08/08/99 - Creation
# mpoess 08/08/99 - Creation
#
```

```

. $KIT_DIR/env

OH=$ORACLE_HOME
# ACID_DIR=$TPCD_KIT_DIR/audit set in env
OUT_DIR=$ACID_OUT
DURA_DIR=$ACID_DIR/dura

usage() {
    echo ""
    echo "Usage: $0 [-n iter] [-p prog] [-u usr/pwd] -h"
    echo ""
    echo "-n iter : number of iterations, default is 100"
    echo "-p prog : program to run, default is atranspl.ott"
    echo "-u usr/pwd : user/password combo for database access,
default is tpcd/tpcd"
    echo "-h      : print this usage summary"
    exit 1;
}

ITER=3
SF=1
PROG=$KIT_DIR/utils/atranspl
OUT=${OUT_DIR}/atom
USER=${DATABASE_USER}

set --`getopt "n:p:u:h" "$@"` || usage

while :
do
    case "$1" in
        -n) shift; ITER=$1;;
        -p) shift; PROG=$1;;
        -u) shift; USER=$1;;
        -h) usage; exit 0;;
        -) break;;
    esac
    shift
done

echo "Starting Atomicity Test at `date` ..."
echo ""
echo "Performing $ITER ACID transactions with COMMIT"
echo ""

$KIT_DIR/utils/randkey $ITER $SF u$USER | $PROG 1 1 1 0
u$USER > ${OUT}c 2>&1

echo "ACID transactions with COMMIT ended. Output in
${OUT}c"
echo ""
echo "Performing $ITER ACID transactions with ROLLBACK"
echo ""

$KIT_DIR/utils/randkey $ITER $SF u$USER | $PROG 1 1 0 0
u$USER > ${OUT}r 2>&1

echo "ACID transactions with ROLLBACK ended. Output in
${OUT}r"
echo ""
echo "Ending Atomicity Test at `date` ..."

/*
NAME
atranspl.c - <one-line expansion of the name>

DESCRIPTION
TPC-HR benchmark ACID transaction driver, OCI version 8

NOTES
<other useful comments, qualifications, etc.>

MODIFIED (MM/DD/YY)
mpoess 10/23/02 - mpoess_update_from_visa
mpoess 10/17/01 - add parameter in ACIDinit
mpoess 02/22/01 - enlarge timing array
mpoess 01/04/01 - Creation

*/
#include <stdio.h>
#include <stdlib.h>
#include <sys/types.h>
#include <sys/stat.h>
#include <fcntl.h>
#include "atranspl.h"

/* Declare error handling functions */

double gettime();
void sql_error();
void usage();
void ACIDinit();
void ACIDexit();
int atoi();
void srand48();
long lrand48();

/* declarations for ORDERS */

int o_key = 0;
double o_tprice = 0.0;
double o_newtprice = 0.0;

/* declarations for LINEITEM */

int l_key = 0;
int l_pkey = 0;
int l_skey = 0;

int l_quan = 0;
int l_newquan = 0;
double l_eprice = 0.0;
double l_neweprice = 0.0;
double l_disc = 0.0;
double l_tax = 0.0;

sb2 l_npricei;

/* other declarations */

int delta = 0;
double rprice;
double cost;

int proc_no = 1; /* process number, global */
int num_streams = 1; /* number of transaction streams */
int trig = 0; /* Trigger Time */
int slp = 0; /* Sleep Time */

int logfile; /* fdes for logfile for durability (optional) */

```

C.4 atranspl.c

/* Copyright (c) 2001, 2002, Oracle Corporation. All rights reserved. */

/*

```

int outfile = 1;      /* output file (optional)          */
#ifndef LINUX
FILE *infile;    /* input file (optional)          */
#else
FILE *infile = stdin; /* input file (optional)          */
/* in the format of <o_key><delta> */
#endif
char lname[UNAME_LEN]; /* username/passwd combo        */
char *passwd;      /* pointer to password          */
char buf[WRITE_BUF_LEN]; /* buffer to write             */
unsigned flag = (unsigned) 0; /* flag to store all sorts of options */
/* */

#define INFILE 0x01u
#define OUTFILE 0x02u
#define LOGFILE 0x04u
#define COMMIT 0x08u
#define DELTA 0x10u

double tr_end = 0.0; /* transaction end time          */
double tr_start = 0.0; /* transaction start time        */
/* */

int num_iter = 0; /* number of iterations          */
time_t curr_time; /* Current Time                 */
/* OCI handles */

OCIEnv *tpcenv = NULL;
OCIServer *tpcsrv = NULL;
OCIError *errhp = NULL;
OCISvcCtx *tpcsvc = NULL;
OCISession *tpcusr = NULL;
OCISstmt *curi = NULL;
OCISstmt *curr = NULL;
OCISstmt *cure1 = NULL;
OCISstmt *cure2 = NULL;

/* OCI bind handles */

#ifdef NOLKEY
OCIBind *l_keyi_bp = NULL;
OCIBind *o_keyi_bp = NULL;
#endif /* NOLKEY */

OCIBind *l_key_bp = NULL;
OCIBind *o_key_bp = NULL;
OCIBind *delta_bp = NULL;
OCIBind *l_pkey_bp = NULL;
OCIBind *l_skey_bp = NULL;
OCIBind *l_quan_bp = NULL;
OCIBind *l_newquan_bp = NULL;
OCIBind *l_tax_bp = NULL;
OCIBind *l_disc_bp = NULL;
OCIBind *l_eprice_bp = NULL;
OCIBind *l_neweprice_bp = NULL;
OCIBind *o_tprice_bp = NULL;
OCIBind *o_newtprice_bp = NULL;
OCIBind *rprice_bp = NULL;
OCIBind *cost_bp = NULL;

OCIBind *l_neweprice1_bp = NULL;
OCIBind *l_newquan1_bp = NULL;
OCIBind *o_key1_bp = NULL;
OCIBind *l_key1_bp = NULL;
OCIBind *o_newtprice2_bp = NULL;

OCIBind *o_key2_bp = NULL;
sword status = OCI_SUCCESS; /* OCI return value */
char sqlstmt[1024];
/* usage: prints the usage of the program */
void usage()
{
    fprintf(stderr,"Usage: atrans.o[st]t <proc_no> <num_streams>
<commit> <delta>\n[i<pathname for input>] [o<pathname for
output>] [d<pathname for durability file>] [u<uid/passwd>] \n\n");
    printf(stderr," proc_no :the process number within this
ACID\n");
    printf(stderr," num_streams :the total number of ACID
transaction streams\n");
    printf(stderr," commit :1 to commit transaction, abort
otherwise\n\n");
    printf(stderr," delta :1 to generate new random delta,
otherwise obtain delta from input\n\n");
    printf(stderr," OPTIONAL PARAMETERS:\n");
    printf(stderr," i<pathname for input> :full path name for input
file - default is stdin\n");
    printf(stderr," o<pathname for output> :full path name for
output file - default is stdout\n");
    printf(stderr," d<pathname for durability> :full path name for
durability success file - must specify for durability test\n");
    printf(stderr," u<uid/passwd> :Username/Password
string - default is tcpd/tcdn");
    printf(stderr," t<trigger> :Trigger Time - sleep
<trigger> seconds before start\n\n");
    printf(stderr," s<sleep> :Sleep Time - sleep <sleep>
seconds before commit or rollback\n\n");
    exit(-1);
}

void ACIDexit()
{
    OCILogoff(tpcsvc,errhp);
    OCIhfree(tpcenv,OCI_HTYPE_STMT);
    OCIhfree(tpcsvc,OCI_HTYPE_SVCCTX);
    OCIhfree(tpcsrv,OCI_HTYPE_SERVER);
    OCIhfree(tpcusr,OCI_HTYPE_SESSION);
}

/* type: 0 if environment handle is passed, 1 if error handle is
passwd */

void sql_error(errhp,status,type)
    OCIError *errhp;
    sword status;
    sword type;
{
    char msg[2048];
    ub4 errcode;
    ub4 msglen;
    int i,j;

    switch(status) {
    case OCI_SUCCESS_WITH_INFO:
        fprintf(stderr, "Error: Statement returned with info.\n");
        if (type)

```

```

(void) OCIErrorGet(errhp,1,NULL,(sb4*)&errcode, (text*)
msg,
2048, OCI_HTYPE_ERROR);
else
(void) OCIErrorGet(errhp,1,NULL,(sb4*)&errcode, (text*)
msg,
2048, OCI_HTYPE_ENV);
fprintf(stderr,"%s\n",msg);
break;
case OCI_ERROR:
fprintf(stderr, "Error: OCI call error.\n");
if (type)
(void) OCIErrorGet(errhp,1,NULL, (sb4 *) &errcode, (text*)
msg,
2048,OCI_HTYPE_ERROR);
else
(void) OCIErrorGet(errhp,1,NULL, (sb4 *) &errcode, (text*)
msg,
2048,OCI_HTYPE_ENV);
fprintf(stderr,"%s\n",msg);
break;
case OCI_INVALID_HANDLE:
fprintf(stderr, "Error: Invalid Handle.\n");
if (type)
(void) OCIErrorGet(errhp,1,NULL, (sb4 *) &errcode, (text*)
msg,
2048,OCI_HTYPE_ERROR);
else
(void) OCIErrorGet(errhp,1,NULL, (sb4 *) &errcode, (text*)
msg,
2048,OCI_HTYPE_ENV);
fprintf(stderr,"%s\n",msg);
break;
}
/* Rollback just in case */

(void) OCITransRollback(tpcsvc,errhp,OCI_DEFAULT);

fprintf(stderr, "Exiting Oracle...\n");
fflush(stderr);

ACIDexit();

exit(1);
}

#endif LINUX
int main(argc,argv)
#else
void main(argc,argv)
#endif
{
    int argc;
    char *argv[];
}

int i;
char line[64];
ub4 errcode;
char msg[2048];
int need_commit = 0;

/* Initialize some variables */
#ifndef LINUX
infile=fopen("/dev/stdin","r");
#endif
strcpy((char *) lname, "tpcd/tpcd");

if ((argc > 10) || (argc < 5)) {
    usage();
}

/* argv[1] - Process Number */
proc_no = atoi(argv[1]);

/* argv[2] - Number of Streams */
num_streams = atoi(argv[2]);

/* argv[3] - Commit? */
if (atoi(argv[3]) == 1)
    BIS(flag, COMMIT);

/* argv[4] - Delta? */
if (atoi(argv[4]) == 1)
    BIS(flag, DELTA);

/* Process optional parameters */
argc -= 4;
argv += 4;

while(-argc) {
    ++argv;
    switch(argv[0][0]) {
    case 'u':
        strncpy((char *) lname, ++(argv[0]), UNAME_LEN);
        if (strchr((char *) lname, '/') == NULL) {
            fprintf(stderr, "Login name must be in the format of
userid/passwd\n");
            usage();
            exit(-1);
        }
        break;
    case 'i':
        if ((infile = fopen(++(argv[0]), "r")) == NULL) {
            fprintf(stderr,"Cannot open input file %s\n", argv[0]);
            fprintf(stderr,"%s\n",strerror(errno));
            exit(-1);
        }
        BIS(flag, INFILE);
        break;
    case 'o':
        if ((outfile = open(++(argv[0]), (O_RDWR | O_SYNC |
O_CREAT), S_IRWXU)) == -1) {
            fprintf(stderr,"Cannot open output file %s\n", argv[0]);
            fprintf(stderr,"%s\n",strerror(errno));
            exit(-1);
        }
        BIS(flag, OUTFILE);
        break;
    case 'd':
        if ((logfile = open(++(argv[0]), (O_RDWR | O_SYNC |
O_CREAT), S_IRWXU)) == -1) {
            fprintf(stderr,"Cannot open durability success file %s\n",
argv[0]);
            fprintf(stderr,"%s\n",strerror(errno));
            exit(-1);
        }
        BIS(flag, LOGFILE);
        break;
    case 'b':
        num_iter = atoi(++(argv[0]));
        break;
    case 't':
        trig = atoi(++(argv[0]));
        break;
    case 's':

```

```

slp = atoi(++(argv[0]));
break;
default:
    fprintf(stderr, "Unknown argument %s\n", argv[0]);
    usage();
    break;
}
}

FPRTF(outfile, "-----\n");
/* Initialize the cursors etc. */
(void) ACIDinit();

/* sleep for some time (triggering) */

sleep(trig);

/* start doing the ACID transactions */

tr_start = gettime();

/* The number of iteration we will run depends on the number of */
/* input lines */
while (fgets(line, 64, infile) != NULL) {

#endif NOLKEY
    sscanf(line, "%d %d\n", &o_key, &delta);

    /* Obtain l_key from l_key query */

    OCIexec(tpcsvc,curi,errhp,1);

    /* l_key is the highest l_linenumber available. We need to pick */
    /* at random a number between 1..l_key. */

    l_key = (int) ((lrand48() % l_key) + 1);
#else
    sscanf(line, "%d %d %d\n", &o_key, &l_key, &delta);
#endif /* NOLKEY */

    /* Generate delta if necessary */

    if (BIT(flag, DELTA))
        delt_a = (int) (floor((drand48() * 100)) + 1);

    /* Now, we are ready to run the ACID transaction. */

    curr_time = time(NULL);

    FPRTF2(outfile, "Starting ACID transaction %d at %s...\n",
    (++num_iter),
    ctime(&curr_time));

    FPRTF1(outfile, "o_key: %d\n", (int) o_key);
    FPRTF1(outfile, "l_key: %d\n", (int) l_key);
    FPRTF1(outfile, "delta: %d\n", (int) delta);

    OCIexec(tpcsvc,curi,errhp,1);

    curr_time = time(NULL);

    if (!BIT(flag, LOGFILE)) {
        FPRTF1(outfile, "BEFORE COMMIT/ROLLBACK
TRANSACTION at %s\n", ctime(&curr_time));
        FPRTF1(outfile, "l_extendedprice: %.2f\n", l_eprice);
        FPRTF1(outfile, "l_quantity:    %d\n", (int) l_quan);
        FPRTF1(outfile, "o_totalprice: %.2f\n", o_tprice);
    }
}

}

FPRTF1(outfile, "Sleep %d seconds before
COMMIT/ROLLBACK...\n\n", slp);
sleep(slp);

/* Shall we commit? */

if (BIT(flag, COMMIT)) {
    need_commit = 1;
    while (need_commit) {
        if((status=OCITransCommit(tpcsvc,errhp,OCI_DEFAULT)) !=
        OCI_SUCCESS) {
            OCIrol(tpcsvc,errhp);
            OCIexec(tpcsvc,curr,errhp,1);
        } else {
            need_commit = 0;
            curr_time = time(NULL);
            FPRTF2(outfile, "ACID Transaction iteration %d
COMMITTED at %s\n",
            num_iter, ctime(&curr_time));
        }
    }
} else {
    OCIrol(tpcsvc,errhp);
    curr_time = time(NULL);
    FPRTF2(outfile, "ACID Transaction iteration %d ROLLBACK
at %s\n",
    num_iter, ctime(&curr_time));
}

/* Report all results to outfile and if necessary, to success file. */

/* Report initial and new values for o_totalprice, l_extendedprice,
*/
/* l_quantity. */
/*
curr_time = time(NULL);
FPRTF1(outfile, "Transaction Completed at %s\n",
ctime(&curr_time));
*/
/*
/* Get the values in LINEITEM and ORDERS after the
transaction */

if (BIT(flag, LOGFILE)) {
    FPRTF1(logfile, "p_key:   %d\n", (int) l_pkey);
    FPRTF1(logfile, "s_key:   %d\n", (int) l_skey);
    FPRTF1(logfile, "o_key:   %d\n", (int) o_key);
    FPRTF1(logfile, "l_key:   %d\n", (int) l_key);
    FPRTF1(logfile, "delta:   %d\n", (int) delta);
    FPRTF1(logfile, "Transaction Completed at %s\n",
    ctime(&curr_time));
    FPRTF(logfile, "-----\n");
} else {
    OCIexec(tpcsvc,cure1,errhp,1);
    OCIexec(tpcsvc,cure2,errhp,1);
}

FPRTF(outfile, "AFTER TRANSACTION:\n");
FPRTF1(outfile, "l_extendedprice: %.2f\n", l_neweprice);
FPRTF1(outfile, "l_quantity:    %d\n", (int) l_newquan);
FPRTF1(outfile, "o_totalprice: %.2f\n", o_newtprice);
FPRTF1(outfile, "l_tax:      %.2f\n", l_tax);
FPRTF1(outfile, "l_discount: %.2f\n", l_disc);
FPRTF1(outfile, "rprice:     %.2f\n", rprice);
FPRTF1(outfile, "cost:       %.2f\n", cost);
FPRTF(outfile, "-----\n");
}

```

```

}

tr_end = gettime();

if (!BIT(flag,LOGFILE)) {
    FPRTF1(outfile, "Start Time: %.2f\n", tr_start);
    FPRTF1(outfile, "End Time: %.2f\n", tr_end);
    FPRTF1(outfile, "Elapsed Time: %.2f\n", (tr_end - tr_start));
    FPRTF1(outfile, "Transaction Count: %d\n", num_iter);
    FPRTF1(outfile, "Transaction Rate: %.2f\n", num_iter/(tr_end - tr_start));
} else {
    FPRTF1(logfile, "Start Time: %.2f\n", tr_start);
    FPRTF1(logfile, "End Time: %.2f\n", tr_end);
    FPRTF1(logfile, "Elapsed Time: %.2f\n", (tr_end - tr_start));
    FPRTF1(logfile, "Transaction Count: %d\n", num_iter);
}

/* Disconnect from ORACLE. */

if (BIT(flag, INFILE))
    fclose(infile);
if (BIT(flag, OUTFILE))
    close(outfile);
if (BIT(flag, LOGFILE))
    close(logfile);

ACIDexit();

exit(0);
}

void ACIDinit()
{
    /* run random seed */

    srand48(getpid());

    /* Connect to ORACLE. Program will call sql_error()
       if an error occurs in connecting to the default database. */

    (void) OCIInitialize(OCI_DEFAULT,(dvoid *)0,0,0,0);
    if((status=OCIEnvInit((OCIEnv
    **)&tpcenv,OCI_DEFAULT,0,(dvoid **)0)) != OCI_SUCCESS)
        sql_error(tpcenv, status, 0);

    OCHalloc(tpcenv,&enrh,OCL_HTYPE_ERROR);
    OCHalloc(tpcenv,&curi,OCL_HTYPE_STMT);
    OCHalloc(tpcenv,&curr,OCL_HTYPE_STMT);
    OCHalloc(tpcenv,&curl1,OCL_HTYPE_STMT);
    OCHalloc(tpcenv,&curl2,OCL_HTYPE_STMT);
    OCHalloc(tpcenv,&tpcsvc,OCL_HTYPE_SVCCTX);
    OCHalloc(tpcenv,&tpcsrv,OCL_HTYPE_SERVER);
    OCHalloc(tpcenv,&tpcusr,OCL_HTYPE_SESSION);

    /* Disables auto commit */
    /*
    if (ocof(&tpclda)) {
        sql_error(&tpclda, &tpclda);
        ologof(&tpclda);
        exit(-1);
    }
    */

    /* get username and password */
    passwd = strchr(lname, '/');
}

    *passwd = '\0';
    passwd++;

    if ((status = OCIServerAttach(tpcsrv,v,errhp,(text
    *)0,OCI_DEFAULT)) != OCI_SUCCESS)
        sql_error(errhp,status,1);

    OCIaset(tpcsvc,OCL_HTYPE_SVCCTX,tpcsrv,0,OCI_ATTR_SER
    VER,errhp);

    OCIaset(tpcusr,OCL_HTYPE_SESSION,lname,strlen(lname),OCI_
    ATTR_USERNAME,
    errhp);

    OCIaset(tpcusr,OCL_HTYPE_SESSION,passwd,strlen(passwd),OCI
    _ATTR_PASSWORD,
    errhp);

    if ((status = OCISessionBegin(tpcsvc, errhp, tpcusr,
    OCI_CRED_RDBMS,
    OCI_DEFAULT)) != OCI_SUCCESS)
        sql_error(errhp,status,1);

    OCIaset(tpcsvc,OCL_HTYPE_SVCCTX,tpcusr,0,OCI_ATTR_SESS
    ION,errhp);

    /* Enable session parallel dml */

    sprintf((char *) sqlstmt, PDMLTXT);
    OCIStmtPrepare(curi,errhp,(text *)sqlstmt,strlen((char *)sqlstmt),
    OCI_NTV_SYNTAX,OCI_DEFAULT);
    OCIexec(tpcsvc,curi,errhp,1);

    /* Enable session parallel ddl */

    /*sprintf((char *) sqlstmt, PDDLTXT);
    OCIStmtPrepare(curi,errhp,(text *)sqlstmt,strlen((char *)sqlstmt),
    OCI_NTV_SYNTAX,OCI_DEFAULT);
    OCIexec(tpcsvc,curi,errhp,1);*/

    /* Make session serializable */

    sprintf ((char *) sqlstmt, ISOTXT);
    OCIStmtPrepare(curi,errhp,(text *)sqlstmt,strlen((char *)sqlstmt),
    OCI_NTV_SYNTAX,OCI_DEFAULT);
    OCIexec(tpcsvc,curi,errhp,1);

    /* Set optimizer_index_cost_adj = 25 */

    sprintf ((char *) sqlstmt, OICATXT);
    OCIStmtPrepare(curi,errhp,(text *)sqlstmt,strlen((char *)sqlstmt),
    OCI_NTV_SYNTAX,OCI_DEFAULT);
    OCIexec(tpcsvc,curi,errhp,1);

    curr_time = time(NULL);
    printf("\nConnected to ORACLE as user: %s at %s\n", lname,
    ctime(&curr_time));

#ifndef NOLKEY
    /* Open and Parse cursor for query to choose determine l_key. */
    /* Binds l_key to :l_key. */

    sprintf((char *) sqlstmt,SQLTXT1);
    OCIStmtPrepare(curi,errhp,sqlstmt,strlen((char
    *)sqlstmt),OCI_NTV_SYNTAX,OCI_DEFAULT);

```

```

OCIbbname(curi,&l_keyi_bp,errhp,:l_key",ADR(l_key),SIZ(l_key)
,SQLT_INT);

OCIbbname(curi,&o_keyi_bp,errhp,:o_key",ADR(o_key),SIZ(o_ke
y),SQLT_INT);

#endif /* NOLKEY */

/* Open and Parse cursor for the ACID transaction. */

sprintf((char *) sqlstmt,SQLTXT2);
OCIStmtPrepare(curr,errhp,(text *)sqlstmt,strlen((char *)sqlstmt),
OCI_NTV_SYNTAX,OCI_DEFAULT);

/* bind variables */

OCIbbname(curr,l_key_bp,errhp,:l_key",ADR(l_key),SIZ(l_key),S
QLT_INT);

OCIbbname(curr,o_key_bp,errhp,:o_key",ADR(o_key),SIZ(o_key)
,SQLT_INT);

OCIbbname(curr,delta_bp,errhp,:delta",ADR(delta),SIZ(delta),SQL
T_INT);

OCIbbname(curr,l_pkey_bp,errhp,:l_pkey",ADR(l_pkey),SIZ(l_pk
ey),SQLT_INT);

OCIbbname(curr,l_skey_bp,errhp,:l_skey",ADR(l_skey),SIZ(l_ske
y),SQLT_INT);

OCIbbname(curr,l_quan_bp,errhp,:l_quan",ADR(l_quan),SIZ(l_qu
an),SQLT_INT);

OCIbbname(curr,l_newquan_bp,errhp,:l_newquan",ADR(l_newqua
n),
SIZ(l_newquan),SQLT_INT);

OCIbbname(curr,l_tax_bp,errhp,:l_tax",ADR(l_tax),SIZ(l_tax),SQ
LT_FLT);

OCIbbname(curr,l_disc_bp,errhp,:l_disc",ADR(l_disc),SIZ(l_disc),
SQLT_FLT);

OCIbbname(curr,l_eprice_bp,errhp,:l_eprice",ADR(l_eprice),SIZ(l
_eprice),
SQLT_FLT);

OCIbbname(curr,l_neweprice_bp,errhp,:l_neweprice",ADR(l_newe
price),
SIZ(l_neweprice),SQLT_FLT);

OCIbbname(curr,o_tprice_bp,errhp,:o_tprice",ADR(o_tprice),SIZ(
o_tprice),
SQLT_FLT);

OCIbbname(curr,o_newtprice_bp,errhp,:o_newtprice",ADR(o_new
tprice),
SIZ(o_newtprice),SQLT_FLT);

OCIbbname(curr,rprice_bp,errhp,:rprice",ADR(rprice),SIZ(rprice),
SQLT_FLT);
OCIbbname(curr,cost_bp,errhp,:cost",ADR(cost),SIZ(cost),
SQLT_FLT);

/* Open & Parse cursor for end values query */

```

```

sprintf((char *) sqlstmt,SQLTXT3);
OCIStmtPrepare(cure1,errhp,(text *)sqlstmt,strlen((char *)sqlstmt),
OCI_NTV_SYNTAX,OCI_DEFAULT);

sprintf((char *) sqlstmt,SQLTXT4);
OCIStmtPrepare(cure2,errhp,(text *)sqlstmt,strlen((char *)sqlstmt),
OCI_NTV_SYNTAX,OCI_DEFAULT);

/* bind variables */

OCIbbname(cure1,l_neweprice1_bp,errhp,:l_neweprice",ADR(l_ne
weprice),
SIZ(l_neweprice),SQLT_FLT);

OCIbbname(cure1,l_newquan1_bp,errhp,:l_newquan",ADR(l_new
quan),
SIZ(l_newquan),SQLT_INT);

OCIbbname(cure1,o_key1_bp,errhp,:o_key",ADR(o_key),SIZ(o_k
ey),SQLT_INT);

OCIbbname(cure1,l_key1_bp,errhp,:l_key",ADR(l_key),SIZ(l_key
),SQLT_INT);

OCIbbname(cure2,o_newtprice2_bp,errhp,:o_newtprice",ADR(o_n
ewtprice),
SIZ(o_newtprice),SQLT_FLT);

OCIbbname(cure2,o_key2_bp,errhp,:o_key",ADR(o_key),SIZ(o_k
ey),SQLT_INT);

}


```

C.5 atranspl.h

/* Copyright (c) 2001, 2002, Oracle Corporation. All rights reserved. */

```

/*
 NAME
 atranspl.h - <one-line expansion of the name>

 DESCRIPTION

 MODIFIED (MM/DD/YY)
 mpoess 10/23/02 - mpoess_update_from_visa
 mpoess 10/17/01 - add TXT parameter
 mpoess 04/09/01 - add hint to find max linenumber
 mpoess 01/04/01 - Creation

```

```

*/
#ifndef ATRANSPL_H

#define ATRANSPL_H

#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <sys/param.h>
#include <sys/types.h>
#include <time.h>
#include <errno.h>
#include <math.h>
```

```

#include <oratypes.h>
#ifndef OCIDFN
#include <ocidfn.h>
#endif /* OCIDFN */

#ifndef OCI_ORACLE
#include <oci.h>
#endif /* OCI_ORACLE */

/*
#ifndef __STDC__
#include <ociapr.h>
#else
#include <ocikpr.h>
#endif /* __STDC__ */
extern int errno;

#ifndef NULL
#define NULL 0
#endif

#ifndef NULLP
#define NULLP (void *)NULL
#endif /* NULLP */

#ifndef DISCARD
#define DISCARD (void)
#endif

#ifndef sword
#define sword int
#endif

#ifndef ub1
#define ub1 unsigned char
#endif

#define UNAME_LEN 64
#define WRITE_BUF_LEN 1024

#define NA -1 /* ANSI SQL NULL */
#define VER7 2
#define NOT_SERIALIZABLE 8177 /* ORA-08177: transaction
not serializable */
#define WRITE_BUF_LEN 1024

#define ADR(object) ((ub1 *)&(object))
#define SIZ(object) ((sword)sizeof(object))
#define BIS(flg,mask) (unsigned) (flg |= (unsigned) mask)
#define BIT(flg,mask) (unsigned) (unsigned) flg & (unsigned) mask)

#define FPRTF(fd,s) \
{sprintf(buf,s); write(fd, buf, strlen(s));}
#define FPRTF1(fd,s,p) \
{sprintf(buf,s,p); write(fd, buf, strlen(buf));}
#define FPRTF2(fd,s,p1,p2) \
{sprintf(buf,s,p1,p2); write(fd, buf, strlen(buf));}

#define OCIalloc(envh,hndl,htyp) \
if((stat us=OCIBHandleAlloc((dvoid *)envh,(dvoid \
**)hndl,htyp,0,(dvoid **))!=OCI_SUCCESS) \
sql_error(envh,status,0); \
else \
DISCARD 0

#define OCIhfree(hndl,htyp) \
if((status=OCIBHandleFree((dvoid *)hndl,htyp))== \
OCI_SUCCESS) \
printf(stderr, "Error freeing handle of type %d\n", htyp)

#define OCIaget(hndl,htyp,attp,size,atyp,errh) \
if((status=OCIAAttrGet((dvoid *)hndl,htyp,(dvoid *)attp,(dvoid \
*)size,atyp,errh)) != OCI_SUCCESS) \
sql_error(errh,status,1); \
else \
DISCARD 0

#define OCIaset(hndl,htyp,attp,size,atyp,errh) \
if((status=OCIAAttrSet((dvoid *)hndl,htyp,(dvoid \
*)attp,size,atyp,errh)) != OCI_SUCCESS) \
sql_error(errh,status,1); \
else \
DISCARD 0

#define OCIexec(svch,stmh,errh,iter) \
if((status=OCIStmtExecute(svch,stmh,errh,iter,0,NULL,NULL,OCI \
_DEFAULT)) != OCI_SUCCESS) \
sql_error(errh,status,1); \
else \
DISCARD 0

#define OCIbbname(stmh,bindp,errh,sqlvar,progv,progvl,ftype) \
if((status=OCIBBindByName(stmh,&bindp,errh,(text \
*)sqlvar,strlen(sqlvar), \
progv,progvl,ftype,0,0,0,0,OCI_DEFAULT)) != \
OCI_SUCCESS) \
sql_error(errh,status,1); \
else \
DISCARD 0

#define OCIbbnamei(stmh,bindp,errh,sqlvar,progv,progvl,ftype,indp) \
if((status=OCIIHandleAlloc((dvoid *)stmh,(dvoid \
**)&bindp,OCI_HTYPE_BIND, \
0,(dvoid **))!=OCI_SUCCESS) \
sql_error(stmh,status,0); \
if((status=OCIBBindByName(stmh,&bindp,errh,(text \
*)sqlvar,strlen(sqlvar), \
progv,progvl,ftype,indp,0,0,0,OCI_DEFAULT)) != \
OCI_SUCCESS) \
sql_error(errh,status,1); \
else \
DISCARD 0

#define OCIcom(svcp,errh) \
if((status=OCITransCommit(svcp,errh,OCI_DEFAULT)) != \
OCI_SUCCESS) \
sql_error(errh,status,1); \
else \
DISCARD 0

#define OCIrol(svcp,errh) \
if((status=OCITransRollback(svcp,errh,OCI_DEFAULT)) != \
OCI_SUCCESS) \
sql_error(errh,status,1); \
else \
DISCARD 0

#define ISOTXT "alter session set isolation_level = serializable"
#define PDMLTXT "alter session force parallel dml parallel (degree \
4)"
#define PDDLTXT "alter session force parallel ddl parallel (degree \
4)"
#define OICATXT "alter session set optimizer_index_cost_adj=25"

```

```

#define SQLTXT1 "BEGIN SELECT /*+
index(lineitem,i_l_orderkey) */ MAX(l_linenumber) INTO :l_key
FROM lineitem \
WHERE l_orderkey = :o_key; END;"

#define SQLTXT2 "BEGIN d_atrans.doatrans(:l_key, :o_key, :delta,
:l_pkey, \
:l_skey, :l_quan, :l_newquan, :l_tax, :l_disc, :l_eprice, :l_neweprice,
\
:o_tprice, :o_newtprice, :rprice, :cost); END;"

#define SQLTXT3 "BEGIN SELECT l_extendedprice, l_quantity \
INTO :l_neweprice, :l_newquan \
FROM lineitem \
WHERE l_orderkey = :o_key \
AND l_linenumber = :l_key; END;"

#define SQLTXT4 "BEGIN SELECT o_totalprice INTO
:o_newtprice \
FROM orders \
WHERE o_orderkey = :o_key; END;"

#define SQLTXT5 "BEGIN SELECT l_extendedprice, l_quantity \
INTO :l_eprice, :l_quan \
FROM lineitem \
WHERE l_orderkey = :o_key \
AND l_linenumber = :l_key; END;"

#define SQLTXT6 "BEGIN SELECT o_totalprice INTO :o_tprice \
FROM orders \
WHERE o_orderkey = :o_key; END;"

#endif /* ATRANSPL_H */

```

C.6 ckpt.sh

```

#!/bin/ksh
#
# $Header: ckpt.sh 08-aug-99.17:37:07 mpoess Exp $
#
# ckpt.sh
#
# Copyright (c) Oracle Corporation 1999. All Rights Reserved.
#
# NAME
#   ckpt.sh - <one-line expansion of the name>
#
# DESCRIPTION
#   Usage: ckpt.sh
#   Start database checkpoint
#
# NOTES
#   <other useful comments, qualifications, etc.>
#
# MODIFIED (MM/DD/YY)
#   mpoess 08/08/99 - Creation
#   mpoess 08/08/99 - Creation
#
. $KIT_DIR/env

sqlplus -s /NOLOG << !
    connect / as sysdba;
    alter system switch logfile;
    alter system switch logfile;
    exit;
!

KEY=$OUT_DIR/key$$_
OUTFILE=${OUT_DIR}/consrte
CON1=${OUT_DIR}/conb
CON2=${OUT_DIR}/cona
CHK=${OUT_DIR}/consckpt

/bin/rm -rf ${KEY}* $CON1 $CON2 $OUTFILE $CHK
trap "/bin/rm -rf ${KEY}*; exit 1" 1 2 3 15

STREAM=${NUM_STREAMS}
let STREAM="$STREAM + 1" # add one for the update stream
ITER=100
PROG=atranspl
USER=${DATABASE_USER}
CK=10

usage() {
    echo ""
    echo "Usage: $0 [-n iter] [-s number of stream] [-p prog] [-u
usr/pwd] -h"
    echo ""
    echo "  -n iter      : number of iterations, default is 100"
}
```

C.7 cnt_hist.sql

```

select count(*) from history;
exit;

```

C.8 consist.sh

```

#!/bin/ksh
#
# $Header: consist.sh 08-aug-99.14:20:51 mpoess Exp $
#
# consist.sh
#
# Copyright (c) Oracle Corporation 1999. All Rights Reserved.
#
# NAME
#   consist.sh - <one-line expansion of the name>
#
# DESCRIPTION
#   Performs consistency tests.
#   Usage: consist.sh [-n iter] [-s number of stream] [-p prog]
#           [-u usr/pwd] -h
#
# Options: See usage below
#
# NOTES
#   <other useful comments, qualifications, etc.>
#
# MODIFIED (MM/DD/YY)
#   mpoess 08/08/99 - Creation
#   mpoess 08/08/99 - Creation
#
. $KIT_DIR/env

```

```

OH=$ORACLE_HOME
#ACID_DIR=$TPCD_KIT_DIR/audit set in env
OUT_DIR=$ACID_OUT

KEY=$OUT_DIR/key$$_
OUTFILE=${OUT_DIR}/consrte
CON1=${OUT_DIR}/conb
CON2=${OUT_DIR}/cona
CHK=${OUT_DIR}/consckpt

/bin/rm -rf ${KEY}* $CON1 $CON2 $OUTFILE $CHK
trap "/bin/rm -rf ${KEY}*; exit 1" 1 2 3 15

STREAM=${NUM_STREAMS}
let STREAM="$STREAM + 1" # add one for the update stream
ITER=100
PROG=atranspl
USER=${DATABASE_USER}
CK=10

usage() {
    echo ""
    echo "Usage: $0 [-n iter] [-s number of stream] [-p prog] [-u
usr/pwd] -h"
    echo ""
    echo "  -n iter      : number of iterations, default is 100"
}
```

```

echo "-s number of stream : number of streams, default is 2"
echo "-p prog      : program to run, default is atranspl.ott"
echo "-u usr/pswd   : user/password for database access, default
is tpccd/tpcd"
echo "-t chkpt     : time after the start of ACID transaction to
perform the checkpoint"
echo "          default is 10 seconds"
echo "-h          : print this usage summary"
exit 1;
}

set --`getopt "n:p:u:s:h" "$@"` || usage

while :
do
  case "$1" in
    -s) shift; STREAM=$1;;
    -n) shift; ITER=$1;;
    -p) shift; PROG=$1;;
    -u) shift; USER=$1;;
    -t) shift; CK=$1;;
    -h) usage; exit 0;;
    -) break;;
  esac
  shift
done

if [ $ITER -lt 100 ]
then
echo "Error: Must at least run 100 iterations!"
echo "Exiting..."
exit 1
fi

if [ $STREAM -lt 2 ]
then
echo "Error: Must at least run 2 streams!"
echo "Exiting..."
exit 1
fi

echo "Starting Consistency Test at `date`..."
echo ""
echo "Generate some keys first"
echo ""

i=0

while [ $i -lt $STREAM ]
do
  echo randkey $ITER 1 u$USER
  randkey $ITER 1 u$USER > ${KEY}${i}
  i=`expr $i + 1`
done

echo "Check consistency before Submitting Transactions `date`"
echo "Check consistency before Submitting Transactions `date`" >>
$CON1

echo "Obtain 10 keys from the each key file to check consistency"

i=0
while [ $i -lt $STREAM ]
do
  KEYS=`head -10 ${KEY}${i} | awk '{printf "%d ", $1}'`"
  echo "The 10 Keys for file $i are: $KEYS"
  #for j in `head -10 ${KEY}${i} | awk '{printf "%d ", $1}'`"
  for j in $KEYS
  do
    sqlplus $USER @/dbms/oracle10i/kit/acid/consistency/consist $j
    >> $CON1
    echo "-----" >> $CON1
    done
    i=`expr $i + 1`
  done
done

sqlplus $USER @/dbms/oracle10i/kit/acid/consistency/consist $j
>> $CON1
echo "-----" >> $CON1
done
i=`expr $i + 1`
done

echo ""
echo "Starting ACID transactions at `date`"
echo ""

i=0

while [ $i -lt $STREAM ]
do
  SPROG $i $STREAM 1 0 u${USER} i${KEY}${i}
  o${OUTFILE}${i} s1 &
  i=`expr $i + 1`
done

echo "Schedule a Checkpoint"
echo "Checkpoint scheduled at $CK seconds after `date`"
(sleep $CK; $ACID_DIR/ckpt.sh) &

wait

echo ""
echo "Ending ACID transactions at `date`"
echo ""

echo "Complet ed $STREAM transaction streams with $ITER
iterations each"
echo ""

echo "Check consistency after Submitting Transactions `date`"
echo "Check consistency after Submitting Transactions `date`" >>
$CON2

cat ${ORACLE_HOME}/rdbms/log/alert_${ORACLE_SID}.log >>
$CHK

i=0
while [ $i -lt $STREAM ]
do
  KEYS=`head -10 ${KEY}${i} | awk '{printf "%d ", $1}'`"
  #for j in `head -10 ${KEY}${i} | awk '{printf "%d ", $1}'`"
  echo "The keys to check for consistency after the test from file $i
are:"
  echo "$KEYS"
  for j in $KEYS
  do
    sqlplus $USER @/dbms/oracle10i/kit/acid/consistency/consist $j
    >> $CON2
    echo "-----" >> $CON2
  done
  i=`expr $i + 1`
done

```

C.9 consist.sql

```

Rem
Rem $Header: consist.sql 08-aug-99.16:59:17 mpoess Exp $
Rem
Rem consist.sql
Rem
Rem Copyright (c) Oracle Corporation 1999. All Rights Reserved.
Rem

```

```

Rem NAME
Rem   consist.sql - <one-line expansion of the name>
Rem
Rem DESCRIPTION
Rem   Verifies the consistency of TPC-D database using the
Rem   consistency condition.
Rem
Rem Usage: sqlplus tpcd/tpcd @consist
Rem
Rem NOTE
Rem REQUIRES PACKAGES prvtotpt and dbmsotpt
rem
Rem MODIFIED (MM/DD/YY)
Rem mpoess 08/08/99 - Creation
Rem mpoess 08/08/99 - Created
Rem

set verify off
rem set termout on
rem set echo on

REM
REM Get today's date.
REM

select
substr(TO_CHAR(sysdate,'YYYY-MM-DD HH:MI:SS'),1,20) as
CURRENT_TIME
from dual;

set serverout on;

DECLARE
    o_okey      number;
    o_tprice    number;
    l_tprice    number;
    diff        number;
BEGIN
    select o_totalprice
    into o_tprice
    from orders
    where o_orderkey = &&1;

    select sum(trunc((trunc(l_extendedprice * (1-l_discount)), 2)
    * (1+l_tax)), 2))
    into l_tprice
    from lineitem
    where l_orderkey = &&1;

    diff := l_tprice - o_tprice;

    dbms_output.put_line('O_TOTALPRICE: ' ||
TO_CHAR(trunc(o_tprice,2)));
    dbms_output.put_line('L_TOTALPRICE: ' ||
TO_CHAR(trunc(l_tprice,2)));
    dbms_output.put_line('Difference: ' || TO_CHAR(trunc(diff,2)));

END;
/
spool off
exit

```

C.10 count_tx.sh

```

#!/bin/ksh

STEM=$1
ITER=$2
OUT=$3
FIN=FALSE
while [ "$FIN" = "FALSE" ]
do
    s=0
    FIN=TRUE
    while [ $s -lt $STEM ]
    do
        nt=`grep "Transaction Completed" $OUT/dura${s} | wc -l`
        if [ $nt -lt $ITER ];then
            FIN=FALSE
        fi
        s=`expr $s + 1`
    done
    sleep 5
done
echo all streams have committed $ITER transactions

```

C.11 d_hist.sql

```

Rem
Rem $Header: d_hist.sql 07-aug-99.21:33:08 mpoess Exp $
Rem
Rem d_hist.sql
Rem
Rem Copyright (c) Oracle Corporation 1999. All Rights Reserved.
Rem
Rem NAME
Rem   d_hist.sql - <one-line expansion of the name>
Rem
Rem DESCRIPTION
Rem   Creates a history table for ACID test purpose.
Rem
Rem NOTES
Rem   <other useful comments, qualifications, etc.>
Rem
Rem MODIFIED (MM/DD/YY)
Rem mpoess 08/07/99 - Creation
Rem mpoess 08/07/99 - Created
Rem

set termout on;
set serverout on;
set echo on;

drop table history;
create table history
(
    h_p_key  number,
    h_s_key  number,
    h_o_key  number,
    h_l_key  number,
    h_delta  number,
    h_date_t date
);
exit;

```

C.12 end_acid.sh

```
#!/bin/ksh
#
# $Header: end_acid.sh 08-aug-99.17:06:20 mpoess Exp $
#
# end_acid.sh
#
# Copyright (c) Oracle Corporation 1999. All Rights Reserved.
#
# NAME
#   end_acid.sh - <one-line expansion of the name>
#
# DESCRIPTION
#   end_cons.sh <pid of the durability run>
#   Options: See usage below
#
# NOTES
#   <other useful comments, qualifications, etc.>
#
# MODIFIED (MM/DD/YY)
#   mpoess 08/08/99 - Creation
#   mpoess 08/08/99 - Creation
#
. $KIT_DIR/env

OH=$ORACLE_HOME
# ACID_DIR=$OH/tacd/audit set in env
OUT_DIR=$ACID_OUT/
DURA_DIR=$ACID_OUT/dura
RUN_ID_FILE=$ACID_DIR/run_id

SHELL_PID=`cat ${DURA_DIR}/shellpid`
ITER=100
STEM=${NUM_STREAMS}
let STEM="$STEM + 1" # add one for the update stream
PROG=${ACID_DIR}/atranspl.ott
IN=${ACID_DIR}/acid_in
DURA=${DURA_DIR}/drate
OUT=${DURA_DIR}/drate
DSMPL=${DURA_DIR}/durasmpl
KEY=${DURA_DIR}/key${SHELL_PID}
USER=tpch/tpch
TRIG=1
HCNT=duracnta

# get history count

sqlplus $USER @cnt_hist > $DURA_DIR/$HCNT 2>&1

# perform the consistency

i=0
while [ $i -lt $STEM ]
do
  for j in `head -10 ${KEY}${i} | awk '{printf "%d ",$1}'` do
    sqlplus tpch/tpch @consist $j >> $DURA_DIR/duraconsa
  done
  i=`expr $i + 1`
done

i=0
while [ $i -lt $STEM ]
do
  sample.sh $DURA${i} > ${DSMPL}${i} 2>&1
  i=`expr $i + 1`
done
```

```
cat $ORACLE_HOME/rdbms/log/alert_1g.log >
${DURA_DIR}/alert_1g.log.post_dura 2>&1
```

C.13 iso.sh

```
#!/bin/ksh
#
# $Header: iso.sh 17-aug-99.15:44:51 mpoess Exp $
#
# iso.sh
#
# Copyright (c) Oracle Corporation 1999. All Rights Reserved.
#
# NAME
#   iso.sh
#
# DESCRIPTION
#   This script triggers all 6 isolation tests. In addition,
#   it creates more readable formats of the isolation test output.
#
# NOTES
#   <other useful comments, qualifications, etc.>
#
# MODIFIED (MM/DD/YY)
#   mpoess 08/17/99 - Creation
#   mpoess 08/17/99 - Creation
#
for iso in iso1 iso2 iso3 iso4 iso5 iso6;do
  echo Running isolation test $iso
  /dbms/oracle10i/kit/acid/isolation/${iso}.sh
  echo Creating nicely formated output of ACID test $iso
  /dbms/oracle10i/kit/acid/isolation/xiso.pl -o
${ACID_OUT}/${iso}
done
```

C.14 iso1.sh

```
#!/bin/ksh
#
# $Header: iso1.sh 29-jul-98.17:00:11 akarasik Exp $
#
# iso1.sh
#
# Copyright (c) Oracle Corporation 1998. All Rights Reserved.
#
# NAME
#   iso1.sh
#
# DESCRIPTION
#   Usage: iso1.sh [-u user/password] [-n remote_node] -h
#   Options: See usage below
#
# NOTES
#   For a cross node isolation test, assume the local node is
#   one of the participating nodes. The other node can be
#   specified by the -n option.
#   You need to set the environment variable TPCD_KIT_DIR
#
# MODIFIED (MM/DD/YY)
#   mpoess 12/16/98 - update to version 8.1.6
#   mpoess 09/25/98 - update audit
#   akarasik 07/29/98 -
#   akarasik 07/29/98 - Creation
#
. $KIT_DIR/env
```

```

# May need to change the following:
RSH=rsh

OH=$ORACLE_HOME
#ACID_DIR=$KIT_DIR/acid is set in env
OUT_DIR=$ACID_OUT

TXN1FILE=$OUT_DIR/txn1$$out
TXN2FILE=$OUT_DIR/txn2$$out
KEYFILE=$OUT_DIR/key$$out
ISOFILE=$OUT_DIR/iso1

USER=$DATABASE_USER
PROG=atranspl

/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE

trap "/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE; exit 1" 1 2 3
15

usage() {

echo """
echo "Usage: $0 [-u user/password] [-n remote_node] -h"
echo """
exit 1;
}

set -- ` getopt "u:n:h" "$@" || usage

while :
do
  case "$1" in
    -u) shift; USER=$1;;
    -n) shift; HOST="$1";;
    -h) usage; exit 0;;
    -) break;;
    esac
    shift;
done

de=`direxists.sh $ACID_OUT c` # I am not using $de afterward, but
I want to avoid the output of direxists

# generate key files
randkey 1 0.1 u"$USER" > $KEYFILE

OKEY=`cat $KEYFILE | awk '{print $1}'`
echo "o_key is \"$OKEY"

# before the ACID transaction, let's run a ACID query to record the
# initial state of lineitem

echo "Running ACID query BEFORE the start of Isolation Test 1"
>> $TXN2FILE
echo "'date'" >> $TXN2FILE
echo "" >> $TXN2FILE
sqlplus $USER @$ACID_DIR/isolation/a_query $OKEY >>
$TXN2FILE
echo "" >> $TXN2FILE
echo "-----" >> $TXN2FILE

sleep 1

# start ACID transaction, Sleep for 60 second before COMMIT
$PROG 1 1 0 i$KEYFILE u$USER s60 b0 >> $TXN1FILE &

# let's sleep 10 seconds before starting ACID query
sleep 10

# start ACID query with the same OKEY

echo "Running ACID query 10 seconds AFTER the start of ACID
Transaction" \
>> $TXN2FILE
echo "'date'" >> $TXN2FILE
if [ "$HOST" != "" ]
then
echo "Starting ACID query on node $HOST" >> $TXN2FILE
$RSH -n $HOST sqlplus $USER
@$ACID_DIR/isolation/a_query $OKEY >> $TXN2FILE
else
sqlplus $USER @$ACID_DIR/isolation/a_query $OKEY >>
$TXN2FILE
fi

echo "-----" >> $TXN2FILE
wait
echo "-----" >> $TXN1FILE
cat $TXN1FILE $TXN2FILE >> $ISOFILE
/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE

```

C.15 iso2.sh

```

#!/bin/ksh
#
# $Header: iso2.sh 04-aug-99.09:19:54 mpoess Exp $
#
# iso2.sh
#
# Copyright (c) Oracle Corporation 1999. All Rights Reserved.
#
# NAME
#   iso2.sh - <one-line expansion of the name>
#
# DESCRIPTION
#   Usage: iso2.sh [-u user/password] [-n remote_node] -h
#   Options: See usage below
#
# NOTES
#   For a cross node isolation test, assume the local node is
#   one of the participating nodes. The other node can be
#   specified by the -n option.
#   You need to set the environment variable TPCD_KIT_DIR
#
# MODIFIED (MM/DD/YY)
# mpoess 08/04/99 - Creation
# mpoess 08/04/99 - Creation
#
#
=====
=====+
# May need to change the following:
. $KIT_DIR/env

RSH=rsh

OH=$ORACLE_HOME
# ACID_DIR=$TPCD_KIT_DIR/audit is set in env

```

```

OUT_DIR=$ACID_OUT
DURA_DIR=$ACID_DIR/dura
TXN1FILE=$OUT_DIR/txn1$$$.out
TXN2FILE=$OUT_DIR/txn2$$$.out
KEYFILE=$OUT_DIR/key$$$.out
ISOFILE=$OUT_DIR/iso2

USER=$DATABASE_USER
PROG=atranspl

/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE

trap "/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE; exit 1" 1 2 3
15

usage() {
    echo ""
    echo "Usage: $0 [-u user/passwd] [-n remote_node] -h"
    echo ""
    exit 1;
}

set --`getopt "u:n:h" "$@"` || usage

while :
do
    case "$1" in
        -u) shift; USER=$1;;
        -n) shift; HOST="$1";;
        -h) usage; exit 0;;
        -) break;;
    esac
    shift;
done

# generate key files
randkey 1 0.1 u"$USER" > $KEYFILE
OKEY=`cat $KEYFILE | awk '{print $1}'`
echo "o_key is \"$OKEY"

# before the ACID transaction, let's run a ACID query to record the
# initial state of lineitem

echo "Running ACID query BEFORE the start of Isolation Test 1"
>> $TXN2FILE
echo "date` >> $TXN2FILE
echo "" >> $TXN2FILE
sqlplus "$USER" @$ACID_DIR/isolation/a_query $OKEY >>
$TXN2FILE
echo "" >> $TXN2FILE
echo "-----" >> $TXN2FILE

sleep 1

# start ACID transaction, Sleep for 30 second before ROLLBACK
$PROG 1 1 0 0 i$KEYFILE u$USER s30 >> $TXN1FILE &

# let's sleep 10 seconds before starting ACID query
sleep 10

# start ACID query with the same OKEY

```

```

echo "Running ACID query 10 seconds AFTER the start of ACID
transaction" \
>> $TXN2FILE
echo "date" >> $TXN2FILE
if [ "$HOST" != "" ]
then
echo "Starting ACID query on node $HOST" >> $TXN2FILE
${RSH} -n ${HOST} sqlplus "$USER"
@$ACID_DIR/isolation/a_query $OKEY >> $TXN2FILE
else
sqlplus $USER @$ACID_DIR/isolation/a_query $OKEY >>
$TXN2FILE
fi

echo "-----" >> $TXN2FILE
wait
echo "-----" >> $TXN1FILE

cat $TXN1FILE $TXN2FILE >> $ISOFILE

/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE

```

C.16 iso3.sh

```

#!/bin/ksh
#
# $Header: iso 3.sh 04-aug-99.09:20:35 mpoess Exp $
#
# iso3.sh
#
# Copyright (c) Oracle Corporation 1999. All Rights Reserved.
#
# NAME
#   iso3.sh - <one-line expansion of the name>
#
# DESCRIPTION
#   Usage: iso3.sh [-u user/password] [-n remote_node] -h
#   Options: See usage below
#
# NOTES
#   For a cross node isolation test, assume the local node is
#   one of the participating nodes. The other node can be
#   specified by the -n option.
#
#   We need to make sure the remote node has access to the
#   file system on the local node. Otherwise, we need to rcp
#   the keyfile to the remote system.
#
#   You need to set the environment variable TPCD_KIT_DIR
#
# MODIFIED (MM/DD/YY)
# mpoess 08/04/99 - Creation
# mpoess 08/04/99 - Creation
#
. $KIT_DIR/env

# May need to change the following:
RSH=rsh

OH=$ORACLE_HOME
#ACID_DIR=$TPCD_KIT_DIR/audit is set in env
OUT_DIR=$ACID_OUT

DURA_DIR=$ACID_DIR/dura

TXN1FILE=$OUT_DIR/txn1$$$.out
TXN2FILE=$OUT_DIR/txn2$$$.out
KEYFILE=$OUT_DIR/key$$$.out
ISOFILE=$OUT_DIR/iso3

```

```

USER=$DATABASE_USER
PROG=atranspl

/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE

trap "/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE; exit 1" 1 2 3
15

usage() {

echo ""
echo "Usage: $0 [-u user/passwd] [-n remote_node] -h"
echo ""
exit 1;
}

set --`getopt "u:n:h" "$@"` || usage

while :
do
  case "$1" in
    -u) shift; USER=$1;;
    -n) shift; HOST="$1";;
    -h) usage; exit 0;;
    -) break;;
  esac
  shift
done

# generate key files

randkey 1 0.1 u"$USER" > $KEYFILE
rcp $KEYFILE ${HOST}:$KEYFILE

sleep 1

# start ACID transaction, Sleep for 30 second before COMMIT

$PROG 1 2 1 0 i$KEYFILE u$USER s30 b0 >> $TXN1FILE &

# let's sleep 10 seconds before starting second ACID transaction

sleep 10

# start another ACID transaction with the same LKEY and OKEY
# but different DELTA

# Do not sleep before COMMIT so that we can see TXN2 has
waited.

if [ "$HOST" != "" ]
then
echo "Starting TXN2 on node $HOST" >> $TXN2FILE
${RSH} -n ${HOST} $PROG 2 2 1 1 i$KEYFILE u$USER s1 b1
>> $TXN2FILE &
else
$PROG 2 2 1 1 i$KEYFILE u$USER s1 b1 >> $TXN2FILE &
fi

wait
echo "-----" >> $TXN2FILE
echo "-----" >> $TXN1FILE

cat $TXN1FILE $TXN2FILE >> $ISOFILe

/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE

```

C.17 iso4.sh

```

#!/bin/ksh
#
# $Header: iso4.sh 04-aug-99.09:21:12 mpoess Exp $
#
# iso4.sh
#
# Copyright (c) Oracle Corporation 1999. All Rights Reserved.
#
# NAME
#   iso4.sh - <one-line expansion of the name>
#
# DESCRIPTION
#   Usage: iso4.sh [-u user/password] [-n remote_node] -h
#   Options: See usage below
#
# NOTES
#   For a cross node isolation test, assume the local node is
#   one of the participating nodes. The other node can be
#   specified by the -n option.
#   We need to make sure the remote node has access to the
#   file system on the local node. Otherwise, we need to rcp
#   the keyfile to the remote system.
#   You need to set the environment variable TPCD_KIT_DIR
#
# MODIFIED (MM/DD/YY)
#   mpoess 08/04/99 - Creation
#   mpoess 08/04/99 - Creation
#
. $KIT_DIR/env

# May need to change the following:
RSR=rsh

OH=$ORACLE_HOME
# ACID_DIR=$TPCD_KIT_DIR/audit is set in env
OUT_DIR=$ACID_OUT

DURA_DIR=$ACID_DIR/dura

TXN1FILE=$OUT_DIR/txn1$$$.out
TXN2FILE=$OUT_DIR/txn2$$$.out
KEYFILE=$OUT_DIR/key$$$.out
ISOFILe=$OUT_DIR/iso4

USER=$DATABASE_USER
PROG=atranspl

/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE

trap "/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE; exit 1" 1 2 3
15

usage() {

echo ""
echo "Usage: $0 [-u user/passwd] [-n remote_node] -h"
echo ""
exit 1;
}

set --`getopt "u:n:h" "$@"` || usage

while :
do
  case "$1" in
    -u) shift; USER=$1;;
    -n) shift; HOST="$1";;
    -h) usage; exit 0;;
  esac
  shift
done

```

```

--) break;;
esac
shift
done

# generate key files

randkey 1 0.1 u"$USER" > $KEYFILE
rcp $KEYFILE ${HOST}:$KEYFILE

sleep 1

# start ACID transaction, Sleep for 30 second before ROLLBACK

$PROG 1 2 0 0 i$KEYFILE u$USER s30 b0 >> $TXN1FILE &

# let's sleep 10 seconds before starting second ACID transaction

sleep 10

# start another ACID transaction with the same LKEY and OKEY
# but different DELTA

# Do not sleep before COMMIT so that we can see TXN2 has
waited.

if [ "$HOST" != "" ]
then
echo "Starting TXN2 on node $HOST" >> $TXN2FILE
${RSH} -n ${HOST} $PROG 2 2 1 1 i$KEYFILE u$USER s1 b1
>> $TXN2FILE &
else
$PROG 2 2 1 1 i$KEYFILE u$USER s1 b1 >> $TXN2FILE &
fi

wait
echo "-----" >> $TXN2FILE
echo "-----" >> $TXN1FILE

cat $TXN1FILE $TXN2FILE >> $ISOFILE

/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE

```

C.18 iso5.sh

```

#!/bin/ksh
#
# $Header: iso5.sh 04-aug-99.09:21:45 mpoess Exp $
#
# iso5.sh
#
# Copyright (c) Oracle Corporation 1999. All Rights Reserved.
#
# NAME
#   iso5.sh - <one-line expansion of the name>
#
# DESCRIPTION
#   Usage: iso5.sh [-u user/password] [-n remote_node] -h
#   Options: See usage below
# NOTES
#   For a cross node isolation test, assume the local node is
#   one of the participating nodes. The other node can be
#   specified by the -n option.
#   You need to set the environment variable TPCD_KIT_DIR
#
# MODIFIED (MM/DD/YY)
#   mpoess 08/04/99 - Creation

```

```

#   mpoess 08/04/99 - Creation
#
. $KIT_DIR/env

# May need to change the following:
RSH=rsh

OH=$ORACLE_HOME
# ACID_DIR=$TPCD_KIT_DIR/audit is set in env
OUT_DIR=$ACID_OUT
DURA_DIR=$ACID_DIR/dura

TXN1FILE=$OUT_DIR/txn1$.out
TXN2FILE=$OUT_DIR/txn2$.out
KEYFILE=$OUT_DIR/key$.out
ISOFILE=$OUT_DIR/iso5

USER=$DATABASE_USER
PROG=atranspl

/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE

trap "/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE; exit 1" 1 2 3
15

usage() {
echo ""
echo "Usage: $0 [-u user/passwd] [-n remote_node] -h"
echo ""
exit 1;
}

set -- ` getopt "u:n:h" "$@"` || usage

while :
do
case "$1" in
-u) shift; USER=$1;;
-n) shift; HOST="$1";;
-h) usage; exit 0;;
-) break;;
esac
shift;
done

```

```

# generate key files

randkey 1 0.1 u"$USER" > $KEYFILE
rcp $KEYFILE ${HOST}:$KEYFILE

OKEY=`cat $KEYFILE | awk '{print $1}'`
echo "o_key is \"$OKEY"

# before the ACID transaction, let's run a ACID query to record the
# initial state of lineitem

echo "Running ACID query BEFORE the start of Isolation Test 5"
>> $TXN1FILE
echo "">> $TXN1FILE
echo "">> $TXN1FILE
sqlplus ${USER}@$ACID_DIR/isolation/a_query $OKEY >>
$TXN1FILE
echo "">> $TXN1FILE
echo "-----" >> $TXN1FILE

sleep 1

```

```

# start ACID transaction, Sleep for 60 second before COMMIT
$PROG 1 1 1 0 i$KEYFILE u$USER s60 >> $TXN1FILE &
# let's sleep 5 seconds before starting PARTSUPP query
sleep 5
# First generate PS_PARTKEY and PS_SUPPKEY
PSKEY=`randpsup 1` 
echo "Running PARTSUPP query 5 seconds AFTER the start of
ACID Transaction" \
>> $TXN2FILE
echo "date" >> $TXN2FILE
echo "PS_PARTKEY and PS_SUPPKEY are: $PSKEY" >>
$TXN2FILE
if [ "$HOST" != "" ]
then
echo "Starting PARTSUPP query on node $HOST" >> $TXN2FILE
${RSH} -n ${HOST} sqlplus $USER
@${ACID_DIR}/isolation/a_query2 ${PSKEY} >> $TXN2FILE &
else
sqlplus $USER @${ACID_DIR}/isolation/a_query2 ${PSKEY} >>
$TXN2FILE &
fi
wait
echo "-----" >> $TXN2FILE
echo "-----" >> $TXN1FILE
cat $TXN1FILE $TXN2FILE >> $ISOFIE
/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE

```

C.19 iso6.sh

```

#!/bin/ksh
#
# $Header: iso6.sh 04-aug-99.09:22:12 mpoess Exp $
#
# iso6.sh
#
# Copyright (c) Oracle Corporation 1999. All Rights Reserved.
#
# NAME
#   iso6.sh - <one-line expansion of the name>
#
# DESCRIPTION
#   Usage: iso6.sh [-u user/password] [-n remote_node] -h
#   Options: See usage below
#
# NOTES
#   For a cross node isolation test, assume the local node is
#   one of the participating nodes. The other node can be
#   specified by the -n option.
#   We need to make sure the remote node has access to the
#   file system on the local node. Otherwise, we need to rcp
#   the keyfile to the remote system.
#   You need to set the environment variable TPCD_KIT_DIR
#
# MODIFIED (MM/DD/YY)
#   mpoess 08/04/99 - Creation
#   mpoess 08/04/99 - Creation
#

```

```

. $KIT_DIR/env
# May need to change the following:
RSH=rsh
#OH=/private/tpcd
# ACID_DIR=$TPCD_KIT_DIR/audit is set in env
OUT_DIR=$ACID_OUT
DURA_DIR=$ACID_DIR/dura
TXN1FILE=$OUT_DIR/txn1$$*.out
TXN2FILE=$OUT_DIR/txn2$$*.out
TXN3FILE=$OUT_DIR/txn3$$*.out
KEYFILE=$OUT_DIR/key$$*.out
ISOFIE=$OUT_DIR/iso6
USER=$DATABASE_USER
PROG=atranspl
/bin/rm -rf $TXN1FILE $TXN2FILE $TXN3FILE $KEYFILE
trap "/bin/rm -rf $TXN1FILE $TXN2FILE $TXN3FILE
$KEYFILE; exit 1" 1 2 3 15
usage() {
echo ""
echo "Usage: $0 [-u user/password] [-n remote_node] -h"
echo ""
exit 1;
}
set -- `getopt "u:n:h" "$@"` || usage
while :
do
case "$1" in
-u) shift; USER=$1;;
-n) shift; HOST="$1";;
-h) usage; exit 0;;
--) break;;
esac
shift;
done

# generate key files
randkey 1 0.1 u"$USER" > $KEYFILE
#rcp $KEYFILE ${HOST}:$KEYFILE
OKEY=`cat $KEYFILE | awk '{print $1}'`
echo "o_key is \"$OKEY\""

# before the any transaction, let's run a ACID query to record the
# initial state of lineitem
echo "Running ACID query BEFORE the start of Isolation Test 6"
>> $TXN2FILE
echo "date" >> $TXN2FILE
echo "" >> $TXN2FILE
sqlplus $USER @${ACID_DIR}/isolation/a_query $OKEY >>
$TXN2FILE
echo "-----" >> $TXN2FILE
sleep 1
# start Query 1, use 0 as the delta

```

```

echo "Running Query 21 at `date`" >> $TXN1FILE
sqlplus $USER @$KIT_DIR/acid/isolation/q21 >> $TXN1FILE &

# sleep 2 seconds before starting ACID transaction

sleep 2

# start ACID transaction, COMMIT after one second

echo "Starting ACID transaction at `date`" >> $TXN2FILE

if [ "$HOST" != "" ]
then
echo "Starting ACID transaction on node $HOST" >> $TXN2FILE
${RSH} -n $HOST $PROG 1 1 1 0 i$KEYFILE u$USER s1 >>
$TXN2FILE &
else
$PROG 1 1 1 0 i$KEYFILE u$USER s1 >> $TXN2FILE &
fi

# start Query 1

sleep 2

echo "Running 2nd Query 21 at `date`" >> $TXN3FILE
sqlplus $USER @$KIT_DIR/acid/isolation/q21 >> $TXN3FILE &
# wait for everyone to finish

wait

echo "-----" >> $TXN3FILE
echo "-----" >> $TXN2FILE
echo "-----" >> $TXN1FILE

cat $TXN1FILE $TXN2FILE $TXN3FILE >> $ISOFILE

/bin/rm -rf $TXN1FILE $TXN2FILE $TXN3FILE $KEYFILE

```

C.20 randkey.c

/* Copyright (c) 2001, 2002, Oracle Corporation. All rights reserved. */

/*

NAME
randkey.c - <one-line expansion of the name>

DESCRIPTION

Generate random keys for ACID transactions:
O_ORDERKEY unique random (1..SF*150000*4) and only
first 8 keys out of every 32 are populated.
and
L_ORDERKEY based on Clause 3.1.6.2
DELTA random (1..100)

*/

```
#include <stdio.h>
#include <stdlib.h>
#include <math.h>
#include "atranspl.h"

#define ORDERCNT 150000.0

/* MK_SPARSE adopted from dss.h */

#define MK_SPARSE(key, seq) \

```

(((((key>>3)<<2)|(seq & 0x0003)<<3)|(key & 0x0007))

```

void sql_error();
void usage();
void ACIDinit();
long atol();
void srand48();
long lrand48();

/* Not really used here, but retained it for future purposes. */

typedef struct aciddef {
    long okey;
    long lkey;
    int delta;
} adef;

long l_key = 0;
long o_key = 0;
char lname[UNAME_LEN];
char *passwd;

/* OCI handles */

OCIEnv *tpcenv;
OCIServer *tpcsrv;
OCIError *errhp;
OCISvcCtx *tpcsvc;
OCISession *tpcusr;
OCISStmt *curi;

OCIBind *l_key_bp;
OCIBind *o_key_bp;

sword status = OCI_SUCCESS; /* OCI return value */

char sqlstmt[1024];

```

```

void ACIDexit() {
    OCILogoff(tpcsvc,errhp);
    OCIfree(tpcenv,OCI_HTYPE_STMT);
    OCIfree(tpcsvc,OCI_HTYPE_SVCCTX);
    OCIfree(tpcsrv,OCI_HTYPE_SERVER);
    OCIfree(tpcusr,OCI_HTYPE_SESSION);
}

```

/* type: 0 if environment handle is passed, 1 if error handle is
passwd */

```

void sql_error(errhp,status,type)
    OCIError *errhp;
    sword status;
    sword type;
{
    char msg[2048];
    sb4 errcode;
    ub4 msglen;
    int i,j;

    switch(status) {
        case OCI_SUCCESS_WITH_INFO:
            fprintf(stderr, "Error: Statement returned with info.\n");
            if (type)
                (void) OCIErrorGet(errhp,1,NULL,(sb4 *) &errcode,(text
*)msg,
                                2048,OCI_HTYPE_ERROR);
            else

```

```

(void) OCIErrorGet(errhp,1,NULL,(sb4 *) &errcode,(text
*)msg,
2048,OCI_HTYPE_ENV);
fprintf(stderr,"%s\n",msg);
break;
case OCI_ERROR:
fprintf(stderr, "Error: OCI call error.\n");
if(type)
(void) OCIErrorGet(errhp,1,NULL,(sb4 *) &errcode,(text
*)msg,
2048,OCI_HTYPE_ERROR);
else
(void) OCIErrorGet(errhp,1,NULL,(sb4 *) &errcode,(text
*)msg,
2048,OCI_HTYPE_ENV);
fprintf(stderr,"%s\n",msg);
break;
case OCI_INVALID_HANDLE:
fprintf(stderr, "Error: Invalid Handle.\n");
if(type)
(void) OCIErrorGet(errhp,1,NULL,(sb4 *) &errcode,(text
*)msg,
2048,OCI_HTYPE_ERROR);
else
(void) OCIErrorGet(errhp,1,NULL,(sb4 *) &errcode,(text
*)msg,
2048,OCI_HTYPE_ENV);
fprintf(stderr,"%s\n",msg);
break;
}
/* Rollback just in case */
(void) OCITransRollback(tpcscv,errhp,OCI_DEFAULT);

printf(stderr, "Exiting Oracle...\n");
fflush(stderr);

ACIDexit();
exit(1);
}

main(argc, argv)
int argc;
char **argv;
{
long count;
long i;
double sf; /* need to accomodate sf 0.1 */
double random;
double ordcnt;
adef *res;

if ((argc < 3) || (argc > 4)) {
usage();
exit(-1);
}

strcpy((char *) lname, "tpcd/tpcd");

count = atol(argv[1]);
sf = atof(argv[2]);

argc -= 2;
argv += 2;

while (-argc) {
++argv;
switch(argv[0][0]) {
case 'u':
strncpy((char *) lname, ++(argv[0]), UNAME_LEN);
if (strchr((char *) lname, '/') == NULL) {
usage();
exit(-1);
}
break;
default:
fprintf(stderr, "Unknown argument %s\n", argv[0]);
usage();
break;
}
}

ACIDinit();

/* initialize array for random numbers */

res = (adef *) malloc(count*sizeof(adef));
ordcnt = (double) ORDERCNT * (double) sf;

for (i=0; i<count; i++) {

/* The algorithm:
/* Assumes drand's output is 'unique', first get a number within */
/* the range of [0..sf*ORDERCNT) and then maps the different */
/* ranges to generate the real output. */

random = floor(drand48() * (double) ordcnt) + 1;
res[i].okey = o_key = (long) MK_SPARSE((long) random, 0);
res[i].delta = (long) floor(drand48() * 100) + 1;

/* Obtain l_key from l_key query */

OCIexec(tpcscv,curi,errhp,1);

/* l_key is the highest l_linenumber available. We need to pick */
/* at random a number between 1..l_key. */

res[i].lkey = (lrand48() % l_key) + 1;

printf("%ld %ld %d\n", res[i].okey, res[i].lkey, res[i].delta);
}

ACIDexit();
free(res);
}

void usage() {

printf(stderr, "Usage: randkey <number of random keys to
generate> <SF> u<user/password>\n");
fprintf(stderr, "\n");
}

void ACIDinit()
{
/* run random seed */

srand48(getpid());

/* Connect to ORACLE. Program will call sql_error()
if an error occurs in connecting to the default database. */

(void) OCIIInitialize(OCI_DEFAULT,(dvoid *)0,0,0,0);
}

```

```

if((status=OCIEnvInit((OCIEnv
**)&tpcenv,OCI_DEFAULT,0,(dvoid **)0)) !=  

    OCI_SUCCESS)  

    sql_error(tpcenv, status, 0);  

OChalloc(tpcenv,&errhp,OCI_HTYPE_ERROR);  

OChalloc(tpcenv,&curi,OCI_HTYPE_STMT);  

OChalloc(tpcenv,&tpcsvc,OCI_HTYPE_SVCCTX);  

OChalloc(tpcenv,&tpcsrv,OCI_HTYPE_SERVER);  

OChalloc(tpcenv,&tpcusr,OCI_HTYPE_SESSION);  

/* get username and password */  

passwd = strchr(lname, '/');  

*passwd = '\0';  

passwd++;  

if ((status=OCIServerAttach(tpcsrv,errhp,(text
*)0,OCI_DEFAULT))!=OCI_SUCCESS)
    sql_error(errhp,status,1);  

OCIaset(tpcsvc,OCI_HTYPE_SVCCTX,tpcsrv,0,OCI_ATTR_SER
VER,errhp);  

OCIaset(tpcusr,OCI_HTYPE_SESSION,lname,strlen(lname),OCI_
ATTR_USERNAME,
        errhp);  

OCIaset(tpcusr,OCI_HTYPE_SESSION,passwd,strlen(passwd),OCI
_ATTR_PASSWORD,
        errhp);  

if ((status = OCISessionBegin(tpcsvc, errhp, tpcusr,
    OCI_CRED_RDBMS,
        OCI_DEFAULT)) != OCI_SUCCESS)
    sql_error(errhp,status,1);  

OCIaset(tpcsvc,OCI_HTYPE_SVCCTX,tpcusr,0,OCI_ATTR_SESS
ION,errhp);  

/* Open and Parse cursor for query to choose determine l_key. */
/* Binds l_key to :l_key. */  

sprintf((char *) sqlstmt,SQLTXT1);
OCIStmtPrepare(curi,errhp,(text *)sqlstmt,strlen((char *)sqlstmt),
    OCI_NTV_SYNTAX,OCI_DEFAULT);  

OCIbbname(curi,l_key_bp,errhp,:l_key",ADR(l_key),SIZ(l_key),S
QLT_INT);  

OCIbbname(curi,o_key_bp,errhp,:o_key",ADR(o_key),SIZ(o_key),
SQLT_INT);
}

C.21 randpsup.c  

/* Copyright (c) 2001, 2002, Oracle Corporation. All rights
reserved. */  

/*  

NAME  

randpsup.c - <one-line expansion of the name>  

DESCRIPTION

```

Generate random keys for ACID PARTSUPP transactions:
(Clause 4.2.3)
PS_PARTKEY random within [SF*200000]
and
PS_SUPPKEY = (PS_PARTKEY + (i * ((S/4) +
(int)(PS_PARTKEY - 1)
/S))) % S + 1
where i random within [0..3] and S = SF * 10000

MODIFIED
mpoess 10/23/02 - mpoess_update_from_visa
mpoess 01/04/01 - Creation

*/

```

#include <stdio.h>
#include <stdlib.h>
#include <math.h>

#define PS_PER_SF 200000.0
#define S_PER_SF 10000.0
#define SUPP_PER_PART 4

/* borrowed from build.c in the dbgen distribution */

#define PART_SUPP_BRIDGE(tgt, p, s) \
{ \
    long tot_scnt = (long) (S_PER_SF * sf); \
    tgt = (p + s * (tot_scnt / SUPP_PER_PART + \
        (long) ((p - 1) / tot_scnt))) % tot_scnt + 1; \
}

void usage();
double atof();
void srand48();
long lrand48();

main(argc, argv)
    int argc;
    char **argv;
{
    double sf = 0.1;           /* scale factor */
    long supp;                /* the i-th supplier */
    long pkey;                /* partkey */
    long maxpkey;             /* highest partkey */
    long ps_skey;              /* ps_suppkey */

    if (argc < 2) {
        usage();
        exit(-1);
    }

    /* seed the random number generator */

    srand48(getpid());

    sf = atof(argv[1]);
    maxpkey = (long) (sf * PS_PER_SF);
    supp = lrand48() % 4;
    pkey = lrand48() % maxpkey + 1;

    PART_SUPP_BRIDGE(ps_skey, pkey, supp);

    fprintf(stdout, "%ld %ld", pkey, ps_skey);

    exit(0);
}

```

```

void usage()
{
    fprintf(stderr, "Usage: randpsup <SF>\n\n");
}

```

C.22 sample.sh

```

#!/bin/ksh
#
# $Header: sample.sh 08-aug-99.17:10:00 mpoess Exp $
#
# sample.sh
#
# Copyright (c) Oracle Corporation 1999. All Rights Reserved.
#
# NAME
#   sample.sh - <one-line expansion of the name>
#
# DESCRIPTION
#   <short description of component this file declares/defines>
#
# NOTES
#   <other useful comments, qualifications, etc.>
#
# MODIFIED (MM/DD/YY)
#   mpoess 08/08/99 - Creation
#   mpoess 08/08/99 - Creation
#
# $1 durability output file

. $KIT_DIR/env

cat $1 | grep o_key | awk '{printf "%d\n", $2}' | head -106 >
/tmp/okey$$
cat $1 | grep l_key | awk '{printf "%d\n", $2}' | head -106 >
/tmp/lkey$$

paste /tmp/okey$$ /tmp/lkey$$ > /tmp/keys$$
tail -6 /tmp/keys$$ > /tmp/6keys$$

echo "Keys chosen are:"
cat /tmp/6keys$$

i=1
while [ $i -le 6 ]
do

j=`cat /tmp/6keys$$ | tail -$i | head -1` 
sqlplus tpch/tpch @sample $j
i=`expr $i + 1`
done

#/bin/rm -f /tmp/*key*

```

C.23 sample.sql

```

Rem
Rem $Header: sample.sql 08-aug-99.17:10:34 mpoess Exp $

```

```

Rem
Rem sample.sql
Rem
Rem Copyright (c) Oracle Corporation 1999. All Rights Reserved.
Rem
Rem NAME
Rem   sample.sql - <one-line expansion of the name>
Rem
Rem DESCRIPTION
Rem   <short description of component this file declares/defines>
Rem
Rem NOTES
Rem   <other useful comments, qualifications, etc.>
Rem
Rem MODIFIED (MM/DD/YY)
Rem   mpoess 08/08/99 - Creation
Rem   mpoess 08/08/99 - Created
Rem

alter session set nls_date_format = 'YYYY-MM-DD HH:MI:SS';
select * from history where h_o_key = &&1 and h_l_key = &&2;

exit;

```

C.24 atrans.sql

```

Rem
Rem $Header: atrans.sql 07-aug-99.21:27:13 mpoess Exp $
Rem
Rem atrans.sql
Rem
Rem Copyright (c) Oracle Corporation 1999. All Rights Reserved.
Rem
Rem NAME
Rem   atrans.sql - <one-line expansion of the name>
Rem
Rem DESCRIPTION
Rem   Creates ACID Transaction Package for TPC-D benchmark.
Rem   Asks user to input values for o_key, delta and output file.
Rem
Rem NOTES
Rem   <other useful comments, qualifications, etc.>
Rem
Rem MODIFIED (MM/DD/YY)
Rem   mpoess 08/07/99 - Creation
Rem   mpoess 08/07/99 - Created
Rem

set serverout on;
set termout on;
set echo on;

CREATE OR REPLACE PACKAGE d_atrans
IS
PROCEDURE doatrans
(
    l_key          IN OUT integer,
    o_key          IN OUT integer,
    delta          IN OUT integer,
    l_pkey         IN OUT integer,
    l_skey         IN OUT integer,
    l_quan        IN OUT integer,
    l_newquan     IN OUT integer,
    l_tax          IN OUT number,
    l_disc         IN OUT number,
    l_eprice       IN OUT number,

```

```

    l_neweprice IN OUT number,
    o_tprice   IN OUT number,
    o_newtprice      IN OUT number,
    rprice        IN OUT number,
    cost          IN OUT number
);
END;
/

CREATE OR REPLACE PACKAGE BODY d_atrans
IS
PROCEDURE doatrans
(
    l_key           IN OUT integer,
    o_key           IN OUT integer,
    delta          IN OUT integer,
    l_pkey         IN OUT integer,
    l_skey         IN OUT integer,
    l_quan        IN OUT integer,
    l_newquan     IN OUT integer,
    l_tax          IN OUT number,
    l_disc         IN OUT number,
    l_eprice       IN OUT number,
    l_neweprice    IN OUT number,
    o_tprice       IN OUT number,
    o_newtprice    IN OUT number,
    rprice         IN OUT number,
    cost          IN OUT number
)
IS
    ototal number;
    not_serializable EXCEPTION;
    PRAGMA EXCEPTION_INIT(not_serializable,-8177);
BEGIN
LOOP BEGIN
    select o_totalprice
        into o_tprice
        from orders
        where o_orderkey = o_key;

    select l_quantity, l_extendedprice, l_partkey, l_suppkey, l_tax,
    l_discount
        into l_quan, l_eprice, l_pkey, l_skey, l_tax, l_disc
        from lineitem
        where l_orderkey = o_key
        and l_linenumber = l_key;

    ototal := o_tprice - trunc((trunc((l_eprice * (1.0-l_disc)),2) *
(1.0+l_tax)),2);
    rprice := trunc((l_eprice/l_quan), 2);
    cost := trunc((rprice * delta), 2);
    l_neweprice := l_eprice + cost;
    o_newtprice := trunc((l_neweprice * (1.0 - l_disc)), 2);
    o_newtprice := ototal + trunc((o_newtprice * (1.0 + l_tax)), 2);
    l_newquan := l_quan + delta;

    update lineitem
        set l_extendedprice = l_neweprice,
        l_quantity = l_newquan
        where l_orderkey = o_key
        and l_linenumber = l_key;

    update orders
        set o_totalprice = o_newtprice
        where o_orderkey = o_key;

    insert into history (h_p_key, h_s_key, h_o_key, h_l_key, h_delta,
    h_date_t)
        values (l_pkey, l_skey, o_key, l_key, delta, sysdate);

    EXIT;
EXCEPTION
    WHEN not_serializable THEN
        ROLLBACK;
    END;
END LOOP;
END doatrans;
END;
/
exit;

```

C.25

C.26 run_acid.sh

```

#!/bin/ksh
#
# $Header: run_acid.sh 08-aug-99.15:30:10 mpoess Exp $
#
# run_acid.sh
#
# Copyright (c) Oracle Corporation 1999. All Rights Reserved.
#
# NAME
#   run_acid.sh - <one-line expansion of the name>
#
# DESCRIPTION
#   Usage: run_acid.sh [-n iter] [-s stream] [-p prog] [-i infile]
#                      [-o outfile] [-d durafile] [-u usr/pswd]
#                      [-t trigger] [-f scale factor] -h
#
# Options: See usage below
#
# MODIFIED (MM/DD/YY)
# mpoess 08/08/99 - Creation
# mpoess 08/08/99 - Creation
#
. $KIT_DIR/env

OH=$ORACLE_HOME
ACID_DIR=$ACID_DIR
OUT_DIR=$ACID_OUT

usage() {
    echo ""
    echo "Usage: $0 [-n iter] [-s stream] [-p prog] [-i infile] [-o
outfile]"
    echo "          [-d durafile] [-u usr/pswd] -h"
    echo ""
    echo "-n iter : number of iterations, default is 100"
    echo "-s stream : number of streams, default is 2"
    echo "-p prog : program to run, default is atranspl.ott"
    echo "-i infile : input file prefix, suffix by process number within
a"
    echo "          stream and run ID, default is ./acid_in"
    echo "-o outfile : output file prefix, similar to input file"
    echo "          default is ./out/acid_out"
    echo "-d durafile : durability file prefix, used for durability tests"
    echo "          default is ./dura/acid_dura"
    echo "-u usr/pswd : user/password combo for database access,
default is tpch/tpch"
}

```

```

echo "-t trigger : trigger time between process starts, default is 1
second"
echo "-h      : print this usage summary"
exit 1;
}

ITER=600
STEM=${NUM_STREAMS}
let STEM="$STEM + 1" # add one for the update stream
SF=1
PROG=atranspl
IN=${ACID_DIR}/acid_in
DURA_DIR=${ACID_OUT}/dura
OUT=${DURA_DIR}/drate
DURA=${DURA_DIR}/dura
KEY=${DURA_DIR}/key$$_
echo "$$ > ${DURA_DIR}/shellpid
USER=tpch/tpch
TRIG=1
HCNT=duracntb

set --`getopt "n:s:p:i:o:d:u:ht:f:" "$@"` || usage

# get all the options

while :
do
  case "$1" in
    -n) shift; ITER=$1;;
    -s) shift; STEM=$1;;
    -p) shift; PROG=$1;;
    -i) shift; IN=$1;;
    -o) shift; OUT=$1;;
    -d) shift; DURA=$1;;
    -u) shift; USER=$1;;
    -h) usage; exit 0;;
    -t) shift; TRIG=$1;;
    -f) shift; SF=$1;;
    -) break;;
    esac
    shift;
done

#collect system info before durability start
cat /var/adm/syslog/syslog.log > ${DURA_DIR}/syslog_pre_dura
2>&1
ps -ef > ${DURA_DIR}/ps.out.pre_dura 2>&1
cat $ORACLE_HOME/rdbms/log/alert_1g.log >
${DURA_DIR}/alert_1g.log.pre_dura 2>&1

echo "Starting ACID run..."

i=0
T=`expr $STEM \* $TRIG + 6` 

# Get history count before the run

sqlplus $USER @cnt_hist > ${DURA_DIR}/$HCNT 2>&1

while [ $i -lt $STEM ]
do
  randkey $ITER ${SF} u$USER > ${KEY}${i} &
  i=`expr $i + 1` 
done

wait
# perform the consistency

i=0
while [ $i -lt $STEM ]
do
  for j in `head -10 ${KEY}${i} | awk '{printf "%d ",$1}'` 
  do
    sqlplus tpch/tpch @consist $j >> ${DURA_DIR}/duraconsb
  done
  i=`expr $i + 1` 
done

echo "Starting Transaction Counting Program"
count_tx.sh $STEM 100 ${DURA_DIR} &

i=0
while [ $i -lt $STEM ]
do
  $PROG $i $STEM 1 0 ${KEY}${i} o${OUT}${i}
  d${DURA}${i} u$USER s1 &
  T=`expr $T - $TRIG` 
  i=`expr $i + 1` 
done

done
wait
echo "ACID run completed"

```

C.27 prepare4acid.sh

```

#!/bin/ksh
#
#$Header: prepare4acid.sh 12-aug-99.17:09:18 mpoess Exp $
#
#prepare4acid.sh
#
# Copyright (c) Oracle Corporation 1999. All Rights Reserved.
#
# NAME
#   prepare4acid.sh
#
# DESCRIPTION
#   Prepares the qualification database for the acid tests.
#
# NOTES
#
# MODIFIED (MM/DD/YY)
#   mpoess 08/12/99 - Creation
#   mpoess 08/12/99 - Creation
#
. $KIT_DIR/env

sqlplus $DATABASE_USER @d_hist
sqlplus $DATABASE_USER @atrans

```

C.28 q21.sql

```

set serverout on;

select
'BEFORE ACID QUERY' as STAGE,
substr(TO_CHAR(sysdate,'YYYY-MM-DD HH:MI:SS'),1,20) as
CURRENT_TIME
from dual;

select * from (

```

```

select
  s_name,
  count(*) numwait
from
  supplier,
  lineitem l1,
  orders,
  nation
where
  s_suppkey = l1.l_suppkey
  and o_orderkey = l1.l_orderkey
  and o_orderstatus = 'F'
  and l1.l_receiptdate > l1.l_commitdate
  and exists (
    select
      *
    from
      lineitem l2
    where
      l2.l_orderkey = l1.l_orderkey
      and l2.l_suppkey <> l1.l_suppkey
)
and not exists (
  select
    *
  from
    lineitem l3
)
  where
    l3.l_orderkey = l1.l_orderkey
    and l3.l_suppkey <> l1.l_suppkey
    and l3.l_receiptdate > l3.l_commitdate
    and s_name = 'SAUDI ARABIA'
  )
group by
  s_name
order by
  numwait desc,
  s_name
where rownum <= 10;

select
  'AFTER ACID QUERY' as STAGE,
  substr(TO_CHAR(sysdate, 'YYYY-MM-DD HH:MI:SS'), 1, 20) as
  CURRENT_TIME
from dual;
exit;

```

Appendix D Query text and Output

D.1 qryqual

-- TPC-H/TPC-R Pricing Summary Report Query (Q1)
-- Functional Query Definition
-- Approved February 1998

```
select
l_returnflag,
l_linenstatus,
sum(l_quantity) as sum_qty,
sum(l_extendedprice) as sum_base_price,
sum(l_extendedprice * (1 - l_discount)) as sum_disc_price,
sum(l_extendedprice * (1 - l_discount) * (1 + l_tax)) as sum_charge,
avg(l_quantity) as avg_qty,
avg(l_extendedprice) as avg_price,
avg(l_discount) as avg_disc,
count(*) as count_order
from
lineitem
where
l_shipdate <= to_date ('1998-12-01','YYYY-MM-DD') - 90
group by
l_returnflag,
l_linenstatus
order by
l_returnflag,
l_linenstatus
```

L_RETURNFLAG	L_LINESTATUS	SUM_QTY	
SUM_BASE_PRICE	SUM_DISC_PRICE	SUM_CHARGE	AVG_QTY
AVG_PRICE	AVG_DISC	COUNT_ORDER	
A F	37734107.00	56586554400.73	
53758257134.87	55909065222.83	25.52	
38273.13	0.05	1478493.00	
N F	991417.00	1487504710.38	
1413082168.05	1469649223.19	25.52	
38284.47	0.05	38854.00	
N O	74476040.00	111701729697.74	
106118230307.61	110367043872.50	25.50	
38249.12	0.05	2920374.00	
R F	37719753.00	56568041380.90	
53741292684.60	55889619119.83	25.51	
38250.85	0.05	1478870.00	

4 rows processed.

Query Processed in 1.26 seconds.

-- @(#).sql 2.1.6.2
-- TPC-H/TPC-R Minimum Cost Supplier Query (Q2)
-- Functional Query Definition
-- Approved February 1998

```
select * from (
select
s_acctbal,
s_name,
n_name,
p_partkey,
p_mfgr,
```

```
s_address,
s_phone,
s_comment
from
part,
supplier,
partsupp,
nation,
region
where
p_partkey = ps_partkey
and s_suppkey = ps_suppkey
and p_size = 15
and p_type like '%BRASS'
and s_nationkey = n_nationkey
and n_regionkey = r_regionkey
and r_name = 'EUROPE'
and ps_supplycost =
select
min(ps_supplycost)
from
partsupp,
supplier,
nation,
region
where
p_partkey = ps_partkey
and s_suppkey = ps_suppkey
and s_nationkey = n_nationkey
and n_regionkey = r_regionkey
and r_name = 'EUROPE'
)
select
min(ps_supplycost)
from
partsupp,
supplier,
nation,
region
where
p_partkey = ps_partkey
and s_suppkey = ps_suppkey
and s_nationkey = n_nationkey
and n_regionkey = r_regionkey
and r_name = 'EUROPE'
)
order by
s_acctbal desc,
n_name,
s_name,
p_partkey
)
where rownum <= 100
```

S_ACCTBAL	S_NAME	N_NAME
P_PARTKEY	P_MFGR	
S_ADDRESS		S_PHONE
S_COMMENT		
9938.53	Supplier#000005359	UNITED KINGDOM
185358.00	Manufacturer#4	
QKuHYh,vZGiwu2FWEJoLdx04		33-429-790-6131
blithely silent pinto beans are furiously. slyly final deposits across		
9937.84	Supplier#000005969	ROMANIA
108438.00	Manufacturer#1	
ANDENSOSSmk,miq23Xfb5RWt6dvUcv6Qa		29-520-692-3537
carefully slow deposits use furiously. slyly ironic platelets above the		
ironic		
9936.22	Supplier#000005250	UNITED KINGDOM
249.00	Manufacturer#4	
B3rqp0xbSEim4Mpy2RH J		33-320-228-2957
blithely special packages are. stealthily express deposits across the		
closely final instructi		
9923.77	Supplier#000002324	GERMANY
29821.00	Manufacturer#4	
y3OD9UywSTOK		17-779-299-1839
quickly express packages breach quiet pinto beans. requ		
9871.22	Supplier#000006373	GERMANY
43868.00	Manufacturer#5	
J8fcXWsTqM		17-813-485-8637
never silent deposits integrate furiously blit		
9870.78	Supplier#000001286	GERMANY
81285.00	Manufacturer#2	
YKA,E2fjiVd7eUrzp2Ef8j1QxGo2DFnosaTEH		17-516-924-4574
final theodolites cajole slyly special,		

9870.78	Supplier#000001286	GERMANY	9612.94	Supplier#000003228	ROMANIA
181285.00	Manufacturer#4		198189.00	Manufacturer#4	
YKA,E2fjiVd7eUrzp2Ef8j1QxGo2DFnosaTEH	17-516-924-4574		KDdpNKN3cWu7ZSrbdq7AfSLxx,qWB	29-325-784-8187	
final theodolites cajole slyly special,			carefully pending accounts serve. furiously close deposits boost		
9852.52	Supplier#000008973	RUSSIA	slyly. q		
18972.00	Manufacturer#2		9571.83	Supplier#000004305	ROMANIA
t5L67YdBYYH6o,Vz24jpDyQ9	32-188-594-7038		179270.00	Manufacturer#2	
quickly regular instructions wake-- carefully unusual braids into the			qNHZ7WmCzygwMPRDO9Ps	29-973-481-1831	
expres			furiously final deposits		
9847.83	Supplier#000008097	RUSSIA	9558.10	Supplier#000003532	UNITED KINGDOM
130557.00	Manufacturer#2		88515.00	Manufacturer#4	
xMe97bpE69NzdwLoX	32-375-640-3593	 delete lines		
slyly regular dependencies sleep slyly furiously express dep			33094.00	Manufacturer#5	
9847.57	Supplier#000006345	FRANCE	kkYvL6IuvjlgTNG IKkaXQDYgx8ILohj	17-627-663-8014	
86344.00	Manufacturer#1		quickly regular requests are furiously. pending deposits wake		
VSt3rzk3qG698u6ld8HhOBbyvrTcSTsVQIDQDag	16-886-766-7945		7937.93	Supplier#000009012	ROMANIA
silent pinto beans should have to snooze carefully along the final			83995.00	Manufacturer#2	
reques			iUiTzih,Ek3i4lwSgunXMgrcTzwdb	29-250-925-9690	
9847.57	Supplier#000006345	FRANCE	blithely bold ideas haggle quickly final, regular request		
173827.00	Manufacturer#2		7914.45	Supplier#000001013	RUSSIA
VSt3rzk3qG698u6ld8HhOBbyvrTcSTsVQIDQDag	16-886-766-7945		125988.00	Manufacturer#2	
silent pinto beans should have to snooze carefully along the final			riRcntps4KEdtYScjpMIWeYF6mNnR	32-194-698-3365	
reques			final, ironic theodolites alongside of the ironic		
9836.93	Supplier#000007342	RUSSIA	7912.91	Supplier#000004211	GERMANY
4841.00	Manufacturer#4		159180.00	Manufacturer#5	
JOIK7C1,7xrEZSSOw	32-399-414-5385		2wQRVovHrm3,v03IKzfTd,1PYsFXQFFOG	17-266-947-7315	
final accounts haggle. bold accounts are furiously dugouts. furiously			final requests integrate slyly above the silent, even		
silent asymptotes are slyly			7912.91	Supplier#000004211	GERMANY
9817.10	Supplier#000002352	RUSSIA	184210.00	Manufacturer#4	
124815.00	Manufacturer#2		2wQRVovHrm3,v03IKzfTd,1PYsFXQFFOG	17-266-947-7315	
4Lf0HUZjgjEbAKw TgdKcgOc4D4uCYw	32-551-831-1437		final requests integrate slyly above the silent, even		
blithely pending packages across the ironic accounts grow slyly after			7894.56	Supplier#000007981	GERMANY
the furiously			85472.00	Manufacturer#4	
9817.10	Supplier#000002352	RUSSIA	NSJ96vMROAbExp	17-963-404-3760	
152351.00	Manufacturer#3		regular, even theodolites integrate carefully. bold, special theodolites		
4Lf0HUZjgjEbAKw TgdKcgOc4D4uCYw	32-551-831-1437		are slyly fluffy iron		
blithely pending packages across the ironic accounts grow slyly after			7887.08	Supplier#000009792	GERMANY
the furiously			164759.00	Manufacturer#3	
9739.86	Supplier#000003384	FRANCE	Y28ITVeYriT3kIGdV2K8fSZ V2UqT5H1OtZ	17-988-938-4296	
138357.00	Manufacturer#2		pending, ironic packages sleep among the carefully ironic accounts.		
o,Z3v4POifevE k9U1b 6JlucX,I	16-494-913-5925		quickly final accounts		
slyly ironic theodolites hag			7871.50	Supplier#000007206	RUSSIA
9721.95	Supplier#000008757	UNITED KINGDOM	104695.00	Manufacturer#1	
156241.00	Manufacturer#3		3w fNCnrVmVJjE95sgWZzvW	32-432-452-7731	
Atg6GnM4dT2	33-821-407-2995		furiously dogged pinto beans cajole. bold, express notornis until the		
ironic, even dolphins above the furiously ironic foxes sleep slyly			slyly pending		
around the caref			7852.45	Supplier#000005864	RUSSIA
9681.33	Supplier#000008406	RUSSIA	8363.00	Manufacturer#4	
78405.00	Manufacturer#1		WCNfBPZeSXh3h,c	32-454-883-3821	
,qUuXcfUI	32-139-873-8571		blithely regular deposits		
furiously even deposits affix thinly special theodolites. furiou			7850.66	Supplier#000001518	UNITED KINGDOM
9643.55	Supplier#000005148	ROMANIA	86501.00	Manufacturer#1	
107617.00	Manufacturer#1		ONda3YJiHKJOC	33-730-383-3892	
kT4ciVFslx9z4s79p Js825	29-252-617-4850		furiously final accounts wake carefully idle requests. even dolphins		
doggedly even ideas boost furiously against the furiously express			wake acc		
9624.82	Supplier#000001816	FRANCE	7843.52	Supplier#000006683	FRANCE
34306.00	Manufacturer#3		11680.00	Manufacturer#4	
e7vab91vLJPWxxZnewmnDBpDmxYHrb	16-392-237-6726		2Z0JGkv01Y0ooCFwUGfvIBhzCdy	16-464-517-8943	
blithely regular accounts cajole furiously. regular			carefully bold accounts doub		
9624.78	Supplier#000009658	ROMANIA			
189657.00	Manufacturer#1				
oE9uBgEfSS4opIcepXyAYM,x	29-748-876-2014				
regular deposits haggle. furiously express asympto					
9612.94	Supplier#000003228	ROMANIA			
120715.00	Manufacturer#2				
KDdpNKN3cWu7ZSrbdq7AfSLxx,qWB	29-325-784-8187				
carefully pending accounts serve. furiously close deposits boost					
slyly. q					

100 rows processed.
Query Processed in 3.87 seconds.

-- @(#).sql 2.1.6.2
-- TPC-H/TPC-R Shipping Priority Query (Q3)
-- Functional Query Definition
-- Approved February 1998

```

select * from (
select
l_orderkey,
sum(l_extendedprice * (1 - l_discount)) as revenue,
o_orderdate,
o_shippriority
from
customer,
orders,
lineitem
where
c_mktsegment = 'BUILDING'
and c_custkey = o_custkey
and l_orderkey = o_orderkey
and o_orderdate < to_date('1995-03-15', 'YYYY-MM-DD')
and l_shipdate > to_date('1995-03-15', 'YYYY-MM-DD')
group by
l_orderkey,
o_orderdate,
o_ship priority
order by
revenue desc,
o_orderdate)
where rownum <= 10

```

L_ORDERKEY	REVENUE	O_ORDERDATE
O_SHIPPRIORITY		
2456423.00	406181.01	1995-03-05 0.00
3459808.00	405838.70	1995-03-04 0.00
492164.00	390324.06	1995-02-19 0.00
1188320.00	384537.94	1995-03-09 0.00
2435712.00	378673.06	1995-02-26 0.00
4878020.00	378376.80	1995-03-12 0.00
5521732.00	375153.92	1995-03-13 0.00
2628192.00	373133.31	1995-02-22 0.00
993600.00	371407.46	1995-03-05 0.00
2300070.00	367371.15	1995-03-13 0.00

10 rows processed.
Query Processed in 2.33 seconds.

```

-- @(#)4.sql      2.1.6.2
-- TPC-H/TPC-R Order Priority Checking Query (Q4)
-- Functional Query Definition
-- Approved February 1998

```

```

select
o_orderpriority,
count(*) as order_count
from
orders
where
o_orderdate >= to_date('1993-07-01', 'YYYY-MM-DD')
and o_orderdate < add_months(to_date('1993-07-01', 'YYYY-MM-DD'), 3)
and exists (
select
*
from
lineitem
where
l_orderkey = o_orderkey
and l_commitdate < l_receiptdate
)
group by
o_orderpriority

```

```

order by
o_orderpriority
O_ORDERPRIORITY ORDER_COUNT
1-URGENT    10594.00
2-HIGH      10476.00
3-MEDIUM     10410.00
4-NOT SPECIFIED 10556.00
5-LOW       10487.00

```

5 rows processed.
Query Processed in 1.72 seconds.

```

-- @(#)5.sql      2.1.6.2
-- TPC-H/TPC-R Local Supplier Volume Query (Q5)
-- Functional Query Definition
-- Approved February 1998

```

```

select
n_name,
sum(l_extendedprice * (1 - l_discount)) as revenue
from
customer,
orders,
lineitem,
supplier,
nation,
region
where
c_custkey = o_custkey
and l_orderkey = o_orderkey
and l_suppkey = s_suppkey
and c_nationkey = s_nationkey
and s_nationkey = n_nationkey
and n_regionkey = r_regionkey
and r_name = 'ASIA'
and o_orderdate >= to_date('1994-01-01', 'YYYY-MM-DD')
and o_orderdate < add_months(to_date('1994-01-01', 'YYYY-MM-DD'), 12)
group by
n_name
order by
revenue desc

```

N_NAME	REVENUE
INDONESIA	55502041.17
VIETNAM	55295087.00
CHINA	53724494.26
INDIA	52035512.00
JAPAN	45410175.70

5 rows processed.
Query Processed in 4.92 seconds.

```

-- @(#)6.sql      2.1.6.2
-- TPC-H/TPC-R Forecasting Revenue Change Query (Q6)
-- Functional Query Definition
-- Approved February 1998

```

```

select
sum(l_extendedprice * l_discount) as revenue
from
lineitem
where

```

```

l_shipdate >= to_date('1994-01-01', 'YYYY-MM-DD')
and l_shipdate < add_months(to_date('1994-01-01', 'YYYY-MM-
DD'), 12)
and l_discount between .06 - 0.01 and .06 + 0.01
and l_quantity < 24

```

REVENUE
123141078.23

1 row processed.
Query Processed in 0.15 seconds.

```

-- @(#)7.sql 2.1.6.2
-- TPC-H/TPC-R Volume Shipping Query (Q7)
-- Functional Query Definition
-- Approved February 1998

```

```

select
supp_nation,
cust_nation,
l_year,
sum(volume) as revenue
from
(
select
n1.n_name as supp_nation,
n2.n_name as cust_nation,
to_number(to_char
(l_shipdate,'yyyy')) as l_year,
l_extendedprice * (1 - l_discount) as volume
from
supplier,
lineitem,
orders,
customer,
nation n1,
nation n2
where
s_suppkey = l_suppkey
and o_orderkey = l_orderkey
and c_custkey = o_custkey
and s_nationkey = n1.n_nationkey
and c_nationkey = n2.n_nationkey
and (
(n1.n_name = 'FRANCE' and n2.n_name = 'GERMANY')
or (n1.n_name = 'GERMANY' and n2.n_name = 'FRANCE')
)
and l_shipdate between to_date('1995-01-01', 'YYYY-MM-DD')
and to_date('1996-12-31', 'YYYY-MM-DD')
) shipping
group by
supp_nation,
cust_nation,
l_year
order by
supp_nation,
cust_nation,
l_year

```

SUPP_NATION	CUST_NATION	L_YEAR
REVENUE		
FRANCE	GERMANY	1995.00
54639732.73		
FRANCE	GERMANY	1996.00
54633083.31		
GERMANY	FRANCE	1995.00
52531746.67		

GERMANY	FRANCE	1996.00
52520549.02		

4 rows processed.
Query Processed in 4.79 seconds.

```

-- @(#)8a.sql 2.1.6.2
-- TPC-H/TPC-R National Market Share Query (Q8)
-- Variant A
-- Approved February 1998

```

```

select
o_year,
sum(case when nation='BRAZIL' then volume else 0 end )/
sum(volume)
as mkt_share
from
(
select
to_number(to_char(o_orderdate, 'yyyy')) as o_year,
l_extendedprice * (1 - l_discount) as volume,
n2.n_name as nation
from
part,
supplier,
lineitem,
orders,
customer,
nation n1,
nation n2,
region
where
p_partkey = l_partkey
and s_suppkey = l_suppkey
and l_orderkey = o_orderkey
and o_custkey = c_custkey
and c_nationkey = n1.n_nationkey
and n1.n_regionkey = r_regionkey
and r_name = 'AMERICA'
and s_nationkey = n2.n_nationkey
and o_orderdate between to_date('1995-01-01', 'YYYY-MM-DD')
and to_date('1996-12-31', 'YYYY-MM-DD')
and p_type = 'ECONOMY ANODIZED STEEL'
) all_nations
group by
o_year
order by
o_year

```

O_YEAR	MKT_SHARE
1995.00	0.03
1996.00	0.04

2 rows processed.
Query Processed in 8.04 seconds.

```

-- @(#)9.sql 2.1.6.2
-- TPC-H/TPC-R Product Type Profit Measure Query (Q9)
-- Functional Query Definition
-- Approved February 1998

```

```

select
nation,
o_year,

```

```

sum(amount) as sum_profit
from
(
select
n_name as nation,
to_number (to_char (o_orderdate, 'yyyy')) as o_year,
l_extendedprice * (1 - l_discount) - ps_supplycost * l_quantity as
amount
from
part,
supplier,
lineitem,
partsupp,
orders,
nation
where
s_suppkey = l_suppkey
and ps_suppkey = l_suppkey
and ps_partkey = l_partkey
and p_partkey = l_partkey
and o_orderkey = l_orderkey
and s_nationkey = n_nationkey
and p_name like '%green%'
) profit
group by
nation,
o_year
order by
nation,
o_year desc

```

NATION	O_YEAR	SUM_PROFIT		
ALGERIA	1998.00	31342867.23	EGYPT	1995.00 48311550.32
ALGERIA	1997.00	57138193.02	EGYPT	1994.00 49790644.74
ALGERIA	1996.00	56140140.13	EGYPT	1993.00 48904292.97
ALGERIA	1995.00	53051469.65	EGYPT	1992.00 49434932.62
ALGERIA	1994.00	53867582.13	ETHIOPIA	1998.00 28040717.27
ALGERIA	1993.00	54942718.13	ETHIOPIA	1997.00 47455009.87
ALGERIA	1992.00	54628034.71	ETHIOPIA	1996.00 46491097.57
ARGENTINA	1998.00	30211185.71	ETHIOPIA	1995.00 46804449.30
ARGENTINA	1997.00	50805741.75	ETHIOPIA	1994.00 48516143.92
ARGENTINA	1996.00	51923746.58	ETHIOPIA	1993.00 46551891.56
ARGENTINA	1995.00	49298625.77	ETHIOPIA	1992.00 44934648.64
ARGENTINA	1994.00	50835610.11	FRANCE	1998.00 32226407.84
ARGENTINA	1993.00	51646079.18	FRANCE	1997.00 47121485.86
ARGENTINA	1992.00	50410314.99	FRANCE	1996.00 47263135.50
BRAZIL	1998.00	27217924.38	FRANCE	1995.00 47275997.57
BRAZIL	1997.00	48378669.20	FRANCE	1994.00 47067209.33
BRAZIL	1996.00	50482870.36	FRANCE	1993.00 51163370.11
BRAZIL	1995.00	47623383.63	GERMANY	1998.00 28624942.66
BRAZIL	1994.00	47840165.73	GERMANY	1997.00 49309074.88
BRAZIL	1993.00	49054694.04	GERMANY	1996.00 49918683.17
BRAZIL	1992.00	48667639.08	GERMANY	1995.00 52650718.72
CANADA	1998.00	30379833.77	GERMANY	1994.00 50346900.42
CANADA	1997.00	50465052.31	GERMANY	1993.00 50991895.81
CANADA	1996.00	52560501.39	GERMANY	1992.00 48274126.10
CANADA	1995.00	52375332.81	INDIA	1998.00 29943144.35
CANADA	1994.00	52600364.66	INDIA	1997.00 50665453.23
CANADA	1993.00	52644504.07	INDIA	1996.00 50283092.29
CANADA	1992.00	53932871.70	INDIA	1995.00 50006774.64
CHINA	1998.00	31075466.16	INDIA	1994.00 48995190.76
CHINA	1997.00	50551874.45	INDIA	1993.00 50286902.85
CHINA	1996.00	51039293.88	INDIA	1992.00 50850329.40
CHINA	1995.00	49287534.62	INDONESIA	1998.00 27672340.00
CHINA	1994.00	50851090.07	INDONESIA	1997.00 50512145.73
CHINA	1993.00	54229629.83	INDONESIA	1996.00 51653060.12
CHINA	1992.00	52400529.37	INDONESIA	1995.00 51508779.59
EGYPT	1998.00	29054433.39	INDONESIA	1994.00 52817950.32
EGYPT	1997.00	50627611.45	INDONESIA	1993.00 47959994.96
EGYPT	1996.00	49542212.84	INDONESIA	1992.00 51776605.03
			IRAN	1998.00 29065736.24
			IRAN	1997.00 50042063.05
			IRAN	1996.00 50926653.19
			IRAN	1995.00 51249667.65
			IRAN	1994.00 50337085.87
			IRAN	1993.00 51730763.49
			IRAN	1992.00 49955856.56
			IRAQ	1998.00 31624551.00
			IRAQ	1997.00 55121749.02
			IRAQ	1996.00 55897663.79
			IRAQ	1995.00 54815472.52
			IRAQ	1994.00 54408516.13
			IRAQ	1993.00 53633167.98
			IRAQ	1992.00 55891939.34
			JAPAN	1998.00 27934179.67
			JAPAN	1997.00 44517162.55
			JAPAN	1996.00 42545606.12
			JAPAN	1995.00 43749356.40
			JAPAN	1994.00 44840243.07
			JAPAN	1993.00 44660015.53
			JAPAN	1992.00 45410249.12
			JORDAN	1998.00 26901488.58
			JORDAN	1997.00 45471878.41
			JORDAN	1996.00 46794325.79
			JORDAN	1995.00 45178828.58
			JORDAN	1994.00 45333636.51
			JORDAN	1993.00 47971496.10
			JORDAN	1992.00 44717239.18
			KENYA	1998.00 28597614.34
			KENYA	1997.00 47949733.73
			KENYA	1996.00 46886924.62

KENYA	1995.00	46072338.76	customer,
KENYA	1994.00	45772061.17	orders,
KENYA	1993.00	46308728.23	lineitem,
..... delete lines			nation
PERU	1992.00	47523899.05	where
ROMANIA	1998.00	30368667.40	c_custkey = o_custkey
ROMANIA	1997.00	50365683.85	and l_orderkey = o_orderkey
ROMANIA	1996.00	49598999.01	and o_orderdate >= to_date ('1993-10-01', 'YYYY-MM-DD')
ROMANIA	1995.00	47537642.87	and o_orderdate < add_months(to_date('1993-10-01', 'YYYY-MM-DD'), 3)
ROMANIA	1994.00	51455283.01	and l_returnflag = 'R'
ROMANIA	1993.00	50407136.89	and c_nationkey = n_nationkey
ROMANIA	1992.00	48185385.13	group by
RUSSIA	1998.00	28322384.03	c_custkey,
RUSSIA	1997.00	50106685.18	c_name,
RUSSIA	1996.00	51753342.43	c_acctbal,
RUSSIA	1995.00	49215820.36	c_phone,
RUSSIA	1994.00	52205666.44	n_name,
RUSSIA	1993.00	51860230.03	c_address,
RUSSIA	1992.00	53251677.15	c_comment
SAUDI ARABIA	1998.00	31541259.81	order by
SAUDI ARABIA	1997.00	52438750.81	revenue desc)
SAUDI ARABIA	1996.00	52543737.82	where rownum <= 20
SAUDI ARABIA	1995.00	52938696.53	
SAUDI ARABIA	1994.00	51389601.97	
SAUDI ARABIA	1993.00	52937508.88	
SAUDI ARABIA	1992.00	54843459.64	
UNITED KINGDOM	1998.00	28494874.00	C_CUSTKEY C_NAME REVENUE
UNITED KINGDOM	1997.00	49381810.90	C_ACCTBAL N_NAME
UNITED KINGDOM	1996.00	51386853.96	C_ADDRESS C_PHONE
UNITED KINGDOM	1995.00	51509586.79	C_COMMENT
UNITED KINGDOM	1994.00	48086499.71	57040.00 Customer#000057040 734235.25
UNITED KINGDOM	1993.00	49166827.22	632.87 JAPAN
UNITED KINGDOM	1992.00	49349122.08	Eioyzjf4pp 22-895-641-3466
UNITED STATES	1998.00	25126238.95	requests sleep blithely about the furiously i
UNITED STATES	1997.00	50077306.42	143347.00 Customer#000143347 721002.69
UNITED STATES	1996.00	48048649.47	2557.47 EGYPT
UNITED STATES	1995.00	48809032.42	1aReFYv,Kw4 14-742-935-3718
UNITED STATES	1994.00	49296747.18	fluffly bold excuses haggle finally after the u
UNITED STATES	1993.00	48029946.80	60838.00 Customer#000060838 679127.31
UNITED STATES	1992.00	48671944.50	2454.77 BRAZIL
VIETNAM	1998.00	30442736.06	64EaJ5vMAHWJIBOxIklpNc2RJiWE 12-913-494-9813
VIETNAM	1997.00	50309179.79	furiously even pinto beans integrate under the ruthless foxes; ironic,
VIETNAM	1996.00	50488161.41	even dolphins across the syl
VIETNAM	1995.00	49658284.61	101998.00 Customer#000101998 637029.57
VIETNAM	1994.00	50596057.26	3790.89 UNITED KINGDOM
VIETNAM	1993.00	50953919.15	01c9CILnNtfOQYmZj 33-593-865-6378
VIETNAM	1992.00	49613838.32	accounts doze blithely! enticing, final deposits sleep blithely special
			accounts. slyly express accounts pla
-- @(#)10.sql 2.1.6.2			125341.00 Customer#000125341 633508.09
-- TPC-H/TPC-R Returned Item Reporting Query (Q10)			4983.51 GERMANY
-- Functional Query Definition			S29ODD6bcU8QSuuEJznkNaK 17-582-695-5962
-- Approved February 1998			quickly express requests wake quickly blithely
			25501.00 Customer#000025501 620269.78
			7725.04 ETHIOPIA
			W556MXuoiaYCCZamJI,Rn0B4ACUGdkQ8DZ 15-874-808-
			6793
			quickly special requests sleep evenly among the special deposits.
			special deposi
			115831.00 Customer#000115831 596423.87
			5098.10 FRANCE
			rFeBbEEyk dl ne7zV5fDrmiq1oK09wV7pxqCgIc 16-715-386-3788
			carefully bold excuses sleep alongside of the thinly idle
			84223.00 Customer#000084223 594998.02
			528.65 UNITED KINGDOM
			nAVZCs6BaWap rrM27N 2qBnzc5WBauxbA 33-442-824-8191
			pending, final ideas haggle final requests. unusual, regular
			asymptotes affix according to the even foxes.
			54289.00 Customer#000054289 585603.39
			5583.02 IRAN
			vXCxoCsU0Bad5JQI ,oobkZ 20-834-292-4707
			express requests sublate blithely regular requests. regular, even ideas
			solve.

175 rows processed.
Query Processed in 2.51 seconds.

```
-- @(#)10.sql      2.1.6.2
-- TPC-H/TPC-R Returned Item Reporting Query (Q10)
-- Functional Query Definition
-- Approved February 1998
```

```
select * from (
select
c_custkey,
c_name,
sum(l_extendedprice * (1 - l_discount)) as revenue,
c_acctbal,
n_name,
c_address,
c_phone,
c_comment
from
```

39922.00 Customer#000039922 584878.11
 7321.11 GERMANY
 Zgy4s50l2GKN4pLDPBU8m342gIw6R 17-147-757-8036
 even pinto beans haggle, slyly bold accounts inte
 6226.00 Customer#000006226 576783.76
 2230.09 UNITED KINGDOM
 8gPu8,NPGkfYQQ0hcIYUGPIBWc,ybP5g, 33-657-701-3391
 quickly final requests against the regular instructions wake blithely
 final instructions. pa
 922.00 Customer#000000922 576767.53
 3869.25 GERMANY
 Az9RFaut7NkPnc5zSD2PwHgVwr4jRzq 17-945-916-9648
 boldly final requests cajole blith
 147946.00 Customer#000147946 576455.13
 2030.13 ALGERIA
 iANyZHzjqhyy7Ajah0pTrYyhJ 10-886-956-3143
 furiously even accounts are blithely above the furious
 115640.00 Customer#000115640 569341.19
 6436.10 ARGENTINA
 Vtgfia9qI 7EpHgecU1X 11-411-543-4901
 final instructions are slyly according to the
 73606.00 Customer#000073606 568656.86
 1785.67 JAPAN
 xuR0Tro5yChDfOCrjkd2ol 22-437-653-6966
 furiously bold orbits about the furiously busy requests wake across
 the furiously quiet theodolites. d
 110246.00 Customer#000110246 566842.98
 7763.35 VIETNAM
 7KzflgX MDOq7sOkI 31-943-426-9837
 dolphins sleep blithely among the slyly final
 142549.00 Customer#000142549 563537.24
 5085.99 INDONESIA
 ChqEoK43OysjdHbtKCp6dKqjNyvvi9 19-955-562-2398
 regular, unusual dependencies boost slyly; ironic attainments nag
 fluffy into the unusual packages?
 146149.00 Customer#000146149 557254.99
 1791.55 ROMANIA
 s87fvzFQpU 29-744-164-6487
 silent, unusual requests detect quickly slyly regul
 52528.00 Customer#000052528 556397.35
 551.79 ARGENTINA
 NFztyTOR10UOJ 11-208-192-3205
 unusual requests detect, slyly dogged theodolites use slyly. deposit
 23431.00 Customer#000023431 554269.54
 3381.86 ROMANIA
 HgiV0phqhaIa9aydNoIlb 29-915-458-2654
 instructions nag quickly. furiously bold accounts cajol

group by
 ps_partkey having
 sum(ps_supplycost * ps_availqty) > (

select
 sum(ps_supplycost * ps_availqty) * 0.000100000
 from
 partsupp,
 supplier,
 nation
 where
 ps_suppkey = s_suppkey
 and s_nationkey = n_nationkey
 and n_name = 'GERMANY'
)
 order by
 value desc

PS_PARTKEY	VALUE
129760.00	17538456.86
166726.00	16503353.92
191287.00	16474801.97
161758.00	16101755.54
34452.00	15983844.72
139035.00	15907078.34
9403.00	15451755.62
154358.00	15212937.88
38823.00	15064802.86
85606.00	15053957.15
33354.00	14408297.40
154747.00	14407580.68
82865.00	14235489.78
76094.00	14094247.04
222.00	13937777.74
121271.00	13908336.00
55221.00	13716120.47
22819.00	13666434.28
76281.00	13646853.68
85298.00	13581154.93
85158.00	13554904.00
139684.00	13535538.72
31034.00	13498025.25
87305.00	13482847.04
10181.00	13445148.75
62323.00	13411824.30
26489.00	13377256.38
96493.00	13339057.83
56548.00	13329014.97
55576.00	13306843.35
159751.00	13306614.48
92406.00	13287414.50
182636.00	13223726.74
199969.00	13135288.21
62865.00	13001926.94
7284.00	12945298.19
197867.00	12944510.52
11562.00	12931575.51
75165.00	12916918.12
97175.00	12911283.50
140840.00	12896562.23
65241.00	12890600.46
166120.00	12876927.22
9035.00	12863828.70
144616.00	12853549.30
176723.00	12832309.74
170884.00	12792136.58
29790.00	12723300.33
95213.00	12555483.73
183873.00	12550533.05
171235.00	12476538.30
21533.00	12437821.32

```

-- @(#11.sql      2.1.6.2
-- TPC-H/TPC-R Important Stock Identification Query (Q11)
-- Functional Query Definition
-- Approved February 1998

select
  ps_partkey,
  sum(ps_supplycost * ps_availqty) as value
from
  partsupp,
  supplier,
  nation
where
  ps_suppkey = s_suppkey
  and s_nationkey = n_nationkey
  and n_name = 'GERMANY'

```

17290.00	12432159.50	95952.00	7927972.78
156397.00	12260623.50	196514.00	7927180.70
122611.00	12222812.98	4403.00	7925729.04
139155.00	12220319.25	2267.00	7925649.37
146316.00	12215800.61	45924.00	7925047.68
171381.00	12199734.52	11493.00	7916722.23
198633.00	12078226.95	104478.00	7916253.60
167417.00	12046637.62	166794.00	7913842.00
59512.00	12043468.76	161995.00	7910874.27
31688.00	12034893.64	23538.00	7909752.06
159586.00	12001505.84	41093.00	7909579.92
8993.00	11963814.30	112073.00	7908617.57
120302.00	11857707.55	92814.00	7908262.50
43536.00	11779340.52	88919.00	7907992.50
9552.00	11776909.16	79753.00	7907933.88
86223.00	11772205.08	108765.00	7905338.98
53776.00	11758669.65	146530.00	7905336.60
131285.00	11616953.74	71475.00	7903367.58
91628.00	11611114.83	36289.00	7901946.50
169644.00	11567959.72	61739.00	7900794.00
182299.00	11567462.05	52338.00	7898638.08
33107.00	11453818.76	194299.00	7898421.24
104184.00	11436657.44	105235.00	7897829.94
67027.00	11419127.14	77207.00	7897752.72
176869.00	11371451.71	96712.00	7897575.27
30885.00	11369674.79	10157.00	7897046.25
54420.00	11345076.88	171154.00	7896814.50
72240.00	11313951.05	79373.00	7896186.00
178708.00	11294635.17	113808.00	7893353.88
81298.00	11273686.13	27901.00	7892952.00
158324.00	11243442.72	128820.00	7892882.72
117095.00	11242535.24	25891.00	7890511.20
176793.00	11237733.38	122819.00	7888881.02
86091.00	11177793.79	154731.00	7888301.33
116033.00	11145434.36	101674.00	7879324.60
129058.00	11119112.20	51968.00	7879102.21
193714.00	11104706.39	72073.00	7877736.11
117195.00	11077217.96	5182.00	7874521.73
49851.00	11043701.78		
19791.00	11030662.62		
75800.00	11012401.62	1048 rows processed.	
161562.00	10996371.69	Query Processed in 4.01 seconds.	
10119.00	10980015.75		
39185.00	10970042.56		
47223.00	10950022.13	-- @(#)12.sql	2.1.6.2
175594.00	10942923.05	-- TPC-H/TPC-R Shipping Modes and Order Priority Query (Q12)	
111295.00	10893675.61	-- Functional Query Definition	
155446.00	10852764.57	-- Approved February 1998	
156391.00	10839810.38		
40884.00	10837234.19		
141288.00	10837130.21		
152388.00	10830977.82		
33449.00	10830858.72		
149035.00	10826130.02		
162620.00	10814275.68		
118324.00	10791788.10		
38932.00	10777541.75		
121294.00	10764225.22		
48721.00	10762582.49		
63342.00	10740132.60		
5614.00	10724668.80		
62266.00	10711143.10		
100202.00	10696675.55		
197741.00	10688560.72		
..... delete lines			
71518.00	7932261.69		
72922.00	7930400.64		
146699.00	7929167.40		
92387.00	7928972.67		
186289.00	7928786.19		

```

-- @(#)12.sql          2.1.6.2
-- TPC-H/TPC-R Shipping Modes and Order Priority Query (Q12)
-- Functional Query Definition
-- Approved February 1998

select
    l_shipmode,
    sum(case
        when o_orderpriority = '1-URGENT'
            or o_orderpriority = '2-HIGH'
            then 1
        else 0
    end) as high_line_count,
    sum(case
        when o_orderpriority <> '1-URGENT'
            and o_orderpriority <> '2-HIGH'
            then 1
        else 0
    end) as low_line_count
from
    orders,
    lineitem
where
    o_orderkey = l_orderkey
    and l_shipmode in ('MAIL', 'SHIP')

```

```

        and l_commitdate < l_receiptdate
        and l_shipdate < l_commitdate
and l_receiptdate >= to_date('1994-01-01', 'YYYY-MM-DD')
and l_receiptdate < add_months(to_date('1994-01-01', 'YYYY-
MM-DD'), 12)
group by
    l_shipmode
order by
    l_shipmode

L_SHIPMODE HIGH_LINE_COUNT    LOW_LINE_COUNT
MAIL      6202.00          9324.00
SHIP      6200.00          9262.00

2 rows processed.
Query Processed in 1.49 seconds.

27.00      1185.00
4.00       1033.00
28.00      869.00
29.00      559.00
3.00       398.00
30.00      373.00
31.00      235.00
2.00       144.00
32.00      128.00
33.00      71.00
34.00      48.00
35.00      33.00
1.00       23.00
36.00      17.00
37.00      7.00
40.00      4.00
38.00      4.00
39.00      2.00
41.00      1.00

```

```

-- @(#)13.sql      2.1.6.2
-- TPC-H/TPC-R Customer Distribution Query (Q13)
-- Functional Query Definition
-- Approved February 1998

```

```

select
c_count,
count(*) as custdist
from
(
select
c_custkey,
count(o_orderkey) as c_count
from
customer, orders where
c_custkey = o_custkey(+)
and o_comment(+) not like '%special%requests%'
group by
c_custkey
) c_orders
group by
c_count
order by
custdist desc,
c_count desc

```

C_COUNT	CUSTDIST
0.00	50004.00
9.00	6641.00
10.00	6566.00
11.00	6058.00
8.00	5949.00
12.00	5553.00
13.00	4989.00
19.00	4748.00
7.00	4707.00
18.00	4625.00
15.00	4552.00
17.00	4530.00
14.00	4484.00
20.00	4461.00
16.00	4323.00
21.00	4217.00
22.00	3730.00
6.00	3334.00
23.00	3129.00
24.00	2622.00
25.00	2079.00
5.00	1972.00
26.00	1593.00

```

-- @(#)14.sql      2.1.6.2
-- TPC-H/TPC-R Promotion Effect Query (Q14)
-- Functional Query Definition
-- Approved February 1998

select
100.00 * sum(case
                when p_type like 'PROMO%'
                    then l_extendedprice * (1 -
l_discount)
                else 0
            end) / sum(l_extendedprice * (1 - l_discount)) as
promo_revenue
from
lineitem,
part
where
l_partkey = p_partkey
and l_shipdate >= date '1995-09-01'
and l_shipdate < date '1995-09-01' + interval '1' month

```

PROMO_REVENUE
16.38

1 row processed.
Query Processed in 1.08 seconds.

```

-- @(#)15.sql 2.1.6.2
-- TPC-H/TPC-R Top Supplier Query (Q15)
-- Functional Query Definition
-- Approved February 1998

```

```

with revenue
as (select
l_suppkey supplier_no,
sum(l_extendedprice * (1 - l_discount)) total_revenue
from
lineitem
where
l_shipdate >= to_date('1996-01-01', 'YYYY-MM-DD')
)
```

```

and l_shipdate < add_months( to_date ('1996-01-01', 'YYYY-MM-
DD'), 3)
group by
l_suppkey)
select
s_suppkey,
s_name,
s_address,
s_phone,
total_revenue
from
supplier,
revenue
where
s_suppkey = supplier_no
and total_revenue =(
select
max(total_revenue)
from
revenue )
order by
s_suppkey

```

S_SUPPKEY	S_NAME	S_PHONE
S_ADDRESS		
TOTAL_REVENUE		
8449.00	Supplier#000008449	
Wp34zim9qYFbVctdW		20-469-856-8873 1772627.21

1 row processed.
Query Processed in 15.60 seconds.

```

-- @(#)16.sql      2.1.6.2
-- TPC-H/TPC-R Parts/Supplier Relationship Query (Q16)
-- Functional Query Definition
-- Approved February 1998

```

```

select
p_brand,
p_type,
p_size,
count(distinct ps_suppkey) as supplier_cnt
from
partsupp,
part
where
p_partkey = ps_partkey
and p_brand <> 'Brand#45'
and p_type not like 'MEDIUM POLISHED%'
and p_size in (49, 14, 23, 45, 19, 3, 36, 9)
and ps_suppkey not in (
select
s_suppkey
from
supplier
where
s_comment like '%Customer%Complaints%'
)
group by
p_brand,
p_type,
p_size
order by
supplier_cnt desc,
p_brand,
p_type,
p_size

```

P_BRAND	P_TYPE	P_SIZE	
SUPPLIER_CNT			
Brand#41	MEDIUM BRUSHED TIN	3.00	28.00
Brand#54	STANDARD BRUSHED COPPER	14.00	
	27.00		
Brand#11	STANDARD BRUSHED TIN	23.00	24.00
Brand#11	STANDARD BURNISHED BRASS	36.00	
	24.00		
Brand#15	MEDIUM ANODIZED NICKEL	3.00	
	24.00		
Brand#15	SMALL ANODIZED BRASS	45.00	24.00
Brand#15	SMALL BURNISHED NICKEL	19.00	
	24.00		
Brand#21	MEDIUM ANODIZED COPPER	3.00	
	24.00		
Brand#22	SMALL BRUSHED NICKEL	3.00	24.00
Brand#22	SMALL BURNISHED BRASS	19.00	
	24.00		
Brand#25	MEDIUM BURNISHED COPPER	36.00	
	24.00		
Brand#31	PROMO POLISHED COPPER	36.00	
Brand#33	LARGE POLISHED TIN	23.00	24.00
Brand#33	PROMO POLISHED STEEL	14.00	
Brand#35	PROMO BRUSHED NICKEL	14.00	24.00
Brand#41	ECONOMY BRUSHED STEEL	9.00	
	24.00		
Brand#41	ECONOMY POLISHED TIN	19.00	24.00
Brand#41	LARGE PLATED COPPER	36.00	
Brand#42	ECONOMY PLATED BRASS	3.00	24.00
Brand#42	STANDARD POLISHED TIN	49.00	
Brand#43	PROMO BRUSHED TIN	3.00	24.00
Brand#43	SMALL ANODIZED COPPER	36.00	
	24.00		
Brand#44	STANDARD POLISHED NICKEL	3.00	
	24.00		
Brand#52	ECONOMY PLATED TIN	14.00	24.00
Brand#52	STANDARD BURNISHED NICKEL	3.00	
	24.00		
Brand#53	MEDIUM ANODIZED STEEL	14.00	
	24.00		
Brand#14	PROMO ANODIZED NICKEL	45.00	
	23.00		
Brand#32	ECONOMY PLATED BRASS	9.00	23.00
Brand#52	SMALL ANODIZED COPPER	3.00	23.00
Brand#11	ECONOMY BRUSHED COPPER	45.00	
	20.00		
Brand#11	ECONOMY PLATED BRASS	23.00	
	20.00		
Brand#11	LARGE BRUSHED COPPER	49.00	20.00
Brand#11	LARGE POLISHED COPPER	49.00	
Brand#12	STANDARD ANODIZED TIN	49.00	
	20.00		
Brand#12	STANDARD PLATED BRASS	19.00	
	20.00		
Brand#13	ECONOMY BRUSHED BRASS	9.00	
	20.00		
Brand#13	ECONOMY BURNISHED STEEL	14.00	
	20.00		
Brand#13	LARGE BURNISHED NICKEL	19.00	
	20.00		
Brand#13	MEDIUM BURNISHED COPPER	36.00	
	20.00		
Brand#13	SMALL BRUSHED TIN	45.00	20.00
Brand#13	STANDARD ANODIZED COPPER	3.00	
	20.00		
Brand#13	STANDARD PLATED NICKEL	23.00	
	20.00		
Brand#14	ECONOMY ANODIZED COPPER	14.00	
	20.00		

Brand#14	ECONOMY PLATED TIN	36.00	20.00	Brand#35	MEDIUM ANODIZED STEEL	23.00
Brand#14	ECONOMY POLISHED NICKEL	3.00		20.00		
20.00				Brand#35	PROMO ANODIZED COPPER	49.00
Brand#14	MEDIUM ANODIZED NICKEL	3.00		20.00		
20.00				Brand#35	SMALL POLISHED COPPER	14.00
Brand#14	SMALL POLISHED TIN	14.00	20.00	20.00		20.00
Brand#15	MEDIUM ANODIZED COPPER	9.00		Brand#41	LARGE ANODIZED STEEL	3.00
20.00				Brand#41	LARGE BRUSHED NICKEL	23.00
Brand#15	MEDIUM PLATED TIN	23.00	20.00	Brand#41	LARGE BURNISHED COPPER	3.00
Brand#15	PROMO PLATED BRASS	14.00	20.00	20.00		
Brand#15	SMALL ANODIZED COPPER	45.00		Brand#41	MEDIUM PLATED STEEL	19.00
20.00				Brand#41	SMALL BURNISHED COPPER	23.00
Brand#15	SMALL PLATED COPPER	49.00	20.00	20.00		
Brand#15	STANDARD PLATED TIN	3.00	20.00	Brand#42	MEDIUM BURNISHED BRASS	14.00
Brand#21	LARGE ANODIZED COPPER	36.00		20.00		
20.00				Brand#42	SMALL BURNISHED COPPER	3.00
Brand#21	LARGE BRUSHED TIN	3.00	20.00	20.00		
Brand#21	MEDIUM ANODIZED COPPER	14.00		Brand#43	ECONOMY POLISHED COPPER	9.00
20.00				20.00		
Brand#21	PROMO BRUSHED TIN	36.00	20.00	Brand#43	SMALL PLATED STEEL	3.00
Brand#21	PROMO POLISHED NICKEL	45.00	20.00	20.00	STANDARD BURNISHED TIN	23.00
Brand#21	SMALL ANODIZED COPPER	9.00	20.00	20.00		
Brand#21	SMALL POLISHED NICKEL	23.00	20.00	Brand#44	LARGE ANODIZED STEEL	23.00
Brand#22	LARGE ANODIZED COPPER	36.00		20.00		
20.00				Brand#44	PROMO ANODIZED TIN	23.00
Brand#22	LARGE BRUSHED COPPER	49.00	20.00	20.00		
Brand#22	PROMO ANODIZED TIN	49.00	20.00	Brand#51	ECONOMY BRUSHED BRASS	49.00
Brand#22	PROMO POLISHED BRASS	45.00	20.00	20.00		
Brand#22	SMALL BURNISHED STEEL	45.00	20.00 delete lines		
Brand#23	MEDIUM ANODIZED STEEL	45.00		Brand#55	STANDARD PLATED BRASS	49.00
20.00				Brand#55	STANDARD PLATED COPPER	9.00
Brand#23	PROMO POLISHED STEEL	23.00	20.00	4.00		
Brand#23	STANDARD BRUSHED TIN	14.00	20.00	Brand#55	STANDARD PLATED COPPER	45.00
Brand#23	STANDARD PLATED NICKEL	36.00		4.00		
20.00				Brand#55	STANDARD PLATED NICKEL	3.00
Brand#24	PROMO PLATED COPPER	49.00	20.00	4.00		
Brand#24	PROMO PLATED STEEL	49.00	20.00	Brand#55	STANDARD PLATED NICKEL	19.00
Brand#24	PROMO POLISHED STEEL	9.00	20.00	4.00		
Brand#24	STANDARD BRUSHED TIN	36.00	20.00	Brand#55	STANDARD PLATED NICKEL	45.00
Brand#25	LARGE ANODIZED BRASS	3.00	20.00	4.00		
Brand#25	PROMO BURNISHED TIN	3.00	20.00	Brand#55	STANDARD PLATED STEEL	14.00
Brand#31	ECONOMY POLISHED NICKEL	3.00		4.00		
20.00				Brand#55	STANDARD PLATED STEEL	23.00
Brand#31	MEDIUM PLATED TIN	45.00	20.00	4.00		
Brand#31	SMALL ANODIZED STEEL	14.00	20.00	Brand#55	STANDARD PLATED STEEL	49.00
Brand#32	ECONOMY ANODIZED COPPER	36.00		4.00		
20.00				Brand#55	STANDARD PLATED TIN	9.00
Brand#32	ECONOMY BRUSHED NICKEL	49.00		4.00		
20.00				Brand#55	STANDARD PLATED TIN	14.00
Brand#32	LARGE ANODIZED TIN	19.00	20.00	4.00		
Brand#32	MEDIUM BURNISHED COPPER	19.00		Brand#55	STANDARD PLATED TIN	36.00
20.00				Brand#55	STANDARD POLISHED BRASS	3.00
Brand#32	SMALL ANODIZED STEEL	45.00	20.00	4.00		
Brand#33	ECONOMY POLISHED COPPER	19.00		Brand#55	STANDARD POLISHED BRASS	9.00
20.00				Brand#55	STANDARD POLISHED BRASS	23.00
Brand#33	PROMO PLATED NICKEL	14.00	20.00	4.00		
Brand#33	SMALL POLISHED TIN	9.00	20.00	Brand#55	STANDARD POLISHED COPPER	3.00
Brand#33	STANDARD ANODIZED BRASS	49.00		4.00		
20.00				Brand#55	STANDARD POLISHED NICKEL	3.00
Brand#33	STANDARD BURNISHED BRASS	45.00		4.00		
20.00				Brand#55	STANDARD POLISHED NICKEL	23.00
Brand#34	ECONOMY BRUSHED NICKEL	49.00		4.00		
20.00				Brand#55	STANDARD POLISHED NICKEL	49.00
Brand#34	LARGE BRUSHED BRASS	19.00	20.00	4.00		
Brand#34	SMALL BRUSHED TIN	3.00	20.00	Brand#55	STANDARD POLISHED STEEL	14.00
Brand#34	STANDARD PLATED COPPER	9.00		4.00		
20.00				Brand#55	STANDARD POLISHED STEEL	23.00
Brand#35	LARGE ANODIZED NICKEL	3.00	20.00	4.00		
Brand#35	MEDIUM ANODIZED BRASS	45.00		Brand#55	STANDARD POLISHED TIN	9.00
20.00				Brand#55	STANDARD POLISHED TIN	19.00

Brand#11	SMALL BRUSHED TIN	19.00	3.00	
Brand#15	LARGE PLATED NICKEL	45.00	3.00	orders, lineitem
Brand#15	LARGE POLISHED NICKEL	9.00	3.00	where o_orderkey in (
Brand#21	PROMO BURNISHED STEEL	45.00	3.00	select l_orderkey
Brand#22	STANDARD PLATED STEEL	23.00	3.00	from lineitem
Brand#25	LARGE PLATED STEEL	19.00	3.00	group by l_orderkey having
Brand#32	STANDARD ANODIZED COPPER	23.00	3.00	sum(l_quantity) > 300)
				and c_custkey = o_custkey and o_orderkey = l_orderkey
Brand#33	SMALL ANODIZED BRASS	9.00	3.00	group by c_name,
Brand#35	MEDIUM ANODIZED TIN	19.00	3.00	c_custkey, o_orderkey,
Brand#51	SMALL PLATED BRASS	23.00	3.00	o_orderdate, o_totalprice
Brand#52	MEDIUM BRUSHED BRASS	45.00	3.00	order by o_totalprice desc,
Brand#53	MEDIUM BRUSHED TIN	45.00	3.00	o_orderdate
Brand#54	ECONOMY POLISHED BRASS	9.00	3.00)
Brand#55	PROMO PLATED BRASS	19.00	3.00	where rownum <= 100
Brand#55	STANDARD PLATED TIN	49.00	3.00	

18314 rows processed.

Query Processed in 1.73 seconds.

```
-- @(#)17.sql      2.1.6.2
-- TPC-H/TPC-R Small-Quantity-Order Revenue Query (Q17)
-- Functional Query Definition
-- Approved February 1998
```

```
select
sum(l_extendedprice) / 7.0 as avg_yearly
from
lineitem,
part
where
p_partkey = l_partkey
and p_brand = 'Brand#23'
and p_container = 'MED BOX'
and l_quantity < (
select
0.2 * avg(l_quantity)
from
lineitem
where
l_partkey = p_partkey
)

AVG_YEARLY
348406.05
```

1 row processed.

Query Processed in 2.32 seconds.

```
-- @(#)18.sql      2.1.6.2
-- TPC-H/TPC-R Large Volume Customer Query (Q18)
-- Function Query Definition
-- Approved February 1998
```

```
select * from (
select
c_name,
c_custkey,
o_orderkey,
o_orderdate,
o_totalprice,
sum(l_quantity)
from
customer,
```

C_NAME	C_CUSTKEY	O_ORDERKEY
O_ORDERDATE		
O_TOTALPRICE	SUM(L_QUANTITY)	
Customer#000128120	128120.00	4722021.00
1994-04-07		
544089.09	323.00	
Customer#000144617	144617.00	3043270.00
1997-02-12		
530604.44	317.00	
Customer#000013940	13940.00	2232932.00
1997-04-13		
522720.61	304.00	
Customer#000066790	66790.00	2199712.00
1996-09-30		
515531.82	327.00	
Customer#000046435	46435.00	4745607.00
1997-07-03		
508047.99	309.00	
Customer#000015272	15272.00	3883783.00
1993-07-28		
500241.33	302.00	
Customer#000146608	146608.00	3342468.00
1994-06-12		
499794.58	303.00	
Customer#000096103	96103.00	5984582.00
1992-03-16		
494398.79	312.00	
Customer#000024341	24341.00	1474818.00
1992-11-15		
491348.26	302.00	
Customer#000137446	137446.00	5489475.00
1997-05-23		
487763.25	311.00	
Customer#000107590	107590.00	4267751.00
1994-11-04		
485141.38	301.00	
Customer#000050008	50008.00	2366755.00
1996-12-09		
483891.26	302.00	
Customer#000015619	15619.00	3767271.00
1996-08-07		
480083.96	318.00	
Customer#00007260	77260.00	1436544.00
1992-09-12		

479499.43	307.00				Customer#000037729	37729.00	4134341.00
Customer#000109379	109379.00	5746311.00			1995-06-29		
1996-10-10					441082.97	309.00	
478064.11	302.00				Customer#000003566	3566.00	2329187.00
Customer#000054602	54602.00	5832321.00			1998-01-04		
1997-02-09					439803.36	304.00	
471220.08	307.00				Customer#000045538	45538.00	4527553.00
Customer#000105995	105995.00	2096705.00			1994-05-22		
1994-07-03					436275.31	305.00	
469692.58	307.00				Customer#000081581	81581.00	4739650.00
Customer#000148885	148885.00	2942469.00			1995-11-04		
1992-05-31					435405.90	305.00	
469630.44	313.00				Customer#000119989	119989.00	1544643.00
Customer#000114586	114586.00	551136.00			1997-09-20		
1993-05-19					434568.25	320.00	
469605.59	308.00				Customer#000003680	3680.00	3861123.00
Customer#000105260	105260.00	5296167.00			1998-07-03		
1996-09-06					433525.97	301.00	
469360.57	303.00				Customer#000113131	113131.00	967334.00
Customer#000147197	147197.00	1263015.00			1995-12-15		
1997-02-02					432957.75	301.00	
467149.67	320.00				Customer#000141098	141098.00	565574.00
Customer#000064483	64483.00	2745894.00			1995-09-24		
1996-07-04					430986.69	301.00	
466991.35	304.00				Customer#000093392	93392.00	5200102.00
Customer#000136573	136573.00	2761378.00			1997-01-22		
1996-05-31					425487.51	304.00	
461282.73	301.00				Customer#000015631	15631.00	1845057.00
Customer#000016384	16384.00	502886.00			1994-05-12		
1994-04-12					419879.59	302.00	
458378.92	312.00				Customer#000112987	112987.00	4439686.00
Customer#000117919	117919.00	2869152.00			1996-09-17		
1996-06-20					418161.49	305.00	
456815.92	317.00				Customer#000012599	12599.00	4259524.00
Customer#000012251	12251.00	735366.00			1998-02-12		
1993-11-24					415200.61	304.00	
455107.26	309.00				Customer#000105410	105410.00	4478371.00
Customer#000120098	120098.00	1971680.00			1996-03-05		
1995-06-14					412754.51	302.00	
453451.23	308.00				Customer#000149842	149842.00	5156581.00
Customer#000066098	66098.00	5007490.00			1994-05-30		
1992-08-07					411329.35	302.00	
453436.16	304.00				Customer#000010129	10129.00	5849444.00
Customer#000117076	117076.00	4290656.00			1994-03-21		
1997-02-05					409129.85	309.00	
449545.85	301.00				Customer#000069904	69904.00	1742403.00
Customer#000129379	129379.00	4720454.00			1996-10-19		
1997-06-07					408513.00	305.00	
448665.79	303.00				Customer#000017746	17746.00	6882.00
Customer#000126865	126865.00	4702759.00			1997-04-09		
1994-11-07					408446.93	303.00	
447606.65	320.00				Customer#000013072	13072.00	1481925.00
Customer#000088876	88876.00	983201.00			1998-03-15		
1993-12-30					399195.47	301.00	
446717.46	304.00				Customer#000082441	82441.00	857959.00
Customer#000036619	36619.00	4806726.00			1994-02-07		
1995-01-17					382579.74	305.00	
446704.09	328.00				Customer#000088703	88703.00	2995076.00
Customer#000141823	141823.00	2806245.00			1994-01-30		
1996-12-29					363812.12	302.00	
446269.12	310.00						
Customer#000053029	53029.00	2662214.00					
1993-08-13							
446144.49	302.00						
Customer#000018188	18188.00	3037414.00					
1995-01-25							
443807.22	308.00						
Customer#000066533	66533.00	29158.00					
1995-10-21							
443576.50	305.00						

57 rows processed.
Query Processed in 1.23 seconds.

-- @(#)19.sql 2.1.6.2
-- TPC-H/TPC-R Discounted Revenue Query (Q19)
-- Functional Query Definition
-- Approved February 1998

```

select
sum(l_extendedprice* (1 - l_discount)) as revenue
from
lineitem,
part
where
(
p_partkey = l_partkey
and p_brand = 'Brand#12'
and p_container in ('SM CASE', 'SM BOX', 'SM PACK', 'SM PKG')
and l_quantity >= 1 and l_quantity <= 1 + 10
and p_size between 1 and 5
and l_shipmode in ('AIR', 'AIR REG')
and l_shipinstruct = 'DELIVER IN PERSON'
)
or
(
p_partkey = l_partkey
and p_brand = 'Brand#23'
and p_container in ('MED BAG', 'MED BOX', 'MED PKG', 'MED PACK')
and l_quantity >= 10 and l_quantity <= 10 + 10
and p_size between 1 and 10
and l_shipmode in ('AIR', 'AIR REG')
and l_shipinstruct = 'DELIVER IN PERSON'
)
or
(
p_partkey = l_partkey
and p_brand = 'Brand#34'
and p_container in ('LG CASE', 'LG BOX', 'LG PACK', 'LG PKG')
and l_quantity >= 20 and l_quantity <= 20 + 10
and p_size between 1 and 15
and l_shipmode in ('AIR', 'AIR REG')
and l_shipinstruct = 'DELIVER IN PERSON'
)

REVENUE
3083843.06

```

1 row processed.
Query Processed in 1.39 seconds.

```

-- @(#)20.sql      2.1.6.2
-- TPC-H/TPC-R Potential Part Promotion Query (Q20)
-- Function Query Definition
-- Approved February 1998

```

```

select
s_name,
s_address
from
supplier,
nation
where
s_suppkey in (
select
ps_suppkey
from
partsupp
where
ps_partkey in (
select
p_partkey
from

```

```

part
where
p_name like 'forest%'
)
and ps_availqty > (
select
0.5 * sum(l_quantity)
from
lineitem
where
l_partkey = ps_partkey
and l_suppkey = ps_suppkey
and l_shipdate >= to_date ('1994-01-01', 'YYYY-MM-DD')
and l_shipdate < add_months( to_date ('1994-01-01', 'YYYY-MM-DD'), 12 )
)
)
and s_nationkey = n_nationkey
and n_name = 'CANADA'
order by
s_name

S_NAME          S_ADDRESS
Supplier#000000020  iybAE,RmTymrZVYafZva2SH.j
Supplier#000000091
YV45D7TkfdQanOOZ7q9QxkyGUapU1oOWU6q3
Supplier#000000197  YC2Acon6kjY3zj3Fbxs2k4Vdf7X0cd2F
Supplier#000000226  83qOdu2EYRdPQAQhEtn GRZEd
Supplier#000000285  Br7e1nnt1yxrw6ImgpJ7YdhFDjuBf
Supplier#000000378  FfbhyCxWvcPrO8ltp9
Supplier#000000402  i9Sw4DoyMhzKhXCH9By,AYSgmD
Supplier#000000530  0qwCMwobKY
OcmLyfRXlagA8ukENJv,
Supplier#000000688  D
fw5ocppmZpYBBIP1718hCihLDZ5KhKX
Supplier#000000710  f19YPvOyb
QoYwjKC,oPycpGfieBAcwKJo
Supplier#000000736
l6i2nMwVuovfKnuVgaSGK2rDy65DIAFLegiL7
Supplier#000000761
zlSLelQUj2XrvTTFnv7WAcYZGvvMTx882d4
Supplier#000000884  bmhEShejaS
Supplier#000000887  urEaTejH5POADP2ARrf
Supplier#000000935  ij98czM 2KzWe7dDTOxB8sq0UfcdrvX
Supplier#000000975  ,AC.e,tBpNwKb5xMUzeohxiRn,
hdZJ073gFQF8y
Supplier#000001263  rQWr6nf8ZhB2TAiIDIVo5Io
Supplier#000001399  LmrocnIMSyYOWuANx7
Supplier#000001446  lch9HMNU1R7a0LiIbsUodVknk6
Supplier#000001454  TOpimgu2TVXIjhiL93h,
Supplier#000001500  wDmF5xLxtQch9ctVu,
Supplier#000001602  uKNWleafaM644
Supplier#000001626  UhxNRzUu1dtFmp0
Supplier#000001682  pXTkGxrTQVYh1Rr
Supplier#000001699  Q9C4rfJ26oijVPqqcqVXeRI
Supplier#000001700  7hMICof1Y5zLFg
Supplier#000001726  TeRY7TtTH24sEword7yAaSkjx8
Supplier#000001730  Rc8e,1Pybn r6zo0VJIEiD0UD vhk
Supplier#000001746
qWsendlOekQG1aW4uq06uQaCm51se8lirv7 hBRd
Supplier#000001752  Fra7outx41THYJaRThdOGiBk
Supplier#000001856
jXcRgzYF0ah05iR8p6w5SbJJLcUGyYiURPvFwUWM
Supplier#000001931  FpJbMU2h6ZR2eBv8I9NIxF
Supplier#000001939  NrkJA4bfReUs
Supplier#000001990
DSDJkCgBJzuPg1yuM,CUdLnsRliOxkkHezTCA
Supplier#000002020  jB6r1d7MxP6co
Supplier#000002022  dwebGX7Id2pc25YvY33
Supplier#000002036  20ytTrVObjKUU12WCB0A

```

Supplier#000002204	VfZ I1J,mwp4aS
uYmlr46C06udCqanj0KiRs0TQakZsEyssL	Supplier#000004388
Supplier#000002243 nSOEV3JeOU79	Supplier#000004406
Supplier#000002245	Ah0ZaLu6VwufPWUz,7kbXgYZhauEaHqGIg
hz2qWXWVjOyKhqPYMoEwz6zFkrTaDM	Supplier#000004430
Supplier#000002282	yvSsKNSTL5HLXBET4luOsPNLxKzAMk
ES21K9dxoW1I1TzWCj7ekdINwSWnv1Z 6mQ,BKn	Supplier#000004522 xXtCKwsZDArxIBGDfzX2PgobGZsBg
Supplier#000002303 nCoWfpB6YOymbgOh7ltfklpkHI	Supplier#000004527 p vXNCnxgcklWF6A1o3OHY3qW6
Supplier#000002373 RzHSxOTQmElCxjBiVA52Z	NJSbLJDroYG2y1r3rDiKg
JB58rJhPRylR	Supplier#000004574 1HvGwnVueZ5CIIndc
Supplier#000002419 qydBQd14I5l5mVXA4fYY	Supplier#000004655 67NqBc4 t3PG3F8aO
Supplier#000002481 nLKHUOn2M19TOA06Znq9GEMcIlMO2	IsqWNq4kGaPowYL
Supplier#000002571 JZUugz04c iJFLrlGsz90 N,W	Supplier#000004701 6jX4u47URzIMHf
1rVHNIReyq	Supplier#000004711 bEzjp1QdQu ls2ERMxv0km
Supplier#000002585 CsPoKpw2QuTY4AV1NkWuttneIa4SN	vn6bu2zXIL1
Supplier#000002630 ZIQAvjNUY9KH5ive zm7k	Supplier#000004987 UFx1upJ8MvOvgFjA8
ViPiD7CCo21	Supplier#000005000 DeX804 wH8FrCUvahgy ilbzBX3NK
Supplier#000002719 4nnzQI2CbqREQUuIsXTBVUkaP4mNS3	Supplier#000005100 OfvYps3Io,wEvvlHNnaLuCX
Supplier#000002721 HvDFAN2JHMQSpKm	Supplier#000005192 JDp4rhXiDw0kf6RH
Supplier#000002730 IIxFxR4fzm31C6,muzJwl84z	Supplier#000005195 Woi3b2ZaicPh ZSfu1EfXhE
Supplier#000002775 yDclaDaBD4ihH delete lines
Supplier#000002853 rTNAOItXka	Supplier#000007885 u3sicchh5ZpyTUpN1cJKNcAoabIWgY
Supplier#000002875 6JgMi	Supplier#000007918 r,v9mBQ6LoEYyj1
9Qt6VmW3Ltt1SRlKww0keLQ,RAZa	Supplier#000007926 ErzCF80K9Uy
Supplier#000002934 m,trBENy wSArwg3Dhb	Supplier#000007957 ELwnio14ssoU1 dRyZIL OK3Vtzb
Supplier#000002941 Naddba 8YTEKekZyP0	Supplier#000007965 F7Un5IJ7p5hhj
Supplier#000002960	DsF9UIZ2Fo6HXN9aErvyg likHoD582HSGZpP
KCPCEsRGGo6vx8TygHh60nAYf9rStQT2T	Supplier#000007998 LnASFBFYRF0o9d6d,asBvVq9Lo2P
Supplier#000002980	Supplier#000008168 aOa82a8ZbKCnfDLX
B9k9yVsyAxWktOSHezqHiAEp9id0SKzkw	Supplier#000008231 IK7eGw Yj90sTdpSP,vcqWxLB
Supplier#000003062 LSQNggY1xnOzz9zBCapy7HwOZQ	Supplier#000008243 2AyePMkDqmzVzjGTizXthFl08h
Supplier#000003087 ANwe8QsZ4rgj1HSqVz991eWQ	EiudCMxOmIIG
Supplier#000003089 s5b VClZqMSZVa r	Supplier#000008275 BlbNDFWg,gpXKQILN
g7LTdgc29GbTE7rI1x	Supplier#000008323 75118sZmASwm
Supplier#000003095 HxON3jJhUi3zjt,r mTD	POeheRMdj9tmpyeQ,BfCXN5BIAb
Supplier#000003201 E87ywss6I,t0qNs4QW7UzExKiJnJDZWue	Supplier#000008366
Supplier#000003213 pxrRP4irQ1VoyfQ,dTf3	h778cEj14BuW9OEKlvPTWq4iwASR6EBBXN7zeS8
Supplier#000003241 j06SU,LS9O3mwjAMoViA NeIhb	Supplier#000008423 RQhKnkAhR0DAr3Ix4Q1weMMn00hNe
Supplier#000003275 9xO4nyJ2QJcX6vGf	Kq
Supplier#000003288 EDDfNt7E5Uc,xLTupoIgYL4yY7ujh,	Supplier#000008480 4sSDA4ACReklNjEm5T6b
Supplier#000003313	Supplier#000008532
EI2I7we,049SPrvomUm4hZwJoOhZkvLxLJXgVH	Uc29q4,5xVdDOF87UZrxhr4xWS0ihEUXuh
Supplier#000003314	Supplier#000008595 MH0iB73GQ3z UW3O DbCbqmc
jnisU8MzqO4iUB3zsPcrysMw3DDUojS4q7LD	Supplier#000008610
Supplier#000003380	SgVgP90vP452sUNTgzL9zKwXHxAzV6tV
jPv0V,pszouuuFT3YsAqlP,kxT3u,gTFiEbRtx	Supplier#000008705 aE,trRNdPx,4yinTD903DebDlp
Supplier#000003403 e3X2o_KCG9tsHj18A XXXCxiF2hZWBw	Supplier#000008742 HmPIQEzKCPEctUL14,kKq
Supplier#000003421 Sh3dt9W5oeofWvovFhrq,	Supplier#000008841 I 85L1sekbg2xrSIzm0
Supplier#000003441 zvFJzS,oUuShHjpcX	Supplier#000008895 2cH4okfaLSZTTg8sKRbbJQxkmeFu2Esj
Supplier#000003590 sy79CMLxqb,Cbo	Supplier#000008967 2kwEHyMG
Supplier#000003607 lNqFHQYjwSAkf	7FwozNIImAUE6mH0hYtqYcuLM
Supplier#000003625	Supplier#000008972 w2vF6 D5YZO3visPXsqVfLADTK
qY588W0Yk5iaUy1RXTgNrEKrMAjBYHcKs	Supplier#000009032 qK,trB6Sdy4Dz1BRUFN
Supplier#000003656 eEYmm02gmD JdfG32XtDgJV,db56	Supplier#000009147 rOAuryHxpZ9eOvx
Supplier#000003782 iVsPZg7bk06TqNMwi0LkbLurC1zmrg	Supplier#000009252 F7cZaPUHwh1 ZKjy3xmAVWC1Xdp
Supplier#000003918 meRvrCsJoAbfqd0Re4	ue1p5m,i
Supplier#000003941 Pmb05mQfBMS618O7WKqZJ 9yyv	Supplier#000009278 RqYTzgxj93CLX 0mcYfCENOefD
Supplier#000003994 W00LZp3Njk0	Supplier#000009327 uoqMd7e7Gj9dbQ53
Supplier#000004005 V723F1wCy2eA4OgIu8TjBtOVUH	Supplier#000009430 igRqmneft
Supplier#000004033 ncsAhv9Je,kFXTNjfB2	Supplier#000009567 r4Wfx4c3xsEAjcGj71HHZByorml
Supplier#000004140 0hL7DJyYjcHL	D9vrztXlv4
Supplier#000004165	Supplier#000009601 51m637bO,Rw5DnHWFUvLacRx9
wTJ2dZNQA8P2oi99N6DT47ndHy,XKD2	Supplier#000009709 rRnCbHYgDgj9PZYnyWKVYSUW0vKg
Supplier#000004207 tF64pwIM04IkWjN3mS,e06WuAjLx	Supplier#000009753 wLhVEcRmd7PkJF4FBnGK7Z
Supplier#000004236	Supplier#000009796 zy4ldmr15DOvPuqYG
dl,HptlmGipxYsSqn9wmqkuWjst,mCeJ8O6T	Supplier#000009799 4wNjXGa4OKW1
Supplier#000004246 Xha aXQF7u4qU3LsHD	Supplier#000009811 E3iuyq7UnZxU7oPZle2Gu6
Supplier#000004278 bBddbpBxIVp Di9	Supplier#000009812 APFRMy3ICbgFga53n5t9DxzFPQPgnjrGt32
Supplier#000004343 GK3sbopqrQEkWLMvVBFCG	Supplier#000009862 rJzweWeN58
Supplier#000004346 S3076LEOwo	

Supplier#000009868	ROjGgx5gvtkmnUUoeyy7v	Supplier#000002005	16.00
Supplier#000009869		Supplier#000002095	16.00
ucLqxzrpBTRMewGSM29t0rNTM30g!Tu3Xgg3mKag		Supplier#000005799	16.00
Supplier#000009899	7XdpaHrzrlt,UQFZE	Supplier#000005842	16.00
Supplier#000009974	7wJ,J5DKcxSU4Kp1cQLpbcAvB5AsvKT	Supplier#000006450	16.00
		Supplier#000006939	16.00
		Supplier#000009200	16.00
		Supplier#000009727	16.00
		Supplier#000000486	15.00
		Supplier#000000565	15.00
		Supplier#000001046	15.00
		Supplier#000001047	15.00
-- @(#)21.sql	2.1.6.2	Supplier#000001161	15.00
-- TPC-H/TPC-R Suppliers Who Kept Orders Waiting Query (Q21)		Supplier#000001336	15.00
-- Functional Query Definition		Supplier#000001435	15.00
-- Approved February 1998		Supplier#000003075	15.00
		Supplier#000003335	15.00
		Supplier#000005649	15.00
		Supplier#000006027	15.00
		Supplier#000006795	15.00
		Supplier#000006800	15.00
		Supplier#000006824	15.00
		Supplier#000007131	15.00
		Supplier#000007382	15.00
		Supplier#000008913	15.00
		Supplier#000009787	15.00
		Supplier#000000633	14.00
		Supplier#000001960	14.00
		Supplier#000002323	14.00
		Supplier#000002490	14.00
		Supplier#000002993	14.00
		Supplier#000003101	14.00
		Supplier#000004489	14.00
		Supplier#000005435	14.00
		Supplier#000005583	14.00
		Supplier#000005774	14.00
		Supplier#000007579	14.00
		Supplier#000008180	14.00
		Supplier#000008695	14.00
		Supplier#000009224	14.00
		Supplier#000000357	13.00
		Supplier#000000436	13.00
		Supplier#000000610	13.00
		Supplier#000000788	13.00
		Supplier#000000889	13.00
		Supplier#000001062	13.00
		Supplier#000001498	13.00
		Supplier#000002056	13.00
		Supplier#000002312	13.00
		Supplier#000002344	13.00
		Supplier#000002596	13.00
		Supplier#000002615	13.00
		Supplier#000002978	13.00
		Supplier#000003048	13.00
		Supplier#000003234	13.00
		Supplier#000003727	13.00
		Supplier#000003806	13.00
		Supplier#000004472	13.00
		Supplier#000005236	13.00
S_NAME	NUMWAIT	Supplier#000005906	13.00
Supplier#000002829	20.00	Supplier#000006241	13.00
Supplier#000005808	18.00	Supplier#000006326	13.00
Supplier#000000262	17.00	Supplier#000006384	13.00
Supplier#000000496	17.00	Supplier#000006394	13.00
Supplier#000002160	17.00	Supplier#000006624	13.00
Supplier#000002301	17.00	Supplier#000006629	13.00
Supplier#000002540	17.00	Supplier#000006682	13.00
Supplier#000003063	17.00	Supplier#000006737	13.00
Supplier#000005178	17.00	Supplier#000006825	13.00
Supplier#000008331	17.00	Supplier#000007021	13.00

204 rows processed.
Query Processed in 1.77 seconds.

```
-- @(#)21.sql          2.1.6.2
-- TPC-H/TPC-R Suppliers Who Kept Orders Waiting Query (Q21)
-- Functional Query Definition
-- Approved February 1998
```

```
select * from (
select
s_name,
count(*) numwait
from
supplier,
lineitem l1,
orders,
nation
where
s_suppkey = l1.l_suppkey
and o_orderkey = l1.l_orderkey
and o_orderstatus = 'F'
and l1.l_receiptdate > l1.l_commitdate
and exists (
select
*
from
lineitem l2
where
l2.l_orderkey = l1.l_orderkey
and l2.l_suppkey <> l1.l_suppkey
)
and not exists (
select
*
from
lineitem l3
where
l3.l_orderkey = l1.l_orderkey
and l3.l_suppkey <> l1.l_suppkey
and l3.l_receiptdate > l3.l_commitdate
)
and s_nationkey = n_nationkey
and n_name = 'SAUDI ARABIA'
group by
s_name
order by
numwait desc,
s_name)
where rownum <= 100
```

S_NAME	NUMWAIT
Supplier#000002829	20.00
Supplier#000005808	18.00
Supplier#000000262	17.00
Supplier#000000496	17.00
Supplier#000002160	17.00
Supplier#000002301	17.00
Supplier#000002540	17.00
Supplier#000003063	17.00
Supplier#000005178	17.00
Supplier#000008331	17.00

```

Supplier#000007417    13.00
Supplier#000007497    13.00
Supplier#000007602    13.00
Supplier#000008134    13.00
Supplier#000008234    13.00
Supplier#000009435    13.00
Supplier#000009436    13.00
Supplier#000009564    13.00
Supplier#000009896    13.00
Supplier#000000379    12.00
Supplier#000000673    12.00
Supplier#000000762    12.00
Supplier#000000811    12.00
Supplier#000000821    12.00
Supplier#000001337    12.00
Supplier#000001916    12.00
Supplier#000001925    12.00
Supplier#000002039    12.00
Supplier#000002357    12.00
Supplier#000002483    12.00

```

100 rows processed.

Query Processed in 17.89 seconds.

```

-- @(#)22.sql 2.1.4.2
-- TPC-H/TPC-R Global Sales Opportunity Query (Q22)
-- Functional Query Definition
-- Approved February 1998

```

```

select
avg(c_acctbal)
from
customer
where
c_acctbal > 0.00
and substr(c_phone, 1, 2) in
('13', '31', '23', '29', '30', '18', '17')
)
and not exists (
select
*
from
orders
where
o_custkey = c_custkey
)
) custsale
group by
cntrycode
order by
cntrycode

```

CNTRYCODE	NUMCUST	TOTACCTBAL
13	888.00	6737713.99
17	861.00	6460573.72
18	964.00	7236687.40
23	892.00	6701457.95
29	948.00	7158866.63
30	909.00	6808436.13
31	922.00	6806670.18

```

select
cntrycode,
count(*) as numcust,
sum(c_acctbal) as totacctbal
from
(
select
substr(c_phone, 1, 2) as cntrycode,
c_acctbal
from
customer
where
substr(c_phone,1, 2) in
('13', '31', '23', '29', '30', '18', '17')
and c_acctbal > (

```

7 rows processed.
Query Processed in 1.11 seconds.

Ended Executing this Stream at Mon Dec 15 14:30:31 2003

Stream Started at 1071527346.99
Stream Ended at 1071527431.96
Stream Processed in 84.97 seconds

SQL statements processed: 22

Appendix E Seed and Input Parameters

E.1 seed

1205185144

E.2 stream00

14	1994-09-01		
2	2 STEEL EUROPE		
9	honeydew		
20	deep 1994-01-01 CANADA		
6	1995-01-01 0.06 25		
17	Brand#42 JUMBO BOX		
18	313		
8	PERU AMERICA MEDIUM		
BURNISHED STEEL			
21	FRANCE		
13	special requests		
3	BUILDING 1995-03-23		
22	13 22 17 27 30		
19	12		
16	Brand#14 SMALL POLISHED 1 13 2		
31	34 8 5 29		
4	1996-08-01		
11	EGYPT 0.0000000100		
15	1996-11-01		
1	68		
10	1994-01-01		
19	Brand#42 Brand#21 Brand#54 7 11		
28			
5	ASIA 1995-01-01		
7	JORDAN PERU		
12	RAIL REG AIR 1994-01-01		

E.3 stream01

21	UNITED KINGDOM		
3	HOUSEHOLD 1995-03-09		
18	314		
5	EUROPE 1996-01-01		
11	PERU 0.0000000100		
7	ETHIOPIA INDONESIA		
6	1996-01-01 0.03 24		
20	pale 1997-01-01 CHINA		
17	Brand#44 JUMBO PACK		
12	AIR REG AIR 1994-01-01		
16	Brand#44 LARGE BRUSHED 26 29		
17	13 10 32 11 7		
15	1994-08-01		
13	special requests		
10	1994-10-01		
2	40 NICKEL AMERICA		
8	INDONESIA ASIA SMALL BRUSHED		
STEEL			
14	1994-12-01		
19	Brand#44 Brand#54 Brand#54 3 12		
24			
9	frosted		
22	28 30 18 15 29		
27	19		
1	76		
4	1994-05-01		

E.4 stream02

6	1996-01-01 0.09 24
17	Brand#41 JUMBO DRUM
14	1995-04-01
16	Brand#34 STANDARD BURNISHED 12 4
9	16 38 30 5
23	
19	Brand#41 Brand#42 Brand#43 8 13
20	
10	1993-08-01
9	dim
2	28 TIN MIDDLE EAST
15	1997-02-01
8	ARGENTINA AMERICA SMALL
PLATED	STEEL
5	MIDDLE EAST 1996-01-01
22	18 15 21 29 26
27	25
12	SHIP REG AIR 1995-01-01
7	RUSSIA ARGENTINA
13	special requests
18	312
1	84
4	1996-12-01
20	blanched 1996-01-01 GERMANY
3	BUILDING 1995-03-25
11	ETHIOPIA 0.0000000100
21	MOROCCO

E.5 stream03

8	CHINA ASIA SMALL ANODIZED COPPER
5	AFRICA 1996-01-01
4	1994-09-01
6	1996-01-01 0.06 25
17	Brand#43 WRAP BOX
7	KENYA CHINA
1	92
18	313
22	13 23 18 29 17
27	14
14	1995-07-01
9	cornflower
10	1994-05-01
15	1994-11-01
11	CHINA 0.0000000100
20	lime 1994-01-01 RUSSIA
2	16 COPPER AMERICA
21	GERMANY
19	Brand#53 Brand#25 Brand#42 3 14
27	special requests
13	Brand#14 MEDIUM PLATED 43 10
16	48 19 17 23
20	
12	FOB REG AIR 1995-01-01
3	HOUSEHOLD 1995-03-11

E.6 stream04

5	AMERICA 1996-01-01
21	UNITED STATES
14	1995-10-01
19	Brand#55 Brand#53 Brand#41 9 15
23	
15	1997-06-01

17 Brand#45 WRAP PACK
 12 MAIL REG AIR 1995-01-01
 6 1996-01-01 0.04 24
 4 1997-04-01
 9 burlywood
 8 IRAN MIDDLE EAST STANDARD
POLISHED COPPER
 16 Brand#44 ECONOMY BRUSHED 29 1
 7 19 31 10 41
 17
 11 FRANCE 0.000000100
 2 3 STEEL MIDDLE EAST
 10 1993-02-01
 18 315
 1 100
 13 special accounts
 7 FRANCE IRAN
 22 10 17 29 26 21
 16 19
 3 AUTOMOBILE 1995-03-27
 20 tan 1997-01-01 JAPAN

E.7 stream05

21 MOZAMBIQUE
 15 1995-02-01
 4 1995-01-01
 6 1997-01-01 0.09 24
 7 UNITED KINGDOM BRAZIL
 16 Brand#34 SMALL ANODIZED 9 15 7
 11 28 32 41 10
 19 Brand#52 Brand#41 Brand#31 4 16
 20
 18 312
 14 1996-01-01
 22 21 17 29 10 24
 16 20
 11 ROMANIA 0.000000100
 13 special accounts
 3 FURNITURE 1995-03-13
 1 108
 2 41 BRASS ASIA
 5 ASIA 1997-01-01
 8 BRAZIL AMERICA STANDARD
BURNISHED COPPER
 20 gainsboro 1996-01-01 ARGENTINA
 12 TRUCK AIR 1995-01-01
 17 Brand#41 WRAP DRUM
 10 1993-11-01
 9 bisque

E.8 stream06

10 1994-08-01
 3 AUTOMOBILE 1995-03-30
 15 1997-09-01
 13 special accounts
 6 1997-01-01 0.07 25
 8 ROMANIA EUROPE PROMO BRUSHED
COPPER
 9 yellow
 7 MOROCCO ROMANIA
 4 1997-08-01
 11 GERMANY 0.000000100
 22 26 19 31 18 10
 14 32
 18 314
 12 RAIL AIR 1996-01-01
 1 116

5 MIDDLE EAST 1997-01-01
 16 Brand#14 LARGE PLATED 3 38
 45 23 24 44 43
 20
 2 29 TIN MIDDLE EAST
 14 1996-05-01
 19 Brand#14 Brand#24 Brand#35 9 17
 27
 20 purple 1994-01-01 MOZAMBIQUE
 17 Brand#43 SM BAG
 21 INDONESIA

E.9 stream07
 18 315
 8 IRAQ MIDDLE EAST PROMO PLATED
COPPER
 20 chocolate 1993-01-01 FRANCE
 21 ARGENTINA
 2 17 COPPER ASIA
 4 1995-05-01
 22 16 20 24 26 28
 30 12
 17 Brand#45 SM PACK
 1 63
 11 SAUDI ARABIA 0.000000100
 9 thistle
 19 Brand#11 Brand#12 Brand#24 4 18
 23
 3 FURNITURE 1995-03-15
 13 special accounts
 5 AFRICA 1997-01-01
 7 GERMANY IRAQ
 10 1993-06-01
 16 Brand#44 PROMO POLISHED 6 9
 11 13 35 4 48
 38
 6 1997-01-01 0.04 24
 14 1996-08-01
 15 1995-06-01
 12 REG AIR AIR 1996-01-01

E.10 stream08

19 Brand#13 Brand#45 Brand#23 10 19
 30
 1 72
 15 1993-03-01
 17 Brand#42 SM DRUM
 5 AMERICA 1997-01-01
 8 CANADA AMERICA PROMO BURNISHED
TIN
 9 slate
 12 SHIP AIR 1996-01-01
 14 1996-11-01
 7 UNITED STATES CANADA
 4 1993-02-01
 3 MACHINERY 1995-03-01
 20 misty 1996-01-01 VIETNAM
 16 Brand#34 MEDIUM ANODIZED 10
 23 37 14 17 35
 20 39
 6 1997-01-01 0.09 24
 22 29 20 16 26 11
 34 23
 10 1994-03-01
 13 pending deposits
 2 5 STEEL AFRICA

21	CHINA			4	1995-08-01						
18	313			22	22	18	26	28	32		
11	INDIA	0.0000000100			24	17					
				1	80						
				7	MOZAMBIQUE	SAUDI ARABIA					
				12	FOB	RAIL	1997-01-01				
				9	saddle						
				14	1997-02-01						
				5	ASIA	1997-01-01					
				16	Brand#14	ECONOMY BURNISHED	45				
					23	6	5	11	29		7
					9						
E.11	stream09										
8	SAUDI ARABIA	MIDDLE EAST	ECONOMY								
	BRUSHED TIN										
13	pending	deposits									
2	42	BRASS	ASIA								
20	almond	1995-01-01	IRAN								
17	Brand#44	LG BAG									
3	FURNITURE	1995-03-17									
6	1997-01-01	0.07	25								
21	IRAN										
18	314										
11	VIETNAM	0.0000000100									
19	Brand#21	Brand#33	Brand#23	5	20						
	26										
10	1994-12-01										
15	1995-09-01										

Appendix F Benchmark Scripts

F. 1 dbtables.sql

```
set echo on
set numwidth 25
spool rdbtablest
```

```
SELECT COUNT(*) FROM LINEITEM;
```

```
SELECT * FROM LINEITEM
WHERE L_ORDERKEY IN
( 4, 26598, 148577, 387431, 56704, 517442, 600000)
AND L_LINENUMBER = 1
ORDER BY L_ORDERKEY;
```

```
SELECT * FROM REGION;
```

```
SELECT COUNT(*) FROM NATION;
```

```
SELECT * FROM NATION
WHERE N_NATIONKEY IN (3,10,14,20)
ORDER BY N_NATIONKEY;
```

```
SELECT COUNT(*) FROM ORDERS;
```

```
SELECT * FROM ORDERS
WHERE O_ORDERKEY IN ( 7, 44065, 287590, 411111, 483876,
599942 )
ORDER BY O_ORDERKEY;
```

```
SELECT COUNT(*) FROM PART;
```

```
SELECT * FROM PART
WHERE P_PARTKEY IN (1,984,8743,9028,13876,17899,20000)
ORDER BY P_PARTKEY;
```

```
SELECT COUNT(*) FROM PARTSUPP;
```

```
SELECT* FROM PARTSUPP
WHERE PS_PARTKEY = 3398
AND PS_SUPPKEY = (SELECT MIN(PS_SUPPKEY)
FROM PARTSUPP WHERE PS_PARTKEY = 3398);
```

```
SELECT* FROM PARTSUPP
WHERE PS_PARTKEY = 15873
AND PS_SUPPKEY = (SELECT MIN(PS_SUPPKEY)
FROM PARTSUPP WHERE PS_PARTKEY = 15873);
```

```
SELECT* FROM PARTSUPP
WHERE PS_PARTKEY = 11394
AND PS_SUPPKEY = (SELECT MIN(PS_SUPPKEY)
FROM PARTSUPP WHERE PS_PARTKEY = 11394);
```

```
SELECT* FROM PARTSUPP
WHERE PS_PARTKEY = 6743
AND PS_SUPPKEY = (SELECT MIN(PS_SUPPKEY)
FROM PARTSUPP WHERE PS_PARTKEY = 6743);
```

```
SELECT* FROM PARTSUPP
```

```
WHERE PS_PARTKEY = 19763
AND PS_SUPPKEY = (SELECT MIN(PS_SUPPKEY)
FROM PARTSUPP WHERE PS_PARTKEY = 19763);
```

```
SELECT COUNT(*) FROM SUPPLIER;
```

```
SELECT * FROM SUPPLIER
WHERE S_SUPPKEY IN (83,265,492,784,901,1000)
ORDER BY S_SUPPKEY;
```

```
DROP TABLE MINMAX;
```

```
CREATE TABLE MINMAX
(TNAME CHAR(15),
KEYMIN INTEGER,
KEYMAX INTEGER);
```

```
INSERT INTO MINMAX
SELECT
'LINEITEM_ORD',MIN(L_ORDERKEY),MAX(L_ORDERKEY)
FROM LINEITEM ;
```

```
INSERT INTO MINMAX
SELECT
'LINEITEM_NBR',MIN(L_LINENUMBER),MAX(L_LINENUMBER)
FROM LINEITEM;
```

```
INSERT INTO MINMAX
SELECT
'ORDERTBL',MIN(O_ORDERKEY),MAX(O_ORDERKEY)
FROM ORDERS;
```

```
INSERT INTO MINMAX
SELECT 'CUSTOMER',MIN(C_CUSTKEY),MAX(C_CUSTKEY)
FROM CUSTOMER;
```

```
INSERT INTO MINMAX
SELECT 'PART',MIN(P_PARTKEY),MAX(P_PARTKEY)
FROM PART;
```

```
INSERT INTO MINMAX
SELECT 'SUPPLIER',MIN(S_SUPPKEY),MAX(S_SUPPKEY)
FROM SUPPLIER;
```

```
INSERT INTO MINMAX
SELECT
'PARTSUPP_PART',MIN(PS_PARTKEY),MAX(PS_PARTKEY)
FROM PARTSUPP;
```

```
INSERT INTO MINMAX
SELECT
'PARTSUPP_SUPP',MIN(PS_SUPPKEY),MAX(PS_SUPPKEY)
FROM PARTSUPP ;
```

```
INSERT INTO MINMAX
SELECT
'NATION',MIN(N_NATIONKEY),MAX(N_NATIONKEY)
FROM NATION;
```

```
INSERT INTO MINMAX
SELECT
'REGION',MIN(R_REGIONKEY),MAX(R_REGIONKEY)
FROM REGION;
```

```
SELECT * FROM MINMAX;
```

```

spool off
exit;
/* end of file gtime.c */

```

F. 2 gen_seed.sh

```

#!/bin/ksh
SEED_FILE=$1

#Generate the seed
echo "Setting the random number seed"
PSEED=`date +%m:%d:%H:%M:%S | sed -e 's/://g'`
echo "Using ${PSEED} as seed0"
echo ${PSEED} > $SEED_FILE
echo "Done setting the random number seed"

```

F. 3 gtime.c

/* Copyright (c) 2001, 2002, Oracle Corporation. All rights reserved. */

```

/*
NAME
gtime.c - <one-line expansion of the name>

DESCRIPTION
<short description of facility this file declares/defines>

EXPORT FUNCTION(S)
<external functions defined for use outside package - one-line descriptions>

INTERNAL FUNCTION(S)
<other external functions defined - one-line descriptions>

STATIC FUNCTION(S)
<static functions defined - one-line descriptions>

NOTES
<other useful comments, qualifications, etc.>

MODIFIED (MM/DD/YY)
mpoess 10/23/02 - mpoess_update_from_visa
mpoess 08/29/01 - Creation

*/
#include<stdio.h>
#include<stdlib.h>

#include <sys/time.h>

main ()
{
    struct timeval tv;

    (void) gettimeofday (&tv, (struct timezone *) 0);

    printf ("% .2f\n", ((double) tv.tv_sec + (1.0e-6 * (double)
tv.tv_usec)) );
}
```

F. 4 qexecpl.c

```

#ifndef RCSID
static char *RCSid =
"$Header: qexecpl.c 17-oct-2001.09:29:47 mpoess Exp $ ";
#endif /* RCSID */

/* Copyright (c) 1999, 2001, Oracle Corporation. All rights
reserved. */

/*
NAME
qexecpl.c - <one-line expansion of the name>

DESCRIPTION
SQL Execution Engine, Oracle v8, OCI version

PRIVATE FUNCTION(S)
<list of static functions defined in .c file - with one-line
descriptions>

MODIFIED (MM/DD/YY)
mpoess 10/17/01 - add serialization level in SQLInit
mpoess 02/22/01 - add linux changes
mpoess 08/05/99 - make compile
mpoess 11/13/98 - fix pdll statement
pswong 02/19/97 - migrating to version 8
pswong 04/02/96 - more polishing
pswong 03/25/96 - polish up
pswong 03/06/96 - created

*/
#include <stdio.h>
#include <string.h>
#include <setjmp.h>
#include <sys/param.h>
#include <errno.h>
#include <math.h>
#include <string.h>
#include <sys/types.h>
#include <time.h>
#include <stdlib.h>

#include "qexecpl.h"

/* Function Prototypes */

extern double gettime();

/* function prototypes from gen.c */

int get_statement();

/* Declare error handling functions */

void sql_error();

/* Other prototypes */

int define_output_variables();
void process_select_list();
void usage();
void SQLInit();
```

```

void SQLexec();
void SQLexit();
void *memalloc();
void print_header();
void print_rows();
int OFEN();
void remove_newline();

char logname[UNAME_LEN]; /* username/passwd combo */
char *passwd;

double tr_start = 0.0; /* query start time */
double tr_end = 0.0; /* query end time */

double s_tr_start = 0.0; /* statement start time */
double s_tr_end = 0.0; /* statement end time */

/* For our purpose of timing, we will treat comments as delimiters */
/* for queries. Thus, we will collect query timings whenever we */
/* encounter a comment (of course not for the first comment in a */
/* file). */

int end_flag = 0; /* flag to indicate that we have reached */
/* the end of a query */

int stmt_cnt = 0; /* Number of statements processed. */
int qry_cnt = 0; /* Number of query processed. */

double product = 1.0; /* cumulative product of query times */
int rows_ret = 0; /* the number of rows fetched */
int num_sel_list = 0; /* the number of select list item */

long num_to_fetch = -1; /* Number of rows to fetch. -1 means
fetch all */

sltype slist[MAX_SEL_LIST]; /* Array for describing Select List
*/
dltype *dlist[MAX_SEL_LIST]; /* Array of ptrs for Defining Select
List */

char stmt[SQL_LEN]; /* The SQL statement or comment line.
*/
char qn[3]; /* Number of the query being executed */
char qnp[3]; /* Number of the previous query executed */
char cmnt[5000]; /* Buffer to save the comment. */
#ifndef LINUX
FILE *qtemp; /* fd for query template */
FILE *logfile; /* log and report files */
FILE *rep;
#else
FILE *qtemp = stdin; /* fd for query template */
FILE *logfile = stdout; /* log and report files */
FILE *rep = stdout;
#endif
void *defbuf; /* Buffer pointer for ODEFIN */
int deflen = 0; /* Size of data type for ODEFIN */
int deftype = 1; /* Oracle type number for ODEFIN */

int pfmem = PFMEMSIZE; /* Memory to prefetch rows */

time_t tim; /* To get wall clock time */

/* OCI handles */

OCIEnv *tpcenv = NULL;
OCIServer *tpcsrv = NULL;
OCIError *errhp = NULL;
OCISvcCtx *tpcsvc = NULL;
OCISession *tpcusr = NULL;
OCIStmt *curq = NULL;

OCIStmt *cur_dml = NULL;
OCIStmt *cur_ddl = NULL;
OCIParam *tpcpar = NULL;

sword status = OCI_SUCCESS; /* OCI return value */

/* usage: prints the usage of the program */

void usage() {

    fprintf(stderr, "\nUsage: qexec username/password [q<path name
for query template file>] \n");
    fprintf(stderr, "          [l<path name for log>] [r<path name for
reports>] \n\n");
    fprintf(stderr, "Options:\n");
    fprintf(stderr, "  q<path for query>      : full path name for the query
template file.\n");
    fprintf(stderr, "  (default is stdin)\n");
    fprintf(stderr, "  l<path name for log>   : full path name for log
files\n");
    fprintf(stderr, "  (default is stdout)\n");
    fprintf(stderr, "  r<path name for reports> : full path name for
reports\n");
    fprintf(stderr, "  (default is stdout)\n");
    exit(1);
}

/* type: 0 if environment handle is passed, 1 if error handle is
passwd */

void sql_error(errhp,status,type)
    OCIError *errhp;
    sword status;
    sword type;
{
    char msg[2048];
    ub4 errcode;
    ub4 msglen;
    int i,j;

    switch(status) {
    case OCI_SUCCESS_WITH_INFO:
        fprintf(stderr, "Error: Statement returned with info.\n");
        if(type)
            (void) OCIErrorGet(errhp,1,NULL,(sb4*)&errcode,(text*)msg,
                2048,OCI_HTYPE_ERROR);
        else
            (void) OCIErrorGet(errhp,1,NULL,(sb4*)&errcode,(text*)msg,
                2048,OCI_HTYPE_ENV);
        fprintf(stderr,"%s\n",msg);
        break;
    case OCI_ERROR:
        fprintf(stderr, "Error: OCI call error.\n");
        if(type)
            (void) OCIErrorGet(errhp,1,NULL,(sb4*)&errcode,(text*)msg,
                2048,OCI_HTYPE_ERROR);
        else
            (void) OCIErrorGet(errhp,1,NULL,(sb4*)&errcode,(text*)msg,
                2048,OCI_HTYPE_ENV);
        fprintf(stderr,"%s\n",msg);
        break;
    case OCI_INVALID_HANDLE:
        fprintf(stderr, "Error: Invalid Handle.\n");
        if(type)
            (void) OCIErrorGet(errhp,1,NULL,(sb4*)&errcode,(text*)msg,
                2048,OCI_HTYPE_ERROR);
        else
            (void) OCIErrorGet(errhp,1,NULL,(sb4*)&errcode,(text*)msg,
                2048,OCI_HTYPE_ENV);
    }
}

```

```

2048,OCI_HTYPE_ENV);
fprintf(stderr,"%s\n",msg);
break;
}

/* Rollback just in case */

(void) OCITransRollback(tpcsvc,errhp,OCI_DEFAULT);

fprintf(stderr, "Exiting Oracle...\n");
fflush(stderr);

SQLexit();

exit(1);
}

#endif LINUX
int main(argc,argv)
#else
void main(argc,argv)
#endif
{
    int argc;
    char *argv[];

    int i,pos,pos2;
    int retcode; /* Return code for get_statement */
#endif LINUX
    logfile=fopen("/dev/stdout","w");
    qtemp=fopen("/dev/stdin","rw");
    rep=fopen("/dev/stdout","w");
#endif
/* Initialize some variables */

if ((argc > 5) || (argc < 2)) {
    usage();
}
/* argv[1] - User and Password for Database */

strcpy(logname, argv[1]);

/* Process optional parameters */

argc -= 1;
argv += 1;

while(--argc) {
    ++argv;
    switch(argv[0][0]) {
    case 'q':
        if ((qtemp = fopen(++(argv[0]),"r")) == NULL) {
            fprintf(stderr,"Unable to open file '%s'\n", argv[0]);
            fprintf(stderr,"%s: %s\n", argv[0], strerror(errno));
            exit(-1);
        }
        break;
    case 'r':
        if ((rep = fopen(++(argv[0]),"a")) == NULL) {
            fprintf(stderr,"Unable to open file '%s'\n", argv[0]);
            fprintf(stderr,"%s: %s\n", argv[0], strerror(errno));
            exit(-1);
        }
        break;
    case 't':
        if ((logfile = fopen(++(argv[0]),"a")) == NULL) {
            fprintf(stderr,"Unable to open file '%s'\n", argv[0]);
            fprintf(stderr,"%s: %s\n", argv[0], strerror(errno));
            exit(-1);
        }
        break;
    }
}

2048,OCI_HTYPE_ENV);
}

break;
default:
    fprintf(stderr,"Invalid Option: %c\n", argv[0][0]);
    usage();
    break;
}

/* Do some initialization and establish connection with the database */

SQLinit();

/* May want to add some triggering mechanism here */

time(&tim);
fprintf(logfile, "Begin Execution at %s\n\n", ctime(&tim));
fprintf(rep, "Begin Executing this Stream at %s\n\n", ctime(&tim));
/* Get the next statement and start processing it */

while ((retcode = get_statement()) > 0) {

    switch (retcode) {

        /* If this is a comment, skips it */
        case COMMENT:
            /*if (end_flag) {
                end_flag = 0; /* reset query end flag */
                /* save the comment so that we can print it out later on */
                /* strcpy(cmnt, stmt);
                break;
            }*/
            if (stmt[3]== '@') {
                pos=4;
                strcpy(qnp,qn);
                while (stmt[pos] != ')') {
                    pos++;
                }
                pos2=0;
                pos++;
                while (stmt[pos] != '.') {
                    /*printf ("qn %d %c \n",pos2,stmt[pos]);*/
                    qn[pos2]=st mt[pos];
                    pos2++;
                    pos++;
                }
                qn[pos2] = 0;
                /* printf("found a new query: %s\n",qn); */
            }
            /* save the comment so that we can print it out later on */
            strcat(cmmt, stmt);
            break;

        /* if this is a set_row_fetch command */
        case SET_FETCHROW:
            fprintf(logfile,"Setting the number of rows to fetch to: %ld\n\n",
                   num_to_fetch);
            break;

        /* if this is a SQL statement */
        case SQL_STMT:
            /* Executes the query */
            SQLexec();

            stmt_cnt++;
            qry_cnt++;
            fflush(rep);
            fflush(logfile);
    }
}

```

```

/*
fprintf(logfile,"Statement Started at %.2f\n", s_tr_start);
fprintf(logfile,"Statement Ended at %.2f\n", s_tr_end);

fprintf(logfile,"Statement Processed in %.2f seconds.\n",
        (s_tr_end - s_tr_start));
fprintf(rep, "Query %s: Execution Time: %.2f started %.2f ended
%.2f\n",
        qn,(s_tr_end - s_tr_start)s_tr_start,s_tr_end);
fflush(rep);
fflush(logfile);*/
break;

/* Should never reach here */
default:
    fprintf(stderr, "Invalid statement type!!\n");
    SQLExit();
    break;
}

/* Get Timing for the last query */

tr_end = gettime();

fprintf(logfile,"Query Processed in %.2f seconds.\n\n",(tr_end -
s_tr_start));

/* print comments for this query that we have saved */

/* fprintf(logfile, "%s\n", cmnt); */

/* fprintf(rep, "Query %s : Execution time %.2f\n", qn,(tr_end -
s_tr_start));*/
fprintf(rep, "Query %s: Execution Time: %.2f started %.2f ended
%.2f\n",
        qn,(tr_end - s_tr_start),s_tr_start,tr_end);

time(&tim);
fprintf(logfile,"\\nEnded Executing this Stream at %s\\n",
ctime(&tim));
fprintf(logfile,"\\nStream Started at %.2f\\n", tr_start);
fprintf(logfile,"Stream Ended at %.2f\\n", tr_end);
fprintf(logfile,"Stream Processed in %.2f seconds\\n\\n",(tr_end -
tr_start));

fprintf(rep,"\\nEnded Executing this Stream at %s\\n", ctime(&tim));
fprintf(rep,"\\nStream Started at %.2f\\n", tr_start);
fprintf(rep,"Stream Ended at %.2f\\n", tr_end);
fprintf(rep,"Stream Processed in %.2f seconds\\n\\n",
        (tr_end - tr_start));

fprintf(logfile, "\\nSQL statements processed: %d\\n", stmt_cnt);
/*fprintf(logfile, "Queries processed: %d\\n", qry_cnt);*/

fflush(rep);
fflush(logfile);

/* Close the query template file */

fclose(qtemp);

/* Disconnect from ORACLE. */

SQLExit();
exit(0);
}

/* SQLInit(): Perform initialization tasks. */
/*
Logs on to Oracle, opens some files and open a cursor for
*/
/*
later use.
*/
void SQLInit() {

int i;

/* preallocate MAX_PREALLOC members of the dlist array
*/
/* initializes others to NULL so that we can determine who to free
later */

for (i=0; i<MAX_SEL_LIST; i++) {
    if (i < MAX_PREALLOC) {
        dlist[i] = (dltype *) memalloc (sizeof(dltype));
        dlist[i]->defhdl = NULL;
        /* OCIAlloc(curq,&(dlist[i]->defhdl),OCI_HTYPE_DEFINE);
        */
    }
    else
        dlist[i] = NULL;
}

/* Connect to ORACLE. Program will call sql_error()
   /* if an error occurs in connecting to the default database. */

(void) OCIInitialize(OCI_DEFAULT,(dvoid *)0,0,0,0);

if((status=OCIEnvInit((OCIEnv
***)&tpcenv,OCI_DEFAULT,0,(dvoid ***)0)) !=

OCI_SUCCESS)
    sql_error(tpcenv, status, 0);

OCIAlloc(tpcenv,&errhp,OCI_HTYPE_ERROR);
OCIAlloc(tpcenv,&curq,OCI_HTYPE_STMT);
OCIAlloc(tpcenv,&cur_dml,OCI_HTYPE_STMT);
OCIAlloc(tpcenv,&cur_ddl,OCI_HTYPE_STMT);
OCIAlloc(tpcenv,&tpcsvc,OCI_HTYPE_SVCCTX);
OCIAlloc(tpcenv,&tpcsrv,OCI_HTYPE_SERVER);
OCIAlloc(tpcenv,&tpcusr,OCI_HTYPE_SESSION);

/* get username and password */

passwd = strchr(logname, '/');
*passwd = '\\0';
passwd++;

if ((status = OCIServerAttach(tpcsrv,errhp,(text
*)0,0,OCI_DEFAULT)) != OCI_SUCCESS)
    sql_error(errhp,status,1);

OCIAsSet(tpcsvc,OCI_HTYPE_SVCCTX,tpcsrv,0,OCI_ATTR_SER
VER,errhp);

OCIAsSet(tpcusr,OCI_HTYPE_SESSION,logname,strlen(logname),O
CI_ATTR_USERNAME,
errhp);

OCIAsSet(tpcusr,OCI_HTYPE_SESSION,passwd,strlen(passwd),OCI
_ATTR_PASSWORD,
errhp);

if ((status = OCISessionBegin(tpcsvc, errhp, tpcusr,
OCL_CRED_RDBMS,
OCI_DEFAULT)) !=

OCI_SUCCESS)
    sql_error(errhp,status,1);
}

```

```

OCIaset(tpcsvc,OCI_HTYPE_SVCCTX,tpcurl,0,OCI_ATTR_SESS
ION,errhp);

/*
 if ((status=OCILogon((OCIEnv *)tpcenv,(OCIError
*)errhp,(OCISvcCtx *)tpcsvc,
                      (text *)logname, strlen(logname), (text
*)passwd,
                      strlen(passwd), (text *) 0, 0)) !=

OCI_SUCCESS)
    sql_error(errhp, status, 1);
*/
printf("\nConnected to ORACLE as user: %s\n\n", logname);

}

/* SQLexec() Executes the SQL statement. */
/* Parse the SQL statement. */
/* If DDL or DML statements, execute right away. */
/* Else describe and define select list outputs, */
/* execute and fetch results. */

void SQLexec()
{
    int i;
    ub2 stmttyp = OCI_STMT_SELECT; /* default is a SELECT
statement */

/* Clause 5.3.6.2: QI(i,s) is the time between the first character */
/*          of this query text is submitted and the first */
/*          character of the next query text is submitted. */

if (qry_cnt) {
    time(&tim);
    s_tr_end = gettime();
    fprintf(logfile,"Query Processed in %.2f seconds.\n\n",
(s_tr_end - s_tr_start));

/* print comments for this query that we have saved */

/* fprintf(logfile, "%s\n", cmnt); */

/*fprintf(rep, "Query %s : Execution time %.2f\n", qnp,(s_tr_end
- s_tr_start));*/
    fprintf(rep, "Query %s: Execution Time: %.2f started %.2f ended
%.2f\n",
qnp,(s_tr_end - s_tr_start),s_tr_start,s_tr_end);

/* Let's fflush stuff so that we can see what's going on */

fflush(logfile);
fflush(rep);
}
else
    tr_start = gettime();

s_tr_start = gettime();

/* prepare the statement */

if ((status = OCISstmtPrepare(curq, errhp, (text*) stmt, (ub4)
strlen(stmt),
                           OCI_NTV_SYNTAX,
                           OCI_DEFAULT)) != OCI_SUCCESS)
    sql_error(errhp,status,1);

/* Prints the query text and comment to the logfile */

fprintf(logfile, "\n%s\n", cmnt);
cmnt[0]=0;
fprintf(logfile, "\n%s\n", stmt);

/* if this is a DDL or DML statement, execute it right away */
/* only worries about SELECT statements right now, cannot */
/* execute a stored PL/SQL procedure in this version */

OCIaget(curq,OCI_HTYPE_STMT,&stmttyp,NULL,OCI_ATTR_S
TMT_TYPE,errhp);

if (stmttyp != OCI_STMT_SELECT) {
    OCIexec(tpcsvc,curq,errhp,1);
    return;
}

/* otherwise, this is a select statement */
/* Describe and define output variables */

/* first let's execute it to get the select -list definition */

OCIaset(curq, OCI_HTYPE_STMT, &pfmem, 0,
OCI_ATTR_PREFETCH_MEMORY, errhp);

OCIexec(tpcsvc,curq,errhp,0);

num_sel_list = define_output_variables();

/* Executes the query and fetches the rows */

(void) process_select_list(num_sel_list);

/* Need to get the number of rows fetched first */
/* since the following statements will screw it up */

OCIaget(curq,OCI_HTYPE_STMT,&rows_ret,NULL,OCI_ATTR_
ROW_COUNT,errhp);

/* To control memory usage, let's free up the extra dlist entries */
/* that we have allocated. */

i=MAX_PREALLOC;
while(dlist[i] != NULL) {
    free(dlist[i]);
    dlist[i+1] = NULL;
}

/* reset set_fetchrows */

num_to_fetch = -1;

}

void SQLexit()
{
    int i;

    OCIlogoff(tpcsvc,errhp);
    OCIhfree(tpcenv,OCI_HTYPE_STMT);
    OCIhfree(tpcsvc,OCI_HTYPE_SVCCTX);
    OCIhfree(tpcurl,OCI_HTYPE_SERVER);
    OCIhfree(tpcurl,OCI_HTYPE_SESSION);

    /* free all memory */
}

```

```

for (i=0; i<MAX_SEL_LIST; i++) {
    if (dlist[i] != NULL) {
        free(dlist[i]);
    }
}

/* Flush all output */

fflush(rep);
fflush(logfile);

}

/* define_output_variables(): Describe and define select -list items
for */
/*
     a query statement.          */
/*
     Returns the number of select-list items   */
/*
     for this query.           */

int define_output_variables()
{
    int i;
    int retflag = 0;

    for (i=0; i<MAX_SEL_LIST; i++) {

        slist[i].buflen = MAX_COLNAME_SIZE;

        if (OCIPParamGet(curq, OCI_HTYPE_STMT, errhp, (dvoid **) &tpcpar,
                         POS(i)) != OCI_SUCCESS)
            break;

        /* dsize and nullok fields of dlist not used */

        OCIaget(tpcpar, OCI_DTYPE_PARAM, &(slist[i].dbsize),
                NULL, OCI_ATTR_DATA_SIZE, errhp);
        OCIaget(tpcpar, OCI_DTYPE_PARAM, &(slist[i].dbtype),
                NULL, OCI_ATTR_DATA_TYPE, errhp);
        OCIaget(tpcpar, OCI_DTYPE_PARAM, &(slist[i].buf),
                &(slist[i].buflen), OCI_ATTR_NAME, errhp);
        OCIaget(tpcpar, OCI_DTYPE_PARAM, &(slist[i].precision),
                NULL, OCI_ATTR_PRECISION, errhp);
        OCIaget(tpcpar, OCI_DTYPE_PARAM, &(slist[i].scale),
                NULL, OCI_ATTR_SCALE, errhp);

        /* For formatting purpose, remove trailing blanks in select-list
         name. */

        /*
        if (slist[i].buflen < MAX_COLNAME_SIZE)
            (slist[i].buf)[slist[i].buflen] = '\0';
        */
        /* Well, we need to allocate for entries for dlist */

        if (i >= MAX_PREALLOC) {
            dlist[i] = (dltype *) memalloc(sizeof(dltype));
            dlist[i]->defhdl = NULL;
        }

        /* Let's check the sizes and types for this select list item */

        switch (slist[i].dbtype) {

        case OCI_TYPECODE_NUMBER:
            /* The odescri will not give a good estimate to the scale if */

            /* no scale was given in the Oracle table definition.      */

            #ifdef HAVE_SCALE
                if (slist[i].scale != 0) {
                    defbuf = (double *) dlist[i]->fbuf;
                    deflen = FLT;
                    deftype = OCI_TYPECODE_DOUBLE;
                    slist[i].dbtype = OCI_TYPECODE_DOUBLE;
                } else {
                    defbuf = (int *) dlist[i]->ibuf;
                    deflen = INT;
                    deftype = OCI_TYPECODE_INTEGER;
                    slist[i].dbtype = OCI_TYPECODE_INTEGER;
                }
            #else
                defbuf = (double *) dlist[i]->fbuf;
                deflen = FLT;
                deftype = OCI_TYPECODE_FLOAT;
                slist[i].dbtype = OCI_TYPECODE_FLOAT;
            #endif /* HAVE_SCALE */
        }

        break;
    }

    default:
        /* default is character string */

        defbuf = (char **) dlist[i]->sbuf;
        deflen = MAX_STR_LEN;
        deftype = SQLT_STR;
        /*
        deftype = OCI_TYPECODE_CHAR; */
        break;
    }

    /* Define the column */

    if ((status=OCIDefineByPos(curq,&(dlist[i]->defhdl),errhp,POS(i),
                               defbuf,deflen,deftype,NULL,
                               dlist[i]->rlen,NULL,OCI_DEFAULT))!=OCI_SUCCESS)
        sql_error(errhp,status,1);
    return i;
}

/* process_select_list(): Fetch rows from a query. */

void process_select_list(num)
    int num;      /* number of select list items */
{
    int i,j;
    int ntf;
    int num_so_far;
    sword stats = OCI_SUCCESS;

    /* Print the headers for the query execution result */

    print_header(num);

    /* See if we need to limit the rows to fetch */

    ntf = (num_to_fetch >= 0) ? num_to_fetch : MAX_ARRAY;

    /* Fetch the rows and print them out */

    if ((ntf > MAX_ARRAY) || (num_to_fetch == -1)) {

```

```

stats = OCIStmtFetch(curq, errhp, MAX_ARRAY,
OCI_FETCH_NEXT, OCI_DEFAULT);

OCILaget(curq,OCI_HTYPE_STMT,&rows_ret,NULL,OCI_ATTR_
ROW_COUNT,errhp);

print_rows(num,rows_ret);

/* To avoid 1022 from OFEN */
/* More rows to fetch... */

if (stats != OCI_NO_DATA) {
    if (num_to_fetch == -1) {
        while ((stats =
OCIStmtFetch(curq,errhp,MAX_ARRAY,OCI_FETCH_NEXT,
            OCI_DEFAULT)) ==
OCI_SUCCESS) {

OCILaget(curq,OCI_HTYPE_STMT,&num_so_far,NULL,
            OCI_ATTR_ROW_COUNT,errhp);
    print_rows(num,(num_so_far-rows_ret));
    rows_ret = num_so_far;
}
/* Print the final rows */
OCILaget(curq,OCI_HTYPE_STMT,&num_so_far,NULL
,
            OCI_ATTR_ROW_COUNT,errhp);
    print_rows(num,(num_so_far-rows_ret));
    rows_ret = num_so_far;
} else {
    ntf -= MAX_ARRAY;

    while ((stats = OCIStmtFetch(curq,errhp,
((ntf>MAX_ARRAY) ? MAX_ARRAY:ntf),
OCI_FETCH_NEXT, OCI_DEFAULT)) ==
            OCI_SUCCESS) {
        ntf -= MAX_ARRAY;

OCILaget(curq,OCI_HTYPE_STMT,&num_so_far,NULL,
            OCI_ATTR_ROW_COUNT,errhp);
    print_rows(num,(num_so_far-rows_ret));
    rows_ret = num_so_far;
    if (ntf <= 0) break;
}
OCILaget(curq,OCI_HTYPE_STMT,&num_so_far,NULL
,
            OCI_ATTR_ROW_COUNT,errhp);
    print_rows(num,(num_so_far-rows_ret));
    rows_ret = num_so_far;
}
} else {
    OCIStmtFetch(curq, errhp, ntf, OCI_FETCH_NEXT,
    OCI_DEFAULT);

OCILaget(curq,OCI_HTYPE_STMT,&rows_ret,NULL,OCI_ATTR_
ROW_COUNT,errhp);
    print_rows(num,rows_ret);
}

fprintf(logfile,"\\n\\n%d row%c processed.\\n", rows_ret,
    rows_ret == 1 ? '\\0' : 's');

}

int get_statement()
{
    char line[128];
    char *pos, *str;

    /* Reset statement buffer */

    stmt[0] = '\\0';

    while (fgets(line, 127, qtemp) != NULL) {

        /* skip blank lines */
        if (line[0] == '\\n')
            continue;

        /* remove blanks */
        str = line;

        while (*str == ' ') str++;

        /* Let's get the line together first */
        strcat(stmt, str);

        /* if this is a comment line */
        if ((str[0] == '-') && (str[1] == '-'))
            return COMMENT;

        /* see if this is a set_fetchrows line */
        if (strncmp(str, "set_fetchrows", 13) == 0) {
            pos = strchr(str, ':');
            *pos = '\\0';
            pos = strchr(str, '=');
            num_to_fetch = atoi(++pos);
            return SET_FETCHROW;
        }

        /* if this is the end of the current statement */
        if ((pos = strchr(stmt, ';')) != NULL) {
            *pos = '\\0';
            return SQL_STMT;
        }
        return END_OF_FILE;
    }

    /* memalloc(): Allocates memory, exit program if we have a
problem. */

    void *memalloc(size)
        int size;
    {

        void *tmp;

        if ((tmp = (void *) malloc(size)) == NULL) {
            fprintf(stderr, "Error in malloc\\n");
            SQLExit();
            return NULL;      /* should never reach here */
        } else {
            return tmp;
        }
    }

    void print_header(nsel)
        int nsel;           /* Number of select list items */

```

```

{
    }

int i, diff;
char colname[MAX_COLNAME_SIZE];
int len = 0; /* Running column length */
int cwdid = 0;

fprintf(logfile, "\n");
for (i=0; i<nse1; i++) {
    /* extract the column name */

    strncpy((char *)colname, (char *)slist[i].buf, slist[i].buflen);
    colname[slist[i].buflen] = '\0';

    /* format the output a little */

    cwdid = MAX(slist[i].dbsize, slist[i].buflen);

    /* do a little bit of formatting */

    if (cwdid > 80) {
        fprintf(logfile, "\n");
        len = 0;
    } else if ((len += cwdid) > 80) {
        fprintf(logfile, "\n");
        len = cwdid;
    }
#ifndef FORMAT1
    if ((slist[i].dbtype == INT_TYPE) || (slist[i].dbtype ==
    FLT_TYPE))
        fprintf(logfile, "%*s ", cwdid, slist[i].buf);
    else /* string type */
        fprintf(logfile, "%*s ", - cwdid, slist[i].buf);
#else
    fprintf(logfile, "%*s ", - cwdid, colname);
#endif /* FORMAT1 */
}

fprintf(logfile, "\n");
}

void print_rows(ncol, nrow)
    int ncol;
    int nrow;
{
    int i,j;
    int len;
    int diff;
    int cwdid;

    for (i=0;i<nrow;i++) {

        len = 0;

        for (j=0;j<ncol;j++) {

            cwdid = MAX(slist[j].dbsize, slist[j].buflen);

            /* do a little bit of formatting */

            if (cwdid > 80) {
                fprintf(logfile, "\n");
                len = 0;
            } else if ((len += cwdid) > 80) {
                fprintf(logfile, "\n");
                len = cwdid;
            }

switch(slist[j].dbtype) {
    case INT_TYPE:
#ifndef HAVE_SCALE
        fprintf(logfile, "%*ld", cwdid, (dlist[j]->ibuf)[i]);
        break;
#endif /* HAVE_SCALE */
    case FLT_TYPE:
#ifndef FORMAT1
        fprintf(logfile, "%*.2f ", cwdid, (dlist[j]->fbuf)[i]);
#else
        fprintf(logfile, "%*.2f ", - cwdid, (dlist[j]->fbuf)[i]);
#endif /* FORMAT1 */
        break;
    default:
        fprintf(logfile, "%*s ", -( cwdid), (dlist[j]->sbuf)[i]);
        break;
}
}
fprintf(logfile, "\n");
}

/* remove_newline(): Remove newline character from str. */

void remove_newline(str)
    char *str;
{
    char *p;

    while ((p = strchr(str, '\n')) != NULL)
        *p = ' ';
}

```

F. 5 qexecpl.h

```

/*
 * $Header: qexecpl.h 13-nov-2001.17:52:35 mpoess Exp $
 */

/* Copyright (c) 1999, 2001, Oracle Corporation. All rights
reserved. */

/* NOTE: See 'header_template.doc' in the 'doc' dve under the
'forms'
directory for the header file template that includes instructions.
*/
/*
  NAME
  qexecpl.h

  DESCRIPTION
  SQL statement execution front-end header file.

  PUBLIC FUNCTION(S)
  <list of external functions declared/defined - with one-line
descriptions>

  PRIVATE FUNCTION(S)
  <list of static functions defined in .c file - with one-line
descriptions>

  EXAMPLES

```

NOTES

<other useful comments, qualifications, etc.>

MODIFIED (MM/DD/YY)

mpoess 11/13/01 - change DOP to 84 for DML and DDL
 mpoess 02/22/01 - add linux changes
 mpoess 08/05/99 - make compile
 mpoess 07/15/99 - Creation
 mpoess 07/15/99 - Creation

*/

/*

```
#ifndef S_ORACLE
# include <s.h>
#endif
*/
```

```
#ifndef QSTREAMPL_H
```

```
#define QSTREAMPL_H
```

```
#include <stdio.h>
#include <string.h>
#include <sys/param.h>
#include <sys/types.h>
#include <time.h>
#include <errno.h>
#include <math.h>
```

```
#include <oratypes.h>
```

```
#include <oratypes.h>
```

```
#ifndef OCIDFN
#include <ocidfn.h>
#endif /* OCIDFN */
```

```
#ifndef OCI_ORACLE
#include <oci.h>
#endif /* OCI_ORACLE */
/*
```

```
#ifdef __STDC__
#include <ociapr.h>
#else
#include <ocikpr.h>
#endif /* __STDC__ */
```

/* some basic definitions */

```
#define UNAME_LEN 64
#define MAX_FILE_PATH_LEN 128
```

```
#ifndef TRUE
#define TRUE 1
#endif /* TRUE */
```

```
#ifndef FALSE
#define FALSE 1
#endif /* FALSE */
```

```
#ifndef LINUX
#define MAX(x,y) ((x >= y) ? x : y)
#define MIN(x,y) ((x <= y) ? x : y)
#endif
```

/* defines and typedefs for parsing */

```
#define CRT_TBL_1
#define INS_STMT 3
#define SEL_STMT 4
#define UPD_STMT 5
#define DRP_VIEW 7
```

```
#define DRP_TBL_8
#define DEL_STMT 9
#define CRT_VIEW 10
```

/* defines and typedefs for query description */

```
#define MAX_COLNAME_SIZE 32 /* Maximum length of
Column name */
#define MAX_SEL_LIST 16 /* Maximum items on a select list
*/
```

```
#define END_OF_LIST 1007 /* Error code when we reach the
end of the */
/* select list. */
```

/* types for describe */

```
#define CHAR_TYPE 1
#define NUM_TYPE 2
#define INT_TYPE 3
#define FLT_TYPE 4
#define STR_TYPE 5
#define DATE_TYPE 12
```

```
#define NUMWIDTH 16 /* Width of the numeric fields */
```

```
#define POS(i) (i+1) /* The position is 1...n instead */
#define IND(i) (i-1) /* of 0..n-1 as in an array. */
```

```
typedef struct des
{
    ub2 dbsize;
    ub4 buflen;
    /* sb2 dsize; */
    sb4 scale;
    /* sb2 nullok; */
    OCITypeCode dbtype;
    /* text buf[MAX_COLNAME_SIZE]; */
    text *buf;
    ub1 precision;
} sltype;
```

/* defines and typedefs for query select list definition */

```
#define MAX_ARRAY 50 /* Maximum array size for array
fetch */
#define PFMEMSIZE 65536 /* Memory size of prefetch buffer
*/
```

```
#define MAX_STR_LEN 256 /* Maximum size for string
variables */
#define MAX_PREALLOC 8 /* Maximum number of
preallocated select list */
/* definitions. */
```

```
#define INT sizeof(long)
#define STR sizeof(char)
#define FLT sizeof(double)
```

```
#define FLTP (double *)
#define INTP (long *)
#define STRP (char **)
```

```
typedef struct def
{
    long ibuf[MAX_ARRAY];
    double fbuf[MAX_ARRAY];
    char sbuf[MAX_ARRAY][MAX_STR_LEN];
    ub2 rlen[MAX_ARRAY]; /* return length */
}
```

```

OCIDefine *defhdl;
} dltpe;

extern int errno;

#define SQL_LEN 2048

#ifndef NULL
#define NULL 0
#endif

#ifndef NULLP
#define NULLP (void *)NULL
#endif /* NULLP */

#ifndef DISCARD
#define DISCARD (void)
#endif

#ifndef sword
#define sword int
#endif

#ifndef ub1
#define ub1 unsigned char
#endif

#define NA -1 /* ANSI SQL NULL */
#define VER7 2
#define NOT_SERIALIZABLE 8177 /* ORA-08177: transaction
not serializable */

#define ADR(object) ((ub1 *)&(object))
#define SIZ(object) ((sword)sizeof(object))
#define SID(sid) ((sid == -1) ? 0 : sid)

/* For get_statement */

#define END_OF_FILE -1
#define COMMENT 1
#define SQL_STMT 2
#define SET_FETCHROW 3

#define OCIalloc(envh,hndl,htyp) \
if((status=OCIHandleAlloc((dvoid *)envh,(dvoid \
**)hndl,htyp,0,(dvoid **)0))!=OCI_SUCCESS) \
    sql_error(envh,status,0); \
else \
    DISCARD 0

#define OCIhfree(hndl,htyp) \
if((status=OCIHandleFree((dvoid *)hndl,htyp))== \
OCI_SUCCESS) \
    fprintf(stderr, "Error freeing handle of type %d\n", htyp)

#define OCIaget(hndl,htyp,attp,size,atyp,errh) \
if((status=OCIAttrGet((dvoid *)hndl,htyp,(dvoid *)attp,(dvoid \
*)size,atyp,errh)) != OCI_SUCCESS) \
    sql_error(errh,status,1); \
else \
    DISCARD 0

#define OCIaset(hndl,htyp,attp,size,atyp,errh) \
if((status=OCIAttrSet((dvoid *)hndl,htyp,(dvoid \
*)attp,size,atyp,errh)) != OCI_SUCCESS) \
    sql_error(errh,status,1); \
else \
    DISCARD 0

#define OCIsexec(svch,stmh,errh,iter) \
if((status=OCIStmtExecute(svch,stmh,errh,iter,0,NULL,NULL,OCI \
_DEFAULT)) != OCI_SUCCESS) \
    sql_error(errh,status,1); \
else \
    DISCARD 0

#define ISOTXT "alter session set isolation_level = serializable"
#define PDMLTXT "alter session force parallel dml parallel (degree
84)"
#define PDDLTXT "alter session force parallel ddl parallel (degree
84)"

#endif /* QSTREAMPL_H */


```

F. 6 runTPCHall

```

#!/bin/ksh
. $KIT_DIR/env

ECHO=echo

sqlplus=$ORACLE_HOME/bin/sqlplus
GTIME=${KIT_DIR}/utils/gtime

RUN_ID_FILE=${KIT_DIR}/audit/r_id

if [ ! -f $RUN_ID_FILE ]
then
    echo "0" > $RUN_ID_FILE
fi

RUN_ID=`cat $RUN_ID_FILE`
RUN_ID=`expr $RUN_ID + 1`
echo $RUN_ID > $RUN_ID_FILE

OUT_DIR=${KIT_DIR}/audit/tests/${RUN_ID}
if [ ! -d $OUT_DIR ]
then
    mkdir $OUT_DIR
fi

SCRIPT_LOG_FILE=${OUT_DIR}/main.out
RDB_TABLES=${OUT_DIR}/rdbtablest
FIRST_TEN=${OUT_DIR}/firstten
LD1DBCRE=${OUT_DIR}/Ld1dbcre
LD2SCTSO=${OUT_DIR}/Ld2sctso
LD3DAPOP=${OUT_DIR}/Ld3dapop
LD4IXCRE=${OUT_DIR}/Ld4ixcre
LD5ANLYZ=${OUT_DIR}/Ld5anlyz
DAT_FILE=/dbms/oracle10i/kit/audit/10TB.dat

echo Start TPC-H Benchmark SEQUENCE NUMBER: $RUN_ID >
$SCRIPT_LOG_FILE
echo >> $SCRIPT_LOG_FILE
echo "Starting a new Oracle log file:
$ORACLE_HOME/rdbms/log/alert_${ORACLE_SID}.log" >>
$SCRIPT_LOG_FILE
echo >> $SCRIPT_LOG_FILE

mv $ORACLE_HOME/rdbms/log/alert_${ORACLE_SID}.log
$ORACLE_HOME/rdbms/log/alert_${ORACLE_SID}.log.preAudit.$RUN_ID
```

```

touch $ORACLE_HOME/rdbms/log/alert_${ORACLE_SID}.log

echo "Start: load database `date`" >> $SCRIPT_LOG_FILE
bumpx.pl -s -x -o ${DAT_FILE} -p dbcre > $LD1_DBCRE
bumpx.pl -s -x -o ${DAT_FILE} -p sctso > $LD2SCTSO
STIME=`$GTIME`
echo "Start: timed load portion `date`" >> $SCRIPT_LOG_FILE
${KIT_DIR}/audit/tstart >> $SCRIPT_LOG_FILE
bumpx.pl -s -x -o ${DAT_FILE} -p dapop > $LD3DAPOP
bumpx.pl -s -x -o ${DAT_FILE} -p ixcre > $LD4IXCRE
bumpx.pl -s -x -o ${DAT_FILE} -p anlyz > $LD5ANLYZ
${KIT_DIR}/audit/tshut
${KIT_DIR}/audit/tstart
${KIT_DIR}/audit/ckpnt.sh
echo "End: timed load portion `date`" >> $SCRIPT_LOG_FILE

${KIT_DIR}/audit/gen_seed.sh ${KIT_DIR}/audit/seed
echo Generated seed: `cat ${KIT_DIR}/audit/seed` >>
$SCRIPT_LOG_FILE

echo "Start: dbtables.sql and count.sql" >> $SCRIPT_LOG_FILE
$sqlplus ${DATABASE_USER} @${KIT_DIR}/audit/dbtables >
${RDB_TABLES} 2>&1
$sqlplus ${DATABASE_USER} @${KIT_DIR}/audit/firstten >
${FIRST_TEN} 2>&1
echo "End: dbtables.sql and count.sql `date`" >>
$SCRIPT_LOG_FILE

${KIT_DIR}/audit/tshut >> $SCRIPT_LOG_FILE
${KIT_DIR}/audit/tstart >> $SCRIPT_LOG_FILE
${KIT_DIR}/audit/ckpnt.sh
runTPCHpt ${SCALE_FACTOR} 1 ${RUN_ID}

${KIT_DIR}/audit/tshut >> $SCRIPT_LOG_FILE
${KIT_DIR}/audit/tstart >> $SCRIPT_LOG_FILE
${KIT_DIR}/audit/ckpnt.sh
runTPCHpt ${SCALE_FACTOR} 2 ${RUN_ID}

sleep 600
# call the auditor: don't tshut >> $SCRIPT_LOG_FILE

cp $ORACLE_HOME/rdbms/log/alert_${ORACLE_SID}.log
$OUT_DIR

echo "End TPC-H Benchmark SEQUENCE NUMBER: ${RUN_ID}
`date`" >> $SCRIPT_LOG_FILE

```

F. 7 runTPCHpt

```

#!/bin/ksh
. ${KIT_DIR}/env
#set -x
#ECHO=/bin/echo
SCRIPT_DIR=${KIT_DIR}/scripts
UPD_DIR=${KIT_DIR}/update
SRC_DIR=${KIT_DIR}/utils
QRY_DIR=${KIT_DIR}/queries # this is the location of the query
template file
QGEN_DIR=${KIT_DIR}/dbgen
QGEN=${QGEN_DIR}/qgen
QEXEC=${SRC_DIR}

DSS_QUERY=${KIT_DIR}/queries
export DSS_QUERY

UPD_SQL=${UPD_DIR}/sql
UPD_SPT=${UPD_DIR}/scripts
UPD_SRC=${UPD_DIR}/source

```

```

UPD_DAT=${UPD_DIR}/data
TPCD_BIN=${KIT_DIR}/audit/bin
GTIME=${SRC_DIR}/gtime
SEED_FILE=${KIT_DIR}/audit/seed
DF=/dev/null
HID=1
INTERVAL=60
COUNT=1200
# The defaults
QPROG=${QEXEC}/qexec
usage () {
echo ""
echo "Usage: $0 [-p <program for query stream>] [-u1 <program for
UF1>]"
echo "      [-u2 <program for UF2>] [-o] [-s] [-h] [-u
<user/password>]"
echo "      <scale factor> <run_number>"
echo ""
echo "scale factor : The scale factor of the run."
echo "update |ism : The parallelism to use for the UFs."
echo ""
echo "-p <program> : Program for Query Stream."
echo "      Default is $QPROG."
echo "-u1 <program> : Program for UF1."
echo "      Default is $U1PROG."
echo "-u2 <program> : Program for UF2."
echo "      Default is $U2PROG."
echo "-o : Collect Oracle statistics."
echo "-s : Collect System statistics."
echo "-u <user/passwd> : User/Password. Default is tpch/tpch."
echo "-h : Displays this message."
}
set -- `getopt "p:u1:u2:osu:h" "$@"` || usage

while :
do
  case "$1" in
    -u1) shift; U1PROG=$1;;
    -u2) shift; U2PROG=$1;;
    -p) shift; QPROG=$1;;
    # not needed ? -o) OSTAT=1;;
    # not needed ? -s) SSTAT=1;;
    -h) usage; exit 0;;
    -) shift; break;;
    esac
    shift;
done

if [ "$#" -ne "3" ]
then
  usage
  exit 1
fi

SF=$1
PARA=$2
RUN_ID=$3

OUT_DIR=${KIT_DIR}/audit/tests/${RUN_ID}
if [ ! -d $OUT_DIR ]
then
  mkdir $OUT_DIR

```

```

fi

# Execute UF2

UF2_START=`${GTIME}`
E2DATE=`date`

echo "End Query Part `\$GTIME` , \$E2DATE" >>
$SCRIPT_LOG_FILE
echo "" >> $SCRIPT_LOG_FILE

echo "Start UF2 \$UF2_START, `date`" >> $SCRIPT_LOG_FILE
${ECHO} ${UPD_SPT}/runuf2.sh ${UF_SET} >> $UF2_LOG
2>&1
UF2_END=`${GTIME}`
END=`${GTIME}`
EDATE=`date`

UF2_TIME=`echo \$UF2_END - \$UF2_START | bc`
echo UF2: Execution Time: \$UF2_TIME >> ${TPCD_RPT_FILE}
echo Start Time: \$UF2_START, \$E2DATE >>
${TPCD_RPT_FILE}
echo End Time: \$UF2_END, \$EDATE >> ${TPCD_RPT_FILE}

echo "End UF2 \$UF2_END, \$EDATE" >> $SCRIPT_LOG_FILE
echo UF2: Execution Time: \$UF2_TIME >> $SCRIPT_LOG_FILE
echo >> $SCRIPT_LOG_FILE

echo "End TPC-H Power Test- RUN:${PARA} SEQUENCE:${RUN_ID}"
SEQUENCE:${RUN_ID}, $END, \$EDATE" >>
$SCRIPT_LOG_FILE
MEA_INT=`echo \$END - \$START | bc`
echo "Elapsed Time for TPC-H Power Test - RUN:${PARA} "
SEQUENCE:${RUN_ID} is \$MEA_INT" >>
$SCRIPT_LOG_FILE
echo >> $SCRIPT_LOG_FILE

${KIT_DIR}/audit/abridge.pl ${TPCD_LOG_FILE}

i=$START_SET
PSEED=`cat $SEED_FILE`

while [ $i -le $STOP_SET ]; do
  TPCD_LOG_FILE=${TPCD_LOG}/mt${RUN_ID}_${i}.log
  TPCD_RPT_FILE=${TPCD_RPT}/mt${RUN_ID}_${i}.rpt
  QUERY_PARAMETER=${TPCD_LOG}/qp${PARA}.
${i}
  QRY_FILE=${TPCD_RPT}/qtemp.${PARA}s${i}
  PSEED=`expr $PSEED + 1`
  ${QGEN} -c -r ${PSEED} -p ${i} -s ${SF} -1
  QUERY_PARAMETER > ${QRY_FILE}

  i=`expr $i + 1`
done

TH_START_D=`date`
TH_START_T=`${GTIME}`
echo >> $SCRIPT_LOG_FILE

rm -f /tmp/th_pipe1
mknod /tmp/th_pipe1 p
rm -f /tmp/th_pipe2
mknod /tmp/th_pipe2 p
i=$START_SET

echo "Start Throughput Test - RUN:${PARA} "
SEQUENCE:${RUN_ID} \$TH_START_T, \$TH_START_D" >>
$SCRIPT_LOG_FILE

# starts a script to count the streams during the throughput run

```

```

(scnt.sh $PARA $RUN_ID > $STREAM_COUNT_LOG &

while [ $i -le $STOP_SET ]; do
  M_SDATE=`date`
  M_STIME=`${GTIME}`
  TPCD_LOG_FILE=${TPCD_LOG}/m${PARA}s${i}
  TPCD_RPT_FILE=${TPCD_RPT}/m${PARA}s${i}.int
er
  echo "Start Query Stream $i $M_STIME, ${M_SDATE}" >>
$SCRIPT_LOG_FILE
  QRY_FILE=${TPCD_RPT}/qtemp.${PARA}s${i}
  ${QPROG} ${DATABASE_USER} q${QRY_FILE}
l${TPCD_LOG_FILE} r${TPCD_RPT_FILE} | grep -v "Connected
to ORACLE" >> $SCRIPT_LOG_FILE &
  i=`expr $i + 1` 
done

(${KIT_DIR}/audit/runTPCHus $RUN_ID
$START_SET_UPDATE $STOP_SET_UPDATE ${SF} $PARA
>> $SCRIPT_LOG_FILE 2>&1 &)

wait
THQ_END_T=`$GTIME`
THQ_END_D=`date`
echo End all Query Streams $THQ_END_T, $THQ_END_D >>
$SCRIPT_LOG_FILE
print >/tmp/th_pipe1
read </tmp/th_pipe2

TH_END_D=`date`
TH_END_T= ${GTIME}
echo End Update Stream ${TH_END_T}, ${TH_END_D} >>
$SCRIPT_LOG_FILE
echo >> $SCRIPT_LOG_FILE
echo "End Throughput Test ${TH_END_T}, ${TH_END_D}" >>
$SCRIPT_LOG_FILE
echo Execution Time Throughput Test: `echo ${TH_END_T} -
${TH_START_T} | bc` >> $SCRIPT_LOG_FILE

i=$START_SET
while [ $i -le $STOP_SET ]; do
  TPCD_LOG_FILE=${TPCD_LOG}/m${PARA}s${i}
  ${KIT_DIR}/audit/abridge.pl ${TPCD_LOG_FILE}
  i=`expr $i + 1` 
done
PIDS=`ps -fu oracle | grep scnt.sh | grep -v grep | awk '{print $2}'` 
kill -9 $PIDS
#calculate the metric
#analyze_streams.pl -f p -n $RUN_ID >
${TPCD_RPT}/tpch_metric.${RUN_ID}.${HID}.rpt

# Execute UF1
UF1_LOG=${OUT_DIR}/m${PARA}s${j}rf1
UF2_LOG=${OUT_DIR}/m${PARA}s${j}rf2
RPT_FILE=${OUT_DIR}/m${PARA}s${j}inter
SDATE=`date`
UF1_START=`$GTIME`
echo "Start UF1-${j} at ${UF1_START}, ${SDATE}" >>
${RPT_FILE}
echo "End UF1-${j} at ${UF1_END}, ${EDATE}" >>
${RPT_FILE}
echo UF1-${j} Execution Time: `echo ${UF1_END} -
${UF1_START} | bc` >> ${RPT_FILE}

# Execute UF2
UF2_START=`$GTIME`
echo "Start UF2-${j} at ${UF2_START}, ${SDATE}" >>
${RPT_FILE}
UF2_END=`$GTIME`
EDATE=`date`
echo "End UF2-${j} at ${UF2_END}, ${EDATE}" >>
${RPT_FILE}
echo UF2-${j} Execution Time: `echo ${UF2_END} -
${UF2_START} | bc` >> ${RPT_FILE}

i=`expr $i + 1` 
j=`expr $j + 1` 

RUN_ID=$1
START_SET_UPDATE=$2
STOP_SET_UPDATE=$3
SF=$4
PARA=$5

OUT_DIR=${KIT_DIR}/audit/tests/${RUN_ID}
if [ ! -d $OUT_DIR ]
then
  mkdir $OUT_DIR
fi

TPCD_RPT=$OUT_DIR
SCRIPT_LOG_FILE=${OUT_DIR}/m${PARA}timing
OUT=$OUT_DIR

GTIME=${SRC_DIR}/gtme
HID=1

START=`$GTIME`
echo "Start Update Stream $START, `date`" >>
$SCRIPT_LOG_FILE
echo "" >> $SCRIPT_LOG_FILE

#waiting for all the query streams to finish first
read </tmp/th_pipe1

i=$START_SET_UPDATE
j=1
while [ $i -le $STOP_SET_UPDATE ]; do
  # Execute UF1
  UF1_LOG=${OUT_DIR}/m${PARA}s${j}rf1
  UF2_LOG=${OUT_DIR}/m${PARA}s${j}rf2
  RPT_FILE=${OUT_DIR}/m${PARA}s${j}inter
  SDATE=`date`
  UF1_START=`$GTIME`
  echo "Start UF1-${j} at ${UF1_START}, ${SDATE}" >>
  ${RPT_FILE}
  echo "End UF1-${j} at ${UF1_END}, ${EDATE}" >>
  ${RPT_FILE}
  echo UF1-${j} Execution Time: `echo ${UF1_END} -
  ${UF1_START} | bc` >> ${RPT_FILE}

  # Execute UF2
  UF2_START=`$GTIME`
  echo "Start UF2-${j} at ${UF2_START}, ${SDATE}" >>
  ${RPT_FILE}
  UF2_END=`$GTIME`
  EDATE=`date`
  echo "End UF2-${j} at ${UF2_END}, ${EDATE}" >>
  ${RPT_FILE}
  echo UF2-${j} Execution Time: `echo ${UF2_END} -
  ${UF2_START} | bc` >> ${RPT_FILE}

  i=`expr $i + 1` 
  j=`expr $j + 1` 

```

F. 8 runTPCHus

```

#!/bin/ksh
. ${KIT_DIR}/env

SCRIPT_DIR=${KIT_DIR}/scripts
SQL_DIR=${KIT_DIR}/sql
UPD_DIR=${KIT_DIR}/update
UPD_SPT=${UPD_DIR}/scripts
SRC_DIR=${KIT_DIR}/utils
QRY_DIR=${KIT_DIR}/queries # this is the location of the query
template file
QGEN_DIR=${KIT_DIR}/dbgen
QGEN=${QGEN_DIR}/qgen

DSS_QUERY=${KIT_DIR}/queries
export DSS_QUERY

```

done

```
print >/tmp/th_pipe2
```

F. 9 runuf1.sh

```
#!/bin/ksh
#
# $Header: runuf1.sh 25-oct-2001.15:56:04 mpoess Exp $
#
# runuf1.sh
#
# Copyright (c) 1999, 2001, Oracle Corporation. All rights reserved.
#
# NAME
#   runuf1.sh - <one-line expansion of the name>
#
# DESCRIPTION
#   runuf1.sh -l [<path name for reports>] -u [<uid/passwd>]
#           -p [<program>] <run_id> <scale factor> <pair number>
#           <parallelism>
#
# USAGE
#   To execute UF1.
#
# NOTES
#   <other useful comments, qualifications, etc.>
#
# MODIFIED (MM/DD/YY)
#   mpoess 10/25/01 - change default directory for update sets
#   mpoess 10/17/01 - add support for external tables
#   mpoess 08/15/99 - Creation
#   mpoess 08/15/99 - Creation
#
#
. ${KIT_DIR}/env
O=${ORACLE_HOME}
UPDATE_DIR=${KIT_DIR}/update
SCRIPT_DIR=${UPDATE_DIR}/scripts
UTILS_DIR=${KIT_DIR}/utils
LOG_DIR=${UPDATE_DIR}/log
GTIME=${UTILS_DIR}/gtime
SF=${SCALE_FACTOR}
PAR_HINT=${UPDATE_1_DOP}

LOGPATH=-
PASSWD=${DATABASE_USER}

if [ $# -lt 1 ];
then
  echo runuf1.sh setnum
  exit 1
fi
SETNUM=$1
i=1
PID=""

# perform the update function 1

START=`$GTIME`

# first create the temp tables

sqlplus /NOLOG << !
connect $PASSWD;
set timing on
set serveroutput on
set echo on
```

```
drop directory data_dir;
create directory data_dir as '/dbms/oracle10i/kit/update/update_sets';

drop table temp_l_et;
create table temp_l_et(
  l_orderkey      number ,
  l_partkey       number ,
  l_suppkey       number ,
  l_linenumber    number ,
  l_quantity      number ,
  l_extendedprice number ,
  l_discount      number ,
  l_tax           number ,
  l_returnflag    char(1),
  l_linestatus    char(1),
  l_shipdate      date ,
  l_commitdate    date ,
  l_receiptdate   date ,
  l_shipinstruct  char(25),
  l_shipmode      char(10),
  l_comment       varchar(44)
)
organization external (
  type ORACLE_LOADER
  default directory data_dir
  access parameters
  (
    records delimited by newline
    badfile 'l_et.${SETNUM}.bad'
    logfile 'l_et.${SETNUM}.log'
    fields terminated by '|'
    missing field values are null
  )
  location (
    'lineitem.tbl.u${SETNUM}'
  )
)
reject limit unlimited;

drop table temp_o_et;
create table temp_o_et(
  o_orderkey      number ,
  o_custkey       number ,
  o_orderstatus   char(1),
  o_totalprice   number ,
  o_orderdate    date ,
  o_orderpriority char(15),
  o_clerk        char(15),
  o_shippriority  number ,
  o_comment       varchar(79)
)
organization external (
  type ORACLE_LOADER
  default directory data_dir
  access parameters
  (
    records delimited by newline
    badfile 'o_et.${SETNUM}.bad'
    logfile 'o_et.${SETNUM}.log'
    fields terminated by '|'
    missing field values are null
  )
  location (
    'orders.tbl.u${SETNUM}'
  )
)
reject limit unlimited;

alter table temp_l_et parallel ${PAR_HINT};
alter table temp_o_et parallel ${PAR_HINT};
```

```

alter session force parallel dml parallel (degree ${PAR_HINT});
alter session set isolation_level = serializable;
alter session set optimizer_index_cost_adj=10;

insert into orders
select
  o_orderdate      ,
  o_orderkey       ,
  o_custkey        ,
  o_orderpriority  ,
  o_shippriority   ,
  o_clerk          ,
  o_orderstatus    ,
  o_totalprice     ,
  o_comment        ,
from temp_o_et;

insert into lineitem
select
  l_shipdate      ,
  l_orderkey       ,
  l_discount       ,
  l_extendedprice  ,
  l_suppkey        ,
  l_quantity       ,
  l_returnflag     ,
  l_partkey        ,
  l_linenumber     ,
  l_shipinstruct   ,
  l_comment        ,
from temp_l_et;

commit;

drop table temp_l_et;
drop table temp_o_et;

exit;
!

END=`$GTIME`
```

Done

echo ""

echo "Update Function 1 Set \$SETNUM done!"

echo "Elapsed Time is `echo \$END - \$START | bc`"

echo ""

F. 10 runuf2.sh

```

#!/bin/ksh
#
# $Header: runuf2.sh 25-oct-2001.15:56:05 mpoess Exp $
#
# runuf2.sh
#
# Copyright (c) 1999, 2001, Oracle Corporation. All rights reserved.
#
# NAME
#   runuf2.sh - <one-line expansion of the name>
```

```

#
# DESCRIPTION
#   runuf2.sh [-u <uid/passwd to login>] [-p <program>] <run_id>
#           <scale factor> <pair number> <parallelism>
#
# USAGE
#   To execute UF2.
#
# NOTES
#   <other useful comments, qualifications, etc.>
#
# MODIFIED (MM/DD/YY)
#   mpoess  10/25/01 - change default directory for update sets
#   mpoess  10/17/01 - add support for external tables
#   mpoess  08/15/99 - Creation
#   mpoess  08/15/99 - Creation
#
# . $KIT_DIR/env
UPDATE_DIR=${KIT_DIR}/update
SCRIPT_DIR=${UPDATE_DIR}/scripts
UTILS_DIR=${KIT_DIR}/utils
GTIME=${UTILS_DIR}/gtime
LOG_DIR=${UPDATE_DIR}/log
PAR_HINT=${UPDATE_2_DOP}
SF=${SCALE_FACTOR}
PASSWD=${DATABASE_USER}

if [ $# -lt 1 ]
then
  usage
  exit 1
fi

SETNUM=$1

i=1
PID=""

START=`$GTIME`
# first create the temp tables

sqlplus /NOLOG << !
connect $PASSWD;
set timing on
set serveroutput on
set echo on

drop directory data_dir;
create directory data_dir as '/dbms/oracle10i/kit/update/update_sets';

drop table temp_okey_et;
drop table temp_okey;

create table temp_okey_et(
  t_orderkey      number
)
organization external (
  type ORACLE_LOADER
  default directory data_dir
  access parameters
  (
    records delimited by newline
    badfile 'okey.${SETNUM}.bad'
    logfile 'okey.${SETNUM}.log'
    fields terminated by '|'
    missing field values are null
  )
  location (
    'delete.${SETNUM}')
)
reject limit unlimited;
```

```

alter table temp_okey_et parallel 4;

create table temp_okey parallel 4 nologging as select * from
temp_okey_et;

create unique index i_temp_okey on temp_okey (t_orderkey)
parallel 4 nologging compute statistics;

analyze table temp_okey estimate statistics sample 2 percent;

alter session force parallel dml parallel ${PAR_HINT};
alter session set isolation_level=serializable;
alter session set optimizer_index_cost_adj=10;

delete from (select /*+ use_nl(o) */ o.rowid from orders o,
temp_okey t where o.o_orderkey = t.t_orderkey order by 1);

delete from (select /*+ use_nl(l) */ l.rowid from lineitem
l,temp_okey t where l.l_orderkey = t.t_orderkey order by 1);

commit;

drop table temp_okey;
drop table temp_okey_et;
exit;
!

END=`$GTIME`
```

Done

```

echo ""
echo "Update Function 2 Set $SETNUM done!"
echo "Elapsed Time is `echo $END - $START | bc`"
echo ""
```

F. 11 tstart

```
#!/bin/ksh
```

```

mpsched -P RR sqlplus /NOLOG << !
connect / as sysdba
startup pfile=/oracle/dbs/10TB_run.ora
exit
!
```

```

/Lvm/set_queue;
exit
```

F. 12 tshut

```

#!/bin/ksh

sqlplus /NOLOG << !
connect / as sysdba
shutdown
exit
!
```

F. 13 set_queue

```

#!/sbin/sh

set -x

for c in c2 c4 c6 c8 c12 c10 c147 c146 \
        c14 c16 c18 c20 c22 c24 c151 c150 \
        c26 c28 c30 c32 c34 c36 c155 c154 \
        c38 c40 c42 c44 c46 c48 c159 c158 \
        c50 c52 c54 c56 c58 c60 c163 c162 \
        c62 c64 c66 c68 c70 c72 c167 c166 \
        c74 c76 c78 c80 c82 c84 c171 c170 \
        c86 c88 c90 c92 c94 c96 c175 c174 \
        c98 c100 c102 c104 c106 c108 c179 c178 \
        c110 c112 c114 c116 c118 c120 c183 c182 \
        c122 c124 c126 c128 c130 c132 c187 c186 \
        c134 c136 c138 c140 c142 c144 c191 c190
do
    /usr/sbin/scsictl -m queue_depth=64 /dev/rdsk/${c}t0d0
    /usr/sbin/scsictl -m queue_depth=64 /dev/rdsk/${c}t0d1
    /usr/sbin/scsictl -m queue_depth=64 /dev/rdsk/${c}t0d2
    /usr/sbin/scsictl -m queue_depth=64 /dev/rdsk/${c}t0d3
    /usr/sbin/scsictl -m queue_depth=64 /dev/rdsk/${c}t0d4
    /usr/sbin/scsictl -m queue_depth=64 /dev/rdsk/${c}t0d5
    /usr/sbin/scsictl -m queue_depth=64 /dev/rdsk/${c}t0d6
done
exit
```

Appendix G Price Quotes

The following pages contain the price quotes for the hardware included in this FDR.

Juergen Mueller
HP
Cupertino, CA 95014
December 17, 2003



HP Unix Sales Development
19111 Pruneridge Avenue
Cupertino, CA 95014
(408) 447-2320

 HP Integrity Superdome Enterprise Server		TPC-H Rev 2				
		Report Date: December 17, 2003				
Server Hardware						
Superdome left chassis	A5201A, Opt. 429	1	205,840	1	205840	
Superdome right chassis	A5202A, Opt. 429	1	218,435	1	218,435	
IPF Superdome Cell Board (sx1000)	A6866A	1	16,000	16	256,000	
3 Year Svc & Support Price (Hardware and Software)						838,197
4GB SDRAM (4x1GB DIMMS)	A6863A	1	17,750	64	1,136,000	
PCI-x I/O chassis	A6864A	1	16,805	12	201,660	
Core I/O Card	A6865A	1	1,045	1	1,045	
CPU Itanium 2, 1.5GHz w/6MB iL 3 cache (2 CPUs)	A6924A	1	40,000	32	1,280,000	
PCI 1000BT Lan Adapter	A6847A, Opt. 0D1	1	2,135	1	2,135	
I/O chassis enclosure for PCI chassis	A5862A	1	25,725	2	51,450	
Graphite I/O expansion power subsystem	A5861D	1	34,860	1	34,860	
PCI 2GB Fibre Channel Adapter	A6795A	1	2,240	96	215,040	
PCI Ultra160 SCSI Adapter	A6828A	1	1,323	1	1,323	
HP Surestore Disk System 2100	A5675A	1	700	1	700	
1-36GB LP 10K LVD SE U320 HDD	A6571A	1	720	4	2,880	
TA5300 Enclosure for DAT tape	C7508AZ	1	1,395	1	1,395	
DDS 4 tape	C5687B	1	1,450	1	1,450	
DVD Rom drive	C7499A	1	688	1	688	
SCSI Terminator LVD/SE HDT68 Multimedia	C2364A	1	100	1	100	
HP Tape Array PSU/Fan Kit	C7496A	1	425	1	425	
SCSI Cable 10m VHDT68/DHTS68 M/M Multimed	C2363B	1	335	1	335	
SCSI Cable 0.5m HDT68 M/M Multimedia	C2978B	1	99	1	99	
SMS for HP Integrity Superdome Tower	A9801A	1	5,140	1	5,140	
				Subtotal	3,617,000	838,197
Storage						
16 meter Fibre Optic Cable	A7525A	1	260	96	24,960	
HP Surestore VA 7110 w/ dual controller, 1024MB r *(large quantity discount)	A7294A	1	25,440	96	2,442,240	
3 Year Support Price						364,224
73GB 15K RPM FC HDD (10% sparing included)* *(large quantity discount)	A7288A, Opt 0D1	1	1,702	1584	2,696,522	138,240
HP Rack System/E, 41U, Quartz Color	A4902A	1	1,910	8	15,280	
HP Rear Door for 41U Quartz Rack	A5213AZ	1	334	8	2,672	
Modular Power Dist.	A5137AZ	1	145	32	4,640	
200-240 Volts Power Option	A5137AZ, Opt AW4	1	94	32	3,008	
				Subtotal	5,189,322	502,464
						Total
						8,806,322
						1,340,661
						(161,200)
						(4,469,089)
						(638,813)
						Grand Tot
						4176033.29
						701848.4

All the components in the price list are currently available. Maintenance support price is for 24 hours, 7 days with 4 hour response time.

From: MaryBeth Pierantoni [mailto:mary.beth.pierantoni@oracle.com]
Sent: Monday December 17, 2003
To: lucille_boushey@hp.com
Subject: Oracle Pricing for Oracle/HP SuperdomeTPCH Benchmark

Oracle Database 10g Enterprise Edition for 3 years, Named User Plus	10,000	64	640,000
Partitioning for 3 years, Named User Plus	2,500	64	160,000
Oracle Database Server Support Package for 3 years:		1	6,000
Oracle Mandatory E-Business Discount on (Licenses and Support)			(161,200)

Oracle pricing contact: MaryBeth Pierantoni, mary.beth.pierantoni@oracle.com, 650-506-2118