



Hewlett-Packard Company

TPC Benchmark™ C
Full Disclosure Report
for
HP ProLiant DL585-G1/2.4GHz Dual Core
using
Microsoft SQL Server 2005 Enterprise (x64) Edition
and
Windows Server 2003, Enterprise Edition x64

**First Edition
Submitted for Review
November 4, 2005**

Hewlett-Packard Company (HP) believes that the information in this document is accurate as of the publication date. The information in this document is subject to change without notice. HP assumes no responsibility for any errors that may appear in this document. The pricing information in this document is believed to accurately reflect the current prices as of the publication date. However, HP provides no warranty of the pricing information in this document.

Benchmark results are highly dependent upon workload, specific application requirements, and system design and implementation. Relative system performance will vary as a result of these and other factors. Therefore, TPC Benchmark C should not be used as a substitute for a specific customer application benchmark when critical capacity planning and/or product evaluation decisions are contemplated.

All performance data contained in this report were obtained in a rigorously controlled environment. Results obtained in other operating environments may vary significantly. HP does not warrant or represent that a user can or will achieve similar performance expressed in transactions per minute (tpmC) or normalized price/performance (\$/tpmC). No warranty of system performance or price/performance is expressed or implied in this report.

Copyright 2005 Hewlett-Packard Company.

All rights reserved. Permission is hereby granted to reproduce this document in whole or in part provided the copyright notice printed above is set forth in full text or on the title page of each item reproduced.

Printed in U.S.A., 2005

HP, NonStop, ProLiant DL585-G1, and ProLiant are registered trademarks of Hewlett-Packard Company.

Microsoft, Windows 2000, Windows Server 2003 x64 and SQL Server 2005 x64 are registered trademarks of Microsoft Corporation.

Xeon is a registered trademark of Intel.

Opteron is a registered trademark of AMD.

TPC Benchmark is a trademark of the Transaction Processing Performance Council.

Other product names mentioned in this document may be trademarks and/or registered trademarks of their respective companies.

Table of Contents

TABLE OF CONTENTS	3
PREFACE	5
TPC BENCHMARK C OVERVIEW	5
ABSTRACT	6
OVERVIEW	6
TPC BENCHMARK C METRICS	6
STANDARD AND EXECUTIVE SUMMARY STATEMENTS	6
AUDITOR	6
GENERAL ITEMS	10
TEST SPONSOR	10
APPLICATION CODE AND DEFINITION STATEMENTS	10
PARAMETER SETTINGS	10
CONFIGURATION ITEMS	10
CLAUSE 1 RELATED ITEMS	12
TABLE DEFINITIONS	12
PHYSICAL ORGANIZATION OF DATABASE	12
<i>Benchmarked Configuration</i>	12
PRICED CONFIGURATION VS. MEASURED CONFIGURATION:	14
INSERT AND DELETE OPERATIONS	14
PARTITIONING	14
REPLICATION, DUPLICATION OR ADDITIONS	14
CLAUSE 2 RELATED ITEMS	15
RANDOM NUMBER GENERATION	15
INPUT/OUTPUT SCREEN LAYOUT	15
PRICED TERMINAL FEATURE VERIFICATION	15
PRESENTATION MANAGER OR INTELLIGENT TERMINAL	15
TRANSACTION STATISTICS	15
QUEUEING MECHANISM	16
CLAUSE 3 RELATED ITEMS	17
TRANSACTION SYSTEM PROPERTIES (ACID)	17
ATOMICITY	17
<i>Completed Transactions</i>	17
<i>Aborted Transactions</i>	17
CONSISTENCY	17
ISOLATION	17
DURABILITY	18
<i>Durable Media Failure</i>	18
<i>Instantaneous Interruption and Loss of Memory</i>	19
CLAUSE 4 RELATED ITEMS	20
INITIAL CARDINALITY OF TABLES	20
DATABASE LAYOUT	20

TYPE OF DATABASE.....	21
DATABASE MAPPING.....	21
60 DAY SPACE.....	21
CLAUSE 5 RELATED ITEMS.....	22
THROUGHPUT.....	22
KEYING AND THINK TIMES.....	22
RESPONSE TIME FREQUENCY DISTRIBUTION CURVES AND OTHER GRAPHS.....	23
STEADY STATE DETERMINATION.....	28
WORK PERFORMED DURING STEADY STATE.....	28
MEASUREMENT PERIOD DURATION.....	28
REGULATION OF TRANSACTION MIX.....	29
TRANSACTION STATISTICS.....	29
CHECKPOINT COUNT AND LOCATION.....	30
CHECKPOINT DURATION.....	30
CLAUSE 6 RELATED ITEMS.....	31
RTE DESCRIPTIONS.....	31
EMULATED COMPONENTS.....	31
FUNCTIONAL DIAGRAMS.....	31
NETWORKS.....	31
OPERATOR INTERVENTION.....	31
CLAUSE 7 RELATED ITEMS.....	32
SYSTEM PRICING.....	32
AVAILABILITY, THROUGHPUT, AND PRICE PERFORMANCE.....	32
COUNTRY SPECIFIC PRICING.....	32
USAGE PRICING.....	32
CLAUSE 9 RELATED ITEMS.....	33
AUDITOR'S REPORT.....	33
AVAILABILITY OF THE FULL DISCLOSURE REPORT.....	33

Preface

The TPC Benchmark C was developed by the Transaction Processing Performance Council (TPC). The TPC was founded to define transaction processing benchmarks and to disseminate objective, verifiable performance data to the industry. This full disclosure report is based on the TPC Benchmark C Standard Specifications Version 5.5.

TPC Benchmark C Overview

The TPC describes this benchmark in Clause 0.1 of the specifications as follows:

TPC Benchmark™ C (TPC-C) is an OLTP workload. It is a mixture of read-only and update intensive transactions that simulate the activities found in complex OLTP application environments. It does so by exercising a breadth of system components associated with such environments, which are characterized by:

- The simultaneous execution of multiple transaction types that span a breadth of complexity
- On-line and deferred transaction execution modes
- Multiple on-line terminal sessions
- Moderate system and application execution time
- Significant disk input/output
- Transaction integrity (ACID properties)
- Non-uniform distribution of data access through primary and secondary keys
- Databases consisting of many tables with a wide variety of sizes, attributes, and relationships
- Contention on data access and update

The performance metric reported by TPC-C is a "business throughput" measuring the number of orders processed per minute. Multiple transactions are used to simulate the business activity of processing an order, and each transaction is subject to a response time constraint. The performance metric for this benchmark is expressed in transactions-per-minute-C (tpmC). To be compliant with the TPC-C standard, all references to tpmC results must include the tpmC rate, the associated price-per-tpmC, and the availability date of the priced configuration.

Although these specifications express implementation in terms of a relational data model with conventional locking scheme, the database may be implemented using any commercially available database management system (DBMS), database server, file system, or other data repository that provides a functionally equivalent implementation. The terms "table", "row", and "column" are used in this document only as examples of logical data structures.

TPC-C uses terminology and metrics that are similar to other benchmarks, originated by the TPC or others. Such similarity in terminology does not in any way imply that TPC-C results are comparable to other benchmarks. The only benchmark results comparable to TPC-C are other TPC-C results conformant with the same revision.

Despite the fact that this benchmark offers a rich environment that emulates many OLTP applications, this benchmark does not reflect the entire range of OLTP requirements. In addition, the extent to which a customer can achieve the results reported by a vendor is highly dependent on how closely TPC-C approximates the customer application. The relative performance of systems derived from this benchmark does not necessarily hold for other workloads or environments. Extrapolations to any other environment are not recommended.

Benchmark results are highly dependent upon workload, specific application requirements, and systems design and implementation. Relative system performance will vary as a result of these and other factors. Therefore, TPC-C should not be used as a substitute for a specific customer application benchmarking when critical capacity planning and/or product evaluation decisions are contemplated.

Abstract

Overview

This report documents the methodology and results of the TPC Benchmark C test conducted on the HP ProLiant DL585-G1. The operating system used for the benchmark was Windows Server 2003, Enterprise Edition x64. The DBMS used was Microsoft SQL Server 2005 Enterprise (x64) Edition.

TPC Benchmark C Metrics

The standard TPC Benchmark C metrics, tpmC (transactions per minute), price per tpmC (three year capital cost per measured tpmC), and the availability date are reported as:

206,181tpmC
USD \$2.30 per tpmC

The availability date is November 7, 2005.

Standard and Executive Summary Statements

The following pages contain executive summary of results for this benchmark.


Auditor

The benchmark configuration, environment and methodology were audited by Tom Sawyer of Performance Metrics, Inc. to verify compliance with the relevant TPC specifications.

Hewlett-Packard Company	HP ProLiant DL585-G1 2.4GHz Dual Core 4P	TPC-C Rev. 5.5
	C/S with 8 HP ProLiant DL360G4	Report Date: Nov 4, 2005

Total System Cost	TPC-C Throughput	Price/Performance	Availability Date
USD \$472,539	206,181	USD \$2.30	Nov 7, 2005

Database Server Processors /Cores/Threads	Database Manager	Operating System	Other Software	Number of Users
4/8/8 AMD Opteron 2.4 GHz DC	Microsoft SQL Server 2005 Enterprise (x64) Edition	Windows Server 2003, Enterprise (X64) Edition	Microsoft Visual C++ Microsoft COM+	164000



	Server		Each Client	
System Components	Quantity	Description	Quantity	Description
Processors/Cores/Threads	4/8/8	2.4 GHz DC AMD Opteron w/ 1M Cache	2/2/4	3.6 GHz Intel Xeon w/ 1MB cache
Memory	16	8 GB DDR (2 X 4 GB)	2	512MB
Disk Controllers	1	Integrated Smart 5i Controller	1	Integrated SMART 6i Controller
	7	SMART 6404 Array Controllers		
	1	SMART 642 Array Controller		
Disk Drives	12	146GB SCSI Drive	2	36 GB SCSI Drive
	394	36 GB SCSI Drive		
Total Storage		15,005.24 GB		33.9 GB

Hewlett-Packard Company		HP ProLiant DL585-G1 2.4GHz DC-4P Client/Server			TPC-C Rev. 5.5 Report Date: 4-Nov-05		
Description	Part Number	Third Party	Unit Price	Qty	Extended Price	3 yr. Maint. Price	
Server Hardware							
		Brand Pricing					
DL585 2.4GHz dual core (2P) 2GB PC2700/Dual port gigabit NIC/Smart 5i controller	397841-001	1	15,999	1	15,999		
DL585 2.4GHz/2700 dual core Processor Option Kit	397843-B21	1	5,699	2	11,398		
HP 8GB Reg PC2700 2x4GB Memory	395409-B21	1	7,499	16	119,984		
HP Storageworks MSA 30 SB Storage	302969-B21	1	2,829	28	79,212		
HP Modular Smart Array 500 G2 Storage includes 2 Smart Array 642 Adapters	335880-B21	1	4,499	1	4,499		
HP Modular Smart Array 500 G2 Controller	335881-B21	1	2,499	1	2,499		
HP Smart Array 6404/256MB Controller	273914-B21	1	1,899	7	13,293		
HP s7540 17in. CRT Monitor	PF997AA#ABA	1	149	1	149		
HP PS/2 Scroll Mouse carbonite	DG169AV	1	5	1	5		
HP Enhanced Keyboard	DG170AV#ABA	1	10	1	10		
HP 5642 Pallet Unassembled Rack	358254-B21	1	689	2	1,378		
UPS R1500 XR Low Voltage US	204404-001	1	866	1	866		
36GB 15K U320 Pluggable Hard Drive	286776-B22	1	299	394	117,806		
36GB 15K U320 Pluggable Hard Drive (10% spares)	286776-B22	1	299	40		11,960	
HP 146GB U320 10K Hot Plug Hard Drive	371535-B21	1	499	12	5,988		
HP CP 3Y 4H 24x7 HW 500 Srs 4-Hour 24 Hour x 7 Day Coverage 3 Years	401782-002	1	1,795	1		1,795	
HP Storageworks MSA 30 SB Storage (10% spares)	302969-B21	1	2,829	3		8,487	
HP 3y 4h 24x7 MSA500 HW Support	U6456E	1	1,950	1		1,950	
				Subtotal	373,086	24,192	
Server Software							
Microsoft SQL Server 2005 Enterprise X64 Edition(per processor)	810-03134	Microsoft	2	23,432	4	93,728	Incl Below
Microsoft Visual C++ Standard	254-00170	Microsoft	2	109	1	109	Incl Below
Microsoft Windows 2003 Server, Enterprise Edition X64	P72-00274	Microsoft	2	2,334	1	2,334	Incl Below
Microsoft Problem Resolution Services		Microsoft	2	245	1	245	
				Subtotal	96,171	245	
Client Hardware							
HP DL360G4 X3.6GHz \ 1GB SCSI US Rack Server	360528-001	1	2,799	8	22,392		
Dual Integrated Gigabit NIC, Integrated Smart Array Controller 6i							
Intel Xeon 3.6GHz 1MB DL360G4 Processor	354583-B21	1	999	8	7,992		
36GB 15K U320 Pluggable Hard Drive	286776-B22	1	299	16	4,784		
HP CP 3Y 4H 24x7 HW Entry300 4-Hour 24 Hour x 7 Day Coverage 3 Years	162675-002	1	599	8		4,792	
				Subtotal	35,168	4,792	
Client Software							
Windows Server 2000, Standard Edition	C11-00821	Microsoft	2	738	8	5,904	Incl. Above
				Subtotal	5,904	0	
User Connectivity							
HP ProCurve Switch 2824	J4903A#ABA	1	2499	1	2,499		
HP CP for HP ProCurve Networking products 3 Yr 4 hr/24x7	U2856E	1	1000	1		1,000	
				Subtotal	2,499	1,000	
Large Purchase and Cash discount (See Note 1)	16.0%	1					
					(\$65,720)	(\$4,797)	
				Total	\$447,108	\$25,432	
Prices used in TPC benchmarks reflect the actual prices a customer would pay for a one-time purchase of the stated components. Individually negotiated discounts are not permitted. Special prices based on assumptions about past or future purchases are not permitted. All discounts reflect standard pricing policies for the listed components. For complete details, see the pricing sections of the TPC benchmark pricing specifications. If you find that the stated prices are not available according to these terms, please inform the TPC at pricing@tpc.org. Thank you.				Three-Year Cost of Ownership: USD \$472,539			
				tpmC Rating: 206,181			
				\$ / tpmC: USD \$2.30			
Pricing: 1=HP Direct 2= Microsoft							
Note 1 = Discount based on HP Direct guidance with large purchase and Net 30 discount.Applies to all lines with 1 in pricing cc							
Note2: The benchmark results and test methodology were audited by Tom Sawyer of Performance Metrics, Inc.							
Note3: For ordering information call:							

Numerical Quantities Summary

MQTH, Computed Maximum Qualified Throughput

206,181 tpmC

Response Times (in seconds)	Average	90%	Maximum
New-Order	0.28	0.54	5.18
Payment	0.26	0.52	5.05
Order-Status	0.27	0.53	5.09
Delivery (interactive portion)	0.10	0.11	0.90
Delivery (deferred portion)	0.16	0.22	4.45
Stock-Level	0.28	0.54	5.28
Menu	0.10	0.11	1.00

Transaction Mix, in percent of total transaction

New-Order	44.93%
Payment	43.02%
Order-Status	4.01%
Delivery	4.01%
Stock-Level	4.03%

Emulation Delay (in seconds)

Resp.Time Menu

New-Order	0.10	0.10
Payment	0.10	0.10
Order-Status	0.10	0.10
Delivery (interactive)	0.10	0.10
Stock-Level	0.10	0.10

Keying/Think Times (in seconds)

Min. Average Max.

New-Order	18.02/0.00	18.03/12.07	18.36/120.64
Payment	3.02/0.00	3.03/12.07	3.32/120.64
Order-Status	2.02/0.00	2.03/10.07	2.31/100.63
Delivery (interactive)	2.02/0.00	2.03/5.08	2.31/50.63
Stock-Level	2.02/0.00	2.03/5.08	2.31/50.63

Test Duration

Ramp-up time	52 minutes
Measurement interval	120 minutes
Transactions (all types) completed during measurement interval	57,272,439
Ramp down time	5 minutes

Checkpointing

Number of checkpoints	4
Checkpoint interval	30 minutes

General Items

Test Sponsor

A statement identifying the benchmark sponsor(s) and other participating companies must be provided.

This benchmark was sponsored by Hewlett-Packard Company. The benchmark was developed and engineered by Hewlett-Packard Company. Testing took place at HP benchmarking laboratories in Houston, Texas.

Application Code and Definition Statements

The application program (as defined in clause 2.1.7) must be disclosed. This includes, but is not limited to, the code implementing the five transactions and the terminal input output functions.

Appendix A contains all source code implemented in this benchmark.

Parameter Settings

Settings must be provided for all customer-tunable parameters and options which have been changed from the defaults found in actual products, including by not limited to:

- *Database options*
- *Recover/commit options*
- *Consistency locking options*
- *Operating system and application configuration parameters*

This requirement can be satisfied by providing a full list of all parameters.


Appendix C contains the tunable parameters to for the database, the operating system, and the transaction monitor.

Configuration Items

Diagrams of both measured and priced configurations must be provided, accompanied by a description of the differences.

The configuration diagram for both the tested and priced systems are included on the following page.

Figure 1. Benchmarked and Priced Configuration



Clause 1 Related Items

Table Definitions

Listing must be provided for all table definition statements and all other statements used to set up the database.

Appendix B contains the code used to define and load the database tables.

Physical Organization of Database

The physical organization of tables and indices within the database must be disclosed.

The tested configuration consisted of 392 drives at 36GB for database data, two 36GB drive for the operating system, and 12 drives at 146GB for database log. There were 392 X 36GB drives for database data on seven SMART 6404 controllers, 12 X 146GB drives for the SMART 642 controller connected to an MSA 500G2, and 2 X 36GB drives for the integrated Smart 5i controller.

Benchmarked Configuration:

Integrated Smart 5i Controller, Array A

LOGICAL DRIVE C: Total Capacity = 33.91 GB RAID 0+1
Microsoft Windows Server 2003, Enterprise Edition (X64)

SMART-642 Controller, Slot 3, Array A

LOGICAL DRIVE E: Total Capacity = 820.39 GB RAID 0+1
MSSQL_tpcc_log

SMART-6404 Controller, Slot 1A, Array A

LOGICAL DRIVE C:\cs\cs1: Total Capacity = 74.21GB RAID 0
Cs_fg

LOGICAL DRIVE C:\misc\misc1: Total Capacity = 39.06GB RAID 0
Misc_fg

LOGICAL DRIVE W: Total Capacity = 418.15GB RAID 0+1
tpccback1

SMART-6404 Controller, Slot 1B, Array A

LOGICAL DRIVE C:\cs\cs2 Total Capacity = 74.21GB RAID 0
Cs_fg

LOGICAL DRIVE C:\misc\misc2 Total Capacity = 39.06GB RAID 0
Misc_fg

SMART-6404 Controller, Slot 2A, Array A

LOGICAL DRIVE C:\cs\cs3 Total Capacity = 74.21GB RAID 0
Cs_fg

LOGICAL DRIVE C:\misc\misc3 Total Capacity = 39.06GB RAID 0
Misc_fg

LOGICAL DRIVE X: Total Capacity = 418.15GB RAID 0+1
tpccback2

SMART-6404 Controller, Slot 2B, Array A		
<u>LOGICAL DRIVE C:\cs\cs4</u>	<u>Total Capacity = 74.21GB</u>	<u>RAID 0</u>
Cs_fg		
<u>LOGICAL DRIVE C:\misc\misc4</u>	<u>Total Capacity = 39.06GB</u>	<u>RAID 0</u>
Misc_fg		
SMART-6404 Controller, Slot 4A, Array A		
<u>LOGICAL DRIVE C:\cs\cs5</u>	<u>Total Capacity = 74.21GB</u>	<u>RAID 0</u>
Cs_fg		
<u>LOGICAL DRIVE C:\misc\misc5</u>	<u>Total Capacity = 39.06GB</u>	<u>RAID 0</u>
Misc_fg		
<u>LOGICAL DRIVE Y:</u>	<u>Total Capacity = 418.15GB</u>	<u>RAID 0+1</u>
tpcback3		
SMART-6404 Controller, Slot 4B, Array A		
<u>LOGICAL DRIVE C:\cs\cs6</u>	<u>Total Capacity = 74.21GB</u>	<u>RAID 0</u>
Cs_fg		
<u>LOGICAL DRIVE C:\misc\misc6</u>	<u>Total Capacity = 39.06GB</u>	<u>RAID 0</u>
Misc_fg		
SMART-6404 Controller, Slot 5A, Array A		
<u>LOGICAL DRIVE C:\cs\cs7</u>	<u>Total Capacity = 74.21GB</u>	<u>RAID 0</u>
Cs_fg		
<u>LOGICAL DRIVE C:\misc\misc7</u>	<u>Total Capacity = 39.06GB</u>	<u>RAID 0</u>
Misc_fg		
SMART-6404 Controller, Slot 5B, Array A		
<u>LOGICAL DRIVE C:\cs\cs8</u>	<u>Total Capacity = 74.21GB</u>	<u>RAID 0</u>
Misc_fg		
<u>LOGICAL DRIVE C:\misc\misc8</u>	<u>Total Capacity = 39.06GB</u>	<u>RAID 0</u>
Misc_fg		
SMART-6404 Controller, Slot 6A, Array A		
<u>LOGICAL DRIVE C:\cs\cs9</u>	<u>Total Capacity = 74.21GB</u>	<u>RAID 0</u>
Cs_fg		
<u>LOGICAL DRIVE C:\misc\misc9</u>	<u>Total Capacity = 39.06GB</u>	<u>RAID 0</u>
Misc_fg		
<u>LOGICAL DRIVE Z:</u>	<u>Total Capacity = 418.15GB</u>	<u>RAID 0+1</u>
tpcback4		
SMART-6404 Controller, Slot 6B, Array A		
<u>LOGICAL DRIVE C:\cs\cs10</u>	<u>Total Capacity = 74.21GB</u>	<u>RAID 0</u>
Cs_fg		
<u>LOGICAL DRIVE C:\misc\misc10</u>	<u>Total Capacity = 39.06GB</u>	<u>RAID 0</u>
Misc_fg		
SMART-6404 Controller, Slot 7A, Array A		
<u>LOGICAL DRIVE C:\cs\cs11</u>	<u>Total Capacity = 74.21GB</u>	<u>RAID 0</u>
Cs_fg		
<u>LOGICAL DRIVE C:\misc\misc11</u>	<u>Total Capacity = 39.06GB</u>	<u>RAID 0</u>
Misc_fg		

SMART-6404 Controller, Slot 7B, Array A

<u>LOGICAL DRIVE C:\cs\cs12</u> Misc_fg	<u>Total Capacity = 74.21GB</u>	<u>RAID 0</u>
<u>LOGICAL DRIVE C:\misc\misc12</u> Misc_fg	<u>Total Capacity = 39.06GB</u>	<u>RAID 0</u>

SMART-6404 Controller, Slot 8A, Array A

<u>LOGICAL DRIVE C:\cs\cs13</u> Cs_fg	<u>Total Capacity = 74.21GB</u>	<u>RAID 0</u>
<u>LOGICAL DRIVE C:\misc\misc13</u> Misc_fg	<u>Total Capacity = 39.06GB</u>	<u>RAID 0</u>

SMART-6404 Controller, Slot 8B, Array A

<u>LOGICAL DRIVE C:\cs\cs14</u> Cs_fg	<u>Total Capacity = 74.21GB</u>	<u>RAID 0</u>
<u>LOGICAL DRIVE C:\misc\misc14</u> Misc_fg	<u>Total Capacity = 39.06GB</u>	<u>RAID 0</u>

Priced Configuration vs. Measured Configuration:

None

Insert and Delete Operations

It must be ascertained that insert and/or delete operations to any of the tables can occur concurrently with the TPC-C transaction mix. Furthermore, any restrictions in the SUT database implementation that precludes inserts beyond the limits defined in Clause 1.4.11 must be disclosed. This includes the maximum number of rows that can be inserted and the minimum key value for these new rows.

All insert and delete functions were fully operational during the entire benchmark.

Partitioning

While there are a few restrictions placed upon horizontal or vertical partitioning of tables and rows in the TPC-C benchmark, any such partitioning must be disclosed.

No partitioning was used in this benchmark.

Replication, Duplication or Additions

Replication of tables, if used, must be disclosed. Additional and/or duplicated attributes in any table must be disclosed along with a statement on the impact on performance.

No replications, duplications or additional attributes were used in this benchmark.

Clause 2 Related Items

Random Number Generation

The method of verification for the random number generation must be described.

In the Benchcraft RTE from Microsoft, each driver engine uses an independent random number sequence. All of the users within a given driver draw from the same sequence.

The Benchcraft RTE computes random integers as described in "Random Numbers Generators: Good Ones Are Hard to Find." Communications of the ACM - October 1988 Volume 31 Number 10.

The seeds for each user were captured and verified by the auditor to be unique. In addition, the contents of the database were systematically searched, and randomly sampled by the auditor for patterns that would indicate the random number generator had affected any kind of a discernible pattern; none was found.

Input/Output Screen Layout

The actual layout of the terminal input/output screens must be disclosed.

All screen layouts followed the specifications exactly.

Priced Terminal Feature Verification

The method used to verify that the emulated terminals provide all the features described in Clause 2.2.2.4 must be explained. Although not specifically priced, the type and model of the terminals used for the demonstration in 8.1.3.3 must be disclosed and commercially available (including supporting software and maintenance).

The terminal attributes were verified by the auditor. The auditor manually exercised each specification on a representative HP ProLiant web server.

Presentation Manager or Intelligent Terminal

Any usage of presentation managers or intelligent terminals must be explained.

Application code running on the client machines implemented the TPC-C user interface. No presentation manager software or intelligent terminal features were used. The source code for the forms applications is listed in Appendix A.

Transaction Statistics

Table 2.1 lists the numerical quantities that Clauses 8.1.3.5 to 8.1.3.11 require.

Table 2.1 Transaction Statistics

Statistic		Value
New Order	Home warehouse order lines	99.00%
	Remote warehouse order lines	1.00%
	Rolled back transactions	1.00%
	Average items per order	10.00

Statistic		Value
Payment	Home warehouse payments	85.00%
	Remote warehouse payments	15.00%
	Accessed by last name	60.01%
Order Status	Accessed by last name	60.05%
Transaction Mix	New Order	44.93%
	Payment	43.02%
	Order status	4.01%
	Delivery	4.01%
	Stock level	4.03%

Queuing Mechanism

The queuing mechanism used to defer the execution of the Delivery transaction must be disclosed.

Microsoft COM+ on each client machine served as the queuing mechanism to the database. Each delivery request was submitted to Microsoft COM+ asynchronously with control being returned to the client process immediately and the deferred delivery part completing asynchronously.

The source code is listed in Appendix A.

Clause 3 Related Items

Transaction System Properties (ACID)

The results of the ACID tests must be disclosed along with a description of how the ACID requirements were met. This includes disclosing which case was followed for the execution of Isolation Test 7.

All ACID property tests were successful. The executions are described below.

Atomicity

The system under test must guarantee that the database transactions are atomic; the system will either perform all individual operations on the data or will assure that no partially completed operations leave any effects on the data.

Completed Transactions

A row was selected in a script from the warehouse, district and customer tables, and the balances noted. A payment transaction was started with the same warehouse, district and customer identifiers and a known amount. The payment transaction was committed and the rows were verified to contain correctly updated balances.

Aborted Transactions

A row was selected in a script from the warehouse, district and customer tables, and the balances noted. A payment transaction was started with the same warehouse, district and customer identifiers and a known amount. The payment transaction was rolled back and the rows were verified to contain the original balances.

Consistency

Consistency is the property of the application that requires any execution of a database transaction to take the database from one consistent state to another, assuming that the database is initially in a consistent state.

Consistency conditions one through four were tested using a script to issue queries to the database. The results of the queries verified that the database was consistent for all four tests.

A run was executed under full load lasting over two hours and included a checkpoint.

The script was executed again. The result of the same queries verified that the database remained consistent after the run.

Isolation

Sufficient conditions must be enabled at either the system or application level to ensure the required isolation defined above (clause 3.4.1) is obtained.

Isolation tests one through nine were executed using shell scripts to issue queries to the database. Each script included timestamps to demonstrate the concurrency of operations. The results of the queries were captured to files. The captured files were verified by the auditor to demonstrate the required isolation had been met.

In addition, the phantom tests and the stock level tests were executed and verified.

For Isolation test seven, case A was followed.

Durability

The tested system must guarantee durability: the ability to preserve the effects of committed transaction and insure database consistency after recovery from any one of the failures listed in Clause 3.5.3.

Durable Media Failure

Loss of Data and Log

To demonstrate recovery from a permanent failure of durable medium containing DBMS logs and TPC-C tables, the following steps were executed. This test was executed on a fully scaled database of 1680 warehouses under a load of 16800 users.

- The total number of New Orders was determined by the sum of D_NEXT_O_ID of all rows in the DISTRICT table giving the beginning count.
- The RTEs were started with 10% of the benchmark users.
- The test was allowed to run for a minimum of 10 minutes.
- One log disk was removed from the MSA 500G2 drive cabinet.
- Since the disk was mirrored, processing was not interrupted. This was verified by checking the user's status on the RTE.
- One of the data disks was removed from one MSA 30 drive cabinet.
- When Microsoft SQL Server recorded errors about not being able to access the database, the RTE was shut down.
- Microsoft SQL Server was shutdown, and the system rebooted after replacing the pulled drives with new drives.
- After the RAID recovery process finished Microsoft SQL Server was started, and a dump of the transaction log was taken.
- The database was restored from backup and the transaction log dump was applied.
- Consistency condition #3 was executed and verified.
- Step 2 was repeated and the difference between the first and second counts was noted.
- An RTE report was generated for the entire run time giving the number of NEW-ORDERS successfully returned to the RTE.
- The counts in steps 12 and 13 were compared and the results verified that all committed transactions had been successfully recovered.
- Samples were taken from the RTE files and used to query the database to demonstrate successful transactions had corresponding rows in the ORDER table.

Instantaneous Interruption and Loss of Memory

Because loss of power erases the contents of memory, the instantaneous interruption and the loss of memory tests were combined into a single test. This test was executed on a fully scaled database of 16800 warehouses (of which 16400 were used) under a full load of 164000 users. The following steps were executed:

- The total number of New Orders was determined by the sum of D_NEXT_O_ID of all rows in the DISTRICT table giving the beginning count.
- The RTE was started with 164000 users.
- The test was allowed to run for a minimum of 10 minutes.
- Pulling the power cords from the SUT induced system crash and loss of memory. No battery backup or Uninterruptible Power Supply (UPS) were used to preserve the contents of memory.
- The RTE was paused then stopped.
- Power was restored and the system restarted.
- Microsoft SQL Server was restarted and performed an automatic recovery.
- Consistency condition #3 was executed and verified.
- Step 1 was repeated and the difference between the first and second counts was noted.
- An RTE report was generated for the entire run time giving the number of NEW-ORDERS successfully returned to the RTE.
- The counts in step 9 and 10 were compared and the results verified that all committed transactions had been successfully recovered.
- Samples were taken from the RTE files and used to query the database to demonstrate successful transactions had corresponding rows in the ORDER table.

Clause 4 Related Items

Initial Cardinality of Tables

The cardinality (e.g. number of rows) of each table, as it existed at the start of the benchmark run, must be disclosed. If the database was over-scaled and inactive rows of the WAREHOUSE table were deleted, the cardinality of the WAREHOUSE table as initially configured and the number of rows deleted must be disclosed.

Table 4.1 Number of Rows for Server

Table	Cardinality as built
Warehouse	16,800
District	168,000
Customer	504,000,000
History	504,000,000
Orders	504,000,000
New Order	151,200,000
Order Line	5,039,988,259
Stock	1,680,000,000
Item	100,000
Deleted Warehouses	0

Database Layout

The distribution of tables and logs across all media must be explicitly depicted for tested and priced systems.

The benchmarked configuration used 7 SMART-6404 Array controllers with 4 SCSI channels each. Each controller is capable of accessing up to 14 disk drives per channel and supports RAID 0, RAID 0+1, and RAID 5 per each logical volume configured. The data tables were stored on 14 RAID arrays of (28) 36GB 15K drives each. Each array was configured as RAID 0 and housed a logical drive for database data. Some of these controllers also housed a RAID 0+1 volume used for backup of the database. The SMART-642 Array controller was connected to an MSA 500G2 which had one array consisting of (12) 146GB 15K drives, and housed a RAID 0+1 logical volume for the database log. The operating system was housed internally on the integrated Smart 5i controller on a RAID 1 set of (2) 36GB 15K drives. The Array Accelerators on the data controllers were configured as 100% write cache and were enabled for all logical drives. The SMART 642 controller had no physical cache module installed, but the redundant controllers in the MSA 500G2 had cache enabled for the transaction log. All RAID volumes used hardware RAID.

Section 1.2 of this report details the distribution of database tables across all disks. The code that creates the file groups and tables is included in Appendix B.

Type of Database

A statement must be provided that describes:

- *The data model implemented by DBMS used (e.g. relational, network, hierarchical).*
- *The database interface (e.g. embedded, call level) and access language (e.g. SQL, DL/I, COBOL read/write used to implement the TPC-C transaction. If more than one interface/access language is used to implement TPC-C, each interface/access language must be described and a list of which interface/access language is used with which transaction type must be disclosed.*

Microsoft SQL Server 2005 Enterprise (x64) Edition is a relational DBMS.

The interface used was Microsoft SQL Server stored procedures accessed with Remote Procedure Calls embedded in C code.

Database Mapping

The mapping of database partitions/replications must be explicitly described.

The database was not replicated.

60 Day Space

Details of the 60-day space computations along with proof that the database is configured to sustain 8 hours of growth for the dynamic tables (Order, Order-Line, and History) must be disclosed.

To calculate the space required to sustain the database log for 8 hours of growth at steady state, the following steps were followed:

- The free space on the log file was queried using *dbcc sqlperf(logspace)*.
- Transactions were run against the database with a full load of users.
- The free space was again queried using *dbcc sqlperf(logspace)*.
- The space used was calculated as the difference between the first and second query.
- The number of NEW-ORDERS was verified from the difference in the sum(d_next_o_id) taken from before and after the run.
- The space used was divided by the number of NEW-ORDERS giving a space used per NEW-ORDER transaction.
- The space used per transaction was multiplied by the measured tpmC rate times 480 minutes.

The same methodology was used to compute growth requirements for dynamic tables Order, Order-Line and History.

Details of both the 8-hour transaction log space requirements and the 60-day space requirements are shown in Appendix D.

Clause 5 Related Items

Throughput

Measured tpmC must be reported

Measured tpmC 206,181 tpmC
Price per tpmC USD \$2.30

Response Times

Ninetieth percentile, maximum and average response times must be reported for all transaction types as well as for the menu response time.

Table 5.2: Response Times

Type	Average	90 th %	Maximum
New-Order	0.28	0.54	5.18
Payment	0.26	0.52	5.05
Order-Status	0.27	0.53	5.09
Interactive Delivery	0.10	0.11	0.90
Deferred Delivery	0.16	0.22	4.45
Stock-Level	0.28	0.54	5.28
Menu	0.10	0.11	1.00

Keying and Think Times

The minimum, the average, and the maximum keying and think times must be reported for each transaction type.

Table 5.3: Keying Times

Type	Minimum	Average	Maximum
New-Order	18.02	18.03	18.36
Payment	3.02	3.03	3.32
Order-Status	2.02	2.03	2.31
Interactive Delivery	2.02	2.03	2.31
Stock-Level	2.02	2.03	2.31

Table 5.4: Think Times

Type	Minimum	Average	Maximum
New-Order	0.00	12.07	120.64
Payment	0.00	12.07	120.64
Order-Status	0.00	10.07	100.63
Interactive Delivery	0.00	5.08	50.63
Stock-Level	0.00	5.08	50.63

Response Time Frequency Distribution Curves and Other Graphs

Response Time frequency distribution curves (see Clause 5.6.1) must be reported for each transaction type.

The performance curve for response times versus throughput (see Clause 5.6.2) must be reported for the New-Order transaction.

Think Time frequency distribution curves (see Clause 5.6.3) must be reported for each transaction type.

Keying Time frequency distribution curves (see Clause 5.6.4) must be reported for each transaction type.

A graph of throughput versus elapsed time (see Clause 5.6.5) must be reported for the New-Order transaction.

Figure 2. New Order Response Time Distribution




Figure 3. Payment Response Time Distribution




Figure 4. Order Status Response Time Distribution




Figure 5. Delivery Response Time Distribution




Figure 6. Stock Level Response Time Distribution




Figure 7. Response Time vs. Throughput




Figure 8. New Order Think Time Distribution





Figure 9. Throughput vs. Time Distribution



Steady State Determination

The method used to determine that the SUT had reached a steady state prior to commencing the measurement interval must be disclosed.

Steady state was determined using real time monitor utilities from the RTE. Steady state was further confirmed by the throughput data collected during the run and graphed in Figure 10.

Work Performed During Steady State

A description of how the work normally performed during a sustained test (for example checkpointing, writing redo/undo log records, etc.), actually occurred during the measurement interval must be reported.

The RTE generated the required input data to choose a transaction from the menu. This data was timestamped. The input screen for the requested transaction was returned and timestamped. The difference between these two timestamps was the menu response time. The RTE writes to the log file once per transaction on selective fields such as order id. There is one log file per driver engine.

The RTE generated the required input data for the chosen transaction. It waited to complete the minimum required key time before transmitting the input screen. The transmission was timestamped. The return of the screen with the required response data was timestamped. The difference between these two timestamps was the response time for that transaction.

The RTE then waited the required think time interval before repeating the process starting at selecting a transaction from the menu.

The RTE transmissions were sent to application processes running on the client machines through Ethernet LANs. These client application processes handled all screen I/O as well as all requests to the database on the server. The applications communicated with the database server over gigabit Ethernet LANs using DBLIB and RPC calls.

To perform checkpoints at specific intervals, the SQL Server *recovery interval* was set to 32767 and a script was written to schedule multiple checkpoints at specific intervals. The script included a wait time between each checkpoint equal to 30 minutes. The measurement interval was 120 minutes. The checkpoint script was started manually after the RTE had all users logged in and the database had achieved steady state.

At each checkpoint, Microsoft SQL Server wrote to disk all memory pages that had been updated but not yet physically written to disk. The positioning of the measurement interval is depicted on the graph in Figure 9.

Measurement Period Duration

A statement of the duration of the measurement interval for the reported Maximum Qualified Throughput (tpmC) must be included.

The reported measured interval was exactly 120 minutes long.

Regulation of Transaction Mix

The method of regulation of the transaction mix (e.g., card decks or weighted random distribution) must be described. If weighted distribution is used and the RTE adjusts the weights associated with each transaction type, the maximum adjustments to the weight from the initial value must be disclosed.

The RTE was given a weighted random distribution, which was not adjusted during the run.

Transaction Statistics

The percentage of the total mix for each transaction type must be disclosed. The percentage of New-Order transactions rolled back as a result of invalid item number must be disclosed. The average number of order-lines entered per New-Order transaction must be disclosed. The percentage of remote order lines per New-Order transaction must be disclosed. The percentage of remote Payment transactions must be disclosed. The percentage of customer selections by customer last name in the Payment and Order-Status transactions must be disclosed. The percentage of Delivery transactions skipped due to there being fewer than necessary orders in the New-Order table must be disclosed.

Table 5.5: Transaction Statistics

Statistic		Value
New Order	Home warehouse order lines	99.00%
	Remote warehouse order lines	1.00%
	Rolled back transactions	1.00%
	Average items per order	10.00
Payment	Home warehouse payments	85.00%
	Remote warehouse payments	15.00%
	Accessed by last name	60.01%
Delivery	Skipped transactions (interactive)	0
	Skipped transactions (deferred)	0
Order Status	Accessed by last name	60.05%
Transaction Mix	New Order	44.93%
	Payment	43.02%
	Order status	4.01%
	Delivery	4.01%
	Stock level	4.03%

Checkpoint Count and Location

The number of checkpoints in the Measurement Interval, the time in seconds from the start of the Measurement Interval to the first checkpoint, and the Checkpoint Interval must be disclosed.

The initial checkpoint was started 52 minutes after the start of the ramp-up. Subsequent checkpoints occurred every 30 minutes. Each checkpoint in the measurement interval lasted 27 minutes and thirty seconds. The measurement interval contains four checkpoints.

Checkpoint Duration

The start time and duration in seconds of at least the four longest checkpoints during the Measurement Interval must be disclosed.

Checkpoint Start Time	Duration
13:10:08.04 pm	27 minutes, 30 seconds
13:40:05.13 pm	27 minutes, 30 seconds
14:10:02.07 pm	27 minutes, 30 seconds
14:39:59.10 pm	27 minutes, 30 seconds

Clause 6 Related Items

RTE Descriptions

If the RTE is commercially available, then its inputs must be specified. Otherwise, a description must be supplied of what inputs (e.g., scripts) to the RTE had been used.

The RTE used was Microsoft Benchcraft RTE. Benchcraft is a proprietary tool provided by Microsoft and is not commercially available. The RTE's input is listed in Appendix A.

Emulated Components

It must be demonstrated that the functionality and performance of the components being emulated in the Driver System are equivalent to the priced system. The results of the test described in Clause 6.6.3.4 must be disclosed.

The driver system consisted of 8 HP ProLiant servers. These driver machines emulated the users' web browsers.

Functional Diagrams

A complete functional diagram of both the benchmark configuration and the configuration of the proposed (target) system must be disclosed. A detailed list of all hardware and software functionality being performed on the Driver System and its interface to the SUT must be disclosed.

The driver system performed the data generation and input functions of the priced display device. It also captured the input and output data and timestamps for post-processing of the reported metrics. No other functionality was included on the driver system.

Section 1.4 of this report contains detailed diagrams of both the benchmark configuration and the priced configuration.

Networks

The network configuration of both the tested services and proposed (target) services that are being represented and a thorough explanation of exactly which parts of the proposed configuration are being replaced with the Driver System must be disclosed.

The bandwidth of the networks used in the tested/priced configuration must be disclosed.

In the tested configuration, 8 driver (RTE) machines were connected through a gigabit Ethernet switch to the client machines at 1Gbps, thus providing the path from the RTEs to the clients. The server (SUT) was connected to the clients through a gigabit Ethernet switch on a separate LAN.

The priced configuration was connected in the same manner as the tested configuration.

Operator Intervention

If the configuration requires operator intervention (see Clause 6.6.6), the mechanism and the frequency of this intervention must be disclosed.

This configuration does not require any operator intervention to sustain eight hours of the reported throughput.

Clause 7 Related Items

System Pricing

A detailed list of hardware and software used in the priced system must be reported. Each separately orderable item must have vendor part number, description, and release/revision level, and either general availability status or committed delivery data. If package-pricing is used, vendor part number of the package and a description uniquely identifying each of the components of the package must be disclosed. Pricing source and effective date(s) of price(s) must also be reported.

The total 3 year price of the entire configuration must be reported, including: hardware, software, and maintenance charges. Separate component pricing is recommended. The basis of all discounts used must be disclosed.

The details of the hardware and software are reported in the front of this report as part of the executive summary. All third party quotations are included at the end of this report as Appendix E.

Availability, Throughput, and Price Performance

The committed delivery date for general availability (availability date) of products used in the price calculation must be reported. When the priced system included products with different availability dates, the reported availability date for the priced system must be the date at which all components are committed to be available.

A statement of the measured tpmC as well as the respective calculations for the 5-year pricing, price/performance (price/tpmC), and the availability date must be included.

- **Maximum Qualified Throughput** **206,181tpmC**
- **Price per tpmC** **USD \$2.30 per tpmC**
- **Availability** **November 7, 2005**

Country Specific Pricing

Additional Clause 7 related items may be included in the Full Disclosure Report for each country specific priced configuration. Country specific pricing is subject to Clause 7.1.7

This system is being priced for the United States of America.

Usage Pricing

For any usage pricing, the sponsor must disclose:

- *Usage level at which the component was priced.*
- *A statement of the company policy allowing such pricing.*

The component pricing based on usage is shown below:

- 8 Microsoft Windows Server 2000 Standard Edition
- 1 Microsoft Windows Server 2003, Enterprise x64 Edition
- 1 Microsoft SQL Server 2005 Enterprise Edition x64 (per processor)
- 1 Microsoft Visual C++
- HP Servers include 3 years of support.

Clause 9 Related Items

Auditor's Report

The auditor's name, address, phone number, and a copy of the auditor's attestation letter indicating compliance must be included in the Full Disclosure Report.

This implementation of the TPC Benchmark C was audited by Tom Sawyer of Performance Metrics, Inc.

Performance Metrics, Inc.
PO Box 984
Klamath CA 95548
(phone) 707-482-0523
(fax) 707-482-0575
e-mail: lornaL@perfmetrics.com

Availability of the Full Disclosure Report

The Full Disclosure Report must be readily available to the public at a reasonable charge, similar to the charges for similar documents by the test sponsor. The report must be made available when results are made public. In order to use the phrase "TPC Benchmark™ C", the Full Disclosure Report must have been submitted to the TPC Administrator as well as written permission obtained to distribute same.

Requests for this TPC Benchmark C Full Disclosure Report should be sent to:

TPC
Presidio of San Francisco
Building 572B Ruger St. (surface)
P.O. Box 29920 (mail)
San Francisco, CA 94129-0920

or

Hewlett-Packard Company
Database Performance Engineering
P.O. Box 692000
Houston, TX 77269-2000



PERFORMANCE METRICS INC.
TPC Certified Auditors

October 25, 2005

Mr. David Adams
 Hewlett-Packard Company
 Database Performance Lab
 20555 SH 249
 Houston, TX 77070

I have verified the TPC Benchmark™ C client/server for the following configuration:

Platform: HP ProLiant DL585 G1 4P
 Database Manager: Microsoft SQL Server 2005 Enterprise Edition X64
 Operating System: Microsoft Windows 2003 Server, Enterprise Edition X64
 Transaction Monitor: COM+

System Under Test: HP ProLiant DL585 G1				
CPU's	Memory	Disks (total)	90% Response	TpmC
4 AMD Opteron dual core @2.4GHz	Main: 128 GB	392 @36GB 12 @ 146GB 2 @ 36GB (OS)	0.54	206,181
8 clients: DL360G4 each with:				
2 Intel Xeon @3.6 GHz	Main: 1 GB	2 @ 36GB	Na	Na

In my opinion, these performance results were produced in compliance with the TPC requirements for the benchmark. The following attributes of the benchmark were given special attention:

- The transactions were correctly implemented.
- The database was properly sized and populated.
- The database was properly scaled with 16,800 warehouses, 16,400 of which were used. I verified that d_next_o_id and w_ytd contained initial values for the unused warehouses
- The ACID properties were met. The disk-loss tests used 1,680 warehouses of the full database and the performance exceeded 10% of the measured tpmC.

137 Yankton St. Suite 101, Folsom 95630
 (916) 985-1131 fax: (916) 985-1185 email: Lorna@PerfMetrics.com

Page 1

PERFORMANCE METRICS INC.
TPC Certified Auditors

- Input data was generated according to the specified percentages.
- Eight hours of mirrored log space was configured on the measured system.
- Eight hours of dynamic table growth space was configured on the measured system.
- The 60-day space calculation was verified; the measured system had sufficient storage.
- Measurement cycle times included a delay of 0.1 seconds.
- There were 164,000 user contexts present on the system.
- Each group of emulated users started with the same random number seed.
- The NURand constants used for database load and at run time were 123 and 25.
- The steady state portion of the test was 2 hours.
- The system pricing was checked for major components and maintenance.

Auditor Notes:

None

Sincerely,



Tom Sawyer
Auditor

Appendix A: Source Code

The client source code is listed below.

delivery.h

```
/* Generated by IDL compiler version DEC DCE V2.0.0-6
*/
#ifndef _delivery_v1_0_included
#define _delivery_v1_0_included
#include IDLBASE H
#include <dce\idlbase.h>
#endif
#include <dce\rpc.h>
#include "trpc/trpc.h"

#ifdef __cplusplus
extern "C" {
#endif

#ifndef nbase_v0_0_included
#include "dce\nbase.h"
#endif
#ifndef trpcImports_v0_0_included
#include "trpc\trpcImports.h"
#endif
#ifndef mon_handle_v1_0_included
#include "tpm\mon\mon_handle.h"
#endif
#ifndef tpcc_types_v1_0_included
#include "tpcc_type.h"
#endif
#include <dce\rpcexc.h>
extern EXCEPTION encina_x_transaction_aborted;
extern EXCEPTION encina_x_server_shutdown;
extern EXCEPTION encina_x_permission_denied;
extern EXCEPTION encina_x_object_not_found;
extern EXCEPTION encina_x_empty_slot1;
extern EXCEPTION encina_x_empty_slot2;
extern EXCEPTION encina_x_empty_slot3;
extern EXCEPTION encina_x_empty_slot4;
extern EXCEPTION encina_x_empty_slot5;
extern EXCEPTION encina_x_undefined_exception;
extern void IDL_STD_STDCALL _delivery_GetApplId(
#ifdef IDL_PROTOTYPES
/* [in] */ handle_t handle,
/* [out] */ trpc_byteData_t applString,
/* [out] */ idl_ulong_int *applStringLength,
/* [out] */ trpc_byteData_t address,
/* [out] */ idl_ulong_int *addressLength,
/* [out] */ error_status_t *c_status,
/* [out] */ error_status_t *f_status
#endif
);
#endif
```

```
/* [out] */ error_status_t *c_status,
/* [out] */ error_status_t *f_status
#endif
);
extern void IDL_STD_STDCALL _impTPCCDelivery(
#ifdef IDL_PROTOTYPES
/* [in] */ handle_t trpc_h,
/* [in] */ idl_long_int length,
/* [in, out] */ idl_char *dataP,
/* [in, out] */ data_header *headerP,
/* [in] */ trpc_byteData_t applAndAddress,
/* [in] */ idl_ulong_int applAndAddressLength,
/* [in] */ trpc_callbackData_t inCallbackData,
/* [in] */ idl_ulong_int numOfInCallbackData
#endif
);
globalref mon_handle_t handle;
#ifdef __VMS && (defined(__DECC) ||
defined(__cplusplus))
#pragma extern_model __save
#pragma extern_model __common_block __shr
#endif
typedef struct _delivery_v1_0_epv_t {
void ( IDL_STD_STDCALL *_delivery_GetApplId)(
#ifdef IDL_PROTOTYPES
/* [in] */ handle_t handle,
/* [out] */ trpc_byteData_t applString,
/* [out] */ idl_ulong_int *applStringLength,
/* [out] */ trpc_byteData_t address,
/* [out] */ idl_ulong_int *addressLength,
/* [out] */ error_status_t *c_status,
/* [out] */ error_status_t *f_status
#endif
);
void ( IDL_STD_STDCALL *_impTPCCDelivery)(
#ifdef IDL_PROTOTYPES
/* [in] */ handle_t trpc_h,
/* [in] */ idl_long_int length,
/* [in, out] */ idl_char *dataP,
/* [in, out] */ data_header *headerP,
/* [in] */ trpc_byteData_t applAndAddress,
/* [in] */ idl_ulong_int applAndAddressLength,
/* [in] */ trpc_callbackData_t inCallbackData,
/* [in] */ idl_ulong_int numOfInCallbackData
#endif
);
}_delivery_v1_0_epv_t;
extern rpc_if_handle_t _delivery_v1_0_c_ifspec;
extern rpc_if_handle_t _delivery_v1_0_s_ifspec;
#ifdef __VMS && (defined(__DECC) ||
defined(__cplusplus))
#pragma extern_model __restore
#endif
#ifdef __cplusplus
}
#endif
#endif
```

neworder.h

```
/* Generated by IDL compiler version DEC DCE V2.0.0-6
*/
#ifndef _neworder_v1_0_included
#define _neworder_v1_0_included
#include IDLBASE H
#include <dce\idlbase.h>
#endif
#include <dce\rpc.h>
#include "trpc/trpc.h"

#ifdef __cplusplus
extern "C" {
#endif

#ifndef nbase_v0_0_included
#include "dce\nbase.h"
#endif
#ifndef trpcImports_v0_0_included
#include "trpc\trpcImports.h"
#endif
#ifndef mon_handle_v1_0_included
#include "tpm\mon\mon_handle.h"
#endif
#ifndef tpcc_types_v1_0_included
#include "tpcc_type.h"
#endif
#include <dce\rpcexc.h>
extern EXCEPTION encina_x_transaction_aborted;
extern EXCEPTION encina_x_server_shutdown;
extern EXCEPTION encina_x_permission_denied;
extern EXCEPTION encina_x_object_not_found;
extern EXCEPTION encina_x_empty_slot1;
extern EXCEPTION encina_x_empty_slot2;
extern EXCEPTION encina_x_empty_slot3;
extern EXCEPTION encina_x_empty_slot4;
extern EXCEPTION encina_x_empty_slot5;
extern EXCEPTION encina_x_undefined_exception;
extern void IDL_STD_STDCALL _neworder_GetApplId(
#ifdef IDL_PROTOTYPES
/* [in] */ handle_t handle,
/* [out] */ trpc_byteData_t applString,
/* [out] */ idl_ulong_int *applStringLength,
/* [out] */ trpc_byteData_t address,
/* [out] */ idl_ulong_int *addressLength,
/* [out] */ error_status_t *c_status,
/* [out] */ error_status_t *f_status
#endif
);
extern void IDL_STD_STDCALL _impTPCCNewOrder(
#ifdef IDL_PROTOTYPES
/* [in] */ handle_t trpc_h,
/* [in] */ idl_long_int length,
/* [in, out] */ idl_char *dataP,
/* [in, out] */ data_header *headerP,
/* [in] */ trpc_byteData_t applAndAddress,
/* [in] */ idl_ulong_int applAndAddressLength,
/* [in] */ trpc_callbackData_t inCallbackData,
/* [in] */ idl_ulong_int numOfInCallbackData
#endif
);
#endif
```

```

#endif
);
extern void IDL_STD_STDCALL _impTPCCNOInfo(
#ifdef IDL_PROTOTYPES
    /* [in] */ handle_t trpc_h,
    /* [out] */ dbInfo_data_t *dataP,
    /* [in] */ trpc_byteData_t applAndAddress,
    /* [in] */ idl_ulong_int applAndAddressLength,
    /* [in] */ trpc_callbackData_t inCallbackData,
    /* [in] */ idl_ulong_int numOfInCallbackData
#endif
);
globalref mon_handle_t handle;
#if defined(__VMS) && (defined(__DECC) ||
defined(__cplusplus))
#pragma extern_model __save
#pragma extern_model __common_block __shr
#endif
typedef struct _neworder_v1_0_epv_t {
void ( IDL_STD_STDCALL * _neworder_GetAppId)(
#ifdef IDL_PROTOTYPES
    /* [in] */ handle_t handle,
    /* [out] */ trpc_byteData_t applString,
    /* [out] */ idl_ulong_int *applStringLength,
    /* [out] */ trpc_byteData_t address,
    /* [out] */ idl_ulong_int *addressLength,
    /* [out] */ error_status_t *c_status,
    /* [out] */ error_status_t *f_status
#endif
);
void ( IDL_STD_STDCALL * _impTPCCNewOrder)(
#ifdef IDL_PROTOTYPES
    /* [in] */ handle_t trpc_h,
    /* [in] */ idl_long_int length,
    /* [in, out] */ idl_char *dataP,
    /* [in, out] */ data_header *headerP,
    /* [in] */ trpc_byteData_t applAndAddress,
    /* [in] */ idl_ulong_int applAndAddressLength,
    /* [in] */ trpc_callbackData_t inCallbackData,
    /* [in] */ idl_ulong_int numOfInCallbackData
#endif
);
void ( IDL_STD_STDCALL * _impTPCCNOInfo)(
#ifdef IDL_PROTOTYPES
    /* [in] */ handle_t trpc_h,
    /* [out] */ dbInfo_data_t *dataP,
    /* [in] */ trpc_byteData_t applAndAddress,
    /* [in] */ idl_ulong_int applAndAddressLength,
    /* [in] */ trpc_callbackData_t inCallbackData,
    /* [in] */ idl_ulong_int numOfInCallbackData
#endif
);
} _neworder_v1_0_epv_t;
extern rpc_if_handle_t _neworder_v1_0_c_ifspec;
extern rpc_if_handle_t _neworder_v1_0_s_ifspec;
#if defined(__VMS) && (defined(__DECC) ||
defined(__cplusplus))
#pragma extern_model __restore
#endif
#endif
#endif

```

```

}
#else
#endif
#endif

```

orderstatus.h

```

/* Generated by IDL compiler version DEC DCE V2.0.0-6
*/
#ifdef _orderstatus_v1_0_included
#define _orderstatus_v1_0_included
#endif
#include <dce\idlbase.h>
#endif
#include <trpc\trpc.h>
#include "trpc/trpc.h"

#ifdef __cplusplus
extern "C" {
#endif

#ifdef nbase_v0_0_included
#include "dce\nbase.h"
#endif

#ifdef trpcImports_v0_0_included
#include "trpc\trpcImports.h"
#endif

#ifdef mon_handle_v1_0_included
#include "tpm/mon\mon_handle.h"
#endif

#ifdef tpcc_types_v1_0_included
#include "tpcc_type.h"
#endif

#include <dce\rpcexc.h>
extern EXCEPTION encina_x_transaction_aborted;
extern EXCEPTION encina_x_server_shutdown;
extern EXCEPTION encina_x_permission_denied;
extern EXCEPTION encina_x_object_not_found;
extern EXCEPTION encina_x_empty_slot1;
extern EXCEPTION encina_x_empty_slot2;
extern EXCEPTION encina_x_empty_slot3;
extern EXCEPTION encina_x_empty_slot4;
extern EXCEPTION encina_x_empty_slot5;
extern EXCEPTION encina_x_undefined_exception;
extern void IDL_STD_STDCALL _orderstatus_GetAppId(
#ifdef IDL_PROTOTYPES
    /* [in] */ handle_t handle,
    /* [out] */ trpc_byteData_t applString,
    /* [out] */ idl_ulong_int *applStringLength,
    /* [out] */ trpc_byteData_t address,
    /* [out] */ idl_ulong_int *addressLength,
    /* [out] */ error_status_t *c_status,
    /* [out] */ error_status_t *f_status
#endif
);
extern void IDL_STD_STDCALL _impTPCCOrderStatus(
#ifdef IDL_PROTOTYPES
    /* [in] */ handle_t trpc_h,
    /* [in] */ idl_long_int length,

```

```

    /* [in, out] */ idl_char *dataP,
    /* [in, out] */ data_header *headerP,
    /* [in] */ trpc_byteData_t applAndAddress,
    /* [in] */ idl_ulong_int applAndAddressLength,
    /* [in] */ trpc_callbackData_t inCallbackData,
    /* [in] */ idl_ulong_int numOfInCallbackData
#endif
);
globalref mon_handle_t handle;
#if defined(__VMS) && (defined(__DECC) ||
defined(__cplusplus))
#pragma extern_model __save
#pragma extern_model __common_block __shr
#endif
typedef struct _orderstatus_v1_0_epv_t {
void ( IDL_STD_STDCALL * _orderstatus_GetAppId)(
#ifdef IDL_PROTOTYPES
    /* [in] */ handle_t handle,
    /* [out] */ trpc_byteData_t applString,
    /* [out] */ idl_ulong_int *applStringLength,
    /* [out] */ trpc_byteData_t address,
    /* [out] */ idl_ulong_int *addressLength,
    /* [out] */ error_status_t *c_status,
    /* [out] */ error_status_t *f_status
#endif
);
void ( IDL_STD_STDCALL * _impTPCCOrderStatus)(
#ifdef IDL_PROTOTYPES
    /* [in] */ handle_t trpc_h,
    /* [in] */ idl_long_int length,
    /* [in, out] */ idl_char *dataP,
    /* [in, out] */ data_header *headerP,
    /* [in] */ trpc_byteData_t applAndAddress,
    /* [in] */ idl_ulong_int applAndAddressLength,
    /* [in] */ trpc_callbackData_t inCallbackData,
    /* [in] */ idl_ulong_int numOfInCallbackData
#endif
);
} _orderstatus_v1_0_epv_t;
extern rpc_if_handle_t _orderstatus_v1_0_c_ifspec;
extern rpc_if_handle_t _orderstatus_v1_0_s_ifspec;
#if defined(__VMS) && (defined(__DECC) ||
defined(__cplusplus))
#pragma extern_model __restore
#endif
#endif
#endif

#ifdef __cplusplus
}
#endif

#else
#endif
#endif

```

payment.h

```

/* Generated by IDL compiler version DEC DCE V2.0.0-6
*/
#ifdef _payment_v1_0_included
#define _payment_v1_0_included
#endif
#include IDLBASE_H

```

```

#include <dce\idlbase.h>
#endif
#include <dce\rpc.h>
#include "trpc/trpc.h"

#ifdef __cplusplus
extern "C" {
#endif

#ifndef nbase_v0_0_included
#include "dce\nbase.h"
#endif
#ifndef trpcImports_v0_0_included
#include "trpc\trpcImports.h"
#endif
#ifndef mon_handle_v1_0_included
#include "tpm\mon\mon_handle.h"
#endif
#ifndef tpcc_types_v1_0_included
#include "tpcc_type.h"
#endif
#include <dce\rpcexc.h>
extern EXCEPTION encina_x_transaction_aborted;
extern EXCEPTION encina_x_server_shutdown;
extern EXCEPTION encina_x_permission_denied;
extern EXCEPTION encina_x_object_not_found;
extern EXCEPTION encina_x_empty_slot1;
extern EXCEPTION encina_x_empty_slot2;
extern EXCEPTION encina_x_empty_slot3;
extern EXCEPTION encina_x_empty_slot4;
extern EXCEPTION encina_x_empty_slot5;
extern EXCEPTION encina_x_undefined_exception;
extern void IDL_STD_STDCALL _payment_GetApplId(
#ifdef IDL_PROTOTYPES
    /* [in] */ handle_t handle,
    /* [out] */ trpc_byteData_t applString,
    /* [out] */ idl_ulong_int *applStringLength,
    /* [out] */ trpc_byteData_t address,
    /* [out] */ idl_ulong_int *addressLength,
    /* [out] */ error_status_t *c_status,
    /* [out] */ error_status_t *f_status
#endif
);
extern void IDL_STD_STDCALL _impTPCCPayment(
#ifdef IDL_PROTOTYPES
    /* [in] */ handle_t trpc_h,
    /* [in] */ idl_long_int length,
    /* [in, out] */ idl_char *dataP,
    /* [in, out] */ data_header *headerP,
    /* [in] */ trpc_byteData_t applAndAddress,
    /* [in] */ idl_ulong_int applAndAddressLength,
    /* [in] */ trpc_callbackData_t inCallbackData,
    /* [in] */ idl_ulong_int numOfInCallbackData
#endif
);
globalref mon_handle_t handle;
#if defined(__VMS) && (defined(__DECC) ||
defined(__cplusplus))
#pragma extern_model __save
#pragma extern_model __common_block __shr
#endif

```

```

typedef struct _payment_v1_0_epv_t {
void ( IDL_STD_STDCALL * _payment_GetApplId) (
#ifdef IDL_PROTOTYPES
    /* [in] */ handle_t handle,
    /* [out] */ trpc_byteData_t applString,
    /* [out] */ idl_ulong_int *applStringLength,
    /* [out] */ trpc_byteData_t address,
    /* [out] */ idl_ulong_int *addressLength,
    /* [out] */ error_status_t *c_status,
    /* [out] */ error_status_t *f_status
#endif
);
void ( IDL_STD_STDCALL * _impTPCCPayment) (
#ifdef IDL_PROTOTYPES
    /* [in] */ handle_t trpc_h,
    /* [in] */ idl_long_int length,
    /* [in, out] */ idl_char *dataP,
    /* [in, out] */ data_header *headerP,
    /* [in] */ trpc_byteData_t applAndAddress,
    /* [in] */ idl_ulong_int applAndAddressLength,
    /* [in] */ trpc_callbackData_t inCallbackData,
    /* [in] */ idl_ulong_int numOfInCallbackData
#endif
);
};
extern rpc_if_handle_t _payment_v1_0_c_ifspec;
extern rpc_if_handle_t _payment_v1_0_s_ifspec;
#if defined(__VMS) && (defined(__DECC) ||
defined(__cplusplus))
#pragma extern_model __restore
#endif

#ifdef __cplusplus
}
#else
#endif
#endif

stocklevel.h
/* Generated by IDL compiler version DEC DCE V2.0.0-6
*/
#ifndef _stocklevel_v1_0_included
#define _stocklevel_v1_0_included
#endif
#include <dce\idlbase.h>
#include <dce\rpc.h>
#include "trpc/trpc.h"

#ifdef __cplusplus
extern "C" {
#endif

#ifndef nbase_v0_0_included
#include "dce\nbase.h"
#endif
#ifndef trpcImports_v0_0_included
#include "trpc\trpcImports.h"

```

```

#endif
#ifndef mon_handle_v1_0_included
#include "tpm\mon\mon_handle.h"
#endif
#ifndef tpcc_types_v1_0_included
#include "tpcc_type.h"
#endif
#include <dce\rpcexc.h>
extern EXCEPTION encina_x_transaction_aborted;
extern EXCEPTION encina_x_server_shutdown;
extern EXCEPTION encina_x_permission_denied;
extern EXCEPTION encina_x_object_not_found;
extern EXCEPTION encina_x_empty_slot1;
extern EXCEPTION encina_x_empty_slot2;
extern EXCEPTION encina_x_empty_slot3;
extern EXCEPTION encina_x_empty_slot4;
extern EXCEPTION encina_x_empty_slot5;
extern EXCEPTION encina_x_undefined_exception;
extern void IDL_STD_STDCALL _stocklevel_GetApplId(
#ifdef IDL_PROTOTYPES
    /* [in] */ handle_t handle,
    /* [out] */ trpc_byteData_t applString,
    /* [out] */ idl_ulong_int *applStringLength,
    /* [out] */ trpc_byteData_t address,
    /* [out] */ idl_ulong_int *addressLength,
    /* [out] */ error_status_t *c_status,
    /* [out] */ error_status_t *f_status
#endif
);
extern void IDL_STD_STDCALL _impTPCCStockLevel(
#ifdef IDL_PROTOTYPES
    /* [in] */ handle_t trpc_h,
    /* [in] */ idl_long_int length,
    /* [in, out] */ idl_char *dataP,
    /* [in, out] */ data_header *headerP,
    /* [in] */ trpc_byteData_t applAndAddress,
    /* [in] */ idl_ulong_int applAndAddressLength,
    /* [in] */ trpc_callbackData_t inCallbackData,
    /* [in] */ idl_ulong_int numOfInCallbackData
#endif
);
globalref mon_handle_t handle;
#if defined(__VMS) && (defined(__DECC) ||
defined(__cplusplus))
#pragma extern_model __save
#pragma extern_model __common_block __shr
#endif
typedef struct _stocklevel_v1_0_epv_t {
void ( IDL_STD_STDCALL * _stocklevel_GetApplId) (
#ifdef IDL_PROTOTYPES
    /* [in] */ handle_t handle,
    /* [out] */ trpc_byteData_t applString,
    /* [out] */ idl_ulong_int *applStringLength,
    /* [out] */ trpc_byteData_t address,
    /* [out] */ idl_ulong_int *addressLength,
    /* [out] */ error_status_t *c_status,
    /* [out] */ error_status_t *f_status
#endif
);
void ( IDL_STD_STDCALL * _impTPCCStockLevel) (
#ifdef IDL_PROTOTYPES

```

```

/* [in] */ handle_t trpc_h,
/* [in] */ idl_long_int length,
/* [in, out] */ idl_char *dataP,
/* [in, out] */ data_header *headerP,
/* [in] */ trpc_byteData_t applAndAddress,
/* [in] */ idl_ulong_int applAndAddressLength,
/* [in] */ trpc_callbackData_t inCallbackData,
/* [in] */ idl_ulong_int numOfInCallbackData
#endif
);
}_stocklevel_v1_0_epv_t;
extern rpc_if_handle_t _stocklevel_v1_0_c_ifspec;
extern rpc_if_handle_t _stocklevel_v1_0_s_ifspec;
#if defined(__VMS) && (defined(__DECC) ||
defined(__cplusplus))
#pragma extern_model __restore
#endif

#ifdef __cplusplus
}
#else
#endif
#endif

```

client_utils.c

```

/* client_utils.c
*/

#include <stdio.h>
#include <time.h>
#include <windows.h>
#include <winperf.h>
#include <winsock.h>
#include "client_utils.h"

#define Li2Double(x) ((double)((x).HighPart) *
4.294967296E9 + (double)((x).LowPart))

static LARGE_INTEGER pFreq;
static double sFreq;
static int print_thread_id = 1;
static int user_id = 0;
static char *user_code = "C";

/*
 * get_thread_id
 * A function that returns the thread ID of the
current thread
*/
static int get_thread_id()
{
return(GetCurrentThreadId());
}

/*
 * get_prefix
 * Format the output prefix for printing:

```

```

* It contains the user_id, 'C' or 'T'
depending on whether it
* is a terminal or a client and optional a
thread identifier
* The prefix is written in the buffer passed
in by the caller.
*/
static void get_prefix(char *buffer)
{
if (print_thread_id) {
int thread_id = get_thread_id();
sprintf(buffer, "%s(%d-%s-
%d)%s",
user_id < 10 ? " " : user_id <
100 ? " " : "",
user_id,
user_code,
thread_id,
thread_id < 10 ? " " : "");
} else {
sprintf(buffer, "%s(%2d-%s)",
user_id < 10 ? " " : "", user_id,
user_code);
}
}

/*
 * err_printf
 * A var-arg function that appends the current
time and
* other data to the print request and sends it
to stderr
* if it is not a web client, to a file if it is
*/
void err_printf(char *format, ...)
{
time_t cur_time;
char time_str[30];
char line_prefix[50];
va_list ap;

va_start(ap, format);

cur_time = time(&cur_time);
strftime(time_str, 29, "%X",
localtime(&cur_time));

get_prefix(line_prefix);

fprintf(ERROROUT, "%s %s - ", line_prefix,
time_str);
vfprintf(ERROROUT, format, ap);
fflush(ERROROUT);

va_end(ap);
}

/*
 * encina_error_message
 *

```

```

* Report an encina error message by interpreting it
and writing
* it to both the logfile (if any) and to standard
error
*/
void encina_error_message(char *msg, unsigned long n)
{
char errorMsg[ENCINA_MAX_STATUS_STRING_SIZE];
encina_StatusToString(n,
errorMsg);
ENCINA_MAX_STATUS_STRING_SIZE, errorMsg);
err_printf("ERROR: %s. Error code = %s (%d 0x%x)
\n", msg, errorMsg, n, n);
}

int get_time_init()
{
QueryPerformanceFrequency(&pFreq);
sFreq=Li2Double(pFreq);
return 0;
}

int get_local_time(time_type *timeP)
{
double cur_t;
LARGE_INTEGER counter;

QueryPerformanceCounter(&counter);
cur_t = Li2Double(counter) / sFreq;
timeP->sec = (long)cur_t;
/* timeP->usec = ((long)cur_t - timeP->sec) *
1000000;*/
timeP->usec = (long)((cur_t - timeP->sec) *
1000000);
return 0;
}

/*
 * time_diff_ms
 * Return the difference in milliseconds between
two times
*/
int time_diff_ms(struct timeval *t2, struct timeval
*t1)
{
int t_diff;

t_diff = (t2->tv_usec + 1000000 - t1->tv_usec +
500) / 1000 +
(t2->tv_sec - t1->tv_sec - 1) * 1000;

return(t_diff);
}

/*
 * perfClntDataInit:
 * Initialization for the shared file mapping.
 *
 * return: pointer to the shared memory space
 *
 * This routine creates a named mapped memory section
that is used

```

```

* to communicate the TPCC performance data to the
extensible
* counter DLL for NT perfmon.
*/
total_tran_count_t *perfClntDataInit()
{
    HANDLE hMappedObject;
    total_tran_count_t *pClntInfo = NULL;
    TCHAR szMappedObjectName[] =
TEXT("TPCC_CLNT_COUNTER_BLOCK");

    /* create named section for the performance
data */
    hMappedObject =
CreateFileMapping((HANDLE)0xFFFFFFFF,
    NULL,
    PAGE_READWRITE,
    0,
    sizeof(total_tran_count_t),
    szMappedObjectName);
    if (hMappedObject == NULL) {
        err_printf("perfClntDataInit:
CreateFileMapping failed %x\n",
            GetLastError());
    } else {
        pClntInfo = NULL;
        /* map the section and assign the counter
block pointer
* to this section of memory
*/
        pClntInfo = (total_tran_count_t *)
MapViewOfFile(hMappedObject,
                FILE_MAP_ALL_ACCESS,
                0,
                0,
                0);
        if (pClntInfo == NULL) {
            err_printf("perfClntDataInit:
MapViewOfFile failed %x\n",
                GetLastError());
        } else {
            err_printf("perfClntDataInit:
MapViewOfFile success %n");
        }
    }
    return(pClntInfo);
}

```

client_utils.h

```

#ifndef TPCC_CLIENT_UTILS_H
#define TPCC_CLIENT_UTILS_H

#include <stdio.h>
#include <time.h>
#include <dce/rpc.h>
#include <dce/dce_error.h>
#include <encina/encina.h>

```

```

#include <stdlib.h>
#include <utils/trace.h>
#include <winsock.h>
#include "mon_client.h"
#include "../include/tpcc_type.h"

extern FILE * errtpcc;
extern FILE * logtpcc;
extern int debug;
extern char log_file_name[];
extern void logprintf( char *format, ...);
extern void err_printf( char *format, ...);
extern void encina_error_message(char *msg, unsigned
long n);
extern int time_diff_ms(struct timeval *t2, struct
timeval *t1);

typedef struct {
    int num;
    int errs;
    double RTtotal[2]; // 1 for server RT and 0 for
client RT
    int RTcount;
} tran_info_t;

/*
* total_tran_count_t
*
* structure that holds the total count of
transaction of each type
* as well as the reposne times.
*/
typedef struct {
    tran_info_t tran[MAX_TRAN_TYPE + 1];
    int errors;
    double time;
} total_tran_count_t;

/* enc_status_t
* structure that holds error information
*/
typedef struct {
    int status;
    int line;
    char file[268];
    unsigned long encinaError;
    char errorMsg[ENCINA_MAX_STATUS_STRING_SIZE];
} enc_status_t;

#define FALSE 0
#define TRUE 1

#define DPRINT(args) if (0) err_printf args

#define CHECK_ENVIRON(str,var) if (str == NULL) {
fprintf(ERROROUT, \
        "%s environment variable is
not defined.\n",var); }

```

```

#define CHK_STATUS(st, val, _errMsg)
\
    if(st) {
\
        enc_status.status=val;
\
        strcpy(enc_status.file, __FILE__);
\
        enc_status.line= __LINE__;
\
        enc_status.encinaError = st;
\
        if(_errMsg)strcpy(enc_status.errorMsg,
_errMsg);
        if(st!=1) return;
\
    }

#define UTIL_IDENT(a)          a

#if ENCINA_C_ANSI_STRING_TOKEN_SUPPORT
#define UTIL_STRING(a)        # a
#define UTIL_CONCAT(a, b)    a ## b
#else /* ENCINA_C_ANSI_STRING_TOKEN_SUPPORT */
#define UTIL_STRING(a)        "a"
#define UTIL_CONCAT(a, b)    UTIL_IDENT(a)b
#endif /* ENCINA_C_ANSI_STRING_TOKEN_SUPPORT */

/* ENCINA_CALL: Make fail-fast calls on the various
services. */
#define ENCINA_CALL(proc_name,call) \
{ \
    unsigned long _status; \
    ENCINA_CALL_RC(proc_name,call, _status); \
    if (_status) exit_program(_status); \
}

#define ENCINA_CALL_RC(proc_name,call,rc) \
{ \
    char _errorMsg[ENCINA_MAX_STATUS_STRING_SIZE]; \
    DPRINT(("ENCINA_CALL_RC: before call %s\n", \
proc_name)); \
    rc = (call); \
    DPRINT(("ENCINA_CALL_RC: after call %s\n", \
proc_name)); \
    if (rc) { \
        encina_StatusToString(rc, \
ENCINA_MAX_STATUS_STRING_SIZE, \
            _errorMsg); \
        err_printf( "%x \n", rc); \
        err_printf( "%s \n", _errorMsg); \
    } \
}

```



```

err_printf( "%s \n", proc_name);
\
}
\
}

void err_printf(char *format, ...);
void encina_error_message(char *msg, unsigned long
n);
int get_time_init();
int get_local_time(time_type *timeP);
int time_diff_ms(struct timeval *t2, struct timeval
*t1);

#endif /* TPCC_CLIENT_UTILS_H */

```

databuf.h

```

/*
 * databuf.h
 *
 * $Revision: 1.1 $
 * $Date: 1998/11/06 21:10:11 $
 * $Log: databuf.h,v $
 * Revision 4.2 95/05/16 10:55:31 10:55:31 tpcc
(TPCC Benchmark)
 * Added necessary RCS ident strings
 *
 * Revision 4.1 95/05/09 15:21:02 15:21:02 strue
(Scott Truesdale)
 * New code from Transarc - initial version
 *
 * Revision 3.2 95/04/03 17:43:09 17:43:09 strue
(Scott Truesdale)
 * Changes from Transarc - added sql error handling
in client; cleaned up debug handling with macros;
added check on db paramters via call to server.
 *
 * Revision 3.1 95/04/03 15:10:30 15:10:30 strue
(Scott Truesdale)
 * Base of rev 3 - shipped to transarc
 *
 *
 *
 * $TALog: databuf.h,v $
 * Revision 1.1 1998/11/06 21:10:11 dongfeng
 * - Move all files common to client and server to
tpcc/common
 * directory
 * [added by delta dongfeng-23677-TPCC-new-directory-
structures, r1.1]
 *
 * Revision 1.3 1998/10/22 15:33:04 wenjian
 * Make changes to Encina server code to connect with
SQL server and add
 * callsql.c and sql directory.
 *
 * Add ERR_BAD_ITEM_ID, which is returned by SLQnew
and same as INVALID_NEWO

```

```

 * [from r1.2 by delta wenjian-23529-TPCC-integrate-
with-SQL-server, r1.1]
 *
 * Revision 1.2 1998/01/23 15:07:47 oz
 * - Updated the SP TPCC directory to the latest
files used
 * during the SP tpcc audit.
 * [from r1.1 by delta oz-20774-TPCC-update-to-
latest-SP-version-11-27, r1.1]
 *
 * Revision 1.1 1997/04/20 11:57:57 oz
 * - This is the code base modified at IBM
Poughkeepsie
 * by Ofer Zajicek and Radha Sivaramakrishnan for
the
 * SP scaling test for TPCC.
 * [added by delta oz-19782-TPCC-add-ibm-sp-code,
r1.1]
 *
 * Revision 1.31 1995/10/30 19:10:54 oz
 * [merge of changes from 1.29 to 1.30 into 1.27]
 *
 * Revision 1.30 1995/10/27 15:41:30 oz
 * - Modified the tpc-c code to work with the new
informix
 * sql code that is in ex_trans.ec
 * [from r1.29 by delta oz-16761-TPCC-modify-code-to-
work-with-oracle, r1.1]
 *
 * Revision 1.27 1995/10/20 18:44:30 ctipper
 * [merge of changes from 1.17 to 1.25 into 1.22]
 *
 * Revision 1.25 1995/10/20 18:15:34 ctipper
 * Incorporate changes per code review.
 *
 * - add DISTRIBUTED_TRAN_FAILED,
TPCC_DB_INFO_PARTIAL, and
 * TPCC_DB_INFO_FAILED error codes to tpcc_rc_t
 * - got rid of MAX_NUM_SERVERS variables
 * [from r1.23 by delta ctipper-16547-TPCC-more-
distributed-trans, r1.2]
 *
 * Revision 1.23 1995/10/13 17:00:26 ctipper
 * This delta encompasses all changes necessary to do
distributed, XA
 * transactions with the TPCC benchmark. This
includes the changes
 * necessary to build with Informix version 6.
 *
 * Each client still talks to only one server,
however, if a distributed
 * transaction is necessary, the client sends the
request to a different
 * interface of that server which then forwards all
or part of the
 * request on to the appropriate remote server.
 *
 * - added new error codes to the tpcc_rc_t
enumeration.
 * - defined MAX_NUM_SERVERS to be 10

```

```

 * [from r1.19 by delta ctipper-16547-TPCC-more-
distributed-trans, r1.1]
 *
 * Revision 1.19 1995/09/20 21:02:39 oz
 * -Corrected code for the payment transaction
 * - The distributed case now no longer uses
 * stored procedures
 * [from r1.18 by delta oz-16547-TPCC-add-
distributed-transactions, r1.2]
 *
 * Revision 1.18 1995/09/20 17:51:10 oz
 * - Added distributed transactions for the new order
and
 * payment transaction
 *
 * - Added new error codes
 * [from r1.17 by delta oz-16547-TPCC-add-
distributed-transactions, r1.1]
 *
 * Revision 1.22 1995/10/02 20:31:07 oz
 * - Corrected definition of ERROR()
 * [from r1.21 by delta oz-16638-tpcc-modify-
terminal-for-RTE, r1.3]
 *
 * Revision 1.21 1995/10/02 18:51:45 oz
 * - Added definitions needed for utils.c and
liberty.c
 * [from r1.20 by delta oz-16638-tpcc-modify-
terminal-for-RTE, r1.2]
 *
 * Revision 1.20 1995/10/02 15:52:35 oz
 * - Modified the TPC-C benchmark to be compatible
with the RTE.
 * - There are now 3 terminal processes:
 * emulator: the old terminal process with a
built in
 * simple emulator
 * curses: An interactive terminal process using
curses
 * liberty: An interactive terminal process to be
used with
 * the RTE compatible with the liberty
freedom terminal.
 *
 * - Define TRUE and FALSE only if they are not
already defined.
 * (curses.h defines TRUE)
 * - Removed READ_TO_DATE and YEAR_TO_SECOND
 * - Added term_type_t
 * - Added
 * GOOD_INPUT (0)
 * WRONG_INPUT (10)
 * [from r1.17 by delta oz-16638-tpcc-modify-
terminal-for-RTE, r1.1]
 *
 * Revision 1.17 1995/07/28 15:28:23 oz
 * - Added a -null and -no_marshallng option to TPCC
 *
 * - Added INVALID_TRAN_TYPE return code
 * [from r1.16 by delta oz-16070-TPCC-add-null-and-
marshalling-test, r1.1]

```

```

*
* Revision 1.16 1995/07/18 17:02:38 oz
* - Added a DCE_ERROR error code
* [from r1.15 by delta oz-15938-TPCC-add-dce-only-
client, r1.1]
*
* Revision 1.15 1995/05/22 19:50:48 shl
* [merge of changes from 1.12 to 1.13 into 1.14]
*
* Revision 1.13 1995/05/18 15:11:27 oz
* [from r1.12 by delta oz-15290-TPCC-incorporate-hp-
drop-of-05-16-95, r1.1]
*
* Revision 1.14 1995/05/22 17:26:35 ctipper
* [merge of changes from 1.5 to 1.9 into 1.11]
*
* [*** log entries omitted ***]
*
*/

#ifndef TPCC_DATABUF_H
#define TPCC_DATABUF_H

#define I_NAME_LEN 24
#define I_DATA 50
#define W_NAME_LEN 10
#define ADDR_LEN 20
#define STATE_LEN 2
#define ZIP_LEN 9
#define DIST_INFO_LEN 24
#define S_DATA_LEN 50
#define D_NAME_LEN 10
#define H_DATA_LEN 24
#define CARRIER_LEN 2
#define C_LAST_LEN 17
#define C_MID_LEN 2
#define PHONE_LEN 16
#define CREDIT_LEN 2
#define C_DATA_LEN 500
#define BC_DTA_LEN 23

#define YEAR_TO_DATE 1
#define YEAR_TO_SECOND 2

#define ERROR(x) fprintf(stderr, "Error:
%s\n", #x), exit(11)

#define MAX_STR_LEN 255
#define MAX_OL 15

#ifndef TRUE
#define TRUE 1
#endif
#ifndef FALSE
#define FALSE 0
#endif

#define CANCEL -1

#define DATETIME_LEN 19

```

```

#define D_PER_W 10

#define COLLECTOR 1 /* ctipper
5/3/95 */

#define ERR_BAD_ITEM_ID 1 /* copied from sql/tpcc.h
*/
#define RPC_ERROR -2
#define SUCCESS_CODE 0

#define CHAR_NULL '\0' /* strue
1/23/95 */

typedef enum {
liberty_term,
curses_term,
emulator_term
} term_type_t;

typedef enum {
GOOD_INPUT = 0,

SQL_ERROR = 2,
DCE_ERROR = 4,
NO_SUCH_LAST_NAME = 5,
INVALID_TRAN_TYPE = 6,
INVALID_HANDLE = 7,

WRONG_INPUT = 10,

DISTRIBUTED_TRAN_FAILED = 15,

TPCC_DB_INFO_PARTIAL = 20,
TPCC_DB_INFO_FAILED,

TPCC_ERROR_BEGIN_NEWO = 110,

TPCC_ERROR_DECL_NEWO_SEL_ITEM,
TPCC_ERROR_OPEN_NEWO_SEL_ITEM,
TPCC_ERROR_OPEN_DIST_NEWO_SEL_ITEM,
TPCC_ERROR_FETCH_NEWO_SEL_ITEM,
TPCC_ERROR_FETCH_DIST_NEWO_SEL_ITEM,
TPCC_ERROR_PREP_NEWO_SEL_STCK,
TPCC_ERROR_DECL_NEWO_SEL_STCK,
TPCC_ERROR_OPEN_NEWO_SEL_STCK,
TPCC_ERROR_OPEN_DIST_NEWO_SEL_STCK,
TPCC_ERROR_FETCH_NEWO_SEL_STCK,
TPCC_ERROR_FETCH_DIST_NEWO_SEL_STCK,
TPCC_ERROR_NEWO_SELECT,
TPCC_ERROR_NEWO_UPD_STCK,
TPCC_ERROR_DIST_NEWO_UPD_STCK,
TPCC_ERROR_NEWO_SELECT_2,
TPCC_ERROR_DECL_NEWO_SEL_CUST,
TPCC_ERROR_OPEN_NEWO_SEL_CUST,
TPCC_ERROR_OPEN_DIST_NEWO_SEL_CUST,
TPCC_ERROR_FETCH_NEWO_SEL_CUST,
TPCC_ERROR_FETCH_DIST_NEWO_SEL_CUST,
TPCC_ERROR_DECL_NEWO_SEL_DIST,
TPCC_ERROR_OPEN_NEWO_SEL_DIST,
TPCC_ERROR_OPEN_DIST_NEWO_SEL_DIST,
TPCC_ERROR_FETCH_NEWO_SEL_DIST,

```

```

TPCC_ERROR_FETCH_DIST_NEWO_SEL_DIST,
TPCC_ERROR_PREP_NEWO_INS_OL,
TPCC_ERROR_DECL_NEWO_INS_OL,
TPCC_ERROR_OPEN_NEWO_INS_OL,
TPCC_ERROR_OPEN_DIST_NEWO_INS_OL,
TPCC_ERROR_PUT_NEWO_INS_OL,
TPCC_ERROR_PUT_DIST_NEWO_INS_OL,
TPCC_ERROR_DECL_NEWO_SEL_WARE,
TPCC_ERROR_OPEN_NEWO_SEL_WARE,
TPCC_ERROR_OPEN_DIST_NEWO_SEL_WARE,
TPCC_ERROR_FETCH_NEWO_SEL_WARE,
TPCC_ERROR_FETCH_DIST_NEWO_SEL_WARE,
TPCC_ERROR_EXECUTE_NEWO_UPD_INS,
TPCC_ERROR_UPDATE_NEWO_NEXT_OID,
TPCC_ERROR_PREP_NEWO_INS,
TPCC_ERROR_EXECUTE_DIST_NEWO_INS,
TPCC_ERROR_EXECUTE_NEWO_COMMIT,
TPCC_ERROR_ROLLBACK_NEWO,
TPCC_ERROR_REMOTE_OL_SELECT,
TPCC_ERROR_REMOTE_OL_UPDATE,

TPCC_ERROR_OPEN_ORDS_CNT_CID = 200,
TPCC_ERROR_FETCH_ORDS_CNT_CID,
TPCC_ERROR_OPEN_ORDS_SEL_CLAST,
TPCC_ERROR_FETCH_ORDS_SEL_CLAST,
TPCC_ERROR_OPEN_ORDS_SEL_CID,
TPCC_ERROR_FETCH_ORDS_SEL_CID,
TPCC_ERROR_OPEN_ORDS_SEL_OLDORD,
TPCC_ERROR_FETCH_ORDS_OLDORD,
TPCC_ERROR_OPEN_ORDS_SEL_OL,
TPCC_ERROR_FETCH_ORDS_SEL_OL,
TPCC_ERROR_EXECUTE_ORDS_COMMIT,

TPCC_ERROR_OPEN_DELIVERY_OLDEST_OID = 300,
TPCC_ERROR_FETCH_DELIVERY_OLDEST_OID,
TPCC_ERROR_EXECUTE_DELIVERY_COMMIT,
TPCC_ERROR_OPEN_DELIVERY_SEL_ORD,
TPCC_ERROR_FETCH_DELIVERY_SEL_ORD,
TPCC_ERROR_OPEN_DELIVERY_SEL_SUM_OL,
TPCC_ERROR_FETCH_DELIVERY_SEL_SUM_OL,
TPCC_ERROR_EXECUTE_DELIVERY_EXEC_DVRY,
TPCC_ERROR_SELECT_DELIVERY_ORDER_ID,
TPCC_ERROR_SELECT_DELIVERY_CARRIER_ID,
TPCC_ERROR_SELECT_DELIVERY_BALANCE,

TPCC_ERROR_OPEN_STOCKLEVEL_SEL_OID = 400,
TPCC_ERROR_FETCH_STOCKLEVEL_SEL_OID,
TPCC_ERROR_OPEN_STOCKLEVEL_CNT_SID,
TPCC_ERROR_FETCH_STOCKLEVEL_CNT_SID,
TPCC_ERROR_OPEN_STOCKLEVEL_FIND,
TPCC_ERROR_FETCH_STOCKLEVEL_FIND,
TPCC_ERROR_EXECUTE_STOCKLEVEL_COMMIT,

TPCC_ERROR_OPEN_PAYMENT_CNT_CID = 500,
TPCC_ERROR_FETCH_PAYMENT_CNT_CID,
TPCC_ERROR_OPEN_PAYMENT_SEL_CLAST,
TPCC_ERROR_FETCH_PAYMENT_SEL_CLAST,
TPCC_ERROR_OPEN_PAYMENT_SEL_CID,
TPCC_ERROR_FETCH_PAYMENT_SEL_CID,
TPCC_ERROR_DECL_PAYMENT_SEL_DIST,
TPCC_ERROR_OPEN_PAYMENT_SEL_DIST,

```

```

TPCC_ERROR_OPEN_DIST_PAYMENT_SEL_DIST,
TPCC_ERROR_FETCH_PAYMENT_SEL_DIST,
TPCC_ERROR_FETCH_DIST_PAYMENT_SEL_DIST,
TPCC_ERROR_DECL_PAYMENT_SEL_WARE,
TPCC_ERROR_OPEN_PAYMENT_SEL_WARE,
TPCC_ERROR_OPEN_DIST_PAYMENT_SEL_WARE,
TPCC_ERROR_FETCH_PAYMENT_SEL_WARE,
TPCC_ERROR_FETCH_DIST_PAYMENT_SEL_WARE,
TPCC_ERROR_EXECUTE_PAYMENT_UPD_CUST_LAST,
TPCC_ERROR_EXECUTE_PAYMENT_UPD_CUST_ID,
TPCC_ERROR_COMMIT_PAYMENT_UPD_CUST,
TPCC_ERROR_SELECT_PAYMENT_W_YTD,
TPCC_ERROR_SELECT_PAYMENT_D_YTD,
TPCC_ERROR_BEGIN_PAYMENT,
TPCC_ERROR_EXECUTE_PAYMENT_COMMIT,
TPCC_ERROR_PAYMENT_UPD_CUST_BY_NAME,
TPCC_ERROR_PAYMENT_UPD_CUST_BY_ID,
TPCC_ERROR_PAYMENT_UPDATE_DIST,
TPCC_ERROR_PAYMENT_UPDATE_WH,
TPCC_ERROR_PAYMENT_INSERT_HISTORY,
TPCC_ERROR_EXECUTE_PAYMENT_WH_DIST
} tpcc_rc_t;

typedef enum {
    TPCC_DEADLOCK_MSG = 10,
    TPCC_RETRY_MSG
} tpcc_msg_t;

#endif /* __TPCC_DATABUF_H__ */

```

delivery.h

```

#ifndef TRANSARC_delivery_h
#define TRANSARC_delivery_h

#include <trpc/trpc.h>
#include "delivery.h"

#include <encina/c_prologue.h>

#if defined(BUILDDLL)
#define DLLEXPORT __declspec( dllexport )
#else
#define DLLEXPORT extern
#endif

#ifndef ENCINA_STUB_CALLING
#define ENCINA_STUB_CALLING ENCINA_RPC_CALLING
#endif

#define delivery_v1_0_c_ifspec
    delivery_v1_0_c_ifspec
#define delivery_v1_0_s_ifspec
    delivery_v1_0_s_ifspec

typedef struct delivery_v1_0_epv {
void (ENCINA_STUB_CALLING *impTPCCDelivery) (
#ifdef IDL_PROTOTYPES

```

```

    idl_long_int length,
    idl_char *dataP,
    data_header *headerP,
    trpc_status_t *trpcStatus
#endif
);

} delivery_v1_0_epv_t;

DLLEXPORT void ENCINA_STUB_CALLING impTPCCDelivery (
#ifdef IDL_PROTOTYPES
    idl_long_int length,
    idl_char *dataP,
    data_header *headerP,
    trpc_status_t *trpcStatus
#endif
);

trpc_handle_t          ENCINA_CALLING
mon_handle_t_tranBind(
#ifdef IDL_PROTOTYPES
    mon_handle_t          handle,
    trpc_tranInfo_t      *tranInfoP,
    trpc_ifSpec_t        *ifSpecP
#endif
);

void          ENCINA_CALLING mon_handle_t_tranUnBind(
#ifdef IDL_PROTOTYPES
    mon_handle_t          handle,
    trpc_handle_t        trpcHandle,
    trpc_tranInfo_t      *tranInfoP,
    trpc_ifSpec_t        *ifSpecP
#endif
);

trpc_handle_t          ENCINA_CALLING
mon_handle_t_tranBind(
#ifdef IDL_PROTOTYPES
    mon_handle_t          handle,
    trpc_tranInfo_t      *tranInfoP,
    trpc_ifSpec_t        *ifSpecP
#endif
);

void          ENCINA_CALLING mon_handle_t_tranUnBind(
#ifdef IDL_PROTOTYPES
    mon_handle_t          handle,
    trpc_handle_t        trpcHandle,
    trpc_tranInfo_t      *tranInfoP,
    trpc_ifSpec_t        *ifSpecP
#endif
);

extern delivery_v1_0_epv_t
    delivery_v1_0_client_epv;
extern _delivery_v1_0_epv_t
    delivery_v1_0_manager_epv;
extern rpc_mgr_epv_t
    delivery_v1_0_mgr_epv;

```

```

#include <encina/c_epilogue.h>
#endif /* TRANSARC_delivery_h */

```

dlldata.c

```

/*****
****
DllData file -- generated by MIDL compiler

DO NOT ALTER THIS FILE

This file is regenerated by MIDL on every IDL file
compile.

To completely reconstruct this file, delete it and
rerun MIDL
on all the IDL files in this DLL, specifying this
file for the
/dlldata command line option

****/

#include <rpcproxy.h>

#ifdef __cplusplus
extern "C" {
#endif

EXTERN_PROXY_FILE( tpcc_com_ps )

PROXYFILE_LIST_START
/* Start of list */
REFERENCE_PROXY_FILE( tpcc_com_ps ),
/* End of list */
PROXYFILE_LIST_END

DLLDATA_ROUTINES( aProxyFileList, GET_DLL_CLSID )

#ifdef __cplusplus
} /*extern "C" */
#endif

/* end of generated dlldata file */

```

install.c

```

/* FILE: INSTALL.C
*
* Microsoft
* TPC-C Kit Ver. 4.51.000
* Copyright
* Microsoft, 2003
* All Rights Reserved
*
* not audited

```

```

*
* PURPOSE: Automated installation
application for TPC-C Web Kit
* Contact: Charles Levine
(clevine@microsoft.com)
*
* Change history:
* 4.20.000 - added COM installation
steps
* 4.50.000 - added IIS6 configuration options
* 4.51.000 - added routines to copy
Visual Studio runtime module (MSVCR70.DLL)
* to
SystemRoot\System32
*/

#include <windows.h>
#include <direct.h>
#include <io.h>
#include <stdlib.h>
#include <stdio.h>
#include <commctrl.h>
#include "..\..\common\src\ReadRegistry.h"
#include <process.h>

#include "resource.h"

#define WM_INITTEXT WM_USER+100

HICON hIcon;
HINSTANCE hInst;

DWORD versionExeMS;
DWORD versionExeLS;
DWORD versionExeMM;
DWORD versionDllMS;
DWORD versionDllLS;

// TPC-C registry settings
TPCCREGISTRYDATA Reg;

static int iPoolThreadLimit;
static int iMaxPoolThreads;
static int iThreadTimeout;
static int iListenBackLog;
static int iAcceptExOutstanding;
static int iUriEnableCache;
static int iUriScavengerPeriod;
static int iMaxConnections;

static int iIISMajorVersion;
static int iNumberOfProcessors;

static int iMaxPhysicalMemory;
//max physical memory in MB
static char szLastFileName[64]; //
last file we worked on (for error reporting)

BOOL CALLBACK LicenseDlgProc(HWND hwnd, UINT
uMsg, WPARAM wParam, LPARAM lParam);

```

```

BOOL CALLBACK UpdatedDlgProc(HWND hwnd, UINT
uMsg, WPARAM wParam, LPARAM lParam);
BOOL CALLBACK MainDlgProc(HWND hwnd, UINT uMsg,
WPARAM wParam, LPARAM lParam);
BOOL CALLBACK CopyDlgProc(HWND hwnd, UINT uMsg,
WPARAM wParam, LPARAM lParam);
static void ProcessOK(HWND hwnd,
char *szDllPath, char *szWindowsPath);
static void
ReadRegistrySettings(void);
static void
WriteRegistrySettings(char *szDllPath);
static BOOL RegisterDLL(char
*szFileName);
static int
CopyFiles(HWND hDlg, char *szDllPath, char
*szWindowsPath);
static BOOL GetInstallPath(char
*szDllPath);
static BOOL
GetWindowsInstallPath(char *szWindowsPath);
static void GetVersionInfo(char
*szDLLPath, char *szExePath);
static BOOL
CheckWWWebService(void);
static BOOL
StartWWWebService(void);
static BOOL StopWWWebService(void);
static void UpdateDialog(HWND
hDlg);
static void ConfigureIIS6(HWND
hwnd, HWND hDlg);

SYSTEM_INFO siSysInfo;

BOOL install_com(char *szDllPath);

#include "..\..\common\src\ReadRegistry.cpp"

int WINAPI WinMain( HINSTANCE hInstance, HINSTANCE
hPrevInstance, LPSTR lpCmdLine, int nCmdShow )
{
    int iRc;

    hInst = hInstance;

    InitCommonControls();

    hIcon = LoadIcon(hInstance,
MAKEINTRESOURCE(IDI_ICON1));

    iRc = DialogBox(hInstance,
MAKEINTRESOURCE(IDD_DIALOG4), GetDesktopWindow(),
LicenseDlgProc);
    if ( iRc )
    {
        iRc = DialogBox(hInstance,
MAKEINTRESOURCE(IDD_DIALOG1), GetDesktopWindow(),
MainDlgProc);
        if ( iRc )
        {

```

```

        DialogBoxParam(hInstance,
MAKEINTRESOURCE(IDD_DIALOG2), GetDesktopWindow(),
UpdatedDlgProc, (LPARAM)iRc);
    }
}

DestroyIcon(hIcon);
return 0;
}

BOOL CALLBACK LicenseDlgProc(HWND hwnd, UINT uMsg,
WPARAM wParam, LPARAM lParam)
{
    HGLOBAL hRes;
    HRSRC hResInfo;
    BYTE *pSrc, *pDst;
    DWORD dwSize;
    static HFONT hFont;

    switch(uMsg)
    {
        case WM_INITDIALOG:
            hFont = CreateFont(-12,
0, 0, 0, 400, 0, 0, 0, 0, 0, 0, 0, 0, "Arial");
            SendMessage(
GetDlgItem(hwnd, IDR_LICENSE1), WM_SETFONT,
(WPARAM)hFont, MAKELPARAM(0, 0) );
            PostMessage(hwnd,
WM_INITTEXT, (WPARAM)0, (LPARAM)0);
            return TRUE;
        case WM_INITTEXT:
            hResInfo =
FindResource(hInst, MAKEINTRESOURCE(IDR_LICENSE1),
"LICENSE");
            dwSize =
SizeofResource(hInst, hResInfo);
            hRes =
LoadResource(hInst, hResInfo );
            pSrc = (BYTE
*)LockResource(hRes);
            pDst = (unsigned char
*)malloc(dwSize+1);
            if ( pDst )
            {
                memcpy(pDst,
pSrc, dwSize);
            }
            pDst[dwSize]
= 0;

            SetDlgItemText(hwnd, IDC_LICENSE, (const
char *)pDst);
            free(pDst);
        }
        else
        {
            SetDlgItemText(hwnd, IDC_LICENSE, (const
char *)pSrc);
            return TRUE;
        }
        case WM_DESTROY:
            DeleteObject(hFont);
    }
}

```

```

        return TRUE;
    case WM_COMMAND:
        if ( wParam == IDOK )
            EndDialog(hwnd, TRUE);
        if ( wParam == IDCANCEL
)
            EndDialog(hwnd, FALSE);
        default:
            break;
    }
    return FALSE;
}

BOOL CALLBACK UpdatedDlgProc(HWND hwnd, UINT uMsg,
WPARAM wParam, LPARAM lParam)
{
    switch(uMsg)
    {
        case WM_INITDIALOG:
            switch(lParam)
            {
                case 1:
                case 2:

                    SetDlgItemText(hwnd, IDC_RESULTS, "TPC-C
Web Client Installed");

                    break;
            }
            return TRUE;
        case WM_COMMAND:
            if ( wParam == IDOK )
                EndDialog(hwnd, TRUE);
            break;
        default:
            break;
    }
    return FALSE;
}

BOOL CALLBACK MainDlgProc(HWND hwnd, UINT uMsg,
WPARAM wParam, LPARAM lParam)
{
    PAINTSTRUCT ps;
    MEMORYSTATUS memoryStatus;
    OSVERSIONINFO VI;
    char szTmp[256];
    static char
szDllPath[256];
    static char
szWindowsPath[256];
    static char
szExePath[256];

    switch(uMsg)
    {
        case WM_INITDIALOG:

```

```

        GlobalMemoryStatus(&memoryStatus);
        iMaxPhysicalMemory =
(memoryStatus.dwTotalPhys/ 1048576);

        if (
GetWindowsInstallPath(szWindowsPath) )
        {
            MessageBox(hwnd, "Error: Cannot determine
Windows System Root.", NULL, MB_ICONSTOP | MB_OK);
            EndDialog(hwnd, FALSE);
            return TRUE;
        }
        if (
GetInstallPath(szDllPath) )
        {
            MessageBox(hwnd, "Error internet service
inetsrv is not installed.", NULL, MB_ICONSTOP |
MB_OK);
            EndDialog(hwnd, FALSE);
            return TRUE;
        }
        // set default values
        ZeroMemory( &Reg,
sizeof(Reg) );

        Reg.dwNumberOfDeliveryThreads = 4;
        Reg.dwMaxConnections =
100;

        Reg.dwMaxPendingDeliveries = 100;
        Reg.eDB_Protocol =
DBLIB;

        Reg.eTxnMon = None;
        strcpy(Reg.szDbServer,
"");
        strcpy(Reg.szDbName,
"tpcc");
        strcpy(Reg.szDbUser,
"sa");
        strcpy(Reg.szDbPassword,
"");

        iPoolThreadLimit =
iMaxPhysicalMemory * 2;

        iThreadTimeout = 86400;
        iListenBackLog = 15;
        iAcceptExOutstanding =
40;

        ReadTPCCRegistrySettings( &Reg );
        ReadRegistrySettings();

```

```

        // copy the hardware
information to the SYSTEM_INFO structure
        GetSystemInfo(&siSysInfo);
        // store the number of
processors on this system
        iNumberOfProcessors =
siSysInfo.dwNumberOfProcessors;

        GetModuleFileName(hInst, szExePath,
sizeof(szExePath));
        GetVersionInfo(szDllPath, szExePath);

        wsprintf(szTmp,
"Version %d.%2d.%3d", versionExeMS, versionExeMM,
versionExeLS);
        SetDlgItemText(hwnd,
IDC_VERSION, szTmp);

        SetDlgItemText(hwnd,
IDC_PATH, szDllPath);

        SetDlgItemText(hwnd,
ED_DB_SERVER, Reg.szDbServer);
        SetDlgItemText(hwnd,
ED_DB_USER_ID, Reg.szDbUser);
        SetDlgItemText(hwnd,
ED_DB_PASSWORD, Reg.szDbPassword);
        SetDlgItemText(hwnd,
ED_DB_NAME, Reg.szDbName);

        SetDlgItemInt(hwnd,
ED_THREADS, Reg.dwNumberOfDeliveryThreads, FALSE);
        SetDlgItemInt(hwnd,
ED_MAXCONNECTION, Reg.dwMaxConnections, FALSE);
        SetDlgItemInt(hwnd,
ED_MAXDELIVERIES, Reg.dwMaxPendingDeliveries, FALSE);
        SetDlgItemInt(hwnd,
ED_IIS_MAX_THREAD_POOL_LIMIT, iPoolThreadLimit,
FALSE);
        SetDlgItemInt(hwnd,
ED_IIS_THREAD_TIMEOUT, iThreadTimeout, FALSE);
        SetDlgItemInt(hwnd,
ED_IIS_LISTEN_BACKLOG, iListenBackLog, FALSE);
        SetDlgItemInt(hwnd,
ED_WEB_SERVICE_BACKLOG_QUEUE_SIZE,
iAcceptExOutstanding, FALSE);

        CheckDlgButton(hwnd,
IDC_DBLIB, 0);
        CheckDlgButton(hwnd,
IDC_ODBC, 0);
        if ( Reg.eDB_Protocol
== DBLIB )
            CheckDlgButton(hwnd, IDC_DBLIB, 1);
        else
            CheckDlgButton(hwnd, IDC_ODBC, 1);

```

```

// check OS version
level for COM. Must be at least Windows 2000
VI.dwOSVersionInfoSize
= sizeof(VI);
GetVersionEx( &VI );
if (VI.dwMajorVersion <
5)
{
    HWND hDlg =
GetDlgItem( hwnd, IDC_TM_MTS );
    EnableWindow(
hDlg, 0 ); // disable COM option
    if
(Reg.eTxnMon == COM)
        Reg.eTxnMon = None;
}
CheckDlgButton(hwnd,
IDC_TM_NONE, 0);
CheckDlgButton(hwnd,
IDC_TM_TUXEDO, 0);
CheckDlgButton(hwnd,
IDC_TM_MTS, 0);
CheckDlgButton(hwnd,
IDC_TM_ENCINA, 0);
switch (Reg.eTxnMon)
{
case None:
    CheckDlgButton(hwnd, IDC_TM_NONE, 1);
    break;
case TUXEDO:
    CheckDlgButton(hwnd, IDC_TM_TUXEDO, 1);
    break;
case ENCINA:
    CheckDlgButton(hwnd, IDC_TM_ENCINA, 1);
    break;
case COM:
    CheckDlgButton(hwnd, IDC_TM_MTS, 1);
    break;
}
return TRUE;
case WM_PAINT:
    if ( IsIconic(hwnd) )
    {
        BeginPaint( hwnd, &ps );
        DrawIcon(ps.hdc, 0, 0, hIcon);
        EndPaint( hwnd, &ps );
    }
    break;
case WM_COMMAND:

```

```

if ( HIWORD(wParam) ==
BN_CLICKED )
{
    switch(
LOWORD(wParam) )
{
case IDC_DBLIB:
    return TRUE;
case IDC_ODBC:
    return TRUE;
case IDOK:
    ProcessOK(hwnd, szDllPath, szWindowsPath);
    return TRUE;
case IDCANCEL:
    EndDialog(hwnd, FALSE);
    return TRUE;
default:
    return FALSE;
}
}
break;
default:
    break;
}
return FALSE;
}
static void ProcessOK(HWND hwnd, char *szDllPath,
char *szWindowsPath)
{
    int d;
    HWND hDlg;
    int rc;
    BOOL bSvcRunning;
    char szFullName[256];
    char szErrTxt[128];
    // read settings from dialog
    Reg.dwNumberOfDeliveryThreads =
GetDlgItemInt( hwnd, ED_THREADS, &d, FALSE );
    Reg.dwMaxConnections = GetDlgItemInt( hwnd,
ED_MAXCONNECTION, &d, FALSE );
    Reg.dwMaxPendingDeliveries =
GetDlgItemInt( hwnd, ED_MAXDELIVERIES, &d, FALSE );
    GetDlgItemText( hwnd, ED_DB_SERVER,
Reg.szDbServer, sizeof(Reg.szDbServer) );

```

```

    GetDlgItemText( hwnd, ED_DB_USER_ID,
Reg.szDbUser, sizeof(Reg.szDbUser) );
    GetDlgItemText( hwnd, ED_DB_PASSWORD,
Reg.szDbPassword, sizeof(Reg.szDbPassword) );
    GetDlgItemText( hwnd, ED_DB_NAME,
Reg.szDbName, sizeof(Reg.szDbName) );
    if ( IsDlgButtonChecked( hwnd, IDC_DBLIB ) )
    {
        Reg.eDB_Protocol = DBLIB;
        rc = 1;
    }
    else if ( IsDlgButtonChecked( hwnd,
IDC_ODBC ) )
    {
        Reg.eDB_Protocol = ODBC;
        rc = 2;
    }
    if ( IsDlgButtonChecked( hwnd, IDC_TM_NONE ) )
        Reg.eTxnMon = None;
    else if ( IsDlgButtonChecked( hwnd,
IDC_TM_TUXEDO ) )
        Reg.eTxnMon = TUXEDO;
    else if ( IsDlgButtonChecked( hwnd,
IDC_TM_MTS ) )
        Reg.eTxnMon = COM;
    else if ( IsDlgButtonChecked( hwnd,
IDC_TM_ENCINA ) )
        Reg.eTxnMon = ENCINA;
    iPoolThreadLimit = GetDlgItemInt( hwnd,
ED_IIS_MAX_THREAD_POOL_LIMIT, &d, FALSE );
    iThreadTimeout = GetDlgItemInt( hwnd,
ED_IIS_THREAD_TIMEOUT, &d, FALSE );
    iListenBackLog = GetDlgItemInt( hwnd,
ED_IIS_LISTEN_BACKLOG, &d, FALSE );
    iAcceptExOutstanding = GetDlgItemInt( hwnd,
ED_WEB_SERVICE_BACKLOG_QUEUE_SIZE, &d, FALSE );
    ShowWindow( hwnd, SW_HIDE );
    hDlg = CreateDialog( hInst,
MAKEINTRESOURCE( IDD_DIALOG3 ), hwnd, CopyDlgProc );
    ShowWindow( hDlg, SW_SHOWNA );
    UpdateDialog( hDlg );
    // check to see if the web services are
running
    bSvcRunning = CheckWWWWebService();
    if ( bSvcRunning )
    {
        SetDlgItemText( hDlg, IDC_STATUS,
"Stopping Web Service." );
        SendDlgItemMessage( hDlg,
IDC_PROGRESS1, PBM_STEPIT, 0, 0 );
        UpdateDialog( hDlg );
        StopWWWWebService();
    }

```

```

        SendDlgItemMessage(hDlg,
IDC_PROGRESS1, PBM_STEPIT, 0, 0);
        UpdateDialog(hDlg);
    }

    // write binaries to inetpub\wwwroot
    rc = CopyFiles(hDlg, szDllPath,
szWindowsPath);
    if ( !rc )
    {
        ShowWindow(hwnd, SW_SHOWNA);
        DestroyWindow(hDlg);
        strcpy( szErrTxt, "Error(s)
occured when creating " );
        strcat( szErrTxt, szLastFileName
);
        MessageBox(hwnd, szErrTxt, NULL,
MB_ICONSTOP | MB_OK);
        EndDialog(hwnd, 0);
        return;
    }

    // while we have the web services shutdown,
check to see if this
// is IIS6. If it is, then call
ConfigureIIS6
    if ( iIISMajorVersion == 6)
    {
        ConfigureIIS6(hwnd, hDlg);
    }

    //if we stopped service restart it.
    if ( bSvcRunning )
    {
        SetDlgItemText(hDlg, IDC_STATUS,
"Starting Web Service.");
        SendDlgItemMessage(hDlg,
IDC_PROGRESS1, PBM_STEPIT, 0, 0);
        UpdateDialog(hDlg);
        StartWWWebService();
    }

    // update registry
    SetDlgItemText(hDlg, IDC_STATUS, "Updating
Registry.");
    SendDlgItemMessage(hDlg, IDC_PROGRESS1,
PBM_STEPIT, 0, 0);
    UpdateDialog(hDlg);
    WriteRegistrySettings(szDllPath);

    // register com proxy stub
    strcpy(szFullName, szDllPath);
    strcat(szFullName, "tpcc_com_ps.dll");
    if (!RegisterDLL(szFullName))
    {
        ShowWindow(hwnd, SW_SHOWNA);
        DestroyWindow(hDlg);
        strcpy( szErrTxt, "Error occured
when registering " );
        strcat( szErrTxt, szFullName );

```

```

        MessageBox(hwnd, szErrTxt, NULL,
MB_ICONSTOP | MB_OK);
        EndDialog(hwnd, 0);
        return;
    }

    // if using COM
    if (Reg.eTxnMon == COM)
    {
        SetDlgItemText(hDlg, IDC_STATUS,
"Configuring COM.");
        SendDlgItemMessage(hDlg,
IDC_PROGRESS1, PBM_STEPIT, 0, 0);
        UpdateDialog(hDlg);

        if (install_com(szDllPath))
        {
            ShowWindow(hwnd,
SW_SHOWNA);
            DestroyWindow(hDlg);
            strcpy( szErrTxt,
"Error occured when configuring COM settings." );
            MessageBox(hwnd,
szErrTxt, NULL, MB_ICONSTOP | MB_OK);
            EndDialog(hwnd, 0);
            return;
        }

        Sleep(100);

        ShowWindow(hwnd, SW_SHOWNA);
        DestroyWindow(hDlg);
        EndDialog(hwnd, rc);
        return;
    }

static void ReadRegistrySettings(void)
{
    HKEY    hKey;
    DWORD   size;
    DWORD   type;

    if ( RegOpenKeyEx(HKEY_LOCAL_MACHINE,
"SOFTWARE\Microsoft\InetStp", 0, KEY_READ, &hKey)
== ERROR_SUCCESS )
    {
        size = sizeof(iIISMajorVersion);
        if ( RegQueryValueEx(hKey,
"MajorVersion", 0, &type, (char *)&iIISMajorVersion,
&size) == ERROR_SUCCESS )
            if ( !iIISMajorVersion

                iIISMajorVersion = 5;
            }

        if ( RegOpenKeyEx(HKEY_LOCAL_MACHINE,
"SYSTEM\CurrentControlSet\Services\Inetinfo\Param
eters", 0, KEY_READ, &hKey) == ERROR_SUCCESS )

```

```

        {
            if ( iIISMajorVersion == 6)
            {
                // since IIS6 handles
the pool thread parameters differently, we need to
fill in the dialog
                // with the
MaxPoolThreads rather than PoolThreadLimit
                // for ease of coding,
we are just going to stuff the value into
iPoolThreadLimit
                size = sizeof(iPoolThreadLimit);
                if (
RegQueryValueEx(hKey, "MaxPoolThreads", 0, &type,
(char *)&iPoolThreadLimit, &size) == ERROR_SUCCESS )
                    if ( !iPoolThreadLimit

                        iPoolThreadLimit = iMaxPhysicalMemory * 2;
                    }
                    else
                    {
                        size =
sizeof(iPoolThreadLimit);
                        if (
RegQueryValueEx(hKey, "MaxPoolThreads", 0, &type,
(char *)&iPoolThreadLimit, &size) == ERROR_SUCCESS )
                            if ( !iPoolThreadLimit

                                iPoolThreadLimit = iMaxPhysicalMemory * 2;
                            }

                            size = sizeof(iThreadTimeout);
                            if ( RegQueryValueEx(hKey,
"ThreadTimeout", 0, &type, (char *)&iThreadTimeout,
&size) == ERROR_SUCCESS )
                                if ( !iThreadTimeout )

                                    iThreadTimeout = 86400;

                                size = sizeof(iListenBackLog);
                                if ( RegQueryValueEx(hKey,
"ListenBackLog", 0, &type, (char *)&iListenBackLog,
&size) == ERROR_SUCCESS )
                                    if ( !iListenBackLog )

                                        iListenBackLog = 15;

                                RegCloseKey(hKey);
                            }

                            if ( RegOpenKeyEx(HKEY_LOCAL_MACHINE,
"SYSTEM\CurrentControlSet\Services\W3SVC\Paramete
rs", 0, KEY_READ, &hKey) == ERROR_SUCCESS )
                                {
                                    size =
sizeof(iAcceptExOutstanding);
                                    if ( RegQueryValueEx(hKey,
"AcceptExOutstanding", 0, &type, (char
*)&iAcceptExOutstanding, &size) == ERROR_SUCCESS )

```

```

        if (
!iAcceptExOutstanding )
            iAcceptExOutstanding = 40;
            RegCloseKey(hKey);
        }
        if ( RegOpenKeyEx(HKEY_LOCAL_MACHINE,
"SYSTEM\\CurrentControlSet\\Services\\HTTP\\Parameter
s", 0, KEY_READ, &hKey) == ERROR_SUCCESS )
        {
            size = sizeof(iUriEnableCache);
            if ( RegQueryValueEx(hKey,
"UriEnableCache", 0, &type, (char *)&iUriEnableCache,
&size) == ERROR_SUCCESS )
                if ( !iUriEnableCache )
                    iUriEnableCache = 0;

            size =
sizeof(iUriScavengerPeriod);
            if ( RegQueryValueEx(hKey,
"UriScavengerPeriod", 0, &type, (char
*)&iUriScavengerPeriod, &size) == ERROR_SUCCESS )
                if (
!iUriScavengerPeriod )
                    iUriScavengerPeriod = 10800;

            size = sizeof(iMaxConnections);
            if ( RegQueryValueEx(hKey,
"MaxConnections", 0, &type, (char *)&iMaxConnections,
&size) == ERROR_SUCCESS )
                if ( !iMaxConnections )
                    iMaxConnections = 100000;

            RegCloseKey(hKey);
        }
}

static void WriteRegistrySettings(char *szDllPath)
{
    HKEY    hKey;
    DWORD   dwDisposition;
    char    szTmp[256];
    char    *ptr;
    int     iRc;

    if ( RegCreateKeyEx(HKEY_LOCAL_MACHINE,
"SOFTWARE\\Microsoft\\TPCC", 0, NULL,
REG_OPTION_NON_VOLATILE, KEY_ALL_ACCESS, NULL, &hKey,
&dwDisposition) == ERROR_SUCCESS )
    {
        strcpy(szTmp, szDllPath);
        ptr = strstr(szTmp, "tpcc");
        if ( ptr )
            *ptr = 0;
    }
}

```

```

            RegSetValueEx(hKey, "Path", 0,
REG_SZ, szTmp, strlen(szTmp)+1);

            RegSetValueEx(hKey,
"NumberOfDeliveryThreads", 0, REG_DWORD, (char
*)&Reg.dwNumberOfDeliveryThreads,
sizeof(Reg.dwNumberOfDeliveryThreads));
            RegSetValueEx(hKey,
"MaxConnections", 0, REG_DWORD, (char
*)&Reg.dwMaxConnections,
sizeof(Reg.dwMaxConnections));
            RegSetValueEx(hKey,
"MaxPendingDeliveries", 0, REG_DWORD, (char
*)&Reg.dwMaxPendingDeliveries,
sizeof(Reg.dwMaxPendingDeliveries));

            RegSetValueEx(hKey,
"DB_Protocol", 0, REG_SZ,
szDBNames[Reg.eDB_Protocol],
strlen(szDBNames[Reg.eDB_Protocol])+1);
            RegSetValueEx(hKey, "TxnMonitor",
0, REG_SZ, szTxnMonNames[Reg.eTxnMon],
strlen(szTxnMonNames[Reg.eTxnMon])+1);

            RegSetValueEx(hKey, "DbServer",
0, REG_SZ, Reg.szDbServer, strlen(Reg.szDbServer)+1);
            RegSetValueEx(hKey, "DbName", 0,
REG_SZ, Reg.szDbName, strlen(Reg.szDbName)+1);
            RegSetValueEx(hKey, "DbUser", 0,
REG_SZ, Reg.szDbUser, strlen(Reg.szDbUser)+1);
            RegSetValueEx(hKey, "DbPassword",
0, REG_SZ, Reg.szDbPassword,
strlen(Reg.szDbPassword)+1);

            strcpy(szTmp, "YES");
            RegSetValueEx(hKey,
"COM_SinglePool", 0, REG_SZ, szTmp, strlen(szTmp)+1);

            RegFlushKey(hKey);
            RegCloseKey(hKey);
        }
    }

    if (
(iRc=RegCreateKeyEx(HKEY_LOCAL_MACHINE,
"SYSTEM\\CurrentControlSet\\Services\\Inetinfo\\Param
eters", 0, NULL, REG_OPTION_NON_VOLATILE,
KEY_ALL_ACCESS, NULL, &hKey, &dwDisposition)) ==
ERROR_SUCCESS )
    {
        // if this is IIS6, then we need
to treat the PoolThreadLimit differently
        // if IIS6, then PoolThreadLimit
is the maximum number of threads for the entire
system.
        // IIS6 added MaxPoolThreads
which controls the number of threads per processor.
For IIS6
        // we will set MaxPoolThreads to
the value the user provided in the dialog and then
set
    }
}

```

```

        // PoolThreadLimit to
MaxPoolThreads * number of processors on this system
        if ( iIISMajorVersion == 6 )
        {
            iMaxPoolThreads =
iPoolThreadLimit;
            iPoolThreadLimit =
iMaxPoolThreads * iNumberOfProcessors;
            RegSetValueEx(hKey,
"PoolThreadLimit", 0, REG_DWORD, (char
*)&iPoolThreadLimit, sizeof(iPoolThreadLimit));
            RegSetValueEx(hKey,
"MaxPoolThreads", 0, REG_DWORD, (char
*)&iMaxPoolThreads, sizeof(iMaxPoolThreads));
        }
        else
        {
            RegSetValueEx(hKey,
"PoolThreadLimit", 0, REG_DWORD, (char
*)&iPoolThreadLimit, sizeof(iPoolThreadLimit));
        }

        RegSetValueEx(hKey,
"ThreadTimeout", 0, REG_DWORD, (char
*)&iThreadTimeout, sizeof(iThreadTimeout));
        RegSetValueEx(hKey,
"ListenBackLog", 0, REG_DWORD, (char
*)&iListenBackLog, sizeof(iListenBackLog));

        RegFlushKey(hKey);
        RegCloseKey(hKey);
    }
}

    if (
(iRc=RegCreateKeyEx(HKEY_LOCAL_MACHINE,
"SYSTEM\\CurrentControlSet\\Services\\W3SVC\\Paramet
ers", 0, NULL, REG_OPTION_NON_VOLATILE,
KEY_ALL_ACCESS, NULL, &hKey, &dwDisposition)) ==
ERROR_SUCCESS )
    {
        RegSetValueEx(hKey,
"AcceptExOutstanding", 0, REG_DWORD, (char
*)&iAcceptExOutstanding,
sizeof(iAcceptExOutstanding));

        RegFlushKey(hKey);
        RegCloseKey(hKey);
    }
}

    return;
}

BOOL CALLBACK CopyDlgProc(HWND hwnd, UINT uMsg,
WPARAM wParam, LPARAM lParam)
{
    if ( uMsg == WM_INITDIALOG )
    {
        SendDlgItemMessage(hwnd,
IDC_PROGRESS1, PBM_SETRANGE, 0, MAKELPARAM(0, 16));
        SendDlgItemMessage(hwnd,
IDC_PROGRESS1, PBM_SETSTEP, (WPARAM)1, 0);
    }
}

```



```

        return TRUE;
    }
    return FALSE;
}

BOOL RegisterDLL(char *szFileName)
{
    HINSTANCE hLib;
    FARPROC lpDllEntryPoint;

    hLib = LoadLibrary(szFileName);
    if ( hLib == NULL )
        return FALSE;
    // Find the entry point.
    lpDllEntryPoint = GetProcAddress(hLib,
"DllRegisterServer");
    if (lpDllEntryPoint != NULL)
    {
        return ((*lpDllEntryPoint)() ==
S_OK);
    }
    else
        return FALSE; //unable to
locate entry point
}

BOOL FileFromResource( char *szResourceName, int
iResourceId, char *szDllPath, char *szFileName )
{
    HGLOBAL hDLL;
    HRSRC hResInfo;
    HANDLE hFile;
    DWORD dwSize;
    BYTE *pSrc;
    DWORD d;
    char szFullName[256];

    hResInfo = FindResource(hInst,
MAKEINTRESOURCE(iResourceId), szResourceName);

    strcpy(szFullName, szDllPath);
    strcat(szFullName, szFileName);

    dwSize = SizeofResource(hInst, hResInfo);
    hDLL = LoadResource(hInst, hResInfo);
    pSrc = (BYTE *)LockResource(hDLL);
    remove(szFullName);

    if ( !(hFile = CreateFile(szFullName,
GENERIC_WRITE, 0, NULL, CREATE_ALWAYS,
FILE_ATTRIBUTE_NORMAL, NULL)) )
        return FALSE;

    if ( !WriteFile(hFile, pSrc, dwSize, &d,
NULL) )
        return FALSE;

    CloseHandle(hFile);

    UnlockResource(hDLL);

```

```

    FreeResource(hDLL);
    return TRUE;
}

static int CopyFiles(HWND hDlg, char *szDllPath, char
*szWindowsPath)
{
    SetDlgItemText(hDlg, IDC_STATUS, "Copying
Files...");
    SendDlgItemMessage(hDlg, IDC_PROGRESS1,
PBM_STEPIT, 0, 0);
    UpdateDialog(hDlg);

    // install TPCC.DLL
    strcpy( szLastFileName, "tpcc.dll" );
    if (!FileFromResource( "TPCCDLL",
IDR_TPCCDLL, szDllPath, szLastFileName ))
        return 0;
    SendDlgItemMessage(hDlg, IDC_PROGRESS1,
PBM_STEPIT, 0, 0);
    UpdateDialog(hDlg);

    // install MSVCR70.DLL
    strcpy( szLastFileName, "msvcr70.dll" );
    if (!FileFromResource( "MSVCR70",
IDR_MSVCRT701, szWindowsPath, szLastFileName ))
        return 0;
    SendDlgItemMessage(hDlg, IDC_PROGRESS1,
PBM_STEPIT, 0, 0);
    UpdateDialog(hDlg);

    // install tpcc_dblib.dll
    strcpy( szLastFileName, "tpcc_dblib.dll" );
    if (!FileFromResource( "DBLIB_DLL",
IDR_DBLIB_DLL, szDllPath, szLastFileName ))
        return 0;
    SendDlgItemMessage(hDlg, IDC_PROGRESS1,
PBM_STEPIT, 0, 0);
    UpdateDialog(hDlg);

    // install tpcc_odbc.dll
    strcpy( szLastFileName, "tpcc_odbc.dll" );
    if (!FileFromResource( "ODBC_DLL",
IDR_ODBC_DLL, szDllPath, szLastFileName ))
        return 0;
    SendDlgItemMessage(hDlg, IDC_PROGRESS1,
PBM_STEPIT, 0, 0);
    UpdateDialog(hDlg);

    // install tuxapp.exe
    strcpy( szLastFileName, "tuxapp.exe" );
    if (!FileFromResource( "TUXEDO_APP",
IDR_TUXEDO_APP, szDllPath, szLastFileName ))
        return 0;
    //SendDlgItemMessage(hDlg, IDC_PROGRESS1,
PBM_STEPIT, 0, 0);
    //UpdateDialog(hDlg);

    // install tpcc_tuxedo.dll

```

```

    strcpy( szLastFileName, "tpcc_tuxedo.dll"
);
    if (!FileFromResource( "TUXEDO_DLL",
IDR_TUXEDO_DLL, szDllPath, szLastFileName ))
        return 0;
    //SendDlgItemMessage(hDlg, IDC_PROGRESS1,
PBM_STEPIT, 0, 0);
    //UpdateDialog(hDlg);

    // install tpcc_com.dll
    strcpy( szLastFileName, "tpcc_com.dll" );
    if (!FileFromResource( "COM_DLL",
IDR_COM_DLL, szDllPath, szLastFileName ))
        return 0;
    SendDlgItemMessage(hDlg, IDC_PROGRESS1,
PBM_STEPIT, 0, 0);
    UpdateDialog(hDlg);

    // install tpcc_com_all.tlb
    strcpy( szLastFileName, "tpcc_com_all.tlb"
);
    if (!FileFromResource( "COM_TYPLIB",
IDR_COMTYPLIB_DLL, szDllPath, szLastFileName ))
        return 0;
    SendDlgItemMessage(hDlg, IDC_PROGRESS1,
PBM_STEPIT, 0, 0);
    UpdateDialog(hDlg);

    // install tpcc_com_ps.dll
    strcpy( szLastFileName, "tpcc_com_ps.dll"
);
    if (!FileFromResource( "COM_PS_DLL",
IDR_COMPS_DLL, szDllPath, szLastFileName ))
        return 0;
    SendDlgItemMessage(hDlg, IDC_PROGRESS1,
PBM_STEPIT, 0, 0);
    UpdateDialog(hDlg);

    // install tpcc_com_all.dll
    strcpy( szLastFileName, "tpcc_com_all.dll"
);
    if (!FileFromResource( "COM_ALL_DLL",
IDR_COMALL_DLL, szDllPath, szLastFileName ))
        return 0;
    SendDlgItemMessage(hDlg, IDC_PROGRESS1,
PBM_STEPIT, 0, 0);
    UpdateDialog(hDlg);

    SendDlgItemMessage(hDlg, IDC_PROGRESS1,
PBM_STEPIT, 0, 0);
    UpdateDialog(hDlg);

    return 1;
}

static BOOL GetInstallPath(char *szDllPath)
{
    HKEY hKey;
    BYTE szData[256];
    DWORD sv;
    BOOL bRc;

```

```

int len;
int iRc;

// Registry key
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\InetStp\PathWWW
Root is used to find the
// IIS default web site directory and
determine that IIS is installed.

szDllPath[0] = 0;
bRc = TRUE;
if ( RegOpenKeyEx(HKEY_LOCAL_MACHINE,
"SOFTWARE\Microsoft\InetStp", 0, KEY_ALL_ACCESS,
&hKey) == ERROR_SUCCESS )
{
    sv = sizeof(szData);
    iRc = RegQueryValueEx( hKey,
"PathWWWRoot", NULL, NULL, szData, &sv ); // used by
IIS 5.0 & 6.0
    if (iRc == ERROR_SUCCESS)
    {
        bRc = FALSE;
        strcpy(szDllPath,
szData);
        len =
strlen(szDllPath);
        if ( szDllPath[len-1]
!= '\\' )
        {
            szDllPath[len] = '\\';
            szDllPath[len+1] = 0;
        }
        RegCloseKey( hKey );
    }
    return bRc;
}

static BOOL GetWindowsInstallPath(char
*szWindowsPath)
{
    HKEY hKey;
    BYTE szData[256];
    DWORD sv;
    BOOL bRc;
    int len;
    int iRc;

    // Registry key
    HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows
NT\CurrentVersion\SystemRoot is used to find the
// system root to install the VC70 DLL.

    szWindowsPath[0] = 0;
    bRc = TRUE;

```

```

    if ( RegOpenKeyEx(HKEY_LOCAL_MACHINE,
"SOFTWARE\Microsoft\Windows NT\CurrentVersion", 0,
KEY_ALL_ACCESS, &hKey) == ERROR_SUCCESS )
    {
        sv = sizeof(szData);
        iRc = RegQueryValueEx( hKey,
"SystemRoot", NULL, NULL, szData, &sv );
        if (iRc == ERROR_SUCCESS)
        {
            bRc = FALSE;
            strcpy(szWindowsPath,
szData);
            len =
strlen(szWindowsPath);
            if ( szWindowsPath[len-
1] != '\\' )
            {
                szWindowsPath[len] = '\\';
                szWindowsPath[len+1] = 0;
                // now append the path
                strcat(szWindowsPath,
"SYSTEM32\");
            }
            RegCloseKey( hKey );
        }
        return bRc;
    }
    static void GetVersionInfo(char *szDLLPath, char
*szExePath)
    {
        DWORD d;
        DWORD dwSize;
        DWORD dwBytes;
        char *ptr;
        VS_FIXEDFILEINFO *vs;

        versionDllMS = 0;
        versionDllLS = 0;
        if ( _access(szDLLPath, 00) == 0 )
        {
            dwSize =
GetFileVersionInfoSize(szDLLPath, &d);
            if ( dwSize )
            {
                ptr = (char
*)malloc(dwSize);
                GetFileVersionInfo(szDLLPath, 0, dwSize,
ptr);
                VerQueryValue( ptr,
"\",&vs, &dwBytes);

```

```

                versionDllMS = vs-
>dwProductVersionMS;
                versionDllLS = vs-
>dwProductVersionLS;
            }
            versionExeMS = 0x7FFF;
            versionExeLS = 0x7FFF;
            dwSize = GetFileVersionInfoSize(szExePath,
&d);
            if ( dwSize )
            {
                ptr = (char *)malloc(dwSize);
                GetFileVersionInfo(szExePath, 0,
dwSize, ptr);
                VerQueryValue( ptr, "\",&vs,
&dwBytes);
                versionExeMS = vs-
>dwProductVersionMS;
                versionExeLS = LOWORD(vs-
>dwProductVersionLS);
                versionExeMM = HIWORD(vs-
>dwProductVersionLS);
                free(ptr);
            }
            return;
        }
        static BOOL CheckWWWWebService(void)
        {
            SC_HANDLE schSCManager;
            SC_HANDLE schService;
            SERVICE_STATUS ssStatus;

            schSCManager = OpenSCManager(NULL, NULL,
SC_MANAGER_ALL_ACCESS);
            schService = OpenService(schSCManager,
TEXT("W3SVC"), SERVICE_ALL_ACCESS);
            if (schService == NULL)
                return FALSE;

            if (! QueryServiceStatus(schService,
&ssStatus) )
                goto ServiceNotRunning;

            if (! ControlService(schService,
SERVICE_CONTROL_STOP, &ssStatus) )
                goto ServiceNotRunning;
            //start Service pending, Check the status
until the service is running.
            if (! QueryServiceStatus(schService,
&ssStatus) )
                goto ServiceNotRunning;

            CloseServiceHandle(schService);
            return TRUE;
        }
        ServiceNotRunning:

```

```

        CloseServiceHandle(schService);
        return FALSE;
    }

static BOOL StartWWWebService(void)
{
    SC_HANDLE      schSCManager;
    SC_HANDLE      schService;
    SERVICE_STATUS ssStatus;
    DWORD          dwOldCheckPoint;

    schSCManager = OpenSCManager(NULL, NULL,
    SC_MANAGER_ALL_ACCESS);
    schService = OpenService(schSCManager,
    TEXT("W3SVC"), SERVICE_ALL_ACCESS);
    if (schService == NULL)
        return FALSE;

    if (! StartService(schService, 0, NULL) )
        goto StartWWWebErr;
    //start Service pending, Check the status
    until the service is running.
    if (! QueryServiceStatus(schService,
    &ssStatus) )
        goto StartWWWebErr;
    while( ssStatus.dwCurrentState !=
    SERVICE_RUNNING)
    {
        dwOldCheckPoint =
    ssStatus.dwCheckPoint;
        //Save the current checkpoint.
        Sleep(ssStatus.dwWaitHint);

        //Wait for the specified interval.
        if (
    !QueryServiceStatus(schService, &ssStatus) )
            //Check the status again.
            break;
        if (dwOldCheckPoint >=
    ssStatus.dwCheckPoint) //Break if
    the checkpoint has not been incremented.
            break;
    }

    if (ssStatus.dwCurrentState ==
    SERVICE_RUNNING)
        goto StartWWWebErr;

    CloseServiceHandle(schService);
    return TRUE;

StartWWWebErr:
    CloseServiceHandle(schService);
    return FALSE;
}

static BOOL StopWWWebService(void)
{

```

```

    SC_HANDLE      schSCManager;
    SC_HANDLE      schService;
    SERVICE_STATUS ssStatus;
    DWORD          dwOldCheckPoint;

    schSCManager = OpenSCManager(NULL, NULL,
    SC_MANAGER_ALL_ACCESS);
    //schService = OpenService(schSCManager,
    TEXT("W3SVC"), SERVICE_ALL_ACCESS);
    schService = OpenService(schSCManager,
    TEXT("IISADMIN"), SERVICE_ALL_ACCESS);
    if (schService == NULL)
        return FALSE;

    if (! QueryServiceStatus(schService,
    &ssStatus) )
        goto StopWWWebErr;

    if (! ControlService(schService,
    SERVICE_CONTROL_STOP, &ssStatus) )
        goto StopWWWebErr;
    //start Service pending, Check the status
    until the service is running.
    if (! QueryServiceStatus(schService,
    &ssStatus) )
        goto StopWWWebErr;
    while( ssStatus.dwCurrentState ==
    SERVICE_RUNNING)
    {
        dwOldCheckPoint =
    ssStatus.dwCheckPoint;
        //Save the current checkpoint.
        Sleep(ssStatus.dwWaitHint);

        //Wait for the specified interval.
        if (
    !QueryServiceStatus(schService, &ssStatus) )
            //Check the status again.
            break;
        if (dwOldCheckPoint >=
    ssStatus.dwCheckPoint) //Break if
    the checkpoint has not been incremented.
            break;
    }

    if (ssStatus.dwCurrentState ==
    SERVICE_RUNNING)
        goto StopWWWebErr;

    CloseServiceHandle(schService);
    return TRUE;

StopWWWebErr:
    CloseServiceHandle(schService);
    return FALSE;
}

static void UpdateDialog(HWND hDlg)
{

```

```

    MSG msg;

    UpdateWindow(hDlg);
    while( PeekMessage(&msg, hDlg, 0, 0,
    PM_REMOVE) )
    {
        TranslateMessage(&msg);
        DispatchMessage(&msg);
    }
    Sleep(250);
    return;
}

static void ConfigureIIS6(HWND hwnd, HWND hDlg)
{
    int      irc;
    char     szErrTxt[128];
    FILE     *fErrorFile;

    SetDlgItemText(hDlg, IDC_STATUS,
    "Configuring IIS6...");
    //SendDlgItemMessage(hDlg, IDC_PROGRESS1,
    PBM_STEPIT, 0, 0);
    UpdateDialog(hDlg);

    irc = system("IIS6_CONFIG.CMD");

    // since the return code from the command
    file is always 1,
    // check to see if the file iis6_config.err
    exists
    // if it does, then something hosed
    fErrorFile = fopen("IIS6_CONFIG.err","r");
    if ( fErrorFile != NULL )
    {
        ShowWindow(hwnd, SW_SHOWNA);
        DestroyWindow(hDlg);
        strcpy( szErrTxt, "IIS6
    configuration error." );
        strcat( szErrTxt, "Check
    iis6_config.err" );
        MessageBox(hwnd, szErrTxt, NULL,
    MB_ICONSTOP | MB_OK);
        EndDialog(hwnd, 0);
        return;
    }
}

install.h
//{{NO_DEPENDENCIES}}
// Microsoft Developer Studio generated include file.
// Used by install.rc
//
#define IDD_DIALOG1          101
#define IDI_ICON1           102
#define IDR_TPCCDLL         103
#define IDD_DIALOG2        105
#define IDI_ICON2           106

```

```

#define IDR_DELIVERY 107
#define IDD_DIALOG3 108

#define BN_LOG
1001
#define ED_KEEP
1002
#define ED_THREADS
1003
#define ED_THREADS2
1004
#define IDC_PATH
1007
#define IDC_VERSION
1009
#define IDC_RESULTS
1010
#define IDC_PROGRESS1
1011
#define IDC_STATUS
1012
#define IDC_BUTTON1
1013
#define ED_MAXCONNECTION
1014
#define ED_IIS_MAX_THREAD_POOL_LIMIT
1015
#define ED_WEB_SERVICE_BACKLOG_QUEUE_SIZE
1017
#define ED_IIS_THREAD_TIMEOUT
1018
#define ED_IIS_LISTEN_BACKLOG
1019
#define IDC_DBLIB
1021
#define IDC_ODBC
1022
#define IDC_CONNECT_POOL
1023
#define ED_USER_CONNECT_DELAY_TIME
1024

// Next default values for new objects
//

install.rc

// Microsoft Visual C++ generated resource script.
//
#include "resource.h"

#define APSTUDIO_READONLY_SYMBOLS
////////////////////////////////////
////////////////////////////////////
//
// Generated from the TEXTINCLUDE 2 resource.
//
#include "afxres.h"

```

```

////////////////////////////////////
////////////////////////////////////
#undef APSTUDIO_READONLY_SYMBOLS

////////////////////////////////////
////////////////////////////////////
// English (U.S.) resources

#ifdef AFX_RESOURCE_DLL
#ifdef AFX_TARG_ENU
#ifdef _WIN32
LANGUAGE LANG_ENGLISH, SUBLANG_ENGLISH_US
#pragma code_page(1252)
#endif // _WIN32

////////////////////////////////////
////////////////////////////////////
//
// Dialog
//

IDD_DIALOG1 DIALOGEX 0, 0, 219, 351
STYLE DS_SETFONT | DS_MODALFRAME | DS_CENTER |
WS_MINIMIZEBOX | WS_POPUP |
WS_CAPTION | WS_SYSMENU
CAPTION "TPC-C Web Client Installation Utility"
FONT 8, "MS Sans Serif", 0, 0, 0x1
BEGIN
    EDITTEXT        ED_THREADS,164,45,34,12,ES_RIGHT
    | ES_NUMBER,
    WS_EX_RTLREADING

    EDITTEXT        ED_MAXDELIVERIES,164,59,34,12,ES_RIGHT | ES_NUMBER,
    WS_EX_RTLREADING

    EDITTEXT        ED_MAXCONNECTION,164,73,34,12,ES_RIGHT | ES_NUMBER,
    WS_EX_RTLREADING

    CONTROL
    "None",IDC_TM_NONE,"Button",BS_AUTORADIOBUTTON |
    WS_GROUP |
    WS_TABSTOP,43,100,33,10

    CONTROL
    "COM",IDC_TM_MTS,"Button",BS_AUTORADIOBUTTON |
    WS_TABSTOP,43,113,32,10

    CONTROL
    "TUXEDO",IDC_TM_TUXEDO,"Button",BS_AUTORADIOBUTTON |
    WS_TABSTOP,106,100,46,10

    CONTROL
    "ENCINA",IDC_TM_ENCINA,"Button",BS_AUTORADIOBUTTON |
    WS_DISABLED |
    WS_TABSTOP,106,113,43,10

    EDITTEXT
    ED_DB_SERVER,131,152,67,12,ES_AUTOHSCROLL
    EDITTEXT
    ED_DB_USER_ID,131,165,67,12,ES_AUTOHSCROLL
    EDITTEXT
    ED_DB_PASSWORD,131,178,67,12,ES_AUTOHSCROLL
    EDITTEXT
    ED_DB_NAME,131,191,67,12,ES_AUTOHSCROLL

```

```

CONTROL
"DBLIB",IDC_DBLIB,"Button",BS_AUTORADIOBUTTON |
WS_GROUP |
WS_TABSTOP,45,219,39,12

CONTROL
"ODBC",IDC_ODBC,"Button",BS_AUTORADIOBUTTON |
WS_TABSTOP,
91,219,39,12

EDITTEXT
ED_IIS_MAX_THREAD_POOL_LIMIT,164,263,34,12,ES_RIGHT |
ES_NUMBER,WS_EX_RTLREADING

EDITTEXT
ED_WEB_SERVICE_BACKLOG_QUEUE_SIZE,164,277,34,12,ES_RI
GHT |
ES_NUMBER,WS_EX_RTLREADING

EDITTEXT
ED_IIS_THREAD_TIMEOUT,164,291,34,12,ES_RIGHT |
ES_NUMBER,
WS_EX_RTLREADING

EDITTEXT
ED_IIS_LISTEN_BACKLOG,164,305,34,12,ES_RIGHT |
ES_NUMBER,
WS_EX_RTLREADING

DEFPUSHBUTTON "OK",IDOK,53,331,50,14
PUSHBUTTON "Cancel",IDCANCEL,119,331,50,14
EDITTEXT
IDC_PATH,106,26,91,13,ES_AUTOHSCROLL | ES_READONLY
LTEXT "Number of Delivery
Threads:",IDC_STATIC,35,45,115,12
LTEXT "Max Number of
Connections:",IDC_STATIC,35,73,115,12
RTEXT "Version
4.11",IDC_VERSION,120,4,89,9
LTEXT "IIS Max Thread Pool
Limit:",IDC_STATIC,36,263,115,12
LTEXT "Web Service Backlog Queue
Size:",IDC_STATIC,36,277,115,
12
LTEXT "IIS Thread Timeout
(seconds):",IDC_STATIC,36,291,115,12
LTEXT "IIS Listen
Backlog:",IDC_STATIC,36,307,115,10
GROUPBOX "Database
Interface",IDC_STATIC,35,208,163,27,WS_GROUP
LTEXT "Installation
directory:",IDC_STATIC,35,29,71,10
GROUPBOX "Transaction
Monitor",IDC_STATIC,33,90,165,37
LTEXT "Server
Name:",IDC_STATIC,35,155,56,8
LTEXT "User ID:",IDC_STATIC,35,168,60,8
LTEXT "User
Password:",IDC_STATIC,35,181,83,8
LTEXT "Database
Name:",IDC_STATIC,35,194,54,8
GROUPBOX "SQL Server Connection
Properties",IDC_STATIC,22,139,187,
102
GROUPBOX "Web Client
Properties",IDC_STATIC,22,15,187,118

```

```

GROUPBOX "IIS
Settings", IDC_STATIC, 22, 247, 187, 79
LTEXT "Max Pending
Deliveries:", IDC_STATIC, 35, 59, 115, 12
END

IDD_DIALOG2 DIALOGEX 0, 0, 117, 62
STYLE DS_SETFONT | DS_SETFOREGROUND | DS_3DLOOK |
DS_CENTER | WS_POPUP |
WS_BORDER
EXSTYLE WS_EX_STATICEDGE
FONT 12, "MS Sans Serif", 0, 0, 0x1
BEGIN
DEFPUSHBUTTON "OK", IDOK, 33, 45, 50, 9
CTEXT "HTML TPC-C Installation
Successful", IDC_RESULTS, 7, 22,
102, 18, 0, WS_EX_CLIENTEDGE
ICON
IDI_ICON2, IDC_STATIC, 50, 7, 18, 20, SS_REALSIZEIMAGE,
WS_EX_TRANSPARENT
END

IDD_DIALOG3 DIALOG 0, 0, 91, 40
STYLE DS_SYSMODAL | DS_SETFONT | DS_MODALFRAME |
DS_3DLOOK | DS_CENTER |
WS_CAPTION
CAPTION "Installing TPC-C Web Client"
FONT 12, "Arial Black"
BEGIN
CONTROL
"Progress1", IDC_PROGRESS1, "msctls_progress32", WS_BORD
ER,
7, 20, 77, 13
CTEXT
"Static", IDC_STATUS, 7, 7, 77, 12, SS_SUNKEN
END

IDD_DIALOG4 DIALOG 0, 0, 291, 202
STYLE DS_SETFONT | DS_MODALFRAME | DS_CENTER |
WS_POPUP | WS_CAPTION |
WS_SYSMENU
CAPTION "Client End User License"
FONT 8, "MS Sans Serif"
BEGIN
EDITTEXT
IDC_LICENSE, 7, 7, 271, 167, ES_MULTILINE | ES_AUTOVSCROLL
|
ES_AUTOHSCROLL | ES_READONLY |
WS_VSCROLL | WS_HSCROLL
DEFPUSHBUTTON "I &Agree", IDOK, 87, 181, 50, 14
PUSHBUTTON "&Cancel", IDCANCEL, 153, 181, 50, 14
END

#####
//
// DESIGNINFO
//
#ifdef APSTUDIO_INVOKED

```

```

GUIDELINES DESIGNINFO
BEGIN
IDD_DIALOG1, DIALOG
BEGIN
LEFTMARGIN, 22
RIGHTMARGIN, 209
VERTGUIDE, 35
VERTGUIDE, 198
TOPMARGIN, 4
BOTTOMMARGIN, 345
END

IDD_DIALOG2, DIALOG
BEGIN
LEFTMARGIN, 7
RIGHTMARGIN, 109
TOPMARGIN, 7
BOTTOMMARGIN, 54
END

IDD_DIALOG3, DIALOG
BEGIN
LEFTMARGIN, 7
RIGHTMARGIN, 84
TOPMARGIN, 7
BOTTOMMARGIN, 33
END

IDD_DIALOG4, DIALOG
BEGIN
LEFTMARGIN, 7
RIGHTMARGIN, 278
TOPMARGIN, 7
BOTTOMMARGIN, 195
END
END
#endif // APSTUDIO_INVOKED

#ifdef APSTUDIO_INVOKED
#####
//
// TEXTINCLUDE
//
1 TEXTINCLUDE
BEGIN
"resource.h\0"
END

2 TEXTINCLUDE
BEGIN
#include "afxres.h"\r\n"
"\0"
END

3 TEXTINCLUDE
BEGIN
"\r\n"
"\0"

```

```

END
#endif // APSTUDIO_INVOKED

#####
//
// Icon
//
// Icon with lowest ID value placed first to ensure
application icon
// remains consistent on all systems.
IDI_ICON1 ICON
"icon1.ico"
IDI_ICON2 ICON
"icon2.ico"

#####
//
// TPCCDLL
//
IDR_TPCCDLL TPCCDLL
"..\\..\\sapi_dll\\bin\\tpcc.dll"

#####
//
// Version
//
VS_VERSION_INFO VERSIONINFO
FILEVERSION 0,4,50,0
PRODUCTVERSION 0,4,50,0
FILEFLAGSMASK 0x3fL
#ifdef DEBBUG
FILEFLAGS 0x1L
#else
FILEFLAGS 0x0L
#endif
#endef
FILEOS 0x40004L
FILETYPE 0x1L
FILESUBTYPE 0x0L
BEGIN
BLOCK "StringFileInfo"
BEGIN
BLOCK "040904b0"
BEGIN
VALUE "Comments", "TPC-C Web Client
Installer"
VALUE "CompanyName", "Microsoft"
VALUE "FileDescription", "install"
VALUE "FileVersion", "0, 4, 20, 0"
VALUE "InternalName", "install"
VALUE "LegalCopyright", "Copyright ©
1999"
VALUE "OriginalFilename", "install.exe"
VALUE "ProductName", "Microsoft install"

```

```

        VALUE "ProductVersion", "0, 4, 20, 0"
    END
END
BLOCK "VarFileInfo"
BEGIN
    VALUE "Translation", 0x409, 1200
END
END

////////////////////////////////////
//
// LICENSE
//
IDR_LICENSE1          LICENSE
"license.txt"

////////////////////////////////////
//
// DBLIB_DLL
//
IDR_DBLIB_DLL         DBLIB_DLL
"..\\..\\db_dblib_dll\\bin\\Release\\tpcc_dblib.dll"

////////////////////////////////////
//
// ODBC_DLL
//
IDR_ODBC_DLL          ODBC_DLL
"..\\..\\db_odbc_dll\\bin\\Release\\tpcc_odbc.dll"

////////////////////////////////////
//
// TUXEDO_APP
//
IDR_TUXEDO_APP        TUXEDO_APP
"..\\..\\tuxapp\\bin\\tuxapp.exe"

////////////////////////////////////
//
// TUXEDO_DLL
//
IDR_TUXEDO_DLL        TUXEDO_DLL
"..\\..\\tm_tuxedo_dll\\bin\\tpcc_tuxedo.dll"

////////////////////////////////////
//
// COM_DLL
//

```

```

IDR_COM_DLL           COM_DLL
"..\\..\\tm_com_dll\\bin\\tpcc_com.dll"

////////////////////////////////////
//
// COM_PS_DLL
//
IDR_COMPS_DLL         COM_PS_DLL
"..\\..\\tpcc_com_ps\\bin\\tpcc_com_ps.dll"

////////////////////////////////////
//
// COM_ALL_DLL
//
IDR_COMALL_DLL        COM_ALL_DLL
"..\\..\\tpcc_com_all\\bin\\tpcc_com_all.dll"

////////////////////////////////////
//
// COM_TYPLIB
//
IDR_COMTYPLIB_DLL    COM_TYPLIB
"..\\..\\tpcc_com_all\\src\\tpcc_com_all.tlb"

////////////////////////////////////
//
// MSVCRT70
//
IDR_MSVCRT70         MSVCRT70
"C:\\WINDOWS\\system32\\msvcr70.dll"
#endif // English (U.S.) resources
////////////////////////////////////

#ifndef APSTUDIO_INVOKED
////////////////////////////////////
//
// Generated from the TEXTINCLUDE 3 resource.
//
////////////////////////////////////

#endif // not APSTUDIO_INVOKED

```

install_com.cp

p

```

/* FILE:          INSTALL_COM.CPP
 *               Microsoft
 * TPC-C Kit Ver. 4.51.000
 *               Copyright
 * Microsoft, 1999
 *               All Rights Reserved
 *
 *               not audited
 *
 * PURPOSE:  installation code for COM
 * application for TPC-C Web Kit
 * Contact:  Charles Levine
 * (clevine@microsoft.com)
 *
 * Change history:
 * 4.20.000 - first version
 */

#define WIN32_WINNT 0x0500

#include <comdef.h>
#include <comadmin.h>
#include <stdio.h>
#include <tchar.h>

extern "C"
{
    BOOL install_com(char *szDllPath);
}

BOOL install_com(char *szDllPath)
{
    ICOMAdminCatalog* pCOMAdminCat = NULL;
    ICatalogCollection* pCatalogCollectionApp
= NULL;
    ICatalogCollection* pCatalogCollectionCo
= NULL;
    ICatalogCollection* pCatalogCollectionItf
= NULL;
    ICatalogCollection*
pCatalogCollectionMethod = NULL;
    ICatalogObject*
pCatalogObjectApp = NULL;
    ICatalogObject*
pCatalogObjectCo = NULL;
    ICatalogObject*
pCatalogObjectItf = NULL;
    ICatalogObject*
pCatalogObjectMethod = NULL;

    _bstr_t
bstrTemp, bstrTemp2, bstrTemp3, bstrTemp4;
    _bstr_t
bstrDllPath = szDllPath;

```

```

        _variant_t
        vTmp, vKey;
        long
        lActProp, lCount, lCountCo, lCountItf,
lCountMethod;
        bool
        bTmp;

        CoInitializeEx(NULL, COINIT_MULTITHREADED);

        HRESULT hr =
CoCreateInstance(CLSID_COMAdminCatalog,

                NULL,

                CLSCTX_INPROC_SERVER,

                IID_ICOMAdminCatalog,

                (void**)
&pCOMAdminCat);

        if (!SUCCEEDED(hr)) goto Error;

        bstrTemp = "Applications";

        // Attempt to connect to "Applications" in
the Catalog
        hr = pCOMAdminCat->GetCollection(bstrTemp,

                (IDispatch**)
&pCatalogCollectionApp);
        if (!SUCCEEDED(hr)) goto Error;

        // Attempt to load the "Applications"
collection
        hr = pCatalogCollectionApp->Populate();
        if (!SUCCEEDED(hr)) goto Error;

        hr = pCatalogCollectionApp-
>get_Count(&lCount);
        if (!SUCCEEDED(hr)) goto Error;

        // iterate through applications to delete
existing "TPC-C" application (if any)
        while (lCount > 0)
        {
                hr = pCatalogCollectionApp-
>get_Item(lCount - 1, (IDispatch**)
&pCatalogObjectApp);
                if (!SUCCEEDED(hr)) goto Error;

                hr = pCatalogObjectApp-
>get_Name(&vTmp);
                if (!SUCCEEDED(hr)) goto Error;

                if (wcsncmp(vTmp.bstrVal, L"TPC-
C"))

```

```

        {
                lCount--;
                continue;
        }
        else
        {
                hr =
pCatalogCollectionApp->Remove(lCount - 1);
                if (!SUCCEEDED(hr))
goto Error;

                break;
        }
        }

        hr = pCatalogCollectionApp-
>SaveChanges(&lActProp);
        if (!SUCCEEDED(hr)) goto Error;

        // add the new application
        hr = pCatalogCollectionApp-
>Add((IDispatch**) &pCatalogObjectApp);
        if (!SUCCEEDED(hr)) goto Error;

        // set properties
        bstrTemp = "Name";
        vTmp = "TPC-C";
        hr = pCatalogObjectApp->put_Value(bstrTemp,
vTmp);
        if (!SUCCEEDED(hr)) goto Error;

        // set as a library (in process)
application
        bstrTemp = "Activation";
        lActProp = COMAdminActivationInproc;
        vTmp = lActProp;
        hr = pCatalogObjectApp->put_Value(bstrTemp,
vTmp);
        if (!SUCCEEDED(hr)) goto Error;

        // set security level to process
        bstrTemp = "AccessChecksLevel";
        lActProp =
COMAdminAccessChecksApplicationLevel;
        vTmp = lActProp;
        hr = pCatalogObjectApp->put_Value(bstrTemp,
vTmp);
        if (!SUCCEEDED(hr)) goto Error;

        // save key to get the Components
collection later
        hr = pCatalogObjectApp->get_Key(&vKey);
        if (!SUCCEEDED(hr)) goto Error;

        // save changes (app creation) so component
installation will work
        hr = pCatalogCollectionApp-
>SaveChanges(&lActProp);
        if (!SUCCEEDED(hr)) goto Error;

        pCatalogObjectApp->Release();
        pCatalogObjectApp = NULL;

```

```

        bstrTemp = "TPC-C";
        // app name
        bstrTemp2 = bstrDllPath +
"tpcc_com_all.dll"; // DLL
        bstrTemp3 = bstrDllPath +
"tpcc_com_all.tlb"; // type library (TLB)
        bstrTemp4 = bstrDllPath +
"tpcc_com_ps.dll"; // proxy/stub dll

        hr = pCOMAdminCat-
>InstallComponent(bstrTemp,

                bstrTemp2,

                bstrTemp3,

                bstrTemp4);
        if (!SUCCEEDED(hr)) goto Error;

        bstrTemp = "Components";
        hr = pCatalogCollectionApp-
>GetCollection(bstrTemp, vKey, (IDispatch**)
&pCatalogCollectionCo);
        if (!SUCCEEDED(hr)) goto Error;

        hr = pCatalogCollectionCo->Populate();
        if (!SUCCEEDED(hr)) goto Error;

        hr = pCatalogCollectionCo-
>get_Count(&lCountCo);
        if (!SUCCEEDED(hr)) goto Error;

        // iterate through components in
application and set the properties
        while (lCountCo > 0)
        {
                hr = pCatalogCollectionCo-
>get_Item(lCountCo - 1, (IDispatch**)
&pCatalogObjectCo);
                if (!SUCCEEDED(hr)) goto Error;

                // used for debugging (view the
name)
                hr = pCatalogObjectCo-
>get_Name(&vTmp);
                if (!SUCCEEDED(hr)) goto Error;

                bstrTemp = "ConstructionEnabled";
                bTmp = TRUE;
                vTmp = bTmp;
                hr = pCatalogObjectCo-
>put_Value(bstrTemp, vTmp);
                if (!SUCCEEDED(hr)) goto Error;

                bstrTemp = "ConstructorString";

```

```

remove);
        bstrTemp2 = "dummy string (do not
vTmp = bstrTemp2;
hr = pCatalogObjectCo-
>put_Value(bstrTemp, vTmp);
        if (!SUCCEEDED(hr)) goto Error;

        bstrTemp =
"JustInTimeActivation";
        bTmp = TRUE;
vTmp = bTmp;
hr = pCatalogObjectCo-
>put_Value(bstrTemp, vTmp);
        if (!SUCCEEDED(hr)) goto Error;

        bstrTemp = "MaxPoolSize";
vTmp.Clear(); // clear
variant so it isn't stored as a bool (_variant_t
feature)
        vTmp = (long)30;
hr = pCatalogObjectCo-
>put_Value(bstrTemp, vTmp);
        if (!SUCCEEDED(hr)) goto Error;

        bstrTemp =
"ObjectPoolingEnabled";
        bTmp = TRUE;
vTmp = bTmp;
hr = pCatalogObjectCo-
>put_Value(bstrTemp, vTmp);
        if (!SUCCEEDED(hr)) goto Error;

        // save key to get the
InterfacesForComponent collection
        hr = pCatalogObjectCo-
>get_Key(&vKey);
        if (!SUCCEEDED(hr)) goto Error;

        bstrTemp =
"InterfacesForComponent";
        hr = pCatalogCollectionCo-
>GetCollection(bstrTemp, vKey, (IDispatch**)
&pCatalogCollectionItf);
        if (!SUCCEEDED(hr)) goto Error;

        hr = pCatalogCollectionItf-
>Populate();
        if (!SUCCEEDED(hr)) goto Error;

        hr = pCatalogCollectionItf-
>get_Count(&lCountItf);
        if (!SUCCEEDED(hr)) goto Error;

        // iterate through interfaces in
component
        while (lCountItf > 0)
        {

```

```

        hr =
pCatalogCollectionItf->get_Item(lCountItf - 1,
(IDispatch**) &pCatalogObjectItf);
        if (!SUCCEEDED(hr))
        goto Error;

        // save key to get the
MethodsForInterface collection
        hr = pCatalogObjectItf-
>get_Key(&vKey);
        if (!SUCCEEDED(hr))
        goto Error;

        bstrTemp =
"MethodsForInterface";
        hr =
pCatalogCollectionItf->GetCollection(bstrTemp, vKey,
(IDispatch**) &pCatalogCollectionMethod);
        if (!SUCCEEDED(hr))
        goto Error;

        hr =
pCatalogCollectionMethod->Populate();
        if (!SUCCEEDED(hr))
        goto Error;

        hr =
pCatalogCollectionMethod->get_Count(&lCountMethod);
        if (!SUCCEEDED(hr))
        goto Error;

        // iterate through
methods of interface
        while (lCountMethod >
0)
        {
                hr =
pCatalogCollectionMethod->get_Item(lCountMethod - 1,
(IDispatch**) &pCatalogObjectMethod);
                if
(!SUCCEEDED(hr)) goto Error;

                bstrTemp =
"AutoComplete";
                bTmp = TRUE;
vTmp = bTmp;
hr =
pCatalogObjectMethod->put_Value(bstrTemp, vTmp);
                if
(!SUCCEEDED(hr)) goto Error;

                pCatalogObjectMethod->Release();

                pCatalogObjectMethod = NULL;

                lCountMethod-
-;
        }

        // save changes

```

```

        hr =
pCatalogCollectionMethod->SaveChanges(&lActProp);
        if (!SUCCEEDED(hr))
        goto Error;

        pCatalogObjectItf-
>Release();
        pCatalogObjectItf =
NULL;

        lCountItf--;
    }

    pCatalogObjectCo->Release();
    pCatalogObjectCo = NULL;

    lCountCo--;
}

// save changes
hr = pCatalogCollectionCo-
>SaveChanges(&lActProp);
if (!SUCCEEDED(hr)) goto Error;

pCatalogCollectionApp->Release();
pCatalogCollectionApp = NULL;

pCatalogCollectionCo->Release();
pCatalogCollectionCo = NULL;

pCatalogCollectionItf->Release();
pCatalogCollectionItf = NULL;

pCatalogCollectionMethod->Release();
pCatalogCollectionMethod = NULL;

Error:
CoUninitialize();

if (!SUCCEEDED(hr))
{
        LPTSTR lpBuf;
        DWORD dwRes =
FormatMessage(FORMAT_MESSAGE_ALLOCATE_BUFFER |
FORMAT_MESSAGE_FROM_SYSTEM,
                NULL,
                hr,
                MAKELANGID(LANG_NEUTRAL, SUBLANG_DEFAULT),
                (LPTSTR)
&lpBuf,
                0,

```



```

                NULL);
//          tprintf(_T("Error adding
components. HRESULT: 0x%x\n%s"), hr, lpBuf);
                return TRUE;
        }
        else
                return FALSE;
}

```

license.txt

END-USER LICENSE AGREEMENT FOR
MICROSOFT TPC-C BENCHMARK KIT

IMPORTANT READ CAREFULLY: This Microsoft End-User License Agreement (EULA) is a legal agreement between you (either an individual or a single entity) and Microsoft Corporation for the Microsoft software product identified above, which includes computer software and may include associated media, printed materials, and online or electronic documentation (SOFTWARE PRODUCT). By installing, copying, or otherwise using the SOFTWARE PRODUCT, you agree to be bound by the terms of this EULA. If you do not agree to the terms of this Agreement, you are not authorized to use the SOFTWARE PRODUCT.

The SOFTWARE PRODUCT is protected by copyright laws and international copyright treaties, as well as other intellectual property laws and treaties. The SOFTWARE PRODUCT is licensed, not sold.

1. GRANT OF LICENSE. This EULA grants you the following rights:

Use. Microsoft grants to you the right to install and use copies of the SOFTWARE PRODUCT only in conjunction with validly licensed copies of Microsoft SQL Server and/or Microsoft Windows NT Server software. You may also make copies of the SOFTWARE PRODUCT for backup and archival purposes.

2. RESTRICTIONS.

--You must maintain all copyright notices on all copies of the SOFTWARE PRODUCT.
--You may not distribute copies of the SOFTWARE PRODUCT to third parties.
--You may not rent, lease or lend the SOFTWARE PRODUCT.
--You may not use the SOFTWARE PRODUCT or any

derivative works thereof to internally test database management system software other than Microsoft SQL Server and/or operating system software other than Microsoft Windows NT.
-- You may not disclose the results of any benchmark tests using the SOFTWARE PRODUCT to any third party without Microsoft's prior written approval.
-- You may not disclose or provide the SOFTWARE PRODUCT or any derivative works thereof, or any information relating to the SOFTWARE PRODUCT (including the existence of the SOFTWARE PRODUCT or the results of use and testing or benchmark testing), to any third party without Microsoft's written permission.

3. TERMINATION. Without prejudice to any other rights, Microsoft may terminate this EULA if you fail to comply with the terms and conditions of this EULA. In such event, you must destroy all copies of the SOFTWARE PRODUCT.

4. COPYRIGHT. All title and copyrights in and to the SOFTWARE PRODUCT and any copies thereof are owned by Microsoft or its suppliers. All title and intellectual property rights in and to the content which may be accessed through use of the SOFTWARE PRODUCT is the property of the respective content owner and may be protected by applicable copyright or other intellectual property laws and treaties. This EULA grants you no rights to use such content.

5. UPGRADES. If the SOFTWARE PRODUCT is labeled as an upgrade, you must be properly licensed to use a product identified by Microsoft as being eligible for the upgrade in order to use the SOFTWARE PRODUCT. A SOFTWARE PRODUCT labeled as an upgrade replaces and/or supplements the product that formed the basis for your eligibility for the upgrade. You may use the resulting upgraded product only in accordance with the terms of this EULA.

6. U.S. GOVERNMENT RESTRICTED RIGHTS.

The SOFTWARE PRODUCT is provided with RESTRICTED RIGHTS. Use, duplication, or disclosure by the Government is subject to restrictions as set forth in subparagraph (c) (1) (ii) of the Rights in Technical Data and Computer Software clause at

DFARS 252.227-7013 or subparagraphs (c) (1) and (2) of the Commercial Computer Software Restricted Rights at 48 CFR 52.227-19, as applicable. Manufacturer is Microsoft Corporation/One Microsoft Way/Redmond, WA 98052-6399.

7. EXPORT RESTRICTIONS.

You agree that you will not export or re-export the SOFTWARE PRODUCT to any country, person, entity or end user subject to U.S.A. export restrictions. Restricted countries currently include, but are not necessarily limited to Cuba, Iran, Iraq, Libya, North Korea, Syria, and the Federal Republic of Yugoslavia (Serbia and Montenegro, U.N. Protected Areas and areas of Republic of Bosnia and Herzegovina under the control of Bosnian Serb forces). You warrant and represent that neither the U.S.A. Bureau of Export Administration nor any other federal agency has suspended, revoked or denied your export privileges.

8. NO WARRANTY. ANY USE OF THE SOFTWARE PRODUCT IS AT YOUR OWN RISK. THE SOFTWARE PRODUCT IS PROVIDED FOR USE ONLY WITH MICROSOFT SQL SERVER AND/OR MICROSOFT WINDOWS NT SERVER SOFTWARE. TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, MICROSOFT AND ITS SUPPLIERS DISCLAIM ALL WARRANTIES AND CONDITIONS, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND NON-INFRINGEMENT.

9. NO LIABILITY FOR CONSEQUENTIAL DAMAGES. TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, IN NO EVENT SHALL MICROSOFT OR ITS SUPPLIERS BE LIABLE FOR ANY SPECIAL, INCIDENTAL, INDIRECT, OR CONSEQUENTIAL DAMAGES WHATSOEVER (INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOSS OF BUSINESS PROFITS, BUSINESS INTERRUPTION, LOSS OF BUSINESS INFORMATION, OR ANY OTHER PECUNIARY LOSS) ARISING OUT OF THE USE OF OR INABILITY TO USE THE SOFTWARE PRODUCT, EVEN IF MICROSOFT HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. BECAUSE SOME STATES AND JURISDICTIONS DO NOT ALLOW THE EXCLUSION OR LIMITATION OF LIABILITY FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES, THE ABOVE LIMITATION MAY NOT APPLY TO YOU.

10. LIMITATION OF LIABILITY. MICROSOFT'S

ENTIRE LIABILITY AND YOUR EXCLUSIVE REMEDY UNDER THIS EULA SHALL NOT EXCEED FIVE DOLLARS (US\$5.00).

11. MISCELLANEOUS
This EULA is governed by the laws of the State of Washington, U.S.A.
Should you have any questions concerning this EULA, or if you desire to contact Microsoft for any reason, please contact the Microsoft subsidiary serving your country, or write:
Microsoft Sales Information Center/One Microsoft Way/Redmond, WA 98052-6399.

Si vous avez acquis votre produit Microsoft au CANADA, la garantie limit,e suivante vous concerne:

EXCLUSION DE GARANTIES. Microsoft renonce entièrément ... toute garantie pour le LOGICIEL. Le LOGICIEL et toute autre documentation s'y rapportant sont fournis ® comme tels - sans aucune garantie quelle qu'elle soit, expresse ou implicite, y compris, mais ne se limitant pas aux garanties implicites de la qualit, marchande ou un usage particulier. Le risque total d,coulant de l'utilisation ou de la performance du LOGICIEL est entre vos mains.

RESPONSABILIT LIMITÉE. La seule obligation de Microsoft et votre recours exclusif concernant ce contrat n'excéderont pas cinq dollare (US\$5.00).

ABSENCE DE RESPONSABILIT POUR LES DOMMAGES INDIRECTS.
Microsoft ou ses fournisseurs ne pourront être tenus responsables en aucune circonstance de tout dommage quel qu'il soit (y compris mais non de faon limitative les dommages directs ou indirects caus,s par la perte de b,n,fices commerciaux, l'interruption des affaires, la perte d'information commerciale ou toute autre perte p,cuniaire) r,sultant de l'utilisation ou de l'impossibilit, d'utilisation de ce produit, et ce, m'me si la soci,t, Microsoft a ,t, avis,e de l',ventualit, de tels dommages. Certains ,tats/juridictions ne permettent pas l'exclusion ou la limitation de responsabilit, relative aux

dommages indirects ou cons,cutifs, et la limitation ci-dessus peut ne pas s'appliquer ... votre ,gard. La pr,sente Convention est r,gie par les lois de la province d'Ontario, Canada.
Chacune des parties ... la pr,sente reconnaEt irr,vocablement la comp,tence des tribunaux de la province d'Ontario et consent ... instituer tout litige qui pourrait d,couler de la pr,sente aupr's des tribunaux situ,s dans le district judiciaire de York, province d'Ontario. Au cas o- vous auriez des questions concernant cette licence ou que vous d,siriez vous mettre en rapport avec Microsoft pour quelque raison que ce soit, veuillez contacter la succursale Microsoft desservant votre pays, dont l'adresse est fournie dans ce produit, ou ,crire ...: Microsoft Customer Sales and Service, One Microsoft Way, Redmond, Washington 98052 6399.

Methods.h

```
/* FILE: METHODS.H
 * Microsoft
 * TPC-C Kit Ver. 4.20.000
 * Copyright
 * Microsoft, 1999
 * All Rights Reserved
 *
 * not yet
 * audited
 *
 * PURPOSE: Header file for COM components.
 *
 * Change history:
 * 4.20.000 - first version
 */

enum COMPONENT_ERROR
{
    ERR_MISSING_REGISTRY_ENTRIES = 1,
    ERR_LOADDLL_FAILED,
    ERR_GETPROCADDR_FAILED,
    ERR_UNKNOWN_DB_PROTOCOL
};

class CCOMPONENT_ERR : public CBaseErr
{
public:
```

```
CCOMPONENT_ERR(COMPONENT_ERROR
Err)
{
    m_Error = Err;
    m_szTextDetail = NULL;
    m_SystemErr = 0;
    m_szErrorText = NULL;
};

CCOMPONENT_ERR(COMPONENT_ERROR
Err, char *szTextDetail, DWORD dwSystemErr)
{
    m_Error = Err;
    m_szTextDetail = new
char[strlen(szTextDetail)+1];
    strcpy( m_szTextDetail,
szTextDetail );
    m_SystemErr =
dwSystemErr;
    m_szErrorText = NULL;
};

~CCOMPONENT_ERR()
{
    if (m_szTextDetail !=
NULL)
        delete []
m_szTextDetail;
    if (m_szErrorText !=
NULL)
        delete []
m_szErrorText;
};

COMPONENT_ERROR m_Error;
char
*m_szTextDetail;
char
*m_szErrorText;
DWORD
m_SystemErr;

int ErrorType() {return
ERR_TYPE_COMPONENT};
char *ErrorTypeStr() { return
"COMPONENT"; }
int ErrorNum() {return m_Error;};
char *ErrorText();

};

static void WriteMessageToEventLog(LPCTSTR lpszMsg);

////////////////////////////////////
////////////////////////////////////
// CTPCC_Common
class CTPCC_Common :
public ITPCC,
public IObjectControl,
public IObjectConstruct,
```

```

        public
CComObjectRootEx<CComSingleThreadModel>
{
public:
BEGIN_COM_MAP(CTPCC_Common)
    COM_INTERFACE_ENTRY(ITPCC)
    COM_INTERFACE_ENTRY(IObjectControl)
    COM_INTERFACE_ENTRY(IObjectConstruct)
END_COM_MAP()

    CTPCC_Common();
    ~CTPCC_Common();

// ITPCC
public:
    HRESULT __stdcall NewOrder(
        VARIANT txn_in, VARIANT* txn_out);
    HRESULT __stdcall Payment(
        VARIANT txn_in, VARIANT* txn_out);
    HRESULT __stdcall Delivery(
        VARIANT txn_in, VARIANT* txn_out) {return
E_NOTIMPL;}
    HRESULT __stdcall StockLevel( VARIANT
txn_in, VARIANT* txn_out);
    HRESULT __stdcall OrderStatus(
        VARIANT txn_in, VARIANT* txn_out);

    HRESULT __stdcall CallSetComplete();

// IObjectControl
    STDMETHODCALLTYPE CanBePooled() { return
m_bCanBePooled; }
    STDMETHODCALLTYPE Activate() { return S_OK; }
    // we don't support COM Services
    transactions (no enlistment)
    STDMETHODCALLTYPE Deactivate() { /*
nothing to do */ }

// IObjectConstruct
    STDMETHODCALLTYPE Construct(IDispatch * pUnk);

// helper methods
private:
    BOOL m_bCanBePooled;
    CTPCC_BASE *m_pTxn;

    struct COM_DATA
    {
        int retval;
        int error;
        union
        {
            NEW_ORDER_DATA
            PAYMENT_DATA
            DELIVERY_DATA
            STOCK_LEVEL_DATA
        }
    };
};

```

```

ORDER_STATUS_DATA
OrderStatus;
    };
};

////////////////////////////////////
////////////////////////////////////
// CTPCC
class CTPCC :
    public CTPCC_Common,
    public CComCoClass<CTPCC, &CLSID_TPCC>
{
public:
    DECLARE_REGISTRY_RESOURCEID(IDR_TPCC)

    BEGIN_COM_MAP(CTPCC)
        //COM_INTERFACE_ENTRY2(IUnknown,
CComObjectRootEx<CComSingleThreadModel>)
        COM_INTERFACE_ENTRY2(IUnknown, ITPCC)
        COM_INTERFACE_ENTRY_CHAIN(CTPCC_Common)
    END_COM_MAP()
};

////////////////////////////////////
////////////////////////////////////
// CNewOrder
class CNewOrder :
    public CTPCC_Common,
    public CComCoClass<CNewOrder,
&CLSID_NewOrder>
{
public:
    DECLARE_REGISTRY_RESOURCEID(IDR_NEWORDER)

    BEGIN_COM_MAP(CNewOrder)
        // COM_INTERFACE_ENTRY2(IUnknown,
CComObjectRootEx)
        COM_INTERFACE_ENTRY2(IUnknown, ITPCC)
        COM_INTERFACE_ENTRY_CHAIN(CTPCC_Common)
    END_COM_MAP()

// ITPCC
public:
//
    HRESULT __stdcall NewOrder(
        VARIANT txn_in, VARIANT* txn_out) {return
E_NOTIMPL;}
    HRESULT __stdcall Payment(
        VARIANT txn_in, VARIANT* txn_out) {return
E_NOTIMPL;}
    HRESULT __stdcall StockLevel( VARIANT
txn_in, VARIANT* txn_out) {return E_NOTIMPL;}
    HRESULT __stdcall OrderStatus(
        VARIANT txn_in, VARIANT* txn_out) {return
E_NOTIMPL;}
};

```

```

////////////////////////////////////
////////////////////////////////////
// COrderStatus
class COrderStatus :
    public CTPCC_Common,
    public CComCoClass<COrderStatus,
&CLSID_OrderStatus>
{
public:
    DECLARE_REGISTRY_RESOURCEID(IDR_ORDERSTATUS)

    BEGIN_COM_MAP(COrderStatus)
        // COM_INTERFACE_ENTRY2(IUnknown,
CComObjectRootEx)
        COM_INTERFACE_ENTRY2(IUnknown, ITPCC)
        COM_INTERFACE_ENTRY_CHAIN(CTPCC_Common)
    END_COM_MAP()

// ITPCC
public:
    HRESULT __stdcall NewOrder(
        VARIANT txn_in, VARIANT* txn_out) {return
E_NOTIMPL;}
    HRESULT __stdcall Payment(
        VARIANT txn_in, VARIANT* txn_out) {return
E_NOTIMPL;}
    HRESULT __stdcall StockLevel( VARIANT
txn_in, VARIANT* txn_out) {return E_NOTIMPL;}
    //
    HRESULT __stdcall OrderStatus(
        VARIANT txn_in, VARIANT* txn_out) {return
E_NOTIMPL;}
};

////////////////////////////////////
////////////////////////////////////
// CPayment
class CPayment :
    public CTPCC_Common,
    public CComCoClass<CPayment,
&CLSID_Payment>
{
public:
    DECLARE_REGISTRY_RESOURCEID(IDR_PAYMENT)

    BEGIN_COM_MAP(CPayment)
        // COM_INTERFACE_ENTRY2(IUnknown,
CComObjectRootEx)
        COM_INTERFACE_ENTRY2(IUnknown, ITPCC)
        COM_INTERFACE_ENTRY_CHAIN(CTPCC_Common)
    END_COM_MAP()

// ITPCC
public:
    HRESULT __stdcall NewOrder(
        VARIANT txn_in, VARIANT* txn_out) {return
E_NOTIMPL;}
    //
    HRESULT __stdcall Payment(
        VARIANT txn_in, VARIANT* txn_out) {return
E_NOTIMPL;}
};

```

```

        HRESULT __stdcall StockLevel( VARIANT
txn_in, VARIANT* txn_out) {return E_NOTIMPL;}
        HRESULT __stdcall OrderStatus(
        VARIANT txn_in, VARIANT* txn_out) {return
E_NOTIMPL;}
};

////////////////////////////////////
////////////////////////////////////
// CStockLevel
class CStockLevel :
    public CTPCC_Common,
    public CComCoClass<CStockLevel,
&CLSID_StockLevel>
{
public:
DECLARE_REGISTRY_RESOURCEID(IDR_STOCKLEVEL)

BEGIN_COM_MAP(CStockLevel)
//      COM_INTERFACE_ENTRY2(IUnknown,
CComObjectRootEx)
        COM_INTERFACE_ENTRY2(IUnknown, ITPCC)
        COM_INTERFACE_ENTRY_CHAIN(CTPCC_Common)
END_COM_MAP()

// ITPCC
public:
        HRESULT __stdcall NewOrder(
        VARIANT txn_in, VARIANT* txn_out) {return
E_NOTIMPL;}
        HRESULT __stdcall Payment(
        VARIANT txn_in, VARIANT* txn_out) {return
E_NOTIMPL;}
//      HRESULT __stdcall StockLevel( VARIANT
txn_in, VARIANT* txn_out) {return E_NOTIMPL;}
        HRESULT __stdcall OrderStatus(
        VARIANT txn_in, VARIANT* txn_out) {return
E_NOTIMPL;}
};

```

mon_client.c

```

/*
 *      mon_client.c
 */

#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <stdarg.h>
#include <time.h>
#include <pthread.h>
#include <tpm/mon/mon.h>
#include <utils/trace.h>
#include "../include/delivery.h"
#include "../include/neworder.h"
#include "../include/payment.h"
#include "../include/stocklevel.h"

```

```

#include "../include/orderstatus.h"
#include "../include/tpcc_type.h"
#include "mon_client.h"
#include "client_utils.h"

extern total_tran_count_t *perfClntDataInit();
static void read_mon_environment(void);

static char *cellName;
static int envRetrieval = 0;
static int useSecurity = FALSE;
static CRITICAL_SECTION  init_lock;
static total_tran_count_t *pClientInfo=NULL; /*
keep stats for the client process */
static num_active_threads = 0;
static int iStatsFrequency = 1;
FILE *errtpcc;
char *errFile = "C:/temp/tpcc_encina.out";
enc_status_t enc_status;

#define NewOrder_code      NEWO_TRANS
#define Payment_code      PAYMENT_TRANS
#define OrderStatus_code  ORDER_STAT_TRANS
#define Delivery_code     DELIVERY_TRANS
#define StockLevel_code   STOCK_TRANS

#define INT_ENV_VALUE(var, default) \
    (var = getenv(#var) ? atoi(getenv(#var)) : default)

#define PRE_RPC_WORK(headerP, tran, sub_tran) \
    if (iStatsFrequency > 0) \
        pre_rpc(headerP, tran, sub_tran);

    else
        \
            (headerP)->stats = 0;
#define POST_RPC_WORK(headerP, tran) \
    if (iStatsFrequency > 0) \
        post_rpc(headerP, tran)

/* CALTPCC
 * Macro to sends 1 RPC and then handles any errors.
 *
 * The macro takes the name of the RPC (e.g.,
NewOrder)
 * and makes the RPC by calling the appropriate
function
 * (e.g., impTPCCNewOrder).
 */
#define CALLTPCC(name,length,dataP,header,trpcStatusP)
\
{
\
UTIL_CONCAT(impTPCC,name)(length,dataP,&header,trpcSt
atusP);
    if (*(trpcStatusP)) {
\

```

```

        char msg[100];
        \
        sprintf(msg, "TRPC error during impTPCC%s",
UTIL_STRING(name));
        header.returncode = TRPC_ERROR;
        \
        encina_error_message(msg, *(trpcStatusP));
        \
    } else if ((header.returncode != TPCC_SUCCESS) &&
        \
            (header.returncode != INVALID_NEWO)) {
        \
        char msg[100];
        \
        sprintf(msg, "App error during impTPCC%s: ",
UTIL_STRING(name));
        encina_error_message(msg, header.returncode);
        \
    }
}

/*
 * pre_rpc -- For debug purposes
 *
 * Called before an RPC is made.
 * Set the state of the thread and keep track of the
time the RPC is sent.
 * This is used by the Background thread to report
the state of the client.
 */
static void pre_rpc(data_header *headerP,
        int tran_type,
        int sub_tran_type)
{
    if (iStatsFrequency < 1) {
        headerP->stats = 0;
    } else {
        int num;
        num = ++ (pClientInfo->tran[tran_type].num);
        headerP->stats = (num % iStatsFrequency==0) ?
1 : 0;
        if (headerP->stats)
            { /* measure the time for RT */
                get_local_time(&headerP->clnt_start);
                headerP->srv_start.sec = 0; /*
initialize the server time */
                headerP->srv_start.usec = 0;
                headerP->srv_end.sec = 0;
                headerP->srv_end.usec = 0;
            }
    }
}

/*
 * post_rpc
 *
 * Called when the RPC returns from the server
 */

```

```

* Keeps track of the client response time and the
server response time
* as well as the state of the thread. This is used
by the background
* debug thread to report the state of the client
*/
static void post_rpc(data_header *headerP,
                    int tran_type)
{
    double time_diff;
    int tran_failed;
    struct timeval start_time, end_time;

    if (headerP->stats)
        get_local_time(&headerP-
>clnt_end);
    else
        return;

    /* Store the info for each client.
    * Note: Since we don't use mutex for performance
    reason, pClientInfo
    * may not be accurate if more than one
    thread work on the same
    * data at a same time. But this should
    give us reasonable info.
    */
    if ((headerP->returncode == TPCC_SUCCESS) ||
        (headerP->returncode == INVALID_NEWO)) {
        tran_failed = 0;
    } else {
        pClientInfo->tran[tran_type].errs ++;
        pClientInfo->errors ++;
        tran_failed = 1;
    }
    if (headerP->stats && tran_type <= MAX_TRAN_TYPE
    && tran_type > 0
        && !tran_failed) {
        /* update total server round trip response
        time */
        start_time.tv_sec = headerP-
>srv_start.sec;
        start_time.tv_usec = headerP-
>srv_start.usec;
        end_time.tv_sec = headerP->srv_end.sec;
        end_time.tv_usec = headerP->srv_end.usec;
        time_diff = time_diff_ms(&end_time,
&start_time);
        pClientInfo->tran[tran_type].RTtotal[1] +=
time_diff;
        DPRINT(("srv start_time %d.%d, end_time
%d.%d, time_diff %f\n",
start_time.tv_sec,          start_time.tv_sec,
start_time.tv_usec,        end_time.tv_sec,
end_time.tv_usec,         time_diff));

        /* update total client round trip response
        time */

```

```

        start_time.tv_sec = headerP-
>clnt_start.sec;
        start_time.tv_usec = headerP-
>clnt_start.usec;
        end_time.tv_sec = headerP->clnt_end.sec;
        end_time.tv_usec = headerP-
>clnt_end.usec;
        time_diff = time_diff_ms(&end_time,
&start_time);
        pClientInfo->tran[tran_type].RTtotal[0] +=
time_diff;
        DPRINT(("clnt start_time %d.%d, end_time
%d.%d, time_diff %f\n",
start_time.tv_sec,          start_time.tv_sec,
start_time.tv_usec,        end_time.tv_sec,
end_time.tv_usec,         time_diff));

        /* update num for the number of trans
        which have RT measured */
        pClientInfo->tran[tran_type].RTcount ++;
    }
}

/*
* The following send_*** functions are called from
CTPCC_ENCINA class.
*/
/*
* send_new_order
* Send a new order request to the server
*/
int send_new_order(long length, unsigned char *dataP)
{
    trpc_status_t trpcStatus;
    data_header header;

    PRE_RPC_WORK(&header, NEWO_TRANS, 0);

    CALLTPCC(NewOrder,length,dataP,header,&trpcStatus)
    POST_RPC_WORK(&header, NEWO_TRANS);
    if (header.returncode == INVALID_NEWO)
        return TPCC_SUCCESS;
    else
        return header.returncode;
}

/*
* send_payment
* Send a payment request to the server
*/
int send_payment(long length, unsigned char *dataP)
{
    trpc_status_t trpcStatus;
    data_header header;

    PRE_RPC_WORK(&header, PAYMENT_TRANS, 0);

```

```

    CALLTPCC(Payment,length,dataP,header,&trpcStatus);
    POST_RPC_WORK(&header, PAYMENT_TRANS);
    return header.returncode;
}

/*
* send_order_status
* Send a order status request to the server
*/
int send_order_status(long length, unsigned char
*dataP)
{
    trpc_status_t trpcStatus;
    data_header header;

    PRE_RPC_WORK(&header, ORDER_STAT_TRANS, 0);

    CALLTPCC(OrderStatus,length,dataP,header,&trpcStatus)
;
    POST_RPC_WORK(&header, ORDER_STAT_TRANS);
    return header.returncode;
}

/*
* send_delivery
* Send a delivery request to the server
*/
int send_delivery(long length, unsigned char *dataP)
{
    trpc_status_t trpcStatus;
    data_header header;

    PRE_RPC_WORK(&header, DELIVERY_TRANS, 0);

    CALLTPCC(Delivery,length,dataP,header,&trpcStatus);
    POST_RPC_WORK(&header, DELIVERY_TRANS);
    return header.returncode;
}

/*
* send_stock_level
* Send a stock level request to the server
*/
int send_stock_level(long length, unsigned char
*dataP)
{
    trpc_status_t trpcStatus;
    data_header header;

    PRE_RPC_WORK(&header, STOCK_TRANS, 0);

    CALLTPCC(StockLevel,length,dataP,header,&trpcStatus);
    POST_RPC_WORK(&header, STOCK_TRANS);
    return header.returncode;
}

/*
* Enroll the client:

```

```

*      get the necessary handles.
*      This function should be called only once. Use
static var client_enrolled to control it.
*/
void enroll_client()
{
    static char *clientName="tpcc_client";
    unsigned long status ;
    static int  client_enrolled = 0;
    unsigned32  client_authnLevel;
    unsigned32  client_authzSvc;
    time_type a_time;
    char err_msg[100];

    MUTEX_INIT(&init_lock);
    get_local_time(&a_time);
    srand(a_time.sec ^ a_time.usec);

    MUTEX_LOCK(&init_lock);
    if (client_enrolled) {
        MUTEX_UNLOCK(&init_lock);
        return;
    }

    /* open output file for tracing */
    errtpcc = fopen(errFile, "w");
    if(!errtpcc)
    {
        sprintf(err_msg, "Cannot open
file %s", errFile);
        CHK_STATUS(1,
ERROR_FILE_NOT_FOUND,err_msg);
    }

    get_time_init();
    // initialize the space for perfmon
    pClientInfo = perfClntDataInit();
    if (pClientInfo == NULL) // in case something
wrong
        pClientInfo =
malloc(sizeof(total_tran_count_t));
    memset(pClientInfo, 0,
sizeof(total_tran_count_t));

    read_mon_environment();

    if(!cellName)
        CHK_STATUS(30, CELL_NAME_UNAVAILABLE,
"ENCINA_TPM_CELL is not set!");

    if (useSecurity) {
        client_authnLevel =
rpc_c_protect_level_connect;
        client_authzSvc =
rpc_c_authz_dce;
    } else {
        client_authnLevel =
rpc_c_protect_level_none;
        client_authzSvc =
rpc_c_authz_none;
    }
}

```

```

if (envRetrieval == 0) {
    ENCINA_CALL_RC("mon_RetrieveEnable",mon_RetrieveEnabl
e(FALSE),status);
    CHK_STATUS(status, MON_RETRIEVEENABLE_FAILED,
"mon_RetrieveEnable failed");
}

err_printf("enroll_client: calling mon_InitClient
\n");

ENCINA_CALL_RC("mon_InitClient",mon_InitClient(client
Name,cellName),status);
    CHK_STATUS(status, MON_INITCLIENT_FAILED,
"mon_InitClient failed");

    DPRINT(("mon_SecuritySetDefaults-> authn %d,
authz %d\n",
        client_authnLevel, client_authzSvc));
    ENCINA_CALL_RC("mon_SecuritySetDefaults",
        mon_SecuritySetDefaults(client_authnLevel,c
lient_authzSvc),
        status);
    CHK_STATUS(status, MON_SECURITYSET_FAILED,
"mon_SecuritySetDefaults failed");

ENCINA_CALL_RC("mon_SetHandleCacheRefreshInterval",
        mon_SetHandleCacheRefreshInterval(300),
status);
    CHK_STATUS(status, MON_SETREFRESHINTERVAL_FAILED,
"mon_SetHandleCacheRefreshInterval
failed");
{
    dbInfo_data_t data;
    trpc_status_t trpcStatus;
    /* Get DB Info -- currently id does not do
anything
    but it will tell us if there is a server
out there.
    Better to know instead of when all the
terminals
    are up and ready
    */
    impTPCCNOInfo(&data, &trpcStatus);
    if (trpcStatus) {
        char msg[100];
        sprintf(msg, "TRPC error during db info
at init.");
        encina_error_message(msg, trpcStatus);
        CHK_STATUS(33,NOINFO_TRPC_ERROR,
"TRPC error during db info at
init");
    }
}

client_enrolled = 1;

```

```

MUTEX_UNLOCK(&init_lock);
err_printf("end of enroll_client\n");
}

/*-----*/
/*      Read environment paramaters and registry
entries      */
/*-----*/
static void read_mon_environment()
{
    char *env_str;
    char *registryKey =
"SOFTWARE\\TransarcCorporation\\TxTpcc";
    HKEY hKey;
    DWORD size;
    DWORD type;
    char szTmp[256];

    cellName = getenv("ENCINA_TPM_CELL");
    CHECK_ENVIRON(cellName, "ENCINA_TPM_CELL");

    if (env_str = getenv("TPCC_ENV_RETRIEVE")) {
        envRetrieval = atoi(env_str);
    }

    if ( RegOpenKeyEx(HKEY_LOCAL_MACHINE,
registryKey, 0, KEY_READ, &hKey) != ERROR_SUCCESS )
        return;

    size = sizeof(szTmp);
    if ( RegQueryValueEx(hKey, "StatsFrequency", 0,
&type, szTmp, &size)==ERROR_SUCCESS)
        iStatsFrequency = atoi(szTmp);

    RegCloseKey(hKey);
}

mon_client.h
/*
*      mon_client.h
*
*/

#ifndef MON_CLIENT_H
#define MON_CLIENT_H

#define MUTEX_T CRITICAL_SECTION
#define MUTEX_LOCK(a) EnterCriticalSection(a)
#define MUTEX_UNLOCK(a) LeaveCriticalSection(a)
#define MUTEX_INIT(mut)
InitializeCriticalSection(mut)
#define MUTEX_DESTROY(mut) DeleteCriticalSection(mut)
#define ERROROUT errtpcc

/*initialization status */
#define INIT_SUCCESS 0

```

```

#define INIT_FAILED 1
#define CELL_NAME_UNAVAILABLE 2
#define MON_RETRIEVEENABLE_FAILED 3
#define MON_INITCLIENT_FAILED 4
#define MON_SECURITYSET_FAILED 5
#define MON_SETREFRESHINTERVAL_FAILED 6
#define NOINFO_TRPC_ERROR 7
#define ENROLL_CLIENT_EXCEPTION 8
#define ERROROUT_FILE_NOT_FOUND 9
#define LOG_FILE_NOT_FOUND 10
#define TPCC_KEY_NOT_FOUND 11
#define TERM_ALLOC_FAILED 12

/*
 * Routines and declarations that are common to all
 * clients
 */
#ifdef __cplusplus
extern "C" {
#endif
int send_new_order(long, unsigned char *);
int send_payment(long, unsigned char *);
int send_order_status(long, unsigned char *);
int send_delivery(long, unsigned char *);
int send_stock_level(long, unsigned char *);
void enroll_client();
#ifdef __cplusplus
}
#endif

#endif /* MON_CLIENT_H */

```

neworder.h

```

#ifdef TRANSARC_neworder_h
#define TRANSARC_neworder_h

#include <trpc/trpc.h>
#include "_neworder.h"

#include <encina/c_prologue.h>

#ifdef BUILDDDL
#define DLLEXPORT __declspec( dlllexport )
#else
#define DLLEXPORT extern
#endif

#ifdef ENCINA_STUB_CALLING
#define ENCINA_STUB_CALLING ENCINA_RPC_CALLING
#endif

#define neworder_v1_0_c_ifspec
        _neworder_v1_0_c_ifspec
#define neworder_v1_0_s_ifspec
        _neworder_v1_0_s_ifspec

typedef struct neworder_v1_0_epv {
void (ENCINA_STUB_CALLING *impTPCCNewOrder) (

```

```

#ifdef IDL_PROTOTYPES
        idl_long_int length,
        idl_char *dataP,
        data_header *headerP,
        trpc_status_t *trpcStatus
#endif
};

void (ENCINA_STUB_CALLING *impTPCCNOInfo) (
#ifdef IDL_PROTOTYPES
        dbInfo_data_t *dataP,
        trpc_status_t *trpcStatus
#endif
);

} neworder_v1_0_epv_t;

DLLEXPORT void ENCINA_STUB_CALLING impTPCCNewOrder (
#ifdef IDL_PROTOTYPES
        idl_long_int length,
        idl_char *dataP,
        data_header *headerP,
        trpc_status_t *trpcStatus
#endif
);

DLLEXPORT void ENCINA_STUB_CALLING impTPCCNOInfo (
#ifdef IDL_PROTOTYPES
        dbInfo_data_t *dataP,
        trpc_status_t *trpcStatus
#endif
);

trpc_handle_t          ENCINA_CALLING
mon_handle_t_tranBind(
#ifdef IDL_PROTOTYPES
        mon_handle_t          handle,
        trpc_tranInfo_t      *tranInfoP,
        trpc_ifSpec_t        *ifSpecP
#endif
);

void          ENCINA_CALLING mon_handle_t_tranUnBind(
#ifdef IDL_PROTOTYPES
        mon_handle_t          handle,
        trpc_handle_t        trpcHandle,
        trpc_tranInfo_t      *tranInfoP,
        trpc_ifSpec_t        *ifSpecP
#endif
);

trpc_handle_t          ENCINA_CALLING
mon_handle_t_tranBind(
#ifdef IDL_PROTOTYPES
        mon_handle_t          handle,
        trpc_tranInfo_t      *tranInfoP,
        trpc_ifSpec_t        *ifSpecP

```

```

#endif
);

void          ENCINA_CALLING mon_handle_t_tranUnBind(
#ifdef IDL_PROTOTYPES
        mon_handle_t          handle,
        trpc_handle_t        trpcHandle,
        trpc_tranInfo_t      *tranInfoP,
        trpc_ifSpec_t        *ifSpecP
#endif
);

extern neworder_v1_0_epv_t
        neworder_v1_0_client_epv;
extern _neworder_v1_0_epv_t
        neworder_v1_0_manager_epv;
extern rpc_mgr_epv_t
        neworder_v1_0_mgr_epv;

#include <encina/c_epilogue.h>
#endif /* TRANSARC_neworder_h */

orderstatus.h

#ifdef TRANSARC_orderstatus_h
#define TRANSARC_orderstatus_h

#include <trpc/trpc.h>
#include "_orderstatus.h"

#include <encina/c_prologue.h>

#ifdef BUILDDDL
#define DLLEXPORT __declspec( dlllexport )
#else
#define DLLEXPORT extern
#endif

#ifdef ENCINA_STUB_CALLING
#define ENCINA_STUB_CALLING ENCINA_RPC_CALLING
#endif

#define orderstatus_v1_0_c_ifspec
        _orderstatus_v1_0_c_ifspec
#define orderstatus_v1_0_s_ifspec
        _orderstatus_v1_0_s_ifspec

typedef struct orderstatus_v1_0_epv {
void (ENCINA_STUB_CALLING *impTPCCOrderStatus) (
#ifdef IDL_PROTOTYPES
        idl_long_int length,
        idl_char *dataP,
        data_header *headerP,
        trpc_status_t *trpcStatus
#endif
);

} orderstatus_v1_0_epv_t;

```

```

DLLEXPORT void ENCINA_STUB_CALLING impTPCCOrderStatus
(
#ifdef IDL_PROTOTYPES
    idl_long_int length,
    idl_char *dataP,
    data_header *headerP,
    trpc_status_t *trpcStatus
#endif
);

trpc_handle_t ENCINA_CALLING
mon_handle_t_tranBind(
#ifdef IDL_PROTOTYPES
    mon_handle_t handle,
    trpc_tranInfo_t *tranInfoP,
    trpc_ifSpec_t *ifSpecP
#endif
);

void ENCINA_CALLING mon_handle_t_tranUnBind(
#ifdef IDL_PROTOTYPES
    mon_handle_t handle,
    trpc_handle_t trpcHandle,
    trpc_tranInfo_t *tranInfoP,
    trpc_ifSpec_t *ifSpecP
#endif
);

trpc_handle_t ENCINA_CALLING
mon_handle_t_tranBind(
#ifdef IDL_PROTOTYPES
    mon_handle_t handle,
    trpc_tranInfo_t *tranInfoP,
    trpc_ifSpec_t *ifSpecP
#endif
);

void ENCINA_CALLING mon_handle_t_tranUnBind(
#ifdef IDL_PROTOTYPES
    mon_handle_t handle,
    trpc_handle_t trpcHandle,
    trpc_tranInfo_t *tranInfoP,
    trpc_ifSpec_t *ifSpecP
#endif
);

extern orderstatus_v1_0_epv_t
orderstatus_v1_0_client_epv;
extern _orderstatus_v1_0_epv_t
orderstatus_v1_0_manager_epv;
extern rpc_mgr_epv_t
orderstatus_v1_0_mgr_epv;

#include <encina/c_epilogue.h>
#endif /* TRANSARC_orderstatus_h */

payment.h
#ifdef TRANSARC_payment_h

```

```

#define TRANSARC_payment_h

#include <trpc/trpc.h>
#include "_payment.h"

#include <encina/c_prologue.h>

#ifdef BUILDDDL
#define DLLEXPORT __declspec( dllexport )
#else
#define DLLEXPORT extern
#endif

#ifdef ENCINA_STUB_CALLING
#define ENCINA_STUB_CALLING ENCINA_RPC_CALLING
#endif

#define payment_v1_0_c_ifspec_payment_v1_0_c_ifspec
#define payment_v1_0_s_ifspec_payment_v1_0_s_ifspec

typedef struct payment_v1_0_epv {
void (ENCINA_STUB_CALLING *impTPCCPayment) (
#ifdef IDL_PROTOTYPES
    idl_long_int length,
    idl_char *dataP,
    data_header *headerP,
    trpc_status_t *trpcStatus
#endif
);
} payment_v1_0_epv_t;

DLLEXPORT void ENCINA_STUB_CALLING impTPCCPayment (
#ifdef IDL_PROTOTYPES
    idl_long_int length,
    idl_char *dataP,
    data_header *headerP,
    trpc_status_t *trpcStatus
#endif
);

trpc_handle_t ENCINA_CALLING
mon_handle_t_tranBind(
#ifdef IDL_PROTOTYPES
    mon_handle_t handle,
    trpc_tranInfo_t *tranInfoP,
    trpc_ifSpec_t *ifSpecP
#endif
);

void ENCINA_CALLING mon_handle_t_tranUnBind(
#ifdef IDL_PROTOTYPES
    mon_handle_t handle,
    trpc_handle_t trpcHandle,
    trpc_tranInfo_t *tranInfoP,
    trpc_ifSpec_t *ifSpecP
#endif
);

```

```

trpc_handle_t ENCINA_CALLING
mon_handle_t_tranBind(
#ifdef IDL_PROTOTYPES
    mon_handle_t handle,
    trpc_tranInfo_t *tranInfoP,
    trpc_ifSpec_t *ifSpecP
#endif
);

void ENCINA_CALLING mon_handle_t_tranUnBind(
#ifdef IDL_PROTOTYPES
    mon_handle_t handle,
    trpc_handle_t trpcHandle,
    trpc_tranInfo_t *tranInfoP,
    trpc_ifSpec_t *ifSpecP
#endif
);

extern payment_v1_0_epv_t
payment_v1_0_client_epv;
extern _payment_v1_0_epv_t
payment_v1_0_manager_epv;
extern rpc_mgr_epv_t
payment_v1_0_mgr_epv;

#include <encina/c_epilogue.h>
#endif /* TRANSARC_payment_h */

ReadRegistry.c
pp
/* FILE: READREGISTRY.CPP
* Microsoft
TPC-C Kit Ver. 4.20.000
* Copyright
Microsoft, 1999
* All Rights Reserved
* not yet
audited
* PURPOSE: Implementation for TPC-C Tuxedo
class.
* Contact: Charles Levine
(clevine@microsoft.com)
* Change history:
* 4.20.000 - first version
*/

/* FUNCTION: ReadTPCCRegistrySettings
*
* PURPOSE: This function reads the NT
registry for startup parameters. There parameters are
* under the TPCC key.
*
* RETURNS FALSE = no errors

```



```

*
registry TRUE = error reading
*/
BOOL ReadTPCCRegistrySettings( TPCCREGISTRYDATA *pReg
)
{
    HKEY hKey;
    DWORD size;
    DWORD type;
    DWORD dwTmp;
    char szTmp[256];

    if ( RegOpenKeyEx(HKEY_LOCAL_MACHINE,
"SOFTWARE\\Microsoft\\TPCC", 0, KEY_READ, &hKey) !=
ERROR_SUCCESS )
        return TRUE;

    // determine database protocol to use; may
be either ODBC or DBLIB
    pReg->eDB_Protocol = Unspecified;
    size = sizeof(szTmp);
    if ( RegQueryValueEx(hKey, "DB_Protocol",
0, &type, (BYTE *)&szTmp, &size) == ERROR_SUCCESS )
    {
        if ( !strcmp(szTmp,
szDBNames[ODBC]) )
            pReg->eDB_Protocol =
ODBC;
        else if ( !strcmp(szTmp,
szDBNames[DBLIB]) )
            pReg->eDB_Protocol =
DBLIB;
    }

    pReg->eTxnMon = None;
    // determine txn monitor to use; may be
either TUXEDO, or blank
    size = sizeof(szTmp);
    if ( RegQueryValueEx(hKey, "TxnMonitor", 0,
&type, (BYTE *)&szTmp, &size) == ERROR_SUCCESS )
    {
        if ( !strcmp(szTmp,
szTxnMonNames[TUXEDO]) )
            pReg->eTxnMon = TUXEDO;
        else if ( !strcmp(szTmp,
szTxnMonNames[ENCINA]) )
            pReg->eTxnMon = ENCINA;
        else if ( !strcmp(szTmp,
szTxnMonNames[COM]) )
            pReg->eTxnMon = COM;
    }

    pReg->bCOM_SinglePool = FALSE;
    size = sizeof(szTmp);
    if ( RegQueryValueEx(hKey,
"COM_SinglePool", 0, &type, (BYTE *)&szTmp, &size) ==
ERROR_SUCCESS )
    {
        if ( !strcmp(szTmp, "YES") )
            pReg->bCOM_SinglePool =
TRUE;
    }
}

```

```

}
pReg->dwMaxConnections = 0;
size = sizeof(dwTmp);
if ( ( RegQueryValueEx(hKey,
"MaxConnections", 0, &type, (LPBYTE)&dwTmp, &size) ==
ERROR_SUCCESS )
    && (type == REG_DWORD) )
    pReg->dwMaxConnections = dwTmp;

pReg->dwMaxPendingDeliveries = 0;
size = sizeof(dwTmp);
if ( ( RegQueryValueEx(hKey,
"MaxPendingDeliveries", 0, &type, (LPBYTE)&dwTmp,
&size) == ERROR_SUCCESS )
    && (type == REG_DWORD) )
    pReg->dwMaxPendingDeliveries =
dwTmp;

pReg->dwNumberOfDeliveryThreads = 0;
size = sizeof(dwTmp);
if ( ( RegQueryValueEx(hKey,
"NumberOfDeliveryThreads", 0, &type, (LPBYTE)&dwTmp,
&size) == ERROR_SUCCESS )
    && (type == REG_DWORD) )
    pReg->dwNumberOfDeliveryThreads =
dwTmp;

size = sizeof( pReg->szPath );
if ( RegQueryValueEx(hKey, "Path", 0,
&type, (BYTE *)&pReg->szPath, &size) != ERROR_SUCCESS
)
    pReg->szPath[0] = 0;

size = sizeof( pReg->szDbServer );
if ( RegQueryValueEx(hKey, "DbServer", 0,
&type, (BYTE *)&pReg->szDbServer, &size) !=
ERROR_SUCCESS )
    pReg->szDbServer[0] = 0;

size = sizeof( pReg->szDbName );
if ( RegQueryValueEx(hKey, "DbName", 0,
&type, (BYTE *)&pReg->szDbName, &size) !=
ERROR_SUCCESS )
    pReg->szDbName[0] = 0;

size = sizeof( pReg->szDbUser );
if ( RegQueryValueEx(hKey, "DbUser", 0,
&type, (BYTE *)&pReg->szDbUser, &size) !=
ERROR_SUCCESS )
    pReg->szDbUser[0] = 0;

size = sizeof( pReg->szDbPassword );
if ( RegQueryValueEx(hKey, "DbPassword", 0,
&type, (BYTE *)&pReg->szDbPassword, &size) !=
ERROR_SUCCESS )
    pReg->szDbPassword[0] = 0;

size = sizeof( pReg->szSPPrefix );

```

```

if ( RegQueryValueEx(hKey, L"SPPrefix", 0,
&type, (BYTE *)&pReg->szSPPrefix, &size) !=
ERROR_SUCCESS )
    pReg->szSPPrefix[0] = L'\0';

pReg->dwConnectDelay = 0;
size = sizeof(dwTmp);
if ( ( RegQueryValueEx(hKey,
"ConnectDelay", 0, &type, (LPBYTE)&dwTmp, &size) ==
ERROR_SUCCESS )
    && (type == REG_DWORD) )
    pReg->dwConnectDelay = dwTmp;

pReg->bCallNoDuplicatesNewOrder = FALSE;
size = sizeof(dwTmp);
if ( ( RegQueryValueEx(hKey,
"CallNoDuplicatesNewOrder", 0, &type, (LPBYTE)&dwTmp,
&size) == ERROR_SUCCESS )
    && (type == REG_DWORD) )
    pReg->bCallNoDuplicatesNewOrder =
dwTmp;

RegCloseKey(hKey);

return FALSE;
}

```

ReadRegistry.h

```

/* FILE: ReadRegistry.h
* Microsoft
* TPC-C Kit Ver. 4.20.000
* Copyright
* Microsoft, 1999
* All Rights Reserved
* not audited
* PURPOSE: Header for registry related code.
* Change history:
* 4.20.000 - first version
*/

enum DBPROTOCOL { Unspecified, ODBC, DBLIB };
const char *szDBNames[] = { "Unspecified", "ODBC",
"DBLIB" };

enum TXNMON { None, TUXEDO, ENCINA, COM };
const char *szTxnMonNames[] = { "NONE", "TUXEDO",
"ENCINA", "COM" };

//This structure defines the data necessary to keep
distinct for each terminal or client connection.
typedef struct _TPCCREGISTRYDATA
{
    enum DBPROTOCOL eDB_Protocol;
    enum TXNMON eTxnMon;
    BOOL bCOM_SinglePool;
    DWORD dwMaxConnections;
}

```

```

        DWORD dwMaxPendingDeliveries;
        DWORD dwNumberOfDeliveryThreads;
        char szPath[128];
        char szDbServer[32];
        char szDbName[32];
        char szDbUser[32];
        char szDbPassword[32];
        wchar_t szSPPrefix[32];
        //tpcc_odbc.dll stored procedures prefix
        DWORD dwConnectDelay; // delay in
ms to use in pacing connection open and close
        BOOL bCallNoDuplicatesNewOrder; //
whether to check for non-duplicate item ids and call
a different New Order SP
    } TPCCREGISTRYDATA, *PTPCCREGISTRYDATA;

BOOL ReadTPCCRegistrySettings( TPCCREGISTRYDATA *pReg
);

```

RESOURCE.H

```

//{{(NO DEPENDENCIES)}
// Microsoft Visual C++ generated include file.
// Used by install.rc
//
#define IDD_DIALOG1 101
#define IDI_ICON1 102
#define IDR_TPCCDLL 103
#define IDD_DIALOG2 105
#define IDI_ICON2 106
#define IDR_DELIVERY 107
#define IDD_DIALOG3 108
#define IDR_LICENSE1 112
#define IDD_DIALOG4 113
#define IDR_TPCCOBJ1 117
#define IDR_TPCCSTUB1 118
#define IDR_DBLIB_DLL 122
#define IDR_ODBC_DLL 123
#define IDR_TUXEDO_APP 124
#define IDR_TUXEDO_DLL 125
#define IDR_COM_DLL 126
#define IDR_COMPS_DLL 127
#define IDR_COMALL_DLL 128
#define IDR_COMTYPLIB_DLL 129
#define IDR_MSVCRT701 130
#define BN_LOG 1001
#define ED_KEEP 1002
#define ED_THREADS 1003
#define ED_THREADS2 1004
#define IDC_PATH 1007
#define IDC_VERSION 1009
#define IDC_RESULTS 1010
#define IDC_PROGRESS1 1011
#define IDC_STATUS 1012
#define IDC_BUTTON1 1013
#define ED_MAXCONNECTION 1014
#define ED_IIS_MAX_THREAD_POOL_LIMIT 1015
#define ED_MAXDELIVERIES 1016
#define ED_WEB_SERVICE_BACKLOG_QUEUE_SIZE 1017
#define ED_IIS_THREAD_TIMEOUT 1018

```

```

#define ED_IIS_LISTEN_BACKLOG 1019
#define IDC_DBLIB 1021
#define IDC_LICENSE 1022
#define IDC_ODBC 1022
#define IDC_CONNECT_POOL 1023
#define ED_DB_SERVER 1023
#define ED_USER_CONNECT_DELAY_TIME 1024
#define ED_DB_USER_ID 1024
#define IDC_MTS 1025
#define IDC_TM_MTS 1025
#define IDC_TM_TUXEDO 1026
#define IDC_TM_NONE 1027
#define ED_DB_PASSWORD 1028
#define ED_DB_NAME 1029
#define IDC_TM_ENCINA 1030

// Next default values for new objects
//
#ifdef APSTUDIO_INVOKED
#ifndef APSTUDIO_READONLY_SYMBOLS
#define _APS_NEXT_RESOURCE_VALUE 131
#define _APS_NEXT_COMMAND_VALUE 40001
#define _APS_NEXT_CONTROL_VALUE 1031
#define _APS_NEXT_SYMED_VALUE 101
#endif
#endif

```

stocklevel.h

```

#ifdef TRANSARC_stocklevel_h
#define TRANSARC_stocklevel_h

#include <trpc/trpc.h>
#include "_stocklevel.h"

#include <encina/c_prologue.h>

#ifdef BUILDDDL
#define DLLEXPORT __declspec( dlllexport )
#else
#define DLLEXPORT extern
#endif

#ifdef ENCINA_STUB_CALLING
#define ENCINA_STUB_CALLING ENCINA_RPC_CALLING
#endif

#define stocklevel_v1_0_c_ifspec
        _stocklevel_v1_0_c_ifspec
#define stocklevel_v1_0_s_ifspec
        _stocklevel_v1_0_s_ifspec

typedef struct stocklevel_v1_0_epv {
void (ENCINA_STUB_CALLING *impTPCCStockLevel) (
#ifdef IDL_PROTOTYPES
        idl_long_int length,
        idl_char *dataP,
        data_header *headerP,
        trpc_status_t *trpcStatus

```

```

#endif
);
} stocklevel_v1_0_epv_t;

DLLEXPORT void ENCINA_STUB_CALLING impTPCCStockLevel
(
#ifdef IDL_PROTOTYPES
        idl_long_int length,
        idl_char *dataP,
        data_header *headerP,
        trpc_status_t *trpcStatus
#endif
);

trpc_handle_t ENCINA_CALLING
mon_handle_t tranBind(
#ifdef IDL_PROTOTYPES
        mon_handle_t handle,
        trpc_tranInfo_t *tranInfoP,
        trpc_ifSpec_t *ifSpecP
#endif
);

void ENCINA_CALLING mon_handle_t tranUnBind(
#ifdef IDL_PROTOTYPES
        mon_handle_t handle,
        trpc_handle_t trpcHandle,
        trpc_tranInfo_t *tranInfoP,
        trpc_ifSpec_t *ifSpecP
#endif
);

trpc_handle_t ENCINA_CALLING
mon_handle_t tranBind(
#ifdef IDL_PROTOTYPES
        mon_handle_t handle,
        trpc_tranInfo_t *tranInfoP,
        trpc_ifSpec_t *ifSpecP
#endif
);

void ENCINA_CALLING mon_handle_t tranUnBind(
#ifdef IDL_PROTOTYPES
        mon_handle_t handle,
        trpc_handle_t trpcHandle,
        trpc_tranInfo_t *tranInfoP,
        trpc_ifSpec_t *ifSpecP
#endif
);

extern stocklevel_v1_0_epv_t
        stocklevel_v1_0_client_epv;
extern _stocklevel_v1_0_epv_t
        stocklevel_v1_0_manager_epv;
extern rpc_mgr_epv_t
        stocklevel_v1_0_mgr_epv;

#include <encina/c_epilogue.h>
#endif /* TRANSARC_stocklevel_h */

```

tpcc.cpp

```
/* FILE: TPCC.C Microsoft
 *
 * TPC-C Kit Ver. 4.20.000 Copyright
 * Microsoft, 1999
 * All Rights Reserved
 *
 * Version
 * 4.10.000 audited by Richard Gimarc, Performance
 * Metrics, 3/17/99
 *
 * PURPOSE: Main module for TPCC.DLL which is
 * an ISAPI service dll.
 * Contact: Charles Levine
 * (clevine@microsoft.com)
 *
 * Change history:
 * 4.20.000 - reworked error
 * handling; added options for COM and Encina txn
 * monitors
 */

#include <windows.h>
#include <process.h>
#include <tchar.h>
#include <stdio.h>
#include <stdarg.h>
#include <malloc.h>
#include <stdlib.h>
#include <string.h>
#include <time.h>
#include <sys\timeb.h>
#include <io.h>
#include <assert.h>

#include <sqltypes.h>

#ifdef ICECAP
#include <icapexp.h>
#endif

#include "..\..\common\src\trans.h"
//tpckit transaction header contains
//definitions of structures specific to TPC-C
#include "..\..\common\src\error.h"
#include "..\..\common\src\txn_base.h"
#include "..\..\common\src\ReadRegistry.h"

#include "..\..\common\txnlog\include\rtetime.h"
#include "..\..\common\txnlog\include\spinlock.h"
#include "..\..\common\txnlog\include\txnlog.h"

// Database layer includes
#include "..\..\db_dblib_dll\src\tpcc_dblib.h"
// DBLIB implementation of TPC-C txns
#include "..\..\db_odbc_dll\src\tpcc_odbc.h"
// ODBC implementation of TPC-C txns
```

```
// Txn monitor layer includes
#include "..\..\tm_com_dll\src\tpcc_com.h"
// COM Services implementation on
TPC-C txns
#include "..\..\tm_tuxedo_dll\src\tpcc_tux.h"
// interface to Tuxedo libraries
#include "..\..\tm_encina_dll\src\tpcc_enc.h"
// interface to Encina libraries

#include "httpext.h"
//ISAPI DLL information header
#include "tpcc.h"
//this dlls specific structure, value e.t.
header.

#define LEN_ERR_STRING 256

// defines for Make<Txn>Form calls to distinguish
input and output flavors
#define OUTPUT_FORM 0
#define INPUT_FORM 1

char
szMyComputerName[MAX_COMPUTERNAME_LENGTH+1]
;

//Terminal client id structure
TERM Term = { 0, 0, 0, NULL };

// The WEBCLIENT_VERSION string specifies the version
level of this web client interface.
// The RTE must be synchronized with the interface
level on login, otherwise the login
// will fail. This is a sanity check to catch
problems resulting from mismatched versions
// of the RTE and web client.
#define WEBCLIENT_VERSION "420"

static CRITICAL_SECTION
TermCriticalSection;

static HINSTANCE hLibInstanceTm = NULL;
static HINSTANCE hLibInstanceDb = NULL;

TYPE_CTPCC_DBLIB *pCTPCC_DBLIB_new;
TYPE_CTPCC_ODBC *pCTPCC_ODBC_new;
TYPE_CTPCC_TUXEDO *pCTPCC_TUXEDO_new;
TYPE_CTPCC_ENCINA *pCTPCC_ENCINA_new;
TYPE_CTPCC_ENCINA *pCTPCC_ENCINA_post_init;
TYPE_CTPCC_COM *pCTPCC_COM_new;

// For deferred Delivery txns:
CTxnLog
*txnDelilog = NULL;
//used to log delivery transaction
information

HANDLE
hWorkerSemaphore = INVALID_HANDLE_VALUE;
```

```
HANDLE
hDoneEvent =
INVALID_HANDLE_VALUE;
HANDLE
*pDeliHandles = NULL;

// configuration settings from registry
TPCCREGISTRYDATA Reg;

DWORD
dwNumDeliveryThreads = 4;
CRITICAL_SECTION DelBuffCriticalSection;
//critical section for delivery
transactions cache
DELIVERY_TRANSACTION *pDelBuff
= NULL;

DWORD
dwDelBuffSize = 100;
// size of circular buffer for delivery

txns
DWORD
dwDelBuffFreeCount;
// number of buffers free

DWORD
dwDelBuffBusyIndex = 0;
// index position of entry waiting to be delivered
DWORD
dwDelBuffFreeIndex = 0;
// index position of unused entry

// Critical section to synchronize connection open
and close.
//
CRITICAL_SECTION hConnectCriticalSection;

#include "..\..\common\src\ReadRegistry.cpp"

/* FUNCTION: DllMain
 *
 * PURPOSE: This function is the entry point
 * for the DLL. This implementation is based on the
 * fact that
 * DLL_PROCESS_ATTACH is only called from the inet
 * service once.
 *
 * ARGUMENTS: HANDLE hModule
 * module handle
 *
 * ul_reason_for_call reason for call
 * LPVOID
 *
 * lpReserved
 * reserved for future use
 *
 * RETURNS: BOOL FALSE
 * errors occurred in
 * initialization
 *
 * TRUE
 * successfully initialized
 */
DLL
```

```

BOOL APIENTRY DllMain(HANDLE hModule, DWORD
ul_reason_for_call, LPVOID lpReserved)
{
    DWORD i;
    char szEvent[LEN_ERR_STRING] = "\0";
    char szLogFile[128];
    char szDllName[128];

    // debugging...
    // DebugBreak();

    try
    {
        switch( ul_reason_for_call )
        {
            case
            DLL_PROCESS_ATTACH:
                {
                    DWORD dwSize = MAX_COMPUTERNAME_LENGTH+1;
                    GetComputerName(szMyComputerName, &dwSize);
                    szMyComputerName[dwSize] = 0;
                }

                DisableThreadLibraryCalls((HMODULE)hModule);

                InitializeCriticalSection(&TermCriticalSection);

                if (
                ReadTPCCRegistrySettings( &Reg ) )
                    throw new CWEBCLNT_ERR(
                    ERR_MISSING_REGISTRY_ENTRIES );

                    dwDelBuffSize
                    = min( Reg.dwMaxPendingDeliveries, 10000 ); // min
                    with 10000 as a sanity constraint

                    dwNumDeliveryThreads = min(
                    Reg.dwNumberOfDeliveryThreads, 100 ); // min with
                    100 as a sanity constraint

                    TermInit();

                    // load DLL

                    for txn monitor
                    if
                    (Reg.eTxnMon == TUXEDO)
                    {
                        strcpy( szDllName, Reg.szPath );

                        strcat( szDllName, "tpcc_tuxedo.dll" );

                        hLibInstanceTm = LoadLibrary( szDllName );

```

```

if
(hLibInstanceTm == NULL)
    throw new CWEBCLNT_ERR( ERR_LOADDLL_FAILED,
szDllName, GetLastError() );

//
get function pointer to wrapper for class constructor
    pCTPCC_TUXEDO_new = (TYPE_CTPCC_TUXEDO*)
GetProcAddress(hLibInstanceTm, "CTPCC_TUXEDO_new");
if
(pCTPCC_TUXEDO_new == NULL)
    throw new CWEBCLNT_ERR(
ERR_GETPROCADDR_FAILED, szDllName, GetLastError() );
else if
(Reg.eTxnMon == ENCINA)
    {
        strcpy( szDllName, Reg.szPath );

        strcat( szDllName, "tpcc_encina.dll" );

        hLibInstanceTm = LoadLibrary( szDllName );
        if
        (hLibInstanceTm == NULL)
            throw new CWEBCLNT_ERR( ERR_LOADDLL_FAILED,
szDllName, GetLastError() );

//
get function pointer to wrapper for class constructor
        pCTPCC_ENCINA_new = (TYPE_CTPCC_ENCINA*)
GetProcAddress(hLibInstanceTm, "CTPCC_ENCINA_new");

        pCTPCC_ENCINA_post_init =
        (TYPE_CTPCC_ENCINA*)
        GetProcAddress(hLibInstanceTm, "CTPCC_ENCINA_post_init
        ");
        if
        (pCTPCC_ENCINA_new == NULL)
            throw new CWEBCLNT_ERR(
            ERR_GETPROCADDR_FAILED, szDllName, GetLastError() );
        else if
        (Reg.eTxnMon == COM)
            {
                strcpy( szDllName, Reg.szPath );

                strcat( szDllName, "tpcc_com.dll" );

                hLibInstanceTm = LoadLibrary( szDllName );
                if
                (hLibInstanceTm == NULL)
                    throw new CWEBCLNT_ERR( ERR_LOADDLL_FAILED,
szDllName, GetLastError() );

```

```

//
get function pointer to wrapper for class constructor
    pCTPCC_COM_new = (TYPE_CTPCC_COM*)
GetProcAddress(hLibInstanceTm, "CTPCC_COM_new");
if
(pCTPCC_COM_new == NULL)
    throw new CWEBCLNT_ERR(
ERR_GETPROCADDR_FAILED, szDllName, GetLastError() );

// load DLL
for database connection
    if
    ((Reg.eTxnMon == None) || (dwNumDeliveryThreads > 0))
    {
        if
        (Reg.eDB_Protocol == DBLIB)
            {
                strcpy( szDllName, Reg.szPath );

                strcat( szDllName, "tpcc_dblib.dll" );

                hLibInstanceDb = LoadLibrary( szDllName );

                if (hLibInstanceDb == NULL)
                    throw new CWEBCLNT_ERR(
                    ERR_LOADDLL_FAILED, szDllName, GetLastError() );

                // get function pointer to wrapper for
                class constructor
                pCTPCC_DBLIB_new = (TYPE_CTPCC_DBLIB*)
                GetProcAddress(hLibInstanceDb, "CTPCC_DBLIB_new");

                if (pCTPCC_DBLIB_new == NULL)
                    throw new CWEBCLNT_ERR(
                    ERR_GETPROCADDR_FAILED, szDllName, GetLastError() );
            }
        else if (Reg.eDB_Protocol == ODBC)
            {
                strcpy( szDllName, Reg.szPath );

                strcat( szDllName, "tpcc_odbc.dll" );

                hLibInstanceDb = LoadLibrary( szDllName );

                if (hLibInstanceDb == NULL)
                    throw new CWEBCLNT_ERR(
                    ERR_LOADDLL_FAILED, szDllName, GetLastError() );
            }
    }

```

```

        // get function pointer to wrapper for
class constructor

        pCTPCC_ODBC_new = (TYPE_CTPCC_ODBC*)
GetProcAddress(hLibInstanceDb, "CTPCC_ODBC_new");

        if (pCTPCC_ODBC_new == NULL)

                throw new CWBCLNT_ERR(
ERR_GETPROCADDR_FAILED, szDllName, GetLastError() );

        }

        if

(dwNumDeliveryThreads)

        {

//

Initialize delivery delay critical section

//

        InitializeCriticalSection(&hConnectCritical
Section);

//

for deferred delivery txns:

        hDoneEvent = CreateEvent( NULL, TRUE /*
manual reset */, FALSE /* initially not signalled */,
NULL );

        InitializeCriticalSection(&DelBuffCriticalS
ection);

        hWorkerSemaphore = CreateSemaphore( NULL,
0, dwDelBuffSize, NULL );

        dwDelBuffFreeCount = dwDelBuffSize;

        InitJulianTime(NULL);

//

create unique log file name based on delilog-yyymmdd-
hhmm.log

        SYSTEMTIME Time;

        GetLocalTime( &Time );

        wsprintf( szLogFile, "%sdelivery-
%2.2d%2.2d%2.2d-%2.2d%2.2d-%2.2ds%2.2dms.log",

                Reg.szPath, Time.wYear % 100, Time.wMonth,
Time.wDay, Time.wHour, Time.wMinute, Time.wSecond,
Time.wMilliseconds );

        txnDelilog = new CTxnLog(szLogFile,
TXN_LOG_WRITE);

```

```

        //write event into txn log for START

        txnDelilog-
>WriteCtrlRecToLog(TXN_EVENT_START, szMyComputerName,
sizeof(szMyComputerName));

//

allocate structures for delivery buffers and thread
mgmt

        pDeliHandles = new
HANDLE[dwNumDeliveryThreads];

        pDelBuff = new
DELIVERY_TRANSACTION[dwDelBuffSize];

//

launch DeliveryWorkerThread to perform actual
delivery txns

        for(i=0; i<dwNumDeliveryThreads; i++)

        {

                pDeliHandles[i] = (HANDLE) _beginthread(
DeliveryWorkerThread, 0, NULL );

                if (pDeliHandles[i] ==
INVALID_HANDLE_VALUE)

                        throw new CWBCLNT_ERR(
ERR_DELIVERY_THREAD_FAILED );

        }

        break;

        case

DLL_PROCESS_DETACH:

        if

(dwNumDeliveryThreads)

        {

                if

(txnDelilog != NULL)

        {

                //write event into txn log for STOP

                txnDelilog-
>WriteCtrlRecToLog(TXN_EVENT_STOP, szMyComputerName,
sizeof(szMyComputerName));

                // This will do a clean shutdown of the
delivery log file

                CTxnLog *txnDelilogLocal = txnDelilog;

                txnDelilog= NULL;

                delete txnDelilogLocal;

```

```

        }

        delete [] pDeliHandles;

        delete [] pDelBuff;

        CloseHandle( hWorkerSemaphore );

        CloseHandle( hDoneEvent );

        DeleteCriticalSection(&DelBuffCriticalSecti
on);

//

Delete delivery delay critical section

//

        DeleteCriticalSection(&hConnectCriticalSect
ion);

        DeleteCriticalSection(&TermCriticalSection)

;

        if

(hLibInstanceTm != NULL)

                FreeLibrary( hLibInstanceTm );

                hLibInstanceTm = NULL;

        if

(hLibInstanceDb != NULL)

                FreeLibrary( hLibInstanceDb );

                hLibInstanceDb = NULL;

                Sleep(500);
                break;

        default:

                /* nothing

        }

        }

        catch (CBaseErr *e)

        {

                TCHAR szMsg[256];

                _sntprintf(szMsg, sizeof(szMsg),
"%s error, code %d: %s",

                        e-
>ErrorTypeStr(), e->ErrorNum(), e->ErrorText());

                WriteMessageToEventLog( szMsg );

                delete e;

                TerminateExtension(0);

                return FALSE;

```

```

    }
    catch (...)
    {
        WriteMessageToEventLog(TEXT("Unhandled
exception. DLL could not load.));
        TerminateExtension(0);
        return FALSE;
    }
    return TRUE;
}

/* FUNCTION: GetExtensionVersion
*
* PURPOSE: This function is called by the
inet service when the DLL is first loaded.
*
* ARGUMENTS: HSE_VERSION_INFO *pVer
passed in structure in which to place
expected version number.
*
* RETURNS: TRUE inet service
expected return value.
*/

BOOL WINAPI GetExtensionVersion(HSE_VERSION_INFO
*pVer)
{
    pVer->dwExtensionVersion =
MAKELONG(HSE_VERSION_MINOR, HSE_VERSION_MAJOR);
    lstrcpyn(pVer->lpszExtensionDesc, "TPC-C
Server.", HSE_MAX_EXT_DLL_NAME_LEN);

    // TODO: why do we need this here instead
of in the DLL attach?
    if (Reg.eTxnMon == ENCINA)
        pCTPCC_ENCINA_post_init();

    return TRUE;
}

/* FUNCTION: TerminateExtension
*
* PURPOSE: This function is called by the
inet service when the DLL is about to be unloaded.
*
* Release all resources
in anticipation of being unloaded.
*
* RETURNS: TRUE inet service
expected return value.
*/

BOOL WINAPI TerminateExtension( DWORD dwFlags )
{
    if (pDeliHandles)
    {
        SetEvent( hDoneEvent );
        for (DWORD i=0;
i<dwNumDeliveryThreads; i++)

```

```

        WaitForSingleObject(
pDeliHandles[i], INFINITE );
    }

    TermDeleteAll();
    return TRUE;
}

/* FUNCTION: HttpExtensionProc
*
* PURPOSE: This function is the main entry
point for the TPCC DLL. The internet service
*
* calls this function
passing in the http string.
*
* ARGUMENTS: EXTENSION_CONTROL_BLOCK
*pECB structure pointer to passed in
internet
*
* service information.
*
* RETURNS: DWORD
HSE_STATUS_SUCCESS
connection can be dropped if
error
*
* HSE_STATUS_SUCCESS_AND_KEEP_CONN
keep connect valid comment sent
*
* COMMENTS: None
*/

DWORD WINAPI
HttpExtensionProc(EXTENSION_CONTROL_BLOCK *pECB)
{
    int iCmd, FormId,
TermId, iSyncId;
    char szBuffer[4096];

    int lpbSize;
    static char szHeader[] = "200 Ok";
    DWORD dwSize = 6;
    // initial value is strlen(szHeader)
    char szHeader1[4096];

#ifdef ICECAP
    StartCAP();
#endif

    try
    {
        //process http query
        ProcessQueryString(pECB, &iCmd,
&FormId, &TermId, &iSyncId);

        if (TermId != 0)
        {

```

```

            if ( TermId < 0 ||
TermId >= Term.iNumEntries ||
Term.pClientData[TermId].iNextFree != -1 )
            {
                //
                debugging...
                char
szTmp[128];
                wsprintf(
szTmp, "Invalid term ID; TermId = %d", TermId );
                WriteMessageToEventLog( szTmp );
                throw new
CWEBCLNT_ERR( ERR_INVALID_TERMID );
            }
            //must have a valid
syncid here since termid is valid
            if (iSyncId !=
Term.pClientData[TermId].iSyncId)
                throw new
CWEBCLNT_ERR( ERR_INVALID_SYNC_CONNECTION );
            //set use time
            Term.pClientData[TermId].iTickCount =
GetTickCount();
        }

        switch(iCmd)
        {
        case 0:
            WelcomeForm(pECB,
szBuffer);
            break;
        case 1:
            switch( FormId )
            {
            case
WELCOME_FORM:
            case
MAIN_MENU_FORM:
            case
NEW_ORDER_FORM:
                ProcessNewOrderForm(pECB, TermId,
szBuffer);
                break;
            case
PAYMENT_FORM:
                ProcessPaymentForm(pECB, TermId, szBuffer);
                break;
            case
DELIVERY_FORM:

```

```

        ProcessDeliveryForm(pECB, TermId,
szBuffer);
        break;
        case
ORDER_STATUS_FORM:
        ProcessOrderStatusForm(pECB, TermId,
szBuffer);
        break;
        case
STOCK_LEVEL_FORM:
        ProcessStockLevelForm(pECB, TermId,
szBuffer);
        break;
    }
    break;
    case 2:
        // new-order selected
from menu; display new-order input form
        MakeNewOrderForm(TermId, NULL, INPUT_FORM,
szBuffer);
        break;
    case 3:
        // payment selected
from menu; display payment input form
        MakePaymentForm(TermId,
NULL, INPUT_FORM, szBuffer);
        break;
    case 4:
        // delivery selected
from menu; display delivery input form
        MakeDeliveryForm(TermId, NULL, INPUT_FORM,
szBuffer);
        break;
    case 5:
        // order-status
selected from menu; display order-status input form
        MakeOrderStatusForm(TermId, NULL,
INPUT_FORM, szBuffer);
        break;
    case 6:
        // stock-level selected
from menu; display stock-level input form
        MakeStockLevelForm(TermId, NULL,
INPUT_FORM, szBuffer);
        break;
    case 7:
        // ExitCmd
        TermDelete(TermId);
        WelcomeForm(pECB,
szBuffer);
        break;

```

```

        case 8:
            SubmitCmd(pECB,
szBuffer);
            break;
        case 9:
            // menu
            MakeMainMenuForm(TermId,
Term.pClientData[TermId].iSyncId, szBuffer);
            break;
        case 10:
            // CMD=Clear
            // resets all
connections; should only be used when no other
connections are active
            TermDeleteAll();
            TermInit();
            WelcomeForm(pECB,
szBuffer);
            break;
        case 11:
            // CMD=Stats
            StatsCmd(pECB,
szBuffer);
            break;
    }
    catch (CBaseErr *e)
    {
        ErrorForm( pECB, e->ErrorType(),
e->ErrorNum(), TermId, iSyncId, e->ErrorText(),
szBuffer );
        delete e;
    }
    catch (...)
    {
        ErrorForm( pECB, ERR_TYPE_WEBDLL,
0, TermId, iSyncId, "Error: Unhandled exception in
Web Client.", szBuffer );
    }
#ifdef ICECAP
    StopCAP();
#endif
    lpbSize = strlen(szBuffer);
    sprintf(szHeader1,
"Content-Type:
text/html\r\n"
"Content-Length:
%d\r\n"
"Connection: Keep-
Alive\r\n\r\n", lpbSize);
    strcat( szHeader1, szBuffer );
    (*pECB->ServerSupportFunction)(pECB-
>ConnID, HSE_REQ_SEND_RESPONSE_HEADER, szHeader,
(LPWORD) &dwSize, (LPWORD)szHeader1);
    //finish up and keep connection
pECB->dwHttpStatusCode = 200;

```

```

        return HSE_STATUS_SUCCESS_AND_KEEP_CONN;
    }
}

void WriteMessageToEventLog(LPTSTR lpszMsg)
{
    TCHAR   szMsg[256];
    HANDLE  hEventSource;
    LPTSTR  lpszStrings[2];

    // Use event logging to log the error.
    //
    hEventSource = RegisterEventSource(NULL,
TEXT("TPCC.DLL"));

    _stprintf(szMsg, TEXT("Error in TPCC.DLL: "));
    lpszStrings[0] = szMsg;
    lpszStrings[1] = lpszMsg;

    if (hEventSource != NULL)
    {
        ReportEvent(hEventSource, // handle of event
source
        EVENTLOG_ERROR_TYPE, // event type
0, // event category
0, // event ID
NULL, // current user's
SID
2, // strings in
lpszStrings
0, // no bytes of raw
data
(LPCTSTR *)lpszStrings, // array of
error strings
NULL); // no raw data

        (VOID) DeregisterEventSource(hEventSource);
    }
}

/* FUNCTION: DeliveryWorkerThread
*
* PURPOSE: This function processes deferred
delivery txns. There are typically several
* threads running this
routine. The number of threads is determined by an
entry
* read from the registry.
The thread waits for work by waiting on semaphore.
* When a delivery txn is
posted, the semaphore is released. After processing
* the delivery txn,
information is logged to record the txn status and
execution
* time.
*/

/*static*/ void DeliveryWorkerThread(void *ptr)
{
    CTPCC_BASE *pTxn = NULL;

```

```

DELIVERY_TRANSACTION
delivery;
PDELIVERY_DATA
pDeliveryData;
TXN_RECORD_TPCC_DELIV_DEF    txnDeliRec;

DWORD
index;
HANDLE
handles[2];

SYSTEMTIME                trans_end;
//delivery transaction finished
time
SYSTEMTIME                trans_start;
//delivery transaction start time

assert(txnDeliLog != NULL);

try
{
    if (Reg.eDB_Protocol == ODBC)
    {
        if (Reg.dwConnectDelay
> 0)
        {
            Synchronize connect (for VIA)
            //
            //
            EnterCriticalSection(&hConnectCriticalSection);

            Sleep(Reg.dwConnectDelay);

            pTxn =
pCTPCC_ODBC_new( Reg.szDbServer, Reg.szDbUser,
Reg.szDbPassword,

            szMyComputerName, Reg.szDbName,

            Reg.szSPPrefix,
Reg.bCallNoDuplicatesNewOrder );

            LeaveCriticalSection(&hConnectCriticalSection);
        }
        else
        {
            if (Reg.eDB_Protocol ==
DBLIB)
            pTxn =
pCTPCC_DBLIB_new( Reg.szDbServer, Reg.szDbUser,
Reg.szDbPassword, szMyComputerName, Reg.szDbName );
        }
    }
}

```

```

        pDeliveryData = pTxn-
>BuffAddr_Delivery();
    }
    catch (CBaseErr *e)
    {
        char szTmp[1024];
        wsprintf( szTmp, "Error in
Delivery Txn thread. Could not connect to database.
"
        "%s.
Server=%s, User=%s, Password=%s, Database=%s",
e-
>ErrorText(), Reg.szDbServer, Reg.szDbUser,
Reg.szDbPassword, Reg.szDbName );
        WriteMessageToEventLog( szTmp );
        delete e;
        goto ErrorExit;
    }
    catch (...)
    {
        WriteMessageToEventLog(TEXT("Unhandled
exception caught in DeliveryWorkerThread.));
        goto ErrorExit;
    }

    while (TRUE)
    {
        try
        {
            //while delivery thread
running, i.e. user has not requested termination
            while (TRUE)
            {
                // need to
wait for multiple objects: program exit or worker
semaphore;
                handles[0] =
hDoneEvent;
                handles[1] =
hWorkerSemaphore;
                index =
WaitForMultipleObjects( 2, &handles[0], FALSE,
INFINITE );
                if (index ==
WAIT_OBJECT_0)
                goto ErrorExit;

                ZeroMemory(&txnDeliRec,
sizeof(txnDeliRec));

                txnDeliRec.TxnType =
TXN_REC_TYPE_TPCC_DELIV_DEF;

                // make a
local copy of current entry from delivery buffer and
increment buffer index

```

```

            EnterCriticalSection(&DelBuffCriticalSection);
            delivery =
* (pDelBuff+dwDelBuffBusyIndex);
            dwDelBuffFreeCount++;
            dwDelBuffBusyIndex++;
            if
(dwDelBuffBusyIndex == dwDelBuffSize) // wrap-
around if at end of buffer
            dwDelBuffBusyIndex = 0;

            LeaveCriticalSection(&DelBuffCriticalSection);

            pDeliveryData->w_id = delivery.w_id;
            pDeliveryData->o_carrier_id =
delivery.o_carrier_id;

            txnDeliRec.w_id = pDeliveryData->w_id;
            txnDeliRec.o_carrier_id = pDeliveryData-
>o_carrier_id;

            txnDeliRec.TxnStartT0 =
Get64BitTime(&delivery.queue);

            GetLocalTime(
&trans_start );
            pTxn-
            GetLocalTime(
&trans_end );

            //log txn
            txnDeliRec.TxnStatus = ERR_SUCCESS;
            for (int i=0;
i<10; i++)
            txnDeliRec.o_id[i] = pDeliveryData-
>o_id[i];

            txnDeliRec.DeltaT4 =
(int) (Get64BitTime(&trans_end) -
txnDeliRec.TxnStartT0);

            txnDeliRec.DeltaTxnExec =
(int) (Get64BitTime(&trans_end) -
Get64BitTime(&trans_start));

            if
(txnDeliLog != NULL)

```



```

        txnDelilog->WriteToLog(&txnDeliRec);
    }
    } catch (CBaseErr *e)
    {
        char szTmp[1024];
        wsprintf( szTmp, "%s
Error (code %d) in Delivery Txn thread. %s",
e->ErrorTypeStr(), e->ErrorNum(), e->ErrorText() );
        WriteMessageToEventLog(
szTmp );

        // log the error txn
        txnDeliRec.TxnStatus =
e->ErrorType();
        if (txnDelilog != NULL)
            txnDelilog-
>WriteToLog(&txnDeliRec);

        delete e;
    }
    catch (...)
    {
        // unhandled exception;
        shouldn't happen; not much we can do...

        WriteMessageToEventLog(TEXT("Unhandled
exception caught in DeliveryWorkerThread.));
    }
}

ErrorExit:
if (Reg.dwConnectDelay > 0)
{
    // Synchronize disconnect (for
VIA)
    //
    EnterCriticalSection(&hConnectCriticalSecti
on);

    Sleep(Reg.dwConnectDelay);

    delete pTxn;

    LeaveCriticalSection(&hConnectCriticalSecti
on);
}

_endthread();
}

/* FUNCTION: PostDeliveryInfo
*
* PURPOSE: This function enters the delivery
txn into the deferred delivery buffer.
*

```

```

* RETURNS:          BOOL    FALSE
                  delivery information posted successfully
*
                  TRUE    error cannot post delivery info
*/
BOOL PostDeliveryInfo(long w_id, short o_carrier_id)
{
    BOOL bError;

    EnterCriticalSection(&DelBuffCriticalSectio
n);
    if (dwDelBuffFreeCount > 0)
    {
        bError = FALSE;
        (pDelBuff+dwDelBuffFreeIndex)-
        = w_id;
        (pDelBuff+dwDelBuffFreeIndex)-
        = o_carrier_id;

        GetLocalTime(&(pDelBuff+dwDelBuffFreeIndex)
->queue);

        dwDelBuffFreeCount--;
        dwDelBuffFreeIndex++;
        if (dwDelBuffFreeIndex ==
dwDelBuffSize)
            dwDelBuffFreeIndex = 0;
        // wrap-around if at end of
buffer
    }
    else
        // No free buffers. Return an
error, which indicates that the delivery buffer is
full.
        // Most likely, the number of
delivery worker threads needs to be increased to keep
up
        // with the txn rate.
        bError = TRUE;
    LeaveCriticalSection(&DelBuffCriticalSectio
n);

    if (!bError)
        // increment worker semaphore to
wake up a worker thread
        ReleaseSemaphore(
hWorkerSemaphore, 1, NULL );
    return bError;
}

/* FUNCTION: ProcessQueryString
*
* PURPOSE: This function extracts the
relevant information out of the http command passed
in from
*
* the browser.
*
* COMMENTS: If this is the initial connection
i.e. client is at welcome screen then

```

```

*
* there will
not be a terminal id or current form id. If this is
the case
*
* then the
pTermid and pFormid return values are undefined.
*/

void ProcessQueryString(EXTENSION_CONTROL_BLOCK
*pECB, int *pCmd, int *pFormId, int *pTermId, int
*pSyncId)
{
    char *ptr = pECB->lpszQueryString;
    char szBuffer[25];
    int i;

    //allowable client command strings i.e.
CMD=command
    static char *szCmds[] =
    {
        "Process", ".NewOrder..",
        "..Payment..", "..Delivery..", "..Order-Status..",
        "..Stock-Level..",
        "..Exit..", "Submit", "Menu",
        "Clear", "Stats", ""
    };

    *pCmd = 0; // default is
the login
screen
    *pTermId = 0;

    // if no params (i.e., empty query string),
then return login screen
    if (strlen(pECB->lpszQueryString) == 0)
        return;

    // parse FORMID, TERMID, and SYNCID
    *pFormId = GetIntKeyValue(&ptr, "FORMID",
NO_ERR, NO_ERR);
    *pTermId = GetIntKeyValue(&ptr, "TERMID",
NO_ERR, NO_ERR);
    *pSyncId = GetIntKeyValue(&ptr, "SYNCID",
NO_ERR, NO_ERR);

    // parse CMD
    GetKeyValue(&ptr, "CMD", szBuffer,
sizeof(szBuffer), ERR_COMMAND_UNDEFINED);

    // see which command it matches
    for(i=0; ; i++)
    {
        if (szCmds[i][0] == 0)
            // no more; no match;
return error
            throw new CWEBCLNT_ERR(
ERR_COMMAND_UNDEFINED );
        if (!strcmp(szCmds[i], szBuffer)
)
        {
            *pCmd = i+1;
            break;
        }
    }
}

```

```

    }
}

/* FUNCTION: void WelcomeForm
 *
 */

void WelcomeForm(EXTENSION_CONTROL_BLOCK *pECB, char
*szBuffer)
{
    char szTmp[1024];

    //welcome to tpc-c html form buffer, this
is first form client sees.
    strcpy( szBuffer,
"HTML<HEAD><TITLE>TPC-C Web
Client</TITLE></HEAD><BODY>"

" <B><BIG>Microsoft TPC-C Web Client (ver
4.20)</BIG></B> <BR> <BR>"

" <font face=\\"Courier New\\"><PRE>"

"Compiled: " "__DATE__ ", "__TIME__ " <BR>"

"Source: " "__FILE__ " (" "__TIMESTAMP__ ")
<BR>"

" </PRE></font>"

" <FORM ACTION=\\"tpcc.dll\\" METHOD=\\"GET\\">"

" <INPUT TYPE=\\"hidden\\" NAME=\\"STATUSID\\"
VALUE=\\"0\\">"

" <INPUT TYPE=\\"hidden\\" NAME=\\"ERROR\\"
VALUE=\\"0\\">"

" <INPUT TYPE=\\"hidden\\" NAME=\\"FORMID\\"
VALUE=\\"1\\">"

" <INPUT TYPE=\\"hidden\\" NAME=\\"TERMINID\\"
VALUE=\\"0\\">"

" <INPUT TYPE=\\"hidden\\" NAME=\\"SYNCID\\"
VALUE=\\"0\\">"

" <INPUT TYPE=\\"hidden\\" NAME=\\"VERSION\\"
VALUE=\\" " WEBCLIENT_VERSION " \\">"
);

    sprintf( szTmp,
"Configuration
Settings: <BR><font face=\\"Courier New\\"
color=\\"blue\\"><PRE>"

"Txn Monitor          = <B>%s</B><BR>"

"Database protocol    = <B>%s</B><BR>"

"Max Connections     = <B>%d</B><BR>"

```

```

of Delivery Threads = <B>%d</B><BR>"

"Max Pending Deliveries = <B>%d</B><BR>"

szTxnMonNames[Reg.eTxnMon],
szDBNames[Reg.eDB_Protocol],
    Reg.dwMaxConnections,
dwNumDeliveryThreads, dwDelBuffSize );
    strcat( szBuffer, szTmp);

    if (Reg.eTxnMon == COM)
    {
        sprintf( szTmp,
"COM Single
Pool          = <B>%s</B><BR>",
    Reg.bCOM_SinglePool ?
"YES" : "NO" );
        strcat( szBuffer, szTmp);
    }
    strcat( szBuffer, " </PRE></font>");

    if (Reg.eTxnMon == None)
        // connection options may be
specified when not using a txn monitor
        sprintf( szTmp,
"Please enter
your database options for this connection:<BR>"

" <font face=\\"Courier New\\"
color=\\"blue\\"><PRE>"

"DB Server      = <INPUT NAME=\\"db_server\\"
SIZE=20 VALUE=\\"%s\\"><BR>"

"DB User ID     = <INPUT NAME=\\"db_user\\"
SIZE=20 VALUE=\\"%s\\"><BR>"

"DB Password    = <INPUT NAME=\\"db_passwd\\"
SIZE=20 VALUE=\\"%s\\"><BR>"

"DB Name        = <INPUT NAME=\\"db_name\\"
SIZE=20 VALUE=\\"%s\\"><BR>"

" </PRE></font>"

Reg.szDbServer, Reg.szDbUser, Reg.szDbPassword,
Reg.szDbName );
    else
        // if using a txn monitor,
connection options are determined from registry;
can't
        // set per user. show options
fyi
        sprintf( szTmp,
"Database
options which will be used by the transaction
monitor:<BR>"

" <font face=\\"Courier New\\"
color=\\"blue\\"><PRE>"

"DB Server      = <B>%s</B><BR>"

```

```

"DB User ID          = <B>%s</B><BR>"

"DB Password         = <B>%s</B><BR>"

"DB Name             = <B>%s</B><BR>"

" </PRE></font>"

Reg.szDbServer, Reg.szDbUser, Reg.szDbPassword,
Reg.szDbName );
    strcat( szBuffer, szTmp);

    sprintf( szTmp,
"Please enter your
Warehouse and District for this session:<BR>"

" <font face=\\"Courier New\\"
color=\\"blue\\"><PRE> " );
    strcat( szBuffer, szTmp);
    strcat( szBuffer,
"Warehouse ID = <INPUT
NAME=\\"w_id\\" SIZE=6><BR>"

"District ID = <INPUT NAME=\\"d_id\\"
SIZE=2><BR>"

" </PRE></font><HR>"

" <INPUT TYPE=\\"submit\\" NAME=\\"CMD\\"
VALUE=\\"Submit\\">"

" </FORM></BODY></HTML>");
}

/* FUNCTION: SubmitCmd
 *
 * PURPOSE:      This function allocated a new
terminal id in the Term structure array.
 *
 */

void SubmitCmd(EXTENSION_CONTROL_BLOCK *pECB, char
*szBuffer)
{
    int          iNewTerm;
    char         *ptr = pECB->lpszQueryString;

    char         szVersion[32]      = { 0 };
    char         szServer[32]       = { 0 };
    char         szUser[32]         =
"sa";

    char         szPassword[32]     = { 0 };
    char         szDatabase[32]     = "tpcc";

    // validate version field; the version
field ensures that the RTE is synchronized with the
web client
    GetKeyValue(&ptr, "VERSION", szVersion,
sizeof(szVersion), ERR_VERSION_MISMATCH);
    if ( strcmp( szVersion, WEBCLIENT_VERSION )
)

```

```

        throw new CWEBCLNT_ERR(
ERR_VERSION_MISMATCH );
        if (Reg.eTxnMon == None)
        {
            // parse Server name
            GetKeyValue(&ptr, "db_server",
szServer, sizeof(szServer), ERR_NO_SERVER_SPECIFIED);
            // parse User name
            GetKeyValue(&ptr, "db_user",
szUser, sizeof(szUser), NO_ERR);
            // parse Password
            GetKeyValue(&ptr, "db_passwd",
szPassword, sizeof(szPassword), NO_ERR);
            // parse Database name
            GetKeyValue(&ptr, "db_name",
szDatabase, sizeof(szDatabase), NO_ERR);
        }

        // parse warehouse ID
        int w_id = GetIntKeyValue(&ptr, "w_id",
ERR_HTML_ILL_FORMED, ERR_W_ID_INVALID);
        if ( w_id < 1 )
            throw new CWEBCLNT_ERR(
ERR_W_ID_INVALID );

        // parse district ID
        int d_id = GetIntKeyValue(&ptr, "d_id",
ERR_HTML_ILL_FORMED, ERR_D_ID_INVALID);
        if ( d_id < 1 || d_id > 10 )
            throw new CWEBCLNT_ERR(
ERR_D_ID_INVALID );

        iNewTerm = TermAdd();

        Term.pClientData[iNewTerm].w_id = w_id;
        Term.pClientData[iNewTerm].d_id = d_id;

        try
        {
            if (Reg.eTxnMon == TUXEDO)

                Term.pClientData[iNewTerm].pTxn =
pCTPCC_TUXEDO_new();
            else if (Reg.eTxnMon == ENCINA)

                Term.pClientData[iNewTerm].pTxn =
pCTPCC_ENCINA_new();
            else if (Reg.eTxnMon == COM)

                Term.pClientData[iNewTerm].pTxn =
pCTPCC_COM_new( Reg.bCOM_SinglePool );
            else if (Reg.eDB_Protocol ==
ODBC)

                Term.pClientData[iNewTerm].pTxn =
pCTPCC_ODBC_new( szServer, szUser, szPassword,
szMyComputerName,

```

```

szDatabase, Reg.szSPPrefix,

Reg.bCallNoDuplicatesNewOrder );
        else if (Reg.eDB_Protocol ==
DBLIB)

            Term.pClientData[iNewTerm].pTxn =
pCTPCC_DBLIB_new( szServer, szUser, szPassword,
szMyComputerName, szDatabase );
        }
        catch (...)
        {
            TermDelete(iNewTerm);
            throw; // pass
exception upward
        }

        MakeMainMenuForm(iNewTerm,
Term.pClientData[iNewTerm].iSyncId, szBuffer);
    }

/* FUNCTION: StatsCmd
*
* PURPOSE: This function returns to the
browser the total number of active terminal ids.
*
* This routine is for
development/debugging purposes.
*/

void StatsCmd(EXTENSION_CONTROL_BLOCK *pECB, char
*szBuffer)
{
    int i;
    int iTTotal;

    EnterCriticalSection(&TermCriticalSection);

    iTTotal = 0;
    for(i=0; i<Term.iNumEntries; i++)
    {
        if (Term.pClientData[i].iNextFree
== -1)

            iTTotal++;
    }

    LeaveCriticalSection(&TermCriticalSection);

    wsprintf( szBuffer,

        "<HTML><HEAD><TITLE>TPC-C Web Client
Stats</TITLE></HEAD>"

        "<BODY><B><BIG> Total
Active Connections: %d </BIG></B><BR></BODY></HTML>"
        , iTTotal );
}

char *CWEBCLNT_ERR::ErrorText()

```

```

{
    static SERRORMSG errorMsgs[] =
    {
        { ERR_COMMAND_UNDEFINED,
"Command undefined."
},
        { ERR_D_ID_INVALID,
"Invalid District ID Must be 1 to 10."
},
        {
ERR_DELIVERY_CARRIER_ID_RANGE,
"Delivery Carrier ID out of range
must be 1 - 10."
},
        {
ERR_DELIVERY_CARRIER_INVALID,
"Delivery Carrier ID invalid must be
numeric 1 - 10."
},
        {
ERR_DELIVERY_MISSING_OCD_KEY,
"Delivery missing Carrier ID key \"OCD*\"."
},
        {
ERR_DELIVERY_THREAD_FAILED,
"Could not start delivery worker
thread."
},
        { ERR_GETPROCADDR_FAILED,
"Could not map proc in DLL. GetProcAddr
error. DLL="
},
        { ERR_HTML_ILL_FORMED,
"Required key field is missing from HTML
string."
},
        {
ERR_INVALID_SYNC_CONNECTION,
"Invalid Terminal Sync ID."
},
        {
ERR_INVALID_TERMID,
"Invalid Terminal ID."
},
        {
ERR_LOADDLL_FAILED,
"Load of DLL failed. DLL="
},
        {
ERR_MAX_CONNECTIONS_EXCEEDED,
"No connections available. Max Connections
is probably too low."
},
        {
ERR_MISSING_REGISTRY_ENTRIES,

```

```

"Required registry entries are missing.
Rerun INSTALL to correct." },
{
  ERR_NEWORDER_CUSTOMER_INVALID,
  "New Order customer id invalid
data type, range = 1 to 3000." },
{
  ERR_NEWORDER_CUSTOMER_KEY,
  "New Order missing Customer key
\"CID*\"." },
{
  ERR_NEWORDER_DISTRICT_INVALID,
  "New Order District ID Invalid
range 1 - 10." },
{
  ERR_NEWORDER_FORM_MISSING_DID,
  "New Order missing District key
\"DID*\"." },
{
  ERR_NEWORDER_ITEMID_INVALID,
  "New Order Item Id is wrong data type, must
be numeric." },
{
  ERR_NEWORDER_ITEMID_RANGE,
  "New Order Item Id is out of
range. Range = 1 to 999999." },
{
  ERR_NEWORDER_ITEMID_WITHOUT_SUPPW,
  "New Order Item_Id field entered without a
corresponding Supp_W." },
{
  ERR_NEWORDER_MISSING_IID_KEY,
  "New Order missing Item Id key \"IID*\"." },
{
  ERR_NEWORDER_MISSING_QTY_KEY,
  "New Order Missing Qty key \"Qty##*\"." },
{
  ERR_NEWORDER_MISSING_SUPPW_KEY,
  "New Order missing Supp_W key
\"SP##*\"." },
{
  ERR_NEWORDER_NOITEMS_ENTERED,
  "New Order No order lines entered." },
{
  ERR_NEWORDER_QTY_INVALID,
  "New Order Qty invalid must be
numeric range 1 - 99." },
{
  ERR_NEWORDER_QTY_RANGE,

```

```

"New Order Qty is out of range. Range = 1
to 99." },
{
  ERR_NEWORDER_QTY_WITHOUT_SUPPW,
  "New Order Qty field entered
without a corresponding Supp_W." },
{
  ERR_NEWORDER_SUPPW_INVALID,
  "New Order Supp_W invalid data
type must be numeric." },
{
  ERR_NO_SERVER_SPECIFIED,
  "No Server name specified." },
{
  ERR_ORDERSTATUS_CID_AND_CLT,
  "Order Status Only Customer ID or Last Name
may be entered, not both." },
{
  ERR_ORDERSTATUS_CID_INVALID,
  "Order Status Customer ID invalid, range
must be numeric 1 - 3000." },
{
  ERR_ORDERSTATUS_CLT_RANGE,
  "Order Status Customer last name
longer than 16 characters." },
{
  ERR_ORDERSTATUS_DID_INVALID,
  "Order Status District invalid, value must
be numeric 1 - 10." },
{
  ERR_ORDERSTATUS_MISSING_CID_CLT,
  "Order Status Either Customer ID or Last
Name must be entered." },
{
  ERR_ORDERSTATUS_MISSING_CID_KEY,
  "Order Status missing Customer key
\"CID*\"." },
{
  ERR_ORDERSTATUS_MISSING_CLT_KEY,
  "Order Status missing Customer Last Name
key \"CLT*\"." },
{
  ERR_ORDERSTATUS_MISSING_DID_KEY,
  "Order Status missing District key
\"DID*\"." },
{
  ERR_PAYMENT_CDI_INVALID,
  "Payment Customer district
invalid must be numeric." },
{
  ERR_PAYMENT_CID_AND_CLT,
  "Payment Only Customer ID or Last
Name may be entered, not both." },
{
  ERR_PAYMENT_CUSTOMER_INVALID,

```

```

"Payment Customer data type invalid, must
be numeric." },
{
  ERR_PAYMENT_CWI_INVALID,
  "Payment Customer Warehouse
invalid, must be numeric." },
{
  ERR_PAYMENT_DISTRICT_INVALID,
  "Payment District ID is invalid, must be 1
- 10." },
{
  ERR_PAYMENT_HAM_INVALID,
  "Payment Amount invalid data type
must be numeric." },
{
  ERR_PAYMENT_HAM_RANGE,
  "Payment Amount out of range, 0 - 9999.99." },
{
  ERR_PAYMENT_LAST_NAME_TO_LONG,
  "Payment Customer last name
longer than 16 characters." },
{
  ERR_PAYMENT_MISSING_CDI_KEY,
  "Payment missing Customer district key
\"CDI*\"." },
{
  ERR_PAYMENT_MISSING_CID_CLT,
  "Payment Either Customer ID or Last Name
must be entered." },
{
  ERR_PAYMENT_MISSING_CID_KEY,
  "Payment missing Customer Key \"CID*\"." },
{
  ERR_PAYMENT_MISSING_CLT_KEY,
  "Payment missing Customer Last Name key
\"CLT*\"." },
{
  ERR_PAYMENT_MISSING_CWI_KEY,
  "Payment missing Customer Warehouse key
\"CWI*\"." },
{
  ERR_PAYMENT_MISSING_DID_KEY,
  "Payment missing District Key \"DID*\"." },
{
  ERR_PAYMENT_MISSING_HAM_KEY,
  "Payment missing Amount key \"HAM*\"." },
{

```

```

        {
            ERR_STOCKLEVEL_MISSING_THRESHOLD_KEY,
            "Stock Level; missing Threshold key
        }",
        {
            ERR_STOCKLEVEL_THRESHOLD_INVALID,
            "Stock Level; Threshold value must be in
            the range = 1 - 99." },
        {
            ERR_STOCKLEVEL_THRESHOLD_RANGE,
            "Stock Level Threshold out of
            range, range must be 1 - 99." },
        {
            ERR_VERSION_MISMATCH,
            "Invalid version field. RTE and Web Client
            are probably out of sync." },
        {
            ERR_W_ID_INVALID,
            "Invalid Warehouse ID."
        }
    },
    {
        0,
        ""
    }
};

char szTmp[256];
int i = 0;
while (TRUE)
{
    if (errorMsgs[i].szMsg[0] == 0)
    {
        strcpy( szTmp, "Unknown
        error number." );
        break;
    }
    if (m_Error ==
    errorMsgs[i].iError)
    {
        strcpy( szTmp,
        errorMsgs[i].szMsg );
        break;
    }
    i++;
}

if (m_szTextDetail)
    strcat( szTmp, m_szTextDetail );
if (m_SystemErr)
    wsprintf( szTmp+strlen(szTmp), "
    Error=%d", m_SystemErr );

m_szErrorText = new char[strlen(szTmp)+1];
strcpy( m_szErrorText, szTmp );
return m_szErrorText;
}

```

```

/* FUNCTION: GetKeyValue
 *
 * PURPOSE:      This function parses a http
                 formatted string for specific key values.
 *
 * ARGUMENTS:   char
                 *pQueryString      http string from client
                 browser            char
                 *pKey              char
                 value to look for  char
                 *pValue            char
                 value              character array into which to place key's
                 *                  int
                 *                  iMax
                 *                  maximum length of key value array.
                 *                  WEBERROR
                 err                error value to throw
 *
 * RETURNS:     nothing.
 *
 * ERROR:       if (the pKey value is not found)
                 then
                 *                  if
                 (err == 0)
                 *                  return (empty string)
                 *                  else
                 *                  throw CWBCLNT_ERR(err)
 *
 * COMMENTS:    http keys are formatted either
                 KEY=value& or KEY=value\0. This DLL formats
                 *                  TPC-C input
                 fields in such a manner that the keys can be
                 extracted in the
                 *                  above manner.
 */

void GetKeyValue(char **pQueryString, char *pKey,
char *pValue, int iMax, WEBERROR err)
{
    char *ptr;

    if ( !(ptr=strstr(*pQueryString, pKey)) )
        goto ErrorExit;
    ptr += strlen(pKey);
    if ( *ptr != '=' )
        goto ErrorExit;
    ptr++;

    iMax--; // one position is for terminating
    null
    while( *ptr && *ptr != '&' && iMax)
    {
        *pValue++ = *ptr++;
    }
}

```

```

        iMax--;
    }
    *pValue = 0; // terminating null
    *pQueryString = ptr;
    return;
}

ErrorExit:
    if (err != NO_ERR)
        throw new CWBCLNT_ERR( err );
    *pValue = 0; // return empty result string
}

/* FUNCTION: GetIntKeyValue
 *
 * PURPOSE:      This function parses a http
                 formatted string for a specific key value.
 *
 * ARGUMENTS:   char
                 *pQueryString      http string from client
                 browser            char
                 *pKey              char
                 value to look for  char
                 *                  WEBERROR
                 *                  NoKeyErr      error value to throw if
                 key not found
                 *                  WEBERROR
                 *                  NotIntErr    error value to throw if
                 value not numeric
                 *                  integer
                 * RETURNS:
                 * ERROR:       if (the pKey value is not found)
                 then
                 *                  if
                 (NoKeyErr != NO_ERR)
                 *                  throw CWBCLNT_ERR(err)
                 *                  else
                 *                  return 0
                 *                  else if (non-
                 numeric char found) then
                 *                  if
                 (NotIntErr != NO_ERR) then
                 *                  throw CWBCLNT_ERR(err)
                 *                  else
                 *                  return 0
 *
 * COMMENTS:    http keys are formatted either
                 KEY=value& or KEY=value\0. This DLL formats
                 *                  TPC-C input
                 fields in such a manner that the keys can be
                 extracted in the
                 *                  above manner.
 */

```

```

int GetIntKeyValue(char **pQueryString, char *pKey,
WEBERROR NoKeyErr, WEBERROR NotIntErr)
{
    char *ptr0;
    char *ptr;

    if ( !(ptr=strstr(*pQueryString, pKey)) )
        goto ErrorNoKey;
    ptr += strlen(pKey);
    if ( *ptr != '-' )
        goto ErrorNoKey;
    ptr++;

    ptr0 = ptr;          // remember
starting point
    // scan string until a terminator (null or
&) or a non-digit
    while( *ptr && *ptr != '&' && isdigit(*ptr)
)
        ptr++;

    // make sure we stopped scanning for the
right reason
    if ((ptr0 == ptr) || (*ptr && *ptr != '&'))
    {
        if (NotIntErr != NO_ERR)
            throw new CWBCLNT_ERR(
NoKeyErr );
        return 0;
    }

    *pQueryString = ptr;
    return atoi(ptr0);

ErrorNoKey:
    if (NoKeyErr != NO_ERR)
        throw new CWBCLNT_ERR( NoKeyErr
);
    return 0;
}

/* FUNCTION: TermInit
*
* PURPOSE:      This function initializes the
client terminal structure; it is called when the
TPCC.DLL
*
*               is first loaded by the
inet service.
*
*/

void TermInit(void)
{
    EnterCriticalSection(&TermCriticalSection);

    Term.iMasterSyncId = 1;
    Term.iNumEntries =
Reg.dwMaxConnections+1;

    Term.pClientData = NULL;

```

```

    Term.pClientData =
(PCLIENTDATA)malloc(Term.iNumEntries *
sizeof(CLIENTDATA));
    if (Term.pClientData == NULL)
    {
        LeaveCriticalSection(&TermCriticalSection);
        throw new CWBCLNT_ERR(
ERR_MEM_ALLOC_FAILED );
    }

    ZeroMemory( Term.pClientData,
Term.iNumEntries * sizeof(CLIENTDATA) );

    Term.iFreeList =
Term.iNumEntries-1;
    // build free list
    // note: Term.pClientData[0].iNextFree gets
set to -1, which marks it as "in use".
    // This is intentional, as the zero
entry is used as an anchor and never
    // allocated as an actual
terminal.
    for(int i=0; i<Term.iNumEntries; i++)
        Term.pClientData[i].iNextFree =
i-1;

    LeaveCriticalSection(&TermCriticalSection);
}

/* FUNCTION: TermDeleteAll
*
* PURPOSE:      This function frees allocated
resources associated with the terminal structure.
*
* ARGUMENTS:    none
*
* RETURNS:      None
*
* COMMENTS:     This function is called only when
the inet service unloads the TPCC.DLL
*
*/

void TermDeleteAll(void)
{
    EnterCriticalSection(&TermCriticalSection);

    for(int i=1; i<Term.iNumEntries; i++)
    {
        if (Term.pClientData[i].iNextFree
== -1)
            delete
Term.pClientData[i].pTxn;
    }

    Term.iFreeList = 0;
    Term.iNumEntries = 0;
    if ( Term.pClientData )
        free(Term.pClientData);
    Term.pClientData = NULL;

```

```

        LeaveCriticalSection(&TermCriticalSection);
}

/* FUNCTION: TermAdd
*
* PURPOSE:      This function assigns a terminal
id which is used to identify a client browser.
*
* RETURNS:      int
                assigned terminal id
*
*/

int TermAdd(void)
{
    DWORD i;
    int iNewTerm, iTickCount;

    if (Term.iNumEntries == 0)
        return -1;

    EnterCriticalSection(&TermCriticalSection);
    if (Term.iFreeList != 0)
    {
        // position is available
        iNewTerm = Term.iFreeList;
        Term.iFreeList =
Term.pClientData[iNewTerm].iNextFree;

        Term.pClientData[iNewTerm].iNextFree = -1;
        // indicates this position is in use
    }
    else
    {
        // no open slots, so find the
slot that hasn't been used in the longest time and
reuse it
        for(iNewTerm=1, i=1,
iTickCount=0x7FFFFFFF; i<Reg.dwMaxConnections; i++)
        {
            if (iTickCount >
Term.pClientData[i].iTickCount)
            {
                iTickCount =
Term.pClientData[i].iTickCount;
                iNewTerm = i;
            }
        }
        // if oldest term is less than
one minute old, it probably means that more
connections
        // are being attempted than were
specified as "Max Connections" at install. In this
case,
        // do not bump existing
connection; instead, return error to requestor.
        if ((GetTickCount() - iTickCount)
< 60000)
        {
            LeaveCriticalSection(&TermCriticalSection);

```

```

        throw new CWBECLNT_ERR(
ERR_MAX_CONNECTIONS_EXCEEDED );
    }
}

Term.pClientData[iNewTerm].iTickCount =
GetTickCount();
Term.pClientData[iNewTerm].iSyncId =
Term.iMasterSyncId++;
Term.pClientData[iNewTerm].pTxn = NULL;

LeaveCriticalSection(&TermCriticalSection);
return iNewTerm;
}

/* FUNCTION: TermDelete
 *
 * PURPOSE:      This function makes a terminal
entry in the Term array available for reuse.
 *
 * ARGUMENTS:   int          id
                Terminal id of client exiting
 *
 */
void TermDelete(int id)
{
    if ( id > 0 && id < Term.iNumEntries )
    {
        delete Term.pClientData[id].pTxn;

        // put onto free list

        EnterCriticalSection(&TermCriticalSection);

        Term.pClientData[id].iNextFree =
Term.iFreeList;
        Term.iFreeList = id;

        LeaveCriticalSection(&TermCriticalSection);
    }
}

/* FUNCTION: MakeErrorForm
 */
void ErrorForm(EXTENSION_CONTROL_BLOCK *pECB, int
iType, int iErrorNum, int iTermId, int iSyncId, char
*szErrorText, char *szBuffer )
{
    wsprintf( szBuffer,
    "<HTML><HEAD><TITLE>TPC-C
Error</TITLE></HEAD><BODY>"
    "<FORM ACTION=\"tpcc.dll\"
METHOD=\"GET\">"
    "<INPUT TYPE=\"hidden\"
NAME=\"STATUSID\" VALUE=\"%d\">"

```

```

    "<INPUT TYPE=\"hidden\"
NAME=\"ERROR\" VALUE=\"%d\">"
    "<INPUT TYPE=\"hidden\"
NAME=\"FORMID\" VALUE=\"%d\">"
    "<INPUT TYPE=\"hidden\"
NAME=\"TERMINID\" VALUE=\"%d\">"
    "<INPUT TYPE=\"hidden\"
NAME=\"SYNCID\" VALUE=\"%d\">"
    "<BOLD>An Error
Occurred</BOLD><BR><BR>"
    "%s"
    "<BR><BR><HR>"
    "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\".NewOrder..\">"
    "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\".Payment..\">"
    "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\".Delivery..\">"
    "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\".Order-Status..\">"
    "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\".Stock-Level..\">"
    "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\".Exit..\">"
    "</FORM></BODY></HTML>"
    , iType, iErrorNum,
MAIN_MENU_FORM, iTermId, iSyncId, szErrorText );
}

/* FUNCTION: MakeMainMenuForm
 */
void MakeMainMenuForm(int iTermId, int iSyncId, char
*szForm)
{
    wsprintf( szForm,
    "<HTML><HEAD><TITLE>TPC-C Main
Menu</TITLE></HEAD><BODY>"
    "Select Desired
Transaction.<BR><HR>"
    "<FORM ACTION=\"tpcc.dll\"
METHOD=\"GET\">"
    "<INPUT TYPE=\"hidden\"
NAME=\"STATUSID\" VALUE=\"0\">"
    "<INPUT TYPE=\"hidden\"
NAME=\"ERROR\" VALUE=\"0\">"
    "<INPUT TYPE=\"hidden\"
NAME=\"FORMID\" VALUE=\"%d\">"
    "<INPUT TYPE=\"hidden\"
NAME=\"TERMINID\" VALUE=\"%d\">"
    "<INPUT TYPE=\"hidden\"
NAME=\"SYNCID\" VALUE=\"%d\">"
    "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\".NewOrder..\">"
    "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\".Payment..\">"
    "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\".Delivery..\">"
    "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\".Order-Status..\">"

```

```

    "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\".Stock-Level..\">"
    "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\".Exit..\">"
    "</FORM></BODY></HTML>"
    , MAIN_MENU_FORM, iTermId,
iSyncId);
}

/* FUNCTION: MakeStockLevelForm
 *
 * PURPOSE:      This function constructs the
Stock Level HTML page.
 *
 * COMMENTS:     The internal client buffer is
created when the terminal id is assigned and should
not
                be freed
                except when the client terminal id is no longer
needed.
 */
void MakeStockLevelForm(int iTermId, STOCK_LEVEL_DATA
*pStockLevelData, BOOL bInput, char *szForm)
{
    int          c;

    c = wsprintf( szForm,
    "<HTML><HEAD><TITLE>TPC-C Stock
Level</TITLE></HEAD><FORM ACTION=\"tpcc.dll\"
METHOD=\"GET\">"
    "<INPUT TYPE=\"hidden\"
NAME=\"STATUSID\" VALUE=\"0\">"
    "<INPUT TYPE=\"hidden\"
NAME=\"ERROR\" VALUE=\"0\">"
    "<INPUT TYPE=\"hidden\"
NAME=\"FORMID\" VALUE=\"%d\">"
    "<INPUT TYPE=\"hidden\"
NAME=\"TERMINID\" VALUE=\"%d\">"
    "<INPUT TYPE=\"hidden\"
NAME=\"SYNCID\" VALUE=\"%d\">"
    "<PRE><font face=\"Courier\">
Stock-Level<BR>"
    "Warehouse: %6.6d District:
%2.2d<BR> <BR>,"
    STOCK_LEVEL_FORM, iTermId,
Term.pClientData[iTermId].iSyncId,
Term.pClientData[iTermId].w_id,
Term.pClientData[iTermId].d_id);

    if ( bInput )
    {
        strcpy( szForm+c,
        "Stock Level Threshold:
<INPUT NAME=\"TT*\" SIZE=2><BR> <BR>"
        "low stock:
</font><BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR>
<BR>"
        " <BR> <BR> <BR> <BR>
<BR> <BR> <BR></PRE><HR>"

```

```

        " <INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\"Process\">"
        " <INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\"Menu\">"
    }
    else
    {
        sprintf(szForm+c,
            "Stock Level Threshold:
%2.2d<BR> <BR>"
            "low stock:
%3.3d</font> <BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR>
<BR>"
            " <BR> <BR> <BR> <BR>
<BR> <BR> <BR> <BR></PRE><HR>"
            " <INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\"..NewOrder..\">"
            " <INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\"..Payment..\">"
            " <INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\"..Delivery..\">"
            " <INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\"..Order-Status..\">"
            " <INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\"..Stock-Level..\">"
            " <INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\"..Exit..\">"
            "</FORM></HTML>"
            , pStockLevelData-
>threshold, pStockLevelData->low_stock);
    }
}

/* FUNCTION: MakeNewOrderForm
 *
 * COMMENTS: The internal client buffer is
created when the terminal id is assigned and should
not
 *
 * be freed
except when the client terminal id is no longer
needed.
 */

void MakeNewOrderForm(int iTermId, NEW_ORDER_DATA
*pNewOrderData, BOOL bInput, char *szForm)
{
    int i, c;
    BOOL bValid;
    static char szBR[] = " <BR> <BR> <BR>
<BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR>
<BR> <BR>";

    if (!bInput)
        assert( pNewOrderData-
>exec_status_code == eOK || pNewOrderData-
>exec_status_code == eInvalidItem );

    bValid = (bInput || (pNewOrderData-
>exec_status_code == eOK));

```

```

        c = sprintf(szForm,
            "<HTML><HEAD><TITLE>TPC-C New
Order</TITLE></HEAD><BODY>"
            " <FORM ACTION=\"tpcc.dll\"
METHOD=\"GET\">"
            " <INPUT TYPE=\"hidden\"
NAME=\"STATUSID\" VALUE=\"%d\">"
            " <INPUT TYPE=\"hidden\"
NAME=\"ERROR\" VALUE=\"0\">"
            " <INPUT TYPE=\"hidden\"
NAME=\"FORMID\" VALUE=\"%d\">"
            " <INPUT TYPE=\"hidden\"
NAME=\"TERMINID\" VALUE=\"%d\">"
            " <INPUT TYPE=\"hidden\"
NAME=\"SYNCID\" VALUE=\"%d\">"
            "<PRE><font face=\"Courier\">
New Order<BR>"
            , bValid ? 0 : ERR_BAD_ITEM_ID,
NEW_ORDER_FORM, iTermId,
Term.pClientData[iTermId].iSyncId);

    if ( bInput )
    {
        c += sprintf(szForm+c,
            "Warehouse: %6.6d ", Term.pClientData[iTermId].w_id
            );

        strcpy( szForm+c,
            "District: <INPUT
NAME=\"DID*\" SIZE=1>
Date:<BR>"
            "Customer: <INPUT
NAME=\"CID*\" SIZE=4> Name:
Credit: %Disc:<BR>"
            "Order Number:
Number of Lines: W_tax: D_tax:<BR>
<BR>"
            " Supp_W Item_Id Item
Name Qty Stock B/G Price
Amount<BR>"
            " <INPUT
NAME=\"SP00*\" SIZE=4> <INPUT NAME=\"IID00*\"
SIZE=6> <INPUT
NAME=\"Qty00*\" SIZE=1><BR>"
            " <INPUT
NAME=\"SP01*\" SIZE=4> <INPUT NAME=\"IID01*\"
SIZE=6> <INPUT
NAME=\"Qty01*\" SIZE=1><BR>"
            " <INPUT
NAME=\"SP02*\" SIZE=4> <INPUT NAME=\"IID02*\"
SIZE=6> <INPUT
NAME=\"Qty02*\" SIZE=1><BR>"
            " <INPUT
NAME=\"SP03*\" SIZE=4> <INPUT NAME=\"IID03*\"
SIZE=6> <INPUT
NAME=\"Qty03*\" SIZE=1><BR>"
            " <INPUT
NAME=\"SP04*\" SIZE=4> <INPUT NAME=\"IID04*\"
SIZE=6> <INPUT
NAME=\"Qty04*\" SIZE=1><BR>"

```

```

        " <INPUT
NAME=\"SP05*\" SIZE=4> <INPUT NAME=\"IID05*\"
SIZE=6> <INPUT
NAME=\"Qty05*\" SIZE=1><BR>"
        " <INPUT
NAME=\"SP06*\" SIZE=4> <INPUT NAME=\"IID06*\"
SIZE=6> <INPUT
NAME=\"Qty06*\" SIZE=1><BR>"
        " <INPUT
NAME=\"SP07*\" SIZE=4> <INPUT NAME=\"IID07*\"
SIZE=6> <INPUT
NAME=\"Qty07*\" SIZE=1><BR>"
        " <INPUT
NAME=\"SP08*\" SIZE=4> <INPUT NAME=\"IID08*\"
SIZE=6> <INPUT
NAME=\"Qty08*\" SIZE=1><BR>"
        " <INPUT
NAME=\"SP09*\" SIZE=4> <INPUT NAME=\"IID09*\"
SIZE=6> <INPUT
NAME=\"Qty09*\" SIZE=1><BR>"
        " <INPUT
NAME=\"SP10*\" SIZE=4> <INPUT NAME=\"IID10*\"
SIZE=6> <INPUT
NAME=\"Qty10*\" SIZE=1><BR>"
        " <INPUT
NAME=\"SP11*\" SIZE=4> <INPUT NAME=\"IID11*\"
SIZE=6> <INPUT
NAME=\"Qty11*\" SIZE=1><BR>"
        " <INPUT
NAME=\"SP12*\" SIZE=4> <INPUT NAME=\"IID12*\"
SIZE=6> <INPUT
NAME=\"Qty12*\" SIZE=1><BR>"
        " <INPUT
NAME=\"SP13*\" SIZE=4> <INPUT NAME=\"IID13*\"
SIZE=6> <INPUT
NAME=\"Qty13*\" SIZE=1><BR>"
        " <INPUT
NAME=\"SP14*\" SIZE=4> <INPUT NAME=\"IID14*\"
SIZE=6> <INPUT
NAME=\"Qty14*\" SIZE=1><BR>"
        "Execution Status:
Total:<BR>"
        "</font></PRE><HR>"
        " <INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\"Process\">"
        " <INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\"Menu\">"
        "</FORM></HTML>"
    );
}
else
{
    c += sprintf(szForm+c,
        "Warehouse: %6.6d District: %2.2d
Date: ",
        pNewOrderData->w_id,
pNewOrderData->d_id);
    if ( bValid )
    {

```



```

        c += sprintf(szForm+c,
"%2.2d-%2.2d-%4.4d %2.2d:%2.2d:%2.2d",
        pNewOrderData->o_entry_d.day,
        pNewOrderData->o_entry_d.month,
        pNewOrderData->o_entry_d.year,
        pNewOrderData->o_entry_d.hour,
        pNewOrderData->o_entry_d.minute,
        pNewOrderData->o_entry_d.second);
    }
    c += sprintf(szForm+c,
"<BR>Customer: %4.4d Name: %-16s Credit: %-2s",
        pNewOrderData->c_id,
        pNewOrderData->c_last, pNewOrderData->c_credit);
    if ( bValid )
    {
        c += sprintf(szForm+c,
        "%Disc: %5.2f <BR>"
        "Order Number: %8.8d Number of Lines:
%2.2d W_tax: %5.2f D_tax: %5.2f <BR> <BR>"
        " Supp_W Item_Id Item Name
Qty Stock B/G Price Amount<BR>",
        100.0*pNewOrderData->c_discount,
        pNewOrderData->o_id,
        pNewOrderData->o_ol_cnt,
        100.0 *
        pNewOrderData->w_tax,
        100.0 *
        pNewOrderData->d_tax);
        for(i=0;
i<pNewOrderData->o_ol_cnt; i++)
        {
            c +=
sprintf(szForm+c, "%6.6d %6.6d %-24s %2.2d
%3.3d %1.1s %$6.2f %$7.2f <BR>",
        pNewOrderData->OL[i].ol_supply_w_id,
        pNewOrderData->OL[i].ol_i_id,
        pNewOrderData->OL[i].ol_i_name,
        pNewOrderData->OL[i].ol_quantity,
        pNewOrderData->OL[i].ol_stock,

```

```

pNewOrderData->OL[i].ol_brand_generic,
pNewOrderData->OL[i].ol_i_price,
pNewOrderData->OL[i].ol_amount );
        }
        else
        {
            c += sprintf(szForm+c,
            "%Disc:<BR>"
            "Order
Number: %8.8d Number of Lines: W_tax:
D_tax:<BR> <BR>"
            " Supp_W
Item_Id Item Name Qty Stock B/G
Price Amount<BR>"
            pNewOrderData->o_id);
            i = 0;
            strcpy( szForm+c, szBR, (15-i)*5
);
            c += (15-i)*5;
            if ( bValid )
            c += sprintf(szForm+c,
"Execution Status: Transaction committed.
Total: %$8.2f ",
            pNewOrderData->total_amount);
            else
            c += sprintf(szForm+c,
"Execution Status: Item number is not valid.
Total:");
            strcpy(szForm+c,
            "<BR></font></PRE><HR>"
            "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\"..NewOrder..\">"
            "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\"..Payment..\">"
            "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\"..Delivery..\">"
            "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\"..Order-Status..\">"
            "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\"..Stock-Level..\">"
            "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\"..Exit..\">"
            "</FORM></HTML>"
            );
        }
    }
    /* FUNCTION: MakePaymentForm
    *

```

```

* COMMENTS: The internal client buffer is
created when the terminal id is assigned and should
not
* be freed
* except when the client terminal id is no longer
needed.
*/
void MakePaymentForm(int iTermId, PAYMENT_DATA
*pPaymentData, BOOL bInput, char *szForm)
{
    int c;
    c = sprintf(szForm,
    "<HTML><HEAD><TITLE>TPC-C
Payment</TITLE></HEAD><BODY>"
    "<FORM ACTION=\"tpcc.dll\"
METHOD=\"GET\">"
    "<INPUT TYPE=\"hidden\"
NAME=\"STATUSID\" VALUE=\"0\">"
    "<INPUT TYPE=\"hidden\"
NAME=\"ERROR\" VALUE=\"0\">"
    "<INPUT TYPE=\"hidden\"
NAME=\"FORMID\" VALUE=\"%d\">"
    "<INPUT TYPE=\"hidden\"
NAME=\"TERMINID\" VALUE=\"%d\">"
    "<INPUT TYPE=\"hidden\"
NAME=\"SYNCID\" VALUE=\"%d\">"
    "<PRE><font face=\"Courier\">"
    Payment<BR>"
    "Date: "
    , PAYMENT_FORM, iTermId,
    Term.pClientData[iTermId].iSyncId);
    if ( !bInput )
    {
        c += sprintf(szForm+c, "%2.2d-
%2.2d-%4.4d %2.2d:%2.2d:%2.2d",
        pPaymentData-
>h_date.day,
        pPaymentData-
>h_date.month,
        pPaymentData-
>h_date.year,
        pPaymentData-
>h_date.hour,
        pPaymentData-
>h_date.minute,
        pPaymentData-
>h_date.second);
    }
    if ( bInput )
    {
        c += sprintf(szForm+c,
        "%6.6d"
        "
        District: <INPUT NAME=\"DID*\" SIZE=1><BR> <BR> <BR>
<BR> <BR>"

```

```

"Customer: <INPUT
NAME=\CID*\ " SIZE=4>
"Customer: <INPUT
NAME=\CWI*\ " SIZE=4> "
"Cust-District: <INPUT
NAME=\CDI*\ " SIZE=1><BR>"
"Name:
<INPUT NAME=\CLT*\ " SIZE=16>
Since:<BR>"
"
Credit:<BR>"
"
Disc:<BR>"
"
Phone:<BR> <BR>"
"Amount Paid:
$<INPUT NAME=\HAM*\ " SIZE=7>
New Cust-
Balance:<BR>"
"Credit Limit:<BR>
<BR>Cust-Data: <BR> <BR> <BR> <BR>
<BR></Font></PRE><HR>"
"<INPUT TYPE=\submit\
NAME=\CMD\ " VALUE=\Process\ "><INPUT TYPE=\submit\
NAME=\CMD\ " VALUE=\Menu\ ">"
"</BODY></FORM></HTML>"
Term.pClientData[iTermId].w_id;
}
else
{
c += sprintf(szForm+c,
" <BR> <BR>Warehouse:
%6.6d District: %2.2d<BR>"
"%-20s
"%-20s
"%-20s<BR>"
"%-20s
"%-20s <-2s %5.5s-%4.4s
%<-2s %<-2s %5.5s-%4.4s<BR> <BR>"
"Customer: %4.4d Cust-
Warehouse: %6.6d Cust-District: %2.2d<BR>"
"Name: %<-16s %<-2s %<-
16s Since: %2.2d-%2.2d-%4.4d<BR>"
" %<-20s
Credit: %<-2s<BR>"
,
Term.pClientData[iTermId].w_id, pPaymentData->d_id
, pPaymentData-
>w_street_1, pPaymentData->d_street_1
, pPaymentData-
>w_street_2, pPaymentData->d_street_2
, pPaymentData->w_city,
pPaymentData->w_state, pPaymentData->w_zip,
pPaymentData->w_zip+5
, pPaymentData->d_city,
pPaymentData->d_state, pPaymentData->d_zip,
pPaymentData->d_zip+5
, pPaymentData->c_id,
pPaymentData->c_d_id

```

```

, pPaymentData-
>c_first, pPaymentData->c_middle, pPaymentData-
>c_last
, pPaymentData-
>c_since.day, pPaymentData->c_since.month,
pPaymentData->c_since.year
, pPaymentData-
>c_street_1, pPaymentData->c_credit
);
c += sprintf(szForm+c,
" %<-20s
%%Disc: %5.2f<BR>",
pPaymentData-
>c_street_2, 100.0*pPaymentData->c_discount);
c += sprintf(szForm+c,
" %<-20s %<-2s
%5.5s-%4.4s Phone: %6.6s-%3.3s-%3.3s-%4.4s<BR>
<BR>",
pPaymentData->c_state, pPaymentData->c_zip,
pPaymentData->c_zip+5,
pPaymentData->c_phone,
pPaymentData->c_phone+6, pPaymentData->c_phone+9,
pPaymentData->c_phone+12 );
c += sprintf(szForm+c,
"$%7.2f New Cust-Balance: $%14.2f<BR>"
"$%13.2f<BR> <BR>"
, pPaymentData-
>h_amount, pPaymentData->c_balance
, pPaymentData-
>c_credit_lim
);
if ( pPaymentData->c_credit[0] ==
'B' && pPaymentData->c_credit[1] == 'C' )
c += sprintf(szForm+c,
" Cust-Data: %<-50.50s<BR> %<-
50.50s<BR> %<-50.50s<BR> %<-
50.50s<BR>",
pPaymentData->c_data, pPaymentData-
>c_data+50, pPaymentData->c_data+100, pPaymentData-
>c_data+150 );
else
strcpy(szForm+c, "Cust-
Data: <BR> <BR> <BR> <BR>");
strcat(szForm,
"
"<INPUT TYPE=\submit\ " NAME=\CMD\
VALUE=\..NewOrder..\ ">"
"<INPUT TYPE=\submit\ " NAME=\CMD\
VALUE=\..Payment..\ ">"

```

```

"<INPUT TYPE=\submit\ " NAME=\CMD\
VALUE=\..Delivery..\ ">"
"<INPUT TYPE=\submit\ " NAME=\CMD\
VALUE=\..Order-Status..\ ">"
"<INPUT TYPE=\submit\ " NAME=\CMD\
VALUE=\..Stock-Level..\ ">"
"<INPUT TYPE=\submit\ " NAME=\CMD\
VALUE=\..Exit..\ ">"
"</BODY></FORM></HTML>";
}
}
/* FUNCTION: MakeOrderStatusForm
* COMMENTS: The internal client buffer is
created when the terminal id is assigned and should
not
* be freed
except when the client terminal id is no longer
needed.
*/
void MakeOrderStatusForm(int iTermId,
ORDER_STATUS_DATA *pOrderStatusData, BOOL bInput,
char *szForm)
{
int i, c;
static char szBR[] = " <BR> <BR> <BR> <BR>
<BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR>
<BR>";
c = sprintf(szForm,
"<HTML><HEAD><TITLE>TPC-C Order-
Status</TITLE></HEAD><BODY>"
"<FORM ACTION=\tpcc.dll\
METHOD=\GET\ ">"
"<INPUT TYPE=\hidden\
NAME=\STATUSID\ " VALUE=\0\ ">"
"<INPUT TYPE=\hidden\
NAME=\ERROR\ " VALUE=\0\ ">"
"<INPUT TYPE=\hidden\
NAME=\FORMID\ " VALUE=\%d\ ">"
"<INPUT TYPE=\hidden\
NAME=\TERMINID\ " VALUE=\%d\ ">"
"<INPUT TYPE=\hidden\
NAME=\SYNCID\ " VALUE=\%d\ ">"
"<PRE><font face=\Courier\ ">
Order-Status<BR>"
" Warehouse: %6.6d ",
ORDER_STATUS_FORM, iTermId,
Term.pClientData[iTermId].iSyncId,
Term.pClientData[iTermId].w_id;
if ( bInput )
{

```

```

        strcpy(szForm+c,
                "District: <INPUT
NAME=\"DID*\" SIZE=1><BR>"
                "Customer: <INPUT
NAME=\"CID*\" SIZE=4> Name:
<INPUT NAME=\"CLT*\" SIZE=23><BR>"
                "Cust-Balance:<BR>
<BR>"
                "Order-Number:
Entry-Date:
Number:<BR>"
                "Carrier-
Supply-W Item-Id
Delivery-Date<BR> <BR> <BR> <BR>
" <BR> <BR> <BR> <BR>
" <BR></font></PRE>"
                "<HR><INPUT
TYPE=\"submit\" NAME=\"CMD\" VALUE=\"Process\"><INPUT
TYPE=\"submit\" NAME=\"CMD\" VALUE=\"Menu\">"
                "</BODY></FORM></HTML>"
);
        }
        else
        {
                c += sprintf(szForm+c,
                "District: %2.2d<BR>"
                "Customer: %4.4d
                pOrderStatusData->d_id,
                pOrderStatusData->c_id,
                pOrderStatusData->c_first, pOrderStatusData->c_middle,
                pOrderStatusData->c_last);
                c += sprintf(szForm+c, "Cust-
Balance: %9.2f<BR> <BR>",
                pOrderStatusData->c_balance);
                c += sprintf(szForm+c,
                "Order-Number: %8.8d
                Entry-Date: %2.2d-%2.2d-%4.4d %2.2d:%2.2d:%2.2d
                Carrier-Number: %2.2d<BR>"
                "Supply-W Item-Id
                Delivery-Date<BR>",
                pOrderStatusData->o_id,
                pOrderStatusData->o_entry_d.day,
                pOrderStatusData->o_entry_d.month,
                pOrderStatusData->o_entry_d.year,
                pOrderStatusData->o_entry_d.hour,
                pOrderStatusData->o_entry_d.minute,
                pOrderStatusData->o_entry_d.second,
                pOrderStatusData->o_carrier_id);

```

```

        for(i=0; i< pOrderStatusData-
>o_ol_cnt; i++)
        {
                c += sprintf(szForm+c,
                "%6.6d %6.6d %2.2d %8.2f %2.2d-
%2.2d-%4.4d<BR>",
                pOrderStatusData->ol[i].ol_supply_w_id,
                pOrderStatusData->ol[i].ol_i_id,
                pOrderStatusData->ol[i].ol_quantity,
                pOrderStatusData->ol[i].ol_amount,
                pOrderStatusData->ol[i].ol_delivery_d.day,
                pOrderStatusData->ol[i].ol_delivery_d.month,
                pOrderStatusData->ol[i].ol_delivery_d.year);
        }
        strcpy( szForm+c, szBR, (15-i)*5
);
        c += (15-i)*5;
        strcpy(szForm+c,
                "</font></PRE><HR><INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\".NewOrder.\">"
                "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\".Payment.\">"
                "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\".Delivery.\">"
                "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\".Order-Status.\">"
                "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\".Stock-Level.\">"
                "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\".Exit.\">"
                "</BODY></FORM></HTML>"
);
}
/* FUNCTION: MakeDeliveryForm
 *
 * COMMENTS: The internal client buffer is
created when the terminal id is assigned and should
not
 * be freed
 * except when the client terminal id is no longer
needed.
 */
void MakeDeliveryForm(int iTermId, DELIVERY_DATA
*pDeliveryData, BOOL bInput, char *szForm)
{
        int c;

```

```

        c = sprintf(szForm,
                "<HTML><HEAD><TITLE>TPC-C
Delivery</TITLE></HEAD><BODY>"
                "<FORM ACTION=\"tpcc.dll\"
METHOD=\"GET\">"
                "<INPUT TYPE=\"hidden\"
NAME=\"STATUSID\" VALUE=\"%d\">"
                "<INPUT TYPE=\"hidden\"
NAME=\"ERROR\" VALUE=\"0\">"
                "<INPUT TYPE=\"hidden\"
NAME=\"FORMID\" VALUE=\"%d\">"
                "<INPUT TYPE=\"hidden\"
NAME=\"TERMINID\" VALUE=\"%d\">"
                "<INPUT TYPE=\"hidden\"
NAME=\"SYNCID\" VALUE=\"%d\">"
                "<PRE><font face=\"Courier\">
Delivery<BR>"
                "Warehouse: %6.6d<BR> <BR>",
                (bInput && (pDeliveryData-
>exec_status_code != eOK)) ? ERR_TYPE_DELIVERY_POST :
0,
                DELIVERY_FORM, iTermId,
                Term.pClientData[iTermId].iSyncId,
                Term.pClientData[iTermId].w_id);
        if ( bInput )
        {
                strcpy( szForm+c,
                "Carrier Number: <INPUT
NAME=\"OCD*\" SIZE=1><BR> <BR>"
                "Execution Status: <BR>
<BR> <BR> <BR> <BR> <BR> <BR>
" <BR> <BR> <BR> <BR>
<BR> <BR> <BR> <BR> </font></PRE><HR>"
                "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\"Process\">"
                "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\"Menu\">"
                "</BODY></FORM></HTML>"
);
        }
        else
        {
                sprintf( szForm+c,
                "%2.2d<BR> <BR>"
                "Carrier Number:
                "Execution Status: %s
                <BR> <BR> <BR> <BR> <BR> <BR>
                " <BR> <BR> <BR> <BR>
                <BR> <BR> <BR> <BR> </font></PRE>"
                "<HR><INPUT
TYPE=\"submit\" NAME=\"CMD\" VALUE=\".NewOrder.\">"
                "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\".Payment.\">"
                "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\".Delivery.\">"
                "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\".Order-Status.\">"
                "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\".Stock-Level.\">"

```

```

                "<INPUT TYPE=\"submit\"
NAME=\"CMD\" VALUE=\"..Exit..\">"
                "</BODY></FORM></HTML>"
                , pDeliveryData-
            }
            (pDeliveryData-
            >exec_status_code == eOK) ? "Delivery has been
            queued." : "Delivery Post Failed "
            );
        }
    }
}

/* FUNCTION: ProcessNewOrderForm
 *
 * PURPOSE: This function gets and validates
the input data from the new order form
 *           filling in the required
input variables. it then calls the SQLNewOrder
 *           transaction, constructs
the output form and writes it back to client
 *           browser.
 */

void ProcessNewOrderForm(EXTENSION_CONTROL_BLOCK
 *pECB, int iTermId, char *szBuffer)
{
    PNEW_ORDER_DATA    pNewOrder;

    pNewOrder = Term.pClientData[iTermId].pTxn-
>BuffAddr_NewOrder();

    ZeroMemory(pNewOrder,
sizeof(NEW_ORDER_DATA));
    pNewOrder->w_id =
Term.pClientData[iTermId].w_id;
    GetNewOrderData(pECB->lpszQueryString,
pNewOrder);

    Term.pClientData[iTermId].pTxn->NewOrder();

    pNewOrder = Term.pClientData[iTermId].pTxn-
>BuffAddr_NewOrder();
    MakeNewOrderForm(iTermId, pNewOrder,
OUTPUT_FORM, szBuffer );
}

/* FUNCTION: void ProcessPaymentForm
 *
 * PURPOSE: This function gets and validates
the input data from the payment form
 *           filling in the required
input variables. It then calls the SQLPayment
 *           transaction, constructs
the output form and writes it back to client
 *           browser.
 *
 * ARGUMENTS: EXTENSION_CONTROL_BLOCK
 *             *pECB    passed in structure pointer from
inetsrv.

```

```

    int
    iTermId    client browser terminal id
 */

void ProcessPaymentForm(EXTENSION_CONTROL_BLOCK
 *pECB, int iTermId, char *szBuffer)
{
    PPAYMENT_DATA    pPayment;

    pPayment = Term.pClientData[iTermId].pTxn-
>BuffAddr_Payment();
    ZeroMemory(pPayment, sizeof(PAYMENT_DATA));
    pPayment->w_id =
Term.pClientData[iTermId].w_id;
    GetPaymentData(pECB->lpszQueryString,
pPayment);

    Term.pClientData[iTermId].pTxn->Payment();

    pPayment = Term.pClientData[iTermId].pTxn-
>BuffAddr_Payment();
    MakePaymentForm(iTermId, pPayment,
OUTPUT_FORM, szBuffer);
}

/* FUNCTION: ProcessOrderStatusForm
 *
 * PURPOSE: This function gets and validates
the input data from the Order Status
 *           form filling in the
required input variables. It then calls the
 *           SQLOrderStatus
transaction, constructs the output form and writes it
 *           back to client browser.
 *
 * ARGUMENTS: EXTENSION_CONTROL_BLOCK
 *             *pECB    passed in structure pointer from
inetsrv.
    int
    iTermId    client browser terminal id
 */

void ProcessOrderStatusForm(EXTENSION_CONTROL_BLOCK
 *pECB, int iTermId, char *szBuffer)
{
    PORDER_STATUS_DATA    pOrderStatus;

    pOrderStatus =
Term.pClientData[iTermId].pTxn-
>BuffAddr_OrderStatus();
    ZeroMemory(pOrderStatus,
sizeof(ORDER_STATUS_DATA));
    pOrderStatus->w_id =
Term.pClientData[iTermId].w_id;
    GetOrderStatusData(pECB->lpszQueryString,
pOrderStatus);
}

```

```

    Term.pClientData[iTermId].pTxn-
>OrderStatus();

    pOrderStatus =
Term.pClientData[iTermId].pTxn-
>BuffAddr_OrderStatus();
    MakeOrderStatusForm(iTermId, pOrderStatus,
OUTPUT_FORM, szBuffer);
}

/* FUNCTION: ProcessDeliveryForm
 *
 * PURPOSE: This function gets and validates
the input data from the delivery form
 *           filling in the required
input variables. It then calls the PostDeliveryInfo
 *           Api, The client is then
informed that the transaction has been posted.
 *
 * ARGUMENTS: EXTENSION_CONTROL_BLOCK
 *             *pECB    passed in structure pointer from
inetsrv.
    int
    iTermId    client browser terminal id
 */

void ProcessDeliveryForm(EXTENSION_CONTROL_BLOCK
 *pECB, int iTermId, char *szBuffer)
{
    char *ptr = pECB->lpszQueryString;

    PDELIVERY_DATA    pDelivery;

    pDelivery = Term.pClientData[iTermId].pTxn-
>BuffAddr_Delivery();
    ZeroMemory(pDelivery,
sizeof(DELIVERY_DATA));
    pDelivery->w_id =
Term.pClientData[iTermId].w_id;

    pDelivery->o_carrier_id =
GetIntKeyValue(&ptr, "OCD*");
    ERR_DELIVERY_MISSING_OCD_KEY,
    ERR_DELIVERY_CARRIER_INVALID);
    if ( pDelivery->o_carrier_id > 10 ||
pDelivery->o_carrier_id < 1 )
        throw new CWEBCLNT_ERR(
ERR_DELIVERY_CARRIER_ID_RANGE );

    if (dwNumDeliveryThreads)
    {
        //post delivery info
        if ( PostDeliveryInfo(pDelivery-
>w_id, pDelivery->o_carrier_id ) )
            pDelivery-
>exec_status_code = eDeliveryFailed;
        else
            pDelivery-
>exec_status_code = eOK;
    }
}

```

```

    }
    else // delivery is done synchronously if
no delivery threads configured
        Term.pClientData[iTermId].pTxn-
->Delivery();

    pDelivery = Term.pClientData[iTermId].pTxn-
->BuffAddr_Delivery();
    MakeDeliveryForm(iTermId, pDelivery,
OUTPUT_FORM, szBuffer);
}

/* FUNCTION: ProcessStockLevelForm
*
* PURPOSE: This function gets and validates
the input data from the Stock Level
* form filling in the
required input variables. It then calls the
SQLStockLevel
transaction, constructs the output form and writes it
back to client browser.
*
* ARGUMENTS: EXTENSION_CONTROL_BLOCK
* *pECB passed in structure pointer from
inetsrv.
*
* int
*
* iTermId client browser terminal id
*/

void ProcessStockLevelForm(EXTENSION_CONTROL_BLOCK
*pECB, int iTermId, char *szBuffer)
{
    char *ptr = pECB-
->lpszQueryString;

    PSTOCK_LEVEL_DATA pStockLevel;

    pStockLevel =
Term.pClientData[iTermId].pTxn-
->BuffAddr_StockLevel();
    ZeroMemory( pStockLevel,
sizeof( STOCK_LEVEL_DATA ) );

    pStockLevel->w_id =
Term.pClientData[iTermId].w_id;
    pStockLevel->d_id =
Term.pClientData[iTermId].d_id;

    pStockLevel->threshold =
GetIntKeyValue(&ptr, "TT*",
ERR_STOCKLEVEL_MISSING_THRESHOLD_KEY,
ERR_STOCKLEVEL_THRESHOLD_INVALID);
    if ( pStockLevel->threshold >= 100 ||
pStockLevel->threshold < 0 )
        throw new CWBCLNT_ERR(
ERR_STOCKLEVEL_THRESHOLD_RANGE );

    Term.pClientData[iTermId].pTxn-
->StockLevel();

```

```

        pStockLevel =
Term.pClientData[iTermId].pTxn-
->BuffAddr_StockLevel();
        MakeStockLevelForm(iTermId, pStockLevel,
OUTPUT_FORM, szBuffer);
}

/* FUNCTION: GetNewOrderData
*
* PURPOSE: This function extracts and
validates the new order form data from an http
command string.
*
* ARGUMENTS: LPSTR client
lpszQueryString browser http command string
*
* NEW_ORDER_DATA *pNewOrderData
pointer to new order data structure
*
*/

void GetNewOrderData(LPSTR lpszQueryString,
NEW_ORDER_DATA *pNewOrderData)
{
    char szTmp[26];
    int i;
    short items;
    int ol_i_id, ol_quantity;
    char *ptr = lpszQueryString;

    static char szSP[MAX_OL_NEW_ORDER_ITEMS][6]
=
"SP03*", "SP04*", { "SP00*", "SP01*", "SP02*",
"SP05*", "SP06*", "SP07*",
"SP08*", "SP09*", "SP10*", "SP11*", "SP12*",
"SP13*", "SP14*" };
    static char
szIID[MAX_OL_NEW_ORDER_ITEMS][7] =
{ "IID00*", "IID01*", "IID02*",
"IID03*", "IID04*", "IID05*", "IID06*", "IID07*",
"IID08*", "IID09*", "IID10*", "IID11*", "IID12*",
"IID13*", "IID14*" };
    static char
szQty[MAX_OL_NEW_ORDER_ITEMS][7] =
{ "Qty00*", "Qty01*", "Qty02*",
"Qty03*", "Qty04*", "Qty05*", "Qty06*", "Qty07*",
"Qty08*", "Qty09*", "Qty10*", "Qty11*", "Qty12*",
"Qty13*", "Qty14*" };

    pNewOrderData->d_id = GetIntKeyValue(&ptr,
"DID*", ERR_NEWORDER_FORM_MISSING_DID,
ERR_NEWORDER_DISTRICT_INVALID);

```

```

        pNewOrderData->c_id = GetIntKeyValue(&ptr,
"CID*", ERR_NEWORDER_CUSTOMER_KEY,
ERR_NEWORDER_CUSTOMER_INVALID);

        for(i=0, items=0; i<MAX_OL_NEW_ORDER_ITEMS;
i++)
        {
            GetIntKeyValue(&ptr, szSP[i], szTmp,
sizeof(szTmp), ERR_NEWORDER_MISSING_SUPPW_KEY);
            if ( szTmp[0] )
            {
                if ( !IsNumeric(szTmp)
)
                    throw new
CWBCLNT_ERR( ERR_NEWORDER_SUPPW_INVALID );
                pNewOrderData-
->OL[items].ol_supply_w_id = atoi(szTmp);

                ol_i_id =
pNewOrderData->OL[items].ol_i_id =
GetIntKeyValue(&ptr, szIID[i],
ERR_NEWORDER_MISSING_IID_KEY,
ERR_NEWORDER_ITEMID_INVALID);
                if ( ol_i_id > 999999
|| ol_i_id < 1 )
                    throw new
CWBCLNT_ERR( ERR_NEWORDER_ITEMID_RANGE );

                ol_quantity =
pNewOrderData->OL[items].ol_quantity =
GetIntKeyValue(&ptr, szQty[i],
ERR_NEWORDER_MISSING_QTY_KEY,
ERR_NEWORDER_QTY_INVALID);
                if ( ol_quantity > 99
|| ol_quantity < 1 )
                    throw new
CWBCLNT_ERR( ERR_NEWORDER_QTY_RANGE );

                items++;
            }
            else
            {
                // nothing entered for
supply warehouse, so item id and qty must also be
blank
                GetIntKeyValue(&ptr,
szIID[i], szTmp, sizeof(szTmp),
ERR_NEWORDER_MISSING_IID_KEY);
                if ( szTmp[0] )
                    throw new
CWBCLNT_ERR( ERR_NEWORDER_ITEMID_WITHOUT_SUPPW );

                GetIntKeyValue(&ptr,
szQty[i], szTmp, sizeof(szTmp),
ERR_NEWORDER_MISSING_QTY_KEY);
                if ( szTmp[0] )
                    throw new
CWBCLNT_ERR( ERR_NEWORDER_QTY_WITHOUT_SUPPW );
            }
        }
    }
}

```

```

        if ( items == 0 )
            throw new CWBCLNT_ERR(
ERR_NEWORDER_NOITEMS_ENTERED );
    }
    pNewOrderData->o_ol_cnt = items;
}

/* FUNCTION: GetPaymentData
 *
 * PURPOSE:      This function extracts and
validates the payment form data from an http command
string.
 *
 * ARGUMENTS:    LPSTR          client
                lpszQueryString browser http command string
                *pPaymentData  pointer to
                PAYMENT_DATA   payment data structure
                */

void GetPaymentData(LPSTR lpszQueryString,
PAYMENT_DATA *pPaymentData)
{
    char    szTmp[26];
    char    *ptr = lpszQueryString;
    BOOL    bCustIdBlank;
    int     iLen;

    pPaymentData->d_id = GetIntKeyValue(&ptr,
"DID*", ERR_PAYMENT_MISSING_DID_KEY,
ERR_PAYMENT_DISTRICT_INVALID);

    GetKeyValue(&ptr, "CID*", szTmp,
sizeof(szTmp), ERR_PAYMENT_MISSING_CID_KEY);
    if ( szTmp[0] == 0 )
    {
        bCustIdBlank = TRUE;
        pPaymentData->c_id = 0;
    }
    else
    {
        // parse customer id and verify
that last name was NOT entered
        bCustIdBlank = FALSE;
        if ( !IsNumeric(szTmp) )
            throw new CWBCLNT_ERR(
ERR_PAYMENT_CUSTOMER_INVALID );
        pPaymentData->c_id = atoi(szTmp);
    }

    pPaymentData->c_w_id = GetIntKeyValue(&ptr,
"CWI*", ERR_PAYMENT_MISSING_CWI_KEY,
ERR_PAYMENT_CWI_INVALID);
    pPaymentData->c_d_id = GetIntKeyValue(&ptr,
"CDI*", ERR_PAYMENT_MISSING_CDI_KEY,
ERR_PAYMENT_CDI_INVALID);

    if ( bCustIdBlank )
    {
        // customer id is blank, so last
name must be entered

```

```

        GetKeyValue(&ptr, "CLT*", szTmp,
sizeof(szTmp), ERR_PAYMENT_MISSING_CLT_KEY);
        if ( szTmp[0] == 0 )
            throw new CWBCLNT_ERR(
ERR_PAYMENT_MISSING_CID_CLT );

        _strupr( szTmp );
        if ( strlen(szTmp) >
LAST_NAME_LEN )
            throw new CWBCLNT_ERR(
ERR_PAYMENT_LAST_NAME_TO_LONG );

        strcpy(pPaymentData->c_last,
szTmp);
        // pad with spaces so that the
client layer doesn't have to do it
        // before passing parameters to
stored procedure
        iLen = strlen(pPaymentData-
>c_last);
        memset(pPaymentData->c_last +
iLen, ' ', LAST_NAME_LEN - iLen);
        pPaymentData-
>c_last[LAST_NAME_LEN] = 0;
    }
    else
    {
        // parse customer id and verify
that last name was NOT entered
        GetKeyValue(&ptr, "CLT*", szTmp,
sizeof(szTmp), ERR_PAYMENT_MISSING_CLT_KEY);
        if ( szTmp[0] != 0 )
            throw new CWBCLNT_ERR(
ERR_PAYMENT_CID_AND_CLT );
    }

    GetKeyValue(&ptr, "HAM*", szTmp,
sizeof(szTmp), ERR_PAYMENT_MISSING_HAM_KEY);
    if ( !IsDecimal(szTmp) )
        throw new CWBCLNT_ERR(
ERR_PAYMENT_HAM_INVALID );
    pPaymentData->h_amount = atof(szTmp);
    if ( pPaymentData->h_amount >= 10000.00 ||
pPaymentData->h_amount < 0 )
        throw new CWBCLNT_ERR(
ERR_PAYMENT_HAM_RANGE );
}

/* FUNCTION: GetOrderStatusData
 *
 * PURPOSE:      This function extracts and
validates the payment form data from an http command
string.
 *
 * ARGUMENTS:    LPSTR          client
                lpszQueryString browser http command string
                *pPaymentData  pointer to
                PAYMENT_DATA   payment data structure
                */

void GetOrderStatusData(LPSTR lpszQueryString,
ORDER_STATUS_DATA *pOrderStatusData)
{
    char    szTmp[26];
    char    *ptr = lpszQueryString;
    int     iLen;

```

```

        pOrderStatusData->d_id =
GetIntKeyValue(&ptr, "DID*",
ERR_ORDERSTATUS_MISSING_DID_KEY,
ERR_ORDERSTATUS_DID_INVALID);

        GetKeyValue(&ptr, "CID*", szTmp,
sizeof(szTmp), ERR_ORDERSTATUS_MISSING_CID_KEY);
        if ( szTmp[0] == 0 )
        {
            // customer id is blank, so last
name must be entered
            pOrderStatusData->c_id = 0;
            GetKeyValue(&ptr, "CLT*", szTmp,
sizeof(szTmp), ERR_ORDERSTATUS_MISSING_CLT_KEY);
            if ( szTmp[0] == 0 )
                throw new CWBCLNT_ERR(
ERR_ORDERSTATUS_MISSING_CID_CLT );

            _strupr( szTmp );
            if ( strlen(szTmp) >
LAST_NAME_LEN )
                throw new CWBCLNT_ERR(
ERR_ORDERSTATUS_CLT_RANGE );

            strcpy(pOrderStatusData->c_last,
szTmp);
            // pad with spaces so that the
client layer doesn't have to do it
            // before passing parameters to
stored procedure
            iLen = strlen(pOrderStatusData-
>c_last);
            memset(pOrderStatusData->c_last +
iLen, ' ', LAST_NAME_LEN - iLen);
            pOrderStatusData-
>c_last[LAST_NAME_LEN] = 0;
        }
        else
        {
            // parse customer id and verify
that last name was NOT entered
            if ( !IsNumeric(szTmp) )
                throw new CWBCLNT_ERR(
ERR_ORDERSTATUS_CID_INVALID );
            pOrderStatusData->c_id =
atoi(szTmp);
            GetKeyValue(&ptr, "CLT*", szTmp,
sizeof(szTmp), ERR_ORDERSTATUS_MISSING_CLT_KEY);
            if ( szTmp[0] != 0 )
                throw new CWBCLNT_ERR(
ERR_ORDERSTATUS_CID_AND_CLT );
        }
    }

}

/* FUNCTION: BOOL IsNumeric(char *ptr)
 *
 * PURPOSE:      This function determines if a
string is numeric. It fails if any characters other
than numeric and null
terminator are present.
 *

```

```

* ARGUMENTS:      char
                  *ptr      pointer to string to check.
*
* RETURNS:        BOOL      FALSE   if
string is not all numeric
*
                  TRUE       if string contains only numeric
characters i.e. '0' - '9'
*/

BOOL IsNumeric(char *ptr)
{
    if ( *ptr == 0 )
        return FALSE;

    while( *ptr && isdigit(*ptr) )
        ptr++;
    return ( !*ptr );
}

/* FUNCTION: BOOL IsDecimal(char *ptr)
*
* PURPOSE:        This function determines if a
string is a non-negative decimal value.
*                It fails if any characters other than a
series of numbers followed by a decimal point,
another series of numbers, and a null terminator are
present.
*
* ARGUMENTS:      char
                  *ptr      pointer to string to check.
*
* RETURNS:        BOOL      FALSE   if
string is not a valid non-negative decimal value
*
                  TRUE       if string is OK
*/

BOOL IsDecimal(char *ptr)
{
    char *dotptr;
    BOOL  bValid;

    if ( *ptr == 0 )
        return FALSE;

    // find decimal point
    dotptr = strchr( ptr, '.' );
    if (dotptr == NULL)
        // no decimal point, so just
check for numeric
        return IsNumeric(ptr);
    *dotptr = 0; // temporarily replace
decimal with a terminator

    if ( *ptr != 0 )
        bValid = IsNumeric(ptr);
    // string starts with decimal point
    else if (*(dotptr+1) == 0)

```

```

        return FALSE; // nothing but a
decimal point is bad
    else
        bValid = TRUE;

    if (*(dotptr+1) != 0)
        // check text after decimal point
        bValid &= IsNumeric(dotptr+1);

    *dotptr = '.'; // replace decimal point
    return bValid;
}

```

tpcc.h

```

/* FILE:          TPCC.H
*
*                Microsoft
TPC-C Kit Ver. 4.20.000
*                Copyright
Microsoft, 1999
*                All Rights Reserved
*
*                Version
4.10.000 audited by Richard Gimarc, Performance
Metrics, 3/17/99
*
*                PURPOSE: Header file for ISAPI TPCC.DLL,
defines structures and functions used in the isapi
tpcc.dll.
*/

//VERSION RESOURCE DEFINES
#define _APS_NEXT_RESOURCE_VALUE
101
#define _APS_NEXT_COMMAND_VALUE
40001
#define _APS_NEXT_CONTROL_VALUE
1000
#define _APS_NEXT_SYMED_VALUE
101

#define TP_MAX_RETRIES
50

//note that the welcome form must be processed first
as terminal ids assigned here, once the
//terminal id is assigned then the forms can be
processed in any order.
#define WELCOME_FORM
1
//beginning form no term id assigned, form
id
#define MAIN_MENU_FORM
2
//term id assigned main menu form id
#define NEW_ORDER_FORM
3
//new order form id

```

```

#define PAYMENT_FORM
4
//payment form id
#define DELIVERY_FORM
5
//delivery form id
#define ORDER_STATUS_FORM
6
//order
status id
#define STOCK_LEVEL_FORM
7
//stock level
form id

//This macro is used to prevent the compiler error
unused formal parameter
#define UNUSEDPARAM(x) (x = x)

//This structure defines the data necessary to keep
distinct for each terminal or client connection.
typedef struct _CLIENTDATA
{
    int iNextFree; //index of
//next free element or -1 if this entry in use.
    int w_id; //warehouse
id assigned at welcome form
    int d_id; //district id
assigned at welcome form

    int iSyncId; //synchronization id
    int iTickCount; //time of
last access;

    CTPCC_BASE *pTxn;
} CLIENTDATA, *PCLIENTDATA;

//This structure is used to define the operational
interface for terminal id support
typedef struct _TERM
{
    int iNumEntries;
//total allocated terminal array entries
    int iFreeList;
//next available terminal array element or
-1 if none
    int iMasterSyncId;
//synchronization id
    CLIENTDATA *pClientData; //pointer to
allocated client data
} TERM;

```

```

typedef TERM *PTERM;
//pointer to
terminal structure type

enum WEBERROR
{
    NO_ERR,
    ERR_COMMAND_UNDEFINED,
    ERR_D_ID_INVALID,
    ERR_DELIVERY_CARRIER_ID_RANGE,
    ERR_DELIVERY_CARRIER_INVALID,
    ERR_DELIVERY_MISSING_OCD_KEY,
    ERR_DELIVERY_THREAD_FAILED,
    ERR_GETPROCADDR_FAILED,
    ERR_HTML_ILL_FORMED,
    ERR_INVALID_SYNC_CONNECTION,
    ERR_INVALID_TERMID,
    ERR_LOADDLL_FAILED,
    ERR_MAX_CONNECTIONS_EXCEEDED,
    ERR_MEM_ALLOC_FAILED,
    ERR_MISSING_REGISTRY_ENTRIES,
    ERR_NEWORDER_CUSTOMER_INVALID,
    ERR_NEWORDER_CUSTOMER_KEY,
    ERR_NEWORDER_DISTRICT_INVALID,
    ERR_NEWORDER_FORM_MISSING_DID,
    ERR_NEWORDER_ITEMID_INVALID,
    ERR_NEWORDER_ITEMID_RANGE,
    ERR_NEWORDER_ITEMID WITHOUT SUPPW,
    ERR_NEWORDER_MISSING_IID_KEY,
    ERR_NEWORDER_MISSING_QTY_KEY,
    ERR_NEWORDER_MISSING_SUPPW_KEY,
    ERR_NEWORDER_NOITEMS_ENTERED,
    ERR_NEWORDER_QTY_INVALID,
    ERR_NEWORDER_QTY_RANGE,
    ERR_NEWORDER_QTY WITHOUT SUPPW,
    ERR_NEWORDER_SUPPW_INVALID,
    ERR_NO_SERVER_SPECIFIED,
    ERR_ORDERSTATUS_CID_AND_CLT,
    ERR_ORDERSTATUS_CID_INVALID,
    ERR_ORDERSTATUS_CLT_RANGE,
    ERR_ORDERSTATUS_DID_INVALID,
    ERR_ORDERSTATUS_MISSING_CID_CLT,
    ERR_ORDERSTATUS_MISSING_CID_KEY,
    ERR_ORDERSTATUS_MISSING_CLT_KEY,
    ERR_ORDERSTATUS_MISSING_DID_KEY,
    ERR_PAYMENT_CDI_INVALID,
    ERR_PAYMENT_CID_AND_CLT,
    ERR_PAYMENT_CUSTOMER_INVALID,
    ERR_PAYMENT_CWI_INVALID,
    ERR_PAYMENT_DISTRICT_INVALID,
    ERR_PAYMENT_HAM_INVALID,
    ERR_PAYMENT_HAM_RANGE,
    ERR_PAYMENT_LAST_NAME TO LONG,
    ERR_PAYMENT_MISSING_CDI_KEY,
    ERR_PAYMENT_MISSING_CID_CLT,
    ERR_PAYMENT_MISSING_CID_KEY,
    ERR_PAYMENT_MISSING_CLT,
    ERR_PAYMENT_MISSING_CLT_KEY,

```

```

    ERR_PAYMENT_MISSING_CWI_KEY,
    ERR_PAYMENT_MISSING_DID_KEY,
    ERR_PAYMENT_MISSING_HAM_KEY,
    ERR_STOCKLEVEL_MISSING_THRESHOLD_KEY,
    ERR_STOCKLEVEL_THRESHOLD_INVALID,
    ERR_STOCKLEVEL_THRESHOLD_RANGE,
    ERR_VERSION_MISMATCH,
    ERR_W_ID_INVALID
};

class CWEBCLNT_ERR : public CBaseErr
{
public:
    CWEBCLNT_ERR(WEBERROR Err)
    {
        m_Error = Err;
        m_szTextDetail = NULL;
        m_SystemErr = 0;
        m_szErrorText = NULL;
    };
    CWEBCLNT_ERR(WEBERROR Err, char
    *szTextDetail, DWORD dwSystemErr)
    {
        m_Error = Err;
        m_szTextDetail = new
        char[strlen(szTextDetail)+1];
        strcpy( m_szTextDetail,
        szTextDetail );
        m_SystemErr =
        dwSystemErr;
        m_szErrorText = NULL;
    };
    ~CWEBCLNT_ERR()
    {
        if (m_szTextDetail !=
        NULL)
            delete []
            m_szTextDetail;
        if (m_szErrorText !=
        NULL)
            delete []
            m_szErrorText;
    };
    WEBERROR m_Error;
    char
    *m_szTextDetail; //
    char
    *m_szErrorText;
    DWORD m_SystemErr;
    int ErrorType() {return
    ERR_TYPE_WEBDLL;};
    char *ErrorTypeStr() { return
    "WEBCLIENT"; }
    int ErrorNum() {return m_Error;};
    char *ErrorText();

```

```

};

//These constants have already been defined in
engstat.h, but since we do
//not want to include it in the delisrv executable
#define TXN_EVENT_START 2
#define TXN_EVENT_STOP 4
#define TXN_EVENT_WARNING 6
//used to record a warning into the log

//function prototypes

BOOL APIENTRY DllMain(HANDLE hModule, DWORD
ul_reason_for_call, LPVOID lpReserved);
void WriteMessageToEventLog(LPTSTR lpszMsg);
void ProcessQueryString(EXTENSION_CONTROL_BLOCK
*pECB, int *pCmd, int *pFormId, int *pTermId, int
*pSyncId);
void WelcomeForm(EXTENSION_CONTROL_BLOCK *pECB, char
*szBuffer);
void SubmitCmd(EXTENSION_CONTROL_BLOCK *pECB, char
*szBuffer);
void BeginCmd(EXTENSION_CONTROL_BLOCK *pECB, int
iFormId, int iTermId);
void ProcessCmd(EXTENSION_CONTROL_BLOCK *pECB, int
iFormId, int iTermId);
void StatsCmd(EXTENSION_CONTROL_BLOCK *pECB, char
*szBuffer);
void ErrorMessage(EXTENSION_CONTROL_BLOCK *pECB, int
iError, int iErrorType, char *szMsg, int iTermId);
void GetKeyValue(char **pQueryString, char *pKey,
char *pValue, int iMax, WEBERROR err);
int GetIntKeyValue(char **pQueryString, char *pKey,
WEBERROR NoKeyErr, WEBERROR NotIntErr);
void TermInit(void);
void TermDeleteAll(void);
int TermAdd(void);
void TermDelete(int id);
void ErrorForm(EXTENSION_CONTROL_BLOCK *pECB, int
iType, int iErrorNum, int iTermId, int iSyncId, char
*szErrorText, char *szBuffer);
void MakeMainMenuForm(int iTermId, int iSyncId, char
*szForm);
void MakeStockLevelForm(int iTermId, STOCK_LEVEL_DATA
*pStockLevelData, BOOL bInput, char *szForm);
void MakeNewOrderForm(int iTermId, NEW_ORDER_DATA
*pNewOrderData, BOOL bInput, char *szForm);
void MakePaymentForm(int iTermId, PAYMENT_DATA
*pPaymentData, BOOL bInput, char *szForm);
void MakeOrderStatusForm(int iTermId,
ORDER_STATUS_DATA *pOrderStatusData, BOOL bInput,
char *szForm);
void MakeDeliveryForm(int iTermId, DELIVERY_DATA
*pDeliveryData, BOOL bInput, char *szForm);
void ProcessNewOrderForm(EXTENSION_CONTROL_BLOCK
*pECB, int iTermId, char *szBuffer);
void ProcessPaymentForm(EXTENSION_CONTROL_BLOCK
*pECB, int iTermId, char *szBuffer);
void ProcessOrderStatusForm(EXTENSION_CONTROL_BLOCK
*pECB, int iTermId, char *szBuffer);

```



```

void ProcessDeliveryForm(EXTENSION_CONTROL_BLOCK
*pECB, int iTermId, char *szBuffer);
void ProcessStockLevelForm(EXTENSION_CONTROL_BLOCK
*pECB, int iTermId, char *szBuffer);
void GetNewOrderData(LPSTR lpszQueryString,
NEW_ORDER_DATA *pNewOrderData);
void GetPaymentData(LPSTR lpszQueryString,
PAYMENT_DATA *pPaymentData);
void GetOrderStatusData(LPSTR lpszQueryString,
ORDER_STATUS_DATA *pOrderStatusData);
BOOL PostDeliveryInfo(long w_id, short o_carrier_id);
BOOL IsNumeric(char *ptr);
BOOL IsDecimal(char *ptr);
void DeliveryWorkerThread(void *ptr);

```

tpcc.rc

```

//Microsoft Developer Studio generated resource
script.
//
#include "resource.h"

#define APSTUDIO_READONLY_SYMBOLS
////////////////////
//
// Generated from the TEXTINCLUDE 2 resource.
//
#include "afxres.h"

////////////////////
#undef APSTUDIO_READONLY_SYMBOLS

////////////////////
// English (U.S.) resources

#if !defined(AFX_RESOURCE_DLL) ||
defined(AFX_TARG_ENU)
#ifdef _WIN32
LANGUAGE LANG_ENGLISH, SUBLANG_ENGLISH_US
#pragma code_page(1252)
#endif // _WIN32

#ifdef _MAC
////////////////////
//
// Version
//
VS_VERSION_INFO VERSIONINFO
FILEVERSION 0,4,0,0
PRODUCTVERSION 0,4,0,0
FILEFLAGSMASK 0x3fL
#ifdef _DEBUG
FILEFLAGS 0x1L
#else
FILEFLAGS 0x0L

```

```

#endif
FILEOS 0x40004L
FILETYPE 0x2L
FILESUBTYPE 0x0L
BEGIN
BLOCK "StringFileInfo"
BEGIN
BLOCK "040904b0"
BEGIN
VALUE "Comments", "TPC-C HTML DLL Server
(DBLIB)\0"
VALUE "CompanyName", "Microsoft\0"
VALUE "FileDescription", "TPC-C HTML DLL
Server (DBLIB)\0"
VALUE "FileVersion", "0, 4, 0, 0\0"
VALUE "InternalName", "tpcc\0"
VALUE "LegalCopyright", "Copyright ©
1997\0"
VALUE "OriginalFilename", "tpcc.dll\0"
VALUE "ProductName", "Microsoft tpcc\0"
VALUE "ProductVersion", "0, 4, 0, 0\0"
END
END
BLOCK "VarFileInfo"
BEGIN
VALUE "Translation", 0x409, 1200
END
END
#endif // !_MAC

#ifdef APSTUDIO_INVOKED
////////////////////
//
// TEXTINCLUDE
//
1 TEXTINCLUDE DISCARDABLE
BEGIN
"resource.h\0"
END
2 TEXTINCLUDE DISCARDABLE
BEGIN
#include "afxres.h"\r\n
"\0"
END
3 TEXTINCLUDE DISCARDABLE
BEGIN
"\r\n"
"\0"
END
#endif // APSTUDIO_INVOKED

////////////////////

```

```

//
// Dialog
//
IDD_DIALOG1 DIALOG DISCARDABLE 0, 0, 186, 95
STYLE DS_MODALFRAME | WS_POPUP | WS_CAPTION |
WS_SYSMENU
CAPTION "Dialog"
FONT 8, "MS Sans Serif"
BEGIN
DEFPUSHBUTTON "OK", IDOK, 129, 7, 50, 14
PUSHBUTTON "Cancel", IDCANCEL, 129, 24, 50, 14
END

////////////////////
//
// DESIGNINFO
//
#ifdef APSTUDIO_INVOKED
GUIDELINES DESIGNINFO DISCARDABLE
BEGIN
IDD_DIALOG1, DIALOG
BEGIN
LEFTMARGIN, 7
RIGHTMARGIN, 179
TOPMARGIN, 7
BOTTOMMARGIN, 88
END
#endif // APSTUDIO_INVOKED

#ifdef _English (U.S.) resources
////////////////////
#ifdef APSTUDIO_INVOKED
////////////////////
//
// Generated from the TEXTINCLUDE 3 resource.
//

////////////////////
#endif // not APSTUDIO_INVOKED


```

tpcc_com.cpp

```

/* FILE: TPCC_COM.CPP
* Microsoft
* TPC-C Kit Ver. 4.20.000
* Copyright
* Microsoft, 1999

```

```

*           All Rights Reserved
*
*           not yet
*
* audited
*
*           PURPOSE: Source file for TPC-C COM+ class
implementation.
*           Contact: Charles Levine
(clevine@microsoft.com)
*
* Change history:
*           4.20.000 - first version
*/

// needed for CoInitializeEx
#define WIN32_WINNT 0x0400

#include <windows.h>

// need to declare functions for export
#define DllDecl __declspec( dllexport )

#include "..\..\common\src\trans.h"
//tpckit transaction header contains
definitions of structures specific to TPC-C
#include "..\..\common\src\error.h"
#include "..\..\common\src\txn_base.h"
#include "tpcc_com.h"

#include "..\..\tpcc_com_ps\src\tpcc_com_ps_i.c"
#include "..\..\tpcc_com_all\src\tpcc_com_all_i.c"

// wrapper routine for class constructor
__declspec( dllexport ) CTPCC_COM* CTPCC_COM_new(BOOL
bSinglePool)
{
    return new CTPCC_COM(bSinglePool);
}

CTPCC_COM::CTPCC_COM(BOOL bSinglePool)
{
    HRESULT hr = NULL;
    long lRet = 0;
    ULONG ulTmpSize = 0;

    m_pTxn = NULL;
    m_pNewOrder = NULL;
    m_pPayment = NULL;
    m_pStockLevel = NULL;
    m_pOrderStatus = NULL;

    m_bSinglePool = bSinglePool;

    ulTmpSize = (ULONG) sizeof(COM_DATA);
    VariantInit(&m_vTxn);
    m_vTxn.vt = VT_SAFEARRAY;

    m_vTxn.parray =
SafeArrayCreateVector(VT_UI1, ulTmpSize, ulTmpSize);
    if (!m_vTxn.parray)
        throw new CCOMERR( E_FAIL );

```

```

        memset( (void*)m_vTxn.parray-
>pvData, 0, ulTmpSize);
        m_pTxn = (COM_DATA*)m_vTxn.parray->pvData;

        hr = CoInitializeEx(NULL,
COINIT_MULTITHREADED);
        if (FAILED(hr))
        {
            throw new CCOMERR( hr );
        }

        // create components
        if (m_bSinglePool)
        {
            hr = CoCreateInstance(CLSID_TPCC,
NULL, CLSCTX_SERVER, IID_ITPCC, (void
**) &m_pNewOrder);
            if (FAILED(hr))
                throw new CCOMERR(hr);

            // all txns will use same
            component
            {
                m_pPayment = m_pNewOrder;
                m_pStockLevel = m_pNewOrder;
                m_pOrderStatus = m_pNewOrder;
            }
            else
            {
                // use different components for
each txn
                hr =
CoCreateInstance(CLSID_NewOrder, NULL, CLSCTX_SERVER,
IID_ITPCC, (void **) &m_pNewOrder);
                if (FAILED(hr))
                    throw new CCOMERR(hr);

                hr =
CoCreateInstance(CLSID_Payment, NULL, CLSCTX_SERVER,
IID_ITPCC, (void **) &m_pPayment);
                if (FAILED(hr))
                    throw new CCOMERR(hr);

                hr =
CoCreateInstance(CLSID_StockLevel, NULL,
CLSCTX_SERVER, IID_ITPCC, (void **) &m_pStockLevel);
                if (FAILED(hr))
                    throw new CCOMERR(hr);

                hr =
CoCreateInstance(CLSID_OrderStatus, NULL,
CLSCTX_SERVER, IID_ITPCC, (void **) &m_pOrderStatus);
                if (FAILED(hr))
                    throw new CCOMERR(hr);
            }

            // call setcomplete to release each
component
            back into pool
            hr = m_pNewOrder->CallSetComplete();
            if (FAILED(hr))

```

```

                throw new CCOMERR(hr);
            if (!m_bSinglePool)
            {
                hr = m_pPayment-
>CallSetComplete();
                if (FAILED(hr))
                    throw new CCOMERR(hr);

                hr = m_pStockLevel-
>CallSetComplete();
                if (FAILED(hr))
                    throw new CCOMERR(hr);

                hr = m_pOrderStatus-
>CallSetComplete();
                if (FAILED(hr))
                    throw new CCOMERR(hr);
            }
        }
        CTPCC_COM::~CTPCC_COM()
        {
            if (m_pTxn)
                SafeArrayDestroy(m_vTxn.parray);

            ReleaseInterface(m_pNewOrder);
            if (!m_bSinglePool)
            {
                ReleaseInterface(m_pPayment);
                ReleaseInterface(m_pStockLevel);
                ReleaseInterface(m_pOrderStatus);
            }
            CoUninitialize();
        }

        void CTPCC_COM::NewOrder()
        {
            VARIANT vTxn_out;

            HRESULT hr = m_pNewOrder->NewOrder(m_vTxn,
&vTxn_out);
            if (FAILED(hr))
                throw new CCOMERR( hr );
            memcpy(m_pTxn, (void *)vTxn_out.parray-
>pvData, vTxn_out.parray->rgsabound[0].cElements);
            SafeArrayDestroy(vTxn_out.parray);

            if ( m_pTxn->ErrorType != ERR_SUCCESS )
                throw new CCOMERR( m_pTxn-
>ErrorType, m_pTxn->error );
        }

        void CTPCC_COM::Payment()
        {
            VARIANT vTxn_out;

            HRESULT hr = m_pPayment->Payment(m_vTxn,
&vTxn_out);
            if (FAILED(hr))
                throw new CCOMERR( hr );

```

```

        memcpy(m_pTxn, (void *)vTxn_out.parray-
>pvData, vTxn_out.parray->rgsabound[0].cElements);
        SafeArrayDestroy(vTxn_out.parray);

        if ( m_pTxn->ErrorType != ERR_SUCCESS )
            throw new CCOMERR( m_pTxn-
>ErrorType, m_pTxn->error );
    }

void CTPCC_COM::StockLevel()
{
    VARIANT    vTxn_out;

    HRESULT hr = m_pStockLevel-
>StockLevel(m_vTxn, &vTxn_out);
    if (FAILED(hr))
        throw new CCOMERR( hr );
    memcpy(m_pTxn, (void *)vTxn_out.parray-
>pvData, vTxn_out.parray->rgsabound[0].cElements);
    SafeArrayDestroy(vTxn_out.parray);

    if ( m_pTxn->ErrorType != ERR_SUCCESS )
        throw new CCOMERR( m_pTxn-
>ErrorType, m_pTxn->error );
}

void CTPCC_COM::OrderStatus()
{
    VARIANT    vTxn_out;

    HRESULT hr = m_pOrderStatus-
>OrderStatus(m_vTxn, &vTxn_out);
    if (FAILED(hr))
        throw new CCOMERR( hr );
    memcpy(m_pTxn, (void *)vTxn_out.parray-
>pvData, vTxn_out.parray->rgsabound[0].cElements);
    SafeArrayDestroy(vTxn_out.parray);

    if ( m_pTxn->ErrorType != ERR_SUCCESS )
        throw new CCOMERR( m_pTxn-
>ErrorType, m_pTxn->error );
}

```

tpcc_com.h

```

/* FILE: TPCC_COM.H
 * Microsoft
 * TPC-C Kit Ver. 4.20.000
 * Copyright
 * Microsoft, 1999
 * All Rights Reserved
 *
 * not yet
 * audited
 *
 * PURPOSE: Header file for TPC-C COM+ class
 * implementation.
 *
 * Change history:
 *
 * 4.20.000 - first version

```

```

*/
#pragma once
#include <stdio.h>
#include "..\..\tpcc_com_ps\src\tpcc_com_ps.h"

// need to declare functions for import, unless
// define has already been created
// by the DLL's .cpp module for export.
#ifdef DllDecl
#define DllDecl __declspec( dllimport )
#else
#define DllDecl
#endif

class CCOMERR : public CBaseErr
{
private:
    char m_szErrorText[64];

public:
    // use this interface for genuine
    COM errors
    CCOMERR( HRESULT hr )
    {
        m_hr = hr;
        m_iErrorType = 0;
        m_iError = 0;
    }

    // use this interface to
    impersonate a non-COM error type
    CCOMERR( int iErrorType, int
iError )
    {
        m_iErrorType =
iErrorType;
        m_iError = iError;
        m_hr = S_OK;
    }

    int m_hr;
    int m_iErrorType;
    int m_iError;

    // A CCOMERR class can
    impersonate another class, which happens if the error
    // was not actually a COM
    Services error, but was simply transmitted back via
    COM.
    int ErrorType()
    {
        if (m_iErrorType == 0)
            return
ERR_TYPE_COM;
        else
            return
m_iErrorType;
    }

    char *ErrorTypeStr() { return
"COM"; }

```

```

int ErrorNum() {return m_hr;}

char *ErrorText()
{
    if (m_hr == S_OK)
        sprintf(
m_szErrorText, "Error: Class %d, error # %d",
m_iErrorType, m_iError );
    else
        sprintf(
m_szErrorText, "Error: COM HRESULT %x", m_hr );
    return m_szErrorText;
};

class DllDecl CTPCC_COM : public CTPCC_BASE
{
private:
    BOOL m_bSinglePool;

    // COM Interface pointers
    ITPCC*
m_pNewOrder;
    ITPCC*
m_pPayment;
    ITPCC*
m_pStockLevel;
    ITPCC*
m_pOrderStatus;

    struct COM_DATA
    {
        int ErrorType;
        int error;
        union
        {
            NEW_ORDER_DATA      NewOrder;
            PAYMENT_DATA        Payment;
            DELIVERY_DATA       Delivery;
            STOCK_LEVEL_DATA     StockLevel;
            ORDER_STATUS_DATA    OrderStatus;
        } u;
    } *m_pTxn;

    VARIANT m_vTxn;

public:
    CTPCC_COM(BOOL bSinglePool);
    ~CTPCC_COM(void);

    inline PNEW_ORDER_DATA
    BuffAddr_NewOrder() { return
&m_pTxn->u.NewOrder; };
    inline PPAYMENT_DATA
    BuffAddr_Payment() { return
&m_pTxn->u.Payment; };

```

```

        inline PDELIVERY_DATA
        BuffAddr_Delivery() { return
&m_pTxn->u.Delivery; };
        inline PSTOCK_LEVEL_DATA
        BuffAddr_StockLevel() { return
&m_pTxn->u.StockLevel; };
        inline PORDER_STATUS_DATA
        BuffAddr_OrderStatus() { return
&m_pTxn->u.OrderStatus; };

        void NewOrder          ();
        void Payment           ();
        void StockLevel        ();
        void OrderStatus       ();
        void Delivery          ();
{ throw new CCOMERR(E_NOTIMPL); } // not supported
};

inline void ReleaseInterface(IUnknown *pUnk)
{
    if (pUnk)
    {
        pUnk->Release();
        pUnk = NULL;
    }
}

// wrapper routine for class constructor
extern "C" __declspec(dllexport) CTPCC_COM*
CTPCC_COM_new(BOOL);

typedef CTPCC_COM* (TYPE_CTPCC_COM)(BOOL);

```

tpcc_com_all.c pp

```

/* FILE: TPCC_COM_ALL.CPP
 * Microsoft
 * TPC-C Kit Ver. 4.20.000
 * Copyright
 * Microsoft, 1999
 * All Rights Reserved
 * Version
 * 4.10.000 audited by Richard Gimarc, Performance
 * Metrics, 3/17/99
 * PURPOSE: Implementation for TPC-C Tuxedo
 * class.
 * Contact: Charles Levine
 * (clevine@microsoft.com)
 * Change history:
 * 4.20.000 - updated rev number to
 * match kit
 */

```

```

#define STRICT
#define WIN32_WINNT 0x0400
#define _ATL_APARTMENT_THREADED

#include <stdio.h>
#include <atlbase.h>
//You may derive a class from CComModule and use it
if you want to override
//something, but do not change the name of _Module
extern CComModule _Module;

#include <atlcom.h>
#include <initguid.h>
#include <transact.h>
//#include <atlimpl.cpp>
#include <comsvcs.h>

#include <sqltypes.h>
#include <sql.h>
#include <sqlext.h>

#include "tpcc_com_ps.h"
#include "..\..\common\src\trans.h"
//tpckit transaction
header contains definations of structures specific to
TPC-C
#include "..\..\common\src\txn_base.h"
#include "..\..\common\src\error.h"
#include "..\..\common\src\ReadRegistry.h"
#include "..\..\db_dblib_dll\src\tpcc_dblib.h"
// DBLIB implementation of TPC-C txns
#include "..\..\db_odbc_dll\src\tpcc_odbc.h"
// ODBC implementation of TPC-C txns

#include "resource.h"
#include "tpcc_com_all.h"
#include "tpcc_com_all_i.c"
#include "Methods.h"
#include "..\..\tpcc_com_ps\src\tpcc_com_ps_i.c"
#include "..\..\common\src\ReadRegistry.cpp"

CComModule _Module;

BEGIN_OBJECT_MAP(ObjectMap)
    OBJECT_ENTRY(CLSID_TPCC, CTPCC)
    OBJECT_ENTRY(CLSID_NewOrder, CNewOrder)
    OBJECT_ENTRY(CLSID_OrderStatus,
COrderStatus)
    OBJECT_ENTRY(CLSID_Payment, CPayment)
    OBJECT_ENTRY(CLSID_StockLevel, CStockLevel)
END_OBJECT_MAP()

// configuration settings from registry
TPCCREGISTRYDATA Reg;
char
    szMyComputerName[MAX_COMPUTERNAME_LENGTH+1]
;

```

```

static HINSTANCE hLibInstanceDb = NULL;

TYPE_CTPCC_DBLIB *pCTPCC_DBLIB_new;
TYPE_CTPCC_ODBC *pCTPCC_ODBC_new;

// Critical section to synchronize connection open
and close.
//
CRITICAL_SECTION hConnectCriticalSection;

////////////////////////////////////
// DLL Entry Point

extern "C"
BOOL WINAPI DllMain(HINSTANCE hInstance, DWORD
dwReason, LPVOID /*lpReserved*/)
{
    char szDllName[128];
    try
    {
        if (dwReason ==
DLL_PROCESS_ATTACH)
        {
            _Module.Init(ObjectMap,
hInstance);
            DisableThreadLibraryCalls(hInstance);
            DWORD dwSize =
MAX_COMPUTERNAME_LENGTH+1;
            GetComputerName(szMyComputerName, &dwSize);
            szMyComputerName[dwSize] = 0;
            if (
ReadTPCCRegistrySettings( &Reg ))
                throw new
CCOMPONENT_ERR( ERR_MISSING_REGISTRY_ENTRIES );
            if (Reg.eDB_Protocol ==
DBLIB)
            {
                strcpy(
szDllName, Reg.szPath );
                strcat(
szDllName, "tpcc_dblib.dll");
                hLibInstanceDb = LoadLibrary( szDllName );
                if
(hLibInstanceDb == NULL)
                throw new CCOMPONENT_ERR(
ERR_LOADDLL_FAILED, szDllName, GetLastError() );
                // get
                function pointer to wrapper for class constructor
            }
        }
    }
}

```

```

        pCTPCC_DBLIB_new = (TYPE_CTPCC_DBLIB*)
GetProcAddress(hLibInstanceDb, "CTPCC_DBLIB_new");
        if
(pCTPCC_DBLIB_new == NULL)
        throw new CCOMPONENT_ERR(
ERR_GETPROCADDR_FAILED, szDllName, GetLastError() );
        else if
(Reg.eDB_Protocol == ODBC)
        {
                strcpy(
szDllName, Reg.szPath );
                strcat(
szDllName, "tpcc_odbc.dll");

                hLibInstanceDb = LoadLibrary( szDllName );
                if
(hLibInstanceDb == NULL)
                throw new CCOMPONENT_ERR(
ERR_LOADDLL_FAILED, szDllName, GetLastError() );

                // get
function pointer to wrapper for class constructor

                pCTPCC_ODBC_new = (TYPE_CTPCC_ODBC*)
GetProcAddress(hLibInstanceDb, "CTPCC_ODBC_new");
                if
(pCTPCC_ODBC_new == NULL)
                throw new CCOMPONENT_ERR(
ERR_GETPROCADDR_FAILED, szDllName, GetLastError() );
                else
                throw new
CCOMPONENT_ERR( ERR_UNKNOWN_DB_PROTOCOL );

                if (Reg.dwConnectDelay
> 0)
                {
                        InitializeCriticalSection(&hConnectCritical
Section);
                }
        }
        else if (dwReason ==
DLL_PROCESS_DETACH)
                _Module.Term();
    }
    catch (CBaseErr *e)
    {
            TCHAR szMsg[256];

            _sntprintf(szMsg, sizeof(szMsg),
"%s error, code %d: %s",
                e-
>ErrorTypeStr(), e->ErrorNum(), e->ErrorText());

```

```

        WriteMessageToEventLog( szMsg );

        delete e;
        return FALSE;
    }
    catch (...)
    {
            WriteMessageToEventLog(TEXT("Unhandled
exception in object DllMain"));
            return FALSE;
    }
    return TRUE; // OK
}

////////////////////////////////////
////////////////////////////////////
// Used to determine whether the DLL can be unloaded
by OLE

STDAPI DllCanUnloadNow(void)
{
        return (_Module.GetLockCount()==0) ? S_OK :
S_FALSE;
}

////////////////////////////////////
////////////////////////////////////
// Returns a class factory to create an object of the
requested type

STDAPI DllGetClassObject(REFCLSID rclsid, REFIID
riid, LPVOID* ppv)
{
        return _Module.GetClassObject(rclsid, riid,
ppv);
}

////////////////////////////////////
////////////////////////////////////
// DllRegisterServer - Adds entries to the system
registry

STDAPI DllRegisterServer(void)
{
        // registers object, typelib and all
interfaces in typelib
        return _Module.RegisterServer(TRUE);
}

////////////////////////////////////
////////////////////////////////////
// DllUnregisterServer - Removes entries from the
system registry

STDAPI DllUnregisterServer(void)
{
        _Module.UnregisterServer();
        return S_OK;
}

```

```

static void WriteMessageToEventLog(LPTSTR lpszMsg)
{
        TCHAR szMsg[256];
        HANDLE hEventSource;
        LPTSTR lpszStrings[2];

        // Use event logging to log the error.
        //
        hEventSource = RegisterEventSource(NULL,
TEXT("tpcc_com_all.dll"));

        _sntprintf(szMsg, TEXT("Error in COM+ TPC-C
Component: "));
        lpszStrings[0] = szMsg;
        lpszStrings[1] = lpszStrings;

        if (hEventSource != NULL)
        {
                ReportEvent(hEventSource, // handle of event
source
                        EVENTLOG_ERROR_TYPE, // event type
                        0, // event category
                        0, // event ID
                        NULL, // current user's
SID
                        2, // strings in
lpszStrings
                        0, // no bytes of raw
data
                        (LPCTSTR *)lpszStrings, // array of
error strings
                        NULL); // no raw data

                (VOID) DeregisterEventSource(hEventSource);
        }
}

inline void ReleaseInterface(IUnknown *pUnk)
{
        if (pUnk)
        {
                pUnk->Release();
                pUnk = NULL;
        }
}

/* FUNCTION: CCOMPONENT_ERR::ErrorText
*
*/

char* CCOMPONENT_ERR::ErrorText(void)
{
        static SERRORMSG errorMsgs[] =
        {
                { ERR_MISSING_REGISTRY_ENTRIES,
"Required entries missing from registry." },
                { ERR_LOADDLL_FAILED,
"Load of DLL failed. DLL="

```

```

        },
        { ERR_GETPROCADDR_FAILED,
          "Could not map proc in DLL. GetProcAddress
error. DLL="
        },
        { ERR_UNKNOWN_DB_PROTOCOL,
          "Unknown database protocol specified in
registry."
        },
        { 0, ""
        }
    };

    char szTmp[256];
    int i = 0;
    while (TRUE)
    {
        if (errorMsgs[i].szMsg[0] == 0)
        {
            strcpy( szTmp, "Unknown
error number. ");
            break;
        }
        if (m_Error ==
errorMsgs[i].iError)
        {
            strcpy( szTmp,
errorMsgs[i].szMsg );
            break;
        }
        i++;
    }

    if (m_szTextDetail)
        strcat( szTmp, m_szTextDetail );
    if (m_SystemErr)
        wsprintf( szTmp+strlen(szTmp), "
Error=%d", m_SystemErr );

    m_szErrorText = new char[strlen(szTmp)+1];
    strcpy( m_szErrorText, szTmp );
    return m_szErrorText;
}

CTPCC_Common::CTPCC_Common()
{
    m_pTxn = NULL;
    m_bCanBePooled = TRUE;
}

CTPCC_Common::~CTPCC_Common()
{
    // Pace connection close for VIA.
    //
    if (Reg.dwConnectDelay > 0)
    {

```

```

        EnterCriticalSection(&hConnectCriticalSecti
on);

        Sleep(Reg.dwConnectDelay);
    }

    if (m_pTxn)
    {
        delete m_pTxn;
    }

    if (Reg.dwConnectDelay > 0)
    {
        LeaveCriticalSection(&hConnectCriticalSecti
on);
    }

    HRESULT CTPCC_Common::CallSetComplete()
    {
        IObjectContext* pObjectContext = NULL;

        // get our object context
        HRESULT hr = CoGetObjectContext(
IID_IObjectContext, (void **)&pObjectContext );
        pObjectContext->SetComplete();
        ReleaseInterface(pObjectContext);
        return hr;
    }

    //
    // called by the ctor activator
    //
    STDMETHODIMP CTPCC_Common::Construct(IDispatch *
pUnk)
    {
        // Code to access construction string, if
needed later...
        // if (!pUnk)
        // return E_UNEXPECTED;
        // IObjectConstructString * pString
= NULL;
        // HRESULT hr = pUnk-
>QueryInterface(IID_IObjectConstructString, (void
**)&pString);
        // pString->Release();

        try
        {
            // Pace connection creation for
VIA.
            //
            if (Reg.dwConnectDelay > 0)
            {
                EnterCriticalSection(&hConnectCriticalSecti
on);

```

```

                Sleep(Reg.dwConnectDelay);
            }

            if (Reg.eDB_Protocol == ODBC)
                m_pTxn =
pCTPCC_ODBC_new( Reg.szDbServer, Reg.szDbUser,
Reg.szDbPassword,

                szMyComputerName, Reg.szDbName,

                Reg.szSPPrefix,
Reg.bCallNoDuplicatesNewOrder );
            else if (Reg.eDB_Protocol ==
DBLIB)
                m_pTxn =
pCTPCC_DBLIB_new( Reg.szDbServer, Reg.szDbUser,
Reg.szDbPassword, szMyComputerName, Reg.szDbName );

            if (Reg.dwConnectDelay > 0)
            {
                LeaveCriticalSection(&hConnectCriticalSecti
on);
            }
        } catch (CBaseErr *e)
        {
            TCHAR szMsg[256];

            _snprintf(szMsg, sizeof(szMsg),
"%s error in CTPCC_Common::Construct, code %d: %s",
e-
>ErrorTypeStr(), e->ErrorNum(), e->ErrorText());
            WriteMessageToEventLog( szMsg );
            delete e;
            return E_FAIL;
        }
        catch (...)
        {
            WriteMessageToEventLog(TEXT("Unhandled
exception in object ::Construct"));
            return E_FAIL;
        }

        return S_OK;
    }

    HRESULT CTPCC_Common::NewOrder(VARIANT txn_in,
VARIANT* txn_out)
    {
        PNEW_ORDER_DATA pNewOrder;
        COM_DATA *pData;
        try
        {
            pData = (COM_DATA*)txn_in.parray-
>pvData;

```

```

        pNewOrder = m_pTxn-
>BuffAddr_NewOrder();

        memcpy(pNewOrder, &pData-
>u.NewOrder, sizeof(NEW_ORDER_DATA));

        m_pTxn->NewOrder(); //

        VariantInit(txn_out);
        txn_out->vt = VT_SAFEARRAY;
        txn_out->parray =
SafeArrayCreateVector(VT_UI1,

        txn_in.parray->rgsabound-
>cElements,

        txn_in.parray->rgsabound-
>cElements);

        pData = (COM_DATA*) txn_out-
>parray->pvData;

        memcpy( &pData->u.NewOrder,
pNewOrder, sizeof(NEW_ORDER_DATA));

        pData->retval = ERR_SUCCESS;
        pData->error = 0;
        return S_OK;
    }
    catch (CBaseErr *e)
    {
        // check for lost database
        connection; if yes, component is toast
        if ( ((e->ErrorType() ==
ERR_TYPE_DBLIB) && (e->ErrorNum() == 10005) ||
((e->ErrorType() ==
ERR_TYPE_ODBC) && (e->ErrorNum() == 10054)) )
            m_bCanBePooled = FALSE;

        pData->retval = e->ErrorType();
        pData->error = e->ErrorNum();
        delete e;
        return E_FAIL;
    }
    catch (...)
    {
        WriteMessageToEventLog(TEXT("Unhandled
exception."));

        pData->retval = ERR_TYPE_LOGIC;
        pData->error = 0;
        m_bCanBePooled = FALSE;
        return E_FAIL;
    }
}

HRESULT CTPCC_Common::Payment(VARIANT txn_in,
VARIANT* txn_out)
{
    PPAYMENT_DATA    pPayment;
    COM_DATA          *pData;

```

```

        try
        {
            pData = (COM_DATA*)txn_in.parray-
>pvData;
            pPayment = m_pTxn-
>BuffAddr_Payment();

            memcpy(pPayment, &pData-
>u.Payment, sizeof(PAYMENT_DATA));

            m_pTxn->Payment(); //

            do the actual txn

            VariantInit(txn_out);
            txn_out->vt = VT_SAFEARRAY;
            txn_out->parray =
SafeArrayCreateVector( VT_UI1,

            txn_in.parray->rgsabound-
>cElements,

            txn_in.parray->rgsabound-
>cElements);

            pData = (COM_DATA*) txn_out-
>parray->pvData;

            memcpy( &pData->u.Payment,
pPayment, sizeof(PAYMENT_DATA));

            pData->retval = ERR_SUCCESS;
            pData->error = 0;
            return S_OK;
        }
        catch (CBaseErr *e)
        {
            // check for lost database
            connection; if yes, component is toast
            if ( ((e->ErrorType() ==
ERR_TYPE_DBLIB) && (e->ErrorNum() == 10005) ||
((e->ErrorType() ==
ERR_TYPE_ODBC) && (e->ErrorNum() == 10054)) )
                m_bCanBePooled = FALSE;

            pData->retval = e->ErrorType();
            pData->error = e->ErrorNum();
            delete e;
            return E_FAIL;
        }
        catch (...)
        {
            WriteMessageToEventLog(TEXT("Unhandled
exception."));

            pData->retval = ERR_TYPE_LOGIC;
            pData->error = 0;
            m_bCanBePooled = FALSE;
            return E_FAIL;
        }
    }
}

```

```

HRESULT CTPCC_Common::StockLevel(VARIANT txn_in,
VARIANT* txn_out)
{
    PSTOCK_LEVEL_DATA pStockLevel;
    COM_DATA          *pData;

    try
    {
        pData = (COM_DATA*)txn_in.parray-
>pvData;
        pStockLevel = m_pTxn-
>BuffAddr_StockLevel();

        memcpy(pStockLevel, &pData-
>u.StockLevel, sizeof(STOCK_LEVEL_DATA));

        m_pTxn->StockLevel();

        VariantInit(txn_out);
        txn_out->vt = VT_SAFEARRAY;
        txn_out->parray =
SafeArrayCreateVector( VT_UI1,

        txn_in.parray->rgsabound-
>cElements,

        txn_in.parray->rgsabound-
>cElements);

        pData = (COM_DATA*)txn_out-
>parray->pvData;

        memcpy( &pData->u.StockLevel,
pStockLevel, sizeof(STOCK_LEVEL_DATA));

        pData->retval = ERR_SUCCESS;
        pData->error = 0;
        return S_OK;
    }
    catch (CBaseErr *e)
    {
        // check for lost database
        connection; if yes, component is toast
        if ( ((e->ErrorType() ==
ERR_TYPE_DBLIB) && (e->ErrorNum() == 10005) ||
((e->ErrorType() ==
ERR_TYPE_ODBC) && (e->ErrorNum() == 10054)) )
            m_bCanBePooled = FALSE;

        pData->retval = e->ErrorType();
        pData->error = e->ErrorNum();
        delete e;
        return E_FAIL;
    }
    catch (...)
    {
        WriteMessageToEventLog(TEXT("Unhandled
exception."));

        pData->retval = ERR_TYPE_LOGIC;
        pData->error = 0;
        m_bCanBePooled = FALSE;
    }
}

```

```

        return E_FAIL;
    }
}

HRESULT CTPCC_Common::OrderStatus(VARIANT txn_in,
VARIANT* txn_out)
{
    ORDER_STATUS_DATA pOrderStatus;
    COM_DATA            *pData;
    try
    {
        pData = (COM_DATA*)txn_in.parray-
>pvData;
        pOrderStatus = m_pTxn-
>BuffAddr_OrderStatus();

        memcpy(pOrderStatus, &pData-
>u.OrderStatus, sizeof(ORDER_STATUS_DATA));
        m_pTxn->OrderStatus();

        VariantInit(txn_out);
        txn_out->vt = VT_SAFEARRAY;
        txn_out->parray =
SafeArrayCreateVector( VT_UI1,

        txn_in.parray->rgsabound-
>cElements,

        txn_in.parray->rgsabound-
>cElements);
        pData = (COM_DATA*)txn_out-
>parray->pvData;

        memcpy( &pData->u.OrderStatus,
pOrderStatus, sizeof(ORDER_STATUS_DATA));

        pData->retval = ERR_SUCCESS;
        pData->error = 0;
        return S_OK;
    }
    catch (CBaseErr *e)
    {
        // check for lost database
        connection; if yes, component is toast
        if ( (e->ErrorType() ==
ERR_TYPE_DBLIB) && (e->ErrorNum() == 10005) ||
                (e->ErrorType() ==
ERR_TYPE_ODBC) && (e->ErrorNum() == 10054) )
            m_bCanBePooled = FALSE;

        pData->retval = e->ErrorType();
        pData->error = e->ErrorNum();
        delete e;
        return E_FAIL;
    }
    catch (...)
    {
        WriteMessageToEventLog(TEXT("Unhandled
exception."));
    }
}

```

```

        pData->retval = ERR_TYPE_LOGIC;
        pData->error = 0;
        m_bCanBePooled = FALSE;
        return E_FAIL;
    }
}

tpcc_com_all.h

#pragma warning( disable: 4049 ) /* more than 64k
source lines */

/* this ALWAYS GENERATED file contains the
definitions for the interfaces */

/* File created by MIDL compiler version 6.00.0347
*/
/* at Fri Apr 15 14:48:53 2005
*/
/* Compiler settings for .\src\tpcc_com_all.idl:
Oicf, Wl, Zp8, env=Win32 (32b run)
protocol : dce , ms_ext, c_ext
error checks: allocation ref bounds_check enum
stub_data
VC __declspec() decoration level:
__declspec(uuid()), __declspec(selectany),
__declspec(novtable)
DECLSPEC_UUID(), MIDL_INTERFACE()
*/
//@@MIDL_FILE_HEADERING( )

/* verify that the <rpcndr.h> version is high enough
to compile this file*/
#ifndef __REQUIRED_RPCNDR_H_VERSION__
#define __REQUIRED_RPCNDR_H_VERSION__ 440
#endif

#include "rpc.h"
#include "rpcndr.h"

#ifndef __tpcc_com_all_h__
#define __tpcc_com_all_h__

#if defined(_MSC_VER) && (_MSC_VER >= 1020)
#pragma once
#endif

/* Forward Declarations */

#ifndef __TPCC_FWD_DEFINED__
#define __TPCC_FWD_DEFINED__

#ifdef __cplusplus
typedef class TPCC TPCC;
#else
typedef struct TPCC TPCC;
#endif /* __cplusplus */

```

```

#endif /* __TPCC_FWD_DEFINED__ */

#ifndef __NewOrder_FWD_DEFINED__
#define __NewOrder_FWD_DEFINED__

#ifdef __cplusplus
typedef class NewOrder NewOrder;
#else
typedef struct NewOrder NewOrder;
#endif /* __cplusplus */

#endif /* __NewOrder_FWD_DEFINED__ */

#ifndef __OrderStatus_FWD_DEFINED__
#define __OrderStatus_FWD_DEFINED__

#ifdef __cplusplus
typedef class OrderStatus OrderStatus;
#else
typedef struct OrderStatus OrderStatus;
#endif /* __cplusplus */

#endif /* __OrderStatus_FWD_DEFINED__ */

#ifndef __Payment_FWD_DEFINED__
#define __Payment_FWD_DEFINED__

#ifdef __cplusplus
typedef class Payment Payment;
#else
typedef struct Payment Payment;
#endif /* __cplusplus */

#endif /* __Payment_FWD_DEFINED__ */

#ifndef __StockLevel_FWD_DEFINED__
#define __StockLevel_FWD_DEFINED__

#ifdef __cplusplus
typedef class StockLevel StockLevel;
#else
typedef struct StockLevel StockLevel;
#endif /* __cplusplus */

#endif /* __StockLevel_FWD_DEFINED__ */

/* header files for imported files */
#include "oaidl.h"
#include "ocidl.h"
#include "tpcc_com_ps.h"

#ifdef __cplusplus
extern "C"{
#endif

```



```

void * __RPC_USER MIDL_user_allocate(size_t);
void __RPC_USER MIDL_user_free( void * );

/* interface __MIDL_itf_tpcc_com_all_0000 */
/* [local] */

extern RPC_IF_HANDLE
__MIDL_itf_tpcc_com_all_0000_v0_0_c_ifspec;
extern RPC_IF_HANDLE
__MIDL_itf_tpcc_com_all_0000_v0_0_s_ifspec;

#ifdef __TPCCLib_LIBRARY_DEFINED__
#define __TPCCLib_LIBRARY_DEFINED__

/* library TPCCLib */
/* [helpstring][version][uuid] */

EXTERN_C const IID LIBID_TPCCLib;

EXTERN_C const CLSID CLSID_TPCC;

#ifdef __cplusplus
class DECLSPEC_UUID("122A3128-2520-11D3-BA71-00C04FBFE08B")
TPCC;
#endif

EXTERN_C const CLSID CLSID_NewOrder;

#ifdef __cplusplus
class DECLSPEC_UUID("975BAABF-84A7-11D2-BA47-00C04FBFE08B")
NewOrder;
#endif

EXTERN_C const CLSID CLSID_OrderStatus;

#ifdef __cplusplus
class DECLSPEC_UUID("266836AD-A50D-11D2-BA4E-00C04FBFE08B")
OrderStatus;
#endif

EXTERN_C const CLSID CLSID_Payment;

#ifdef __cplusplus
class DECLSPEC_UUID("CD02F7EF-A4FA-11D2-BA4E-00C04FBFE08B")

```

```

Payment;
#endif

EXTERN_C const CLSID CLSID_StockLevel;

#ifdef __cplusplus
class DECLSPEC_UUID("2668369E-A50D-11D2-BA4E-00C04FBFE08B")
StockLevel;
#endif /* __TPCCLib_LIBRARY_DEFINED__ */

/* Additional Prototypes for ALL interfaces */
/* end of Additional Prototypes */

#ifdef __cplusplus
}
#endif

#endif

//Microsoft Developer Studio generated resource script.
//
#include "resource.h"

#define APSTUDIO_READONLY_SYMBOLS
////////////////////////////////////
//
// Generated from the TEXTINCLUDE 2 resource.
//
#include "winres.h"

////////////////////////////////////
#undef APSTUDIO_READONLY_SYMBOLS

////////////////////////////////////
// English (U.S.) resources

#if !defined(AFX_RESOURCE_DLL) ||
defined(AFX_TARG_ENU)
#ifdef _WIN32
LANGUAGE LANG_ENGLISH, SUBLANG_ENGLISH_US
#pragma code_page(1252)
#endif // _WIN32

#ifdef APSTUDIO_INVOKED

```

tpcc_com_all.r **C**

```

////////////////////////////////////
////////////////////////////////////
//
// TEXTINCLUDE
//
1 TEXTINCLUDE DISCARDABLE
BEGIN
    "resource.h\0"
END

2 TEXTINCLUDE DISCARDABLE
BEGIN
    "#include \"winres.h\"\r\n"
    "\0"
END

3 TEXTINCLUDE DISCARDABLE
BEGIN
    "1 TYPELIB \"tpcc_com_all.tlb\"\r\n"
    "\0"
END

#endif // APSTUDIO_INVOKED

#ifdef _MAC
////////////////////////////////////
////////////////////////////////////
//
// Version
//
VS_VERSION_INFO VERSIONINFO
FILEVERSION 1,0,0,1
PRODUCTVERSION 1,0,0,1
FILEFLAGS 0x3FL
#ifdef _DEBUG
FILEFLAGS 0x1L
#else
FILEFLAGS 0x0L
#endif
FILEOS 0x4L
FILETYPE 0x2L
FILESUBTYPE 0x0L
BEGIN
    BLOCK "StringFileInfo"
    BEGIN
        BLOCK "040904B0"
        BEGIN
            VALUE "CompanyName", "\0"
            VALUE "FileDescription", "tpcc_com_all
Module\0"
            VALUE "FileVersion", "1, 0, 0, 1\0"
            VALUE "InternalName", "TPCCNEWORDER\0"
            VALUE "LegalCopyright", "Copyright
1997\0"
            VALUE "OriginalFilename",
"tpcc_com_all.DLL\0"
            VALUE "ProductName", "tpcc_com_all
Module\0"

```

```

        VALUE "ProductVersion", "1, 0, 0, 1\0"
        VALUE "OLESelfRegister", "\0"
    END
END
BLOCK "VarFileInfo"
BEGIN
    VALUE "Translation", 0x409, 1200
END
END
#endif // !_MAC

////////////////////////////////////
////////////////////////////////////
//
// REGISTRY
//
IDR_TPCC                REGISTRY DISCARDABLE
"tpcc_com_all.rgs"
IDR_NEWORDER           REGISTRY DISCARDABLE
"tpcc_com_no.rgs"
IDR_ORDERSTATUS       REGISTRY DISCARDABLE
"tpcc_com_os.rgs"
IDR_PAYMENT           REGISTRY DISCARDABLE
"tpcc_com_pay.rgs"
IDR_STOCKLEVEL        REGISTRY DISCARDABLE
"tpcc_com_sl.rgs"

////////////////////////////////////
////////////////////////////////////
//
// String Table
//
STRINGTABLE DISCARDABLE
BEGIN
    IDS_PROJNAME        "tpcc_com_all"
END

#endif // English (U.S.) resources
////////////////////////////////////
////////////////////////////////////

#ifndef APSTUDIO_INVOKED
////////////////////////////////////
////////////////////////////////////
//
// Generated from the TEXTINCLUDE 3 resource.
//
1 TYPELIB "tpcc_com_all.tlb"

////////////////////////////////////
////////////////////////////////////
#endif // not APSTUDIO_INVOKED

```

tpcc_com_all.rgs

```

HKCR
{
    TPCC.AllTxns.1 = s 'All Txns Class'
    {
        CLSID = s '{122A3128-2520-11D3-BA71-00C04FBFE08B}'
    }
    TPCC.AllTxns = s 'TPCC Class'
    {
        CurVer = s 'TPCC.AllTxns.1'
    }
    NoRemove CLSID
    {
        ForceRemove {122A3128-2520-11D3-BA71-00C04FBFE08B} = s 'TPCC Class'
    }
    'TPCC.AllTxns.1'
        ProgID = s
        VersionIndependentProgID = s 'TPCC.AllTxns'
        InprocServer32 = s
    '%MODULE%'
        {
            val
        }
    ThreadingModel = s 'Both'
    }
}

```

tpcc_com_all.i.c

```

#pragma warning( disable: 4049 ) /* more than 64k
source lines */

/* this ALWAYS GENERATED file contains the IIDs and
CLSIDs */

/* link this file in with the server and any clients
*/

/* File created by MIDL compiler version 6.00.0347
*/
/* at Fri Apr 15 14:48:53 2005
*/
/* Compiler settings for .\src\tpcc_com_all.idl:
Oicf, W1, Zp8, env=Win32 (32b run)
protocol : dce , ms_ext, c_ext

```

```

error checks: allocation ref bounds_check enum
stub_data
VC __declspec() decoration level:
__declspec(uuid()), __declspec(selectany),
__declspec(novtable)
DECLSPEC_UUID(), MIDL_INTERFACE()
*/
//@@MIDL_FILE_HEADING( )

#if !defined(_M_IA64) && !defined(_M_AMD64)

#ifdef __cplusplus
extern "C"{
#endif

#include <rpc.h>
#include <rpcndr.h>

#ifdef _MIDL_USE_GUIDDEF_

#ifndef INITGUID
#define INITGUID
#include <guiddef.h>
#undef INITGUID
#else
#include <guiddef.h>
#endif

#define DEFINE_GUID(name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8) \
    { name, l, w1, w2, b1, b2, b3, b4, b5, b6, b7, b8 }

#else // !_MIDL_USE_GUIDDEF_

#ifndef __IID_DEFINED__
#define __IID_DEFINED__

typedef struct _IID
{
    unsigned long x;
    unsigned short s1;
    unsigned short s2;
    unsigned char c[8];
} IID;

#endif // __IID_DEFINED__

#ifndef CLSID_DEFINED
#define CLSID_DEFINED
typedef IID CLSID;
#endif // CLSID_DEFINED

#define DEFINE_GUID(name,l,w1,w2,b1,w2,b1,b2,b3,b4,b5,b6,b7,b8) \
    const type name = \
    {1,w1,w2,{b1,b2,b3,b4,b5,b6,b7,b8}}

```

```

#endif !_MIDL_USE_GUIDDEF_

MIDL_DEFINE_GUID(IID,
LIBID_TPCCLib, 0x122A3117, 0x2520, 0x11D3, 0xBA, 0x71, 0x00
, 0xC0, 0x4F, 0xBF, 0xE0, 0x8B);

MIDL_DEFINE_GUID(CLSID,
CLSID_TPCC, 0x122A3128, 0x2520, 0x11D3, 0xBA, 0x71, 0x00, 0x
C0, 0x4F, 0xBF, 0xE0, 0x8B);

MIDL_DEFINE_GUID(CLSID,
CLSID_NewOrder, 0x975BAABF, 0x84A7, 0x11D2, 0xBA, 0x47, 0x0
0, 0xC0, 0x4F, 0xBF, 0xE0, 0x8B);

MIDL_DEFINE_GUID(CLSID,
CLSID_OrderStatus, 0x266836AD, 0xA50D, 0x11D2, 0xBA, 0x4E,
0x00, 0xC0, 0x4F, 0xBF, 0xE0, 0x8B);

MIDL_DEFINE_GUID(CLSID,
CLSID_Payment, 0xCD02F7EF, 0xA4FA, 0x11D2, 0xBA, 0x4E, 0x00
, 0xC0, 0x4F, 0xBF, 0xE0, 0x8B);

MIDL_DEFINE_GUID(CLSID,
CLSID_StockLevel, 0x2668369E, 0xA50D, 0x11D2, 0xBA, 0x4E, 0
x00, 0xC0, 0x4F, 0xBF, 0xE0, 0x8B);

#undef MIDL_DEFINE_GUID

#ifdef __cplusplus
}
#endif

#endif /* !defined(_M_IA64) && !defined(_M_AMD64) */

#pragma warning( disable: 4049 ) /* more than 64k
source lines */

/* this ALWAYS GENERATED file contains the IIDs and
CLSIDs */

/* link this file in with the server and any clients
*/

/* File created by MIDL compiler version 6.00.0347
*/
/* at Fri Apr 15 14:48:53 2005
*/
/* Compiler settings for .\src\tpcc_com_all.idl:
Oicf, W1, Zp8, env=Win64 (32b run,appending)
protocol : dce , ms_ext , c_ext , robust
error checks: allocation ref bounds_check enum
stub_data

```

```

VC __declspec() decoration level:
__declspec(uuid()), __declspec(selectany),
__declspec(novtable)
DECLSPEC_UUID(), MIDL_INTERFACE()
*/
//@@MIDL_FILE_HEADING( )

#ifdef _M_IA64 || defined(_M_AMD64)

#ifdef __cplusplus
extern "C"{
#endif

#include <rpc.h>
#include <rpcndr.h>

#ifdef _MIDL_USE_GUIDDEF_

#ifndef INITGUID
#define INITGUID
#include <guiddef.h>
#undef INITGUID
#else
#include <guiddef.h>
#endif

#define
MIDL_DEFINE_GUID(type,name,l,w1,w2,b1,b2,b3,b4,b5,b6,
b7,b8) \

DEFINE_GUID(name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8)

#else /* !_MIDL_USE_GUIDDEF_

#ifdef __IID_DEFINED__
#define __IID_DEFINED__

typedef struct _IID
{
    unsigned long x;
    unsigned short s1;
    unsigned short s2;
    unsigned char c[8];
} IID;

#endif /* __IID_DEFINED__

#ifdef CLSID_DEFINED
#define CLSID_DEFINED
typedef IID CLSID;
#endif /* CLSID_DEFINED

#define
MIDL_DEFINE_GUID(type,name,l,w1,w2,b1,b2,b3,b4,b5,b6,
b7,b8) \
    const type name =
{1,w1,w2,{b1,b2,b3,b4,b5,b6,b7,b8}}

#endif !_MIDL_USE_GUIDDEF_

```

```

MIDL_DEFINE_GUID(IID,
LIBID_TPCCLib, 0x122A3117, 0x2520, 0x11D3, 0xBA, 0x71, 0x00
, 0xC0, 0x4F, 0xBF, 0xE0, 0x8B);

MIDL_DEFINE_GUID(CLSID,
CLSID_TPCC, 0x122A3128, 0x2520, 0x11D3, 0xBA, 0x71, 0x00, 0x
C0, 0x4F, 0xBF, 0xE0, 0x8B);

MIDL_DEFINE_GUID(CLSID,
CLSID_NewOrder, 0x975BAABF, 0x84A7, 0x11D2, 0xBA, 0x47, 0x0
0, 0xC0, 0x4F, 0xBF, 0xE0, 0x8B);

MIDL_DEFINE_GUID(CLSID,
CLSID_OrderStatus, 0x266836AD, 0xA50D, 0x11D2, 0xBA, 0x4E,
0x00, 0xC0, 0x4F, 0xBF, 0xE0, 0x8B);

MIDL_DEFINE_GUID(CLSID,
CLSID_Payment, 0xCD02F7EF, 0xA4FA, 0x11D2, 0xBA, 0x4E, 0x00
, 0xC0, 0x4F, 0xBF, 0xE0, 0x8B);

MIDL_DEFINE_GUID(CLSID,
CLSID_StockLevel, 0x2668369E, 0xA50D, 0x11D2, 0xBA, 0x4E, 0
x00, 0xC0, 0x4F, 0xBF, 0xE0, 0x8B);

#undef MIDL_DEFINE_GUID

#ifdef __cplusplus
}
#endif

#endif /* defined(_M_IA64) || defined(_M_AMD64) */

```

tpcc_com_no.r ***gs***

```

HKCR
{
    TPCC.NewOrder.1 = s 'NewOrder Class'
    {
        CLSID = s '{975BAABF-84A7-11D2-
BA47-00C04FBFE08B}'
    }
    TPCC.NewOrder = s 'NewOrder Class'
    {
        CurVer = s 'TPCC.NewOrder.1'
    }
    NoRemove CLSID
    {
        ForceRemove {975BAABF-84A7-11D2-
BA47-00C04FBFE08B} = s 'NewOrder Class'
    }
}

```

```

        {
            ProgID = s
'TPCC.NewOrder.1'

            VersionIndependentProgID = s
'TPCC.NewOrder'

            InprocServer32 = s
'%MODULE%'
        {
            val
ThreadingModel = s 'Both'
        }
    }
}

```

tpcc_com_os.rgs

```

HKCR
{
    TPCC.OrderStatus.1 = s 'OrderStatus Class'
    {
        CLSID = s '{266836AD-A50D-11D2-BA4E-00C04FBFE08B}'
    }
    TPCC.OrderStatus = s 'OrderStatus Class'
    {
        CurVer = s 'TPCC.OrderStatus.1'
    }
    NoRemove CLSID
    {
        ForceRemove {266836AD-A50D-11D2-BA4E-00C04FBFE08B} = s 'OrderStatus Class'
    }
    ProgID = s
'TPCC.OrderStatus.1'

    VersionIndependentProgID = s
'TPCC.OrderStatus'

    InprocServer32 = s
'%MODULE%'
    {
        val
ThreadingModel = s 'Both'
    }
}
}

```

tpcc_com_pay.rgs

```

HKCR
{

```

```

    TPCC.Payment.1 = s 'Payment Class'
    {
        CLSID = s '{CD02F7EF-A4FA-11D2-BA4E-00C04FBFE08B}'
    }
    TPCC.Payment = s 'Payment Class'
    {
        CurVer = s 'TPCC.Payment.1'
    }
    NoRemove CLSID
    {
        ForceRemove {CD02F7EF-A4FA-11D2-BA4E-00C04FBFE08B} = s 'Payment Class'
    }
    ProgID = s
'TPCC.Payment.1'

    VersionIndependentProgID = s 'TPCC.Payment'
    InprocServer32 = s
'%MODULE%'
    {
        val
ThreadingModel = s 'Both'
    }
}
}

```

tpcc_com_ps.h

```

#pragma warning( disable: 4049 ) /* more than 64k
source lines */

/* this ALWAYS GENERATED file contains the
definitions for the interfaces */

/* File created by MIDL compiler version 6.00.0347
*/
/* at Fri Apr 15 14:48:43 2005
*/
/* Compiler settings for .\src\tpcc_com_ps.idl:
Oicf, Wl, Zp8, env=Win32 (32b run)
protocol : dce , ms_ext, c_ext
error checks: allocation ref bounds_check enum
stub_data
VC __declspec() decoration level:
__declspec(uuid()), __declspec(selectany),
__declspec(novtable)
DECLSPEC_UUID(), MIDL_INTERFACE()
*/
//@@MIDL_FILE_HEADER( )

/* verify that the <rpcndr.h> version is high enough
to compile this file*/
#ifndef __REQUIRED_RPCNDR_H_VERSION__
#define __REQUIRED_RPCNDR_H_VERSION__ 440
#endif

```

```

#include "rpc.h"
#include "rpcndr.h"

#ifndef __RPCNDR_H_VERSION__
#error this stub requires an updated version of
<rpcndr.h>
#endif // __RPCNDR_H_VERSION__

#ifndef COM_NO_WINDOWS_H
#include "windows.h"
#include "ole2.h"
#endif /*COM_NO_WINDOWS_H*/

#ifndef __tpcc_com_ps_h__
#define __tpcc_com_ps_h__

#if defined(_MSC_VER) && (_MSC_VER >= 1020)
#pragma once
#endif

/* Forward Declarations */

#ifndef __ITPCC_FWD_DEFINED__
#define __ITPCC_FWD_DEFINED__
typedef interface ITPCC ITPCC;
#endif /* __ITPCC_FWD_DEFINED__ */

/* header files for imported files */
#include "oaidl.h"
#include "ocidl.h"

#ifdef __cplusplus
extern "C"{
#endif

void * __RPC_USER MIDL_user_allocate(size_t);
void __RPC_USER MIDL_user_free( void * );

/* interface __MIDL_itf_tpcc_com_ps_0000 */
/* [local] */

extern RPC_IF_HANDLE
__MIDL_itf_tpcc_com_ps_0000_v0_0_c_ifspec;
extern RPC_IF_HANDLE
__MIDL_itf_tpcc_com_ps_0000_v0_0_s_ifspec;

#ifndef __ITPCC_INTERFACE_DEFINED__
#define __ITPCC_INTERFACE_DEFINED__

/* interface ITPCC */
/* [unique][helpstring][uuid][oleautomation][object]
*/

EXTERN_C const IID IID_ITPCC;

```

```

#if defined(__cplusplus) && !defined(CINTERFACE)

    MIDL_INTERFACE("FEE6AA2-84B1-11d2-BA47-
00C04FBFE08B")
    ITPCC : public IUnknown
    {
    public:
        virtual HRESULT __stdcall NewOrder(
            /* [in] */ VARIANT txn_in,
            /* [out] */ VARIANT *txn_out) = 0;

        virtual HRESULT __stdcall Payment(
            /* [in] */ VARIANT txn_in,
            /* [out] */ VARIANT *txn_out) = 0;

        virtual HRESULT __stdcall Delivery(
            /* [in] */ VARIANT txn_in,
            /* [out] */ VARIANT *txn_out) = 0;

        virtual HRESULT __stdcall StockLevel(
            /* [in] */ VARIANT txn_in,
            /* [out] */ VARIANT *txn_out) = 0;

        virtual HRESULT __stdcall OrderStatus(
            /* [in] */ VARIANT txn_in,
            /* [out] */ VARIANT *txn_out) = 0;

        virtual HRESULT __stdcall CallSetComplete(
            void) = 0;

    };

#else /* C style interface */

    typedef struct ITPCCVtbl
    {
        BEGIN_INTERFACE

        HRESULT ( STDMETHODCALLTYPE *QueryInterface
        )(
            ITPCC * This,
            /* [in] */ REFIID riid,
            /* [iid_is][out] */ void **ppvObject);

        ULONG ( STDMETHODCALLTYPE *AddRef )(
            ITPCC * This);

        ULONG ( STDMETHODCALLTYPE *Release )(
            ITPCC * This);

        HRESULT ( STDMETHODCALLTYPE *NewOrder )(
            ITPCC * This,
            /* [in] */ VARIANT txn_in,
            /* [out] */ VARIANT *txn_out);

        HRESULT ( STDMETHODCALLTYPE *Payment )(
            ITPCC * This,
            /* [in] */ VARIANT txn_in,
            /* [out] */ VARIANT *txn_out);

        HRESULT ( STDMETHODCALLTYPE *Delivery )(
            ITPCC * This,
            /* [in] */ VARIANT txn_in,
            /* [out] */ VARIANT *txn_out);

        HRESULT ( STDMETHODCALLTYPE *StockLevel )(
            ITPCC * This,
            /* [in] */ VARIANT txn_in,
            /* [out] */ VARIANT *txn_out);

        HRESULT ( STDMETHODCALLTYPE *OrderStatus )(
            ITPCC * This,
            /* [in] */ VARIANT txn_in,
            /* [out] */ VARIANT *txn_out);

        HRESULT ( STDMETHODCALLTYPE *CallSetComplete )(
            ITPCC * This,
            void);

    };

#endif

```

```

        ITPCC * This,
        /* [in] */ VARIANT txn_in,
        /* [out] */ VARIANT *txn_out);

    HRESULT ( STDMETHODCALLTYPE *NewOrder )(
        ITPCC * This,
        /* [in] */ VARIANT txn_in,
        /* [out] */ VARIANT *txn_out);

    HRESULT ( STDMETHODCALLTYPE *Payment )(
        ITPCC * This,
        /* [in] */ VARIANT txn_in,
        /* [out] */ VARIANT *txn_out);

    HRESULT ( STDMETHODCALLTYPE *Delivery )(
        ITPCC * This,
        /* [in] */ VARIANT txn_in,
        /* [out] */ VARIANT *txn_out);

    HRESULT ( STDMETHODCALLTYPE *StockLevel )(
        ITPCC * This,
        /* [in] */ VARIANT txn_in,
        /* [out] */ VARIANT *txn_out);

    HRESULT ( STDMETHODCALLTYPE *OrderStatus )(
        ITPCC * This,
        /* [in] */ VARIANT txn_in,
        /* [out] */ VARIANT *txn_out);

    HRESULT ( STDMETHODCALLTYPE *CallSetComplete )(
        ITPCC * This,
        void);

    END_INTERFACE
} ITPCCVtbl;

interface ITPCC
{
    CONST_VTBL struct ITPCCVtbl *lpVtbl;
};

#ifdef COBJMACROS

#define ITPCC_QueryInterface(This,riid,ppvObject) \
    (This)->lpVtbl->QueryInterface(This,riid,ppvObject)

#define ITPCC_AddRef(This) \
    (This)->lpVtbl->AddRef(This)

#define ITPCC_Release(This) \
    (This)->lpVtbl->Release(This)

#define ITPCC_NewOrder(This,txn_in,txn_out) \
    (This)->lpVtbl->NewOrder(This,txn_in,txn_out)

#define ITPCC_Payment(This,txn_in,txn_out) \
    (This)->lpVtbl->Payment(This,txn_in,txn_out)

#define ITPCC_Delivery(This,txn_in,txn_out) \
    (This)->lpVtbl->Delivery(This,txn_in,txn_out)

#define ITPCC_StockLevel(This,txn_in,txn_out) \
    (This)->lpVtbl->StockLevel(This,txn_in,txn_out)

#define ITPCC_OrderStatus(This,txn_in,txn_out) \
    (This)->lpVtbl->OrderStatus(This,txn_in,txn_out)

#define ITPCC_CallSetComplete(This) \
    (This)->lpVtbl->CallSetComplete(This)

#endif /* COBJMACROS */

```

```

#endif /* C style interface */

HRESULT __stdcall ITPCC_NewOrder_Proxy(
    ITPCC * This,
    /* [in] */ VARIANT txn_in,
    /* [out] */ VARIANT *txn_out);

void __RPC_STUB ITPCC_NewOrder_Stub(
    IrpStubBuffer *This,
    IRpcChannelBuffer *pRpcChannelBuffer,
    PRPC_MESSAGE_pRpcMessage,
    DWORD *_pdwStubPhase);

HRESULT __stdcall ITPCC_Payment_Proxy(
    ITPCC * This,
    /* [in] */ VARIANT txn_in,
    /* [out] */ VARIANT *txn_out);

void __RPC_STUB ITPCC_Payment_Stub(
    IrpStubBuffer *This,
    IRpcChannelBuffer *pRpcChannelBuffer,
    PRPC_MESSAGE_pRpcMessage,
    DWORD *_pdwStubPhase);

HRESULT __stdcall ITPCC_Delivery_Proxy(
    ITPCC * This,
    /* [in] */ VARIANT txn_in,
    /* [out] */ VARIANT *txn_out);

void __RPC_STUB ITPCC_Delivery_Stub(
    IrpStubBuffer *This,
    IRpcChannelBuffer *pRpcChannelBuffer,
    PRPC_MESSAGE_pRpcMessage,
    DWORD *_pdwStubPhase);

HRESULT __stdcall ITPCC_StockLevel_Proxy(
    ITPCC * This,
    /* [in] */ VARIANT txn_in,
    /* [out] */ VARIANT *txn_out);

void __RPC_STUB ITPCC_StockLevel_Stub(
    IrpStubBuffer *This,
    IRpcChannelBuffer *pRpcChannelBuffer,
    PRPC_MESSAGE_pRpcMessage,
    DWORD *_pdwStubPhase);

HRESULT __stdcall ITPCC_OrderStatus_Proxy(
    ITPCC * This,
    /* [in] */ VARIANT txn_in,
    /* [out] */ VARIANT *txn_out);

```

```

/* [out] */ VARIANT *txn_out);

void __RPC_STUB ITPCC_OrderStatus_Stub(
    IRpcStubBuffer *This,
    IRpcChannelBuffer *pRpcChannelBuffer,
    PRPC_MESSAGE pRpcMessage,
    DWORD *pdwStubPhase);

HRESULT __stdcall ITPCC_CallSetComplete_Proxy(
    ITPCC * This);

void __RPC_STUB ITPCC_CallSetComplete_Stub(
    IRpcStubBuffer *This,
    IRpcChannelBuffer *pRpcChannelBuffer,
    PRPC_MESSAGE pRpcMessage,
    DWORD *pdwStubPhase);

#endif /* __ITPCC_INTERFACE_DEFINED__ */

/* Additional Prototypes for ALL interfaces */

unsigned long
    __RPC_USER
    VARIANT_UserSize(
        unsigned long *, unsigned long
        , VARIANT * );
unsigned char *
    __RPC_USER
    VARIANT_UserMarshal(
        unsigned long *, unsigned char *, VARIANT * );
unsigned char *
    __RPC_USER
    VARIANT_UserUnmarshal(
        unsigned long *, unsigned char
        *, VARIANT * );
void
    __RPC_USER
    VARIANT_UserFree(
        unsigned long *, VARIANT * );

/* end of Additional Prototypes */

#ifdef __cplusplus
}
#endif

#endif

#pragma warning( disable: 4049 ) /* more than 64k
source lines */

/* this ALWAYS GENERATED file contains the IIDs and
CLSIDs */

tpcc_com_ps_i
.C

```

```

/* link this file in with the server and any clients
*/

/* File created by MIDL compiler version 6.00.0347
*/
/* at Fri Apr 15 14:48:43 2005
*/
/* Compiler settings for .\src\tpcc_com_ps.idl:
    Oicf, Wl, Zp8, env=Win32 (32b run)
    protocol : dce , ms_ext, c_ext
    error checks: allocation ref bounds_check enum
stub_data
    VC __declspec() decoration level:
    __declspec(uuid()), __declspec(selectany),
    __declspec(novtable)
    DECLSPEC_UUID(), MIDL_INTERFACE()
*/
//@@MIDL_FILE_HEADING( )

#ifdef _M_IA64 && !defined(_M_AMD64)

#ifdef __cplusplus
extern "C"{
#endif

#include <rpc.h>
#include <rpcndr.h>

#ifdef _MIDL_USE_GUIDDEF_

#ifndef INITGUID
#define INITGUID
#include <guiddef.h>
#undef INITGUID
#else
#include <guiddef.h>
#endif

#define
    MIDL_DEFINE_GUID(type,name,l,w1,w2,b1,b2,b3,b4,b5,b6,
    b7,b8) \

DEFINE_GUID(name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8)

#else // !_MIDL_USE_GUIDDEF_

#ifndef __IID_DEFINED__
#define __IID_DEFINED__

typedef struct _IID
{
    unsigned long x;
    unsigned short s1;
    unsigned short s2;
    unsigned char c[8];
} IID;

#endif // __IID_DEFINED__

```

```

#ifndef CLSID_DEFINED
#define CLSID_DEFINED
typedef IID CLSID;
#endif // CLSID_DEFINED

#define
    MIDL_DEFINE_GUID(type,name,l,w1,w2,b1,b2,b3,b4,b5,b6,
    b7,b8) \
        const type name =
    {l,w1,w2,{b1,b2,b3,b4,b5,b6,b7,b8}}

#endif !_MIDL_USE_GUIDDEF_

MIDL_DEFINE_GUID(IID,
    IID_ITPCC,0xFEEE6AA2,0x84B1,0x11d2,0xBA,0x47,0x00,0xC
    0,0x4F,0xBF,0xE0,0x8B);

#undef MIDL_DEFINE_GUID

#ifdef __cplusplus
}
#endif

#endif /* !defined(_M_IA64) && !defined(_M_AMD64)*/

#pragma warning( disable: 4049 ) /* more than 64k
source lines */

/* this ALWAYS GENERATED file contains the IIDs and
CLSIDs */

/* link this file in with the server and any clients
*/

/* File created by MIDL compiler version 6.00.0347
*/
/* at Fri Apr 15 14:48:43 2005
*/
/* Compiler settings for .\src\tpcc_com_ps.idl:
    Oicf, Wl, Zp8, env=Win64 (32b run,appending)
    protocol : dce , ms_ext, c_ext, robust
    error checks: allocation ref bounds_check enum
stub_data
    VC __declspec() decoration level:
    __declspec(uuid()), __declspec(selectany),
    __declspec(novtable)
    DECLSPEC_UUID(), MIDL_INTERFACE()
*/
//@@MIDL_FILE_HEADING( )

#ifdef _M_IA64 || defined(_M_AMD64)

#ifdef __cplusplus
extern "C"{
#endif

```

```

#include <rpc.h>
#include <rpcndr.h>

#ifdef _MIDL_USE_GUIDDEF_

#ifndef INITGUID
#define INITGUID
#include <guiddef.h>
#undef INITGUID
#else
#include <guiddef.h>
#endif

#define
MIDL_DEFINE_GUID(type,name,l,w1,w2,b1,b2,b3,b4,b5,b6,
b7,b8) \

DEFINE_GUID(name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8)

#else // !_MIDL_USE_GUIDDEF_

#ifndef __IID_DEFINED__
#define __IID_DEFINED__

typedef struct _IID
{
    unsigned long x;
    unsigned short s1;
    unsigned short s2;
    unsigned char c[8];
} IID;

#endif // __IID_DEFINED__

#ifndef CLSID_DEFINED
#define CLSID_DEFINED
typedef IID CLSID;
#endif // CLSID_DEFINED

#define
MIDL_DEFINE_GUID(type,name,l,w1,w2,b1,b2,b3,b4,b5,b6,
b7,b8) \
    const type name =
{1,w1,w2,{b1,b2,b3,b4,b5,b6,b7,b8}}

#endif !_MIDL_USE_GUIDDEF_

MIDL_DEFINE_GUID(IID,
IID_ITPCC,0xFEEB6AA2,0x84B1,0x11d2,0xBA,0x47,0x00,0xC
0,0x4F,0xBF,0xE0,0x8B);

#undef MIDL_DEFINE_GUID

#ifdef __cplusplus
}
#endif

#endif /* defined(_M_IA64) || defined(_M_AMD64)*/

```

tpcc_com_ps_ p.c

```

#pragma warning( disable: 4049 ) /* more than 64k
source lines */

/* this ALWAYS GENERATED file contains the proxy stub
code */

/* File created by MIDL compiler version 6.00.0347
*/
/* at Fri Apr 15 14:48:43 2005
*/
/* Compiler settings for .\src\tpcc_com_ps.idl:
Oicf, Wl, Zp8, env=Win32 (32b run)
protocol : dce , ms_ext, c_ext
error checks: allocation ref bounds_check enum
stub_data
VC __declspec() decoration level:
__declspec(uuid()), __declspec(selectany),
__declspec(novtable)
DECLSPEC_UUID(), MIDL_INTERFACE()
*/
//@@MIDL_FILE_HEADING( )

#if !defined(_M_IA64) && !defined(_M_AMD64)
#define USE_STUBLESS_PROXY

/* verify that the <rpcproxy.h> version is high
enough to compile this file*/
#ifndef __REDQ_RPCPROXY_H_VERSION__
#define __REQUIRED_RPCPROXY_H_VERSION__ 440
#endif

#include "rpcproxy.h"
#ifndef __RPCPROXY_H_VERSION__
#error this stub requires an updated version of
<rpcproxy.h>
#endif // __RPCPROXY_H_VERSION__

#include "tpcc_com_ps.h"

#define TYPE_FORMAT_STRING_SIZE 1023
#define PROC_FORMAT_STRING_SIZE 193
#define TRANSMIT_AS_TABLE_SIZE 0
#define WIRE_MARSHAL_TABLE_SIZE 1

typedef struct _MIDL_TYPE_FORMAT_STRING
{
    short Pad;
    unsigned char Format[ TYPE_FORMAT_STRING_SIZE ];
} MIDL_TYPE_FORMAT_STRING;

```

```

typedef struct _MIDL_PROC_FORMAT_STRING
{
    short Pad;
    unsigned char Format[ PROC_FORMAT_STRING_SIZE ];
} MIDL_PROC_FORMAT_STRING;

static RPC_SYNTAX_IDENTIFIER RpcTransferSyntax =
{{0x8A885D04,0x1CEB,0x11C9,{0x9F,0xE8,0x08,0x00,0x2B,
0x10,0x48,0x60}},{2,0}};

extern const MIDL_TYPE_FORMAT_STRING
__MIDL_TypeFormatString;
extern const MIDL_PROC_FORMAT_STRING
__MIDL_ProcFormatString;

extern const MIDL_STUB_DESC Object_StubDesc;

extern const MIDL_SERVER_INFO ITPCC_ServerInfo;
extern const MIDL_STUBLESS_PROXY_INFO
ITPCC_ProxyInfo;

extern const USER_MARSHAL_ROUTINE_QUADRUPLE
UserMarshalRoutines[ WIRE_MARSHAL_TABLE_SIZE ];

#if !defined(_RPC_WIN32_)
#error Invalid build platform for this stub.
#endif

#if !(TARGET_IS_NT40_OR_LATER)
#error You need a Windows NT 4.0 or later to run this
stub because it uses these features:
#error -Oif or -Oicf, [wire_marshal] or
[user_marshal] attribute.
#error However, your C/C++ compilation flags indicate
you intend to run this app on earlier systems.
#error This app will die there with the
RPC_X_WRONG_STUB_VERSION error.
#endif

static const MIDL_PROC_FORMAT_STRING
__MIDL_ProcFormatString =
{
    0,
    {
        /* Procedure NewOrder */
        FC_AUTO_HANDLE /*
0x33,
*/
        Old Flags: object, Oi2 /*
0x6c,
*/
        /* 2 */ NdrFcLong( 0x0 ), /* 0 */
        /* 6 */ NdrFcShort( 0x3 ), /* 3 */
        /* 8 */ NdrFcShort( 0x1c ), /* x86 Stack
size/offset = 28 */

```

```

/* 10 */ NdrFcShort( 0x0 ), /* 0 */
/* 12 */ NdrFcShort( 0x8 ), /* 8 */
/* 14 */ 0x7, /* Oi2 Flags: srv must
size, clt must size, has return, */
0x3, /*
3 */

/* Parameter txn_in */

/* 16 */ NdrFcShort( 0x8b ), /* Flags: must size,
must free, in, by val, */
/* 18 */ NdrFcShort( 0x4 ), /* x86 Stack
size/offset = 4 */
/* 20 */ NdrFcShort( 0x3e2 ), /* Type
Offset=994 */

/* Parameter txn_out */

/* 22 */ NdrFcShort( 0x4113 ), /* Flags:
must size, must free, out, simple ref, srv alloc
size=16 */
/* 24 */ NdrFcShort( 0x14 ), /* x86 Stack
size/offset = 20 */
/* 26 */ NdrFcShort( 0x3f4 ), /* Type
Offset=1012 */

/* Return value */

/* 28 */ NdrFcShort( 0x70 ), /* Flags: out, return,
base type, */
/* 30 */ NdrFcShort( 0x18 ), /* x86 Stack
size/offset = 24 */
/* 32 */ 0x8, /* FC_LONG */
0x0, /*
0 */

/* Procedure Payment */

/* 34 */ 0x33, /* FC_AUTO_HANDLE */
0x6c, /*
Old Flags: object, Oi2 */
/* 36 */ NdrFcLong( 0x0 ), /* 0 */
/* 40 */ NdrFcShort( 0x4 ), /* 4 */
/* 42 */ NdrFcShort( 0x1c ), /* x86 Stack
size/offset = 28 */
/* 44 */ NdrFcShort( 0x0 ), /* 0 */
/* 46 */ NdrFcShort( 0x8 ), /* 8 */
/* 48 */ 0x7, /* Oi2 Flags: srv must
size, clt must size, has return, */
0x3, /*
3 */

/* Parameter txn_in */

/* 50 */ NdrFcShort( 0x8b ), /* Flags: must size,
must free, in, by val, */
/* 52 */ NdrFcShort( 0x4 ), /* x86 Stack
size/offset = 4 */
/* 54 */ NdrFcShort( 0x3e2 ), /* Type
Offset=994 */

```

```

/* Parameter txn_out */

/* 56 */ NdrFcShort( 0x4113 ), /* Flags:
must size, must free, out, simple ref, srv alloc
size=16 */
/* 58 */ NdrFcShort( 0x14 ), /* x86 Stack
size/offset = 20 */
/* 60 */ NdrFcShort( 0x3f4 ), /* Type
Offset=1012 */

/* Return value */

/* 62 */ NdrFcShort( 0x70 ), /* Flags: out, return,
base type, */
/* 64 */ NdrFcShort( 0x18 ), /* x86 Stack
size/offset = 24 */
/* 66 */ 0x8, /* FC_LONG */
0x0, /*
0 */

/* Procedure Delivery */

/* 68 */ 0x33, /* FC_AUTO_HANDLE */
0x6c, /*
Old Flags: object, Oi2 */
/* 70 */ NdrFcLong( 0x0 ), /* 0 */
/* 74 */ NdrFcShort( 0x5 ), /* 5 */
/* 76 */ NdrFcShort( 0x1c ), /* x86 Stack
size/offset = 28 */
/* 78 */ NdrFcShort( 0x0 ), /* 0 */
/* 80 */ NdrFcShort( 0x8 ), /* 8 */
/* 82 */ 0x7, /* Oi2 Flags: srv must
size, clt must size, has return, */
0x3, /*
3 */

/* Parameter txn_in */

/* 84 */ NdrFcShort( 0x8b ), /* Flags: must size,
must free, in, by val, */
/* 86 */ NdrFcShort( 0x4 ), /* x86 Stack
size/offset = 4 */
/* 88 */ NdrFcShort( 0x3e2 ), /* Type
Offset=994 */

/* Parameter txn_out */

/* 90 */ NdrFcShort( 0x4113 ), /* Flags:
must size, must free, out, simple ref, srv alloc
size=16 */
/* 92 */ NdrFcShort( 0x14 ), /* x86 Stack
size/offset = 20 */
/* 94 */ NdrFcShort( 0x3f4 ), /* Type
Offset=1012 */

/* Return value */

/* 96 */ NdrFcShort( 0x70 ), /* Flags: out, return,
base type, */
/* 98 */ NdrFcShort( 0x18 ), /* x86 Stack
size/offset = 24 */

```

```

/* 100 */ 0x8, /* FC_LONG */
0x0, /*
0 */

/* Procedure StockLevel */

/* 102 */ 0x33, /* FC_AUTO_HANDLE */
0x6c, /*
Old Flags: object, Oi2 */
/* 104 */ NdrFcLong( 0x0 ), /* 0 */
/* 108 */ NdrFcShort( 0x6 ), /* 6 */
/* 110 */ NdrFcShort( 0x1c ), /* x86 Stack
size/offset = 28 */
/* 112 */ NdrFcShort( 0x0 ), /* 0 */
/* 114 */ NdrFcShort( 0x8 ), /* 8 */
/* 116 */ 0x7, /* Oi2 Flags: srv must
size, clt must size, has return, */
0x3, /*
3 */

/* Parameter txn_in */

/* 118 */ NdrFcShort( 0x8b ), /* Flags: must size,
must free, in, by val, */
/* 120 */ NdrFcShort( 0x4 ), /* x86 Stack
size/offset = 4 */
/* 122 */ NdrFcShort( 0x3e2 ), /* Type
Offset=994 */

/* Parameter txn_out */

/* 124 */ NdrFcShort( 0x4113 ), /* Flags:
must size, must free, out, simple ref, srv alloc
size=16 */
/* 126 */ NdrFcShort( 0x14 ), /* x86 Stack
size/offset = 20 */
/* 128 */ NdrFcShort( 0x3f4 ), /* Type
Offset=1012 */

/* Return value */

/* 130 */ NdrFcShort( 0x70 ), /* Flags: out, return,
base type, */
/* 132 */ NdrFcShort( 0x18 ), /* x86 Stack
size/offset = 24 */
/* 134 */ 0x8, /* FC_LONG */
0x0, /*
0 */

/* Procedure OrderStatus */

/* 136 */ 0x33, /* FC_AUTO_HANDLE */
0x6c, /*
Old Flags: object, Oi2 */
/* 138 */ NdrFcLong( 0x0 ), /* 0 */
/* 142 */ NdrFcShort( 0x7 ), /* 7 */
/* 144 */ NdrFcShort( 0x1c ), /* x86 Stack
size/offset = 28 */
/* 146 */ NdrFcShort( 0x0 ), /* 0 */
/* 148 */ NdrFcShort( 0x8 ), /* 8 */

```



```

/* 150 */ 0x7,          /* Oi2 Flags:  srv must
size, clt must size, has return, */
                                0x3,          /*
3 */

        /* Parameter txn_in */

/* 152 */ NdrFcShort( 0x8b ), /* Flags:  must size,
must free, in, by val, */
/* 154 */ NdrFcShort( 0x4 ), /* x86 Stack
size/offset = 4 */
/* 156 */ NdrFcShort( 0x3e2 ), /* Type
Offset=994 */

        /* Parameter txn_out */

/* 158 */ NdrFcShort( 0x4113 ), /* Flags:
must size, must free, out, simple ref, srv alloc
size=16 */
/* 160 */ NdrFcShort( 0x14 ), /* x86 Stack
size/offset = 20 */
/* 162 */ NdrFcShort( 0x3f4 ), /* Type
Offset=1012 */

        /* Return value */

/* 164 */ NdrFcShort( 0x70 ), /* Flags:  out, return,
base type, */
/* 166 */ NdrFcShort( 0x18 ), /* x86 Stack
size/offset = 24 */
/* 168 */ 0x8,          /* FC_LONG */
                                0x0,          /*
0 */

        /* Procedure CallSetComplete */

/* 170 */ 0x33,          /* FC_AUTO_HANDLE */
                                0x6c,          /*
Old Flags:  object, Oi2 */
/* 172 */ NdrFcLong( 0x0 ), /* 0 */
/* 176 */ NdrFcShort( 0x8 ), /* 8 */
/* 178 */ NdrFcShort( 0x8 ), /* x86 Stack
size/offset = 8 */
/* 180 */ NdrFcShort( 0x0 ), /* 0 */
/* 182 */ NdrFcShort( 0x8 ), /* 8 */
/* 184 */ 0x4,          /* Oi2 Flags:  has
return, */
                                0x1,          /*
1 */

        /* Return value */

/* 186 */ NdrFcShort( 0x70 ), /* Flags:  out, return,
base type, */
/* 188 */ NdrFcShort( 0x4 ), /* x86 Stack
size/offset = 4 */
/* 190 */ 0x8,          /* FC_LONG */
                                0x0,          /*
0 */

                                0x0

```

```

}
};

static const MIDL_TYPE_FORMAT_STRING
_MIDL_TypeFormatString =
{
    0,
    {
        0 /*
        /* 2 */
        FC_UP /*
        /* 4 */ NdrFcShort( 0x3ca ), /* Offset=
        970 (974) */
        /* 6 */
        FC_NON_ENCAPSULATED_UNION /*
        /* 9,
        /*
        FC_ULONG /*
        /* 8 */ 0x7,          /* Corr desc: FC_USHORT
        */
        0x0,          /*
        /*
        /* 10 */ NdrFcShort( 0xffff8 ), /* -8 */
        /* 12 */ NdrFcShort( 0x2 ), /* Offset= 2 (14) */
        /* 14 */ NdrFcShort( 0x10 ), /* 16 */
        /* 16 */ NdrFcShort( 0x2f ), /* 47 */
        /* 18 */ NdrFcLong( 0x14 ), /* 20 */
        /* 22 */ NdrFcShort( 0x800b ), /* Simple arm
        type: FC_HYPER */
        /* 24 */ NdrFcLong( 0x3 ), /* 3 */
        /* 28 */ NdrFcShort( 0x8008 ), /* Simple arm
        type: FC_LONG */
        /* 30 */ NdrFcLong( 0x11 ), /* 17 */
        /* 34 */ NdrFcShort( 0x8001 ), /* Simple arm
        type: FC_BYTE */
        /* 36 */ NdrFcLong( 0x2 ), /* 2 */
        /* 40 */ NdrFcShort( 0x8006 ), /* Simple arm
        type: FC_SHORT */
        /* 42 */ NdrFcLong( 0x4 ), /* 4 */
        /* 46 */ NdrFcShort( 0x800a ), /* Simple arm
        type: FC_FLOAT */
        /* 48 */ NdrFcLong( 0x5 ), /* 5 */
        /* 52 */ NdrFcShort( 0x800c ), /* Simple arm
        type: FC_DOUBLE */
        /* 54 */ NdrFcLong( 0xb ), /* 11 */
        /* 58 */ NdrFcShort( 0x8006 ), /* Simple arm
        type: FC_SHORT */
        /* 60 */ NdrFcLong( 0xa ), /* 10 */
        /* 64 */ NdrFcShort( 0x8008 ), /* Simple arm
        type: FC_LONG */
        /* 66 */ NdrFcLong( 0x6 ), /* 6 */
        /* 70 */ NdrFcShort( 0xe8 ), /* Offset= 232 (302) */
        /* 72 */ NdrFcLong( 0x7 ), /* 7 */
        /* 76 */ NdrFcShort( 0x800c ), /* Simple arm
        type: FC_DOUBLE */
        /* 78 */ NdrFcLong( 0x8 ), /* 8 */
        /* 82 */ NdrFcShort( 0xe2 ), /* Offset= 226 (308) */
        /* 84 */ NdrFcLong( 0xd ), /* 13 */
        /* 88 */ NdrFcShort( 0xf4 ), /* Offset= 244 (332) */

```

```

/* 90 */ NdrFcLong( 0x9 ), /* 9 */
/* 94 */ NdrFcShort( 0x100 ), /* Offset=
256 (350) */
/* 96 */ NdrFcLong( 0x2000 ), /* 8192 */
/* 100 */ NdrFcShort( 0x10c ), /* Offset=
268 (368) */
/* 102 */ NdrFcLong( 0x24 ), /* 36 */
/* 106 */ NdrFcShort( 0x31a ), /* Offset=
794 (900) */
/* 108 */ NdrFcLong( 0x4024 ), /* 16420 */
/* 112 */ NdrFcShort( 0x314 ), /* Offset=
788 (900) */
/* 114 */ NdrFcLong( 0x4011 ), /* 16401 */
/* 118 */ NdrFcShort( 0x312 ), /* Offset=
786 (904) */
/* 120 */ NdrFcLong( 0x4002 ), /* 16386 */
/* 124 */ NdrFcShort( 0x310 ), /* Offset=
784 (908) */
/* 126 */ NdrFcLong( 0x4003 ), /* 16387 */
/* 130 */ NdrFcShort( 0x30e ), /* Offset=
782 (912) */
/* 132 */ NdrFcLong( 0x4014 ), /* 16404 */
/* 136 */ NdrFcShort( 0x30c ), /* Offset=
780 (916) */
/* 138 */ NdrFcLong( 0x4004 ), /* 16388 */
/* 142 */ NdrFcShort( 0x30a ), /* Offset=
778 (920) */
/* 144 */ NdrFcLong( 0x4005 ), /* 16389 */
/* 148 */ NdrFcShort( 0x308 ), /* Offset=
776 (924) */
/* 150 */ NdrFcLong( 0x400b ), /* 16395 */
/* 154 */ NdrFcShort( 0x2f2 ), /* Offset=
754 (908) */
/* 156 */ NdrFcLong( 0x400a ), /* 16394 */
/* 160 */ NdrFcShort( 0x2f0 ), /* Offset=
752 (912) */
/* 162 */ NdrFcLong( 0x4006 ), /* 16390 */
/* 166 */ NdrFcShort( 0x2fa ), /* Offset=
762 (928) */
/* 168 */ NdrFcLong( 0x4007 ), /* 16391 */
/* 172 */ NdrFcShort( 0x2f0 ), /* Offset=
752 (924) */
/* 174 */ NdrFcLong( 0x4008 ), /* 16392 */
/* 178 */ NdrFcShort( 0x2f2 ), /* Offset=
754 (932) */
/* 180 */ NdrFcLong( 0x400d ), /* 16397 */
/* 184 */ NdrFcShort( 0x2f0 ), /* Offset=
752 (936) */
/* 186 */ NdrFcLong( 0x4009 ), /* 16393 */
/* 190 */ NdrFcShort( 0x2ee ), /* Offset=
750 (940) */
/* 192 */ NdrFcLong( 0x6000 ), /* 24576 */
/* 196 */ NdrFcShort( 0x2ec ), /* Offset=
748 (944) */
/* 198 */ NdrFcLong( 0x400c ), /* 16396 */
/* 202 */ NdrFcShort( 0x2ea ), /* Offset=
746 (948) */
/* 204 */ NdrFcLong( 0x10 ), /* 16 */
/* 208 */ NdrFcShort( 0x8002 ), /* Simple arm
type: FC_CHAR */
/* 210 */ NdrFcLong( 0x12 ), /* 18 */

```

```

/* 214 */ NdrFcShort( 0x8006 ), /* Simple arm
type: FC_SHORT */
/* 216 */ NdrFcLong( 0x13 ), /* 19 */
/* 220 */ NdrFcShort( 0x8008 ), /* Simple arm
type: FC_LONG */
/* 222 */ NdrFcLong( 0x15 ), /* 21 */
/* 226 */ NdrFcShort( 0x800b ), /* Simple arm
type: FC_HYPER */
/* 228 */ NdrFcLong( 0x16 ), /* 22 */
/* 232 */ NdrFcShort( 0x8008 ), /* Simple arm
type: FC_LONG */
/* 234 */ NdrFcLong( 0x17 ), /* 23 */
/* 238 */ NdrFcShort( 0x8008 ), /* Simple arm
type: FC_LONG */
/* 240 */ NdrFcLong( 0xe ), /* 14 */
/* 244 */ NdrFcShort( 0x2c8 ), /* Offset=
712 (956) */
/* 246 */ NdrFcLong( 0x400e ), /* 16398 */
/* 250 */ NdrFcShort( 0x2cc ), /* Offset=
716 (966) */
/* 252 */ NdrFcLong( 0x4010 ), /* 16400 */
/* 256 */ NdrFcShort( 0x2ca ), /* Offset=
714 (970) */
/* 258 */ NdrFcLong( 0x4012 ), /* 16402 */
/* 262 */ NdrFcShort( 0x286 ), /* Offset=
646 (908) */
/* 264 */ NdrFcLong( 0x4013 ), /* 16403 */
/* 268 */ NdrFcShort( 0x284 ), /* Offset=
644 (912) */
/* 270 */ NdrFcLong( 0x4015 ), /* 16405 */
/* 274 */ NdrFcShort( 0x282 ), /* Offset=
642 (916) */
/* 276 */ NdrFcLong( 0x4016 ), /* 16406 */
/* 280 */ NdrFcShort( 0x278 ), /* Offset=
632 (912) */
/* 282 */ NdrFcLong( 0x4017 ), /* 16407 */
/* 286 */ NdrFcShort( 0x272 ), /* Offset=
626 (912) */
/* 288 */ NdrFcLong( 0x0 ), /* 0 */
/* 292 */ NdrFcShort( 0x0 ), /* Offset= 0 (292) */
/* 294 */ NdrFcLong( 0x1 ), /* 1 */
/* 298 */ NdrFcShort( 0x0 ), /* Offset= 0 (298) */
/* 300 */ NdrFcShort( 0xffffffff ), /* Offset= -1
(299) */
/* 302 */
FC_STRUCT */
/* 304 */ NdrFcShort( 0x8 ), /* 8 */
/* 306 */ 0xb, /* FC_HYPER */
FC_END */
/* 308 */
FC_UP */
/* 310 */ NdrFcShort( 0xc ), /* Offset= 12 (322) */
/* 312 */
FC_CARRAY */
0x15, /*
0x7, /*
7 */
/* 304 */ NdrFcShort( 0x8 ), /* 8 */
/* 306 */ 0xb, /* FC_HYPER */
FC_END */
/* 308 */
FC_UP */
/* 310 */ NdrFcShort( 0xc ), /* Offset= 12 (322) */
/* 312 */
FC_CARRAY */
0x15, /*
0x7, /*
7 */
/* 304 */ NdrFcShort( 0x8 ), /* 8 */
/* 306 */ 0xb, /* FC_HYPER */
FC_END */
/* 308 */
FC_UP */
/* 310 */ NdrFcShort( 0xc ), /* Offset= 12 (322) */
/* 312 */
FC_CARRAY */
0x1b, /*

```

```

1 */
/* 314 */ NdrFcShort( 0x2 ), /* 2 */
/* 316 */ 0x9, /* Corr desc: FC_ULONG
*/
0x0, /*
*/
/* 318 */ NdrFcShort( 0xffffc ), /* -4 */
/* 320 */ 0x6, /* FC_SHORT */
FC_END */
/* 322 */
FC_CSTRUCT */
0x17, /*
0x3, /*
3 */
/* 324 */ NdrFcShort( 0x8 ), /* 8 */
/* 326 */ NdrFcShort( 0xffffffff2 ), /* Offset= -
14 (312) */
/* 328 */ 0x8, /* FC_LONG */
0x8, /*
FC_LONG */
/* 330 */ 0x5c, /* FC_PAD */
FC_END */
/* 332 */
FC_IP */
0x2f, /*
0x5a, /*
FC_CONSTANT_IID */
/* 334 */ NdrFcLong( 0x0 ), /* 0 */
/* 338 */ NdrFcShort( 0x0 ), /* 0 */
/* 340 */ NdrFcShort( 0x0 ), /* 0 */
/* 342 */ 0xc0, /* 192 */
0x0, /*
0 */
/* 344 */ 0x0, /* 0 */
0x0, /*
0 */
/* 346 */ 0x0, /* 0 */
0x0, /*
0 */
/* 348 */ 0x0, /* 0 */
0x46, /*
70 */
/* 350 */
0x2f, /*
0x5a, /*
FC_CONSTANT_IID */
/* 352 */ NdrFcLong( 0x20400 ), /* 132096 */
/* 356 */ NdrFcShort( 0x0 ), /* 0 */
/* 358 */ NdrFcShort( 0x0 ), /* 0 */
/* 360 */ 0xc0, /* 192 */
0x0, /*
0 */
/* 362 */ 0x0, /* 0 */
0x0, /*
0 */
/* 364 */ 0x0, /* 0 */

```

```

0x0, /*
0 */
/* 366 */ 0x0, /* 0 */
0x46, /*
70 */
/* 368 */
FC_UP [pointer_deref] */
/* 370 */ NdrFcShort( 0x2 ), /* Offset= 2 (372) */
/* 372 */
FC_UP */
/* 374 */ NdrFcShort( 0x1fc ), /* Offset=
508 (882) */
/* 376 */
FC_ENCAPSULATED_UNION */
0x2a, /*
0x49, /*
73 */
/* 378 */ NdrFcShort( 0x18 ), /* 24 */
/* 380 */ NdrFcShort( 0xa ), /* 10 */
/* 382 */ NdrFcLong( 0x8 ), /* 8 */
/* 386 */ NdrFcShort( 0x58 ), /* Offset= 88 (474) */
/* 388 */ NdrFcLong( 0xd ), /* 13 */
/* 392 */ NdrFcShort( 0x78 ), /* Offset= 120 (512) */
/* 394 */ NdrFcLong( 0x9 ), /* 9 */
/* 398 */ NdrFcShort( 0x94 ), /* Offset= 148 (546) */
/* 400 */ NdrFcLong( 0xc ), /* 12 */
/* 404 */ NdrFcShort( 0xbc ), /* Offset= 188 (592) */
/* 406 */ NdrFcLong( 0x24 ), /* 36 */
/* 410 */ NdrFcShort( 0x114 ), /* Offset=
276 (686) */
/* 412 */ NdrFcLong( 0x800d ), /* 32781 */
/* 416 */ NdrFcShort( 0x130 ), /* Offset=
304 (720) */
/* 418 */ NdrFcLong( 0x10 ), /* 16 */
/* 422 */ NdrFcShort( 0x148 ), /* Offset=
328 (750) */
/* 424 */ NdrFcLong( 0x2 ), /* 2 */
/* 428 */ NdrFcShort( 0x160 ), /* Offset=
352 (780) */
/* 430 */ NdrFcLong( 0x3 ), /* 3 */
/* 434 */ NdrFcShort( 0x178 ), /* Offset=
376 (810) */
/* 436 */ NdrFcLong( 0x14 ), /* 20 */
/* 440 */ NdrFcShort( 0x190 ), /* Offset=
400 (840) */
/* 442 */ NdrFcShort( 0xffffffff ), /* Offset= -1
(441) */
/* 444 */
FC_CARRAY */
0x1b, /*
0x3, /*
3 */
/* 446 */ NdrFcShort( 0x4 ), /* 4 */
/* 448 */ 0x19, /* Corr desc: field
pointer, FC_ULONG */
0x0, /*
*/
/* 450 */ NdrFcShort( 0x0 ), /* 0 */
/* 452 */

```

<pre> FC_PP */ 0x4b, /* FC_PAD */ /* 454 */ 0x5c, /* FC_VARIABLE_REPEAT */ 0x48, /* 0x49, /* FC_FIXED_OFFSET */ /* 456 */ NdrFcShort(0x4), /* 4 */ /* 458 */ NdrFcShort(0x0), /* 0 */ /* 460 */ NdrFcShort(0x1), /* 1 */ /* 462 */ NdrFcShort(0x0), /* 0 */ /* 464 */ NdrFcShort(0x0), /* 0 */ /* 466 */ 0x12, 0x0, /* FC_UP */ /* 468 */ NdrFcShort(0xfffff6e), /* Offset= - 146 (322) */ /* 470 */ FC_END */ 0x5b, /* FC_LONG */ /* 472 */ 0x5c, /* FC_PAD */ 0x5b, /* FC_END */ /* 474 */ FC_PSTRUCT */ 0x16, /* 0x3, /* 3 */ /* 476 */ NdrFcShort(0x8), /* 8 */ /* 478 */ 0x4b, /* FC_PP */ 0x5c, /* FC_PAD */ /* 480 */ 0x46, /* FC_NO_REPEAT */ 0x5c, /* FC_PAD */ /* 482 */ NdrFcShort(0x4), /* 4 */ /* 484 */ NdrFcShort(0x4), /* 4 */ /* 486 */ 0x11, 0x0, /* FC_RP */ /* 488 */ NdrFcShort(0xfffffd4), /* Offset= - 44 (444) */ /* 490 */ FC_END */ 0x5b, /* FC_LONG */ /* 492 */ 0x8, /* FC_LONG */ 0x5b, /* FC_END */ /* 494 */ FC_BOGUS_ARRAY */ 0x21, /* 0x3, /* 3 */ </pre>	<pre> /* 496 */ NdrFcShort(0x0), /* 0 */ /* 498 */ 0x19, /* Corr desc: field pointer, FC_ULONG */ 0x0, /* /* /* 500 */ NdrFcShort(0x0), /* 0 */ /* 502 */ NdrFcLong(0xffffffff), /* -1 */ /* 506 */ 0x4c, /* FC_EMBEDDED_COMPLEX */ 0x0, /* 0 */ /* 508 */ NdrFcShort(0xfffff50), /* Offset= - 176 (332) */ /* 510 */ 0x5c, /* FC_PAD */ 0x5b, /* FC_END */ /* 512 */ FC_BOGUS_STRUCT */ 0x1a, /* 0x3, /* 3 */ /* 514 */ NdrFcShort(0x8), /* 8 */ /* 516 */ NdrFcShort(0x0), /* 0 */ /* 518 */ NdrFcShort(0x6), /* Offset= 6 (524) */ /* 520 */ 0x8, /* FC_LONG */ 0x36, /* FC_POINTER */ /* 522 */ 0x5c, /* FC_PAD */ 0x5b, /* FC_END */ /* 524 */ 0x11, 0x0, /* FC_RP */ /* 526 */ NdrFcShort(0xfffffe0), /* Offset= - 32 (494) */ /* 528 */ FC_BOGUS_ARRAY */ 0x21, /* 0x3, /* 3 */ /* 530 */ NdrFcShort(0x0), /* 0 */ /* 532 */ 0x19, /* Corr desc: field pointer, FC_ULONG */ 0x0, /* /* /* 534 */ NdrFcShort(0x0), /* 0 */ /* 536 */ NdrFcLong(0xffffffff), /* -1 */ /* 540 */ 0x4c, /* FC_EMBEDDED_COMPLEX */ 0x0, /* 0 */ /* 542 */ NdrFcShort(0xfffff40), /* Offset= - 192 (350) */ /* 544 */ 0x5c, /* FC_PAD */ 0x5b, /* FC_END */ /* 546 */ FC_BOGUS_STRUCT */ 0x1a, /* 0x3, /* 3 */ </pre>	<pre> /* 548 */ NdrFcShort(0x8), /* 8 */ /* 550 */ NdrFcShort(0x0), /* 0 */ /* 552 */ NdrFcShort(0x6), /* Offset= 6 (558) */ /* 554 */ 0x8, /* FC_LONG */ 0x36, /* FC_POINTER */ /* 556 */ 0x5c, /* FC_PAD */ 0x5b, /* FC_END */ /* 558 */ 0x11, 0x0, /* FC_RP */ /* 560 */ NdrFcShort(0xfffffe0), /* Offset= - 32 (528) */ /* 562 */ 0x1b, /* FC_CARRAY */ 0x3, /* 3 */ /* 564 */ NdrFcShort(0x4), /* 4 */ /* 566 */ 0x19, /* Corr desc: field pointer, FC_ULONG */ 0x0, /* /* /* 568 */ NdrFcShort(0x0), /* 0 */ /* 570 */ 0x4b, /* FC_PP */ 0x5c, /* FC_PAD */ /* 572 */ 0x48, /* FC_VARIABLE_REPEAT */ 0x49, /* FC_FIXED_OFFSET */ /* 574 */ NdrFcShort(0x4), /* 4 */ /* 576 */ NdrFcShort(0x0), /* 0 */ /* 578 */ NdrFcShort(0x1), /* 1 */ /* 580 */ NdrFcShort(0x0), /* 0 */ /* 582 */ NdrFcShort(0x0), /* 0 */ /* 584 */ 0x12, 0x0, /* FC_UP */ /* 586 */ NdrFcShort(0x184), /* Offset= 388 (974) */ /* 588 */ 0x5b, /* FC_END */ 0x8, /* FC_LONG */ /* 590 */ 0x5c, /* FC_PAD */ 0x5b, /* FC_END */ /* 592 */ 0x1a, /* FC_BOGUS_STRUCT */ 0x3, /* 3 */ /* 594 */ NdrFcShort(0x8), /* 8 */ /* 596 */ NdrFcShort(0x0), /* 0 */ /* 598 */ NdrFcShort(0x6), /* Offset= 6 (604) */ /* 600 */ 0x8, /* FC_LONG */ </pre>
--	--	---

```

0x36, /*
FC_POINTER */
/* 602 */ 0x5c, /* FC_PAD */
0x5b, /*
FC_END */
/* 604 */
0x11, 0x0, /*
FC_RP */
/* 606 */ NdrFcShort( 0xfffffd4 ), /* Offset= -
44 (562) */
/* 608 */
0x2f, /*
FC_IP */
0x5a, /*
FC_CONSTANT_IID */
/* 610 */ NdrFcLong( 0x2f ), /* 47 */
/* 614 */ NdrFcShort( 0x0 ), /* 0 */
/* 616 */ NdrFcShort( 0x0 ), /* 0 */
/* 618 */ 0xc0, /* 192 */
0x0, /*
0 */
/* 620 */ 0x0, /* 0 */
0x0, /*
0 */
/* 622 */ 0x0, /* 0 */
0x0, /*
0 */
/* 624 */ 0x0, /* 0 */
0x46, /*
70 */
/* 626 */
0x1b, /*
FC_CARRAY */
0x0, /*
0 */
/* 628 */ NdrFcShort( 0x1 ), /* 1 */
/* 630 */ 0x19, /* Corr desc: field
pointer, FC_ULONG */
0x0, /*
*/
/* 632 */ NdrFcShort( 0x4 ), /* 4 */
/* 634 */ 0x1, /* FC_BYTE */
0x5b, /*
FC_END */
/* 636 */
0x1a, /*
FC_BOGUS_STRUCT */
0x3, /*
3 */
/* 638 */ NdrFcShort( 0x10 ), /* 16 */
/* 640 */ NdrFcShort( 0x0 ), /* 0 */
/* 642 */ NdrFcShort( 0xa ), /* Offset= 10 (652) */
/* 644 */ 0x8, /* FC_LONG */
0x8, /*
FC_LONG */
/* 646 */ 0x4c, /* FC_EMBEDDED_COMPLEX
*/
0x0, /*
0 */
/* 648 */ NdrFcShort( 0xfffffd8 ), /* Offset= -
40 (608) */

```

```

/* 650 */ 0x36, /* FC_POINTER */
0x5b, /*
FC_END */
/* 652 */
0x12, 0x0, /*
FC_UP */
/* 654 */ NdrFcShort( 0xfffffe4 ), /* Offset= -
28 (626) */
/* 656 */
0x1b, /*
FC_CARRAY */
0x3, /*
3 */
/* 658 */ NdrFcShort( 0x4 ), /* 4 */
/* 660 */ 0x19, /* Corr desc: field
pointer, FC_ULONG */
0x0, /*
*/
/* 662 */ NdrFcShort( 0x0 ), /* 0 */
/* 664 */
0x4b, /*
FC_PP */
0x5c, /*
FC_PAD */
/* 666 */
0x48, /*
FC_VARIABLE_REPEAT */
0x49, /*
FC_FIXED_OFFSET */
/* 668 */ NdrFcShort( 0x4 ), /* 4 */
/* 670 */ NdrFcShort( 0x0 ), /* 0 */
/* 672 */ NdrFcShort( 0x1 ), /* 1 */
/* 674 */ NdrFcShort( 0x0 ), /* 0 */
/* 676 */ NdrFcShort( 0x0 ), /* 0 */
/* 678 */ 0x12, 0x0, /* FC_UP */
/* 680 */ NdrFcShort( 0xfffffd4 ), /* Offset= -
44 (636) */
/* 682 */
0x5b, /*
FC_END */
0x8, /*
FC_LONG */
/* 684 */ 0x5c, /* FC_PAD */
0x5b, /*
FC_END */
/* 686 */
0x1a, /*
FC_BOGUS_STRUCT */
0x3, /*
3 */
/* 688 */ NdrFcShort( 0x8 ), /* 8 */
/* 690 */ NdrFcShort( 0x0 ), /* 0 */
/* 692 */ NdrFcShort( 0x6 ), /* Offset= 6 (698) */
/* 694 */ 0x8, /* FC_LONG */
0x36, /*
FC_POINTER */
/* 696 */ 0x5c, /* FC_PAD */
0x5b, /*
FC_END */
/* 698 */

```

```

0x11, 0x0, /*
FC_RP */
/* 700 */ NdrFcShort( 0xfffffd4 ), /* Offset= -
44 (656) */
/* 702 */
0x1d, /*
FC_SMPARRAY */
0x0, /*
0 */
/* 704 */ NdrFcShort( 0x8 ), /* 8 */
/* 706 */ 0x1, /* FC_BYTE */
0x5b, /*
FC_END */
/* 708 */
0x15, /*
FC_STRUCT */
0x3, /*
3 */
/* 710 */ NdrFcShort( 0x10 ), /* 16 */
/* 712 */ 0x8, /* FC_LONG */
0x6, /*
FC_SHORT */
/* 714 */ 0x6, /* FC_SHORT */
0x4c, /*
FC_EMBEDDED_COMPLEX */
/* 716 */ 0x0, /* 0 */
NdrFcShort( 0xfffff1 ), /* Offset= -15 (702) */
0x5b, /*
FC_END */
/* 720 */
0x1a, /*
FC_BOGUS_STRUCT */
0x3, /*
3 */
/* 722 */ NdrFcShort( 0x18 ), /* 24 */
/* 724 */ NdrFcShort( 0x0 ), /* 0 */
/* 726 */ NdrFcShort( 0xa ), /* Offset= 10 (736) */
/* 728 */ 0x8, /* FC_LONG */
0x36, /*
FC_POINTER */
/* 730 */ 0x4c, /* FC_EMBEDDED_COMPLEX
*/
0x0, /*
0 */
/* 732 */ NdrFcShort( 0xfffffe8 ), /* Offset= -
24 (708) */
/* 734 */ 0x5c, /* FC_PAD */
0x5b, /*
FC_END */
/* 736 */
0x11, 0x0, /*
FC_RP */
/* 738 */ NdrFcShort( 0xfffff0c ), /* Offset= -
244 (494) */
/* 740 */
0x1b, /*
FC_CARRAY */
0x0, /*
0 */
/* 742 */ NdrFcShort( 0x1 ), /* 1 */

```

```

/* 744 */ 0x19, /* Corr desc: field
pointer, FC_ULONG */
0x0, /*
*/
/* 746 */ NdrFcShort( 0x0 ), /* 0 */
/* 748 */ 0x1, /* FC_BYTE */
0x5b, /*
FC_END */
/* 750 */
FC_PSTRUCT */
0x16, /*
3 */
/* 752 */ NdrFcShort( 0x8 ), /* 8 */
/* 754 */
0x4b, /*
FC_PP */
0x5c, /*
FC_PAD */
/* 756 */
0x46, /*
FC_NO_REPEAT */
0x5c, /*
FC_PAD */
/* 758 */ NdrFcShort( 0x4 ), /* 4 */
/* 760 */ NdrFcShort( 0x4 ), /* 4 */
/* 762 */ 0x12, 0x0, /* FC_UP */
/* 764 */ NdrFcShort( 0xffffffe8 ), /* Offset= -
24 (740) */
/* 766 */
0x5b, /*
FC_END */
0x8, /*
FC_LONG */
/* 768 */ 0x8, /* FC_LONG */
0x5b, /*
FC_END */
/* 770 */
0x1b, /*
FC_CARRAY */
0x1, /*
1 */
/* 772 */ NdrFcShort( 0x2 ), /* 2 */
/* 774 */ 0x19, /* Corr desc: field
pointer, FC_ULONG */
0x0, /*
*/
/* 776 */ NdrFcShort( 0x0 ), /* 0 */
/* 778 */ 0x6, /* FC_SHORT */
0x5b, /*
FC_END */
/* 780 */
0x16, /*
FC_PSTRUCT */
0x3, /*
3 */
/* 782 */ NdrFcShort( 0x8 ), /* 8 */
/* 784 */
0x4b, /*
FC_PP */

```

```

FC_PAD */
/* 786 */
0x5c, /*
FC_NO_REPEAT */
0x46, /*
FC_PAD */
/* 788 */ NdrFcShort( 0x4 ), /* 4 */
/* 790 */ NdrFcShort( 0x4 ), /* 4 */
/* 792 */ 0x12, 0x0, /* FC_UP */
/* 794 */ NdrFcShort( 0xffffffe8 ), /* Offset= -
24 (770) */
/* 796 */
0x5b, /*
FC_END */
0x8, /*
FC_LONG */
/* 798 */ 0x8, /* FC_LONG */
0x5b, /*
FC_END */
/* 800 */
0x1b, /*
FC_CARRAY */
0x3, /*
3 */
/* 802 */ NdrFcShort( 0x4 ), /* 4 */
/* 804 */ 0x19, /* Corr desc: field
pointer, FC_ULONG */
0x0, /*
*/
/* 806 */ NdrFcShort( 0x0 ), /* 0 */
/* 808 */ 0x8, /* FC_LONG */
0x5b, /*
FC_END */
/* 810 */
0x16, /*
FC_PSTRUCT */
0x3, /*
3 */
/* 812 */ NdrFcShort( 0x8 ), /* 8 */
/* 814 */
0x4b, /*
FC_PP */
0x5c, /*
FC_PAD */
/* 816 */
0x46, /*
FC_NO_REPEAT */
0x5c, /*
FC_PAD */
/* 818 */ NdrFcShort( 0x4 ), /* 4 */
/* 820 */ NdrFcShort( 0x4 ), /* 4 */
/* 822 */ 0x12, 0x0, /* FC_UP */
/* 824 */ NdrFcShort( 0xffffffe8 ), /* Offset= -
24 (800) */
/* 826 */
0x5b, /*
FC_END */

```

```

0x8, /*
FC_LONG */
/* 828 */ 0x8, /* FC_LONG */
0x5b, /*
FC_END */
/* 830 */
0x1b, /*
FC_CARRAY */
0x7, /*
7 */
/* 832 */ NdrFcShort( 0x8 ), /* 8 */
/* 834 */ 0x19, /* Corr desc: field
pointer, FC_ULONG */
0x0, /*
*/
/* 836 */ NdrFcShort( 0x0 ), /* 0 */
/* 838 */ 0xb, /* FC_HYPER */
0x5b, /*
FC_END */
/* 840 */
0x16, /*
FC_PSTRUCT */
0x3, /*
3 */
/* 842 */ NdrFcShort( 0x8 ), /* 8 */
/* 844 */
0x4b, /*
FC_PP */
0x5c, /*
FC_PAD */
/* 846 */
0x46, /*
FC_NO_REPEAT */
0x5c, /*
FC_PAD */
/* 848 */ NdrFcShort( 0x4 ), /* 4 */
/* 850 */ NdrFcShort( 0x4 ), /* 4 */
/* 852 */ 0x12, 0x0, /* FC_UP */
/* 854 */ NdrFcShort( 0xffffffe8 ), /* Offset= -
24 (830) */
/* 856 */
0x5b, /*
FC_END */
0x8, /*
FC_LONG */
/* 858 */ 0x8, /* FC_LONG */
0x5b, /*
FC_END */
/* 860 */
0x15, /*
FC_STRUCT */
0x3, /*
3 */
/* 862 */ NdrFcShort( 0x8 ), /* 8 */
/* 864 */ 0x8, /* FC_LONG */
0x8, /*
FC_LONG */
/* 866 */ 0x5c, /* FC_PAD */
0x5b, /*
FC_END */

```

```

/* 868 */
FC_CARRAY */
3 */
/* 870 */ NdrFcShort( 0x8 ), /* 8 */
/* 872 */ 0x7, /* Corr desc: FC_USHORT */
0x0, /*
/* 874 */ NdrFcShort( 0xffd8 ), /* -40 */
/* 876 */ 0x4c, /* FC_EMBEDDED_COMPLEX */
0x0, /*
0 */
/* 878 */ NdrFcShort( 0xfffffee ), /* Offset= -
18 (860) */
/* 880 */ 0x5c, /* FC_PAD */
FC_END */
/* 882 */
FC_BOGUS_STRUCT */
3 */
/* 884 */ NdrFcShort( 0x28 ), /* 40 */
/* 886 */ NdrFcShort( 0xfffffee ), /* Offset= -
18 (868) */
/* 888 */ NdrFcShort( 0x0 ), /* Offset= 0 (888) */
/* 890 */ 0x6, /* FC_SHORT */
FC_SHORT */
/* 892 */ 0x8, /* FC_LONG */
FC_LONG */
/* 894 */ 0x4c, /* FC_EMBEDDED_COMPLEX */
0x0, /*
0 */
/* 896 */ NdrFcShort( 0xffffdf8 ), /* Offset= -
520 (376) */
/* 898 */ 0x5c, /* FC_PAD */
FC_END */
/* 900 */
FC_UP */
/* 902 */ NdrFcShort( 0xffffef6 ), /* Offset= -
266 (636) */
/* 904 */
FC_UP [simple_pointer] */
/* 906 */ 0x1, /* FC_BYTE */
FC_PAD */
/* 908 */
FC_UP [simple_pointer] */
/* 910 */ 0x6, /* FC_SHORT */
FC_PAD */

```

```

/* 912 */
FC_UP [simple_pointer] */
/* 914 */ 0x8, /* FC_LONG */
FC_PAD */
/* 916 */
FC_UP [simple_pointer] */
/* 918 */ 0xb, /* FC_HYPER */
FC_PAD */
/* 920 */
FC_UP [simple_pointer] */
/* 922 */ 0xa, /* FC_FLOAT */
FC_PAD */
/* 924 */
FC_UP [simple_pointer] */
/* 926 */ 0xc, /* FC_DOUBLE */
FC_PAD */
/* 928 */
FC_UP */
/* 930 */ NdrFcShort( 0xffffd8c ), /* Offset= -
628 (302) */
/* 932 */
FC_UP [pointer_deref] */
/* 934 */ NdrFcShort( 0xffffd8e ), /* Offset= -
626 (308) */
/* 936 */
FC_UP [pointer_deref] */
/* 938 */ NdrFcShort( 0xffffda2 ), /* Offset= -
606 (332) */
/* 940 */
FC_UP [pointer_deref] */
/* 942 */ NdrFcShort( 0xffffdb0 ), /* Offset= -
592 (350) */
/* 944 */
FC_UP [pointer_deref] */
/* 946 */ NdrFcShort( 0xffffdbe ), /* Offset= -
578 (368) */
/* 948 */
FC_UP [pointer_deref] */
/* 950 */ NdrFcShort( 0x2 ), /* Offset= 2 (952) */
/* 952 */
FC_UP */
/* 954 */ NdrFcShort( 0x14 ), /* Offset= 20 (974) */
/* 956 */
FC_STRUCT */

```

```

7 */
/* 958 */ NdrFcShort( 0x10 ), /* 16 */
/* 960 */ 0x6, /* FC_SHORT */
FC_BYTE */
/* 962 */ 0x1, /* FC_BYTE */
FC_LONG */
/* 964 */ 0xb, /* FC_HYPER */
FC_END */
/* 966 */
FC_UP */
/* 968 */ NdrFcShort( 0xfffff4 ), /* Offset= -
12 (956) */
/* 970 */
FC_UP [simple_pointer] */
/* 972 */ 0x2, /* FC_CHAR */
FC_PAD */
/* 974 */
FC_BOGUS_STRUCT */
7 */
/* 976 */ NdrFcShort( 0x20 ), /* 32 */
/* 978 */ NdrFcShort( 0x0 ), /* 0 */
/* 980 */ NdrFcShort( 0x0 ), /* Offset= 0 (980) */
/* 982 */ 0x8, /* FC_LONG */
FC_LONG */
/* 984 */ 0x6, /* FC_SHORT */
FC_SHORT */
/* 986 */ 0x6, /* FC_SHORT */
FC_SHORT */
/* 988 */ 0x4c, /* FC_EMBEDDED_COMPLEX */
0x0, /*
0 */
/* 990 */ NdrFcShort( 0xffffc28 ), /* Offset= -
984 (6) */
/* 992 */ 0x5c, /* FC_PAD */
FC_END */
/* 994 */ 0xb4, /* FC_USER_MARSHAL */
131 */
/* 996 */ NdrFcShort( 0x0 ), /* 0 */
/* 998 */ NdrFcShort( 0x10 ), /* 16 */
/* 1000 */ NdrFcShort( 0x0 ), /* 0 */
/* 1002 */ NdrFcShort( 0xffffc18 ), /*
Offset= -1000 (2) */
/* 1004 */
FC_RP [allocated_on_stack] */

```

```

/* 1006 */      NdrFcShort( 0x6 ), /* Offset= 6
(1012) */
/* 1008 */
                                0x13, 0x0, /*
FC_OP */
/* 1010 */      NdrFcShort( 0xfffffcdc ), /*
Offset= -36 (974) */
/* 1012 */      0xb4, /*
FC_USER_MARSHAL */
                                0x83, /*
131 */
/* 1014 */      NdrFcShort( 0x0 ), /* 0 */
/* 1016 */      NdrFcShort( 0x10 ), /* 16 */
/* 1018 */      NdrFcShort( 0x0 ), /* 0 */
/* 1020 */      NdrFcShort( 0xfffffff4 ), /*
Offset= -12 (1008) */
                                0x0
    }
};

static const USER_MARSHAL_ROUTINE_QUADRUPLE
UserMarshalRoutines[ WIRE_MARSHAL_TABLE_SIZE ] =
{
    {
        VARIANT_UserSize
        ,VARIANT_UserMarshal
        ,VARIANT_UserUnmarshal
        ,VARIANT_UserFree
    }
};

/* Standard interface: __MIDL_itf_tpcc_com_ps_0000,
ver. 0.0,

GUID={0x00000000,0x0000,0x0000,{0x00,0x00,0x00,0x00,0
x00,0x00,0x00,0x00}} */

/* Object interface: IUnknown, ver. 0.0,

GUID={0x00000000,0x0000,0x0000,{0xC0,0x00,0x00,0x00,0
x00,0x00,0x00,0x46}} */

/* Object interface: ITPCC, ver. 0.0,

GUID={0xFEE6AA2,0x84B1,0x11d2,{0xBA,0x47,0x00,0xC0,0
x4F,0xBF,0xE0,0x8B}} */

#pragma code_seg(".orpc")
static const unsigned short
ITPCC_FormatStringOffsetTable[] =
{
    0,
    34,
    68,

```

```

102,
136,
170
};

static const MIDL_STUBLESS_PROXY_INFO ITPCC_ProxyInfo
=
{
    &Object_StubDesc,
    _MIDL_ProcFormatString.Format,
    &ITPCC_FormatStringOffsetTable[-3],
    0,
    0,
    0
};

static const MIDL_SERVER_INFO ITPCC_ServerInfo =
{
    &Object_StubDesc,
    0,
    _MIDL_ProcFormatString.Format,
    &ITPCC_FormatStringOffsetTable[-3],
    0,
    0,
    0,
    0
};

CINTERFACE_PROXY_VTABLE(9) _ITPCCProxyVtbl =
{
    &ITPCC_ProxyInfo,
    &IID_ITPCC,
    IUnknown_QueryInterface_Proxy,
    IUnknown_AddRef_Proxy,
    IUnknown_Release_Proxy ,
    (void *) (INT_PTR) -1 /* ITPCC::NewOrder */ ,
    (void *) (INT_PTR) -1 /* ITPCC::Payment */ ,
    (void *) (INT_PTR) -1 /* ITPCC::Delivery */ ,
    (void *) (INT_PTR) -1 /* ITPCC::StockLevel */ ,
    (void *) (INT_PTR) -1 /* ITPCC::OrderStatus */ ,
    (void *) (INT_PTR) -1 /* ITPCC::CallSetComplete
*/
};

const CInterfaceStubVtbl _ITPCCStubVtbl =
{
    &IID_ITPCC,
    &ITPCC_ServerInfo,
    9,
    0, /* pure interpreted */
    CStdStubBuffer_METHODS
};

static const MIDL_STUB_DESC Object_StubDesc =
{
    0,
    NdrOleAllocate,
    NdrOleFree,
    0,
    0,
    0,
    0,

```

```

0,
    _MIDL_TypeFormatString.Format,
    1, /* -error bounds_check flag */
    0x20000, /* Ndr library version */
    0,
    0x600015b, /* MIDL Version 6.0.347 */
    0,
    UserMarshalRoutines,
    0, /* notify & notify_flag routine table */
    0x1, /* MIDL flag */
    0, /* cs routines */
    0, /* proxy/server info */
    0 /* Reserved5 */
};

const CInterfaceProxyVtbl *
_tpcc_com_ps_ProxyVtblList[] =
{
    ( CInterfaceProxyVtbl *) &_ITPCCProxyVtbl,
    0
};

const CInterfaceStubVtbl *
_tpcc_com_ps_StubVtblList[] =
{
    ( CInterfaceStubVtbl *) &_ITPCCStubVtbl,
    0
};

PCInterfaceName const
_tpcc_com_ps_InterfaceNamesList[] =
{
    "ITPCC",
    0
};

#define _tpcc_com_ps_CHECK_IID(n)
IID_GENERIC_CHECK_IID( _tpcc_com_ps, pIID,
n)

int __stdcall _tpcc_com_ps_IID_Lookup( const IID *
pIID, int * pIndex )
{
    if(!_tpcc_com_ps_CHECK_IID(0))
    {
        *pIndex = 0;
        return 1;
    }

    return 0;
}

const ExtendedProxyFileInfo tpcc_com_ps_ProxyFileInfo
=
{
    (PCInterfaceProxyVtblList *) &
_tpcc_com_ps_ProxyVtblList,
    (PCInterfaceStubVtblList *) &
_tpcc_com_ps_StubVtblList,

```

```

(const PCInterfaceName * ) &
_tpsc_com_ps_InterfaceNamesList,
0, // no delegation
& _tpcc_com_ps_IID_Lookup,
1,
2,
0, /* table of [async_uid] interfaces */
0, /* Filler1 */
0, /* Filler2 */
0 /* Filler3 */
};

#endif /* !defined(_M_IA64) && !defined(_M_AMD64) */

#pragma warning( disable: 4049 ) /* more than 64k
source lines */

/* this ALWAYS GENERATED file contains the proxy stub
code */

/* File created by MIDL compiler version 6.00.0347
*/
/* at Fri Apr 15 14:48:43 2005
*/
/* Compiler settings for .\src\tpcc_com_ps.idl:
Oicf, W1, Zp8, env=Win64 (32b run,appending)
protocol : dce , ms_ext, c_ext, robust
error checks: allocation ref bounds_check enum
stub_data
VC __declspec() decoration level:
__declspec(uuid()), __declspec(selectany),
__declspec(novtable)
DECLSPEC_UUID(), MIDL_INTERFACE()
*/
//@@MIDL_FILE_HEADING( )

#if defined(_M_IA64) || defined(_M_AMD64)
#define USE_STUBLESS_PROXY

/* verify that the <rpcproxy.h> version is high
enough to compile this file*/
#ifndef __REDQ_RPCPROXY_H_VERSION__
#define __REQUIRED_RPCPROXY_H_VERSION__ 475
#endif

#include "rpcproxy.h"
#ifndef __RPCPROXY_H_VERSION__
#error this stub requires an updated version of
<rpcproxy.h>
#endif // __RPCPROXY_H_VERSION__

#include "tpcc_com_ps.h"

#define TYPE_FORMAT_STRING_SIZE 1003
#define PROC_FORMAT_STRING_SIZE 253

```

```

#define TRANSMIT_AS_TABLE_SIZE 0
#define WIRE_MARSHAL_TABLE_SIZE 1

typedef struct _MIDL_TYPE_FORMAT_STRING
{
short Pad;
unsigned char Format[ TYPE_FORMAT_STRING_SIZE ];
} MIDL_TYPE_FORMAT_STRING;

typedef struct _MIDL_PROC_FORMAT_STRING
{
short Pad;
unsigned char Format[ PROC_FORMAT_STRING_SIZE ];
} MIDL_PROC_FORMAT_STRING;

static RPC_SYNTAX_IDENTIFIER _RpcTransferSyntax =
{{0x8A885D04,0x1CEB,0x11C9,{0x9F,0xE8,0x08,0x00,0x2B,
0x10,0x48,0x60}},{2,0}};

extern const MIDL_TYPE_FORMAT_STRING
__MIDL_TypeFormatString;
extern const MIDL_PROC_FORMAT_STRING
__MIDL_ProcFormatString;

extern const MIDL_STUB_DESC Object_StubDesc;

extern const MIDL_SERVER_INFO ITPCC_ServerInfo;
extern const MIDL_STUBLESS_PROXY_INFO
ITPCC_ProxyInfo;

extern const USER_MARSHAL_ROUTINE_QUADRUPLE
UserMarshalRoutines[ WIRE_MARSHAL_TABLE_SIZE ];

#if !defined(_RPC_WIN64_)
#error Invalid build platform for this stub.
#endif

static const MIDL_PROC_FORMAT_STRING
__MIDL_ProcFormatString =
{
0,
{
/* Procedure NewOrder */
FC_AUTO_HANDLE /* 0x33, */
/* 0x6c, */
Old Flags: object, Oi2 /*
/* 2 */ NdrFcLong( 0x0 ), /* 0 */
/* 6 */ NdrFcShort( 0x3 ), /* 3 */
/* 8 */ NdrFcShort( 0x30 ), /* ia64 Stack
size/offset = 48 */
/* 10 */ NdrFcShort( 0x0 ), /* 0 */
/* 12 */ NdrFcShort( 0x8 ), /* 8 */

```

```

/* 14 */ 0x47, /* Oi2 Flags: srv must
size, clt must size, has return, has ext, */
0x3, /*
3 */
/* 16 */ 0xa, /* 10 */
0x7, /*
Ext Flags: new corr desc, clt corr check, srv corr
check, */
/* 18 */ NdrFcShort( 0x20 ), /* 32 */
/* 20 */ NdrFcShort( 0x20 ), /* 32 */
/* 22 */ NdrFcShort( 0x0 ), /* 0 */
/* 24 */ NdrFcShort( 0x0 ), /* 0 */

/* Parameter txn_in */

/* 26 */ NdrFcShort( 0x8b ), /* Flags: must size,
must free, in, by val, */
/* 28 */ NdrFcShort( 0x8 ), /* ia64 Stack
size/offset = 8 */
/* 30 */ NdrFcShort( 0x3ce ), /* Type
Offset=974 */

/* Parameter txn_out */

/* 32 */ NdrFcShort( 0x6113 ), /* Flags:
must size, must free, out, simple ref, srv alloc
size=24 */
/* 34 */ NdrFcShort( 0x20 ), /* ia64 Stack
size/offset = 32 */
/* 36 */ NdrFcShort( 0x3e0 ), /* Type
Offset=992 */

/* Return value */

/* 38 */ NdrFcShort( 0x70 ), /* Flags: out, return,
base type, */
/* 40 */ NdrFcShort( 0x28 ), /* ia64 Stack
size/offset = 40 */
/* 42 */ 0x8, /* FC_LONG */
0x0, /*
0 */

/* Procedure Payment */

/* 44 */ 0x33, /* FC_AUTO_HANDLE */
0x6c, /*
Old Flags: object, Oi2 /*
/* 46 */ NdrFcLong( 0x0 ), /* 0 */
/* 50 */ NdrFcShort( 0x4 ), /* 4 */
/* 52 */ NdrFcShort( 0x30 ), /* ia64 Stack
size/offset = 48 */
/* 54 */ NdrFcShort( 0x0 ), /* 0 */
/* 56 */ NdrFcShort( 0x8 ), /* 8 */
/* 58 */ 0x47, /* Oi2 Flags: srv must
size, clt must size, has return, has ext, */
0x3, /*
3 */
/* 60 */ 0xa, /* 10 */
0x7, /*
Ext Flags: new corr desc, clt corr check, srv corr
check, */

```



```

/* 62 */ NdrFcShort( 0x20 ), /* 32 */
/* 64 */ NdrFcShort( 0x20 ), /* 32 */
/* 66 */ NdrFcShort( 0x0 ), /* 0 */
/* 68 */ NdrFcShort( 0x0 ), /* 0 */

    /* Parameter txn_in */

/* 70 */ NdrFcShort( 0x8b ), /* Flags: must size,
must free, in, by val, */
/* 72 */ NdrFcShort( 0x8 ), /* ia64 Stack
size/offset = 8 */
/* 74 */ NdrFcShort( 0x3ce ), /* Type
Offset=974 */

    /* Parameter txn_out */

/* 76 */ NdrFcShort( 0x6113 ), /* Flags:
must size, must free, out, simple ref, srv alloc
size=24 */
/* 78 */ NdrFcShort( 0x20 ), /* ia64 Stack
size/offset = 32 */
/* 80 */ NdrFcShort( 0x3e0 ), /* Type
Offset=992 */

    /* Return value */

/* 82 */ NdrFcShort( 0x70 ), /* Flags: out, return,
base type, */
/* 84 */ NdrFcShort( 0x28 ), /* ia64 Stack
size/offset = 40 */
/* 86 */ 0x8, /* FC_LONG */
0x0, /*
0 */

    /* Procedure Delivery */

/* 88 */ 0x33, /* FC_AUTO_HANDLE */
0x6c, /*
Old Flags: object, Oi2 */
/* 90 */ NdrFcLong( 0x0 ), /* 0 */
/* 94 */ NdrFcShort( 0x5 ), /* 5 */
/* 96 */ NdrFcShort( 0x30 ), /* ia64 Stack
size/offset = 48 */
/* 98 */ NdrFcShort( 0x0 ), /* 0 */
/* 100 */ NdrFcShort( 0x8 ), /* 8 */
/* 102 */ 0x47, /* Oi2 Flags: srv must
size, clt must size, has return, has ext, */
0x3, /*
3 */
/* 104 */ 0xa, /* 10 */
0x7, /*
Ext Flags: new corr desc, clt corr check, srv corr
check, */
/* 106 */ NdrFcShort( 0x20 ), /* 32 */
/* 108 */ NdrFcShort( 0x20 ), /* 32 */
/* 110 */ NdrFcShort( 0x0 ), /* 0 */
/* 112 */ NdrFcShort( 0x0 ), /* 0 */

    /* Parameter txn_in */

```

```

/* 114 */ NdrFcShort( 0x8b ), /* Flags: must size,
must free, in, by val, */
/* 116 */ NdrFcShort( 0x8 ), /* ia64 Stack
size/offset = 8 */
/* 118 */ NdrFcShort( 0x3ce ), /* Type
Offset=974 */

    /* Parameter txn_out */

/* 120 */ NdrFcShort( 0x6113 ), /* Flags:
must size, must free, out, simple ref, srv alloc
size=24 */
/* 122 */ NdrFcShort( 0x20 ), /* ia64 Stack
size/offset = 32 */
/* 124 */ NdrFcShort( 0x3e0 ), /* Type
Offset=992 */

    /* Return value */

/* 126 */ NdrFcShort( 0x70 ), /* Flags: out, return,
base type, */
/* 128 */ NdrFcShort( 0x28 ), /* ia64 Stack
size/offset = 40 */
/* 130 */ 0x8, /* FC_LONG */
0x0, /*
0 */

    /* Procedure StockLevel */

/* 132 */ 0x33, /* FC_AUTO_HANDLE */
0x6c, /*
Old Flags: object, Oi2 */
/* 134 */ NdrFcLong( 0x0 ), /* 0 */
/* 138 */ NdrFcShort( 0x6 ), /* 6 */
/* 140 */ NdrFcShort( 0x30 ), /* ia64 Stack
size/offset = 48 */
/* 142 */ NdrFcShort( 0x0 ), /* 0 */
/* 144 */ NdrFcShort( 0x8 ), /* 8 */
/* 146 */ 0x47, /* Oi2 Flags: srv must
size, clt must size, has return, has ext, */
0x3, /*
3 */
/* 148 */ 0xa, /* 10 */
0x7, /*
Ext Flags: new corr desc, clt corr check, srv corr
check, */
/* 150 */ NdrFcShort( 0x20 ), /* 32 */
/* 152 */ NdrFcShort( 0x20 ), /* 32 */
/* 154 */ NdrFcShort( 0x0 ), /* 0 */
/* 156 */ NdrFcShort( 0x0 ), /* 0 */

    /* Parameter txn_in */

/* 158 */ NdrFcShort( 0x8b ), /* Flags: must size,
must free, in, by val, */
/* 160 */ NdrFcShort( 0x8 ), /* ia64 Stack
size/offset = 8 */
/* 162 */ NdrFcShort( 0x3ce ), /* Type
Offset=974 */

    /* Parameter txn_out */

```

```

/* 164 */ NdrFcShort( 0x6113 ), /* Flags:
must size, must free, out, simple ref, srv alloc
size=24 */
/* 166 */ NdrFcShort( 0x20 ), /* ia64 Stack
size/offset = 32 */
/* 168 */ NdrFcShort( 0x3e0 ), /* Type
Offset=992 */

    /* Return value */

/* 170 */ NdrFcShort( 0x70 ), /* Flags: out, return,
base type, */
/* 172 */ NdrFcShort( 0x28 ), /* ia64 Stack
size/offset = 40 */
/* 174 */ 0x8, /* FC_LONG */
0x0, /*
0 */

    /* Procedure OrderStatus */

/* 176 */ 0x33, /* FC_AUTO_HANDLE */
0x6c, /*
Old Flags: object, Oi2 */
/* 178 */ NdrFcLong( 0x0 ), /* 0 */
/* 182 */ NdrFcShort( 0x7 ), /* 7 */
/* 184 */ NdrFcShort( 0x30 ), /* ia64 Stack
size/offset = 48 */
/* 186 */ NdrFcShort( 0x0 ), /* 0 */
/* 188 */ NdrFcShort( 0x8 ), /* 8 */
/* 190 */ 0x47, /* Oi2 Flags: srv must
size, clt must size, has return, has ext, */
0x3, /*
3 */
/* 192 */ 0xa, /* 10 */
0x7, /*
Ext Flags: new corr desc, clt corr check, srv corr
check, */
/* 194 */ NdrFcShort( 0x20 ), /* 32 */
/* 196 */ NdrFcShort( 0x20 ), /* 32 */
/* 198 */ NdrFcShort( 0x0 ), /* 0 */
/* 200 */ NdrFcShort( 0x0 ), /* 0 */

    /* Parameter txn_in */

/* 202 */ NdrFcShort( 0x8b ), /* Flags: must size,
must free, in, by val, */
/* 204 */ NdrFcShort( 0x8 ), /* ia64 Stack
size/offset = 8 */
/* 206 */ NdrFcShort( 0x3ce ), /* Type
Offset=974 */

    /* Parameter txn_out */

/* 208 */ NdrFcShort( 0x6113 ), /* Flags:
must size, must free, out, simple ref, srv alloc
size=24 */
/* 210 */ NdrFcShort( 0x20 ), /* ia64 Stack
size/offset = 32 */
/* 212 */ NdrFcShort( 0x3e0 ), /* Type
Offset=992 */

```

```

/* Return value */

/* 214 */ NdrPcShort( 0x70 ), /* Flags: out, return,
base type, */
/* 216 */ NdrPcShort( 0x28 ), /* ia64 Stack
size/offset = 40 */
/* 218 */ 0x8, /* FC_LONG */
0x0, /*
0 */

/* Procedure CallSetComplete */

/* 220 */ 0x33, /* FC_AUTO_HANDLE */
0x6c, /*
Old Flags: object, Oi2 */
/* 222 */ NdrPcLong( 0x0 ), /* 0 */
/* 226 */ NdrPcShort( 0x8 ), /* 8 */
/* 228 */ NdrPcShort( 0x10 ), /* ia64 Stack
size/offset = 16 */
/* 230 */ NdrPcShort( 0x0 ), /* 0 */
/* 232 */ NdrPcShort( 0x8 ), /* 8 */
/* 234 */ 0x44, /* Oi2 Flags: has
return, has ext, */
0x1, /*
1 */
/* 236 */ 0xa, /* 10 */
0x1, /*
Ext Flags: new corr desc, */
/* 238 */ NdrPcShort( 0x0 ), /* 0 */
/* 240 */ NdrPcShort( 0x0 ), /* 0 */
/* 242 */ NdrPcShort( 0x0 ), /* 0 */
/* 244 */ NdrPcShort( 0x0 ), /* 0 */

/* Return value */

/* 246 */ NdrPcShort( 0x70 ), /* Flags: out, return,
base type, */
/* 248 */ NdrPcShort( 0x8 ), /* ia64 Stack
size/offset = 8 */
/* 250 */ 0x8, /* FC_LONG */
0x0, /*
0 */
0x0
};

static const MIDL_TYPE_FORMAT_STRING
_MIDL_TypeFormatString =
{
0,
{
NdrPcShort( 0x0 ), /*
0 */
/* 2 */
0x12, 0x0, /*
FC_UP */
/* 4 */ NdrPcShort( 0x3b6 ), /* Offset=
950 (954) */
/* 6 */
FC_NON_ENCAPSULATED_UNION */
0x2b, /*
FC_ULONG */
/* 8 */ 0x7, /* Corr desc: FC_USHORT
*/
0x0, /*
/* 10 */ NdrPcShort( 0xffff8 ), /* -8 */
/* 12 */ NdrPcShort( 0x1 ), /* Corr flags: early,
*/
/* 14 */ NdrPcShort( 0x2 ), /* Offset= 2 (16) */
/* 16 */ NdrPcShort( 0x10 ), /* 16 */
/* 18 */ NdrPcShort( 0x2f ), /* 47 */
/* 20 */ NdrPcShort( 0x14 ), /* 20 */
/* 24 */ NdrPcShort( 0x800b ), /* Simple arm
type: FC_HYPER */
/* 26 */ NdrPcLong( 0x3 ), /* 3 */
/* 30 */ NdrPcShort( 0x8008 ), /* Simple arm
type: FC_LONG */
/* 32 */ NdrPcLong( 0x11 ), /* 17 */
/* 36 */ NdrPcShort( 0x8001 ), /* Simple arm
type: FC_BYTE */
/* 38 */ NdrPcLong( 0x2 ), /* 2 */
/* 42 */ NdrPcShort( 0x8006 ), /* Simple arm
type: FC_SHORT */
/* 44 */ NdrPcLong( 0x4 ), /* 4 */
/* 48 */ NdrPcShort( 0x800a ), /* Simple arm
type: FC_FLOAT */
/* 50 */ NdrPcLong( 0x5 ), /* 5 */
/* 54 */ NdrPcShort( 0x800c ), /* Simple arm
type: FC_DOUBLE */
/* 56 */ NdrPcLong( 0xb ), /* 11 */
/* 60 */ NdrPcShort( 0x8006 ), /* Simple arm
type: FC_SHORT */
/* 62 */ NdrPcLong( 0xa ), /* 10 */
/* 66 */ NdrPcShort( 0x8008 ), /* Simple arm
type: FC_LONG */
/* 68 */ NdrPcLong( 0x6 ), /* 6 */
/* 72 */ NdrPcShort( 0xe8 ), /* Offset= 232 (304) */
/* 74 */ NdrPcLong( 0x7 ), /* 7 */
/* 78 */ NdrPcShort( 0x800c ), /* Simple arm
type: FC_DOUBLE */
/* 80 */ NdrPcLong( 0x8 ), /* 8 */
/* 84 */ NdrPcShort( 0xe2 ), /* Offset= 226 (310) */
/* 86 */ NdrPcLong( 0xd ), /* 13 */
/* 90 */ NdrPcShort( 0xf6 ), /* Offset= 246 (336) */
/* 92 */ NdrPcLong( 0x9 ), /* 9 */
/* 96 */ NdrPcShort( 0x102 ), /* Offset=
258 (354) */
/* 98 */ NdrPcLong( 0x2000 ), /* 8192 */
/* 102 */ NdrPcShort( 0x10e ), /* Offset=
270 (372) */
/* 104 */ NdrPcLong( 0x24 ), /* 36 */
/* 108 */ NdrPcShort( 0x304 ), /* Offset=
772 (880) */
/* 110 */ NdrPcLong( 0x4024 ), /* 16420 */
/* 114 */ NdrPcShort( 0x2fe ), /* Offset=
766 (880) */
/* 116 */ NdrPcLong( 0x4011 ), /* 16401 */
/* 120 */ NdrPcShort( 0x2fc ), /* Offset=
764 (884) */
/* 122 */ NdrPcLong( 0x4002 ), /* 16386 */
/* 126 */ NdrPcShort( 0x2fa ), /* Offset=
762 (888) */
/* 128 */ NdrPcLong( 0x4003 ), /* 16387 */
/* 132 */ NdrPcShort( 0x2f8 ), /* Offset=
760 (892) */
/* 134 */ NdrPcLong( 0x4014 ), /* 16404 */
/* 138 */ NdrPcShort( 0x2f6 ), /* Offset=
758 (896) */
/* 140 */ NdrPcLong( 0x4004 ), /* 16388 */
/* 144 */ NdrPcShort( 0x2f4 ), /* Offset=
756 (900) */
/* 146 */ NdrPcLong( 0x4005 ), /* 16389 */
/* 150 */ NdrPcShort( 0x2f2 ), /* Offset=
754 (904) */
/* 152 */ NdrPcLong( 0x400b ), /* 16395 */
/* 156 */ NdrPcShort( 0x2dc ), /* Offset=
732 (888) */
/* 158 */ NdrPcLong( 0x400a ), /* 16394 */
/* 162 */ NdrPcShort( 0x2da ), /* Offset=
730 (892) */
/* 164 */ NdrPcLong( 0x4006 ), /* 16390 */
/* 168 */ NdrPcShort( 0x2e4 ), /* Offset=
740 (908) */
/* 170 */ NdrPcLong( 0x4007 ), /* 16391 */
/* 174 */ NdrPcShort( 0x2da ), /* Offset=
730 (904) */
/* 176 */ NdrPcLong( 0x4008 ), /* 16392 */
/* 180 */ NdrPcShort( 0x2dc ), /* Offset=
732 (912) */
/* 182 */ NdrPcLong( 0x400d ), /* 16397 */
/* 186 */ NdrPcShort( 0x2da ), /* Offset=
730 (916) */
/* 188 */ NdrPcLong( 0x4009 ), /* 16393 */
/* 192 */ NdrPcShort( 0x2d8 ), /* Offset=
728 (920) */
/* 194 */ NdrPcLong( 0x6000 ), /* 24576 */
/* 198 */ NdrPcShort( 0x2d6 ), /* Offset=
726 (924) */
/* 200 */ NdrPcLong( 0x400c ), /* 16396 */
/* 204 */ NdrPcShort( 0x2d4 ), /* Offset=
724 (928) */
/* 206 */ NdrPcLong( 0x10 ), /* 16 */
/* 210 */ NdrPcShort( 0x8002 ), /* Simple arm
type: FC_CHAR */
/* 212 */ NdrPcLong( 0x12 ), /* 18 */
/* 216 */ NdrPcShort( 0x8006 ), /* Simple arm
type: FC_SHORT */
/* 218 */ NdrPcLong( 0x13 ), /* 19 */
/* 222 */ NdrPcShort( 0x8008 ), /* Simple arm
type: FC_LONG */
/* 224 */ NdrPcLong( 0x15 ), /* 21 */
/* 228 */ NdrPcShort( 0x800b ), /* Simple arm
type: FC_HYPER */
/* 230 */ NdrPcLong( 0x16 ), /* 22 */
/* 234 */ NdrPcShort( 0x8008 ), /* Simple arm
type: FC_LONG */
/* 236 */ NdrPcLong( 0x17 ), /* 23 */

```

```

/* 240 */ NdrFcShort( 0x8008 ), /* Simple arm
type: FC_LONG */
/* 242 */ NdrFcLong( 0xe ), /* 14 */
/* 246 */ NdrFcShort( 0x2b2 ), /* Offset=
690 (936) */
/* 248 */ NdrFcLong( 0x400e ), /* 16398 */
/* 252 */ NdrFcShort( 0x2b6 ), /* Offset=
694 (946) */
/* 254 */ NdrFcLong( 0x4010 ), /* 16400 */
/* 258 */ NdrFcShort( 0x2b4 ), /* Offset=
692 (950) */
/* 260 */ NdrFcLong( 0x4012 ), /* 16402 */
/* 264 */ NdrFcShort( 0x270 ), /* Offset=
624 (888) */
/* 266 */ NdrFcLong( 0x4013 ), /* 16403 */
/* 270 */ NdrFcShort( 0x26e ), /* Offset=
622 (892) */
/* 272 */ NdrFcLong( 0x4015 ), /* 16405 */
/* 276 */ NdrFcShort( 0x26c ), /* Offset=
620 (896) */
/* 278 */ NdrFcLong( 0x4016 ), /* 16406 */
/* 282 */ NdrFcShort( 0x262 ), /* Offset=
610 (892) */
/* 284 */ NdrFcLong( 0x4017 ), /* 16407 */
/* 288 */ NdrFcShort( 0x25c ), /* Offset=
604 (892) */
/* 290 */ NdrFcLong( 0x0 ), /* 0 */
/* 294 */ NdrFcShort( 0x0 ), /* Offset= 0 (294) */
/* 296 */ NdrFcLong( 0x1 ), /* 1 */
/* 300 */ NdrFcShort( 0x0 ), /* Offset= 0 (300) */
/* 302 */ NdrFcShort( 0xffffffff ), /* Offset= -1
(301) */
/* 304 */
0x15, /*
FC_STRUCT */
0x7, /*
7 */
/* 306 */ NdrFcShort( 0x8 ), /* 8 */
/* 308 */ 0xb, /* FC_HYPER */
0x5b, /*
FC_END */
/* 310 */
0x12, 0x0, /*
FC_UP */
/* 312 */ NdrFcShort( 0xe ), /* Offset= 14 (326) */
/* 314 */
0x1b, /*
FC_CARRAY */
0x1, /*
1 */
/* 316 */ NdrFcShort( 0x2 ), /* 2 */
/* 318 */ 0x9, /* Corr desc: FC_ULONG
*/
0x0, /*
*/
/* 320 */ NdrFcShort( 0xfffc ), /* -4 */
/* 322 */ NdrFcShort( 0x1 ), /* Corr flags: early,
*/
/* 324 */ 0x6, /* FC_SHORT */
0x5b, /*
FC_END */

```

```

/* 326 */
FC_CSTRUCT */
0x17, /*
3 */
/* 328 */ NdrFcShort( 0x8 ), /* 8 */
/* 330 */ NdrFcShort( 0xffffffff0 ), /* Offset= -
16 (314) */
/* 332 */ 0x8, /* FC_LONG */
0x8, /*
FC_LONG */
/* 334 */ 0x5c, /* FC_PAD */
0x5b, /*
FC_END */
/* 336 */
0x2E, /*
FC_IP */
0x5a, /*
FC_CONSTANT_IID */
/* 338 */ NdrFcLong( 0x0 ), /* 0 */
/* 342 */ NdrFcShort( 0x0 ), /* 0 */
/* 344 */ NdrFcShort( 0x0 ), /* 0 */
/* 346 */ 0xc0, /* 192 */
0x0, /*
0 */
/* 348 */ 0x0, /* 0 */
0x0, /*
0 */
/* 350 */ 0x0, /* 0 */
0x0, /*
0 */
/* 352 */ 0x0, /* 0 */
0x46, /*
70 */
/* 354 */
0x2E, /*
FC_IP */
0x5a, /*
FC_CONSTANT_IID */
/* 356 */ NdrFcLong( 0x20400 ), /* 132096 */
/* 360 */ NdrFcShort( 0x0 ), /* 0 */
/* 362 */ NdrFcShort( 0x0 ), /* 0 */
/* 364 */ 0xc0, /* 192 */
0x0, /*
0 */
/* 366 */ 0x0, /* 0 */
0x0, /*
0 */
/* 368 */ 0x0, /* 0 */
0x0, /*
0 */
/* 370 */ 0x0, /* 0 */
0x46, /*
70 */
/* 372 */
0x12, 0x10, /*
FC_UP [pointer_deref] */
/* 374 */ NdrFcShort( 0x2 ), /* Offset= 2 (376) */
/* 376 */
0x12, 0x0, /*
FC_UP */

```

```

/* 378 */ NdrFcShort( 0x1e4 ), /* Offset=
484 (862) */
/* 380 */
0x2a, /*
FC_ENCAPSULATED_UNION */
0x89, /*
137 */
/* 382 */ NdrFcShort( 0x20 ), /* 32 */
/* 384 */ NdrFcShort( 0xa ), /* 10 */
/* 386 */ NdrFcLong( 0x8 ), /* 8 */
/* 390 */ NdrFcShort( 0x50 ), /* Offset= 80 (470) */
/* 392 */ NdrFcLong( 0xd ), /* 13 */
/* 396 */ NdrFcShort( 0x70 ), /* Offset= 112 (508) */
/* 398 */ NdrFcLong( 0x9 ), /* 9 */
/* 402 */ NdrFcShort( 0x90 ), /* Offset= 144 (546) */
/* 404 */ NdrFcLong( 0xc ), /* 12 */
/* 408 */ NdrFcShort( 0xb0 ), /* Offset= 176 (584) */
/* 410 */ NdrFcLong( 0x24 ), /* 36 */
/* 414 */ NdrFcShort( 0x102 ), /* Offset=
258 (672) */
/* 416 */ NdrFcLong( 0x800d ), /* 32781 */
/* 420 */ NdrFcShort( 0x11e ), /* Offset=
286 (706) */
/* 422 */ NdrFcLong( 0x10 ), /* 16 */
/* 426 */ NdrFcShort( 0x138 ), /* Offset=
312 (738) */
/* 428 */ NdrFcLong( 0x2 ), /* 2 */
/* 432 */ NdrFcShort( 0x14e ), /* Offset=
334 (766) */
/* 434 */ NdrFcLong( 0x3 ), /* 3 */
/* 438 */ NdrFcShort( 0x164 ), /* Offset=
356 (794) */
/* 440 */ NdrFcLong( 0x14 ), /* 20 */
/* 444 */ NdrFcShort( 0x17a ), /* Offset=
378 (822) */
/* 446 */ NdrFcShort( 0xffffffff ), /* Offset= -1
(445) */
/* 448 */
0x21, /*
FC_BOGUS_ARRAY */
0x3, /*
3 */
/* 450 */ NdrFcShort( 0x0 ), /* 0 */
/* 452 */ 0x19, /* Corr desc: field
pointer, FC_ULONG */
0x0, /*
*/
/* 454 */ NdrFcShort( 0x0 ), /* 0 */
/* 456 */ NdrFcShort( 0x1 ), /* Corr flags: early,
*/
/* 458 */ NdrFcLong( 0xffffffff ), /* -1 */
/* 462 */ NdrFcShort( 0x0 ), /* Corr flags: */
/* 464 */
0x12, 0x0, /*
FC_UP */
/* 466 */ NdrFcShort( 0xffffffff74 ), /* Offset= -
140 (326) */
/* 468 */ 0x5c, /* FC_PAD */
0x5b, /*
FC_END */
/* 470 */

```

```

                                0x1a,          /*
FC_BOGUS_STRUCT */
                                0x3,          /*
3 */
/* 472 */ NdrFcShort( 0x10 ), /* 16 */
/* 474 */ NdrFcShort( 0x0 ), /* 0 */
/* 476 */ NdrFcShort( 0x6 ), /* Offset= 6 (482) */
/* 478 */ 0x8, /* FC_LONG */
                                0x40,          /*
FC_STRUCTPAD4 */
/* 480 */ 0x36, /* FC_POINTER */
                                0x5b,          /*
FC_END */
/* 482 */
                                0x11, 0x0,      /*
FC_RP */
/* 484 */ NdrFcShort( 0xfffffdc ), /* Offset= -
36 (448) */
/* 486 */
                                0x21,          /*
FC_BOGUS_ARRAY */
                                0x3,          /*
3 */
/* 488 */ NdrFcShort( 0x0 ), /* 0 */
/* 490 */ 0x19, /* Corr desc: field
pointer, FC_ULONG */
                                0x0,          /*
*/
/* 492 */ NdrFcShort( 0x0 ), /* 0 */
/* 494 */ NdrFcShort( 0x1 ), /* Corr flags: early,
*/
/* 496 */ NdrFcLong( 0xffffffff ), /* -1 */
/* 500 */ NdrFcShort( 0x0 ), /* Corr flags: */
/* 502 */ 0x4c, /* FC_EMBEDDED_COMPLEX
*/
                                0x0,          /*
0 */
/* 504 */ NdrFcShort( 0xfffff58 ), /* Offset= -
168 (336) */
/* 506 */ 0x5c, /* FC_PAD */
                                0x5b,          /*
FC_END */
/* 508 */
                                0x1a,          /*
FC_BOGUS_STRUCT */
                                0x3,          /*
3 */
/* 510 */ NdrFcShort( 0x10 ), /* 16 */
/* 512 */ NdrFcShort( 0x0 ), /* 0 */
/* 514 */ NdrFcShort( 0x6 ), /* Offset= 6 (520) */
/* 516 */ 0x8, /* FC_LONG */
                                0x40,          /*
FC_STRUCTPAD4 */
/* 518 */ 0x36, /* FC_POINTER */
                                0x5b,          /*
FC_END */
/* 520 */
                                0x11, 0x0,      /*
FC_RP */
/* 522 */ NdrFcShort( 0xfffffdc ), /* Offset= -
36 (486) */

```

```

/* 524 */
FC_BOGUS_ARRAY */
                                0x21,          /*
                                0x3,          /*
3 */
/* 526 */ NdrFcShort( 0x0 ), /* 0 */
/* 528 */ 0x19, /* Corr desc: field
pointer, FC_ULONG */
                                0x0,          /*
*/
/* 530 */ NdrFcShort( 0x0 ), /* 0 */
/* 532 */ NdrFcShort( 0x1 ), /* Corr flags: early,
*/
/* 534 */ NdrFcLong( 0xffffffff ), /* -1 */
/* 538 */ NdrFcShort( 0x0 ), /* Corr flags: */
/* 540 */ 0x4c, /* FC_EMBEDDED_COMPLEX
*/
                                0x0,          /*
0 */
/* 542 */ NdrFcShort( 0xfffff44 ), /* Offset= -
188 (354) */
/* 544 */ 0x5c, /* FC_PAD */
                                0x5b,          /*
FC_END */
/* 546 */
                                0x1a,          /*
FC_BOGUS_STRUCT */
                                0x3,          /*
3 */
/* 548 */ NdrFcShort( 0x10 ), /* 16 */
/* 550 */ NdrFcShort( 0x0 ), /* 0 */
/* 552 */ NdrFcShort( 0x6 ), /* Offset= 6 (558) */
/* 554 */ 0x8, /* FC_LONG */
                                0x40,          /*
FC_STRUCTPAD4 */
/* 556 */ 0x36, /* FC_POINTER */
                                0x5b,          /*
FC_END */
/* 558 */
                                0x11, 0x0,      /*
FC_RP */
/* 560 */ NdrFcShort( 0xfffffdc ), /* Offset= -
36 (524) */
/* 562 */
                                0x21,          /*
FC_BOGUS_ARRAY */
                                0x3,          /*
3 */
/* 564 */ NdrFcShort( 0x0 ), /* 0 */
/* 566 */ 0x19, /* Corr desc: field
pointer, FC_ULONG */
                                0x0,          /*
*/
/* 568 */ NdrFcShort( 0x0 ), /* 0 */
/* 570 */ NdrFcShort( 0x1 ), /* Corr flags: early,
*/
/* 572 */ NdrFcLong( 0xffffffff ), /* -1 */
/* 576 */ NdrFcShort( 0x0 ), /* Corr flags: */
/* 578 */
                                0x12, 0x0,      /*
FC_UP */

```

```

/* 580 */ NdrFcShort( 0x176 ), /* Offset=
374 (954) */
/* 582 */ 0x5c, /* FC_PAD */
                                0x5b,          /*
FC_END */
/* 584 */
                                0x1a,          /*
FC_BOGUS_STRUCT */
                                0x3,          /*
3 */
/* 586 */ NdrFcShort( 0x10 ), /* 16 */
/* 588 */ NdrFcShort( 0x0 ), /* 0 */
/* 590 */ NdrFcShort( 0x6 ), /* Offset= 6 (596) */
/* 592 */ 0x8, /* FC_LONG */
                                0x40,          /*
FC_STRUCTPAD4 */
/* 594 */ 0x36, /* FC_POINTER */
                                0x5b,          /*
FC_END */
/* 596 */
                                0x11, 0x0,      /*
FC_RP */
/* 598 */ NdrFcShort( 0xfffffdc ), /* Offset= -
36 (562) */
/* 600 */
                                0x2f,          /*
FC_IP */
                                0x5a,          /*
FC_CONSTANT_IID */
/* 602 */ NdrFcLong( 0x2f ), /* 47 */
/* 606 */ NdrFcShort( 0x0 ), /* 0 */
/* 608 */ NdrFcShort( 0x0 ), /* 0 */
/* 610 */ 0xc0, /* 192 */
                                0x0,          /*
0 */
/* 612 */ 0x0, /* 0 */
                                0x0,          /*
0 */
/* 614 */ 0x0, /* 0 */
                                0x0,          /*
0 */
/* 616 */ 0x0, /* 0 */
                                0x46,          /*
70 */
/* 618 */
                                0x1b,          /*
FC_CARRAY */
                                0x0,          /*
0 */
/* 620 */ NdrFcShort( 0x1 ), /* 1 */
/* 622 */ 0x19, /* Corr desc: field
pointer, FC_ULONG */
                                0x0,          /*
*/
/* 624 */ NdrFcShort( 0x4 ), /* 4 */
/* 626 */ NdrFcShort( 0x1 ), /* Corr flags: early,
*/
/* 628 */ 0x1, /* FC_BYTE */
                                0x5b,          /*
FC_END */
/* 630 */

```

```

                                0x1a,          /*
FC_BOGUS_STRUCT */
                                0x3,          /*
3 */
/* 632 */ NdrFcShort( 0x18 ), /* 24 */
/* 634 */ NdrFcShort( 0x0 ), /* 0 */
/* 636 */ NdrFcShort( 0xa ), /* Offset= 10 (646) */
/* 638 */ 0x8, /* FC_LONG */
                                0x8,          /*
FC_LONG */
/* 640 */ 0x4c, /* FC_EMBEDDED_COMPLEX */
/*
                                0x0,          /*
0 */
/* 642 */ NdrFcShort( 0xfffffd6 ), /* Offset= -
42 (600) */
/* 644 */ 0x36, /* FC_POINTER */
                                0x5b,          /*
FC_END */
/* 646 */
                                0x12, 0x0,      /*
FC_UP */
/* 648 */ NdrFcShort( 0xfffffe2 ), /* Offset= -
30 (618) */
/* 650 */
                                0x21,          /*
FC_BOGUS_ARRAY */
                                0x3,          /*
3 */
/* 652 */ NdrFcShort( 0x0 ), /* 0 */
/* 654 */ 0x19, /* Corr desc: field
pointer, FC_ULONG */
                                0x0,          /*
*/
/* 656 */ NdrFcShort( 0x0 ), /* 0 */
/* 658 */ NdrFcShort( 0x1 ), /* Corr flags: early,
*/
/* 660 */ NdrFcLong( 0xffffffff ), /* -1 */
/* 664 */ NdrFcShort( 0x0 ), /* Corr flags: */
/* 666 */
                                0x12, 0x0,      /*
FC_UP */
/* 668 */ NdrFcShort( 0xfffffda ), /* Offset= -
38 (630) */
/* 670 */ 0x5c, /* FC_PAD */
                                0x5b,          /*
FC_END */
/* 672 */
                                0x1a,          /*
FC_BOGUS_STRUCT */
                                0x3,          /*
3 */
/* 674 */ NdrFcShort( 0x10 ), /* 16 */
/* 676 */ NdrFcShort( 0x0 ), /* 0 */
/* 678 */ NdrFcShort( 0x6 ), /* Offset= 6 (684) */
/* 680 */ 0x8, /* FC_LONG */
                                0x40,          /*
FC_STRUCTPAD4 */
/* 682 */ 0x36, /* FC_POINTER */
                                0x5b,          /*
FC_END */

```

```

/* 684 */
FC_RP */
/* 686 */ NdrFcShort( 0xfffffdc ), /* Offset= -
36 (650) */
/* 688 */
                                0x1d,          /*
FC_SMPARRAY */
                                0x0,          /*
0 */
/* 690 */ NdrFcShort( 0x8 ), /* 8 */
/* 692 */ 0x1, /* FC_BYTE */
                                0x5b,          /*
FC_END */
/* 694 */
                                0x15,          /*
FC_STRUCT */
                                0x3,          /*
3 */
/* 696 */ NdrFcShort( 0x10 ), /* 16 */
/* 698 */ 0x8, /* FC_LONG */
                                0x6,          /*
FC_SHORT */
/* 700 */ 0x6, /* FC_SHORT */
                                0x4c,          /*
FC_EMBEDDED_COMPLEX */
/* 702 */ 0x0, /* 0 */
                                NdrFcShort( 0xffffff1
), /* Offset= -15 (688) */
                                0x5b,          /*
FC_END */
/* 706 */
                                0x1a,          /*
FC_BOGUS_STRUCT */
                                0x3,          /*
3 */
/* 708 */ NdrFcShort( 0x20 ), /* 32 */
/* 710 */ NdrFcShort( 0x0 ), /* 0 */
/* 712 */ NdrFcShort( 0xa ), /* Offset= 10 (722) */
/* 714 */ 0x8, /* FC_LONG */
                                0x40,          /*
FC_STRUCTPAD4 */
/* 716 */ 0x36, /* FC_POINTER */
                                0x4c,          /*
FC_EMBEDDED_COMPLEX */
/* 718 */ 0x0, /* 0 */
                                NdrFcShort( 0xffffffe7
), /* Offset= -25 (694) */
                                0x5b,          /*
FC_END */
/* 722 */
                                0x11, 0x0,      /*
FC_RP */
/* 724 */ NdrFcShort( 0xffffff12 ), /* Offset= -
238 (486) */
/* 726 */
                                0x1b,          /*
FC_CARRAY */
                                0x0,          /*
0 */
/* 728 */ NdrFcShort( 0x1 ), /* 1 */

```

```

/* 730 */ 0x19, /* Corr desc: field
pointer, FC_ULONG */
                                0x0,          /*
*/
/* 732 */ NdrFcShort( 0x0 ), /* 0 */
/* 734 */ NdrFcShort( 0x1 ), /* Corr flags: early,
*/
/* 736 */ 0x1, /* FC_BYTE */
                                0x5b,          /*
FC_END */
/* 738 */
                                0x1a,          /*
FC_BOGUS_STRUCT */
                                0x3,          /*
3 */
/* 740 */ NdrFcShort( 0x10 ), /* 16 */
/* 742 */ NdrFcShort( 0x0 ), /* 0 */
/* 744 */ NdrFcShort( 0x6 ), /* Offset= 6 (750) */
/* 746 */ 0x8, /* FC_LONG */
                                0x40,          /*
FC_STRUCTPAD4 */
/* 748 */ 0x36, /* FC_POINTER */
                                0x5b,          /*
FC_END */
/* 750 */
                                0x12, 0x0,      /*
FC_UP */
/* 752 */ NdrFcShort( 0xfffffe6 ), /* Offset= -
26 (726) */
/* 754 */
                                0x1b,          /*
FC_CARRAY */
                                0x1,          /*
1 */
/* 756 */ NdrFcShort( 0x2 ), /* 2 */
/* 758 */ 0x19, /* Corr desc: field
pointer, FC_ULONG */
                                0x0,          /*
*/
/* 760 */ NdrFcShort( 0x0 ), /* 0 */
/* 762 */ NdrFcShort( 0x1 ), /* Corr flags: early,
*/
/* 764 */ 0x6, /* FC_SHORT */
                                0x5b,          /*
FC_END */
/* 766 */
                                0x1a,          /*
FC_BOGUS_STRUCT */
                                0x3,          /*
3 */
/* 768 */ NdrFcShort( 0x10 ), /* 16 */
/* 770 */ NdrFcShort( 0x0 ), /* 0 */
/* 772 */ NdrFcShort( 0x6 ), /* Offset= 6 (778) */
/* 774 */ 0x8, /* FC_LONG */
                                0x40,          /*
FC_STRUCTPAD4 */
/* 776 */ 0x36, /* FC_POINTER */
                                0x5b,          /*
FC_END */
/* 778 */

```

```

                                0x12, 0x0,      /*
FC_UP */
/* 780 */ NdrFcShort( 0xffffffe6 ), /* Offset= -
26 (754) */
/* 782 */
                                0x1b,      /*
FC_CARRAY */
                                0x3,      /*
3 */
/* 784 */ NdrFcShort( 0x4 ), /* 4 */
/* 786 */ 0x19, /* Corr desc: field
pointer, FC_ULONG */
                                0x0,      /*
*/
/* 788 */ NdrFcShort( 0x0 ), /* 0 */
/* 790 */ NdrFcShort( 0x1 ), /* Corr flags: early,
*/
/* 792 */ 0x8, /* FC_LONG */
                                0x5b,      /*
FC_END */
/* 794 */
                                0x1a,      /*
FC_BOGUS_STRUCT */
                                0x3,      /*
3 */
/* 796 */ NdrFcShort( 0x10 ), /* 16 */
/* 798 */ NdrFcShort( 0x0 ), /* 0 */
/* 800 */ NdrFcShort( 0x6 ), /* Offset= 6 (806) */
/* 802 */ 0x8, /* FC_LONG */
                                0x40,      /*
FC_STRUCTPAD4 */
/* 804 */ 0x36, /* FC_POINTER */
                                0x5b,      /*
FC_END */
/* 806 */
                                0x12, 0x0,      /*
FC_UP */
/* 808 */ NdrFcShort( 0xffffffe6 ), /* Offset= -
26 (782) */
/* 810 */
                                0x1b,      /*
FC_CARRAY */
                                0x7,      /*
7 */
/* 812 */ NdrFcShort( 0x8 ), /* 8 */
/* 814 */ 0x19, /* Corr desc: field
pointer, FC_ULONG */
                                0x0,      /*
*/
/* 816 */ NdrFcShort( 0x0 ), /* 0 */
/* 818 */ NdrFcShort( 0x1 ), /* Corr flags: early,
*/
/* 820 */ 0xb, /* FC_HYPER */
                                0x5b,      /*
FC_END */
/* 822 */
                                0x1a,      /*
FC_BOGUS_STRUCT */
                                0x3,      /*
3 */
/* 824 */ NdrFcShort( 0x10 ), /* 16 */

```

```

/* 826 */ NdrFcShort( 0x0 ), /* 0 */
/* 828 */ NdrFcShort( 0x6 ), /* Offset= 6 (834) */
/* 830 */ 0x8, /* FC_LONG */
                                0x40,      /*
FC_STRUCTPAD4 */
/* 832 */ 0x36, /* FC_POINTER */
                                0x5b,      /*
FC_END */
/* 834 */
                                0x12, 0x0,      /*
FC_UP */
/* 836 */ NdrFcShort( 0xffffffe6 ), /* Offset= -
26 (810) */
/* 838 */
                                0x15,      /*
FC_STRUCT */
                                0x3,      /*
3 */
/* 840 */ NdrFcShort( 0x8 ), /* 8 */
/* 842 */ 0x8, /* FC_LONG */
                                0x8,      /*
FC_LONG */
/* 844 */ 0x5c, /* FC_PAD */
                                0x5b,      /*
FC_END */
/* 846 */
                                0x1b,      /*
FC_CARRAY */
                                0x3,      /*
3 */
/* 848 */ NdrFcShort( 0x8 ), /* 8 */
/* 850 */ 0x7, /* Corr desc: FC_USHORT
*/
                                0x0,      /*
*/
/* 852 */ NdrFcShort( 0xffc8 ), /* -56 */
/* 854 */ NdrFcShort( 0x1 ), /* Corr flags: early,
*/
/* 856 */ 0x4c, /* FC_EMBEDDED_COMPLEX
*/
                                0x0,      /*
0 */
/* 858 */ NdrFcShort( 0xfffffec ), /* Offset= -
20 (838) */
/* 860 */ 0x5c, /* FC_PAD */
                                0x5b,      /*
FC_END */
/* 862 */
                                0x1a,      /*
FC_BOGUS_STRUCT */
                                0x3,      /*
3 */
/* 864 */ NdrFcShort( 0x38 ), /* 56 */
/* 866 */ NdrFcShort( 0xfffffec ), /* Offset= -
20 (846) */
/* 868 */ NdrFcShort( 0x0 ), /* Offset= 0 (868) */
/* 870 */ 0x6, /* FC_SHORT */
                                0x6,      /*
FC_SHORT */
/* 872 */ 0x8, /* FC_LONG */

```

```

                                0x8,      /*
FC_LONG */
/* 874 */ 0x40, /* FC_STRUCTPAD4 */
                                0x4c,      /*
FC_EMBEDDED_COMPLEX */
/* 876 */ 0x0, /* 0 */
                                NdrFcShort( 0xfffffe0f
), /* Offset= -497 (380) */
                                0x5b,      /*
FC_END */
/* 880 */
                                0x12, 0x0,      /*
FC_UP */
/* 882 */ NdrFcShort( 0xfffff04 ), /* Offset= -
252 (630) */
/* 884 */
                                0x12, 0x8,      /*
FC_UP [simple_pointer] */
/* 886 */ 0x1, /* FC_BYTE */
                                0x5c,      /*
FC_PAD */
/* 888 */
                                0x12, 0x8,      /*
FC_UP [simple_pointer] */
/* 890 */ 0x6, /* FC_SHORT */
                                0x5c,      /*
FC_PAD */
/* 892 */
                                0x12, 0x8,      /*
FC_UP [simple_pointer] */
/* 894 */ 0x8, /* FC_LONG */
                                0x5c,      /*
FC_PAD */
/* 896 */
                                0x12, 0x8,      /*
FC_UP [simple_pointer] */
/* 898 */ 0xb, /* FC_HYPER */
                                0x5c,      /*
FC_PAD */
/* 900 */
                                0x12, 0x8,      /*
FC_UP [simple_pointer] */
/* 902 */ 0xa, /* FC_FLOAT */
                                0x5c,      /*
FC_PAD */
/* 904 */
                                0x12, 0x8,      /*
FC_UP [simple_pointer] */
/* 906 */ 0xc, /* FC_DOUBLE */
                                0x5c,      /*
FC_PAD */
/* 908 */
                                0x12, 0x0,      /*
FC_UP */
/* 910 */ NdrFcShort( 0xfffffda2 ), /* Offset= -
606 (304) */
/* 912 */
                                0x12, 0x10,      /*
FC_UP [pointer_deref] */
/* 914 */ NdrFcShort( 0xfffffda4 ), /* Offset= -
604 (310) */

```

```

/* 916 */
FC_UP [pointer_deref] */
/* 918 */ NdrPcShort( 0xfffffdb8 ), /* Offset= -
582 (336) */
/* 920 */
FC_UP [pointer_deref] */
/* 922 */ NdrPcShort( 0xfffffdc8 ), /* Offset= -
568 (354) */
/* 924 */
FC_UP [pointer_deref] */
/* 926 */ NdrPcShort( 0xffffdd6 ), /* Offset= -
554 (372) */
/* 928 */
FC_UP [pointer_deref] */
/* 930 */ NdrPcShort( 0x2 ), /* Offset= 2 (932) */
/* 932 */
FC_UP */
/* 934 */ NdrPcShort( 0x14 ), /* Offset= 20 (954) */
/* 936 */
FC_STRUCT */
/* 938 */ NdrPcShort( 0x10 ), /* 16 */
/* 940 */ 0x6, /* FC_SHORT */
FC_BYTE */
/* 942 */ 0x1, /* FC_BYTE */
FC_LONG */
/* 944 */ 0xb, /* FC_HYPER */
FC_END */
/* 946 */
FC_UP */
/* 948 */ NdrPcShort( 0xffffffff4 ), /* Offset= -
12 (936) */
/* 950 */
FC_UP [simple_pointer] */
/* 952 */ 0x2, /* FC_CHAR */
FC_PAD */
/* 954 */
FC_BOGUS_STRUCT */
/* 956 */ NdrPcShort( 0x20 ), /* 32 */
/* 958 */ NdrPcShort( 0x0 ), /* 0 */
/* 960 */ NdrPcShort( 0x0 ), /* Offset= 0 (960) */
/* 962 */ 0x8, /* FC_LONG */
FC_LONG */
/* 964 */ 0x6, /* FC_SHORT */

```

```

FC_SHORT */
/* 966 */ 0x6, /* FC_SHORT */
FC_SHORT */
/* 968 */ 0x4c, /* FC_EMBEDDED_COMPLEX */
0 */
/* 970 */ NdrPcShort( 0xfffffc3c ), /* Offset= -
964 (6) */
/* 972 */ 0x5c, /* FC_PAD */
FC_END */
/* 974 */ 0xb4, /* FC_USER_MARSHAL */
131 */
/* 976 */ NdrPcShort( 0x0 ), /* 0 */
/* 978 */ NdrPcShort( 0x18 ), /* 24 */
/* 980 */ NdrPcShort( 0x0 ), /* 0 */
/* 982 */ NdrPcShort( 0xfffffc2c ), /* Offset= -
980 (2) */
/* 984 */
FC_RP [allocated_on_stack] */
/* 986 */ NdrPcShort( 0x6 ), /* Offset= 6 (992) */
/* 988 */
FC_OP */
/* 990 */ NdrPcShort( 0xfffffddc ), /* Offset= -
36 (954) */
/* 992 */ 0xb4, /* FC_USER_MARSHAL */
131 */
/* 994 */ NdrPcShort( 0x0 ), /* 0 */
/* 996 */ NdrPcShort( 0x18 ), /* 24 */
/* 998 */ NdrPcShort( 0x0 ), /* 0 */
/* 1000 */ NdrPcShort( 0xffffffff4 ), /*
Offset= -12 (988) */
0x0
};
static const USER_MARSHAL_ROUTINE_QUADRUPLE
UserMarshalRoutines[ WIRE_MARSHAL_TABLE_SIZE ] =
{
    {
        VARIANT_UserSize
        ,VARIANT_UserMarshal
        ,VARIANT_UserUnmarshal
        ,VARIANT_UserFree
    }
};
/* Standard interface: __MIDL_itf_tpcc_com_ps_0000,
ver. 0.0,

```

```

GUID={0x00000000,0x0000,0x0000,{0x00,0x00,0x00,0x00,0
x00,0x00,0x00,0x00}} */
/* Object interface: IUnknown, ver. 0.0,
GUID={0x00000000,0x0000,0x0000,{0xc0,0x00,0x00,0x00,0
x00,0x00,0x00,0x46}} */
/* Object interface: ITPCC, ver. 0.0,
GUID={0xFEEB6AA2,0x84B1,0x11d2,{0xBA,0x47,0x00,0xC0,0
x4F,0xBF,0xE0,0x8B}} */
#pragma code_seg(".orpc")
static const unsigned short
ITPCC_FormatStringOffsetTable =
{
    0,
    44,
    88,
    132,
    176,
    220
};
static const MIDL_STUBLESS_PROXY_INFO ITPCC_ProxyInfo
=
{
    &Object_StubDesc,
    _MIDL_ProcFormatString.Format,
    &ITPCC_FormatStringOffsetTable[-3],
    0,
    0,
    0
};
static const MIDL_SERVER_INFO ITPCC_ServerInfo =
{
    &Object_StubDesc,
    0,
    _MIDL_ProcFormatString.Format,
    &ITPCC_FormatStringOffsetTable[-3],
    0,
    0,
    0,
    0
};
CINTERFACE_PROXY_VTABLE(9) _ITPCCProxyVtbl =
{
    &ITPCC_ProxyInfo,
    &IID_ITPCC,
    IUnknown_QueryInterface_Proxy,
    IUnknown_AddRef_Proxy,
    IUnknown_Release_Proxy ,
    (void *) (INT_PTR) -1 /* ITPCC::NewOrder */ ,
    (void *) (INT_PTR) -1 /* ITPCC::Payment */ ,
    (void *) (INT_PTR) -1 /* ITPCC::Delivery */ ,
    (void *) (INT_PTR) -1 /* ITPCC::StockLevel */ ,

```

```

        (void *) (INT_PTR) -1 /* ITPCC::OrderStatus */,
        (void *) (INT_PTR) -1 /* ITPCC::CallSetComplete
*/
};

const CInterfaceStubVtbl _ITPCCStubVtbl =
{
    &IID_ITPCC,
    &ITPCC_ServerInfo,
    9,
    0, /* pure interpreted */
    CStdStubBuffer_METHODS
};

static const MIDL_STUB_DESC Object_StubDesc =
{
    0,
    NdrOleAllocate,
    NdrOleFree,
    0,
    0,
    0,
    0,
    0,
    0,
    0,
    0,
    _MIDL_TypeFormatString.Format,
    1, /* -error bounds_check flag */
    0x50002, /* Ndr library version */
    0,
    0x600015b, /* MIDL Version 6.0.347 */
    0,
    UserMarshalRoutines,
    0, /* notify & notify_flag routine table */
    0x1, /* MIDL flag */
    0, /* cs routines */
    0, /* proxy/server info */
    0 /* Reserved5 */
};

const CInterfaceProxyVtbl *
_tpcc_com_ps_ProxyVtblList[] =
{
    ( CInterfaceProxyVtbl *) &ITPCCProxyVtbl,
    0
};

const CInterfaceStubVtbl *
_tpcc_com_ps_StubVtblList[] =
{
    ( CInterfaceStubVtbl *) &ITPCCStubVtbl,
    0
};

PCInterfaceName const
_tpcc_com_ps_InterfaceNamesList[] =
{
    "ITPCC",
    0
};

```

```

#define _tpcc_com_ps_CHECK_IID(n)
    IID_GENERIC_CHECK_IID( _tpcc_com_ps, piID,
n)

int __stdcall _tpcc_com_ps_IID_Lookup( const IID *
piID, int * pIndex )
{
    if(! _tpcc_com_ps_CHECK_IID(0))
    {
        *pIndex = 0;
        return 1;
    }

    return 0;
}

const ExtendedProxyFileInfo tpcc_com_ps_ProxyFileInfo =
{
    (PCInterfaceProxyVtblList *) &
_tpcc_com_ps_ProxyVtblList,
    (PCInterfaceStubVtblList *) &
_tpcc_com_ps_StubVtblList,
    (const PCInterfaceName *) &
_tpcc_com_ps_InterfaceNamesList,
    0, // no delegation
    & _tpcc_com_ps_IID_Lookup,
    1,
    2,
    0, /* table of [async_uuid] interfaces */
    0, /* Filler1 */
    0, /* Filler2 */
    0 /* Filler3 */
};

#endif /* defined(_M_IA64) || defined(_M_AMD64) */

```

tpcc_com_sl.rg

S

```

HKCR
{
    TPCC.StockLevel.1 = s 'StockLevel Class'
    {
        CLSID = s '{2668369E-A50D-11D2-
BA4E-00C04FBFE08B}'
    }
    TPCC.StockLevel = s 'StockLevel Class'
    {
        CurVer = s 'TPCC.StockLevel.1'
    }
    NoRemove CLSID
    {
        ForceRemove {2668369E-A50D-11D2-
BA4E-00C04FBFE08B} = s 'StockLevel Class'

```

```

        {
            ProgID = s
            'TPCC.StockLevel.1'

            VersionIndependentProgID = s
            'TPCC.StockLevel'

            InprocServer32 = s
            '%MODULE%'
            {
                val
                ThreadingModel = s 'Both'
            }
        }
    }
}

```

tpcc_dblib.cpp

```

/* FILE: TPCC_DBLIB.CPP
* Microsoft
* TPC-C Kit Ver. 4.42.000
* Copyright
* Microsoft, 2002
* All Rights Reserved
* Version
* 4.10.000 audited by Richard Gimarc, Performance
Metrics, 3/17/99
*
* PURPOSE: Implements dblib calls for TPC-C
txns.
* Contact: Charles Levine
(clevine@microsoft.com)
*
* Change history:
* 4.42.000 - changed w_id fields
from short to long to support >32K warehouses
* 4.20.000 - updated rev number to
match kit
* 4.10.001 - not deleting error
class in catch handler on deadlock retry;
* not a
functional bug, but a memory leak
* - had to
tweak some declarations to compile with latest SDK;
no functional change
*/

#include <windows.h>
#include <stdio.h>
#include <assert.h>

#define DBNTWIN32
#include <sqlfront.h>
#include <sqlldb.h>

#ifdef ICECAP
#include <icapexp.h>
#endif

```



```

// need to declare functions for export
#define DllDecl __declspec( dllexport )

#include "..\..\common\src\error.h"
#include "..\..\common\src\trans.h"
#include "..\..\common\src\txn_base.h"
#include "tpcc_dblib.h"

#define DEFCLPCKSIZE
4096

// version string; must match return value from
tpcc_version stored proc
const char sVersion[] = "4.20.000";

const iMaxRetries = 10;
// how many retries on deadlock
static long iConnectionCount = 0; // number
of current dblib connections

const int iErrOleDbProvider = 7312;
const char sErrTimeoutExpired[] = "Timeout expired";

BOOL APIENTRY DllMain(HMODULE hModule, DWORD
ul_reason_for_call, LPVOID lpReserved)
{
    switch( ul_reason_for_call )
    {
        case DLL_PROCESS_ATTACH:
            DisableThreadLibraryCalls(hModule);
            dbinit(); //
            initialize dblib
            break;
        case DLL_PROCESS_DETACH:
            dbexit(); //
            close all dblib structures/connections
            break;
        default:
            /* nothing */;
    }
    return TRUE;
}

int err_handler(DBPROCESS *dbproc, int severity, int
dberr, int oserr, LPCSTR dberrstr, LPCSTR oserrstr)
{
    CTPCC_DBLIB
    *pConn;
    assert(dbproc != NULL);
    pConn =
    (CTPCC_DBLIB*)dbgetuserdata(dbproc);
    if (pConn != NULL)
    {
        pConn->SetDbLibError( severity,
        dberr, oserr, dberrstr, oserrstr );
    }
}

```

```

}
return INT_CANCEL;
}

/* FUNCTION: int msg_handler(DBPROCESS *dbproc, DBINT
msgno, int msgstate, int severity, char *msgtext)
*
* PURPOSE: This function handles DB-Library
SQL Server error messages
*
* ARGUMENTS: DBPROCESS *dbproc
DBPROCESS id pointer
DBINT
message number
message state
message severity
message description
*
* RETURNS: int
INT_CONTINUE continue if
error is SQLETIME else INT_CANCEL action
INT_CANCEL
cancel operation
*
* COMMENTS: This function also sets the dead
lock dbproc variable if necessary.
*/

// typedef INT (SQLAPI *DBMSGHANDLE_PROC) (PDBPROCESS,
DBINT, INT, INT, LPCSTR, LPCSTR, LPCSTR,
DBUSMALLINT);

int msg_handler(DBPROCESS *dbproc, DBINT msgno, int
msgstate, int severity,
LPCSTR
msgtext, LPCSTR srvname, LPCSTR procname, DBUSMALLINT
line)
{
    CTPCC_DBLIB
    *pConn;
    assert(dbproc != NULL);
    pConn =
    (CTPCC_DBLIB*)dbgetuserdata(dbproc);
    if (pConn != NULL)
    {
        pConn->SetSqlError( msgno,
        msgstate, severity, msgtext );
    }
    return 0;
}

```

```

}

/* FUNCTION: void UtilStrCpy(char * pDest, char *
pSrc, int n)
*
* PURPOSE: This function copies n characters
from string pSrc to pDest and places a
null character at the
end of the destination string.
*
* ARGUMENTS: char
* pDest destination string pointer
char
* pSrc source string pointer
int
n
number of characters to copy
*
* RETURNS: None
*
* COMMENTS: Unlike strncpy this function
ensures that the result string is
always null
terminated.
*/

inline static void UtilStrCpy(char * pDest, const
BYTE * pSrc, int n)
{
    strncpy(pDest, (char *)pSrc, n);
    pDest[n] = '\0';
    return;
}

/* FUNCTION: CTPCC_DBLIB_ERR::ErrorText
*
*/

char* CTPCC_DBLIB_ERR::ErrorText(void)
{
    int i;
    static SERRORMSG errorMsgs[] =
    {
        { ERR_WRONG_SP_VERSION,
        "Wrong version of stored procs on database
server" },
        { ERR_INVALID_CUST,
        "Invalid Customer id,name." },
        { ERR_NO_SUCH_ORDER,
        "No orders found for customer." },
        { ERR_RETRIED_TRANS,
        "Retries before transaction succeeded." },
        { 0, "" }
    },
}

```

```

    }
};
static char szNotFound[] = "Unknown error
number.";
for(i=0; errorMsgs[i].szMsg[0]; i++)
{
    if ( m_errno ==
errorMsgs[i].iError )
        break;
}
if ( !errorMsgs[i].szMsg[0] )
    return szNotFound;
else
    return errorMsgs[i].szMsg;
}

// wrapper routine for class constructor
__declspec(dllexport) CTPCC_DBLIB* CTPCC_DBLIB_new(
LPCSTR szServer, // name of
SQL server
LPCSTR szUser, //
user name for login
LPCSTR szPassword, // password
for login
LPCSTR szHost, //
workstation name; shows up in sp_who; max 30 chars,
only first 10 kept by SQL Server
LPCSTR szDatabase ) // name of
database to use
{
    return new CTPCC_DBLIB( szServer, szUser,
szPassword, szHost, szDatabase );
}

CTPCC_DBLIB::CTPCC_DBLIB (
LPCSTR szServer, // name of
SQL server
LPCSTR szUser, //
user name for login
LPCSTR szPassword, // password
for login
LPCSTR szHost, //
workstation name; shows up in sp_who; max 30 chars,
only first 10 kept by SQL Server
LPCSTR szDatabase ) // name of
database to use
{
    LOGINREC *login;
    const BYTE *pData;

    // initialization
    m_dbproc = NULL;
    m_DbLibErr = (CDBLIBERR*)NULL;
    m_SqlErr = (CSQLERR*)NULL;

    m_MaxRetries = 10; // how many
retries on deadlock

```

```

// increase max number of connections if
getting close
if ( dbgetmaxprocs() < (iConnectionCount+5)
)
{
    if (
dbsetmaxprocs(iConnectionCount+10) == FAIL )

        ThrowError(CDBLIBERR::eDbSetMaxProcs);
}

// allocate a login structure
login = dblogin();
if (login == NULL)
    ThrowError(CDBLIBERR::eLogin);
InterlockedIncrement( &iConnectionCount );

// register error and message handler
functions
if (dbprocerrhandle(login, err_handler) ==
NULL)
    ThrowError(CDBLIBERR::eDbProcHandler);

if (dbprocmsghandle(login, msg_handler) ==
NULL)
    ThrowError(CDBLIBERR::eDbProcHandler);

DBSETLUSER(login, szUser);
DBSETLPWD(login, szPassword);
DBSETLHOST(login, szHost);
DBSETLPACKET(login, (unsigned
short)DEFCLPACKSIZE);
DBSETLVERSION(login, DBVER60);
// use dblib ver 6.0 client behavior

// set time to wait for login
if (dbsetlogintime(60) == FAIL)
    ThrowError(CDBLIBERR::eDbSet);

// set time to wait for statement execution
if (dbsettime(180) == FAIL)
    ThrowError(CDBLIBERR::eDbSet);

m_dbproc = dbopen(login, szServer);

// deallocate login structure before
checking for success
dbfreelogin( login );

if (m_dbproc == NULL)
    ThrowError(CDBLIBERR::eDbOpen);

// save address of class instance so that
the message and error handler
// can get to data.
dbsetuserdata(m_dbproc, (LPVOID)this);

```

```

// Use the the right database
if (dbuse(m_dbproc, szDatabase) == FAIL)
    ThrowError(CDBLIBERR::eDbUse);

dbcmd(m_dbproc, "set nocount on ");
// do not return row counts
dbcmd(m_dbproc, "set XACT_ABORT ON");
// rollback transaction on abort

if (dbsqlxexec(m_dbproc) == FAIL)
    ThrowError(CDBLIBERR::eDbSqlExec);

DiscardNextResults(2);

// verify that version of stored procs on
server is correct
dbrpcinit(m_dbproc, "tpcc_version", 0);
if (dbrpcexec(m_dbproc) == FAIL)
    ThrowError(CDBLIBERR::eDbRpcExec);

if (dbresults(m_dbproc) != SUCCEED)
    ThrowError(CDBLIBERR::eDbResults);

if (dbnextrow(m_dbproc) != REG_ROW)
    ThrowError(CDBLIBERR::eDbNextRow);

char szSrvVersion[16];
pData=dbdata(m_dbproc, 1);
if (pData)
    UtilStrCpy(szSrvVersion, pData,
dbdatlen(m_dbproc, 1));
else
    szSrvVersion[0]=0;
if (strcmp(szSrvVersion,sVersion))
    throw new CTPCC_DBLIB_ERR(
CTPCC_DBLIB_ERR::ERR_WRONG_SP_VERSION );

DiscardNextRows(0);
DiscardNextResults(0);
}

CTPCC_DBLIB::~CTPCC_DBLIB( void )
{
    // close db connection and deallocate
resources
    dbclose(m_dbproc);
    InterlockedDecrement( &iConnectionCount );
    if (m_DbLibErr != NULL)
        delete m_DbLibErr;
    if (m_SqlErr != NULL)
        delete m_SqlErr;
}

```

```

void CTPCC_DBLIB::SetDbLibError(int severity, int
dberr, int oserr, LPCSTR dberrstr, LPCSTR oserrstr)
{
    delete m_DbLibErr;
    m_DbLibErr = new
CDBLIBERR(CDBLIBERR::eUnknown, severity, dberr,
oserr);

    if (dberrstr != NULL)
    {
        m_DbLibErr->m_dberrstr = new
char[ strlen(dberrstr)+1 ];
        strcpy( m_DbLibErr->m_dberrstr,
dberrstr );
    }

    if (oserrstr != NULL)
    {
        m_DbLibErr->m_oserrstr = new
char[ strlen(oserrstr)+1 ];
        strcpy( m_DbLibErr->m_oserrstr,
oserrstr );
    }
}

void CTPCC_DBLIB::SetSqlError( int /*DBINT*/ msgno,
int msgstate, int severity, LPCSTR msgtext )
{
    if (m_SqlErr == NULL)
        m_SqlErr = new CSQLERR();

    m_SqlErr->m_msgno = msgno;
    m_SqlErr->m_msgstate = msgstate;
    m_SqlErr->m_severity = severity;

    delete [] m_SqlErr->m_msgtext;
    if (msgtext != NULL)
    {
        m_SqlErr->m_msgtext = new char[
strlen(msgtext)+1 ];
        strcpy( m_SqlErr->m_msgtext,
msgtext );
    }
}

void CTPCC_DBLIB::ThrowError( CDBLIBERR::ACTION
eAction )
{
    // discard anything still in return buffer
    DiscardNextRows(-1);
    DiscardNextResults(-1);

    // check for SQL Server error first; if
yes, throw it and ignore any DBLib error.
    if (m_SqlErr != NULL)
    {
        CSQLERR *pSqlErr;
        pSqlErr = m_SqlErr;
        m_SqlErr = NULL; // clear our
pointer to instance; catch handler will delete

```

```

        throw pSqlErr;
    }

    CDBLIBERR *pDbLibErr;
    if (m_DbLibErr == NULL)
        // this case isn't expected to
happen, since it means that an error was returned
        // but the error handlers were
        not called.
        pDbLibErr = new
CDBLIBERR(eAction);
    else
    {
        pDbLibErr = m_DbLibErr;
        pDbLibErr->m_eAction = eAction;
        m_DbLibErr = NULL; //
clear our pointer to instance; catch handler will
delete
    }

    throw pDbLibErr;
}

// Read and discard rows until no more. Throw an
exception if number of rows read doesn't
// match number of rows expected. The row count will
be ignored if the expected count value
// passed in is negative. A typical use of this
routine is to verify that there are no more
// rows to be read.
void CTPCC_DBLIB::DiscardNextRows(int iExpectedCount)
{
    int iRowsRead = 0;
    RETCODE rc;

    while (TRUE)
    {
        rc = dbnextrow(m_dbproc);
        if (rc == NO_MORE_ROWS)
            break;
        if (rc == FAIL)
        {
            if (iExpectedCount >=
0)

                ThrowError(CDBLIBERR::eDbNextRow);
            else
                break;
        }
        iRowsRead++;
    }

    if ((iExpectedCount >= 0) &&
(iExpectedCount != iRowsRead))

        ThrowError(CDBLIBERR::eWrongRowCount);
}

// Read and discard results until no more. Throw an
exception if number of result sets read doesn't

```

```

// match number expected. The result set count will
be ignored if the expected count value
// passed in is negative. A typical use of this
routine is to verify that there are no more
// result sets to be read.
void CTPCC_DBLIB::DiscardNextResults(int
iExpectedCount)
{
    int iResultsRead = 0;
    RETCODE rc;

    while (TRUE)
    {
        rc = dbresults(m_dbproc);
        if (rc == NO_MORE_RESULTS)
            break;
        if (rc == FAIL)
        {
            if (iExpectedCount >=
0)

                ThrowError(CDBLIBERR::eDbResults);
            else
                break;
        }

        DiscardNextRows(-1);
        iResultsRead++;
    }

    if ((iExpectedCount >= 0) &&
(iExpectedCount != iResultsRead))

        ThrowError(CDBLIBERR::eWrongRowCount);
}

void CTPCC_DBLIB::StockLevel()
{
    int iTryCount =
0;
    const BYTE *pData;

    ResetError();

    while (TRUE)
    {
        try
        {
            dbrpcinit(m_dbproc,
"tpcc_stocklevel", 0);

            dbrpcparam(m_dbproc,
NULL, 0, SQLINT4, -1, -1, (BYTE *)
&m_txn.StockLevel.w_id); // @w_id int
            dbrpcparam(m_dbproc,
NULL, 0, SQLINT1, -1, -1, (BYTE *)
&m_txn.StockLevel.d_id); // @d_id
            tinyint
            dbrpcparam(m_dbproc,
NULL, 0, SQLINT2, -1, -1, (BYTE *)

```

```

&m_txn.StockLevel.threshold); // @threshold
smallint
    if (dbrpcexec(m_dbproc)
== FAIL)
    ThrowError(CDBLIBERR::eDbRpcExec);
    if (dbresults(m_dbproc)
!= SUCCEEDED)
    ThrowError(CDBLIBERR::eDbResults);
    if (dbnextrow(m_dbproc)
!= REG_ROW)
    ThrowError(CDBLIBERR::eDbNextRow);
    if
(pData=dbdata(m_dbproc, 1))
    m_txn.StockLevel.low_stock = *((long *)
pData);
    DiscardNextRows(0);
    DiscardNextResults(0);
    m_txn.StockLevel.exec_status_code = eOK;
    return;
}
catch (CSQLERR *e)
{
    if ((e->m_msgno == 1205
||
    (e->m_msgno
== iErrOleDbProvider &&
    strstr(e-
>m_msgtext, sErrTimeoutExpired) != NULL)) &&
    (++iTryCount
<= iMaxRetries))
    {
        // hit
        deadlock; backoff for increasingly longer period
        delete e;
        Sleep(10 *
iTryCount);
    }
    else
        throw;
}
// while (TRUE)
//if (iTryCount)
//    throw new
CTPCC_DBLIB_ERR(CTPCC_DBLIB_ERR::ERR_RETRIED_TRANS,
iTryCount);
}
void CTPCC_DBLIB::NewOrder()

```

```

{
    int i;
    DBINT commit_flag;
    DBDATETIME datetime;
    DBDATETIME daterec;
    int iTryCount =
0;
    const BYTE *pData;
    ResetError();
    while (TRUE)
    {
        try
        {
            dbrpcinit(m_dbproc,
"tpcc_neworder", 0);
            dbrpcparam(m_dbproc,
NULL, 0, SQLINT4, -1, -1, (BYTE *)
&m_txn.NewOrder.w_id);
            dbrpcparam(m_dbproc,
NULL, 0, SQLINT1, -1, -1, (BYTE *)
&m_txn.NewOrder.d_id);
            dbrpcparam(m_dbproc,
NULL, 0, SQLINT4, -1, -1, (BYTE *)
&m_txn.NewOrder.c_id);
            dbrpcparam(m_dbproc,
NULL, 0, SQLINT1, -1, -1, (BYTE *)
&m_txn.NewOrder.o_ol_cnt);
            // check whether any
            order lines are for a remote warehouse
            m_txn.NewOrder.o_all_local = 1;
            for (i = 0; i <
m_txn.NewOrder.o_ol_cnt; i++)
            {
                if
(m_txn.NewOrder.OL[i].ol_supply_w_id !=
m_txn.NewOrder.w_id)
                {
                    m_txn.NewOrder.o_all_local = 0; // at
                    least one remote warehouse
                    break;
                }
            }
            dbrpcparam(m_dbproc,
NULL, 0, SQLINT1, -1, -1, (BYTE *)
&m_txn.NewOrder.o_all_local);
            for (i = 0; i <
m_txn.NewOrder.o_ol_cnt; i++)
            {
                dbrpcparam(m_dbproc, NULL, 0, SQLINT4, -1,
-1, (BYTE *) &m_txn.NewOrder.OL[i].ol_i_id);

```

```

            dbrpcparam(m_dbproc, NULL, 0, SQLINT4, -1,
-1, (BYTE *) &m_txn.NewOrder.OL[i].ol_supply_w_id);
            dbrpcparam(m_dbproc, NULL, 0, SQLINT2, -1,
-1, (BYTE *) &m_txn.NewOrder.OL[i].ol_quantity);
        }
    }
    if (dbrpcexec(m_dbproc)
== FAIL)
    ThrowError(CDBLIBERR::eDbRpcExec);
    // Get order line
    results
    m_txn.NewOrder.total_amount = 0;
    for (i = 0;
i < m_txn.NewOrder.o_ol_cnt; i++)
    {
        if
(dbresults(m_dbproc) != SUCCEEDED)
        ThrowError(CDBLIBERR::eDbResults);
        if
(dbnumcols(m_dbproc) != 5)
        ThrowError(CDBLIBERR::eWrongNumCols);
        if
(dbnextrow(m_dbproc) != REG_ROW)
        ThrowError(CDBLIBERR::eDbNextRow);
        if (pData=dbdata(m_dbproc, 1))
        UtilStrCpy(m_txn.NewOrder.OL[i].ol_i_name,
pData, dbdatlen(m_dbproc, 1));
        if (pData=dbdata(m_dbproc, 2))
        m_txn.NewOrder.OL[i].ol_stock =
(*(DBSMALLINT *) pData);
        if (pData=dbdata(m_dbproc, 3))
        UtilStrCpy(m_txn.NewOrder.OL[i].ol_brand_ge
neric, pData, dbdatlen(m_dbproc, 3));
        if (pData=dbdata(m_dbproc, 4))
        dbconvert(m_dbproc, SQLNUMERIC,
(LPBYTE)pData, dbdatlen(m_dbproc, 4),
SQLFLT8, (BYTE
*)&m_txn.NewOrder.OL[i].ol_i_price, 8);
        if (pData=dbdata(m_dbproc, 5))

```

```

        dbconvert(m_dbproc, SQLNUMERIC,
(LPCBYTE)pData, dbdatlen(m_dbproc, 5),
        SQLFLT8, (BYTE
*)&m_txn.NewOrder.OL[i].ol_amount, 8);

        m_txn.NewOrder.total_amount =
m_txn.NewOrder.total_amount +
m_txn.NewOrder.OL[i].ol_amount;

        DiscardNextRows(0);
    }

    // get remaining values
for w_tax, d_tax, o_id, c_last, c_discount, c_credit,
o_entry_d, commit_flag
if (dbresults(m_dbproc)
!= SUCCEEDED)
    ThrowError(CDBLIBERR::eDbResults);
if (dbnextrow(m_dbproc)
!= REG_ROW)
    ThrowError(CDBLIBERR::eDbNextRow);
if (dbnumcols(m_dbproc)
!= 8)
    ThrowError(CDBLIBERR::eWrongNumCols);

    if
(pData=dbdata(m_dbproc, 1))

        dbconvert(m_dbproc, SQLNUMERIC,
(LPCBYTE)pData, dbdatlen(m_dbproc,1), SQLFLT8, (BYTE
*)&m_txn.NewOrder.w_tax, 8);
    if
(pData=dbdata(m_dbproc, 2))

        dbconvert(m_dbproc, SQLNUMERIC,
(LPCBYTE)pData, dbdatlen(m_dbproc,2), SQLFLT8, (BYTE
*)&m_txn.NewOrder.d_tax, 8);
    if
(pData=dbdata(m_dbproc, 3))

        m_txn.NewOrder.o_id = *(DBINT *) pData);
    if
(pData=dbdata(m_dbproc, 4))

```

```

        UtilStrCpy(m_txn.NewOrder.c_last, pData,
dbdatlen(m_dbproc, 4));
    if
(pData=dbdata(m_dbproc, 5))

        dbconvert(m_dbproc, SQLNUMERIC,
(LPCBYTE)pData, dbdatlen(m_dbproc,5), SQLFLT8, (BYTE
*)&m_txn.NewOrder.c_discount, 8);
    if
(pData=dbdata(m_dbproc, 6))

        UtilStrCpy(m_txn.NewOrder.c_credit, pData,
dbdatlen(m_dbproc, 6));
    if
(pData=dbdata(m_dbproc, 7))
    {
        datetime =
*(DBDATETIME *) pData);
        dbdatecrack(m_dbproc, &daterec, &datetime);
        m_txn.NewOrder.o_entry_d.year =
daterec.year;
        m_txn.NewOrder.o_entry_d.month =
daterec.month;
        m_txn.NewOrder.o_entry_d.day =
daterec.day;
        m_txn.NewOrder.o_entry_d.hour =
daterec.hour;
        m_txn.NewOrder.o_entry_d.minute =
daterec.minute;
        m_txn.NewOrder.o_entry_d.second =
daterec.second;
    }
    if
(pData=dbdata(m_dbproc, 8))
        commit_flag =
*(DBTINYINT *) pData);
        DiscardNextRows(0);
        DiscardNextResults(0);
        if (commit_flag == 1)
        {
            m_txn.NewOrder.total_amount *= ((1 +
m_txn.NewOrder.w_tax + m_txn.NewOrder.d_tax) * (1 -
m_txn.NewOrder.c_discount));
            m_txn.NewOrder.exec_status_code = eOK;
        }
        else

```

```

        m_txn.NewOrder.exec_status_code =
eInvalidItem;
        return;
    }
    catch (CSQLERR *e)
    {
        if ((e->m_msgno == 1205
||
(e->m_msgno
== iErrOleDbProvider &&
strstr(e-
>m_msgtext, sErrTimeoutExpired) != NULL) &&
(++iTryCount
<= iMaxRetries))
        {
            // hit
            deadlock; backoff for increasingly longer period
            delete e;
            Sleep(10 *
iTryCount);
        }
        else
            throw;
    }
    // while (TRUE)
    // if (iTryCount)
    // throw new
CTPCC_DBLIB_ERR(CTPCC_DBLIB_ERR::ERR_RETRIED_TRANS,
iTryCount);
}

void CTPCC_DBLIB::Payment()
{
    DBDATETIME datetime;
    DBDATEREC daterec;

    int iTryCount =
0;
    const BYTE *pData;
    ResetError();
    while (TRUE)
    {
        try
        {
            dbrpcinit(m_dbproc,
"tpcc_payment", 0);
            dbrpcparam(m_dbproc,
NULL, 0, SQLINT4, -1, -1, (BYTE *)
&m_txn.Payment.w_id);
            dbrpcparam(m_dbproc,
NULL, 0, SQLINT4, -1, -1, (BYTE *)
&m_txn.Payment.c_w_id);

```

```

        dbrpcparam(m_dbproc,
NULL, 0, SQLFLT8, -1, -1, (BYTE *)
&m_txn.Payment.h_amount);
        dbrpcparam(m_dbproc,
NULL, 0, SQLINT1, -1, -1, (BYTE *)
&m_txn.Payment.d_id);
        dbrpcparam(m_dbproc,
NULL, 0, SQLINT1, -1, -1, (BYTE *)
&m_txn.Payment.c_d_id);
        dbrpcparam(m_dbproc,
NULL, 0, SQLINT4, -1, -1, (BYTE *)
&m_txn.Payment.c_id);

// if customer id is
zero, then payment is by name
if (m_txn.Payment.c_id
== 0)

        dbrpcparam(m_dbproc, NULL, 0, SQLCHAR, -1,
strlen(m_txn.Payment.c_last), (unsigned char
*)m_txn.Payment.c_last);

== FAIL)
        if (dbrpcexec(m_dbproc)
ThrowError(CDBLIBERR::eDbRpcExec);

        if (dbresults(m_dbproc)
!= SUCCEED)
        ThrowError(CDBLIBERR::eDbResults);

        if (dbnextrow(m_dbproc)
!= REG_ROW)
        ThrowError(CDBLIBERR::eDbNextRow);

        if (dbnumcols(m_dbproc)
!= 27)
        ThrowError(CDBLIBERR::eWrongNumCols);

        if
(pData=dbdata(m_dbproc, 1))
        m_txn.Payment.c_id = *((DBINT *) pData);
        if
(pData=dbdata(m_dbproc, 2))
        UtilStrCpy(m_txn.Payment.c_last, pData,
dbdatlen(m_dbproc, 2));
        if
(pData=dbdata(m_dbproc, 3))
        {
                datetime =
*((DBDATETIME *) pData);
                dbdatecrack(m_dbproc, &daterec, &datetime);
                m_txn.Payment.h_date.year = daterec.year;

```

```

        m_txn.Payment.h_date.month =
daterec.month;
        m_txn.Payment.h_date.day = daterec.day;
        m_txn.Payment.h_date.hour = daterec.hour;
        m_txn.Payment.h_date.minute =
daterec.minute;
        m_txn.Payment.h_date.second =
daterec.second;
        }
        if
(pData=dbdata(m_dbproc, 4))
        UtilStrCpy(m_txn.Payment.w_street_1, pData,
dbdatlen(m_dbproc, 4));
        if
(pData=dbdata(m_dbproc, 5))
        UtilStrCpy(m_txn.Payment.w_street_2, pData,
dbdatlen(m_dbproc, 5));
        if
(pData=dbdata(m_dbproc, 6))
        UtilStrCpy(m_txn.Payment.w_city, pData,
dbdatlen(m_dbproc, 6));
        if
(pData=dbdata(m_dbproc, 7))
        UtilStrCpy(m_txn.Payment.w_state, pData,
dbdatlen(m_dbproc, 7));
        if
(pData=dbdata(m_dbproc, 8))
        UtilStrCpy(m_txn.Payment.w_zip, pData,
dbdatlen(m_dbproc, 8));
        if
(pData=dbdata(m_dbproc, 9))
        UtilStrCpy(m_txn.Payment.d_street_1, pData,
dbdatlen(m_dbproc, 9));
        if
(pData=dbdata(m_dbproc, 10))
        UtilStrCpy(m_txn.Payment.d_street_2, pData,
dbdatlen(m_dbproc, 10));
        if
(pData=dbdata(m_dbproc, 11))
        UtilStrCpy(m_txn.Payment.d_city, pData,
dbdatlen(m_dbproc, 11));
        if
(pData=dbdata(m_dbproc, 12))
        UtilStrCpy(m_txn.Payment.d_state, pData,
dbdatlen(m_dbproc, 12));
        if
(pData=dbdata(m_dbproc, 13))

```

```

        UtilStrCpy(m_txn.Payment.d_zip, pData,
dbdatlen(m_dbproc, 13));
        if
(pData=dbdata(m_dbproc, 14))
        UtilStrCpy(m_txn.Payment.c_first, pData,
dbdatlen(m_dbproc, 14));
        if
(pData=dbdata(m_dbproc, 15))
        UtilStrCpy(m_txn.Payment.c_middle, pData,
dbdatlen(m_dbproc, 15));
        if
(pData=dbdata(m_dbproc, 16))
        UtilStrCpy(m_txn.Payment.c_street_1, pData,
dbdatlen(m_dbproc, 16));
        if
(pData=dbdata(m_dbproc, 17))
        UtilStrCpy(m_txn.Payment.c_street_2, pData,
dbdatlen(m_dbproc, 17));
        if
(pData=dbdata(m_dbproc, 18))
        UtilStrCpy(m_txn.Payment.c_city, pData,
dbdatlen(m_dbproc, 18));
        if
(pData=dbdata(m_dbproc, 19))
        UtilStrCpy(m_txn.Payment.c_state, pData,
dbdatlen(m_dbproc, 19));
        if
(pData=dbdata(m_dbproc, 20))
        UtilStrCpy(m_txn.Payment.c_zip, pData,
dbdatlen(m_dbproc, 20));
        if
(pData=dbdata(m_dbproc, 21))
        UtilStrCpy(m_txn.Payment.c_phone, pData,
dbdatlen(m_dbproc, 21));
        if
(pData=dbdata(m_dbproc, 22))
        {
                datetime =
*((DBDATETIME *) pData);
                dbdatecrack(m_dbproc, &daterec, &datetime);
                m_txn.Payment.c_since.year =
daterec.year;
                m_txn.Payment.c_since.month =
daterec.month;
                m_txn.Payment.c_since.day = daterec.day;
                m_txn.Payment.c_since.hour =
daterec.hour;

```

```

        m_txn.Payment.c_since.minute =
daterec.minute;
        m_txn.Payment.c_since.second =
daterec.second;
    }
    if (pData=dbdata(m_dbproc, 23))
        UtilStrCpy(m_txn.Payment.c_credit, pData,
dbdatlen(m_dbproc, 23));
    if (pData=dbdata(m_dbproc, 24))
        dbconvert(m_dbproc, SQLNUMERIC,
(LPCBYTE)pData, dbdatlen(m_dbproc,24), SQLFLT8, (BYTE
*)&m_txn.Payment.c_credit_lim, 8);
    if (pData=dbdata(m_dbproc, 25))
        dbconvert(m_dbproc, SQLNUMERIC,
(LPCBYTE)pData, dbdatlen(m_dbproc,25), SQLFLT8, (BYTE
*)&m_txn.Payment.c_discount, 8);
    if (pData=dbdata(m_dbproc, 26))
        dbconvert(m_dbproc, SQLNUMERIC,
(LPCBYTE)pData, dbdatlen(m_dbproc,26), SQLFLT8, (BYTE
*)&m_txn.Payment.c_balance, 8);
    if (pData=dbdata(m_dbproc, 27))
        UtilStrCpy(m_txn.Payment.c_data, pData,
dbdatlen(m_dbproc, 27));
        DiscardNextRows(0);
        DiscardNextResults(0);
    if (m_txn.Payment.c_id
== 0)
        throw new
CTPCC_DBLIB_ERR( CTPCC_DBLIB_ERR::ERR_INVALID_CUST );
    else
        m_txn.Payment.exec_status_code = eOK;
        return;
    }
    catch (CSQLERR *e)
    {
        if ((e->m_msgno == 1205
        (e->m_msgno
== iErrOleDbProvider &&
        strstr(e-
>m_msgtext, sErrTimeoutExpired) != NULL) &&
        (++iTryCount
<= iMaxRetries))
    {

```

```

        // hit
        deadlock; backoff for increasingly longer period
        delete e;
        Sleep(10 *
iTryCount);
    }
    else
        throw;
    }
    // while (TRUE)
    {
        if (iTryCount)
            throw new
CTPCC_DBLIB_ERR(CTPCC_DBLIB_ERR::ERR_RETRIED_TRANS,
iTryCount);
    }
    void CTPCC_DBLIB::OrderStatus()
    {
        int i;
        DBDATETIME datetime;
        DBDATERECDaterec;
        int iTryCount =
0;
        RETCODE rc;
        const BYTE *pData;
        ResetError();
        while (TRUE)
        {
            try
            {
                dbrpcinit(m_dbproc,
"tpcc_orderstatus", 0);
                dbrpcparam(m_dbproc,
NULL, 0, SQLINT4, -1, -1, (BYTE *)
&m_txn.OrderStatus.w_id);
                dbrpcparam(m_dbproc,
NULL, 0, SQLINT1, -1, -1, (BYTE *)
&m_txn.OrderStatus.d_id);
                dbrpcparam(m_dbproc,
NULL, 0, SQLINT4, -1, -1, (BYTE *)
&m_txn.OrderStatus.c_id);
                // if customer id is
                zero, then order status is by name
                if
(m_txn.OrderStatus.c_id == 0)
                    dbrpcparam(m_dbproc, NULL, 0, SQLCHAR, -1,
strlen(m_txn.OrderStatus.c_last), (unsigned char
*)&m_txn.OrderStatus.c_last);
                if (dbrpcexec(m_dbproc)
== FAIL)

```

```

        ThrowError(CDBLIBERR::eDbRpcExec);
        // Get order lines
        if (dbresults(m_dbproc)
!= SUCCEEDED)
        {
            if
((m_DbLibErr == NULL) && (m_SqlErr == NULL))
                throw new CTPCC_DBLIB_ERR(
CTPCC_DBLIB_ERR::ERR_NO_SUCH_ORDER );
            else
                ThrowError(CDBLIBERR::eDbResults);
        }
        if (dbnumcols(m_dbproc)
!= 5)
            ThrowError(CDBLIBERR::eWrongNumCols);
        i = 0;
        while (TRUE)
        {
            rc =
dbrpcnextrow(m_dbproc);
            if (rc ==
NO_MORE_ROWS)
                break;
            if (rc !=
REG_ROW)
                ThrowError(CDBLIBERR::eDbNextRow);
            if (pData=dbdata(m_dbproc, 1))
                m_txn.OrderStatus.OL[i].ol_supply_w_id =
(* (DBSMALLINT *) pData);
            if (pData=dbdata(m_dbproc, 2))
                m_txn.OrderStatus.OL[i].ol_i_id = (* (DBINT
*) pData);
            if (pData=dbdata(m_dbproc, 3))
                m_txn.OrderStatus.OL[i].ol_quantity =
(* (DBSMALLINT *) pData);
            if (pData=dbdata(m_dbproc, 4))
                dbconvert(m_dbproc, SQLNUMERIC,
(LPCBYTE)pData, dbdatlen(m_dbproc,4),
SQLFLT8, (BYTE
*)&m_txn.OrderStatus.OL[i].ol_amount, 8);
            if (pData=dbdata(m_dbproc, 5))

```

```

        {
            datetime = *((DBDATETIME *) pData);
            dbdatecrack(m_dbproc, &daterec, &datetime);
            m_txn.OrderStatus.OL[i].ol_delivery_d.year
            = daterec.year;
            m_txn.OrderStatus.OL[i].ol_delivery_d.month
            = daterec.month;
            m_txn.OrderStatus.OL[i].ol_delivery_d.day
            = daterec.day;
            m_txn.OrderStatus.OL[i].ol_delivery_d.hour
            = daterec.hour;
            m_txn.OrderStatus.OL[i].ol_delivery_d.minut
            e = daterec.minute;
            m_txn.OrderStatus.OL[i].ol_delivery_d.secon
            d = daterec.second;
        }
        i++;
    }
    m_txn.OrderStatus.o_ol_cnt = i;

    if (dbresults(m_dbproc)
    != SUCCEED)
        ThrowError(CDBLIBERR::eDbResults);
    if (dbnextrow(m_dbproc)
    != REG_ROW)
        ThrowError(CDBLIBERR::eDbNextRow);
    if (dbnumcols(m_dbproc)
    != 8)
        ThrowError(CDBLIBERR::eWrongNumCols);

    if (pData=dbdata(m_dbproc, 1))
        m_txn.OrderStatus.c_id = (*(DBINT *)
        pData);
    if (pData=dbdata(m_dbproc, 2))
        UtilStrCpy(m_txn.OrderStatus.c_last, pData,
        dbdatlen(m_dbproc,2));
    if (pData=dbdata(m_dbproc, 3))
        UtilStrCpy(m_txn.OrderStatus.c_first,
        pData, dbdatlen(m_dbproc,3));

```

```

    if (pData=dbdata(m_dbproc, 4))
        UtilStrCpy(m_txn.OrderStatus.c_middle,
        pData, dbdatlen(m_dbproc, 4));
    if (pData=dbdata(m_dbproc, 5))
        {
            datetime =
            *((DBDATETIME *) pData);
            dbdatecrack(m_dbproc, &daterec, &datetime);
            m_txn.OrderStatus.o_entry_d.year =
            daterec.year;
            m_txn.OrderStatus.o_entry_d.month =
            daterec.month;
            m_txn.OrderStatus.o_entry_d.day =
            daterec.day;
            m_txn.OrderStatus.o_entry_d.hour =
            daterec.hour;
            m_txn.OrderStatus.o_entry_d.minute =
            daterec.minute;
            m_txn.OrderStatus.o_entry_d.second =
            daterec.second;
        }
    if (pData=dbdata(m_dbproc, 6))
        m_txn.OrderStatus.o_carrier_id =
        (*(DBSMALLINT *) pData);
    if (pData=dbdata(m_dbproc, 7))
        dbconvert(m_dbproc, SQLNUMERIC,
        (LPCBYTE)pData, dbdatlen(m_dbproc,7),
        SQLFLT8, (BYTE
        *)&m_txn.OrderStatus.c_balance, 8);
    if (pData=dbdata(m_dbproc, 8))
        m_txn.OrderStatus.o_id = (*(DBINT *)
        pData);
        DiscardNextRows(0);
        DiscardNextResults(0);
        if
        (m_txn.OrderStatus.o_ol_cnt == 0)
            throw new
            CTPCC_DBLIB_ERR( CTPCC_DBLIB_ERR::ERR_NO_SUCH_ORDER
            );

```

```

        else if
        (m_txn.OrderStatus.c_id == 0 &&
        m_txn.OrderStatus.c_last[0] == 0)
            throw new
            CTPCC_DBLIB_ERR( CTPCC_DBLIB_ERR::ERR_INVALID_CUST );
        else
            m_txn.OrderStatus.exec_status_code = eOK;
            return;
        }
        catch (CSQLERR *e)
        {
            if ((e->m_msgno == 1205
            == iErrOleDbProvider &&
            (e->m_msgno
            >m_msgtext, sErrTimeoutExpired) != NULL) &&
            (++iTryCount
            <= iMaxRetries))
                {
                    // hit
                    deadlock; backoff for increasingly longer period
                    delete e;
                    Sleep(10 *
                    iTryCount);
                }
            else
                throw;
        }
        // while (TRUE)
        // if (iTryCount)
        // throw new
        CTPCC_DBLIB_ERR(CTPCC_DBLIB_ERR::ERR_RETRIED_TRANS,
        iTryCount);
    }

    void CTPCC_DBLIB::Delivery()
    {
        int i;
        int iTryCount =
        0;
        const BYTE *pData;
        ResetError();
        while (TRUE)
        {
            try
            {
                dbrpcinit(m_dbproc,
                "tpcc_delivery", 0);
                dbrpcparam(m_dbproc,
                NULL, 0, SQLINT4, -1, -1, (BYTE *)
                &m_txn.Delivery.w_id);
            }

```



```

        dbrpcparam(m_dbproc,
NULL, 0, SQLINT1, -1, -1, (BYTE *)
&m_txn.Delivery.o_carrier_id);

        if (dbrpcexec(m_dbproc)
== FAIL)
            ThrowError(CDBLIBERR::eDbRpcExec);

        if (dbresults(m_dbproc)
!= SUCCEEDED)
            ThrowError(CDBLIBERR::eDbResults);

        if (dbnextrow(m_dbproc)
!= REG_ROW)
            ThrowError(CDBLIBERR::eDbNextRow);

        if (dbnumcols(m_dbproc)
!= 10)
            ThrowError(CDBLIBERR::eWrongNumCols);

        for (i=0; i<10; i++)
        {
            if (pData =
dbdata(m_dbproc, i+1))
                m_txn.Delivery.o_id[i] = *((DBINT *)pData);

            DiscardNextRows(0);
            DiscardNextResults(0);

            m_txn.Delivery.exec_status_code = eOK;
            return;
        }
        catch (CSQLERR *e)
        {
            if ((e->m_msgno == 1205
||
== iErrOleDbProvider &&
>m_msgtext, sErrTimeoutExpired) != NULL) &&
(&& (++iTryCount
<= iMaxRetries))
            {
                // hit
                deadlock; backoff for increasingly longer period
                delete e;
                Sleep(10 *
iTryCount);
            }
            else
                throw;
        }
    } // while (TRUE)

```

```

//      if (iTryCount)
//          throw new
CTPCC_DBLIB_ERR(CTPCC_DBLIB_ERR::ERR_RETRIED_TRANS,
iTryCount);
}

void CTPCC_DBLIB::ResetError()
{
    if (m_DbLibErr != NULL)
    {
        delete m_DbLibErr;
        m_DbLibErr = (CDBLIBERR*)NULL;
    }

    if (m_SqlErr != NULL)
    {
        delete m_SqlErr;
        m_SqlErr = (CSQLERR*)NULL;
    }

    return;
}

```

tpcc_dblib.h

```

/*      FILE:          TPC_C_DBLIB.H
*      Microsoft
*      TPC-C Kit Ver. 4.20.000
*      Copyright
*      Microsoft, 1999
*      All Rights Reserved
*
*      Version
*      4.10.000 audited by Richard Gimarc, Performance
*      Metrics, 3/17/99
*
*      PURPOSE:  Header file for TPC-C txn class
*      implementation.
*
*      Change history:
*      4.20.000 - updated rev number to
*      match kit
*/
#pragma once

#ifndef PDBPROCESS
#define DBPROCESS void // dbprocess structure type
typedef DBPROCESS * PDBPROCESS;
#endif

// need to declare functions for import, unless
// define has already been created
// by the DLL's .cpp module for export.
#ifdef DllDecl
#define DllDecl __declspec( dllimport )
#endif

class CSQLERR : public CBaseErr
{
public:

```

```

    CSQLERR(void)
    {
        m_msgno = 0;
        m_msgstate = 0;
        m_severity = 0;
        m_msgtext = NULL;
    };

    ~CSQLERR()
    {
        delete [] m_msgtext;
    };

    int          m_msgno;
    int          m_msgstate;
    int          m_severity;
    char        *m_msgtext;

    int          ErrorType()
    {return ERR_TYPE_SQL;};
    char*        ErrorTypeStr() { return
"SQL"; };
    int          ErrorNum()
    {return m_msgno;};
    char*        ErrorText() {return
m_msgtext;};
};

class CDBLIBERR : public CBaseErr
{
public:
    enum ACTION
    {
        eNone,
        eUnknown,
        eLogin,
        // error from dblogin
        eDbOpen,
        // error from dbopen
        eDbUse,
        // error from dbuse
        eDbSqlExec,
        // error from dbsqlexec
        eDbSet,
        // error from one of the dbset*
    };

    routines
    {
        eDbNextRow,
        // error from dbnextrow
        eWrongRowCount,
        // more or less rows returned than expected
        eWrongNumCols,
        // more or less columns returned than
        expected
    };

    eDbResults,
    // error from dbresults
    eDbRpcExec,
    // error from dbrpcexec
    eDbSetMaxProcs,
    // error from dbsetmaxprocs
};

```

```

        eDbProcHandler
        // error from either dbprocerrhandle or
        dbprocmsgshandle
    };

    CDBLIBERR(ACTION eAction, int
severity = 0, int dberror = 0, int oserr = 0)
    {
        m_eAction = eAction;
        m_severity = severity;
        m_dberror = dberror;
        m_oserr = oserr;

        m_dberrstr = NULL;
        m_oserrstr = NULL;
    };

    ~CDBLIBERR()
    {
        delete [] m_dberrstr;
        delete [] m_oserrstr;
    };

    ACTION    m_eAction;
    int       m_severity;
    int       m_dberror;
    int       m_oserr;
    char      *m_dberrstr;
    char      *m_oserrstr;

    int       ErrorType()
    {return ERR_TYPE_DBLIB;};
    char*     ErrorTypeStr() { return
"DBLIB"; }
    int       ErrorNum()
    {return m_dberror;};
    char*     ErrorText() {return
m_dberrstr;};
    int       ErrorAction()
    { return (int)m_eAction; }
};

class CTPCC_DBLIB_ERR : public CBaseErr
{
    public:
        enum CTPCC_DBLIB_ERRS
        {
            ERR_WRONG_SP_VERSION =
1, // "Wrong version of stored proc on
database server"
            ERR_INVALID_CUST,
// "Invalid Customer id,name."
            ERR_NO_SUCH_ORDER,
// "No orders found for
customer."
            ERR_RETRIED_TRANS,
// "Retries before transaction
succeeded."
        };
};

```

```

        CTPCC_DBLIB_ERR( int iErr ) {
m_errno = iErr; m_iTryCount = 0; };

    CTPCC_DBLIB_ERR( int iErr, int
iTryCount ) { m_errno = iErr; m_iTryCount =
iTryCount; };

    int       m_errno;
    int       m_iTryCount;

    int       ErrorType()
    {return ERR_TYPE_TPCC_DBLIB;};
    char*     ErrorTypeStr() { return
"TPCC DBLIB"; }
    int       ErrorNum()
    {return m_errno;};

    char*     ErrorText();

class DllDecl CTPCC_DBLIB : public CTPCC_BASE
{
    private:
        // declare variables and private
        functions here...
        PDBPROCESS    m_dbproc;
        CDBLIBERR *m_DbLibErr;
        // not allocated until needed (maybe never)
        CSQLEERR      *m_SqlErr;
        // not allocated until
        needed (maybe never)
        int           m_MaxRetries;
        // retry
        count on deadlock

        void DiscardNextRows(int
iExpectedCount);
        void DiscardNextResults(int
iExpectedCount);
        void ThrowError(
CDBLIBERR::ACTION eAction );
        void ResetError();

    union
    {
        NEW_ORDER_DATA
        NewOrder;
        PAYMENT_DATA
        Payment;
        DELIVERY_DATA
        Delivery;
        STOCK_LEVEL_DATA
        StockLevel;
        ORDER_STATUS_DATA
        OrderStatus;
    };
    m_txn;
    public:

```

```

        CTPCC_DBLIB(LPCSTR szServer,
LPCSTR szUser, LPCSTR szPassword, LPCSTR szHost,
LPCSTR szDatabase );
    ~CTPCC_DBLIB(void);

    inline PNEW_ORDER_DATA
    BuffAddr_NewOrder() { return
&m_txn.NewOrder; };
    inline PPAYMENT_DATA
    BuffAddr_Payment() { return
&m_txn.Payment; };
    inline PDELIVERY_DATA
    BuffAddr_Delivery() { return
&m_txn.Delivery; };
    inline PSTOCK_LEVEL_DATA
    BuffAddr_StockLevel() { return
&m_txn.StockLevel; };
    inline PORDER_STATUS_DATA
    BuffAddr_OrderStatus() { return
&m_txn.OrderStatus; };

    void NewOrder        ();
    void Payment         ();
    void Delivery        ();
    void StockLevel      ();
    void OrderStatus     ();

    // these are public because they
    must be called from the dblib err_handler and
    msg_hangler
    // outside of the class
    void SetDbLibError(int severity,
int dberr, int oserr, LPCSTR dberrstr, LPCSTR
oserrstr);
    void SetSqlError( int msgno, int
msgstate, int severity, LPCSTR msgtext );
};

extern "C" DllDecl CTPCC_DBLIB* CTPCC_DBLIB_new
( LPCSTR szServer, LPCSTR szUser, LPCSTR
szPassword, LPCSTR szHost, LPCSTR szDatabase );

typedef CTPCC_DBLIB* (TYPE_CTPCC_DBLIB)(LPCSTR,
LPCSTR, LPCSTR, LPCSTR, LPCSTR);

tpcc_enc.cpp
// ctpcc_enc.cpp: implementation of the CTPCC_ENCINA
class.
//
////////////////////////////////////////////////////////////////////
////////////////////////////////////////////////////////////////////

#include <windows.h>
#include <process.h>
#include <stdio.h>
#include <stdarg.h>
#include <malloc.h>

```

```

#include <stdlib.h>
#include <string.h>
#include <time.h>
#include <sys\timeb.h>
#include <io.h>

#ifdef ICECAP
#include <icapexp.h>
#endif

// need to declare functions for export
#define DllDecl __declspec( dllexport )

#include "..\..\common\src\trans.h"
//tpckit transaction header contains definitions of
structures specific to TPC-C
#include "..\..\common\src\error.h"
#include "..\..\common\src\txn_base.h"
#include "tpcc_enc.h"
#include "..\include\tpcc_type.h"
#include "mon_client.h"
#include "client_utils.h"

static CRITICAL_SECTION      TpCriticalSection;
extern "C" char *errFile;

BOOL WINAPI DllMain(HANDLE hModule, DWORD
ul_reason_for_call, LPVOID lpReserved)
{
    switch( ul_reason_for_call )
    {
        case DLL_PROCESS_ATTACH:

DisableThreadLibraryCalls(hModule);

InitializeCriticalSection(&TpCriticalSection);
        break;

        case DLL_PROCESS_DETACH:

DeleteCriticalSection(&TpCriticalSection);
        break;

        default:
            /* nothing */;
    }
    return TRUE;
}

// wrapper routine for class constructor
__declspec(dllexport) CTPCC_ENCINA*
CTPCC_ENCINA_new()
{
    return new CTPCC_ENCINA();
}

// wrapper routine for enroll_client
__declspec(dllexport) CTPCC_ENCINA*
CTPCC_ENCINA_post_init()

```

```

{
    enroll_client();
    return NULL;
}

// constructor and destructor
CTPCC_ENCINA::CTPCC_ENCINA()
{
    // Add initialization of ENCINA
    Structures if any
    m_txn = (ENC_DATA
*)malloc(sizeof(ENC_DATA));
    if (m_txn == NULL)
        throw new
CENCERR(ERR_TYPE_MEMORY, ERR_FATAL_LEVEL);
}

CTPCC_ENCINA::~CTPCC_ENCINA()
{
    // free the data structure allocated with
tpalloc
    free((char *)m_txn);
}

void CTPCC_ENCINA::NewOrder()
{
    // question: if we need to prepare the
data?
    if (send_new_order(sizeof(ENC_DATA), (unsigned
char *)m_txn) == TRPC_ERROR)
        throw new CENCERR(TRPC_ERROR);

    if ( m_txn->ErrorType != ERR_SUCCESS )
        throw new CENCERR( m_txn-
>ErrorType, m_txn->error );
}

void CTPCC_ENCINA::Payment()
{
    if (send_payment(sizeof(ENC_DATA), (unsigned char
*)m_txn) == TRPC_ERROR)
        throw new CENCERR(TRPC_ERROR);

    if ( m_txn->ErrorType != ERR_SUCCESS )
        throw new CENCERR( m_txn-
>ErrorType, m_txn->error );
}

void CTPCC_ENCINA::Delivery()
{
    // Note: Delivery txn code in the tuxedo
server does not implement logging of the delivery
// txn results, so cannot be used as
is to run an auditable TPC-C result. For that
// reason, delivery txns should not
be done via Tuxedo.
// The code is included for
completeness.

```

```

//m_txn->u.Delivery.exec_status_code =
eDeliveryFailed;
//return;

// Note: If we use the delivery thread in
tpcc.dll, it is not possible to get to this
// point for delivery txns. But if we
use Encina delivery server, the code is
// needed. It is suggested using the
delivery thread in tpcc.dll since it is
// convenient and provides best
performance.
    GetLocalTime(&m_txn-
>u.Delivery.queue_time);

    if (send_delivery(sizeof(ENC_DATA), (unsigned
char *)m_txn) == TRPC_ERROR)
        m_txn-
>u.Delivery.exec_status_code = eDeliveryFailed;
    else
        m_txn-
>u.Delivery.exec_status_code = eOK;
}

void CTPCC_ENCINA::StockLevel()
{
    if (send_stock_level(sizeof(ENC_DATA), (unsigned
char *)m_txn) == TRPC_ERROR)
        throw new CENCERR(TRPC_ERROR);

    if ( m_txn->ErrorType != ERR_SUCCESS )
        throw new CENCERR( m_txn-
>ErrorType, m_txn->error );
}

void CTPCC_ENCINA::OrderStatus()
{
    if (send_order_status(sizeof(ENC_DATA), (unsigned
char *)m_txn) == TRPC_ERROR)
        throw new CENCERR(TRPC_ERROR);

    if ( m_txn->ErrorType != ERR_SUCCESS )
        throw new CENCERR( m_txn-
>ErrorType, m_txn->error );
}

char *CENCERR::ErrorText()
{
    if ( m_iErrorType == TRPC_ERROR)
    {
        sprintf( m_szErrorText, "Error:
ENCINA TRPC error (see log file %s for details)",
errFile);
    }
    else
        sprintf( m_szErrorText, "Error:
Class %d, error # %d", m_iErrorType, m_iError );
    return m_szErrorText;
};

```

tpcc_enc.h

```
/* FILE: TPCC_ENCINA.H
 * Microsoft
 * TPC-C Kit Ver. 4.10.000
 * not yet audited
 * PURPOSE: Header file for TPC-C Encina
 * class implementation.
 * Copyright
 * Microsoft, 1999
 * All Rights Reserved
 */

#ifndef _TPCC_ENCINA_H_
#define _TPCC_ENCINA_H_

#pragma once

// need to declare functions for import, unless
// define has already been created
// by the DLL's .cpp module for export.
#ifdef DllDecl
#define DllDecl __declspec( dllimport )
#endif

class CTPCC_ENCINA : public CTPCC_BASE
{
private:
    struct ENC_DATA
    {
        int
        ErrorType;
        int
        error;

        union
        {
            NEW_ORDER_DATA      NewOrder;
            PAYMENT_DATA        Payment;
            DELIVERY_DATA       Delivery;

            STOCK_LEVEL_DATA    StockLevel;

            ORDER_STATUS_DATA   OrderStatus;
        } *m_txn;

public:
    CTPCC_ENCINA();
    virtual ~CTPCC_ENCINA();
};
```

```
inline PNEW_ORDER_DATA
BuffAddr_NewOrder() { return
&m_txn->u.NewOrder; };
inline PPAYMENT_DATA
BuffAddr_Payment() { return
&m_txn->u.Payment; };
inline PDELIVERY_DATA
BuffAddr_Delivery() { return
&m_txn->u.Delivery; };
inline PSTOCK_LEVEL_DATA
BuffAddr_StockLevel() { return
&m_txn->u.StockLevel; };
inline PORDER_STATUS_DATA
BuffAddr_OrderStatus() { return
&m_txn->u.OrderStatus; };

void NewOrder          ();
void Payment           ();
void Delivery          ();
void StockLevel        ();
void OrderStatus       ();
};

class CENCERR : public CBaseErr
{
private:
    char    m_szErrorText[64];
public:
    int     m_errno;

    // int     m_iErrorType;
    // match ErrorType in CTPCC_ENCINA
    int     m_iError;
    // machine error in CTPCC_ENCINA

    // use this interface for genuine
    Encina errors
    CENCERR( int iErr )
    {
        m_errno = iErr; //
        m_iErrorType =
ERR_TYPE_ENCINA;
        m_iError = 0; //
        // only meaningful if m_errno == TPEOS
    };

    // use this interface to
    impersonate a non-Encina error type
    CENCERR( int iErrorType, int
iError )
    {
        m_iErrorType =
iErrorType;
        m_iError = iError;
        m_errno = iError; //
    };
};
```

```
// A CENCERR class can
impersonate another class, which happens if the error
// was not actually a Tuxedo
error, but was simply transmitted back via Tuxedo.
int ErrorType()
{
    return m_iErrorType;
}

int ErrorNum() {return m_errno;};
char *ErrorText();

};

// wrapper routine for class constructor:
extern "C" __declspec(dlllexport) CTPCC_ENCINA*
CTPCC_ENCINA_new();
extern "C" __declspec(dlllexport) CTPCC_ENCINA*
CTPCC_ENCINA_post_init();

typedef CTPCC_ENCINA* (TYPE_CTPCC_ENCINA)();

#endif // !defined(_TPCC_ENCINA_H_)
```

tpcc_odbc.cpp

```
/* FILE: TPCC_ODBC.CPP
 * Microsoft
 * TPC-C Kit Ver. 4.42.000
 * Copyright
 * Microsoft, 2002
 * All Rights Reserved
 * Version
 * 4.10.000 audited by Richard Gimarc, Performance
 * Metrics, 3/17/99
 * PURPOSE: Implements ODBC calls for TPC-C
 * txns.
 * Contact: Charles Levine
 * (clevine@microsoft.com)
 * Change history:
 * 4.42.000 - changed w_id fields
 * from short to long to support >32K warehouses
 * 4.20.000 - updated rev number to
 * match kit
 * 4.10.001 - not deleting error
 * class in catch handler on deadlock retry;
 * not a
 * functional bug, but a memory leak
 */

#include <windows.h>
#include <stdio.h>
#include <assert.h>

#define DBNTWIN32
#include <sqltypes.h>
#include <sql.h>
#include <sqlxext.h>
```

```

// #define COMPILE_FOR_SNAC // define that to
// compile for SQL Native Client; comment out to use
// MDAC

#ifdef COMPILE_FOR_SNAC
#include <odbcss.h>
#else
// Compile for SNAC
#include <sqlncli.h>
#endif

#ifdef ICECAP
#include <icapexp.h>
#endif

// need to declare functions for export
#define DllDecl __declspec( dllexport )

#include "..\..\common\src\error.h"
#include "..\..\common\src\trans.h"
#include "..\..\common\src\txn_base.h"
#include "tpcc_odbc.h"

// version string; must match return value from
// tpcc_version stored proc
const char sVersion[] = "4.20.000";

const iMaxRetries = 10; // how many
retries on deadlock

const int iErrOleDbProvider = 7312;
const char sErrTimeoutExpired[] = "Timeout expired";

static SQLHENV henv = SQL_NULL_HENV;
// ODBC environment handle

BOOL APIENTRY DllMain(HMODULE hModule, DWORD
ul_reason_for_call, LPVOID lpReserved)
{
switch( ul_reason_for_call )
{
case DLL_PROCESS_ATTACH:
DisableThreadLibraryCalls( hModule );
if (
SQLAllocHandleStd( SQL_HANDLE_ENV, SQL_NULL_HANDLE,
&henv ) != SQL_SUCCESS )
return FALSE;
break;

case DLL_PROCESS_DETACH:
if ( henv != NULL )
SQLFreeEnv( henv );
break;

default:
/* nothing */;
}
return TRUE;
}

```

```

}

/* FUNCTION: CTPCC_ODBC_ERR::ErrorText
*/
char* CTPCC_ODBC_ERR::ErrorText( void )
{
int i;

static SERRORMSG errorMsgs[] =
{
{ ERR_WRONG_SP_VERSION,
"Wrong version of stored procs on database
server" },
{ ERR_INVALID_CUST,
"Invalid Customer id,name." },
{ ERR_NO_SUCH_ORDER,
"No orders found for customer." },
{ ERR_RETRIED_TRANS,
"Retries before transaction succeeded." },
{ 0, "" }
};

static char szNotFound[] = "Unknown error
number.";

for( i=0; errorMsgs[i].szMsg[0]; i++ )
{
if ( m_errno ==
errorMsgs[i].iError )
break;
if ( !errorMsgs[i].szMsg[0] )
return szNotFound;
else
return errorMsgs[i].szMsg;
}

// wrapper routine for class constructor
__declspec( dllexport ) CTPCC_ODBC* CTPCC_ODBC_new(
LPCSTR szServer, // name of
SQL server
LPCSTR szUser, //
user name for login
LPCSTR szPassword, // password
for login
LPCSTR szHost, //
not used
LPCSTR szDatabase, // name of
database to use
LPCWSTR szSPPrefix, // prefix to
append to the stored procedure names
)

```

```

BOOL bCallNoDuplicatesNewOrder ) // whether
to check for non-duplicate items in NewOrder and call
a new SP
{
return new CTPCC_ODBC( szServer, szUser,
szPassword, szHost, szDatabase, szSPPrefix,
bCallNoDuplicatesNewOrder );
}

CTPCC_ODBC::CTPCC_ODBC (
LPCSTR szServer,
// name of SQL server
LPCSTR szUser,
// user name for login
LPCSTR szPassword,
// password for login
LPCSTR szHost,
// not used
LPCSTR szDatabase,
// name of database to use
LPCWSTR szSPPrefix,
// prefix to append to the stored procedure
names
BOOL bCallNoDuplicatesNewOrder //
whether to check for non-duplicate items in NewOrder
and call a new SP
)
:
m_bCallNoDuplicatesNewOrder( bCallNoDuplicatesNewOrder
)
{
RETCODE rc;

// initialization
m_hdbc = SQL_NULL_HDBC;
m_hstmt = SQL_NULL_HSTMT;

m_hstmtNewOrder = SQL_NULL_HSTMT;
m_hstmtPayment = SQL_NULL_HSTMT;
m_hstmtDelivery = SQL_NULL_HSTMT;
m_hstmtOrderStatus = SQL_NULL_HSTMT;
m_hstmtStockLevel = SQL_NULL_HSTMT;

m_descNewOrderCols1 = SQL_NULL_HDESC;
m_descNewOrderCols2 = SQL_NULL_HDESC;
m_descOrderStatusCols1 = SQL_NULL_HDESC;
m_descOrderStatusCols2 = SQL_NULL_HDESC;

wcsncpy( m_szSPPrefix, szSPPrefix,
sizeof( m_szSPPrefix ) / sizeof( m_szSPPrefix[0] ) );

if ( SQLAllocHandle( SQL_HANDLE_DBC, henv,
&m_hdbc ) != SQL_SUCCESS )
ThrowError( CODBCERR::eAllocHandle );

if ( SQLSetConnectOption( m_hdbc,
SQL_PACKET_SIZE, 4096 ) != SQL_SUCCESS )

```

```

ThrowError(CODBCERR::eConnOption);

{
    char
    szConnectStr[256];
    char
    szOutStr[1024];
    SQLSMALLINT
    iOutStrLen;

#ifdef COMPILE_FOR_SNAC
    sprintf( szConnectStr,
"DRIVER=SQL
Server;SERVER=%s;UID=%s;PWD=%s;DATABASE=%s",
            szServer, szUser,
szPassword, szDatabase );
#else
    // Compile for SNAC
    sprintf( szConnectStr,
"DRIVER=SQL Native
Client;SERVER=%s;UID=%s;PWD=%s;DATABASE=%s",
            szServer, szUser,
szPassword, szDatabase );
#endif
    rc = SQLDriverConnect(m_hdbc,
NULL, (SQLCHAR*)szConnectStr, sizeof(szConnectStr),
(SQLCHAR*)szOutStr,
sizeof(szOutStr), &iOutStrLen, SQL_DRIVER_NOPROMPT );

    if (rc != SQL_SUCCESS && rc !=
SQL_SUCCESS_WITH_INFO)
        ThrowError(CODBCERR::eConnect);
}

if (SQLAllocHandle(SQL_HANDLE_STMT, m_hdbc,
&m_hstmt) != SQL_SUCCESS)
    ThrowError(CODBCERR::eAllocHandle);

{
    char        buffer[128];

    // set some options affecting
connection behavior
    strcpy(buffer, "set nocount on
set XACT_ABORT ON");
    rc = SQLExecDirect(m_hstmt,
(unsigned char *)buffer, SQL_NTS);
    if (rc != SQL_SUCCESS && rc !=
SQL_SUCCESS_WITH_INFO)
        ThrowError(CODBCERR::eExecDirect);

    // verify that version of stored
procs on server is correct
    char db_sp_version[10];
    strcpy(buffer, "{call
tpcc_version}");

```

```

        rc = SQLExecDirect(m_hstmt,
(unsigned char *)buffer, SQL_NTS);
        if (rc != SQL_SUCCESS && rc !=
SQL_SUCCESS_WITH_INFO)
            ThrowError(CODBCERR::eExecDirect);
        if ( SQLBindCol(m_hstmt, 1,
SQL_C_CHAR, &db_sp_version, sizeof(db_sp_version),
NULL) != SQL_SUCCESS )
            ThrowError(CODBCERR::eBindCol);
        if ( SQLFetch(m_hstmt) ==
SQL_ERROR )
            ThrowError(CODBCERR::eFetch);
        if
(strncmp(db_sp_version,sVersion))
            throw new
CTPCC_ODBC_ERR( CTPCC_ODBC_ERR::ERR_WRONG_SP_VERSION
);

        SQLFreeHandle(SQL_HANDLE_STMT,
m_hstmt);
    }

    // Bind parameters for each of the
transactions
    InitNewOrderParams();
    InitPaymentParams();
    InitOrderStatusParams();
    InitDeliveryParams();
    InitStockLevelParams();
}

CTPCC_ODBC::~CTPCC_ODBC( void )
{
    // note: descriptors are automatically
released when the connection is dropped
    SQLFreeHandle(SQL_HANDLE_STMT,
m_hstmtNewOrder);
    SQLFreeHandle(SQL_HANDLE_STMT,
m_hstmtPayment);
    SQLFreeHandle(SQL_HANDLE_STMT,
m_hstmtDelivery);
    SQLFreeHandle(SQL_HANDLE_STMT,
m_hstmtOrderStatus);
    SQLFreeHandle(SQL_HANDLE_STMT,
m_hstmtStockLevel);

    SQLDisconnect(m_hdbc);
    SQLFreeHandle(SQL_HANDLE_DBC, m_hdbc);
}

void CTPCC_ODBC::ThrowError( CODBCERR::ACTION eAction
)
{
    RETCODE        rc;
    SDWORD         lNativeError;
    char           szState[6];
    char
    szMsg[SQL_MAX_MESSAGE_LENGTH];

```

```

    char
    szTmp[6*SQL_MAX_MESSAGE_LENGTH];
    CODBCERR      *pODBCERR;
    // not allocated until needed (maybe never)

    pODBCERR = new CODBCERR();

    pODBCERR->m_NativeError = 0;
    pODBCERR->m_eAction = eAction;
    pODBCERR->m_bDeadLock = FALSE;

    szTmp[0] = 0;
    while (TRUE)
    {
        rc = SQLError(henv, m_hdbc,
m_hstmt, (BYTE *)&szState, &lNativeError,
(BYTE *)&szMsg, sizeof(szMsg), NULL);
        if (rc == SQL_NO_DATA)
            break;

        // check for deadlock
        if (lNativeError == 1205 ||
(lNativeError == iErrOleDbProvider &&
strstr(szMsg,
sErrTimeoutExpired) != NULL))
            pODBCERR->m_bDeadLock =
TRUE;

        // capture the (first) database
error
        if (pODBCERR->m_NativeError == 0
&& lNativeError != 0)
            pODBCERR->m_NativeError
= lNativeError;

        // quit if there isn't enough
room to concatenate error text
        if ( (strlen(szMsg) + 2) >
(sizeof(szTmp) - strlen(szTmp)) )
            break;

        // include line break after first
error msg
        if (szTmp[0] != 0)
            strcat( szTmp, "\n");
        strcat( szTmp, szMsg );
    }

    if (pODBCERR->m_odbcerrstr != NULL)
    {
        delete [] pODBCERR->m_odbcerrstr;
        pODBCERR->m_odbcerrstr = NULL;
    }

    if (strlen(szTmp) > 0)
    {
        pODBCERR->m_odbcerrstr = new
char[ strlen(szTmp)+1 ];
        strcpy( pODBCERR->m_odbcerrstr,
szTmp );
    }

```

```

    }

    SQLFreeStmt(m_hstmt, SQL_CLOSE);
    throw pODBCErr;
}

void CTPCC_ODBC::InitStockLevelParams()
{
    if ( SQLAllocHandle(SQL_HANDLE_STMT,
m_hdbc, &m_hstmtStockLevel) != SQL_SUCCESS )
        ThrowError(CODBCERR::eAllocHandle);

    m_hstmt = m_hstmtStockLevel;

    int i = 0;
    if ( SQLBindParameter(m_hstmt, ++i,
SQL_PARAM_INPUT, SQL_C_SLONG, SQL_INTEGER, 0, 0,
&m_txn.StockLevel.w_id, 0, NULL) != SQL_SUCCESS
        || SQLBindParameter(m_hstmt, ++i,
SQL_PARAM_INPUT, SQL_C_UTINYINT, SQL_TINYINT, 0, 0,
&m_txn.StockLevel.d_id, 0, NULL) != SQL_SUCCESS
        || SQLBindParameter(m_hstmt, ++i,
SQL_PARAM_INPUT, SQL_C_SSHORT, SQL_SMALLINT, 0, 0,
&m_txn.StockLevel.threshold, 0, NULL) != SQL_SUCCESS
        )
        ThrowError(CODBCERR::eBindParam);

    if ( SQLBindCol(m_hstmt, 1, SQL_C_SLONG,
&m_txn.StockLevel.low_stock, 0, NULL) != SQL_SUCCESS
    )
        ThrowError(CODBCERR::eBindCol);

    //Compose Stock Level statement
    _snprintf(m_szStockLevelCommand,
sizeof(m_szStockLevelCommand)/sizeof(m_szStockLevelCo
mmand[0]),
        L" {call %stpcck_stocklevel
(?, ?, ?) }", m_szSPPrefix);
}

void CTPCC_ODBC::StockLevel()
{
    RETCODE          rc;
    int              iTryCount =
0;

    m_hstmt = m_hstmtStockLevel;

    while (TRUE)
    {
        try
        {
            rc =
SQLExecDirectW(m_hstmt, m_szStockLevelCommand,
SQL_NTS);
            if (rc != SQL_SUCCESS
&& rc != SQL_SUCCESS_WITH_INFO)
                ThrowError(CODBCERR::eExecDirect);

```

```

        if ( SQLFetch(m_hstmt)
== SQL_ERROR )
            ThrowError(CODBCERR::eFetch);

        SQLFreeStmt(m_hstmt,
SQL_CLOSE);

        m_txn.StockLevel.exec_status_code = eOK;
        break;
    }
    catch (CODBCERR *e)
    {
        if (!e->m_bDeadLock)
            if (++iTryCount > iMaxRetries)
                throw;

        // hit deadlock;
        backoff for increasingly longer period
        delete e;
        Sleep(10 * iTryCount);
    }

    // if (iTryCount)
    //     throw new
CTPCC_ODBC_ERR(CTPCC_ODBC_ERR::ERR_RETRIED_TRANS,
iTryCount);
}

void CTPCC_ODBC::InitNewOrderParams()
{
    if ( SQLAllocHandle(SQL_HANDLE_STMT,
m_hdbc, &m_hstmtNewOrder) != SQL_SUCCESS
        ||
SQLAllocHandle(SQL_HANDLE_STMT, m_hdbc,
&m_hstmtNewOrderNoDuplicates) != SQL_SUCCESS
        ||
SQLAllocHandle(SQL_HANDLE_DESC, m_hdbc,
&m_descNewOrderCols1) != SQL_SUCCESS
        ||
SQLAllocHandle(SQL_HANDLE_DESC, m_hdbc,
&m_descNewOrderCols2) != SQL_SUCCESS
        ||
SQLAllocHandle(SQL_HANDLE_DESC, m_hdbc,
&m_descNewOrderNoDuplicatesCols1) != SQL_SUCCESS
        ||
SQLAllocHandle(SQL_HANDLE_DESC, m_hdbc,
&m_descNewOrderNoDuplicatesCols2) != SQL_SUCCESS
        )
        ThrowError(CODBCERR::eAllocHandle);

    m_hstmt = m_hstmtNewOrder;

    if ( SQLSetStmtAttrW(m_hstmt,
SQL_ATTR_APP_ROW_DESC, m_descNewOrderCols1,
SQL_IS_POINTER ) != SQL_SUCCESS )
        ThrowError(CODBCERR::eSetStmtAttr);

```

```

        int i = 0;
        if ( SQLBindParameter(m_hstmt, ++i,
SQL_PARAM_INPUT, SQL_C_SLONG, SQL_INTEGER, 0, 0,
&m_txn.NewOrder.w_id, 0, NULL) != SQL_SUCCESS
            || SQLBindParameter(m_hstmt, ++i,
SQL_PARAM_INPUT, SQL_C_UTINYINT, SQL_TINYINT, 0, 0,
&m_txn.NewOrder.d_id, 0, NULL) != SQL_SUCCESS
            || SQLBindParameter(m_hstmt, ++i,
SQL_PARAM_INPUT, SQL_C_SLONG, SQL_INTEGER, 0, 0,
&m_txn.NewOrder.c_id, 0, NULL) != SQL_SUCCESS
            || SQLBindParameter(m_hstmt, ++i,
SQL_PARAM_INPUT, SQL_C_UTINYINT, SQL_TINYINT, 0, 0,
&m_txn.NewOrder.o_ol_cnt, 0, NULL) != SQL_SUCCESS
            || SQLBindParameter(m_hstmt, ++i,
SQL_PARAM_INPUT, SQL_C_UTINYINT, SQL_TINYINT, 0, 0,
&m_txn.NewOrder.o_all_local, 0, NULL) != SQL_SUCCESS
            )
            ThrowError(CODBCERR::eBindParam);

        for (int j=0; j<MAX_OL_NEW_ORDER_ITEMS;
j++)
        {
            if ( SQLBindParameter(m_hstmt,
++i, SQL_PARAM_INPUT, SQL_C_SLONG, SQL_INTEGER, 0, 0,
&m_txn.NewOrder.OL[j].ol_i_id, 0, NULL) !=
SQL_SUCCESS
                ||
SQLBindParameter(m_hstmt, ++i, SQL_PARAM_INPUT,
SQL_C_SLONG, SQL_INTEGER, 0, 0,
&m_txn.NewOrder.OL[j].ol_supply_w_id, 0, NULL) !=
SQL_SUCCESS
                ||
SQLBindParameter(m_hstmt, ++i, SQL_PARAM_INPUT,
SQL_C_SSHORT, SQL_SMALLINT, 0, 0,
&m_txn.NewOrder.OL[j].ol_quantity, 0, NULL) !=
SQL_SUCCESS
                )
                ThrowError(CODBCERR::eBindParam);
        }

        // set the bind offset pointer
        if ( SQLSetStmtAttrW(m_hstmt,
SQL_ATTR_ROW_BIND_OFFSET_PTR, &m_BindOffset,
SQL_IS_POINTER ) != SQL_SUCCESS )
            ThrowError(CODBCERR::eSetStmtAttr);

        i = 0;
        if ( SQLBindCol(m_hstmt, ++i, SQL_C_CHAR,
&m_txn.NewOrder.OL[0].ol_i_name,
sizeof(m_txn.NewOrder.OL[0].ol_i_name), NULL) !=
SQL_SUCCESS
            || SQLBindCol(m_hstmt, ++i,
SQL_C_SSHORT, &m_txn.NewOrder.OL[0].ol_stock, 0,
NULL) != SQL_SUCCESS
            || SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.NewOrder.OL[0].ol_brand_generic,
sizeof(m_txn.NewOrder.OL[0].ol_brand_generic), NULL)
!= SQL_SUCCESS
            )

```

```

        || SQLBindCol(m_hstmt, ++i,
SQL_C_DOUBLE, &m_txn.NewOrder.OL[0].ol_i_price, 0,
NULL) != SQL_SUCCESS
        || SQLBindCol(m_hstmt, ++i,
SQL_C_DOUBLE, &m_txn.NewOrder.OL[0].ol_amount, 0,
NULL) != SQL_SUCCESS
    )
    ThrowError(CODBCERR::eBindCol);

    // associate the column bindings for the
second result set
    if ( SQLSetStmtAttrW(m_hstmt,
SQL_ATTR_APP_ROW_DESC, m_descNewOrderCols2,
SQL_IS_POINTER ) != SQL_SUCCESS )

        ThrowError(CODBCERR::eSetStmtAttr);

    i = 0;
    if ( SQLBindCol(m_hstmt, ++i,
SQL_C_DOUBLE, &m_txn.NewOrder.w_tax, 0, NULL) !=
SQL_SUCCESS
        || SQLBindCol(m_hstmt, ++i,
SQL_C_DOUBLE, &m_txn.NewOrder.d_tax, 0, NULL) !=
SQL_SUCCESS
        || SQLBindCol(m_hstmt, ++i,
SQL_C_SLONG, &m_txn.NewOrder.o_id, 0, NULL) !=
SQL_SUCCESS
        || SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.NewOrder.c_last,
sizeof(m_txn.NewOrder.c_last), NULL) != SQL_SUCCESS
        || SQLBindCol(m_hstmt, ++i,
SQL_C_DOUBLE, &m_txn.NewOrder.c_discount, 0, NULL)
!= SQL_SUCCESS
        || SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.NewOrder.c_credit,
sizeof(m_txn.NewOrder.c_credit), NULL) != SQL_SUCCESS
        || SQLBindCol(m_hstmt, ++i,
SQL_C_TYPE_TIMESTAMP, &m_txn.NewOrder.o_entry_d, 0,
NULL) != SQL_SUCCESS
        || SQLBindCol(m_hstmt, ++i,
SQL_C_SLONG, &m_no_commit_flag, 0, NULL) !=
SQL_SUCCESS
    )
        ThrowError(CODBCERR::eBindCol);

    //Compose the New Order statement
    snprintf(m_szNewOrderCommand,
sizeof(m_szNewOrderCommand)/sizeof(m_szNewOrderComman
d(0)),
        // 0      1      2
        //
012345678901234567890123456789
        L"{call
%stppcc_neworder(?,?,?,?,?,?,?,?,?,?,?,?,?,
?,?,?,?,?,
L"?,?,?,?,?,?,?,?,?,?,?,?,?,
?,?,?,?,?})", m_szSPPrefix);

```

```

        m_iBeginNewOrderVariablePart = 29 +
wcslen(m_szSPPrefix); // fixed part + prefix
part

        //////////////////////////////////////
////////////////////////////////////
        //
        // Now initialize New Order that
works on no duplicate (w_id,i_id) pairs
        // and returns one result set for
lineitem details.
        //
        //
        m_hstmt = m_hstmtNewOrderNoDuplicates;

        if ( SQLSetStmtAttrW(m_hstmt,
SQL_ATTR_APP_ROW_DESC,
m_descNewOrderNoDuplicatesCols1, SQL_IS_POINTER ) !=
SQL_SUCCESS )

            ThrowError(CODBCERR::eSetStmtAttr);

        i = 0;
        if ( SQLBindParameter(m_hstmt, ++i,
SQL_PARAM_INPUT, SQL_C_SLONG, SQL_INTEGER, 0, 0,
&m_txn.NewOrder.w_id, 0, NULL) != SQL_SUCCESS
            || SQLBindParameter(m_hstmt, ++i,
SQL_PARAM_INPUT, SQL_C_UTINYINT, SQL_TINYINT, 0, 0,
&m_txn.NewOrder.d_id, 0, NULL) != SQL_SUCCESS
            || SQLBindParameter(m_hstmt, ++i,
SQL_PARAM_INPUT, SQL_C_SLONG, SQL_INTEGER, 0, 0,
&m_txn.NewOrder.c_id, 0, NULL) != SQL_SUCCESS
            || SQLBindParameter(m_hstmt, ++i,
SQL_PARAM_INPUT, SQL_C_UTINYINT, SQL_TINYINT, 0, 0,
&m_txn.NewOrder.o_ol_cnt, 0, NULL) != SQL_SUCCESS
            || SQLBindParameter(m_hstmt, ++i,
SQL_PARAM_INPUT, SQL_C_UTINYINT, SQL_TINYINT, 0, 0,
&m_txn.NewOrder.o_all_local, 0, NULL) != SQL_SUCCESS
        )
            ThrowError(CODBCERR::eBindParam);

        for (int j=0; j<MAX_OL_NEW_ORDER_ITEMS;
j++)
        {
            if ( SQLBindParameter(m_hstmt,
++i, SQL_PARAM_INPUT, SQL_C_SLONG, SQL_INTEGER, 0, 0,
&m_txn.NewOrder.OL[j].ol_i_id, 0, NULL) !=
SQL_SUCCESS
                ||
SQLBindParameter(m_hstmt, ++i, SQL_PARAM_INPUT,
SQL_C_SLONG, SQL_INTEGER, 0, 0,
&m_txn.NewOrder.OL[j].ol_supply_w_id, 0, NULL) !=
SQL_SUCCESS
                ||
SQLBindParameter(m_hstmt, ++i, SQL_PARAM_INPUT,
SQL_C_SSHORT, SQL_SMALLINT, 0, 0,
&m_txn.NewOrder.OL[j].ol_quantity, 0, NULL) !=
SQL_SUCCESS
            )

                ThrowError(CODBCERR::eBindParam);

```

```

    }

    // set row-wise binding
    if ( SQLSetStmtAttrW(m_hstmt,
SQL_ATTR_ROW_BIND_TYPE,
(SQLPOINTER)sizeof(m_txn.NewOrder.OL[0]),
SQL_IS_UIINTEGER) != SQL_SUCCESS
        || SQLSetStmtAttrW(m_hstmt,
SQL_ATTR_ROWS_FETCHED_PTR, &m_RowsFetched, 0) !=
SQL_SUCCESS )

        ThrowError(CODBCERR::eSetStmtAttr);

    i = 0;
    if ( SQLBindCol(m_hstmt, ++i, SQL_C_CHAR,
&m_txn.NewOrder.OL[0].ol_i_name,
sizeof(m_txn.NewOrder.OL[0].ol_i_name), NULL) !=
SQL_SUCCESS
        || SQLBindCol(m_hstmt, ++i,
SQL_C_SSHORT, &m_txn.NewOrder.OL[0].ol_stock, 0,
NULL) != SQL_SUCCESS
        || SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.NewOrder.OL[0].ol_brand_generic,
sizeof(m_txn.NewOrder.OL[0].ol_brand_generic), NULL)
!= SQL_SUCCESS
        || SQLBindCol(m_hstmt, ++i,
SQL_C_DOUBLE, &m_txn.NewOrder.OL[0].ol_i_price, 0,
NULL) != SQL_SUCCESS
        || SQLBindCol(m_hstmt, ++i,
SQL_C_DOUBLE, &m_txn.NewOrder.OL[0].ol_amount, 0,
NULL) != SQL_SUCCESS
    )
        ThrowError(CODBCERR::eBindCol);

    // associate the column bindings for the
second result set
    if ( SQLSetStmtAttrW(m_hstmt,
SQL_ATTR_APP_ROW_DESC,
m_descNewOrderNoDuplicatesCols2, SQL_IS_POINTER ) !=
SQL_SUCCESS )

        ThrowError(CODBCERR::eSetStmtAttr);

    i = 0;
    if ( SQLBindCol(m_hstmt, ++i,
SQL_C_DOUBLE, &m_txn.NewOrder.w_tax, 0, NULL) !=
SQL_SUCCESS
        || SQLBindCol(m_hstmt, ++i,
SQL_C_DOUBLE, &m_txn.NewOrder.d_tax, 0, NULL) !=
SQL_SUCCESS
        || SQLBindCol(m_hstmt, ++i,
SQL_C_SLONG, &m_txn.NewOrder.o_id, 0, NULL) !=
SQL_SUCCESS
        || SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.NewOrder.c_last,
sizeof(m_txn.NewOrder.c_last), NULL) != SQL_SUCCESS
        || SQLBindCol(m_hstmt, ++i,
SQL_C_DOUBLE, &m_txn.NewOrder.c_discount, 0, NULL)
!= SQL_SUCCESS
    )

```



```

        || SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR,      &m_txn.NewOrder.c_credit,
sizeof(m_txn.NewOrder.c_credit), NULL) != SQL_SUCCESS
        || SQLBindCol(m_hstmt, ++i,
SQL_C_TYPE_TIMESTAMP, &m_txn.NewOrder.o_entry_d, 0,
NULL) != SQL_SUCCESS
        || SQLBindCol(m_hstmt, ++i,
SQL_C_SLONG,      &m_no_commit_flag, 0, NULL) !=
SQL_SUCCESS
    )
        ThrowError(CODBCERR::eBindCol);

    //Compose the New Order statement
    _snwprintf(m_szNewOrderNoDuplicatesCommand,
sizeof(m_szNewOrderNoDuplicatesCommand)/sizeof(m_szNew
wOrderNoDuplicatesCommand[0]),
        L"{call
%stpc_neworder_new(?,?,?,?,?,?,?,?,?,?,?,?,?,
?, ?, ?, ?, ?, ?, ?,"
        L"?,?,?,?,?,?,?,?,?,?,?,?,?,
?, ?, ?, ?)", m_szSPPrefix);

    m_iBeginNewOrderNoDuplicatesVariablePart =
33 + wcslen(m_szSPPrefix); // fixed part + prefix
part
}

//
// Returns true if there are duplicate
(warehouse_id, item_id)
// lineitem pairs in New Order input
parameters.
//
bool CTPCC_ODBC::DuplicatesInNewOrder()
{
    int i, j;

    for (i = 0; i < m_txn.NewOrder.o_ol_cnt;
++i)
    {
        for (j = i+1; j<
m_txn.NewOrder.o_ol_cnt; ++j)
        {
            if
(m_txn.NewOrder.OL[i].ol_i_id ==
m_txn.NewOrder.OL[j].ol_i_id)
            {
                return true;
            }
        }
    }

    return false;
}

void CTPCC_ODBC::NewOrder()
{
    if (m_bCallNoDuplicatesNewOrder)
    {
        if (DuplicatesInNewOrder())

```

```

        {
            NewOrderDuplicates();
        }
        else
        {
            NewOrderNoDuplicates();
        }
    }
    else
    {
        NewOrderDuplicates();
    }
}

void CTPCC_ODBC::NewOrderDuplicates()
{
    int
i;
    RETCODE          rc;
    int
iTryCount = 0;

    0          1          2          //
    012345678901234567890123456789
    wchar_t
szSqlTemplate[iMAX_SP_NAME_LEN];

    tpcc_neworder(?,?,?,?,?, " // L"{call
L"?,?,?,?,?,?,?,?,?,?,?,?,?, " //
L"?,?,?,?,?,?,?,?,?,?,?,?,?, " //
L"?,?,?,?,?,?,?,?,?,?,?,?,?, " //
L"?,?,?,?,?,?,?,?,?,?,?,?,?, " //
    m_hstmt = m_hstmtNewOrder;

    // associate the parameter and column
bindings for this transaction
    if ( SQLSetStmtAttrW(m_hstmt,
SQL_ATTR_APP_ROW_DESC, m_descNewOrderCols1,
SQL_IS_POINTER ) != SQL_SUCCESS )
        ThrowError(CODBCERR::eSetStmtAttr);

    // clip statement buffer based on number of
parameters
    // fixed part is 29 chars and variable part
is 6 chars per line item
    wcsncpy(szSqlTemplate, m_szNewOrderCommand);
    i = m_iBeginNewOrderVariablePart +
m_txn.NewOrder.o_ol_cnt*6;
    wcsncpy( &szSqlTemplate[i], L" )" );

```

```

        // check whether any order lines are for a
remote warehouse
        m_txn.NewOrder.o_all_local = 1;
        for (i = 0; i < m_txn.NewOrder.o_ol_cnt;
i++)
        {
            if
(m_txn.NewOrder.OL[i].ol_supply_w_id !=
m_txn.NewOrder.w_id)
            {
                m_txn.NewOrder.o_all_local = 0; // at
least one remote warehouse
                break;
            }
        }
        while (TRUE)
        {
            try
            {
                m_BindOffset = 0;
                rc =
SQLExecDirectW(m_hstmt, szSqlTemplate, SQL_NTS);
                if (rc != SQL_SUCCESS
&& rc != SQL_SUCCESS_WITH_INFO)
                    ThrowError(CODBCERR::eExecDirect);

                // Get order line
                results

                m_txn.NewOrder.total_amount = 0;
                for (i = 0;
i<m_txn.NewOrder.o_ol_cnt; i++)
                {
                    // set the
                    m_BindOffset
= i * sizeof(m_txn.NewOrder.OL[0]);

                    if (
SQLFetch(m_hstmt) == SQL_ERROR)
                        ThrowError(CODBCERR::eFetch);

                    // move to
                    the next resultset
                    if (
SQLMoreResults(m_hstmt) == SQL_ERROR )
                        ThrowError(CODBCERR::eMoreResults);

                    m_txn.NewOrder.total_amount +=
m_txn.NewOrder.OL[i].ol_amount;
                }

                // associate the column
bindings for the second result set

```

```

        if ( SQLSetStmtAttrW(
m_hstmt, SQL_ATTR_APP_ROW_DESC, m_descNewOrderCols2,
SQL_IS_POINTER ) != SQL_SUCCESS )

        ThrowError(CODBCERR::eSetStmtAttr);

    == SQL_ERROR)
        if ( SQLFetch(m_hstmt)

        ThrowError(CODBCERR::eFetch);

SQL_CLOSE);

        SQLFreeStmt(m_hstmt,

        if (m_no_commit_flag ==
1)
        {

            m_txn.NewOrder.total_amount += ((1 +
m_txn.NewOrder.w_tax + m_txn.NewOrder.d_tax) * (1 -
m_txn.NewOrder.c_discount));

            m_txn.NewOrder.exec_status_code = eOK;
        }
        else
            m_txn.NewOrder.exec_status_code =
eInvalidItem;

            break;
        }
        catch (CODBCERR *e)
        {
            if (!(e->m_bDeadLock)
|| (++iTryCount > iMaxRetries))
                throw;

            // hit deadlock;
            backoff for increasingly longer period
            delete e;
            Sleep(10 * iTryCount);
        }
    }

//      if (iTryCount)
//          throw new
CTPCC_ODBC_ERR(CTPCC_ODBC_ERR::ERR_RETRIED_TRANS,
iTryCount);
}

//
//      No lineitem duplicates optimized version.
//
void CTPCC_ODBC::NewOrderNoDuplicates()
{
    int
    i;
    RETCODE
    rc;
    int
    iTryCount = 0;

```

```

0      1      2      3      //
0123456789012345678901234567890123      //
wchar_t
szSqlTemplate[iMAX_SP_NAME_LEN];

tpcc_neworder_new(?,?,?,?,"      // L"(call

L"?,?,?,?,?,?,?,?,?,?,?,?,?"      //

L"?,?,?,?,?,?,?,?,?,?,?,?,?"      //

L"?,?,?,?,?,?,?,?,?,?,?,?,?"      //

m_hstmt = m_hstmtNewOrderNoDuplicates;

// associate the parameter and column
bindings for this transaction
if ( SQLSetStmtAttrW( m_hstmt,
SQL_ATTR_APP_ROW_DESC,
m_descNewOrderNoDuplicatesCols1, SQL_IS_POINTER ) !=
SQL_SUCCESS )

    ThrowError(CODBCERR::eSetStmtAttr);

// clip statement buffer based on number of
parameters
// fixed part is 33 chars and variable part
is 6 chars per line item
wcsncpy(szSqlTemplate,
m_szNewOrderNoDuplicatesCommand);
i =
m_iBeginNewOrderNoDuplicatesVariablePart +
m_txn.NewOrder.o_ol_cnt*6;
wcsncpy( &szSqlTemplate[i], L" )" );

// check whether any order lines are for a
remote warehouse
m_txn.NewOrder.o_all_local = 1;
for (i = 0; i < m_txn.NewOrder.o_ol_cnt;
i++)
    {
        if
(m_txn.NewOrder.OL[i].ol_supply_w_id !=
m_txn.NewOrder.w_id)
        {
            m_txn.NewOrder.o_all_local = 0; // at
least one remote warehouse
            break;
        }
    }

while (TRUE)

```

```

{
    try
    {
        // configure block
        cursor
        if (
SQLSetStmtAttrW(m_hstmt, SQL_ATTR_ROW_ARRAY_SIZE,
(SQLPOINTER)1, 0) != SQL_SUCCESS )

            ThrowError(CODBCERR::eSetStmtAttr);

            rc =
SQLExecDirectW(m_hstmt, szSqlTemplate, SQL_NTS);
            if (rc != SQL_SUCCESS
&& rc != SQL_SUCCESS_WITH_INFO)

                ThrowError(CODBCERR::eExecDirect);

            // configure block
            cursor
            if
(SQLSetStmtAttrW(m_hstmt, SQL_ATTR_ROW_ARRAY_SIZE,
(SQLPOINTER)MAX_OL_NEW_ORDER_ITEMS, 0) !=
SQL_SUCCESS)

                ThrowError(CODBCERR::eSetStmtAttr);

            // Get order line
            results
            if ( SQLFetch(m_hstmt)

            == SQL_ERROR)

                ThrowError(CODBCERR::eFetch);

            m_txn.NewOrder.total_amount = 0;
            for (i = 0;
i<m_txn.NewOrder.o_ol_cnt; i++)
            {

                m_txn.NewOrder.total_amount +=
m_txn.NewOrder.OL[i].ol_amount;
            }

            // associate the column
bindings for the second result set
            if ( SQLSetStmtAttrW(
m_hstmt, SQL_ATTR_APP_ROW_DESC,
m_descNewOrderNoDuplicatesCols2, SQL_IS_POINTER ) !=
SQL_SUCCESS )

                ThrowError(CODBCERR::eSetStmtAttr);

            // move to the next
            resultset
            if (
SQLMoreResults(m_hstmt) == SQL_ERROR )

                ThrowError(CODBCERR::eMoreResults);

```

```

        if ( SQLFetch(m_hstmt)
== SQL_ERROR)
        {
            ThrowError(CODBCERR::eFetch);
        }
    }
    SQLFreeStmt(m_hstmt,
SQL_CLOSE);

    if (m_no_commit_flag ==
1)
    {
        m_txn.NewOrder.total_amount *= ((1 +
m_txn.NewOrder.w_tax + m_txn.NewOrder.d_tax) * (1 -
m_txn.NewOrder.c_discount));

        m_txn.NewOrder.exec_status_code = eOK;
    }
    else
    {
        m_txn.NewOrder.exec_status_code =
eInvalidItem;
    }

    break;
}
catch (CODBCERR *e)
{
    if (!e->m_bDeadLock)
    {
        ++iTryCount > iMaxRetries)
        throw;

        // hit deadlock;
        delete e;
        Sleep(10 * iTryCount);
    }
}

// if (iTryCount)
// throw new
CTPCC_ODBC_ERR(CTPCC_ODBC_ERR::ERR_RETRIED_TRANS,
iTryCount);
}

void CTPCC_ODBC::InitPaymentParams()
{
    if ( SQLAllocHandle(SQL_HANDLE_STMT,
m_hdbc, &m_hstmtPayment) != SQL_SUCCESS )
    {
        ThrowError(CODBCERR::eAllocHandle);
    }

    m_hstmt = m_hstmtPayment;

    int i = 0;
    if ( SQLBindParameter(m_hstmt, ++i,
SQL_PARAM_INPUT, SQL_C_SLONG, SQL_INTEGER, 0, 0,
&m_txn.Payment.w_id, 0, NULL) != SQL_SUCCESS
    || SQLBindParameter(m_hstmt, ++i,
SQL_PARAM_INPUT, SQL_C_SLONG, SQL_INTEGER, 0, 0,
&m_txn.Payment.c_w_id, 0, NULL) != SQL_SUCCESS

```

```

    || SQLBindParameter(m_hstmt, ++i,
SQL_PARAM_INPUT, SQL_C_DOUBLE, SQL_NUMERIC, 6, 2,
&m_txn.Payment.h_amount, 0, NULL) != SQL_SUCCESS
    || SQLBindParameter(m_hstmt, ++i,
SQL_PARAM_INPUT, SQL_C_UTINYINT, SQL_TINYINT, 0, 0,
&m_txn.Payment.d_id, 0, NULL) != SQL_SUCCESS
    || SQLBindParameter(m_hstmt, ++i,
SQL_PARAM_INPUT, SQL_C_UTINYINT, SQL_TINYINT, 0, 0,
&m_txn.Payment.c_d_id, 0, NULL) != SQL_SUCCESS
    || SQLBindParameter(m_hstmt, ++i,
SQL_PARAM_INPUT, SQL_C_SLONG, SQL_INTEGER, 0, 0,
&m_txn.Payment.c_id, 0, NULL) != SQL_SUCCESS
    || SQLBindParameter(m_hstmt, ++i,
SQL_PARAM_INPUT, SQL_C_CHAR, SQL_CHAR,
sizeof(m_txn.Payment.c_last), 0,
&m_txn.Payment.c_last, sizeof(m_txn.Payment.c_last),
NULL) != SQL_SUCCESS
    )
    {
        ThrowError(CODBCERR::eBindParam);
    }

    i = 0;
    if ( SQLBindCol(m_hstmt, ++i,
SQL_C_SLONG, &m_txn.Payment.c_id, 0,
NULL) != SQL_SUCCESS
    || SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.Payment.c_last,
sizeof(m_txn.Payment.c_last), NULL) !=
SQL_SUCCESS
    || SQLBindCol(m_hstmt, ++i,
SQL_C_TYPE_TIMESTAMP, &m_txn.Payment.h_date,
0, NULL) != SQL_SUCCESS
    || SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.Payment.w_street_1,
sizeof(m_txn.Payment.w_street_1), NULL) !=
SQL_SUCCESS
    || SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.Payment.w_street_2,
sizeof(m_txn.Payment.w_street_2), NULL) !=
SQL_SUCCESS
    || SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.Payment.w_city,
sizeof(m_txn.Payment.w_city), NULL) !=
SQL_SUCCESS
    || SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.Payment.w_state,
sizeof(m_txn.Payment.w_state), NULL) !=
SQL_SUCCESS
    || SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.Payment.w_zip,
sizeof(m_txn.Payment.w_zip), NULL) !=
SQL_SUCCESS
    || SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.Payment.d_street_1,
sizeof(m_txn.Payment.d_street_1), NULL) !=
SQL_SUCCESS
    || SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.Payment.d_street_2,
sizeof(m_txn.Payment.d_street_2), NULL) !=
SQL_SUCCESS
    || SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.Payment.d_city,

```

```

sizeof(m_txn.Payment.d_city), NULL) !=
SQL_SUCCESS
    || SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.Payment.d_state,
sizeof(m_txn.Payment.d_state), NULL) !=
SQL_SUCCESS
    || SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.Payment.d_zip,
sizeof(m_txn.Payment.d_zip), NULL) !=
SQL_SUCCESS
    || SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.Payment.c_first,
sizeof(m_txn.Payment.c_first), NULL) !=
SQL_SUCCESS
    || SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.Payment.c_middle,
sizeof(m_txn.Payment.c_middle), NULL) !=
SQL_SUCCESS
    || SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.Payment.c_street_1,
sizeof(m_txn.Payment.c_street_1), NULL) !=
SQL_SUCCESS
    || SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.Payment.c_street_2,
sizeof(m_txn.Payment.c_street_2), NULL) !=
SQL_SUCCESS
    || SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.Payment.c_city,
sizeof(m_txn.Payment.c_city), NULL) !=
SQL_SUCCESS
    || SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.Payment.c_state,
sizeof(m_txn.Payment.c_state), NULL) !=
SQL_SUCCESS
    || SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.Payment.c_zip,
sizeof(m_txn.Payment.c_zip), NULL) !=
SQL_SUCCESS
    || SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.Payment.c_phone,
sizeof(m_txn.Payment.c_phone), NULL) !=
SQL_SUCCESS
    || SQLBindCol(m_hstmt, ++i,
SQL_C_TYPE_TIMESTAMP, &m_txn.Payment.c_since,
0, NULL) != SQL_SUCCESS
    || SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.Payment.c_credit,
sizeof(m_txn.Payment.c_credit), NULL) !=
SQL_SUCCESS
    || SQLBindCol(m_hstmt, ++i,
SQL_C_DOUBLE, &m_txn.Payment.c_credit_lim, 0,
NULL) != SQL_SUCCESS
    || SQLBindCol(m_hstmt, ++i,
SQL_C_DOUBLE, &m_txn.Payment.c_discount, 0,
NULL) != SQL_SUCCESS
    || SQLBindCol(m_hstmt, ++i,
SQL_C_DOUBLE, &m_txn.Payment.c_balance, 0,
NULL) != SQL_SUCCESS
    || SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.Payment.c_data,

```

```

        sizeof(m_txn.Payment.c_data), NULL) !=
SQL_SUCCESS
    )
    ThrowError(CODBCERR::eBindCol);

    //Compose Payment statement
    _snwprintf(m_szPaymentCommand,
sizeof(m_szPaymentCommand)/sizeof(m_szPaymentCommand[
0]),
        L"{call %stpcc_payment
(?,?,?,?,?,?)", m_szSPPrefix);
}

void CTPCC_ODBC::Payment()
{
    RETCODE        rc;
    int            iTryCount =
0;

    m_hstmt = m_hstmtPayment;

    if (m_txn.Payment.c_id != 0)
        m_txn.Payment.c_last[0] = 0;

    while (TRUE)
    {
        try
        {
            rc =
SQLExecDirectW(m_hstmt, m_szPaymentCommand, SQL_NTS);
            if (rc != SQL_SUCCESS
&& rc != SQL_SUCCESS_WITH_INFO)

                ThrowError(CODBCERR::eExecDirect);

            if ( SQLFetch(m_hstmt)
== SQL_ERROR)

                ThrowError(CODBCERR::eFetch);

            SQLFreeStmt(m_hstmt,
SQL_CLOSE);

            if (m_txn.Payment.c_id
== 0)

                throw new
CTPCC_ODBC_ERR( CTPCC_ODBC_ERR::ERR_INVALID_CUST );
            else

                m_txn.Payment.exec_status_code = eOK;

            break;
        }
        catch (CODBCERR *e)
        {
            if (!(e->m_bDeadLock)
|| (++iTryCount > iMaxRetries))

                throw;

            // hit deadlock;
            backoff for increasingly longer period

```

```

        delete e;
        Sleep(10 * iTryCount);
    }
}

// if (iTryCount)
// throw new
CTPCC_ODBC_ERR(CTPCC_ODBC_ERR::ERR_RETRIED_TRANS,
iTryCount);
}

void CTPCC_ODBC::InitOrderStatusParams()
{
    if ( SQLAllocHandle(SQL_HANDLE_STMT,
m_hdbc, &m_hstmtOrderStatus) != SQL_SUCCESS
||
SQLAllocHandle(SQL_HANDLE_DESC, m_hdbc,
&m_descOrderStatusCols1) != SQL_SUCCESS
||
SQLAllocHandle(SQL_HANDLE_DESC, m_hdbc,
&m_descOrderStatusCols2) != SQL_SUCCESS
)

    ThrowError(CODBCERR::eAllocHandle);

    m_hstmt = m_hstmtOrderStatus;

    if ( SQLSetStmtAttrW( m_hstmt,
SQL_ATTR_APP_ROW_DESC, m_descOrderStatusCols1,
SQL_IS_POINTER ) != SQL_SUCCESS )

        ThrowError(CODBCERR::eSetStmtAttr);

    int i = 0;
    if ( SQLBindParameter(m_hstmt, ++i,
SQL_PARAM_INPUT, SQL_C_SLONG, SQL_INTEGER, 0, 0,
&m_txn.OrderStatus.w_id, 0, NULL) != SQL_SUCCESS
|| SQLBindParameter(m_hstmt, ++i,
SQL_PARAM_INPUT, SQL_C_UTINYINT, SQL_TINYINT, 0, 0,
&m_txn.OrderStatus.d_id, 0, NULL) != SQL_SUCCESS
|| SQLBindParameter(m_hstmt, ++i,
SQL_PARAM_INPUT, SQL_C_SLONG, SQL_INTEGER, 0, 0,
&m_txn.OrderStatus.c_id, 0, NULL) != SQL_SUCCESS
|| SQLBindParameter(m_hstmt, ++i,
SQL_PARAM_INPUT, SQL_C_CHAR, SQL_CHAR,
sizeof(m_txn.OrderStatus.c_last), 0,
&m_txn.OrderStatus.c_last,
sizeof(m_txn.OrderStatus.c_last), NULL) !=
SQL_SUCCESS
)

        ThrowError(CODBCERR::eBindParam);

    // configure block cursor
    if ( SQLSetStmtAttrW(m_hstmt,
SQL_ATTR_ROW_BIND_TYPE,
(SQLPOINTER)sizeof(m_txn.OrderStatus.OL[0]), 0) !=
SQL_SUCCESS
|| SQLSetStmtAttrW(m_hstmt,
SQL_ATTR_ROWS_FETCHED_PTR, &m_RowsFetched, 0) !=
SQL_SUCCESS
)

```

```

        ThrowError(CODBCERR::eSetStmtAttr);

        i = 0;
        if ( SQLBindCol(m_hstmt, ++i,
SQL_C_SLONG, &m_txn.OrderStatus.OL[0].ol_supply_w_id,
0, NULL) != SQL_SUCCESS
|| SQLBindCol(m_hstmt, ++i,
SQL_C_SLONG, &m_txn.OrderStatus.OL[0].ol_i_id, 0,
NULL) != SQL_SUCCESS
|| SQLBindCol(m_hstmt, ++i,
SQL_C_SSHORT, &m_txn.OrderStatus.OL[0].ol_quantity,
0, NULL) != SQL_SUCCESS
|| SQLBindCol(m_hstmt, ++i,
SQL_C_DOUBLE, &m_txn.OrderStatus.OL[0].ol_amount, 0,
NULL) != SQL_SUCCESS
|| SQLBindCol(m_hstmt, ++i,
SQL_C_TYPE_TIMESTAMP,
&m_txn.OrderStatus.OL[0].ol_delivery_d, 0, NULL) !=
SQL_SUCCESS
)

            ThrowError(CODBCERR::eBindCol);

        if ( SQLSetStmtAttrW( m_hstmt,
SQL_ATTR_APP_ROW_DESC, m_descOrderStatusCols2,
SQL_IS_POINTER ) != SQL_SUCCESS )

            ThrowError(CODBCERR::eSetStmtAttr);

        i = 0;
        if ( SQLBindCol(m_hstmt, ++i,
SQL_C_SLONG, &m_txn.OrderStatus.c_id, 0, NULL) !=
SQL_SUCCESS
|| SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.OrderStatus.c_last,
sizeof(m_txn.OrderStatus.c_last), NULL) !=
SQL_SUCCESS
|| SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.OrderStatus.c_first,
sizeof(m_txn.OrderStatus.c_first), NULL) !=
SQL_SUCCESS
|| SQLBindCol(m_hstmt, ++i,
SQL_C_CHAR, &m_txn.OrderStatus.c_middle,
sizeof(m_txn.OrderStatus.c_middle), NULL) !=
SQL_SUCCESS
|| SQLBindCol(m_hstmt, ++i,
SQL_C_TYPE_TIMESTAMP, &m_txn.OrderStatus.o_entry_d,
0, NULL) != SQL_SUCCESS
|| SQLBindCol(m_hstmt, ++i,
SQL_C_SSHORT, &m_txn.OrderStatus.o_carrier_id, 0,
NULL) != SQL_SUCCESS
|| SQLBindCol(m_hstmt, ++i,
SQL_C_DOUBLE, &m_txn.OrderStatus.o_balance, 0, NULL)
!= SQL_SUCCESS
|| SQLBindCol(m_hstmt, ++i,
SQL_C_SLONG, &m_txn.OrderStatus.o_id, 0, NULL) !=
SQL_SUCCESS
)

            ThrowError(CODBCERR::eBindCol);

```

```

        //Compose Order Status statement
        _snwprintf(m_szOrderStatusCommand,
sizeof(m_szOrderStatusCommand)/sizeof(m_szOrderStatus
Command[0]),
                L"{call %stpcc_orderstatus
(?,?,?,?)", m_szSPPrefix);
}

void CTPCC_ODBC::OrderStatus()
{
    int        iTryCount = 0;
    RETCODE
    rc;

    m_hstmt = m_hstmtOrderStatus;

    if ( SQLSetStmtAttrW( m_hstmt,
SQL_ATTR_APP_ROW_DESC, m_descOrderStatusCols1,
SQL_IS_POINTER ) != SQL_SUCCESS )

        ThrowError(CODBCERR::eSetStmtAttr);

    if (m_txn.OrderStatus.c_id != 0)
        m_txn.OrderStatus.c_last[0] = 0;

    while (TRUE)
    {
        try
        {
            // configure block
            cursor
                if (
SQLSetStmtAttrW(m_hstmt, SQL_ATTR_ROW_ARRAY_SIZE,
(SQLPOINTER)1, 0) != SQL_SUCCESS )

                    ThrowError(CODBCERR::eSetStmtAttr);

            rc =
SQLExecDirectW(m_hstmt, m_szOrderStatusCommand,
SQL_NTS);
            if ( ((rc ==
SQL_SUCCESS_WITH_INFO) && (m_RowsFetched != 0)) ||
(rc == SQL_ERROR) )

                ThrowError(CODBCERR::eExecDirect);

            // configure block
            cursor
                if (
SQLSetStmtAttrW(m_hstmt, SQL_ATTR_ROW_ARRAY_SIZE,
(SQLPOINTER)MAX_OL_ORDER_STATUS_ITEMS, 0) !=
SQL_SUCCESS )

                    ThrowError(CODBCERR::eSetStmtAttr);

            rc = SQLFetchScroll(
m_hstmt, SQL_FETCH_NEXT, 0 );
            if ( ((rc ==
SQL_SUCCESS_WITH_INFO) && (m_RowsFetched != 0)) ||
(rc == SQL_ERROR) )

```

```

        ThrowError(CODBCERR::eFetchScroll);

        m_txn.OrderStatus.o_ol_cnt =
(short)m_RowsFetched;

        if
(m_txn.OrderStatus.o_ol_cnt != 0)
        {
            if (
SQLSetStmtAttrW( m_hstmt, SQL_ATTR_APP_ROW_DESC,
m_descOrderStatusCols2, SQL_IS_POINTER ) !=
SQL_SUCCESS )

                ThrowError(CODBCERR::eSetStmtAttr);

            if (
SQLMoreResults(m_hstmt) == SQL_ERROR )

                ThrowError(CODBCERR::eMoreResults);

            if ( rc =
SQLFetch(m_hstmt)) == SQL_ERROR)

                ThrowError(CODBCERR::eFetch);

            SQLFreeStmt(m_hstmt,
SQL_CLOSE);

            if
(m_txn.OrderStatus.o_ol_cnt == 0)
                throw new
CTPCC_ODBC_ERR( CTPCC_ODBC_ERR::ERR_NO_SUCH_ORDER );
            else if
(m_txn.OrderStatus.c_id == 0 &&
m_txn.OrderStatus.c_last[0] == 0)
                throw new
CTPCC_ODBC_ERR( CTPCC_ODBC_ERR::ERR_INVALID_CUST );

            m_txn.OrderStatus.exec_status_code = eOK;

            break;
        }
        catch (CODBCERR *e)
        {
            if (!(e->m_bDeadLock))
                throw;

            // hit deadlock;
            backoff for increasingly longer period
            delete e;
            Sleep(10 * iTryCount);
        }
    }

    // if (iTryCount)

```

```

        // throw new
CTPCC_ODBC_ERR(CTPCC_ODBC_ERR::ERR_RETRIED_TRANS,
iTryCount);
}

void CTPCC_ODBC::InitDeliveryParams()
{
    if ( SQLAllocHandle(SQL_HANDLE_STMT,
m_hdbc, &m_hstmtDelivery) != SQL_SUCCESS )

        ThrowError(CODBCERR::eAllocHandle);

    m_hstmt = m_hstmtDelivery;

    int i = 0;
    if ( SQLBindParameter(m_hstmt, ++i,
SQL_PARAM_INPUT, SQL_C_SLONG, SQL_INTEGER, 0, 0,
&m_txn.Delivery.w_id, 0, NULL) != SQL_SUCCESS
|| SQLBindParameter(m_hstmt, ++i,
SQL_PARAM_INPUT, SQL_C_SSHORT, SQL_SMALLINT, 0, 0,
&m_txn.Delivery.o_carrier_id, 0, NULL) != SQL_SUCCESS
)
        ThrowError(CODBCERR::eBindParam);

    for (i=0;i<10;i++)
    {
        if ( SQLBindCol(m_hstmt,
(UWORD)(i+1), SQL_C_SLONG, &m_txn.Delivery.o_id[i],
0, NULL) != SQL_SUCCESS )

            ThrowError(CODBCERR::eBindCol);
    }

    //Compose Delivery statement
    _snwprintf(m_szDeliveryCommand,
sizeof(m_szDeliveryCommand)/sizeof(m_szDeliveryComman
d[0]),
                L"{call %stpcc_delivery (?,?)",
m_szSPPrefix);
}

void CTPCC_ODBC::Delivery()
{
    RETCODE        rc;
    int            iTryCount =
0;

    m_hstmt = m_hstmtDelivery;

    while (TRUE)
    {
        try
        {
            rc =
SQLExecDirectW(m_hstmt, m_szDeliveryCommand,
SQL_NTS);
            if (rc != SQL_SUCCESS
&& rc != SQL_SUCCESS_WITH_INFO)

                ThrowError(CODBCERR::eExecDirect);

```

```

        if ( SQLFetch(m_hstmt)
== SQL_ERROR )
        ThrowError(COBCERR::eFetch);

        SQLFreeStmt(m_hstmt,
SQL_CLOSE);

        m_txn.Delivery.exec_status_code = eOK;
        break;
    }
    catch (COBCERR *e)
    {
        if (!(e->m_bDeadLock)
|| (++iTryCount > iMaxRetries))
            throw;

        // hit deadlock;
        backoff for increasingly longer period
        delete e;
        Sleep(10 * iTryCount);
    }
}

// if (iTryCount)
// throw new
CTPCC_ODBC_ERR(CTPCC_ODBC_ERR::ERR_RETRIED_TRANS,
iTryCount);
}

```

tpcc_odbc.h

```

/* FILE: TPC_ODBC.H
 * Microsoft
TPC-C Kit Ver. 4.20.000
 * Copyright
Microsoft, 1999
 * All Rights Reserved
 *
 * Version
4.10.000 audited by Richard Gimarc, Performance
Metrics, 3/17/99
 *
 * PURPOSE: Header file for TPC-C txn class
implementation.
 *
 * Change history:
 * 4.20.000 - updated rev number to
match kit
 */
#pragma once

// need to declare functions for import, unless
define has already been created
// by the DLL's .cpp module for export.
#ifdef DllDecl
#define DllDecl __declspec( dllimport )
#endif

```

```

#define iMAX_SP_NAME_LEN 256 //maximum length of a
stored procedure name with parameters

class COBCERR : public CBaseErr
{
public:
    enum ACTION
    {
        eNone,
        eUnknown,
        eAllocConn,
        // error from SQLAllocConnect
        eAllocHandle,
        // error from SQLAllocHandle
        eConnOption,
        // error from SQLSetConnectOption
        eConnect,
        // error from SQLConnect
        eAllocStmt,
        // error from SQLAllocStmt
        eExecDirect,
        // error from SQLExecDirect
        eBindParam,
        // error from SQLBindParameter
        eBindCol,
        // error from SQLBindCol
        eFetch,
        // error from SQLFetch
        eFetchScroll,
        // error from SQLFetchScroll
        eMoreResults,
        // error from SQLMoreResults
        ePrepare,
        // error from SQLPrepare
        eExecute,
        // error from SQLExecute
        eSetEnvAttr,
        // error from SQLSetEnvAttr
        eSetStmtAttr,
        // error from SQLSetStmtAttr
    };

    COBCERR(void)
    {
        m_eAction = eNone;
        m_NativeError = 0;
        m_bDeadLock = FALSE;
        m_odbcerrstr = NULL;
    };

    ~COBCERR()
    {
        if (m_odbcerrstr !=
NULL)
            delete []
m_odbcerrstr;
    };

    ACTION m_eAction;
    int
m_NativeError;

```

```

        BOOL m_bDeadLock;
        char *m_odbcerrstr;

        int
        ErrorType()
        {return ERR_TYPE_ODBC;};
        char*
        ErrorTypeStr() { return
"ODBC"; }
        int
        ErrorNum()
        {return m_NativeError;};
        char*
        ErrorText() {return
m_odbcerrstr;};
        int
        ErrorAction()
        { return (int)m_eAction; }
    };

class CTPCC_ODBC_ERR : public CBaseErr
{
public:
    enum TPCC_ODBC_ERRS
    {
        ERR_WRONG_SP_VERSION =
1, // "Wrong version of stored procs on
database server"
        ERR_INVALID_CUST,
        // "Invalid Customer id,name."
        ERR_NO_SUCH_ORDER,
        // "No orders found for
customer."
        ERR_RETRIED_TRANS,
        // "Retries before transaction
succeeded."
    };

    CTPCC_ODBC_ERR( int iErr ) {
m_errno = iErr; m_iTryCount = 0; };

    CTPCC_ODBC_ERR( int iErr, int
iTryCount ) { m_errno = iErr; m_iTryCount =
iTryCount; };

        int m_errno;
        int m_iTryCount;

        int
        ErrorType()
        {return ERR_TYPE_TPCC_ODBC;};
        char*
        ErrorTypeStr() { return
"TPCC ODBC"; }
        int
        ErrorNum()
        {return m_errno;};
        char*
        ErrorText();
    };

class DllDecl CTPCC_ODBC : public CTPCC_BASE
{
private:
    // declare variables and private
functions here...
    BOOL m_bDeadlock;
    // transaction was selected as
deadlock victim

```

```

        int
        m_MaxRetries;          // retry
count on deadlock

        SQLHENV          m_henv;
        // ODBC environment

handle
        SQLHDBC          m_hdbc;
        SQLHSTMT m_hstmt;
        // the current hstmt

        SQLHSTMT m_hstmtNewOrder;
        SQLHSTMT
m_hstmtNewOrderNoDuplicates; // NewOrder
with one result set for lineitem details
        SQLHSTMT m_hstmtPayment;
        SQLHSTMT m_hstmtDelivery;
        SQLHSTMT m_hstmtOrderStatus;
        SQLHSTMT m_hstmtStockLevel;

        SQLHDESC m_descNewOrderCols1;
        SQLHDESC m_descNewOrderCols2;
        SQLHDESC
m_descNewOrderNoDuplicatesCols1; //
NewOrder with one result set for lineitem details
        SQLHDESC
m_descNewOrderNoDuplicatesCols2; //
NewOrder with one result set for lineitem details
        SQLHDESC m_descOrderStatusCols1;
        SQLHDESC m_descOrderStatusCols2;

        wchar_t
m_szSPPrefix[32]; // stored procedures
prefix

        wchar_t
m_szNewOrderCommand[iMAX_SP_NAME_LEN];
        wchar_t
m_szNewOrderNoDuplicatesCommand[iMAX_SP_NAME
E_LEN];

        int
m_iBeginNewOrderVariablePart; // begining
of the variable part in NewOrder statement
        int
m_iBeginNewOrderNoDuplicatesVariablePart;
// begining of the variable part in
NewOrder statement
        wchar_t
m_szPaymentCommand[iMAX_SP_NAME_LEN];
        wchar_t
m_szDeliveryCommand[iMAX_SP_NAME_LEN];
        wchar_t
m_szOrderStatusCommand[iMAX_SP_NAME_LEN];
        wchar_t
m_szStockLevelCommand[iMAX_SP_NAME_LEN];

        // new-order specific fields
        SQLINTEGER m_BindOffset;
        SQLINTEGER
m_RowsFetched;

```

```

        int
m_no_commit_flag;

        // tpcc_neworder_new flag
        BOOL
m_bCallNoDuplicatesNewOrder;

        void ThrowError( COBDCERR::ACTION
eAction );

        void InitNewOrderParams();
        void InitPaymentParams();
        void InitDeliveryParams();
        void InitStockLevelParams();
        void InitOrderStatusParams();

        union
        {
                NEW_ORDER_DATA
NewOrder;
                PAYMENT_DATA
Payment;
                DELIVERY_DATA
Delivery;
                STOCK_LEVEL_DATA
StockLevel;
                ORDER_STATUS_DATA
OrderStatus;
        }
m_txn;

        bool DuplicatesInNewOrder();
        void NewOrderDuplicates();
        void NewOrderNoDuplicates();

public:
        CTPCC_ODBC( LPCSTR
szServer, LPCSTR szUser, LPCSTR szPassword,
LPCSTR szHost, LPCSTR szDatabase,
LPCWSTR szSPPrefix, BOOL
bCallNoDuplicatesNewOrder);
        ~CTPCC_ODBC(void);

        inline PNEW_ORDER_DATA
BuffAddr_NewOrder() { return
&m_txn.NewOrder; };
        inline PPAYMENT_DATA
BuffAddr_Payment() { return
&m_txn.Payment; };
        inline PDELIVERY_DATA
BuffAddr_Delivery() { return
&m_txn.Delivery; };
        inline PSTOCK_LEVEL_DATA
BuffAddr_StockLevel() { return
&m_txn.StockLevel; };
        inline PORDER_STATUS_DATA
BuffAddr_OrderStatus() { return
&m_txn.OrderStatus; };

```

```

        void NewOrder          ();
        void Payment          ();
        void Delivery         ();
        void StockLevel       ();
        void OrderStatus      ();
};

// wrapper routine for class constructor
extern "C" DllDecl CTPCC_ODBC* CTPCC_ODBC_new
( LPCSTR szServer, LPCSTR szUser,
LPCSTR szPassword, LPCSTR szHost, LPCSTR szDatabase,
LPCWSTR szSPPrefix, BOOL
bCallNoDuplicatesNewOrder );

typedef CTPCC_ODBC* (TYPE_CTPCC_ODBC) (LPCSTR, LPCSTR,
LPCSTR, LPCSTR, LPCSTR, LPCWSTR, BOOL);

tpcc_tux.cpp
/* FILE: TPCC_TUX.CPP
 * Microsoft
TPC-C Kit Ver. 4.20.000
 * Copyright
Microsoft, 1999
 * All Rights Reserved
 *
 * Version
4.10.000 audited by Richard Gimarc, Performance
Metrics, 3/17/99
 *
 * PURPOSE: Implementation for TPC-C Tuxedo
class.
 * Contact: Charles Levine
(clevine@microsoft.com)
 *
 * Change history:
 * 4.20.000 - updated rev number to
match kit
 */

#include <windows.h>
#include <process.h>
#include <stdio.h>
#include <stdarg.h>
#include <malloc.h>
#include <stdlib.h>
#include <string.h>
#include <time.h>
#include <sys\timeb.h>
#include <io.h>
#include <assert.h>

#include <tmenv.h>
#include <xa.h>
#include <atmi.h>

#ifdef ICECAP

```

```

// for IceCAP profiling
#include <icapexp.h>
#endif

// need to declare functions for export
#define DllDecl __declspec( dllexport )

#include "..\..\common\src\trans.h"
//tpckit transaction header contains
definitions of structures specific to TPC-C
#include "..\..\common\src\error.h"
#include "..\..\common\src\txn_base.h"
#include "tpcc_tux.h"
// interface to Tuxedo libraries

static TPINIT
*tpinf;
static DWORD
TLSIsTpInitedKey;
static CRITICAL_SECTION
TpCriticalSection;

BOOL APIENTRY DllMain(HMODULE hModule, DWORD
ul_reason_for_call, LPVOID lpReserved)
{
    switch( ul_reason_for_call )
    {
        case DLL_PROCESS_ATTACH:
            DisableThreadLibraryCalls(hModule);

            // create thread local
storage to determine Tuxedo initialization per
thread.
            // it really should be
possible to do this in the DLL_THREAD_ATTACH call,
but
            // Ed says he could not
get it to work.
            // assumption: value
init'd to 0
            TLSIsTpInitedKey =
            TlsAlloc();
            if ((tpinf = (TPINIT
*)tpalloc("TPINIT", NULL, sizeof(TPINIT))) == NULL)
            {
                // int TpRc =
                tperrno;
                return FALSE;
            }
            tpinf->flags |=
            TPMULTICONTEXTS;
            InitializeCriticalSection(&TpCriticalSectio
n);
            break;
        case DLL_PROCESS_DETACH:

```

```

TlsFree(TLSIsTpInitedKey);
DeleteCriticalSection(&TpCriticalSection);
break;
    default:
        /* nothing */;
    }
    return TRUE;
}

static void ThrTpInit()
{
    static int num_tpinit=0;
    int iRc, TpRc;

    // has this thread been initialized? check
thread local storage
    if(!TlsGetValue(TLSIsTpInitedKey))
    {
        EnterCriticalSection(&TpCriticalSection);
        itoa(++num_tpinit, tpinf-
>cltname, 10);

        iRc = tpinit(tpinf);
        TpRc = tperrno;

        LeaveCriticalSection(&TpCriticalSection);

        if (iRc < 0)
            throw new CTUXERR(
tperrno );

        int value = 1;

        TlsSetValue(TLSIsTpInitedKey, &value);
    }

    // wrapper routine for class constructor
__declspec( dllexport ) CTPCC_TUXEDO*
CTPCC_TUXEDO_new()
{
    return new CTPCC_TUXEDO();
}

CTPCC_TUXEDO::CTPCC_TUXEDO()
{
    // Add initialization of Tuxedo
Structures
    m_txn = (TUX_DATA *)tpalloc("CARRAY", NULL,
sizeof(TUX_DATA));
    if (m_txn == NULL)
        throw new CTUXERR( tperrno );
}

CTPCC_TUXEDO::~CTPCC_TUXEDO()
{

```

```

// free the data structure allocated with
tpalloc
    tpfree((char *)m_txn);
}

void CTPCC_TUXEDO::NewOrder()
{
    long ilen, *olen;

    ThrTpInit();

    ilen = sizeof(TUX_DATA);
    olen = &ilen;

    if (tpcall("NEWORDER", (char *)m_txn, ilen,
(char **)&m_txn, (long *)olen, TPSIGRSTRT == -1)
        throw new CTUXERR( tperrno );

    if ( m_txn->ErrorType != ERR_SUCCESS )
        throw new CTUXERR( m_txn-
>ErrorType, m_txn->error );
}

void CTPCC_TUXEDO::Payment()
{
    long ilen, *olen;

    ThrTpInit();

    ilen = sizeof(TUX_DATA);
    olen = &ilen;

    if (tpcall("PAYMENT", (char *)m_txn, ilen,
(char **)&m_txn, (long *)olen, TPSIGRSTRT == -1)
        throw new CTUXERR( tperrno );

    if ( m_txn->ErrorType != ERR_SUCCESS )
        throw new CTUXERR( m_txn-
>ErrorType, m_txn->error );
}

void CTPCC_TUXEDO::Delivery()
{
    int iRc;
    long ilen, *olen;

    // Note: Delivery txn code in the tuxedo
server does not implement logging of the delivery
txn results, so cannot be used as
is to run an auditable TPC-C result. For that
reason, delivery txns should not
be done via tuxedo.
    // The code is included for
completeness.
    m_txn->u.Delivery.exec_status_code =
eDeliveryFailed;
    return;

    // normal path...
    ThrTpInit();
}

```



```

        GetLocalTime(&m_txn-
>u.Delivery.queue_time);
        ilen = sizeof(TUX_DATA);
        olen = &ilen;

        if ((iRc = tpacall("DELIVERY", (char
*)m_txn, ilen, TPNOREPLY)) == -1)
        {
            int TpRc = tperrno;
            m_txn-
>u.Delivery.exec_status_code = eDeliveryFailed;
        }
        else
            m_txn-
>u.Delivery.exec_status_code = eOK;
    }

void CTPCC_TUXEDO::StockLevel()
{
    long    ilen, *olen;

    ThrTpInit();

    ilen = sizeof(TUX_DATA);
    olen = &ilen;

    if (tpcall("STOCKLEVEL", (char *)m_txn,
ilen, (char **)&m_txn, (long *)olen, TPSIGRSTRT) == -
1)
        throw new CTUXERR( tperrno );

    if ( m_txn->ErrorType != ERR_SUCCESS )
        throw new CTUXERR( m_txn-
>ErrorType, m_txn->error );
}

void CTPCC_TUXEDO::OrderStatus()
{
    long    ilen, *olen;

    ThrTpInit();

    ilen = sizeof(TUX_DATA);
    olen = &ilen;

    if (tpcall("ORDERSTATUS", (char *)m_txn,
ilen, (char **)&m_txn, (long *)olen, TPSIGRSTRT) == -
1)
        throw new CTUXERR( tperrno );

    if ( m_txn->ErrorType != ERR_SUCCESS )
        throw new CTUXERR( m_txn-
>ErrorType, m_txn->error );
}

char *CTUXERR::ErrorText()
{
    if (m_iErrorType == 0)

```

```

    {
        if (m_errno == TPEOS)
            sprintf( m_szErrorText,
"Error: TUXEDO error # %d, OS error # %d", m_errno,
m_iError );
        else
            sprintf( m_szErrorText,
"Error: TUXEDO error # %d", m_errno );
        }
        else
            sprintf( m_szErrorText, "Error:
Class %d, error # %d", m_iErrorType, m_iError );
        return m_szErrorText;
    };
}

```

tpcc_tux.h

```

/* FILE: TPC_C_TUX.H
 * Microsoft
 * TPC-C Kit Ver. 4.20.000
 * Copyright
 * Microsoft, 1999
 * All Rights Reserved
 *
 * Version
 * 4.10.000 audited by Richard Gimarc, Performance
 * Metrics, 3/17/99
 *
 * PURPOSE: Header file for TPC-C Tuxedo
 * class implementation.
 *
 * Change history:
 * 4.20.000 - updated rev number to
 * match kit
 */

#pragma once

// need to declare functions for import, unless
// define has already been created
// by the DLL's .cpp module for export.
#ifdef DllDecl
#define DllDecl __declspec( dllimport )
#endif

class DllDecl CTPCC_TUXEDO : public CTPCC_BASE
{
private:
    struct TUX_DATA
    {
        int
        ErrorType;
        int
        error;

        union
        {
            NEW_ORDER_DATA          NewOrder;

```

```

            PAYMENT_DATA          Payment;
            DELIVERY_DATA         Delivery;

            STOCK_LEVEL_DATA      StockLevel;

            ORDER_STATUS_DATA     OrderStatus;
        } u;
    };

public:
    CTPCC_TUXEDO();
    ~CTPCC_TUXEDO(void);

    inline PNEW_ORDER_DATA
    BuffAddr_NewOrder() { return
&m_txn->u.NewOrder; };
    inline PPAYMENT_DATA
    BuffAddr_Payment() { return
&m_txn->u.Payment; };
    inline PDELIVERY_DATA
    BuffAddr_Delivery() { return
&m_txn->u.Delivery; };
    inline PSTOCK_LEVEL_DATA
    BuffAddr_StockLevel() { return
&m_txn->u.StockLevel; };
    inline PORDER_STATUS_DATA
    BuffAddr_OrderStatus() { return
&m_txn->u.OrderStatus; };

    void NewOrder          ();
    void Payment           ();
    void Delivery          ();
    void StockLevel        ();
    void OrderStatus      ();
};

class CTUXERR : public CBaseErr
{
private:
    // TODO: should use the sz_Msg
    // field of the base class instead
    char m_szErrorText[64];

public:
    // use this interface for genuine
    // Tuxedo errors
    CTUXERR( int iErr )
    {
        m_errno = iErr;
        m_iErrorType = 0;
        m_iError =
    };

    GetLastError(); // only meaningful if m_errno ==
    TPEOS

    // use this interface to
    // impersonate a non-Tuxedo error type

```

```

iError )
    CTUXERR( int iErrorType, int
    {
        m_iErrorType =
iErrorType;
        m_iError = iError;
        m_errno = 0;
    }

    int m_errno;
    int m_iErrorType;
    int m_iError;

    // A CTUXERR class can
    impersonate another class, which happens if the error
    // was not actually a Tuxedo
    error, but was simply transmitted back via Tuxedo.
    int ErrorType()
    {
        if (m_iErrorType == 0)
            return
ERR_TYPE_TUXEDO;
        else
            return
m_iErrorType;
    }

    int ErrorNum() {return m_errno;};
    char *ErrorText();
};

// wrapper routine for class constructor
extern "C" __declspec(dllexport) CTPCC_TUXEDO*
CTPCC_TUXEDO_new();

typedef CTPCC_TUXEDO* (TYPE_CTPCC_TUXEDO)();

```

tpcc_type.h

```

/* Generated by IDL compiler version DEC DCE V2.0.0-6
*/
#ifndef tpcc_types_v1_0_included
#define tpcc_types_v1_0_included
#endif
#include <dce\idlbase.h>
#endif

#ifdef __cplusplus
extern "C" {
#endif

#ifndef nbase_v0_0_included
#include "dce\nbase.h"
#endif
#define NAME_LENGTH (32)
#define NEWO_INTERFACE (1)
#define PAYMENT_INTERFACE (2)
#define ORDER_STAT_INTERFACE (4)
#define DELIVERY_INTERFACE (8)
#define STOCK_INTERFACE (16)

```

```

#define ONLINE_INTERFACES (23)
#define ALL_INTERFACE (65535)
#define NEWO_TRANS (1)
#define PAYMENT_TRANS (2)
#define ORDER_STAT_TRANS (3)
#define DELIVERY_TRANS (4)
#define STOCK_TRANS (5)
#define MAX_TRAN_TYPE (5)
#define TPCC_SUCCESS (0)
#define TRPC_ERROR (1)
#define INVALID_NEWO (100)
typedef struct {
    idl_long_int sec;
    idl_long_int usec;
} time_type;
typedef struct {
    idl_short_int returncode;
    idl_short_int stats;
    time_type srv_start;
    time_type srv_end;
    time_type clnt_start;
    time_type clnt_end;
} data_header;
typedef struct {
    idl_long_int first_wh;
    idl_long_int last_wh;
    idl_long_int server_id;
} dbInfo_data_t;

#ifdef __cplusplus
}
#endif
#endif

```

trans.h

```

/* FILE: TRANS.H Microsoft
 * TPC-C Kit Ver. 4.42.000 Copyright
 * Microsoft, 2002
 * All Rights Reserved
 * Version
 * 4.10.000 audited by Richard Gimarc, Performance
 * Metrics, 3/17/99
 * PURPOSE: Header file for TPC-C structure
 * templates.
 * Change history:
 * 4.42.000 - changed w_id fields
 * from short to long to support >32K warehouses
 * 4.20.000 - updated rev number to
 * match kit
 */
#pragma once

// String length constants

```

```

#define SERVER_NAME_LEN 20
#define DATABASE_NAME_LEN 20
#define USER_NAME_LEN 20
#define PASSWORD_LEN 20
#define TABLE_NAME_LEN 20
#define I_DATA_LEN 50
#define I_NAME_LEN 24
#define BRAND_LEN 1
#define LAST_NAME_LEN 16
#define W_NAME_LEN 10
#define ADDRESS_LEN 20
#define STATE_LEN 2
#define ZIP_LEN 9
#define S_DIST_LEN 24
#define S_DATA_LEN 50
#define D_NAME_LEN 10
#define FIRST_NAME_LEN 16
#define MIDDLE_NAME_LEN 2
#define PHONE_LEN 16
#define DATETIME_LEN 30
#define CREDIT_LEN 2
#define C_DATA_LEN 250
#define H_DATA_LEN 24
#define DIST_INFO_LEN 24
#define MAX_OL_NEW_ORDER_ITEMS 15
#define MAX_OL_ORDER_STATUS_ITEMS 15
#define STATUS_LEN 25
#define OL_DIST_INFO_LEN 24

// TIMESTAMP_STRUCT is provided by the ODBC header
// file sqltypes.h, but is not available
// when compiling with dblink, so redefined here.
// Note: we are using the symbol "_SQLTYPES"
// (declared in sqltypes.h) as a way to determine if
// TIMESTAMP_STRUCT has been declared.
#ifdef _SQLTYPES
typedef struct
{
    /* SQLSMALLINT */ short
    year;
    SQLSMALLINT */ unsigned short /*
    month;
    SQLSMALLINT */ unsigned short /*
    day;
    SQLSMALLINT */ unsigned short /*
    hour;
    SQLSMALLINT */ unsigned short /*
    minute;
    SQLSMALLINT */ unsigned short /*
    second;
    SQLSMALLINT */ unsigned long /*
    fraction;
} TIMESTAMP_STRUCT;
#endif

// possible values for exec_status_code after
// transaction completes
enum EXEC_STATUS
{
    eOK, // 0
    "Transaction committed."
}

```

```

        eInvalidItem, // 1 "Item number
is not valid."
        eDeliveryFailed // 2 "Delivery
Post Failed."
};

// transaction structures
typedef struct
{
    // input params
    long
    ol_supply_w_id;
    long
    ol_i_id;
    short
    ol_quantity;

    // output params
    char
    ol_i_name[I_NAME_LEN+1];
    char
    ol_brand_generic[BRAND_LEN+1];
    double
    ol_i_price;
    double
    ol_amount;
    short
    ol_stock;
} OL_NEW_ORDER_DATA;

typedef struct
{
    // input params
    long w_id;
    short d_id;
    long c_id;
    short o_ol_cnt;

    // output params
    EXEC_STATUS
    exec_status_code;
    char
    c_last[LAST_NAME_LEN+1];
    char
    c_credit[CREDIT_LEN+1];
    double
    c_discount;
    double
    w_tax;
    double
    d_tax;
    long o_id;
    short
    o_commit_flag;
    TIMESTAMP_STRUCT
    o_entry_d;
    short
    o_all_local;
    double
    total_amount;
    OL_NEW_ORDER_DATA
    OL[MAX_OL_NEW_ORDER_ITEMS];
} NEW_ORDER_DATA, *PNEW_ORDER_DATA;

typedef struct
{
    // input params
    long
    w_id;

```

```

    short
    d_id;
    long
    c_id;
    short
    c_d_id;
    long
    c_w_id;
    double
    h_amount;
    char
    c_last[LAST_NAME_LEN+1];

    // output params
    EXEC_STATUS
    exec_status_code;
    TIMESTAMP_STRUCT
    h_date;
    char
    w_street_1[ADDRESS_LEN+1];
    char
    w_street_2[ADDRESS_LEN+1];
    char
    w_city[ADDRESS_LEN+1];
    char
    w_state[STATE_LEN+1];
    char
    w_zip[ZIP_LEN+1];
    char
    d_street_1[ADDRESS_LEN+1];
    char
    d_street_2[ADDRESS_LEN+1];
    char
    d_city[ADDRESS_LEN+1];
    char
    d_state[STATE_LEN+1];
    char
    d_zip[ZIP_LEN+1];
    char
    c_first[FIRST_NAME_LEN+1];
    char
    c_middle[MIDDLE_NAME_LEN + 1];
    char
    c_street_1[ADDRESS_LEN+1];
    char
    c_street_2[ADDRESS_LEN+1];
    char
    c_city[ADDRESS_LEN+1];
    char
    c_state[STATE_LEN+1];
    char
    c_zip[ZIP_LEN+1];
    char
    c_phone[PHONE_LEN+1];
    TIMESTAMP_STRUCT
    c_since;
    char
    c_credit[CREDIT_LEN+1];
    double
    c_credit_lim;
    double
    c_discount;

```

```

    double
    c_balance;
    char
    c_data[200+1];
} PAYMENT_DATA, *PPAYMENT_DATA;

typedef struct
{
    long
    ol_i_id;
    long
    ol_supply_w_id;
    short
    ol_quantity;
    double
    ol_amount;
    TIMESTAMP_STRUCT
    ol_delivery_d;
} OL_ORDER_STATUS_DATA;

typedef struct
{
    // input params
    long w_id;
    short d_id;
    long c_id;
    char
    c_last[LAST_NAME_LEN+1];

    // output params
    EXEC_STATUS
    exec_status_code;
    char
    c_first[FIRST_NAME_LEN+1];
    char
    c_middle[MIDDLE_NAME_LEN+1];
    double
    c_balance;
    long
    o_id;
    TIMESTAMP_STRUCT
    o_entry_d;
    short
    o_carrier_id;
    OL_ORDER_STATUS_DATA
    OL[MAX_OL_ORDER_STATUS_ITEMS];
    short
    o_ol_cnt;
} ORDER_STATUS_DATA, *PORDER_STATUS_DATA;

typedef struct
{
    // input params
    long w_id;
    short
    o_carrier_id;

    // output params
    EXEC_STATUS
    exec_status_code;
    SYSTEMTIME
    queue_time;
    long
    o_id[10]; // id's of delivered
orders for districts 1 to 10
} DELIVERY_DATA, *PDELIVERY_DATA;

//This structure is used for posting delivery
transactions and for writing them to the delivery
server.

```

```

typedef struct _DELIVERY_TRANSACTION
{
    SYSTEMTIME        queue;
    //time delivery transaction queued
    long              w_id;
    //delivery warehouse
    short             o_carrier_id;
    //carrier id
} DELIVERY_TRANSACTION;

typedef struct
{
    // input params
    long              w_id;
    short             d_id;
    short             threshold;

    // output params
    EXEC_STATUS      exec_status_code;
    long              low_stock;
} STOCK_LEVEL_DATA, *PSTOCK_LEVEL_DATA;

```

tuxapp.cpp

```

/* FILE: TUXAPP.CPP
 * Microsoft
 * TPC-C Kit Ver. 4.20.000
 * Copyright
 * Microsoft, 1999
 * All Rights Reserved
 * Version
 * 4.10.000 audited by Richard Gimarc, Performance
 * Metrics, 3/17/99
 * PURPOSE: Implementation for TPC-C Tuxedo
 * server.
 * Contact: Charles Levine
 * (clevine@microsoft.com)
 * Change history:
 * 4.20.000 - updated rev number to
 * match kit
 */

#include <windows.h>
#include <process.h>
#include <tchar.h>
#include <stdio.h>
#include <stdarg.h>
#include <iostream.h>
#include <malloc.h>
#include <stdlib.h>
#include <string.h>
#include <time.h>
#include <sys\timeb.h>

```

```

#include <io.h>
#include <assert.h>

#include <sqltypes.h>
#include <sql.h>
#include <sqlext.h>

#include <tmenv.h>
#include <xa.h>
#include <atmi.h>

#include "..\..\common\src\trans.h"
//tpckit transaction header contains
definitions of structures specific to TPC-C
#include "..\..\common\src\error.h"
#include "..\..\common\src\txn_base.h"
#include "..\..\common\src\ReadRegistry.h"
#include "..\..\db_dblib_dll\src\tpcc_dblib.h"
// DBLIB implementation of TPC-C txns
#include "..\..\db_odbc_dll\src\tpcc_odbc.h"
// ODBC implementation of TPC-C txns
#include "tuxapp.h"

char
    szMyComputerName[MAX_COMPUTERNAME_LENGTH+1]
;

// configuration settings from registry
TPCCREGISTRYDATA    Reg;

CTPCC_BASE          *pTxn = NULL;

#include "..\..\common\src\ReadRegistry.cpp"

/* FUNCTION: tpsvrinit ( int argc, char *argv[] )
 *
 * PURPOSE: Initialize the Server to Database
 * connection.
 *
 * RETURNS: int 0
 *          Success
 *          Failure -1
 */

int tpsvrinit ( int argc, char *argv[] )
{
    try
    {
        DWORD dwSize =
            MAX_COMPUTERNAME_LENGTH+1;
        GetComputerName(szMyComputerName,
            &dwSize);

        szMyComputerName[dwSize] = 0;

        if ( ReadTPCCRegistrySettings(
            &Reg ) )
            throw new CTUXAPP_ERR(
                ERR_MISSING_REGISTRY_ENTRIES );
    }
}

```

```

GetParameters(argc, argv);

switch (Reg.eDB_Protocol)
{
    case ODBC:
        pTxn = new CTPCC_ODBC(
            Reg.szDbServer, Reg.szDbUser, Reg.szDbPassword,
            szMyComputerName, Reg.szDbName );
        break;
    case DBLIB:
        pTxn = new CTPCC_DBLIB(
            Reg.szDbServer, Reg.szDbUser, Reg.szDbPassword,
            szMyComputerName, Reg.szDbName );
        break;
}
}
catch (CBaseErr *e)
{
    WriteMessageToEventLog(e-
>ErrorText());
    delete e;
}
catch (...)
{
    WriteMessageToEventLog(TEXT("Unhandled
exception."));
}

return 0;
}

/* FUNCTION: tpsvrdone ( void )
 *
 */

void tpsvrdone ( void )
{
    delete pTxn;
    pTxn = NULL;
}

/* FUNCTION: BOOL GetParameters(int argc, char
 *argv[] )
 *
 * PURPOSE: This function parses the command
 * line passed in to the delivery executable,
 * initializing
 * and filling in global
 * variable parameters.
 *
 * ARGUMENTS: int argc
 *             number of command line arguments passed to
 *             delivery
 *             char
 *             *argv[] array of command line argument
 *             pointers
 *
 */

static void GetParameters(int argc, char *argv[])

```

```

{
    // advance through args until "--" is found
    for(int j=0; j<argc; j++)
    {
        if (strcmp(argv[j],"--") == 0)
            break;
    }
    for(int i=j+1; i<argc; i++)
    {
        if ( argv[i][0] == '-' ||
argv[i][0] == '/' )
        {
            switch(argv[i][1])
            {
                case 'S':
                    strcpy(Reg.szDbServer, argv[i+2]);
                    break;
                case 'D':
                    strcpy(Reg.szDbName, argv[i+2]);
                    break;
                case 'P':
                    strcpy(Reg.szDbPassword, argv[i+2]);
                    break;
                case 'U':
                    strcpy(Reg.szDbUser, argv[i+2]);
                    break;
                default:
                    cout << "Microsoft TPC-C Kit" << endl;
                    cout << "Tuxedo Server" << endl << endl;
                    cout << "Usage:" << endl;
                    cout << " tuxapp [<tuxedo-args>] -- -
S<sql-server> [-D<database>] [-U<user>] [-
P<password>]" << endl << endl;
                    cout << "All parameters default to values
in registry." << endl;
                    throw new CTUXAPP_ERR( ERR_BAD_SYNTAX );
            }
        }
    }
}

static void WriteMessageToEventLog(LPTSTR lpszMsg)
{
    TCHAR szMsg[256];
    HANDLE hEventSource;
    LPTSTR lpszStrings[2];

```

```

    // Use event logging to log the error.
    //
    hEventSource = RegisterEventSource(NULL,
TEXT("TUXAPP.EXE"));

    _stprintf(szMsg, TEXT("Error in TUXAPP.EXE: "));
    lpszStrings[0] = szMsg;
    lpszStrings[1] = lpszMsg;

    if (hEventSource != NULL)
    {
        ReportEvent(hEventSource, // handle of event
source
        EVENTLOG_ERROR_TYPE, // event type
        0, // event category
        0, // event ID
        NULL, // current user's
SID
        2, // strings in
lpszStrings
        0, // no bytes of raw
data
        (LPCWSTR *)lpszStrings, // array of
error strings
        NULL); // no raw data

        (VOID) DeregisterEventSource(hEventSource);
    }
}

void NEWORDER( TPSVCINFO *rqst )
{
    PNEW_ORDER_DATA pNewOrder;
    TUX_DATA *pData;
    const int iSize = sizeof(pData-
>u.NewOrder);

    try
    {
        pData = (TUX_DATA*)rqst->data;
        pData->retval = ERR_SUCCESS;
        pData->error = 0;

        pNewOrder = pTxn-
>BuffAddr_NewOrder();
        assert( rqst->len ==
sizeof(TUX_DATA) );
        memcpy(pNewOrder, &pData-
>u.NewOrder, iSize );

        pTxn->NewOrder();
        memcpy( &pData->u.NewOrder,
pNewOrder, iSize );
        tpreturn( TPSUCCESS, 0, rqst-
>data, sizeof(TUX_DATA), 0);
    }
    catch (CBaseErr *e)
    {
        pData->retval = e->ErrorType();
        pData->error = e->ErrorNum();

```

```

        memcpy( &pData->u.NewOrder,
pNewOrder, iSize );
        tpreturn( TPSUCCESS, 0, rqst-
>data, sizeof(TUX_DATA), 0);
        delete e;
    }
    catch (...)
    {
        WriteMessageToEventLog(TEXT("Unhandled
exception."));
        pData->retval = ERR_TYPE_LOGIC;
        pData->error = 0;
        memcpy( &pData->u.NewOrder,
pNewOrder, iSize );
        tpreturn( TPSUCCESS, 0, rqst-
>data, sizeof(TUX_DATA), 0);
    }
}

void PAYMENT( TPSVCINFO *rqst )
{
    PPAYMENT_DATA pPayment;
    TUX_DATA *pData;
    const int iSize = sizeof(pData-
>u.Payment);

    try
    {
        pData = (TUX_DATA*)rqst->data;
        pData->retval = ERR_SUCCESS;
        pData->error = 0;

        pPayment = pTxn-
>BuffAddr_Payment();
        assert( rqst->len ==
sizeof(TUX_DATA) );
        memcpy(pPayment, &pData-
>u.Payment, iSize );

        pTxn->Payment();
        memcpy( &pData->u.Payment,
pPayment, iSize );
        tpreturn( TPSUCCESS, 0, rqst-
>data, sizeof(TUX_DATA), 0);
    }
    catch (CBaseErr *e)
    {
        pData->retval = e->ErrorType();
        pData->error = e->ErrorNum();
        memcpy( &pData->u.Payment,
pPayment, iSize );
        tpreturn( TPSUCCESS, 0, rqst-
>data, sizeof(TUX_DATA), 0);
        delete e;
    }
    catch (...)
    {
        WriteMessageToEventLog(TEXT("Unhandled
exception."));

```

```

        pData->retval = ERR_TYPE_LOGIC;
        pData->error = 0;
        memcpy( &pData->u.Payment,
pPayment, iSize );
        tpreturn( TPSUCCESS, 0, rqst-
>data, sizeof(TUX_DATA), 0);
    }
}
// Note: Delivery txn code below does not implement
// logging of the delivery
// txn results, so cannot be used as is to run
// an auditable TPC-C result.
// The code is included for completeness.
void DELIVERY( TPSVCINFO *rqst )
{
    PDELIVERY_DATA    pDelivery;
    TUX_DATA          *pData;
    const int         iSize = sizeof(pData-
>u.Delivery);

    try
    {
        pData = (TUX_DATA*)rqst->data;
        pData->retval = ERR_SUCCESS;
        pData->error = 0;

        pDelivery = pTxn-
>BuffAddr_Delivery();
        assert( rqst->len ==
sizeof(TUX_DATA) );
        memcpy(pDelivery, &pData-
>u.Delivery, iSize );

        pTxn->Delivery();

        memcpy( &pData->u.Delivery,
pDelivery, iSize );
        tpreturn( TPSUCCESS, 0, rqst-
>data, sizeof(TUX_DATA), 0);
    }
    catch (CBaseErr *e)
    {
        pData->retval = e->ErrorType();
        pData->error = e->ErrorNum();
        memcpy( &pData->u.Delivery,
pDelivery, iSize );
        tpreturn( TPSUCCESS, 0, rqst-
>data, sizeof(TUX_DATA), 0);
        delete e;
    }
    catch (...)
    {
        WriteMessageToEventLog(TEXT("Unhandled
exception."));
        pData->retval = ERR_TYPE_LOGIC;
        pData->error = 0;
        memcpy( &pData->u.Delivery,
pDelivery, iSize );
    }
}

```

```

        tpreturn( TPSUCCESS, 0, rqst-
>data, sizeof(TUX_DATA), 0);
    }
}

void STOCKLEVEL( TPSVCINFO *rqst )
{
    PSTOCK_LEVEL_DATA pStockLevel;
    TUX_DATA          *pData;
    const int         iSize =
sizeof(pData->u.StockLevel);

    try
    {
        pData = (TUX_DATA*)rqst->data;
        pData->retval = ERR_SUCCESS;
        pData->error = 0;

        pStockLevel = pTxn-
>BuffAddr_StockLevel();
        assert( rqst->len ==
sizeof(TUX_DATA) );
        memcpy(pStockLevel, &pData-
>u.StockLevel, iSize );

        pTxn->StockLevel();
        memcpy( &pData->u.StockLevel,
pStockLevel, iSize );
        tpreturn( TPSUCCESS, 0, rqst-
>data, sizeof(TUX_DATA), 0);
    }
    catch (CBaseErr *e)
    {
        pData->retval = e->ErrorType();
        pData->error = e->ErrorNum();
        memcpy( &pData->u.StockLevel,
pStockLevel, iSize );
        tpreturn( TPSUCCESS, 0, rqst-
>data, sizeof(TUX_DATA), 0);
        delete e;
    }
    catch (...)
    {
        WriteMessageToEventLog(TEXT("Unhandled
exception."));
        pData->retval = ERR_TYPE_LOGIC;
        pData->error = 0;
        memcpy( &pData->u.StockLevel,
pStockLevel, iSize );
        tpreturn( TPSUCCESS, 0, rqst-
>data, sizeof(TUX_DATA), 0);
    }
}

void ORDERSTATUS( TPSVCINFO *rqst )
{
    PORDER_STATUS_DATA pOrderStatus;
    TUX_DATA          *pData;
    const int         iSize = sizeof(pData-
>u.OrderStatus);
}

```

```

    try
    {
        pData = (TUX_DATA*)rqst->data;
        pData->retval = ERR_SUCCESS;
        pData->error = 0;

        pOrderStatus = pTxn-
>BuffAddr_OrderStatus();
        assert( rqst->len ==
sizeof(TUX_DATA) );
        memcpy(pOrderStatus, &pData-
>u.OrderStatus, iSize );

        pTxn->OrderStatus();
        memcpy( &pData->u.OrderStatus,
pOrderStatus, iSize );
        tpreturn( TPSUCCESS, 0, rqst-
>data, sizeof(TUX_DATA), 0);
    }
    catch (CBaseErr *e)
    {
        pData->retval = e->ErrorType();
        pData->error = e->ErrorNum();
        memcpy( &pData->u.OrderStatus,
pOrderStatus, iSize );
        tpreturn( TPSUCCESS, 0, rqst-
>data, sizeof(TUX_DATA), 0);
        delete e;
    }
    catch (...)
    {
        WriteMessageToEventLog(TEXT("Unhandled
exception."));
        pData->retval = ERR_TYPE_LOGIC;
        pData->error = 0;
        memcpy( &pData->u.OrderStatus,
pOrderStatus, iSize );
        tpreturn( TPSUCCESS, 0, rqst-
>data, sizeof(TUX_DATA), 0);
    }
}

/* FUNCTION: CTUXAPP_ERR::ErrorText
 *
 */

char* CTUXAPP_ERR::ErrorText(void)
{
    int i;

    static SERRORMSG errorMsgs[] =
    {
        { ERR_MISSING_REGISTRY_ENTRIES,
"Required entries missing from registry."
},
        { ERR_BAD_SYNTAX,
"Syntax error in input
parameters."
},
    },
}

```

```

        { ERR_UNKNOWN_DB_PROTOCOL,
"Unknown database protocol specified in
registry."
        },
        { 0,
        ""
        }
    };

static char szNotFound[] = "Unknown error
number.";

for(i=0; errorMsgs[i].szMsg[0]; i++)
{
    if ( m_Error ==
errorMsgs[i].iError )
        break;
}
if ( !errorMsgs[i].szMsg[0] )
    return szNotFound;
else
    return errorMsgs[i].szMsg;
}

```

tuxapp.h

```

/* FILE: TUXAPP.H Microsoft
 * TPC-C Kit Ver. 4.20.000 Copyright
 * Microsoft, 1999
 * All Rights Reserved
 *
 * Version
4.10.000 audited by Richard Gimarc, Performance
Metrics, 3/17/99
 * PURPOSE: Header file for TPC-C Tuxedo
server.
 * Change history:
 * 4.20.000 - updated rev number to
match kit
 */

enum TUXERROR
{
    ERR_MISSING_REGISTRY_ENTRIES = 1,
    ERR_BAD_SYNTAX,
    ERR_UNKNOWN_DB_PROTOCOL
};

class CTUXAPP_ERR : public CBaseErr
{
public:
    TUXERROR m_Error;

```

```

CTUXAPP_ERR(TUXERROR Err) {
m_Error = Err; };
~CTUXAPP_ERR() {};

int ErrorType() {return
ERR_TYPE_TUXEDO;};

int ErrorNum() {return m_Error;};
char *ErrorText();

};

struct TUX_DATA
{
    int
    retval;
    int
    error;

    union
    {
        NEW_ORDER_DATA
        NewOrder;
        PAYMENT_DATA
        Payment;
        DELIVERY_DATA
        Delivery;
        STOCK_LEVEL_DATA StockLevel;
        ORDER_STATUS_DATA OrderStatus;
    } u;
};

static void GetParameters(int argc, char *argv[]);
static void WriteMessageToEventLog(LPTSTR lpszMsg);

#if defined(__cplusplus)
extern "C" {
#endif

void NEWORDER( TPSVCINFO *rqst );
void PAYMENT( TPSVCINFO *rqst );
void DELIVERY( TPSVCINFO *rqst );
void STOCKLEVEL( TPSVCINFO *rqst );
void ORDERSTATUS( TPSVCINFO *rqst );

#if defined(__cplusplus)
}
#endif

```

tuxmain.c

```

/* FILE: TUXMAIN.C Microsoft
 * TPC-C Kit Ver. 4.20.000 Copyright
 * Microsoft, 1999
 * All Rights Reserved
 *

```

```

 *
 * Version
4.10.000 audited by Richard Gimarc, Performance
Metrics, 3/17/99
 *
 * PURPOSE: Implementation for TPC-C Tuxedo
server.
 * Contact: Charles Levine
(clevine@microsoft.com)
 *
 * Change history:
 * 4.20.000 - updated rev number to
match kit
 */

#include <stdio.h>
#include <xa.h>
#include <atmi.h>

#if defined(__cplusplus)
extern "C" {
#endif
extern int _tmrunserver_((int));
extern void DELIVERY_((TPSVCINFO *));
extern void NEWORDER_((TPSVCINFO *));
extern void ORDERSTATUS_((TPSVCINFO *));
extern void PAYMENT_((TPSVCINFO *));
extern void STOCKLEVEL_((TPSVCINFO *));
#if defined(__cplusplus)
}
#endif

static struct tmdsptchtbl_t_tmdsptchtbl[] = {
    { "DELIVERY", "DELIVERY", (void (*)
_((TPSVCINFO *)) DELIVERY, 0, 0 },
    { "NEWORDER", "NEWORDER", (void (*)
_((TPSVCINFO *)) NEWORDER, 1, 0 },
    { "ORDERSTATUS", "ORDERSTATUS", (void (*)
_((TPSVCINFO *)) ORDERSTATUS, 2, 0 },
    { "PAYMENT", "PAYMENT", (void (*)
_((TPSVCINFO *)) PAYMENT, 3, 0 },
    { "STOCKLEVEL", "STOCKLEVEL", (void (*)
_((TPSVCINFO *)) STOCKLEVEL, 4, 0 },
    { NULL, NULL, NULL, 0, 0 }
};

#ifndef _TMDLLIMPORT
#define _TMDLLIMPORT
#endif

_TMDLLIMPORT extern struct xa_switch_t tnull_switch;

struct tmsvargs_t tmsvargs = {
    NULL,
    & tmdsptchtbl[0],
    0,
    tpsvrinit,
    tpsvrdone,
    _tmrunserver, /* PRIVATE */
    NULL, /* RESERVED
*/

```

```

        NULL,          /* RESERVED
*/
        NULL,          /* RESERVED
*/
        NULL          /* RESERVED
*/
};

struct tmsvrargs_t *
#ifdef _TMPROTOTYPES
_tmgetsvrargs(void)
#else
_tmgetsvrargs()
#endif
{
    tmsvrargs.xa_switch = &tmsvrargs.null_switch;
    return(&tmsvrargs);
}

int
#ifdef _TMPROTOTYPES
main(int argc, char **argv)
#else
main(argc,argv)
int argc;
char **argv;
#endif
{
#ifdef TMMAINEXIT
#include "mainexit.h"
#endif

    return( _tmstartserver( argc, argv,
_tmgetsvrargs()));
}

```

txn_base.h

```

/* FILE: TXN_BASE.H
* Microsoft
TPC-C Kit Ver. 4.20.000
* Copyright
Microsoft, 1999
* All Rights Reserved
* Version
4.10.000 audited by Richard Gimarc, Performance
Metrics, 3/17/99
* PURPOSE: Header file for TPC-C txn class
implementation.
* Change history:
* 4.20.000 - updated rev number to
match kit
*/
#pragma once

```

```

// need to declare functions for import, unless
define has already been created
// by the DLL's .cpp module for export.
#ifdef DllDecl
#define DllDecl __declspec( dllimport )
#endif

class DllDecl CTPCC_BASE
{
public:
    CTPCC_BASE(void) {};
    virtual ~CTPCC_BASE(void) {};

    virtual PNEW_ORDER_DATA
BuffAddr_NewOrder() = 0;
    virtual PPAYMENT_DATA
BuffAddr_Payment() = 0;
    virtual PDELIVERY_DATA
BuffAddr_Delivery() = 0;
    virtual PSTOCK_LEVEL_DATA
BuffAddr_StockLevel() = 0;
    virtual PORDER_STATUS_DATA
BuffAddr_OrderStatus() = 0;

    virtual void NewOrder
() = 0;
    virtual void Payment
() = 0;
    virtual void Delivery
() = 0;
    virtual void StockLevel
() = 0;
    virtual void OrderStatus
() = 0;
};

```

tpcc_oledb.cpp

```

/* FILE: TPCC_OLEDB.CPP
* Microsoft
TPC-C Kit Ver. 4.42.000
* Copyright
Microsoft, 2004
* Written by
Sergey Vasilevskiy
* All Rights Reserved
* PURPOSE: Implements OLEDB calls for TPC-C
txns.
* Contact: Charles Levine
(clevine@microsoft.com)
*/
#include <windows.h>
#include <stdio.h>
#include <assert.h>

```

```

#include <stddef.h>

#define DBINITCONSTANTS
#include <oledb.h>
// #include <sqloledb.h> // Use MDAC
#include <sqlncli.h> // Use SNAC
#include <oledberr.h>

#ifdef ICECAP
#include <icapexp.h>
#endif

// need to declare functions for export
#define DllDecl __declspec( dllexport )

#include "..\..\common\src\error.h"
#include "..\..\common\src\trans.h"
#include "..\..\common\src\txn_base.h"
#include "tpcc_oledb.h"

#ifdef SQL_MAX_MESSAGE_LENGTH
#define SQL_MAX_MESSAGE_LENGTH 512
#endif

// version string; must match return value from
tpcc_version stored proc
const char sVersion[] = "4.20.000";

const iMaxRetries = 10; // how many
retries on deadlock

const int iErrOleDbProvider = 7312;
const char sErrTimeoutExpired[] = "Timeout expired";

// this needs to be the same as the max length of
machine/database/user/password in Benchcraft
(engstut.h)
const static int iMaxNameLen = 32;

BOOL APIENTRY DllMain(HMODULE hModule, DWORD
ul_reason_for_call, LPVOID lpReserved)
{
    switch( ul_reason_for_call )
    {
        case DLL_PROCESS_ATTACH:
            DisableThreadLibraryCalls(hModule);

            break;

        case DLL_PROCESS_DETACH:
            break;

        default:
            /* nothing */;
    }
    return TRUE;
}

/* FUNCTION: CTPCC_OLEDB_ERR::ErrorText

```



```

*
*/
char* CTPCC_OLEDB_ERR::ErrorText(void)
{
    int i;

    static SERRORMSG errorMsgs[] =
    {
        { ERR_WRONG_SP_VERSION,
        "Wrong version of stored procs on database
server" },
        { ERR_INVALID_CUST,
        "Invalid Customer id,name." },
        { ERR_NO_SUCH_ORDER,
        "No orders found for customer." },
        { ERR_RETRIED_TRANS,
        "Retries before transaction succeeded." },
        { 0, "" }
    };

}
};

static char szNotFound[] = "Unknown error
number.";

for(i=0; errorMsgs[i].szMsg[0]; i++)
{
    if ( m_errno ==
errorMsgs[i].iError )
        break;
}
if ( !errorMsgs[i].szMsg[0] )
    return szNotFound;
else
    return errorMsgs[i].szMsg;
}

// wrapper routine for class constructor
_declspec(dllexport) CTPCC_OLEDB* CTPCC_OLEDB_new(
LPCSTR szServer, // name of
SQL server
LPCSTR szUser, //
user name for login
LPCSTR szPassword, // password
for login
LPCSTR szHost, //
not used
LPCSTR szDatabase, // name of
database to use
LPCWSTR szSPPrefix ) //
prefix to append to the stored procedure names
{
    return new CTPCC_OLEDB( szServer, szUser,
szPassword, szHost, szDatabase, szSPPrefix );
}

```

```

CTPCC_OLEDB::CTPCC_OLEDB (
LPCSTR szServer, // name of SQL server
LPCSTR szUser, // user name for login
LPCSTR szPassword, // password for login
LPCSTR szHost, // not used
LPCSTR szDatabase, // name of database to use
LPCWSTR szSPPrefix // prefix to append to the stored procedure
names
)
: m_pIMalloc(NULL)
{
    int
iRc;
int
i;
HRESULT
hr;

IDBInitialize*
pIDBInitialize = NULL; //
data source interface
IDBProperties*
pIDBProperties = NULL;
ICommandText*
pICommandText;
// SQL command without parameters
wchar_t
szwServer[iMaxNameLen]; //
Unicode string used to convert to BSTR
wchar_t
szwDatabase[iMaxNameLen]; // Unicode
string used to convert to BSTR
wchar_t
szwUser[iMaxNameLen]; //
Unicode string used to convert to BSTR
wchar_t
szwPassword[iMaxNameLen]; // Unicode
string used to convert to BSTR

// Copy stored procedures prefix
wcsncpy(m_szSPPrefix, szSPPrefix,
sizeof(m_szSPPrefix)/sizeof(m_szSPPrefix[0]));

// Convert single byte ANSI strings to
Unicode (for later conversion to BSTR)
iRc = MultiByteToWideChar(CP_THREAD_ACP,
MB_PRECOMPOSED, szServer, (int)strlen(szServer)+1,
szwServer, iMaxNameLen);
iRc = MultiByteToWideChar(CP_THREAD_ACP,
MB_PRECOMPOSED, szDatabase,
(int)strlen(szDatabase)+1, szwDatabase, iMaxNameLen);
iRc = MultiByteToWideChar(CP_THREAD_ACP,
MB_PRECOMPOSED, szUser, (int)strlen(szUser)+1,
szwUser, iMaxNameLen);

```

```

iRc = MultiByteToWideChar(CP_THREAD_ACP,
MB_PRECOMPOSED, szPassword,
(int)strlen(szPassword)+1, szwPassword, iMaxNameLen);

// Initialize COM library to be able to use
OLE-DB interfaces
CoInitialize(NULL);

// Initialization - create SQLOLEDB
component
//hr = CoCreateInstance(CLSID_SQLOLEDB, //
GUID of SQLOLEDB component
// Compile for SNAC
hr = CoCreateInstance(CLSID_SQLNCLI, //
GUID of SQLNCLI component
NULL,
// not defining an aggregate
component, so NULL
CLSCTX_INPROC_SERVER, //
run the component in our process
IID_IDBInitialize,
(void**) &pIDBInitialize);

/*
Initialize the property values needed
to establish the connection.
*/
for(i = 0; i < 4; i++)
    VariantInit(&m_InitProperties[i].vValue);
//Server name.
m_InitProperties[0].dwPropertyID =
DBPROP_INIT_DATASOURCE;
m_InitProperties[0].vValue.vt = VT_BSTR;
m_InitProperties[0].vValue.bstrVal=
SysAllocString(szwServer);
m_InitProperties[0].dwOptions =
DBPROPOPTIONS_REQUIRED;
m_InitProperties[0].colid = DB_NULLID;
//Database.
m_InitProperties[1].dwPropertyID =
DBPROP_INIT_CATALOG;
m_InitProperties[1].vValue.vt = VT_BSTR;
m_InitProperties[1].vValue.bstrVal=
SysAllocString(szwDatabase);
m_InitProperties[1].dwOptions =
DBPROPOPTIONS_REQUIRED;
m_InitProperties[1].colid = DB_NULLID;
//Username (login).
m_InitProperties[2].dwPropertyID =
DBPROP_AUTH_USERID;
m_InitProperties[2].vValue.vt = VT_BSTR;
m_InitProperties[2].vValue.bstrVal=
SysAllocString(szwUser);
m_InitProperties[2].dwOptions =
DBPROPOPTIONS_REQUIRED;
m_InitProperties[2].colid = DB_NULLID;
//Password.
m_InitProperties[3].dwPropertyID =
DBPROP_AUTH_PASSWORD;
m_InitProperties[3].vValue.vt = VT_BSTR;
m_InitProperties[3].vValue.bstrVal=
SysAllocString(szwPassword);

```

```

    m_InitProperties[3].dwOptions    =
DBPROPOPTIONS_REQUIRED;
    m_InitProperties[3].colid       = DB_NULLID;
    /*
Construct the DBPROPSET
structure(m_rgInitPropSet). The
DBPROPSET structure is used to pass an array of
DBPROP
structures (m_InitProperties) to the
SetProperties method.
*/
    m_rgInitPropSet.guidPropertySet =
DBPROPSET_DBINIT;
    m_rgInitPropSet.cProperties     = 4;
    m_rgInitPropSet.rgProperties    =
m_InitProperties;
    //Set initialization properties.
    if (FAILED(hr = pIDBInitialize-
>QueryInterface(IID_IDBProperties,
                (void **)&pIDBProperties)))
    {
        ThrowError(pIDBInitialize,
COLEDBERR::eQueryInterface, "CTPCC_OLEDB()");
    }

    hr = pIDBProperties->SetProperties(1,
&m_rgInitPropSet);

    pIDBProperties->Release();
    //Now establish the connection to the data
source.
    hr = pIDBInitialize->Initialize();

    // Free BSTR property strings
    for(i = 0; i < 4; i++)
    {
SysFreeString(m_InitProperties[i].vValue.bstrVal);
    }

    hr = pIDBInitialize-
>QueryInterface(IID_IDBCreateSession, (void
**) &m_pIDBCreateSession);

    // Releasing this has no effect on the SQL
Server connection
// of the data source object because of the
reference maintained by
// m_pIDBCreateSession.
    pIDBInitialize->Release();
    pIDBInitialize = NULL;

    hr = m_pIDBCreateSession-
>CreateSession(NULL, IID_IDBCreateCommand, (IUnknown
**) &m_pIDBCreateCommand);
    if (FAILED(hr))
    {

```

```

        ThrowError(m_pIDBCreateSession,
COLEDBERR::eCreateSession, "CTPCC_OLEDB()");
    }

    hr = m_pIDBCreateCommand-
>CreateCommand(NULL, IID_ICommandText, (IUnknown
**) &pICommandText);
    if (FAILED(hr))
    {
        ThrowError(m_pIDBCreateCommand,
COLEDBERR::eCreateCommand, "CTPCC_OLEDB()");
    }

    hr = pICommandText-
>SetCommandText(DBGUID_SQL, L"set nocount on set
XACT_ABORT ON");
    if (FAILED(hr))
    {
        ThrowError(pICommandText,
COLEDBERR::eSetCommandText, "CTPCC_OLEDB()");
    }

    hr = pICommandText->Execute(NULL, IID_NULL,
NULL, NULL, NULL);
    if (FAILED(hr))
    {
        ThrowError(pICommandText,
COLEDBERR::eExecute, "CTPCC_OLEDB()");
    }

    pICommandText->Release();

    // verify that version of stored procs on
server is correct
    CheckSPVersion();

    // Get IMalloc interface
    hr = CoGetMalloc(1, (LPMALLOC
*) &m_pIMalloc);

    // Bind parameters for each of the
transactions
    InitNewOrderParams();
    InitPaymentParams();
    InitOrderStatusParams();
    InitDeliveryParams();
    InitStockLevelParams();
}

CTPCC_OLEDB::~CTPCC_OLEDB( void )
{
    if (m_pIMalloc != NULL)
    {
        m_pIMalloc->Release();
    }
    m_pIPaymentCommand->Release();
    m_pIDBCreateCommand->Release();
    m_pIDBCreateSession->Release();

    CoUninitialize(); // uninitialized COM
library

```

```

}

/*
* Check stored procedures version on the
server.
*/
void CTPCC_OLEDB::CheckSPVersion()
{
    HRESULT hr;
    char
db_sp_version[10];
    ICommandText* pICommandText;
    IAccessor* pIAccessor;
    IRowset* pRowset;
    const ULONG nOutputParams
= 1;
    // output 1st result set columns
    HACCESSOR
hTpccVersionOutputAccessor;
    // Structure to bind in accessor
    DBBINDING
acOutputDBBinding[nOutputParams];
    DBBINDSTATUS
acOutputDBBindStatus[nOutputParams];
    LONG cRows = 1;
    // number of rows returned in the rowset
    ULONG
cRowsObtained;
    HROW rghRow;
    //returned row handles
    HROW* prghRow =
&rghRow;

    hr = m_pIDBCreateCommand-
>CreateCommand(NULL, IID_ICommandText, (IUnknown
**) &pICommandText);
    if (FAILED(hr))
    {
        ThrowError(m_pIDBCreateCommand,
COLEDBERR::eCreateCommand, "CheckSPVersion()");
    }

    hr = pICommandText-
>SetCommandText(DBGUID_SQL, L"{call tpcc_version}");
    if (FAILED(hr))
    {
        ThrowError(pICommandText,
COLEDBERR::eSetCommandText, "CheckSPVersion()");
    }

    hr = pICommandText-
>QueryInterface(IID_IAccessor, (void **)&pIAccessor);
    if (FAILED(hr))
    {
        ThrowError(pICommandText,
COLEDBERR::eQueryInterface, "CheckSPVersion()");
    }

    // Now fill the binding information for
result set 1 output columns

```

```

        InitBindings(&acOutputDBBinding[0],
nOutputParams, eOutputColumn);

        // Binding for a rowset
        SetBinding(&acOutputDBBinding[0], 0,
sizeof(db_sp_version), DBTYPE_STR);

        hr = pIAccessor->CreateAccessor(
                DBACCESSOR_ROWDATA,
nOutputParams,
acOutputDBBinding,
                sizeof(db_sp_version),

&hTpcVersionOutputAccessor,
                acOutputDBBindStatus);
        if (FAILED(hr))
        {
                ThrowError(pIAccessor,
COLEDBERR::eCreateAccessor, "CheckSPVersion()");
        }

        hr = pICommandText->Execute(NULL,
IID_IRowset, NULL, NULL, (IUnknown **) &pRowset);
        if (FAILED(hr))
        {
                ThrowError(pICommandText,
COLEDBERR::eExecute, "CheckSPVersion()");
        }

        // Fetch the result row handle(s)
        hr = pRowset->GetNextRows(DB_NULL_HCHAPTER,
0, cRows, &cRowsObtained, &prghRow);
        if (FAILED(hr))
        {
                ThrowError(pICommandText,
COLEDBERR::eGetNextRows, "CheckSPVersion()");
        }

        // Fetch the actual row data by handle
        hr = pRowset->GetData(rghRow,
hTpcVersionOutputAccessor, &db_sp_version);
        if (FAILED(hr))
        {
                ThrowError(pICommandText,
COLEDBERR::eGetData, "CheckSPVersion()");
        }

        // Release row(s)
        hr = pRowset->Release();

        pICommandText->Release();

        // Check the retrieved version
        if (strcmp(db_sp_version, sVersion))
                throw new
CTPCC_OLEDB_ERR(
CTPCC_OLEDB_ERR::ERR_WRONG_SP_VERSION );
}

```

```

void CTPCC_OLEDB::ThrowError( IUnknown*
pObjectWithError, COLEDBERR::ACTION eAction, LPCTSTR
szLocation)
{
        HRESULT
        hr;
        //char
        szState[6];
        char
        szMsg[SQL_MAX_MESSAGE_LENGTH];
        char
        szTmp[6*SQL_MAX_MESSAGE_LENGTH];
        COLEDBERR
        *pOLEDBErr;
        //
        not allocated until needed (maybe never)
        int
        iLen;
        // Interfaces
        IErrorInfo*
        piErrorInfoAll
= NULL;
        IErrorInfo*
        piErrorInfoRecord
= NULL;
        IErrorRecords*
        piErrorRecords
= NULL;
        ISupportErrorInfo*
        piSupportErrorInfo
= NULL;
        ISQLServerErrorInfo*
        piSQLServerErrorInfo = NULL;
        ISQLErrorInfo*
        piSQLErrorInfo = NULL;

        // Information used when cannot get custom
error object
        ERRORINFO
        BasicErrorInfo;
        BSTR
        bstrDescription;
        // Number of error records.
        ULONG
        nRecs;
        ULONG
        nRec;

        // SQL Server error information from
ISQLServerErrorInfo.
        SSERRORINFO*
        pSSErrorInfo =
NULL;
        OLECHAR*
        pSSErrorStrings =
NULL;

        assert(pObjectWithError != NULL);

        pOLEDBErr = new COLEDBERR(szLocation);

        pOLEDBErr->m_NativeError = 0;
        pOLEDBErr->m_eAction = eAction;
        pOLEDBErr->m_bDeadLock = FALSE;

        szTmp[0] = 0;

        // Only ask for error information if the
interface supports it.

```

```

        // Note: SMOLEDB provider supports error
interface, so this check is
        // for good style only.
        hr = pObjectWithError-
>QueryInterface(IID_ISupportErrorInfo, (void**)
&piSupportErrorInfo);
        if (FAILED(hr))
        {
                _snprintf(szMsg, sizeof(szMsg),
"SupportErrorInfo interface not supported (hr=0x%X)",
hr);
                pOLEDBErr->m_OLEDBErrStr = new
char[strlen(szMsg)+1];
                strcpy(pOLEDBErr->m_OLEDBErrStr,
szMsg);
                throw pOLEDBErr;
        }
        /*if (FAILED(piSupportErrorInfo-
>InterfaceSupportsErrorInfo(IID_InterfaceWithError)))
        {
                _snprintf(szMsg, sizeof(szMsg),
"InterfaceWithError interface not supported");
                pOLEDBErr->m_OLEDBErrStr = new
char[strlen(szMsg)+1];
                strcpy(pOLEDBErr->m_OLEDBErrStr,
szMsg);
                return;
        }*/

        // Do not test the return of GetErrorInfo.
It can succeed and return
        // a NULL pointer in piErrorInfoAll. Simply
test the pointer.
        GetErrorInfo(0, &piErrorInfoAll);

        if (piErrorInfoAll != NULL)
        {
                // Test to see if it's a valid
OLE DB IErrorInfo interface
                // exposing a list of records.
                if (SUCCEEDED(piErrorInfoAll-
>QueryInterface(IID_IErrorRecords, (void**)
&piErrorRecords)))
        {
                piErrorRecords-
>GetRecordCount(&nRecs);

                // Within each record,
retrieve information from each
                // of the defined
interfaces.
                for (nRec = 0; nRec <
nRecs; nRec++)
        {
                // Request
the generic SQL error interface.

                piErrorRecords->GetCustomErrorObject(nRec,

```

```

IID_ISQLErrorInfo, // generic SQL error
interface
    (IUnknown**) &pISQLErrorInfo);

    if
    (pISQLErrorInfo != NULL)
    {
        //
        Request SQL Server-specific error interface, not the
        generic SQL error interface.
        pISQLErrorInfo->QueryInterface(
            IID_ISQLServerErrorInfo, // SQL Server
            error interface
            (void**) &pISQLServerErrorInfo);
        }
        // Test to
        // get error
        information from ISQLServerErrorInfo.
        if
        (pISQLServerErrorInfo != NULL)
        {
            pISQLServerErrorInfo-
            >GetErrorInfo(&pSSErrorInfo, &pSSErrorStrings);

            //
            ISQLServerErrorInfo::GetErrorInfo succeeds
            //
            even when it has nothing to return. Test the
            //
            pointers before using.
            if
            (pSSErrorInfo)
            {
                // First, add the error message.

                // Convert Unicode error string to ANSI.
                WideCharToMultiByte(CP_THREAD_ACP, 0,
                    pSSErrorInfo->pwszMessage, -1,
                    szMsg, sizeof(szMsg),
                    NULL, NULL);

                // quit if there isn't enough room to
                concatenate error text

```

```

        if ( (strlen(szMsg) + 2) > (sizeof(szTmp) -
        strlen(szTmp)) )
            break;

            // include line break after first error msg
            if (szTmp[0] != 0)
                strcat( szTmp, "\r\n");

                // concatenate the error record to the
                overall error message
                strcat( szTmp, szMsg );

                // Second, add the stored procedure name
                and line number, if available.
                if (wcslen(pSSErrorInfo->pwszProcedure)>0)
                {
                    // Prefix with a line break
                    iLen = sprintf(szMsg,
                    "\r\nProcedure: ");

                    // Convert Unicode error string
                    to ANSI.
                    WideCharToMultiByte(CP_THREAD_ACP, 0,
                        pSSErrorInfo-
                        >pwszProcedure, -1,
                        szMsg[iLen],
                        sizeof(szMsg) - iLen,
                        NULL, NULL);

                        // Check if have space to add the
                        line number.
                        // Assume the line number takes
                        no more than 3 digits.
                        if ((strlen(szMsg) + 4)<
                        sizeof(szMsg))
                        {

```

```

                _snprintf(&szMsg[strlen(szMsg)],
                sizeof(szMsg),
                "%d",
                pSSErrorInfo->wLineNumber);
            }
            // quit if there isn't enough
            room to concatenate error text
            if ( (strlen(szMsg) + 2) >
            (sizeof(szTmp) - strlen(szTmp)) )
                break;

                // concatenate the error record
                to the overall error message
                strcat( szTmp, szMsg );

                // copy the overall error string
                to the exception
                pOLEDBErr->m_OLEDBErrStr = new
                char[strlen(szTmp)+1];
                strcpy(pOLEDBErr->m_OLEDBErrStr,
                szTmp);
            }

            // Third, capture the (first) database
            error
            if (pOLEDBErr->m_NativeError == 0 &&
            pSSErrorInfo->lNative != 0)
            {
                pOLEDBErr->m_NativeError =
                pSSErrorInfo->lNative;

                // Check for deadlock error code
                and set the deadlock flag
                if (pSSErrorInfo->lNative ==
                1205)
                {
                    pOLEDBErr->m_bDeadLock
                    = TRUE;
                }
            }

```

```

    }

    // IMalloc::Free needed to release
    references
    // on returned values.
    if (m_pIMalloc != NULL)
    {
        m_pIMalloc-
        >Free(pSSErrorStrings);
        m_pIMalloc->Free(pSSErrorInfo);
    }

    pISQLServerErrorInfo->Release();
    }
    else
    {
        //
        Custom error object is not supported.
        //
        Use general OLE-DB error interface.
        //
        Get the numeric error code
        pIErrorRecords->GetBasicErrorInfo(nRec,
        &BasicErrorInfo);
        if
        (pOLEDBErr->m_NativeError == 0)
        {
            // Get the failed call HRESULT code, which
            is not really the native error
            pOLEDBErr->m_NativeError =
            BasicErrorInfo.hrError;
        }
        //
        Try to get the string description of the error.
        pIErrorRecords->GetErrorInfo(nRec,
        LOCALE_USER_DEFAULT,
        (IErrorInfo**) &pIErrorInfoRecord);
        if
        (pIErrorInfoRecord)
        {
            pIErrorInfoRecord-
            >GetDescription(&bstrDescription);

```

```

    // Convert Unicode error string to ANSI.
    WideCharToMultiByte(CP_THREAD_ACP, 0,
        bstrDescription, -1,
        szMsg, sizeof(szMsg),
        NULL, NULL);

    pOLEDBErr->m_OLEDBErrStr = new
    char[strlen(szMsg)+1];
    strcpy(pOLEDBErr->m_OLEDBErrStr, szMsg);
}
} // for()
} // if
(SUCCEEDED(pIErrorInfoAll-
>QueryInterface(IID_IErrorRecords, (void**)
&pIErrorRecords)))
else
{
    // No IErrorRecords
    interface supported. Use default IErrorInfo.
    // Note: SQLOLEDB
    supports IErrorRecords, so this check is for good
    style only.
    snprintf(szMsg,
    sizeof(szMsg), "IErrorRecords interface not
    supported");
    pOLEDBErr-
    >m_OLEDBErrStr = new char[strlen(szMsg)+1];
    strcpy(pOLEDBErr-
    >m_OLEDBErrStr, szMsg);
}
pIErrorInfoAll->Release();
}
else
{
    // No IErrorInfo interface
    supported.
    // Note: SQLOLEDB supports
    IErrorInfo, so this check is for good style only.
    _snprintf(szMsg, sizeof(szMsg),
    "IErrorInfo interface not supported");
    pOLEDBErr->m_OLEDBErrStr = new
    char[strlen(szMsg)+1];
    strcpy(pOLEDBErr->m_OLEDBErrStr,
    szMsg);
}
throw pOLEDBErr;
}

```

```

/*
 *
 * Create a new command object from the SQL
 * text passed in.
 *
 */
void CTPCC_OLEDB::CreateCommand(wchar_t*
szSQLCommand, // I: SQL
query for the command

ICommandText**
ppICommandText // O: returned command object
)
{
    HRESULT hr;

    // Create a new command object
    hr = m_pIDBCreateCommand-
    >CreateCommand(NULL, IID_ICommandText, (IUnknown
    **)ppICommandText);
    if (FAILED(hr))
    {
        ThrowError(m_pIDBCreateCommand,
        COLEDBERR::eCreateCommand,
        "CTPCC_OLEDB::CreateCommand");
    }

    // Set command text
    hr = (*ppICommandText)-
    >SetCommandText(DBGUID_SQL, szSQLCommand);
    if (FAILED(hr))
    {
        ThrowError(*ppICommandText,
        COLEDBERR::eSetCommandText,
        "CTPCC_OLEDB::CreateCommand");
    }

    // Prepare the command
    PrepareCommand(*ppICommandText);
}

/*
 * QueryInterface and Prepare in one function
 * for simplicity.
 * DEFERRED PREPARE property is set to off to
 * prepare immediately.
 */
void CTPCC_OLEDB::PrepareCommand(ICommandText*
pICommandText)
{
    HRESULT hr;
    ICommandPrepare* pICommandPrepare;
    ICommandProperties* pICommandProperties;
    DBPROPSET
    rowSetPropSet;
    DBPROP
    rowSetProp;

    // Set the deferred prepare property to
    false.

```

```

        rowSetProp.dwPropertyID =
SSPROP_DEFERPREPARE;
        memset(&rowSetProp.vValue, 0,
sizeof(rowSetProp.vValue));
        rowSetProp.dwOptions =
DBPROPOPTIONS_REQUIRED;
        rowSetProp.colid = DB_NULLID;

        rowSetPropSet.cProperties = 1;
        rowSetPropSet.guidPropertySet =
DBPROPSET_SQLSERVERROWSSET;
        rowSetPropSet.rgProperties = &rowSetProp;

        // Query interface for setting properties
        hr = piCommandText-
>QueryInterface(IID_ICommandProperties, (void
**) &piCommandProperties);
        if (FAILED(hr))
        {
            ThrowError(piCommandText,
COLEDBERR::eQueryInterface,
"CTPCC_OLEDB::PrepareCommand");
        }

        // Set the property set
        hr = piCommandProperties->SetProperties(1,
&rowSetPropSet);
        if (FAILED(hr))
        {
            ThrowError(piCommandText,
COLEDBERR::eQueryInterface,
"CTPCC_OLEDB::PrepareCommand");
        }

        // Get interface for preparing commands
        hr = piCommandText-
>QueryInterface(IID_ICommandPrepare, (void
**) &piCommandPrepare);
        if (FAILED(hr))
        {
            ThrowError(piCommandText,
COLEDBERR::eQueryInterface,
"CTPCC_OLEDB::PrepareCommand");
        }

        // Prepare Payment command
        hr = piCommandPrepare->Prepare(0xFFFFFFFF);
        if (FAILED(hr))
        {
            ThrowError(piCommandPrepare,
COLEDBERR::ePrepare, "CTPCC_OLEDB::PrepareCommand");
        }
    }

/*
 * Initialize fields of an array of bindings
structures.
 * Needs to be called before setting
individual parameter/column bindings.
 */

```

```

void CTPCC_OLEDB::InitBindings(DBBINDING*
pDBBindings, // IO: array of bindings

        int iCount, // I: number of
elements in the array

        eBindingType BindingType) //
I: what the bindings will be used for
(parameters/columns)
{
    int i;

    for(i = 0; i < iCount; i++)
    {
        pDBBindings[i].iOrdinal = i + 1;
        pDBBindings[i].obLength = 0;
        pDBBindings[i].obStatus = 0;
        pDBBindings[i].pTypeInfo = NULL;
        pDBBindings[i].pObject = NULL;
        pDBBindings[i].pBindExt = NULL;
        pDBBindings[i].dwPart = DBPART_VALUE;

        switch (BindingType)
        {
            case eInputParameter:
                pDBBindings[i].eParamIO
= DBPARAMIO_INPUT;
                break;
            case eOutputParameter:
                pDBBindings[i].eParamIO
= DBPARAMIO_OUTPUT;
                break;
            case eInputOutputParameter:
                pDBBindings[i].eParamIO
= DBPARAMIO_INPUT | DBPARAMIO_OUTPUT;
                break;
            case eOutputColumn:
                pDBBindings[i].eParamIO
= DBPARAMIO_NOTPARAM;
                break;
            default:
                assert(false); //
this should never happen
        }

        pDBBindings[i].dwMemOwner =
DBMEMOWNER_CLIENTOWNED;
        pDBBindings[i].dwFlags = 0;
        pDBBindings[i].bPrecision = 0;
        pDBBindings[i].bScale = 0;
    }
}

/*
 * Perform binding for one parameter or output
column.
 */
void CTPCC_OLEDB::SetBinding(DBBINDING* pDBBinding,
// I: binding row structure

```

```

        size_t obValue, // I: parameter (column) offset in the user
buffer

        size_t cbMaxLen, //
I: parameter (column) length

        DBTYPE wType // I: parameter (column) type
    )
    {
        pDBBinding->obValue = (ULONG)obValue;
        pDBBinding->cbMaxLen = (ULONG)cbMaxLen;
        pDBBinding->wType = wType;
    }

void CTPCC_OLEDB::InitStockLevelParams()
{
    int i;
    HRESULT
hr;
    wchar_t
szName[IMAX_SP_NAME_LEN];
    IAccessor*
piAccessor;
    const ULONG
nInputParams = 3; // input parameters
const ULONG
nOutputParams = 1; // output 1st result
set columns
    // Structure to bind in accessor
    DBBINDING
acInputDBBinding[nInputParams];
    DBBINDSTATUS
acInputDBBindStatus[nInputParams];
    DBBINDING
acOutputDBBinding[nOutputParams];
    DBBINDSTATUS
acOutputDBBindStatus[nOutputParams];

    // Set command text
    _snwprintf(szName,
sizeof(szName)/sizeof(szName[0]),
L"%{call
%stpc_stacklevel (?,?,?)", m_szSPPrefix);

    // Create and Prepare a new command object
for StockLevel.
    CreateCommand(szName,
&m_pISockLevelCommand);

    // Describe the consumer buffer by filling
in the array
// of DBBINDING structures. Each binding
associates
// a single parameter to the consumer's buffer.
    InitBindings(&acInputDBBinding[0],
nInputParams, eInputParameter);

```

```

        i = 0;
        // StockLevel parameter 1
        SetBinding(&acInputDBBinding[i++],
offsetof(STOCK_LEVEL_DATA, w_id),
sizeof(m_txn.StockLevel.w_id), DBTYPE_I4);

        // StockLevel parameter 2
        SetBinding(&acInputDBBinding[i++],
offsetof(STOCK_LEVEL_DATA, d_id),
sizeof(m_txn.StockLevel.d_id), DBTYPE_UI1);

        // StockLevel parameter 3
        SetBinding(&acInputDBBinding[i++],
offsetof(STOCK_LEVEL_DATA, threshold),
sizeof(m_txn.StockLevel.threshold), DBTYPE_I2);

        hr = m_pIStockLevelCommand-
>QueryInterface(IID_IAccessor, (void **)&piAccessor);
        if (FAILED(hr))
        {
            ThrowError(m_pIStockLevelCommand,
COLEDBERR::eQueryInterface,
"InitStockLevelParams()");
        }

        hr = piAccessor->CreateAccessor(
            DBACCESSOR_PARAMETERDATA,
            nInputParams,
            acInputDBBinding,
            sizeof(STOCK_LEVEL_DATA),

&m_hStockLevelInputAccessor,
            acInputDBBindStatus);

        if (FAILED(hr))
        {
            ThrowError(piAccessor,
COLEDBERR::eCreateAccessor,
"InitStockLevelParams()");
        }

        m_StockLevelExecuteParams.cParamSets = 1;
        m_StockLevelExecuteParams.hAccessor =
m_hStockLevelInputAccessor;
        m_StockLevelExecuteParams.pData =
&m_txn.StockLevel;

        // Now fill the binding information for
result set 1 output columns
        InitBindings(&acOutputDBBinding[0],
nOutputParams, eOutputColumn);

        // Binding for a rowset that may return
more than one row.
        i = 0;
        // StockLevel output column 1
        SetBinding(&acOutputDBBinding[i++],
offsetof(STOCK_LEVEL_DATA, low_stock),
sizeof(m_txn.StockLevel.low_stock), DBTYPE_I4);

        hr = piAccessor->CreateAccessor(

```

```

            DBACCESSOR_ROWDATA |
DBACCESSOR_OPTIMIZED,
            nOutputParams,
            acOutputDBBinding,
            sizeof(STOCK_LEVEL_DATA),

&m_hStockLevelOutputAccessor,
            acOutputDBBindStatus);

        if (FAILED(hr))
        {
            ThrowError(piAccessor,
COLEDBERR::eCreateAccessor,
"InitStockLevelParams()");
        }
    }

void CTPCC_OLEDB::StockLevel()
{
    HRESULT          hr;
    int              i;
    iTryCount = 0;
    IRowset*        pRowset;
    LONG            cRows = 1;
    // number of rows returned in the rowset
    ULONG          cRowsObtained;
    HROW           rghRow;
    //returned row handles
    HROW*          prghRow =
&rghRow;

    while (TRUE)
    {
        try
        {
            // Execute the prepared
command
            hr =
m_pIStockLevelCommand->Execute(NULL, IID_IRowset,
&m_StockLevelExecuteParams, NULL,

(IUnknown **)&pRowset);
            if (FAILED(hr))
            {
                ThrowError(m_pIStockLevelCommand,
COLEDBERR::eExecute, "StockLevel()");
            }

            // Fetch the result row
handle(s)
            hr = pRowset-
>GetNextRows(DB_NULL_HCHAPTER, 0, cRows,
&cRowsObtained, &prghRow);
            if (FAILED(hr))
            {
                ThrowError(m_pIStockLevelCommand,
COLEDBERR::eGetNextRows, "StockLevel()");
            }
        }
    }
}

```

```

            // Fetch the actual row
data by handle
            hr = pRowset-
>GetData(rghRow, m_hStockLevelOutputAccessor,
&m_txn.StockLevel);
            if (FAILED(hr))
            {
                ThrowError(m_pIStockLevelCommand,
COLEDBERR::eGetData, "StockLevel()");
            }

            // Release row(s)
            hr = pRowset-
>ReleaseRows(cRowsObtained, prghRow, NULL, NULL,
NULL);
            // Release rowset
            hr = pRowset-
>Release();

            m_txn.StockLevel.exec_status_code = eOK;

            break;
        }
        catch (COLEDBERR *e)
        {
            if (!e->m_bDeadLock)
            {
                if (++iTryCount > iMaxRetries)
                    throw;

                // hit deadlock;
                // backoff for increasingly longer period
                delete e;
                Sleep(10 * iTryCount);
            }
        }

        // if (iTryCount)
        // throw new
        CTPCC_OLEDB_ERR(CTPCC_OLEDB_ERR::ERR_RETRIED_TRANS,
iTryCount);
    }

void CTPCC_OLEDB::InitNewOrderParams()
{
    int              i, j, iOlCount;
    HRESULT          hr;
    wchar_t         szName[IMAX_SP_NAME_LEN];
    IAccessor*      piAccessor;
    const ULONG     nInputParams = 5 +
3*MAX_OL_NEW_ORDER_ITEMS; // input parameters
    const ULONG     nOutputParams = 5; // output 1st result
set columns
}

```

```

const ULONG
nOutputParams2 = 8; // output 2nd result
set columns
// Structure to bind in accessor
DBBINDING
acInputDBBinding[nInputParams];
DBBINDSTATUS
acInputDBBindStatus[nInputParams];
DBBINDING
acOutputDBBinding[nOutputParams];
DBBINDSTATUS
acOutputDBBindStatus[nOutputParams];
DBBINDING
acOutputDBBinding2[nOutputParams2];
DBBINDSTATUS
acOutputDBBindStatus2[nOutputParams2];

// Describe the consumer buffer by filling
in the array
// of DBBINDING structures. Each binding
associates
// a single parameter to the consumer's buffer.
InitBindings(&acInputDBBinding[0],
nInputParams, eInputParameter);

i = 0;
// NewOrder parameter 1
SetBinding(&acInputDBBinding[i++],
offsetof(NEW_ORDER_DATA, w_id),
sizeof(m_txn.NewOrder.w_id), DBTYPE_I4);

// NewOrder parameter 2
SetBinding(&acInputDBBinding[i++],
offsetof(NEW_ORDER_DATA, d_id),
sizeof(m_txn.NewOrder.d_id), DBTYPE_UI1);

// NewOrder parameter 3
SetBinding(&acInputDBBinding[i++],
offsetof(NEW_ORDER_DATA, c_id),
sizeof(m_txn.NewOrder.c_id), DBTYPE_I4);

// NewOrder parameter 4
SetBinding(&acInputDBBinding[i++],
offsetof(NEW_ORDER_DATA, o_ol_cnt),
sizeof(m_txn.NewOrder.o_ol_cnt), DBTYPE_UI1);

// NewOrder parameter 5
SetBinding(&acInputDBBinding[i++],
offsetof(NEW_ORDER_DATA, o_all_local),
sizeof(m_txn.NewOrder.o_all_local), DBTYPE_UI1);

for (j=0; j<MAX_OL_NEW_ORDER_ITEMS; j++)
{
SetBinding(&acInputDBBinding[i++],
offsetof(NEW_ORDER_DATA, OL[j].ol_i_id),
sizeof(m_txn.NewOrder.OL[j].ol_i_id), DBTYPE_I4);

SetBinding(&acInputDBBinding[i++],
offsetof(NEW_ORDER_DATA, OL[j].ol_supply_w_id),

```

```

sizeof(m_txn.NewOrder.OL[j].ol_supply_w_id),
DBTYPE_I4);

SetBinding(&acInputDBBinding[i++],
offsetof(NEW_ORDER_DATA, OL[j].ol_quantity),
sizeof(m_txn.NewOrder.OL[j].ol_quantity), DBTYPE_I2);
}

// Now fill the binding information for
result set 1 output columns
InitBindings(&acOutputDBBinding[0],
nOutputParams, eOutputColumn);

// Binding for the order line rowsets (each
consist of one row).
// Bind to offsets of the OL_NEW_ORDER_DATA
structure instead of NEW_ORDER_DATA.
// IRowset::GetData() will be passed
individual array slots OL[i] to fetch the data
// from the row set.

i = 0;
// NewOrder output column 1
SetBinding(&acOutputDBBinding[i++],
offsetof(OL_NEW_ORDER_DATA, ol_i_name),
sizeof(m_txn.NewOrder.OL[0].ol_i_name), DBTYPE_STR);

// NewOrder output column 2
SetBinding(&acOutputDBBinding[i++],
offsetof(OL_NEW_ORDER_DATA, ol_stock),
sizeof(m_txn.NewOrder.OL[0].ol_stock), DBTYPE_I2);

// NewOrder output column 3
SetBinding(&acOutputDBBinding[i++],
offsetof(OL_NEW_ORDER_DATA, ol_brand_generic),
sizeof(m_txn.NewOrder.OL[0].ol_brand_generic),
DBTYPE_STR);

// NewOrder output column 4
SetBinding(&acOutputDBBinding[i++],
offsetof(OL_NEW_ORDER_DATA, ol_i_price),
sizeof(m_txn.NewOrder.OL[0].ol_i_price), DBTYPE_R8);

// NewOrder output column 5
SetBinding(&acOutputDBBinding[i++],
offsetof(OL_NEW_ORDER_DATA, ol_amount),
sizeof(m_txn.NewOrder.OL[0].ol_amount), DBTYPE_R8);

// Now fill the binding information for
result set 2 output columns
InitBindings(&acOutputDBBinding2[0],
nOutputParams2, eOutputColumn);

i = 0;
// NewOrder output column 1

```

```

SetBinding(&acOutputDBBinding2[i++],
offsetof(NEW_ORDER_DATA, w_tax),
sizeof(m_txn.NewOrder.w_tax), DBTYPE_R8);

// NewOrder output column 2
SetBinding(&acOutputDBBinding2[i++],
offsetof(NEW_ORDER_DATA, d_tax),
sizeof(m_txn.NewOrder.d_tax), DBTYPE_R8);

// NewOrder output column 3
SetBinding(&acOutputDBBinding2[i++],
offsetof(NEW_ORDER_DATA, o_id),
sizeof(m_txn.NewOrder.o_id), DBTYPE_I4);

// NewOrder output column 4
SetBinding(&acOutputDBBinding2[i++],
offsetof(NEW_ORDER_DATA, c_last),
sizeof(m_txn.NewOrder.c_last), DBTYPE_STR);

// NewOrder output column 5
SetBinding(&acOutputDBBinding2[i++],
offsetof(NEW_ORDER_DATA, c_discount),
sizeof(m_txn.NewOrder.c_discount), DBTYPE_R8);

// NewOrder output column 6
SetBinding(&acOutputDBBinding2[i++],
offsetof(NEW_ORDER_DATA, c_credit),
sizeof(m_txn.NewOrder.c_credit), DBTYPE_STR);

// NewOrder output column 7
SetBinding(&acOutputDBBinding2[i++],
offsetof(NEW_ORDER_DATA, o_entry_d),
sizeof(m_txn.NewOrder.o_entry_d),
DBTYPE_DBTIMESTAMP);

// NewOrder output column 8
SetBinding(&acOutputDBBinding2[i++],
offsetof(NEW_ORDER_DATA, o_commit_flag),
sizeof(m_txn.NewOrder.o_commit_flag), DBTYPE_I2);

for (j=0; j<MAX_OL_NEW_ORDER_ITEMS; j++)
{
// Set command text first

// Print the fixed first portion
of parameters
i = _snwprintf(szName,
sizeof(szName)/sizeof(szName[0]),
L"call %stpc_neworder (?,?,?,?,"
m_szSPPrefix);

// Now print the variable portion
depending on the number of order line parameters
for (iOlCount = 0; iOlCount <= j;
+iOlCount)
{
i +=
_snwprintf(&szName[i],
sizeof(szName)/sizeof(szName[0]) - i, L",?,?,?");

```



```

    }
    // Print the fixed end
    if (j != MAX_OL_NEW_ORDER_ITEMS -
1)
    {
        // append 'default' for
the parameters that are not used
        i +=
        _snprintf(&szName[i],
sizeof(szName)/sizeof(szName[0]) - i, L"default}");
    }
    else // using all 15 order
line parameters
    {
        i +=
        _snprintf(&szName[i],
sizeof(szName)/sizeof(szName[0]) - i, L"}");
    }
    // Create and Prepare a new
command object for NewOrder.
    CreateCommand(szName,
&m_pINewOrderCommand[j]);
    // Now create the input accessor
for this prepared command
    hr = m_pINewOrderCommand[j]-
>QueryInterface(IID_IAccessor, (void **)&pIAccessor);
    if (FAILED(hr))
    {
        ThrowError(m_pINewOrderCommand[j],
COLEDBERR::eQueryInterface, "InitNewOrderParams()");
    }
    hr = pIAccessor->CreateAccessor(
        DBACCESSOR_PARAMETERDATA,
        3 * (j + 1),
        acInputDBBinding,
        sizeof(NEW_ORDER_DATA),
        &m_hNewOrderInputAccessor[j],
        acInputDBBindStatus);
    if (FAILED(hr))
    {
        ThrowError(pIAccessor,
COLEDBERR::eCreateAccessor, "InitNewOrderParams()");
    }
}

```

```

        m_NewOrderExecuteParams[j].cParamSets = 1;
        //
m_NewOrderExecuteParams.hAccessor is set dynamically
at run-time
        // based on the number of new
order items for the particular transaction call.
        m_NewOrderExecuteParams[j].hAccessor =
m_hNewOrderInputAccessor[j];
        m_NewOrderExecuteParams[j].pData
= &m_txn.NewOrder;
        // Create accessor for the first
rowset
        hr = pIAccessor->CreateAccessor(
            DBACCESSOR_ROWDATA |
            DBACCESSOR_OPTIMIZED,
            nOutputParams,
            acOutputDBBinding,
            sizeof(OL_NEW_ORDER_DATA),
            &m_hNewOrderOutputAccessor[j],
            acOutputDBBindStatus);
        if (FAILED(hr))
        {
            ThrowError(pIAccessor,
COLEDBERR::eCreateAccessor, "InitNewOrderParams()");
        }
        // Create accessor for the second
rowset
        hr = pIAccessor->CreateAccessor(
            DBACCESSOR_ROWDATA, //
cannot be optimized too because #1 accessor is
nOutputParams2,
            acOutputDBBinding2,
            sizeof(NEW_ORDER_DATA),
            &m_hNewOrderOutputAccessor2[j],
            acOutputDBBindStatus2);
        if (FAILED(hr))
        {
            ThrowError(pIAccessor,
COLEDBERR::eCreateAccessor, "InitNewOrderParams()");
        }
        pIAccessor->Release();
    }
}
void CTPCC_OLEDB::NewOrder()
{
    HRESULT
    int
    int
    iTryCount = 0;
    IMultipleResults* pMultipleResults;
    IRowset* pRowset;
    IRowset* pRowset2;
    hr;
}

```

```

        LONG
        cRows = 1; // number of rows
        returned in the 1st rowset
        ULONG
        cRowsObtained;
        HROW
        rghRows; //returned row handles
        for the 1st result set
        HROW*
        prghRows = &rghRows;
        LONG
        cRows2 = 1; // number of rows
        returned in the 2nd rowset
        ULONG
        cRowsObtained2;
        HROW
        rghRows2; //returned row handle
        for the 2nd result set
        HROW*
        prghRows2 = &rghRows2;
        int
        i;
        long
        lRowsAffected; // the number of
affected rows for a rowset
        int
        iHandleIndex; // index into the
handle arrays based on the orders count
        // check whether any order lines are for a
remote warehouse
        m_txn.NewOrder.o_all_local = 1;
        for (i = 0; i < m_txn.NewOrder.o_ol_cnt;
i++)
        {
            if
(m_txn.NewOrder.OL[i].ol_supply_w_id !=
m_txn.NewOrder.w_id)
            {
                m_txn.NewOrder.o_all_local = 0; // at
least one remote warehouse
                break;
            }
        }
        iHandleIndex = m_txn.NewOrder.o_ol_cnt - 1;
// for convenience
        while (TRUE)
        {
            try
            {
                // Execute the prepared
command (according to the number of new orders)
                // Ask for
IMultipleResults because it returns 2 rowsets.
                hr =
m_pINewOrderCommand[iHandleIndex]->Execute(

```

<pre> NULL, IID_MultipleResults, &m_NewOrderExecuteParams[iHandleIndex], NULL, (IUnknown **) &MultipleResults; if (FAILED(hr)) { ThrowError(m_pINewOrderCommand[iHandleIndex], COLEDBERR::eExecute, "NewOrder()"); } ////////////////////////////////////// // Get order line results ////////////////////////////////////// m_txn.NewOrder.total_amount = 0; for (i = 0; i < m_txn.NewOrder.o_ol_cnt; ++i) { // Get the first rowset object hr = pMultipleResults->GetResult(NULL, 0, IID_IRowset, &lRowsAffected, (IUnknown **) &pRowset); if (FAILED(hr)) { char szTmp[256]; _snprintf(szTmp, sizeof(szTmp), "NewOrder() result set %d, hr=0x%X", i, hr); ThrowError(m_pINewOrderCommand[m_txn.NewOrder.o_ol_cnt - 1], COLEDBERR::eGetResult, szTmp); } // Fetch the result row handle(s) hr = pRowset->GetNextRows(DB_NULL_HCHAPTER, 0, cRows, &cRowsObtained, &prghRows); if (FAILED(hr)) { ThrowError(m_pINewOrderCommand[iHandleIndex], COLEDBERR::eGetNextRows, "NewOrder()"); </pre>	<pre> } // Fetch the actual row data by handle hr = pRowset->GetData(rghRows, m_hNewOrderOutputAccessor[iHandleIndex], &m_txn.NewOrder.OL[i]); if (FAILED(hr)) { ThrowError(m_pINewOrderCommand[iHandleIndex], COLEDBERR::eGetData, "NewOrder()"); } m_txn.NewOrder.total_amount += m_txn.NewOrder.OL[i].ol_amount; // Release row(s) hr = pRowset->ReleaseRows(cRowsObtained, prghRows, NULL, NULL, NULL); // Release rowset hr = pRowset->Release(); } ////////////////////////////////////// // Get the second rowset object hr = pMultipleResults->GetResult(NULL, 0, IID_IRowset, &lRowsAffected, (IUnknown **) &pRowset2); if (FAILED(hr)) { char szTmp[256]; _snprintf(szTmp, sizeof(szTmp), "NewOrder() result set %d, hr=%d", i, hr); ThrowError(m_pINewOrderCommand[iHandleIndex], COLEDBERR::eGetResult, szTmp); } // Fetch the result row handle(s) hr = pRowset2->GetNextRows(DB_NULL_HCHAPTER, 0, cRows2, &cRowsObtained2, &prghRows2); if (FAILED(hr)) { </pre>	<pre> ThrowError(m_pINewOrderCommand[iHandleIndex], COLEDBERR::eGetNextRows, "NewOrder()"); } // Fetch the actual row data by handle hr = pRowset2->GetData(rghRows2, m_hNewOrderOutputAccessor2[iHandleIndex], &m_txn.NewOrder); if (FAILED(hr)) { ThrowError(m_pINewOrderCommand[iHandleIndex], COLEDBERR::eGetData, "NewOrder()"); } // Release row(s) hr = pRowset2->ReleaseRows(cRowsObtained2, prghRows2, NULL, NULL, NULL); // Release rowset hr = pRowset2->Release(); // Release the common MultipleResults interface hr = pMultipleResults->Release(); if (m_txn.NewOrder.o_all_local == 1) { m_txn.NewOrder.total_amount *= ((1 + m_txn.NewOrder.w_tax + m_txn.NewOrder.d_tax) * (1 - m_txn.NewOrder.c_discount)); m_txn.NewOrder.exec_status_code = eOK; } else { m_txn.NewOrder.exec_status_code = eInvalidItem; } break; } catch (COLEDBERR *e) { if (!(e->m_bDeadLock) (++iTryCount > iMaxRetries)) throw; // hit deadlock; backoff for increasingly longer period delete e; Sleep(10 * iTryCount); </pre>
--	---	---

```

    }
}
// if (iTryCount)
// throw new
CTPCC_OLEDB_ERR(CTPCC_OLEDB_ERR::ERR_RETRIED_TRANS,
iTryCount);
}

void CTPCC_OLEDB::InitPaymentParams()
{
    int
        i;
    HRESULT
        hr;
    wchar_t
        szName[IMAX_SP_NAME_LEN];
    IAccessor*
        pIAccessor;
    const ULONG
        nInputParams = 7; // input parameters
        const ULONG
        nOutputParams = 27; // output result set
columns
    // Structure to bind in accessor
    DBBINDING
        acInputDBBinding[nInputParams];
    DBBINDSTATUS
        acInputDBBindStatus[nInputParams];
    DBBINDING
        acOutputDBBinding[nOutputParams];
    DBBINDSTATUS
        acOutputDBBindStatus[nOutputParams];

    // Set command text
    _snwprintf(szName,
sizeof(szName)/sizeof(szName[0]), L"call
%stpc_payment(?,?,?,?,?,?)", m_szSPPrefix);

    // Create and Prepare a new command object
for Payment.
    CreateCommand(szName, &m_pIPaymentCommand);

    // Describe the consumer buffer by filling
in the array
    // of DBBINDING structures. Each binding
associates
    // a single parameter to the consumer's buffer.
    InitBindings(&acInputDBBinding[0],
nInputParams, eInputParameter);

    i = 0;
    // Payment parameter 1
    SetBinding(&acInputDBBinding[i++],
offsetof(PAYMENT_DATA, w_id),
sizeof(m_txn.Payment.w_id), DBTYPE_I4);

    // Payment parameter 2

```

```

    SetBinding(&acInputDBBinding[i++],
offsetof(PAYMENT_DATA, c_w_id),
sizeof(m_txn.Payment.c_w_id), DBTYPE_I4);

    // Payment parameter 3
    SetBinding(&acInputDBBinding[i++],
offsetof(PAYMENT_DATA, h_amount),
sizeof(m_txn.Payment.h_amount), DBTYPE_R8);

    // Payment parameter 4
    SetBinding(&acInputDBBinding[i++],
offsetof(PAYMENT_DATA, d_id),
sizeof(m_txn.Payment.d_id), DBTYPE_UI1);

    // Payment parameter 5
    SetBinding(&acInputDBBinding[i++],
offsetof(PAYMENT_DATA, c_d_id),
sizeof(m_txn.Payment.c_d_id), DBTYPE_UI1);

    // Payment parameter 6
    SetBinding(&acInputDBBinding[i++],
offsetof(PAYMENT_DATA, c_id),
sizeof(m_txn.Payment.c_id), DBTYPE_I4);

    // Payment parameter 7
    SetBinding(&acInputDBBinding[i++],
offsetof(PAYMENT_DATA, c_last),
sizeof(m_txn.Payment.c_last), DBTYPE_STR);

    hr = m_pIPaymentCommand-
>QueryInterface(IID_IAccessor, (void **)&pIAccessor);
    if (FAILED(hr))
    {
        ThrowError(m_pIPaymentCommand,
COLEDBERR::eQueryInterface, "InitPaymentParams()");
    }

    hr = pIAccessor->CreateAccessor(
        DBACCESSOR_PARAMETERDATA,
        nInputParams,
        acInputDBBinding,
        sizeof(PAYMENT_DATA),
        &m_hPaymentInputAccessor,
        acInputDBBindStatus);

    if (FAILED(hr))
    {
        ThrowError(pIAccessor,
COLEDBERR::eCreateAccessor, "InitPaymentParams()");
    }

    m_PaymentExecuteParams.cParamSets = 1;
    m_PaymentExecuteParams.hAccessor =
m_hPaymentInputAccessor;
    m_PaymentExecuteParams.pData =
&m_txn.Payment;

    // Now fill the binding information for
output columns
    InitBindings(&acOutputDBBinding[0],
nOutputParams, eOutputColumn);

```

```

    i = 0;
    // Payment output column 1
    SetBinding(&acOutputDBBinding[i++],
offsetof(PAYMENT_DATA, c_id),
sizeof(m_txn.Payment.c_id), DBTYPE_I4);

    // Payment output column 2
    SetBinding(&acOutputDBBinding[i++],
offsetof(PAYMENT_DATA, c_last),
sizeof(m_txn.Payment.c_last), DBTYPE_STR);

    // Payment output column 3
    SetBinding(&acOutputDBBinding[i++],
offsetof(PAYMENT_DATA, h_date),
sizeof(m_txn.Payment.h_date), DBTYPE_DBTIMESTAMP);

    // Payment output column 4
    SetBinding(&acOutputDBBinding[i++],
offsetof(PAYMENT_DATA, w_street_1),
sizeof(m_txn.Payment.w_street_1), DBTYPE_STR);

    // Payment output column 5
    SetBinding(&acOutputDBBinding[i++],
offsetof(PAYMENT_DATA, w_street_2),
sizeof(m_txn.Payment.w_street_2), DBTYPE_STR);

    // Payment output column 6
    SetBinding(&acOutputDBBinding[i++],
offsetof(PAYMENT_DATA, w_city),
sizeof(m_txn.Payment.w_city), DBTYPE_STR);

    // Payment output column 7
    SetBinding(&acOutputDBBinding[i++],
offsetof(PAYMENT_DATA, w_state),
sizeof(m_txn.Payment.w_state), DBTYPE_STR);

    // Payment output column 8
    SetBinding(&acOutputDBBinding[i++],
offsetof(PAYMENT_DATA, w_zip),
sizeof(m_txn.Payment.w_zip), DBTYPE_STR);

    // Payment output column 9
    SetBinding(&acOutputDBBinding[i++],
offsetof(PAYMENT_DATA, d_street_1),
sizeof(m_txn.Payment.d_street_1), DBTYPE_STR);

    // Payment output column 10
    SetBinding(&acOutputDBBinding[i++],
offsetof(PAYMENT_DATA, d_street_2),
sizeof(m_txn.Payment.d_street_2), DBTYPE_STR);

    // Payment output column 11
    SetBinding(&acOutputDBBinding[i++],
offsetof(PAYMENT_DATA, d_city),
sizeof(m_txn.Payment.d_city), DBTYPE_STR);

    // Payment output column 12
    SetBinding(&acOutputDBBinding[i++],
offsetof(PAYMENT_DATA, d_state),
sizeof(m_txn.Payment.d_state), DBTYPE_STR);

```

```

        // Payment output column 13
        SetBinding(&acOutputDBBinding[i++],
offsetof(PAYMENT_DATA, d_zip),
sizeof(m_txn.Payment.d_zip), DBTYPE_STR);

        // Payment output column 14
        SetBinding(&acOutputDBBinding[i++],
offsetof(PAYMENT_DATA, c_first),
sizeof(m_txn.Payment.c_first), DBTYPE_STR);

        // Payment output column 15
        SetBinding(&acOutputDBBinding[i++],
offsetof(PAYMENT_DATA, c_middle),
sizeof(m_txn.Payment.c_middle), DBTYPE_STR);

        // Payment output column 16
        SetBinding(&acOutputDBBinding[i++],
offsetof(PAYMENT_DATA, d_street_1),
sizeof(m_txn.Payment.d_street_1), DBTYPE_STR);

        // Payment output column 17
        SetBinding(&acOutputDBBinding[i++],
offsetof(PAYMENT_DATA, d_street_2),
sizeof(m_txn.Payment.d_street_2), DBTYPE_STR);

        // Payment output column 18
        SetBinding(&acOutputDBBinding[i++],
offsetof(PAYMENT_DATA, d_city),
sizeof(m_txn.Payment.d_city), DBTYPE_STR);

        // Payment output column 19
        SetBinding(&acOutputDBBinding[i++],
offsetof(PAYMENT_DATA, d_state),
sizeof(m_txn.Payment.d_state), DBTYPE_STR);

        // Payment output column 20
        SetBinding(&acOutputDBBinding[i++],
offsetof(PAYMENT_DATA, d_zip),
sizeof(m_txn.Payment.d_zip), DBTYPE_STR);

        // Payment output column 21
        SetBinding(&acOutputDBBinding[i++],
offsetof(PAYMENT_DATA, c_phone),
sizeof(m_txn.Payment.c_phone), DBTYPE_STR);

        // Payment output column 22
        SetBinding(&acOutputDBBinding[i++],
offsetof(PAYMENT_DATA, c_since),
sizeof(m_txn.Payment.c_since), DBTYPE_DBTIMESTAMP);

        // Payment output column 23
        SetBinding(&acOutputDBBinding[i++],
offsetof(PAYMENT_DATA, c_credit),
sizeof(m_txn.Payment.c_credit), DBTYPE_STR);

        // Payment output column 24
        SetBinding(&acOutputDBBinding[i++],
offsetof(PAYMENT_DATA, c_credit_lim),
sizeof(m_txn.Payment.c_credit_lim), DBTYPE_R8);

        // Payment output column 25

```

```

        SetBinding(&acOutputDBBinding[i++],
offsetof(PAYMENT_DATA, c_discount),
sizeof(m_txn.Payment.c_discount), DBTYPE_R8);

        // Payment output column 26
        SetBinding(&acOutputDBBinding[i++],
offsetof(PAYMENT_DATA, c_balance),
sizeof(m_txn.Payment.c_balance), DBTYPE_R8);

        // Payment output column 27
        SetBinding(&acOutputDBBinding[i++],
offsetof(PAYMENT_DATA, c_data),
sizeof(m_txn.Payment.c_data), DBTYPE_STR);

        hr = piAccessor->CreateAccessor(
DBACCESSOR_OPTIMIZED, DBACCESSOR_ROWDATA |
nOutputParams,
acOutputDBBinding,
sizeof(PAYMENT_DATA),
&m_hPaymentOutputAccessor,
acOutputDBBindStatus);

        if (FAILED(hr))
        {
            ThrowError(piAccessor,
COLEDBERR::eCreateAccessor, "InitPaymentParams()");
        }

void CTPCC_OLEDB::Payment()
{
    HRESULT hr;
    int
    iTryCount = 0;
    IRowset* pRowset;
    LONG cRows = 1;
    // number of rows returned in the rowset
    ULONG
    cRowsObtained;
    HROW rghRow;
    //returned row handles
    HROW* prghRow =
&rghRow;

    if (m_txn.Payment.c_id != 0)
        m_txn.Payment.c_last[0] = 0;

    while (TRUE)
    {
        try
        {
            // Execute the prepared
            command
            hr =
m_pIPaymentCommand->Execute(NULL, IID_IRowset,
&m_PaymentExecuteParams, NULL,
(IUnknown **)&pRowset);

```

```

        if (FAILED(hr))
        {
            ThrowError(m_pIPaymentCommand,
COLEDBERR::eExecute, "Payment()");
        }

        // Fetch the result row
        handle(s)
            hr = pRowset-
>GetNextRows(DB_NULL_HCHAPTER, 0, cRows,
&cRowsObtained, &prghRow);
            if (FAILED(hr))
            {
                ThrowError(m_pIPaymentCommand,
COLEDBERR::eGetNextRows, "Payment()");
            }

        // Fetch the actual row
        data by handle
            hr = pRowset-
>GetData(rghRow, m_hPaymentOutputAccessor,
&m_txn.Payment);
            if (FAILED(hr))
            {
                ThrowError(m_pIPaymentCommand,
COLEDBERR::eGetData, "Payment()");
            }

        // Release row(s)
        hr = pRowset-
>ReleaseRows(cRowsObtained, prghRow, NULL, NULL,
NULL);

        // Release rowset
        hr = pRowset-
>Release();

        if (m_txn.Payment.c_id
== 0)
            throw new
CTPCC_OLEDB_ERR( CTPCC_OLEDB_ERR::ERR_INVALID_CUST );
        else
            m_txn.Payment.exec_status_code = eOK;

        break;
    }
    catch (COLEDBERR *e)
    {
        if (!(e->m_bDeadLock)
|| (++iTryCount > iMaxRetries))
            throw;

        // hit deadlock;
        backoff for increasingly longer period
        delete e;
        Sleep(10 * iTryCount);
    }
}

```

```

//      if (iTryCount)
//          throw new
CTPCC_OLEDB_ERR (CTPCC_OLEDB_ERR::ERR_RETRIED_TRANS,
iTryCount);
}

void CTPCC_OLEDB::InitOrderStatusParams()
{
    int            i;
    HRESULT        hr;
    wchar_t       szName[iMAX_SP_NAME_LEN];
    IAccessor*     pIAccessor;
    const ULONG   nInputParams = 4; // input parameters
    const ULONG   nOutputParams = 5; // output 1st result
set columns
    const ULONG   nOutputParams2 = 8; // output 2nd result
set columns
    // Structure to bind in accessor
    DBBINDING
    acInputDBBinding[nInputParams];
    DBBINDSTATUS
    acInputDBBindStatus[nInputParams];
    DBBINDING
    acOutputDBBinding[nOutputParams];
    DBBINDSTATUS
    acOutputDBBindStatus[nOutputParams];
    DBBINDING
    acOutputDBBinding2[nOutputParams2];
    DBBINDSTATUS
    acOutputDBBindStatus2[nOutputParams2];

    // Set command text
    snprintf(szName,
sizeof(szName)/sizeof(szName[0]),
L"call
%stppcc_orderstatus (?, ?, ?, ?)", m_szSPPrefix);

    // Create and Prepare a new command object
    for OrderStatus.
    CreateCommand(szName,
&m_pIOrderStatusCommand);

    // Describe the consumer buffer by filling
    in the array
    // of DBBINDING structures. Each binding
    associates
    // a single parameter to the consumer's buffer.
    InitBindings(&acInputDBBinding[0],
nInputParams, eInputParameter);

    i = 0;
    // OrderStatus parameter 1

```

```

        SetBinding(&acInputDBBinding[i++],
offsetof(ORDER_STATUS_DATA, w_id),
sizeof(m_txn.OrderStatus.w_id), DBTYPE_I4);

    // OrderStatus parameter 2
    SetBinding(&acInputDBBinding[i++],
offsetof(ORDER_STATUS_DATA, d_id),
sizeof(m_txn.OrderStatus.d_id), DBTYPE_UI1);

    // OrderStatus parameter 3
    SetBinding(&acInputDBBinding[i++],
offsetof(ORDER_STATUS_DATA, c_id),
sizeof(m_txn.OrderStatus.c_id), DBTYPE_I4);

    // OrderStatus parameter 4
    SetBinding(&acInputDBBinding[i++],
offsetof(ORDER_STATUS_DATA, c_last),
sizeof(m_txn.OrderStatus.c_last), DBTYPE_STR);

    hr = m_pIOrderStatusCommand-
>QueryInterface(IID_IAccessor, (void **)&pIAccessor);
    if (FAILED(hr))
    {
        ThrowError(m_pIOrderStatusCommand,
COLEDBERR::eQueryInterface,
"InitOrderStatusParams()");
    }

    hr = pIAccessor->CreateAccessor(
        DBACCESSOR_PARAMETERDATA,
        nInputParams,
        acInputDBBinding,
        sizeof(ORDER_STATUS_DATA),
        &m_hOrderStatusInputAccessor,
        acInputDBBindStatus);

    if (FAILED(hr))
    {
        ThrowError(pIAccessor,
COLEDBERR::eCreateAccessor,
"InitOrderStatusParams()");
    }

    m_OrderStatusExecuteParams.cParamSets = 1;
    m_OrderStatusExecuteParams.hAccessor =
m_hOrderStatusInputAccessor;
    m_OrderStatusExecuteParams.pData =
&m_txn.OrderStatus;

    // Now fill the binding information for
    result set 1 output columns
    InitBindings(&acOutputDBBinding[0],
nOutputParams, eOutputColumn);

    // Binding for a rowset that may return
    more than one row.
    // Bind to offsets of the
    OL_ORDER_STATUS_DATA structure instead of
    ORDER_STATUS_DATA.

```

```

    // IRowset::GetData() will be passed
    individual array slots OL[i] to fetch the data
    // from the row set.

    i = 0;
    // OrderStatus output column 1
    SetBinding(&acOutputDBBinding[i++],
offsetof(OL_ORDER_STATUS_DATA, ol_supply_w_id),
sizeof(m_txn.OrderStatus.OL[0].ol_supply_w_id),
DBTYPE_I4);

    // OrderStatus output column 2
    SetBinding(&acOutputDBBinding[i++],
offsetof(OL_ORDER_STATUS_DATA, ol_i_id),
sizeof(m_txn.OrderStatus.OL[0].ol_i_id), DBTYPE_I4);

    // OrderStatus output column 3
    SetBinding(&acOutputDBBinding[i++],
offsetof(OL_ORDER_STATUS_DATA, ol_quantity),
sizeof(m_txn.OrderStatus.OL[0].ol_quantity),
DBTYPE_I2);

    // OrderStatus output column 4
    SetBinding(&acOutputDBBinding[i++],
offsetof(OL_ORDER_STATUS_DATA, ol_amount),
sizeof(m_txn.OrderStatus.OL[0].ol_amount),
DBTYPE_R8);

    // OrderStatus output column 5
    SetBinding(&acOutputDBBinding[i++],
offsetof(OL_ORDER_STATUS_DATA, ol_delivery_d),
sizeof(m_txn.OrderStatus.OL[0].ol_delivery_d),
DBTYPE_DBTIMESTAMP);

    hr = pIAccessor->CreateAccessor(
        DBACCESSOR_ROWDATA |
DBACCESSOR_OPTIMIZED,
        nOutputParams,
        acOutputDBBinding,
        sizeof(OL_ORDER_STATUS_DATA),
        &m_hOrderStatusOutputAccessor,
        acOutputDBBindStatus);

    if (FAILED(hr))
    {
        ThrowError(pIAccessor,
COLEDBERR::eCreateAccessor,
"InitOrderStatusParams()");
    }

    // Now fill the binding information for
    result set 2 output columns
    InitBindings(&acOutputDBBinding2[0],
nOutputParams2, eOutputColumn);

    i = 0;
    // OrderStatus output column 1
    SetBinding(&acOutputDBBinding2[i++],
offsetof(ORDER_STATUS_DATA, c_id),
sizeof(m_txn.OrderStatus.c_id), DBTYPE_I4);

```

```

// OrderStatus output column 2
SetBinding(&acOutputDBBinding2[i++],
offsetof(ORDER_STATUS_DATA, c_last),
sizeof(m_txn.OrderStatus.c_last), DBTYPE_STR);

// OrderStatus output column 3
SetBinding(&acOutputDBBinding2[i++],
offsetof(ORDER_STATUS_DATA, c_first),
sizeof(m_txn.OrderStatus.c_first), DBTYPE_STR);

// OrderStatus output column 4
SetBinding(&acOutputDBBinding2[i++],
offsetof(ORDER_STATUS_DATA, c_middle),
sizeof(m_txn.OrderStatus.c_middle), DBTYPE_STR);

// OrderStatus output column 5
SetBinding(&acOutputDBBinding2[i++],
offsetof(ORDER_STATUS_DATA, o_entry_d),
sizeof(m_txn.OrderStatus.o_entry_d),
DBTYPE_DBTIMESTAMP);

// OrderStatus output column 7
SetBinding(&acOutputDBBinding2[i++],
offsetof(ORDER_STATUS_DATA, o_carrier_id),
sizeof(m_txn.OrderStatus.o_carrier_id), DBTYPE_I2);

// OrderStatus output column 8
SetBinding(&acOutputDBBinding2[i++],
offsetof(ORDER_STATUS_DATA, c_balance),
sizeof(m_txn.OrderStatus.c_balance),
DBTYPE_R8);

// OrderStatus output column 9
SetBinding(&acOutputDBBinding2[i++],
offsetof(ORDER_STATUS_DATA, o_id),
sizeof(m_txn.OrderStatus.o_id),
DBTYPE_I4);

hr = piAccessor->CreateAccessor(
    DBACCESSOR_ROWDATA, //
cannot be optimized too because #1 accessor is
    nOutputParams2,
    acOutputDBBinding2,
    sizeof(NEW_ORDER_DATA),
&m_hOrderStatusOutputAccessor2,
    acOutputDBBindStatus2);

if (FAILED(hr))
{
    ThrowError(piAccessor,
COLEDBERR::eCreateAccessor,
"InitOrderStatusParams()");
}

void CTPCC_OLEDB::OrderStatus()
{
    HRESULT hr;
    int
    iTryCount = 0;
    IMultipleResults* pMultipleResults;
    IRowset* pRowset;

```

```

IRowset* pRowset2;
LONG
cRows = MAX_OL_ORDER_STATUS_ITEMS; //
number of rows returned in the 1st rowset
ULONG
cRowsObtained;
HROW
rghRows[MAX_OL_ORDER_STATUS_ITEMS];
//returned row handles for the 1st result
set
HROW*
prghRows = &rghRows[0];
LONG
cRows2 = 1; // number of rows
returned in the 2nd rowset
ULONG
cRowsObtained2;
HROW
rghRows2; //returned row handle
for the 2nd result set
HROW*
prghRows2 = &rghRows2;
int
i;
long
lRowsAffected; // the number of
affected rows for a rowset

if (m_txn.OrderStatus.c_id != 0)
    m_txn.OrderStatus.c_last[0] = 0;

while (TRUE)
{
    try
    {
        // Execute the prepared
command // Ask for
IMultipleResults because it returns 2 rowsets.
        hr =
m_pIOrderStatusCommand->Execute(NULL,
IID_IMultipleResults, &m_OrderStatusExecuteParams,
NULL,

        (IUnknown **)&pMultipleResults);
        if (FAILED(hr))
        {
            ThrowError(m_pIOrderStatusCommand,
COLEDBERR::eExecute, "OrderStatus()");
        }

        //////////////////////////////////////
        // Get order line
        results
        //////////////////////////////////////

```

```

// Get the first rowset
object
hr = pMultipleResults-
>GetResult(NULL, 0, IID_IRowset, &lRowsAffected,
(IUnknown **)&pRowset);
if (FAILED(hr))
{
    ThrowError(m_pIOrderStatusCommand,
COLEDBERR::eGetResult, "OrderStatus()");
}

// Fetch the result row
handle(s)
hr = pRowset-
>GetNextRows(DB_NULL_HCHAPTER, 0, cRows,
&cRowsObtained, &prghRows);
if (FAILED(hr))
{
    ThrowError(m_pIOrderStatusCommand,
COLEDBERR::eGetNextRows, "OrderStatus()");
}

m_txn.OrderStatus.o_ol_cnt =
(short)cRowsObtained;

// Get the data from
multiple rows in this rowset
for (i = 0; i <
m_txn.OrderStatus.o_ol_cnt; ++i)
{
    // Fetch the
actual row data by handle
hr = pRowset-
>GetData(rghRows[i], m_hOrderStatusOutputAccessor,
&m_txn.OrderStatus.OL[i]);
if
(FAILED(hr))
{
    ThrowError(m_pIOrderStatusCommand,
COLEDBERR::eGetData, "OrderStatus()");
}

// Release row(s)
hr = pRowset-
>ReleaseRows(cRowsObtained, prghRows, NULL, NULL,
NULL);
// Release rowset
hr = pRowset-
>Release();

////////////////////////////////////
// Get the second
rowset object
////////////////////////////////////

```

```

        if
(m_txn.OrderStatus.o_ol_cnt > 0)
    {
        hr =
pMultipleResults->GetResult(NULL, 0, IID_IRowset,
&lRowsAffected, (IUnknown **)&pRowset2);
        if
(FAILED(hr))
        {
            ThrowError(m_pIOrderStatusCommand,
COLEDBERR::eGetResult, "OrderStatus()");
        }

        // Fetch the
result row handle(s)
        hr =
pRowset2->GetNextRows(DB_NULL_HCHAPTER, 0, cRows2,
&cRowsObtained2, &prghRows2);
        if
(FAILED(hr))
        {
            ThrowError(m_pIOrderStatusCommand,
COLEDBERR::eGetNextRows, "OrderStatus()");
        }

        // Fetch the
actual row data by handle
        hr =
pRowset2->GetData(rgRows2,
m_hOrderStatusOutputAccessor2, &m_txn.OrderStatus);
        if
(FAILED(hr))
        {
            ThrowError(m_pIOrderStatusCommand,
COLEDBERR::eGetData, "OrderStatus()");
        }

        // Release
row(s)
        hr =
pRowset2->Release();
    }

    // Release the common
MultipleResults interface
    hr = pMultipleResults-
>Release();

    if
(m_txn.OrderStatus.o_ol_cnt == 0)
        throw new
CTPCC_OLEDB_ERR( CTPCC_OLEDB_ERR::ERR_NO_SUCH_ORDER
);
    else if
(m_txn.OrderStatus.c_id == 0 &&
m_txn.OrderStatus.c_last[0] == 0)
        throw new
CTPCC_OLEDB_ERR( CTPCC_OLEDB_ERR::ERR_INVALID_CUST );

```

```

    else
        m_txn.OrderStatus.exec_status_code = eOK;
        break;
    }
    catch (COLEDBERR *e)
    {
        if (!(e->m_bDeadLock))
        || (++iTryCount > iMaxRetries))
            throw;

        // hit deadlock;
        backoff for increasingly longer period
        delete e;
        Sleep(10 * iTryCount);
    }

    if (iTryCount)
        throw new
CTPCC_OLEDB_ERR(CTPCC_OLEDB_ERR::ERR_RETRIED_TRANS,
iTryCount);

void CTPCC_OLEDB::InitDeliveryParams()
{
    int        i;
    HRESULT    hr;
    wchar_t    szName[IMAX_SP_NAME_LEN];
    IAccessor* pIAccessor;

    const ULONG
nInputParams = 2; // input parameters
const ULONG
nOutputParams = 10; // output 1st result
set columns

    // Structure to bind in accessor
    DBBINDING
acInputDBBinding[nInputParams];
    DBBINDSTATUS
acInputDBBindStatus[nInputParams];
    DBBINDING
acOutputDBBinding[nOutputParams];
    DBBINDSTATUS
acOutputDBBindStatus[nOutputParams];

    // Set command text
    _snwprintf(szName,
sizeof(szName)/sizeof(szName[0]),
L"{call %stpc_delivery
(?,?)", m_szSPPrefix);

    // Create and Prepare a new command object
    CreateCommand(szName,
&m_pIDeliveryCommand);

```

```

        // Describe the consumer buffer by filling
in the array
        // of DBBINDING structures. Each binding
associates
        // a single parameter to the consumer's buffer.
        InitBindings(&acInputDBBinding[0],
nInputParams, eInputParameter);

        i = 0;
        // Delivery parameter 1
        SetBinding(&acInputDBBinding[i++],
offsetof(DELIVERY_DATA, w_id),
sizeof(m_txn.Delivery.w_id), DBTYPE_I4);

        // Delivery parameter 2
        SetBinding(&acInputDBBinding[i++],
offsetof(DELIVERY_DATA, o_carrier_id),
sizeof(m_txn.Delivery.o_carrier_id), DBTYPE_I2);

        hr = m_pIDeliveryCommand-
>QueryInterface(IID_IAccessor, (void **)&pIAccessor);
        if (FAILED(hr))
        {
            ThrowError(m_pIDeliveryCommand,
COLEDBERR::eQueryInterface, "InitDeliveryParams()");
        }

        hr = pIAccessor->CreateAccessor(
            DBACCESSOR_PARAMETERDATA,
nInputParams,
acInputDBBinding,
sizeof(DELIVERY_DATA),

&m_hDeliveryInputAccessor,
acInputDBBindStatus);
        if (FAILED(hr))
        {
            ThrowError(pIAccessor,
COLEDBERR::eCreateAccessor, "InitDeliveryParams()");
        }

        m_DeliveryExecuteParams.cParamSets = 1;
        m_DeliveryExecuteParams.hAccessor =
m_hDeliveryInputAccessor;
        m_DeliveryExecuteParams.pData =
&m_txn.Delivery;

        // Now fill the binding information for
result set 1 output columns
        InitBindings(&acOutputDBBinding[0],
nOutputParams, eOutputColumn);

        // Binding for a rowset that may return
more than
one row.
        for (i = 0; i < 10; ++i)
        {
            // Delivery output column 1
            SetBinding(&acOutputDBBinding[i],
offsetof(DELIVERY_DATA, o_id[i]),
sizeof(m_txn.Delivery.o_id[i]), DBTYPE_I4);

```

```

    }

    hr = pIAccessor->CreateAccessor(
        DBACCESSOR_ROWDATA |
DBACCESSOR_OPTIMIZED,
        nOutputParams,
        acOutputDBBinding,
        sizeof(DELIVERY_DATA),
&m_hDeliveryOutputAccessor,
        acOutputDBBindStatus);
    if (FAILED(hr))
    {
        ThrowError(pIAccessor,
COLEDBERR::eCreateAccessor, "InitDeliveryParams()");
    }
}

void CTPCC_OLEDB::Delivery()
{
    HRESULT                hr;
    int
    iTryCount = 0;
    IRowset*              pRowset;
    LONG                  cRows = 1;
    // number of rows returned in the rowset
    ULONG
    cRowsObtained;
    HROW                  rgRow;
    //returned row handles
    HROW*                 prghRow =
&rgRow;

    while (TRUE)
    {
        try
        {
            // Execute the prepared
command
                hr =
m_pIDeliveryCommand->Execute(NULL, IID_IRowset,
&m_DeliveryExecuteParams, NULL,

                (IUnknown **)&pRowset);
            if (FAILED(hr))
            {
                ThrowError(m_pIDeliveryCommand,
COLEDBERR::eExecute, "Delivery()");
            }

            // Fetch the result row
handle(s)
                hr = pRowset-
>GetNextRows(DB_NULL_HCHAPTER, 0, cRows,
&cRowsObtained, &prghRow);
            if (FAILED(hr))
            {

```

```

                ThrowError(m_pIDeliveryCommand,
COLEDBERR::eGetNextRows, "Delivery()");
            }
        }
        // Fetch the actual row
data by handle
                hr = pRowset-
>GetData(rgRow, m_hDeliveryOutputAccessor,
&m_txn.Delivery);
            if (FAILED(hr))
            {
                ThrowError(m_pIDeliveryCommand,
COLEDBERR::eGetData, "Delivery()");
            }

            // Release row(s)
            hr = pRowset-
>ReleaseRows(cRowsObtained, prghRow, NULL, NULL,
NULL);
            // Release rowset
            hr = pRowset-
>Release();

            m_txn.Delivery.exec_status_code = eOK;

            break;
        }
        catch (COLEDBERR *e)
        {
            if (!(e->m_bDeadLock))
            {
                ++iTryCount > iMaxRetries))
                throw;

            // hit deadlock;
            // error from QueryInterface
            // backoff for increasingly longer period
            delete e;
            Sleep(10 * iTryCount);
        }
    }

    // if (iTryCount)
    // throw new
CTPCC_OLEDB_ERR(CTPCC_OLEDB_ERR::ERR_RETRIED_TRANS,
iTryCount);
}

-----
tpcc_oledb.h
-----
/* FILE: TPC_C_OLEDB.H
 * Microsoft
 * TPC-C Kit Ver. 4.20.000
 * Copyright
 * Microsoft, 1999-2004
 * Written by
 * Sergey Vasilevskiy
 * All Rights Reserved
 *

```

```

 *
 *
 * PURPOSE: Header file for TPC-C txn class
OLE DB implementation.
 *
 *
 */
#pragma once

// need to declare functions for import, unless
define has already been created
// by the DLL's .cpp module for export.
#ifndef DllDecl
#define DllDecl __declspec( dllimport )
#endif

#define IMAX_SP_NAME_LEN 256 //maximum length of a
stored procedure name with parameters

// Type of parameter and result set column bindings.
enum eBindingType
{
    eInputParameter,
    eOutputParameter,
    eInputOutputParameter,
    eOutputColumn
};

class COLEDBERR : public CBaseErr
{
public:
    enum ACTION
    {
        eNone,
        eUnknown,
        eQueryInterface,
        // error from QueryInterface
        eCreateSession,
        eCreateCommand,
        eSetCommandText,
        eExecute,

        // = 6

        eCreateAccessor,
        ePrepare,
        eGetNextRows,
        eGetData,
        eGetResult

        // = 11
    };

    COLEDBERR(LPCTSTR szLoc)
        : CBaseErr(szLoc)
    {
        m_eAction = eNone;
        m_NativeError = 0;
        m_bDeadLock = FALSE;
        m_OLEDBErrStr = NULL;
    };

    ~COLEDBERR()
    {

```



```

        if (m_OLEDBErrStr !=
NULL)
        delete []
m_OLEDBErrStr;
    };

    ACTION    m_eAction;
    int
m_NativeError;
    BOOL      m_bDeadLock;
    char      *m_OLEDBErrStr;

    int
ErrorType()
{return ERR_TYPE_OLEDB;};
    char*
ErrorTypeStr() { return
"OLEDB"; }
    int
ErrorNum()
{return m_NativeError;};
    char*
ErrorText() {return
m_OLEDBErrStr;};
    int
ErrorAction()
{ return (int)m_eAction; }
};

class CTPCC_OLEDB_ERR : public CBaseErr
{
    public:
        enum TPCC_OLEDB_ERRS
        {
            ERR_WRONG_SP_VERSION =
1, // "Wrong version of stored procs on
database server"
            ERR_INVALID_CUST,
// "Invalid Customer id,name."
            ERR_NO_SUCH_ORDER,
// "No orders found for
customer."
            ERR_RETRIED_TRANS,
// "Retries before transaction
succeeded."
        };

        CTPCC_OLEDB_ERR( int iErr ) {
m_errno = iErr; m_iTryCount = 0; };

        CTPCC_OLEDB_ERR( int iErr, int
iTryCount ) { m_errno = iErr; m_iTryCount =
iTryCount; };

        int
m_errno;
        int
m_iTryCount;

        int
ErrorType()
{return ERR_TYPE_TPCC_OLEDB;};
        char*
ErrorTypeStr() { return
"TPCC OLEDB"; }
        int
ErrorNum()
{return m_errno;};

        char*
ErrorText();

```

```

};

class DllDecl CTPCC_OLEDB : public CTPCC_BASE
{
    private:
        // declare variables and private
        functions here...
        BOOL
m_bDeadlock; //
transaction was selected as deadlock victim
        int
m_MaxRetries;
// retry count on deadlock

        DBPROPSET
m_rgInitPropSet; //
initialization property set used to establish a
connection
        DBPROP
m_InitProperties[4]; //
individual initialization properties

        IDBCreateSession*
m_pIDBCreateSession; // session
(connection) interface
        IDBCreateCommand*
m_pIDBCreateCommand; // SQL
command creation interface

        IMalloc*
m_pIMalloc;
// Needed to release error strings.

        // StockLevel
        ICommandText*
m_pIStockLevelCommand;
        HACCESSOR
m_hStockLevelInputAccessor; // accessor
to bind input parameters
        HACCESSOR
m_hStockLevelOutputAccessor; // accessor
to bind output columns
        DBPARAMS
m_StockLevelExecuteParams; //
parameter structure for Execute

        // NewOrder
        // One prepared command for each
possible number of new order line items
        ICommandText*
m_pINewOrderCommand[MAX_OL_NEW_ORDER_ITEMS]
;
        // accessors to bind input
parameters
        // one for each possible number
of new order line items
        HACCESSOR
m_hNewOrderInputAccessor[MAX_OL_NEW_ORDER_I
TEMS];
        // accessor to bind output
columns of the first rowset

```

```

        HACCESSOR
m_hNewOrderOutputAccessor[MAX_OL_NEW_ORDER_
ITEMS];
        // accessor to bind output
columns of the second rowset
        HACCESSOR
m_hNewOrderOutputAccessor2[MAX_OL_NEW_ORDER
_ITEMS];
        // parameter structure for
Execute
        DBPARAMS
m_NewOrderExecuteParams[MAX_OL_NEW_ORDER_IT
EMS];

        // Payment
        ICommandText*
m_pIPaymentCommand;
        HACCESSOR
m_hPaymentInputAccessor; // accessor
to bind input parameters
        HACCESSOR
m_hPaymentOutputAccessor; // accessor
to bind output columns
        DBPARAMS
m_PaymentExecuteParams; //
parameter structure for Execute

        // OrderStatus
        ICommandText*
m_pIOrderStatusCommand;
        HACCESSOR
m_hOrderStatusInputAccessor; // accessor
to bind input parameters
        HACCESSOR
m_hOrderStatusOutputAccessor; // accessor
to bind output columns
        HACCESSOR
m_hOrderStatusOutputAccessor2; //
accessor to bind output columns
        DBPARAMS
m_OrderStatusExecuteParams; //
parameter structure for Execute

        // Delivery
        ICommandText*
m_pIDeliveryCommand;
        HACCESSOR
m_hDeliveryInputAccessor; // accessor
to bind input parameters
        HACCESSOR
m_hDeliveryOutputAccessor; // accessor
to bind output columns
        DBPARAMS
m_DeliveryExecuteParams; // parameter
structure for Execute

        wchar_t
m_szSPPrefix[32]; // stored
procedures prefix

```

```

// new-order specific fields
int
    m_no_commit_flag;

void ThrowError( IUnknown*
pObjectWithError, COLEDBERR::ACTION eAction, LPCTSTR
szLocation );

void CheckSPVersion();

void InitNewOrderParams();
void InitPaymentParams();
void InitDeliveryParams();
void InitStockLevelParams();
void InitOrderStatusParams();

// Helper function to create and
prepare a command
void CreateCommand(wchar_t*
szSQLCommand, ICommandText** ppICommandText);
// Helper function to prepare a
command
void PrepareCommand(ICommandText*
pICommand);

// Helper function to fill one
binding
// Used for both input parameter
and output column bindings
void SetBinding(DBBINDING*
pDBBinding, size_t obValue, size_t cbMaxLen, DBTYPE
wType);

// Helper function to initialize
an array of bindings
void InitBindings(DBBINDING*
pDBBindings, int iCount, eBindingType BindingType);

union
{
    NEW_ORDER_DATA
NewOrder;
    PAYMENT_DATA
Payment;
    DELIVERY_DATA
Delivery;
    STOCK_LEVEL_DATA
StockLevel;
    ORDER_STATUS_DATA
OrderStatus;
}
m_txn;

public:
    CTPCC_OLEDB(LPCSTR szServer,
LPCSTR szUser, LPCSTR szPassword, LPCSTR szHost,
LPCSTR szDatabase, LPCWSTR szSPPrefix);
    ~CTPCC_OLEDB(void);

```

```

inline PNEW_ORDER_DATA
BuffAddr_NewOrder() { return
&m_txn.NewOrder; };
inline PPAYMENT_DATA
BuffAddr_Payment() { return
&m_txn.Payment; };
inline PDELIVERY_DATA
BuffAddr_Delivery() { return
&m_txn.Delivery; };
inline PSTOCK_LEVEL_DATA
BuffAddr_StockLevel() { return
&m_txn.StockLevel; };
inline PORDER_STATUS_DATA
BuffAddr_OrderStatus() { return
&m_txn.OrderStatus; };

void NewOrder ();
void Payment ();
void Delivery ();
void StockLevel ();
void OrderStatus ();

};

// wrapper routine for class constructor
extern "C" DllDecl CTPCC_OLEDB* CTPCC_OLEDB_new
( LPCSTR szServer, LPCSTR szUser, LPCSTR
szPassword, LPCSTR szHost, LPCSTR szDatabase, LPCWSTR
szSPPrefix );

typedef CTPCC_OLEDB* (TYPE_CTPCC_OLEDB)(LPCSTR,
LPCSTR, LPCSTR, LPCSTR, LPCWSTR);

```

tpcc_com_all\resource.h

```

//{{NO_DEPENDENCIES}}
// Microsoft Developer Studio generated include file.
// Used by tpcc_com_all.rc
//
#define IDS_PROJNAME 100
#define IDR_TPCC 101
#define IDR_NEWORDER 102
#define IDR_ORDERSTATUS 103
#define IDR_PAYMENT 104
#define IDR_STOCKLEVEL 105

// Next default values for new objects
//
#ifdef APSTUDIO_INVOKED
#ifdef APSTUDIO_READONLY_SYMBOLS
#define _APS_NEXT_RESOURCE_VALUE 202
#define _APS_NEXT_COMMAND_VALUE 32768
#define _APS_NEXT_CONTROL_VALUE 201
#define _APS_NEXT_SYMED_VALUE 106
#endif
#endif

```

isapi_dll\resource.h

```

//{{NO_DEPENDENCIES}}
// Microsoft Developer Studio generated include file.
// Used by tpcc.rc
//
#define IDD_DIALOG1 101

// Next default values for new objects
//
#ifdef APSTUDIO_INVOKED
#ifdef APSTUDIO_READONLY_SYMBOLS
#define _APS_NEXT_RESOURCE_VALUE 102
#define _APS_NEXT_COMMAND_VALUE 40001
#define _APS_NEXT_CONTROL_VALUE 1000
#define _APS_NEXT_SYMED_VALUE 101
#endif
#endif

```

Appendix B: Database Design

The TPC-C database was created with the following Transact-SQL scripts:

backup.sql

```
-----  
-- File: BACKUP.SQL  
-- Microsoft TPC-C Benchmark Kit Ver. 4.61  
-- Copyright Microsoft, 2005  
-----  
  
DECLARE @startdate DATETIME,  
        @enddate DATETIME  
  
SELECT @startdate = GETDATE()  
SELECT 'Start date:',  
        CONVERT(VARCHAR(30),@startdate, 21)  
  
DUMP DATABASE tpc TO tpcback1, tpcback2, tpcback3, tpcback4 WITH init, stats =  
1  
  
SELECT @enddate = GETDATE()  
SELECT 'End date: ',  
        CONVERT(VARCHAR(30),@enddate, 21)  
SELECT 'Elapsed time (in seconds): ',  
        DATEDIFF(second, @startdate, @enddate)  
GO
```

backupdev.sql

```
-----  
-- File: BACKUPDEV.SQL  
-- Microsoft TPC-C Benchmark Kit Ver. 4.61  
-- Copyright Microsoft, 2005  
-----  
  
USE master  
GO  
  
-----  
-- create backup devices  
-----
```

```
EXEC sp_addumpdevice 'disk','tpcback1','W:\tpcback1.dmp'  
GO  
EXEC sp_addumpdevice 'disk','tpcback2','X:\tpcback2.dmp'  
GO  
EXEC sp_addumpdevice 'disk','tpcback3','Y:\tpcback3.dmp'  
GO  
EXEC sp_addumpdevice 'disk','tpcback4','Z:\tpcback4.dmp'  
GO
```

config.sql

```
-----  
-- File: CONFIG.SQL  
-- Microsoft TPC-C Benchmark Kit Ver. 4.00  
-- Copyright Microsoft, 1996  
-- Purpose: Collects SQL Server configuration parameters  
-----  
  
print " "  
select convert(char(30), getdate(),9)  
print " "  
go  
  
sp_configure "show advanced",1  
go  
reconfigure with override  
go  
  
exec sp_configure "affinity mask", 15  
exec sp_configure "cost threshold for parallelism", 5  
exec sp_configure "index create memory", 704  
exec sp_configure "lightweight pooling", 1  
exec sp_configure "awe enabled", 1  
exec sp_configure "locks", 0  
exec sp_configure "max degree of parallelism", 1  
exec sp_configure "max server memory", 2147483647  
exec sp_configure "max worker threads", 400  
exec sp_configure "min memory per query", 512  
exec sp_configure "min server memory", 0  
exec sp_configure "nested triggers", 1  
exec sp_configure "network packet size", 2048  
exec sp_configure "open objects", 0  
exec sp_configure "priority boost", 1  
exec sp_configure "recovery interval", 32767  
exec sp_configure "set working set size", 0  
exec sp_configure "user connections", 0  
  
go  
  
reconfigure with override  
go  
sp_configure  
go
```

createdb.sql

```
-----  
-- File: CREATEDDB.SQL  
-- Microsoft TPC-C Benchmark Kit Ver. 4.61  
-- Copyright Microsoft, 2005  
-----
```

```

--
-----
SET ANSI_NULL_DFLT_OFF ON
GO

USE master
GO

-----
-- Create temporary table for timing
-----
IF EXISTS( SELECT name FROM sysobjects WHERE name = 'tpcc_timer' )
  DROP TABLE tpcc_timer
GO

CREATE TABLE tpcc_timer
      (start_date  CHAR(30),
       end_date    CHAR(30))
GO

INSERT INTO tpcc_timer VALUES(0,0)
GO

-----
-- Store starting time
-----
UPDATE tpcc_timer
SET start_date = (SELECT CONVERT(CHAR(30), GETDATE(), 21))
GO

-----
-- create main database files
-----
CREATE DATABASE tpcc
ON PRIMARY
(
    NAME = MSSQL_tpcc_root,
    FILENAME = 'c:\MSSQL_tpcc_root.mdf',
    SIZE = 8MB,
    FILEGROWTH = 0),

FILEGROUP MSSQL_cs_fg
(
    NAME = MSSQL_cs1,
    FILENAME = 'c:\cs\cs1\',
    SIZE = 74000MB,
    FILEGROWTH = 0),
(
    NAME = MSSQL_cs2,
    FILENAME = 'c:\cs\cs2\',
    SIZE = 74000MB,
    FILEGROWTH = 0),
(
    NAME = MSSQL_cs3,
    FILENAME = 'c:\cs\cs3\',
    SIZE = 74000MB,
    FILEGROWTH = 0),
(
    NAME = MSSQL_cs4,
    FILENAME = 'c:\cs\cs4\',
    SIZE = 74000MB,
    FILEGROWTH = 0),
(
    NAME = MSSQL_cs5,
    FILENAME = 'c:\cs\cs5\',
    SIZE = 74000MB,
    FILEGROWTH = 0),
(
    NAME = MSSQL_cs6,

```

```

    FILENAME = 'c:\cs\cs6\',
    SIZE = 74000MB,
    FILEGROWTH = 0),
(
    NAME = MSSQL_cs7,
    FILENAME = 'c:\cs\cs7\',
    SIZE = 74000MB,
    FILEGROWTH = 0),
(
    NAME = MSSQL_cs8,
    FILENAME = 'c:\cs\cs8\',
    SIZE = 74000MB,
    FILEGROWTH = 0),
(
    NAME = MSSQL_cs9,
    FILENAME = 'c:\cs\cs9\',
    SIZE = 74000MB,
    FILEGROWTH = 0),
(
    NAME = MSSQL_cs10,
    FILENAME = 'c:\cs\cs10\',
    SIZE = 74000MB,
    FILEGROWTH = 0),
(
    NAME = MSSQL_cs11,
    FILENAME = 'c:\cs\cs11\',
    SIZE = 74000MB,
    FILEGROWTH = 0),
(
    NAME = MSSQL_cs12,
    FILENAME = 'c:\cs\cs12\',
    SIZE = 74000MB,
    FILEGROWTH = 0),
(
    NAME = MSSQL_cs13,
    FILENAME = 'c:\cs\cs13\',
    SIZE = 74000MB,
    FILEGROWTH = 0),
(
    NAME = MSSQL_cs14,
    FILENAME = 'c:\cs\cs14\',
    SIZE = 74000MB,
    FILEGROWTH = 0),

FILEGROUP MSSQL_misc_fg
(
    NAME = MSSQL_misc1,
    FILENAME = 'c:\misc\misc1\',
    SIZE = 39500MB,
    FILEGROWTH = 0),
(
    NAME = MSSQL_misc2,
    FILENAME = 'c:\misc\misc2\',
    SIZE = 39500MB,
    FILEGROWTH = 0),
(
    NAME = MSSQL_misc3,
    FILENAME = 'c:\misc\misc3\',
    SIZE = 39500MB,
    FILEGROWTH = 0),
(
    NAME = MSSQL_misc4,
    FILENAME = 'c:\misc\misc4\',
    SIZE = 39500MB,
    FILEGROWTH = 0),
(
    NAME = MSSQL_misc5,
    FILENAME = 'c:\misc\misc5\',
    SIZE = 39500MB,
    FILEGROWTH = 0),
(
    NAME = MSSQL_misc6,
    FILENAME = 'c:\misc\misc6\',
    SIZE = 39500MB,
    FILEGROWTH = 0),
(
    NAME = MSSQL_misc7,
    FILENAME = 'c:\misc\misc7\',

```

```

        SIZE                = 39500MB,
        FILEGROWTH          = 0),
        NAME                = MSSQL_misc8,
        FILENAME = 'c:\misc\misc8\',
        SIZE                = 39500MB,
        FILEGROWTH          = 0),
        NAME                = MSSQL_misc9,
        FILENAME = 'c:\misc\misc9\',
        SIZE                = 39500MB,
        FILEGROWTH          = 0),
        NAME                = MSSQL_misc10,
        FILENAME = 'c:\misc\misc10\',
        SIZE                = 39500MB,
        FILEGROWTH          = 0),
        NAME                = MSSQL_misc11,
        FILENAME = 'c:\misc\misc11\',
        SIZE                = 39500MB,
        FILEGROWTH          = 0),
        NAME                = MSSQL_misc12,
        FILENAME = 'c:\misc\misc12\',
        SIZE                = 39500MB,
        FILEGROWTH          = 0),
        NAME                = MSSQL_misc13,
        FILENAME = 'c:\misc\misc13\',
        SIZE                = 39500MB,
        FILEGROWTH          = 0),
        NAME                = MSSQL_misc14,
        FILENAME = 'c:\misc\misc14\',
        SIZE                = 39500MB,
        FILEGROWTH          = 0)
LOG ON
(
    NAME                = MSSQL_tpcc_log,
    FILENAME = 'E:',
    SIZE                = 701000MB,
    FILEGROWTH          = 0)
COLLATE Latin1_General_BIN
GO

-----
-- Store ending time
-----
UPDATE tpcc_timer
SET end_date = (SELECT CONVERT(CHAR(30), GETDATE(), 21))
GO

SELECT DATEDIFF(second, (SELECT start_date FROM tpcc_timer), (SELECT end_date FROM
tpcc_timer))
GO

-----
-- remove temporary table
-----
IF EXISTS ( SELECT name FROM sysobjects WHERE name = 'tpcc_timer' )
DROP TABLE tpcc_timer
GO

```

dbopt1.sql

```

-----
--
-- File:  DBOPT1.SQL
-- Microsoft TPC-C Benchmark Kit Ver. 4.62
--

```

```

-- Copyright Microsoft, 2005
--
-- Sets database options for load
--
-----
USE master
GO

ALTER DATABASE tpcc SET RECOVERY BULK_LOGGED
GO

EXEC sp_dboption tpcc, 'trunc. log on chkpt.', TRUE
GO

ALTER DATABASE tpcc SET TORN_PAGE_DETECTION OFF
GO

ALTER DATABASE tpcc SET PAGE_VERIFY NONE
GO

USE tpcc
GO

CHECKPOINT
GO

```

dbopt2.sql

```

-----
--
-- File:  DBOPT2.SQL
-- Microsoft TPC-C Benchmark Kit Ver. 4.62
-- Copyright Microsoft, 2005
--
-- Sets database options after load
--
-----
ALTER DATABASE tpcc SET RECOVERY FULL
GO

USE tpcc
GO

CHECKPOINT
GO

sp_configure 'allow updates', 1
GO

RECONFIGURE WITH OVERRIDE
GO

DECLARE @msg          varchar(50)

-----
-- OPTIONS FOR SQL SERVER 2000
-- Set option values for user-defined indexes
-----

SET @msg = ' '
PRINT @msg
SET @msg = 'Setting SQL Server indexoptions'

```

```

PRINT @msg
SET @msg = ' '
PRINT @msg

EXEC sp_indexopton 'customer', 'DisallowPageLocks', TRUE
EXEC sp_indexopton 'district', 'DisallowPageLocks', TRUE
EXEC sp_indexopton 'warehouse', 'DisallowPageLocks', TRUE
EXEC sp_indexopton 'stock', 'DisallowPageLocks', TRUE
EXEC sp_indexopton 'order_line', 'DisallowRowLocks', TRUE
EXEC sp_indexopton 'orders', 'DisallowRowLocks', TRUE
EXEC sp_indexopton 'new_order', 'DisallowRowLocks', TRUE
EXEC sp_indexopton 'item', 'DisallowRowLocks', TRUE
EXEC sp_indexopton 'item', 'DisallowPageLocks', FALSE
GO

Print ' '
Print '*****'
Print 'Pre-specified Locking Hierarchy:'
Print ' Lockflag = 0 ==> No pre-specified hierarchy'
Print ' Lockflag = 1 ==> Lock at Page-level then Table-level'
Print ' Lockflag = 2 ==> Lock at Row-level then Table-level'
Print ' Lockflag = 3 ==> Lock at Table-level'
Print ' '

SELECT name,
lockflags
FROM sysindexes
WHERE object_id('warehouse') = id OR
object_id('district') = id OR
object_id('customer') = id OR
object_id('stock') = id OR
object_id('orders') = id OR
object_id('order_line') = id OR
object_id('history') = id OR
object_id('new_order') = id OR
object_id('item') = id

ORDER BY lockflags asc
GO

sp_configure 'allow updates',0
GO

RECONFIGURE WITH OVERRIDE
GO

EXEC sp_dboption tpcc, 'auto update statistics', FALSE
EXEC sp_dboption tpcc, 'auto create statistics', FALSE
GO

DECLARE @db_id int,
@tbl_id int

SET @db_id = DB_ID('tpcc')
SET @tbl_id = OBJECT_ID('tpcc..warehouse')
DBCC PINTABLE (@db_id, @tbl_id)

SET @tbl_id = OBJECT_ID('tpcc..district')
DBCC PINTABLE (@db_id, @tbl_id)

SET @tbl_id = OBJECT_ID('tpcc..new_order')
DBCC PINTABLE (@db_id, @tbl_id)

SET @tbl_id = OBJECT_ID('tpcc..item')

```

```

DBCC PINTABLE (@db_id, @tbl_id)
GO

```

delivery.sql

```

-----
-- File: DELIVERY.SQL
-- Microsoft TPC-C Benchmark Kit Ver. 4.62
-- Copyright Microsoft, 2005
--
-- Creates delivery stored procedure
--
-- Interface Level: 4.20.000
-----

SET QUOTED_IDENTIFIER OFF
GO

SET ANSI_NULLS ON
GO

USE tpcc
GO

IF EXISTS ( SELECT name FROM sysobjects WHERE name = 'tpcc_delivery' )
DROP PROCEDURE tpcc_delivery
GO

CREATE PROC tpcc_delivery
@w_id int,
@o_carrier_id smallint

AS
DECLARE @d_id tinyint,
@o_id int,
@c_id int,
@total money,
@oid1 int,
@oid2 int,
@oid3 int,
@oid4 int,
@oid5 int,
@oid6 int,
@oid7 int,
@oid8 int,
@oid9 int,
@oid10 int

SELECT @d_id = 0

BEGIN TRANSACTION d
WHILE (@d_id < 10)
BEGIN
SELECT @d_id = @d_id + 1,
@total = 0,
@o_id = 0

SELECT TOP 1
@o_id = no_o_id
FROM new_order WITH (serializable uplock)

```

```

WHERE no_w_id = @w_id AND
      no_d_id = @d_id
ORDER BY no_o_id ASC

IF (@@rowcount <> 0)
BEGIN
  -- claim the order for this district
  DELETE new_order
  WHERE no_w_id = @w_id AND
        no_d_id = @d_id AND
        no_o_id = @o_id

  -- set carrier_id on this order (and get customer id)
  UPDATE orders
  SET o_carrier_id = @o_carrier_id,
      @c_id = o_c_id
  WHERE o_w_id = @w_id AND
        o_d_id = @d_id AND
        o_id = @o_id

  -- set date in all lineitems for this order (and sum amounts)
  UPDATE order_line
  SET ol_delivery_d = GETDATE(),
      @total = @total + ol_amount
  WHERE ol_w_id = @w_id AND
        ol_d_id = @d_id AND
        ol_o_id = @o_id

  -- accumulate lineitem amounts for this order into customer
  UPDATE customer
  SET c_balance = c_balance + @total,
      c_delivery_cnt = c_delivery_cnt + 1
  WHERE c_w_id = @w_id AND
        c_d_id = @d_id AND
        c_id = @c_id
END

SELECT @oid1 = CASE @d_id WHEN 1 THEN @o_id ELSE @oid1 END,
       @oid2 = CASE @d_id WHEN 2 THEN @o_id ELSE @oid2 END,
       @oid3 = CASE @d_id WHEN 3 THEN @o_id ELSE @oid3 END,
       @oid4 = CASE @d_id WHEN 4 THEN @o_id ELSE @oid4 END,
       @oid5 = CASE @d_id WHEN 5 THEN @o_id ELSE @oid5 END,
       @oid6 = CASE @d_id WHEN 6 THEN @o_id ELSE @oid6 END,
       @oid7 = CASE @d_id WHEN 7 THEN @o_id ELSE @oid7 END,
       @oid8 = CASE @d_id WHEN 8 THEN @o_id ELSE @oid8 END,
       @oid9 = CASE @d_id WHEN 9 THEN @o_id ELSE @oid9 END,
       @oid10 = CASE @d_id WHEN 10 THEN @o_id ELSE @oid10 END

END

COMMIT TRANSACTION d

-- return delivery data to client

SELECT @oid1,
       @oid2,
       @oid3,
       @oid4,
       @oid5,
       @oid6,
       @oid7,
       @oid8,
       @oid9,
       @oid10

```

```

GO

SET QUOTED_IDENTIFIER OFF
GO

SET ANSI_NULLS ON
GO



---


getargs.c


---


// File: GETARGS.C
// Microsoft TPC-C Kit Ver. 4.51
// Copyright Microsoft, 1996, 1997, 1998, 1999,
2000, 2001, 2002, 2003
// Purpose: Source file for command line processing

// Includes
#include "tpcc.h"

//=====
// Function name: GetArgsLoader
//=====

void GetArgsLoader(int argc, char **argv, TPCCCLR_ARGS *pargs)
{
  int i;
  char *ptr;

#ifdef DEBUG
  printf("[%d]DBG: Entering GetArgsLoader()\n", (int) GetCurrentThreadId());
#endif

  /* init args struct with some useful values */
  pargs->server = SERVER;
  pargs->user = USER;
  pargs->password = PASSWORD;
  pargs->database = DATABASE;
  pargs->batch = BATCH;
  pargs->num_warehouses = UNDEF;
  pargs->tables_all = TRUE;
  pargs->table_item = FALSE;
  pargs->table_warehouse = FALSE;
  pargs->table_customer = FALSE;
  pargs->table_orders = FALSE;
  pargs->loader_res_file = LOADER_RES_FILE;
  pargs->log_path = LOADER_LOG_PATH;
  pargs->pack_size = DEFLDPACKSIZE;
  pargs->starting_warehouse = DEF_STARTING_WAREHOUSE;
  pargs->build_index = BUILD_INDEX;
  pargs->index_order = INDEX_ORDER;
  pargs->index_script_path = INDEX_SCRIPT_PATH;
  pargs->scale_down = SCALE_DOWN;

  /* check for zero command line args */
  if ( argc == 1 )
    GetArgsLoaderUsage();

  for ( i = 1; i < argc; ++i)
  {

```

```

if (argv[i][0] != '-' && argv[i][0] != '/')
{
printf("\nUnrecognized command");
GetArgsLoaderUsage();
exit(1);
}

ptr = argv[i];

switch (ptr[1])
{
case '?': /* Fall through */
GetArgsLoaderUsage();
break;

case 'D':
pargs->database = ptr+2;
break;

case 'P':
pargs->password = ptr+2;
break;

case 'S':
pargs->server = ptr+2;
break;

case 'U':
pargs->user = ptr+2;
break;

case 'b':
pargs->batch = atol(ptr+2);
break;

case 'W':
pargs->num_warehouses = atol(ptr+2);
break;

case 's':
pargs->starting_warehouse = atol(ptr+2);
break;

case 't':
{
pargs->tables_all = FALSE;
if (strcmp(ptr+2,"item") == 0)
pargs->table_item =

TRUE;
== 0)
pargs->table_warehouse =

TRUE;
== 0)
pargs->table_customer =

TRUE;
0)
pargs->table_orders =

TRUE;
else
{

```

```

printf("\nUnrecognized command");
GetArgsLoaderUsage();
exit(1);
}

break;
}

case 'f':
pargs->loader_res_file = ptr+2;
break;

case 'L':
pargs->log_path = ptr+2;
break;

case 'p':
pargs->pack_size = atol(ptr+2);
break;

case 'i':
pargs->build_index = atol(ptr+2);
break;

case 'o':
pargs->index_order = atol(ptr+2);
break;

case 'c':
pargs->scale_down = atol(ptr+2);
break;

case 'd':
pargs->index_script_path = ptr+2;
break;

default:
GetArgsLoaderUsage();
exit(-1);
break;
}

}

/* check for required args */
if (pargs->num_warehouses == UNDEF )
{
printf("Number of Warehouses is required\n");
exit(-2);
}

return;
}

//=====
//
// Function name: GetArgsLoaderUsage
//
//=====

void GetArgsLoaderUsage()
{

```



```

#ifdef DEBUG
    printf("[%ld]DBG: Entering GetArgsLoaderUsage()\n", (int) GetCurrentThreadId());
#endif

    printf("TPCCLDR:\n\n");
    printf("Parameter                                     Default\n");
    printf("-----");
\n");
    printf("-W Number of Warehouses to Load                Required \n");
    printf("-S Server                                           %s\n", SERVER);
    printf("-U Username                                           %s\n", USER);
    printf("-P Password                                           %s\n", PASSWORD);
    printf("-D Database                                           %s\n", DATABASE);
    printf("  -b Batch Size                                     %ld\n",
(long) BATCH);
    printf("  -p TDS packet size                               %ld\n",
(long) DEF_LDPACKSIZE);
    printf("  -L Loader BCP Log Path                           %s\n",
LOADER_LOG_PATH);
    printf("  -f Loader Results Output Filename                %s\n",
LOADER_RES_FILE);
    printf("  -s Starting Warehouse                           %ld\n",
(long) DEF_STARTING_WAREHOUSE);
    printf("  -i Build Option (data = 0, data and index = 1)   %ld\n",
(long) BUILD_INDEX);
    printf("  -o Cluster Index Build Order (before = 1, after = 0) %ld\n",
(long) INDEX_ORDER);
    printf("  -c Build Scaled Database (normal = 0, tiny = 1)  %ld\n",
(long) SCALE_DOWN);
    printf("  -d Index Script Path                             %s\n",
INDEX_SCRIPT_PATH);
    printf("  -t Table to Load                                 all tables
\n");
    printf("    [item|warehouse|customer|orders]\n");
    printf("    Notes: \n");
    printf("    - the '-t' parameter may be included multiple times to \n");
    printf("    - specify multiple tables to be loaded \n");
    printf("    - 'item' loads ITEM table \n");
    printf("    - 'warehouse' loads WAREHOUSE, DISTRICT, and STOCK tables \n");
    printf("    - 'customer' loads CUSTOMER and HISTORY tables \n");
    printf("    - 'orders' load NEW-ORDER, ORDERS, ORDER-LINE tables \n");

    printf("\nNote: Command line switches are case sensitive.\n");

    exit(0);
}

```

idxcuscl.sql

```

-----
-- File:      IDXCUSCL.SQL
-- Microsoft TPC-C Benchmark Kit Ver. 4.62
-- Copyright Microsoft, 2005
--
-- Creates clustered index on customer table
-----
USE tpcc
GO

```

```

DECLARE @startdate DATETIME,
        @enddate   DATETIME

SELECT @startdate = GETDATE()
SELECT 'Start date:',
       CONVERT(VARCHAR(30),@startdate,21)

IF EXISTS ( SELECT name FROM sysindexes WHERE name = 'customer_c1' )
    DROP INDEX customer.customer_c1

CREATE UNIQUE CLUSTERED INDEX customer_c1 ON customer(c_w_id, c_d_id, c_id)
ON MSSQL_cs_fg

SELECT @enddate = GETDATE()
SELECT 'End date:',
       CONVERT(VARCHAR(30),@enddate,21)
SELECT 'Elapsed time (in seconds): ',
       DATEDIFF(second, @startdate, @enddate)
GO

-----
-- File:      IDXCUSNC.SQL
-- Microsoft TPC-C Benchmark Kit Ver. 4.62
-- Copyright Microsoft, 2005
--
-- Creates non-clustered index on customer table
-----
USE tpcc
GO

DECLARE @startdate DATETIME,
        @enddate   DATETIME

SELECT @startdate = GETDATE()
SELECT 'Start date:',
       CONVERT(VARCHAR(30),@startdate,21)

IF EXISTS ( SELECT name FROM sysindexes WHERE name = 'customer_nc1' )
    DROP INDEX customer.customer_nc1

CREATE UNIQUE NONCLUSTERED INDEX customer_nc1 ON customer(c_w_id, c_d_id, c_last,
c_first, c_id)
ON MSSQL_cs_fg

SELECT @enddate = GETDATE()
SELECT 'End date:',
       CONVERT(VARCHAR(30),@enddate,21)
SELECT 'Elapsed time (in seconds): ',
       DATEDIFF(second, @startdate, @enddate)
GO

-----
-- File:      IDXDISCL.SQL
-- Microsoft TPC-C Benchmark Kit Ver. 4.62

```

idxdiscl.sql

```

--          Copyright Microsoft, 2005          --
--          Creates clustered index on district table          --
-----
USE tpcc
GO

DECLARE @startdate DATETIME,
        @enddate DATETIME

SELECT @startdate = GETDATE()
SELECT 'Start date:',
       CONVERT(VARCHAR(30),@startdate,21)

IF EXISTS ( SELECT name FROM sysindexes WHERE name = 'district_c1' )
  DROP INDEX district.district_c1

CREATE UNIQUE CLUSTERED INDEX district_c1 ON district(d_w_id, d_id)
  WITH FILLFACTOR=100 ON MSSQL_misc_fg

SELECT @enddate = GETDATE()
SELECT 'End date:',
       CONVERT(VARCHAR(30),@enddate,21)
SELECT 'Elapsed time (in seconds): ',
       DATEDIFF(second, @startdate, @enddate)
GO

```

idxhiscl.sql

```

--          File:  IDXHISCL.SQL          --
--          Microsoft TPC-C Benchmark Kit Ver. 4.62          --
--          Copyright Microsoft, 2005          --
--          Creates clustered index on history table          --
--          CAUTION: This index is only beneficial for systems --
--          CAUTION: with 8 or more processors.          --
--          CAUTION: It may negatively impact performance on --
--          CAUTION: systems with less than 8 processors.    --
-----
USE tpcc
GO

DECLARE @startdate DATETIME,
        @enddate DATETIME

SELECT @startdate = GETDATE()
SELECT 'Start date:',
       CONVERT(VARCHAR(30),@startdate,21)

IF EXISTS ( SELECT name FROM sysindexes WHERE name = 'history_c1' )
  DROP INDEX history.history_c1

CREATE UNIQUE CLUSTERED INDEX history_c1 ON history(h_c_w_id, h_date, h_c_d_id,
  h_c_id, h_amount)
  ON MSSQL_misc_fg

SELECT @enddate = GETDATE()
SELECT 'End date:',

```

```

CONVERT(VARCHAR(30),@enddate,21)
SELECT 'Elapsed time (in seconds): ',
       DATEDIFF(second, @startdate, @enddate)
GO

```

idxitmcl.sql

```

--          File:  IDXITMCL.SQL          --
--          Microsoft TPC-C Benchmark Kit Ver. 4.62          --
--          Copyright Microsoft, 2005          --
--          Creates clustered index on item table          --
-----
USE tpcc
GO

DECLARE @startdate DATETIME,
        @enddate DATETIME

SELECT @startdate = GETDATE()
SELECT 'Start date:',
       CONVERT(VARCHAR(30),@startdate,21)

IF EXISTS ( SELECT name FROM sysindexes WHERE name = 'item_c1' )
  DROP INDEX item.item_c1

CREATE UNIQUE CLUSTERED INDEX item_c1 ON item(i_id)
  ON MSSQL_misc_fg

SELECT @enddate = GETDATE()
SELECT 'End date:',
       CONVERT(VARCHAR(30),@enddate,21)
SELECT 'Elapsed time (in seconds): ',
       DATEDIFF(second, @startdate, @enddate)
GO

```

idxnodcl.sql

```

--          File:  IDXNODCL.SQL          --
--          Microsoft TPC-C Benchmark Kit Ver. 4.62          --
--          Copyright Microsoft, 2005          --
--          Creates clustered index on new-order table          --
-----
USE tpcc
GO

DECLARE @startdate DATETIME,
        @enddate DATETIME

SELECT @startdate = GETDATE()
SELECT 'Start date:',
       CONVERT(VARCHAR(30),@startdate,21)

IF EXISTS ( SELECT name FROM sysindexes WHERE name = 'new_order_c1' )

```

```

DROP INDEX new_order.new_order_c1

CREATE UNIQUE CLUSTERED INDEX new_order_c1 ON new_order(no_w_id, no_d_id, no_o_id)

ON MSSQL_misc_fg

SELECT @enddate = GETDATE()
SELECT 'End date:',
CONVERT(VARCHAR(30),@enddate,21)
SELECT 'Elapsed time (in seconds): ',
DATEDIFF(second, @startdate, @enddate)
GO

```

idxodlcl.sql

```

-----
-- File:      IDXODLCL.SQL
-- Microsoft TPC-C Benchmark Kit Ver. 4.62
-- Copyright Microsoft, 2005
--
-- Creates clustered index on order-line table
-----
USE tpcc
GO

DECLARE @startdate DATETIME,
        @enddate   DATETIME

SELECT @startdate = GETDATE()
SELECT 'Start date:',
CONVERT(VARCHAR(30),@startdate,21)

IF EXISTS ( SELECT name FROM sysindexes WHERE name = 'order_line_c1' )
    DROP INDEX order_line.order_line_c1

CREATE UNIQUE CLUSTERED INDEX order_line_c1 ON order_line(ol_w_id, ol_d_id, ol_o_id,
ol_number)
ON MSSQL_misc_fg

SELECT @enddate = GETDATE()
SELECT 'End date:',
CONVERT(VARCHAR(30),@enddate,21)
SELECT 'Elapsed time (in seconds): ',
DATEDIFF(second, @startdate, @enddate)
GO

```

idxordcl.sql

```

-----
-- File:      IDXORDCL.SQL
-- Microsoft TPC-C Benchmark Kit Ver. 4.62
-- Copyright Microsoft, 2005
--
-- Creates clustered index on orders table
-----
USE tpcc
GO

```

```

DECLARE @startdate DATETIME,
        @enddate   DATETIME

SELECT @startdate = GETDATE()
SELECT 'Start date:',
CONVERT(VARCHAR(30),@startdate,21)

IF EXISTS ( SELECT name FROM sysindexes WHERE name = 'orders_c1' )
    DROP INDEX orders.orders_c1

CREATE UNIQUE CLUSTERED INDEX orders_c1 ON orders(o_w_id, o_d_id, o_id)
ON MSSQL_misc_fg

SELECT @enddate = GETDATE()
SELECT 'End date:',
CONVERT(VARCHAR(30),@enddate,21)
SELECT 'Elapsed time (in seconds): ',
DATEDIFF(second, @startdate, @enddate)
GO

```

idxstkcl.sql

```

-----
-- File:      IDXSTKCL.SQL
-- Microsoft TPC-C Benchmark Kit Ver. 4.62
-- Copyright Microsoft, 2005
--
-- Creates clustered index on stock table
-----
USE tpcc
GO

DECLARE @startdate DATETIME,
        @enddate   DATETIME

SELECT @startdate = GETDATE()
SELECT 'Start date:',
CONVERT(VARCHAR(30),@startdate,21)

IF EXISTS ( SELECT name FROM sysindexes WHERE name = 'stock_c1' )
    DROP INDEX stock.stock_c1

CREATE UNIQUE CLUSTERED INDEX stock_c1 ON stock(s_i_id, s_w_id)
ON MSSQL_cs_fg

SELECT @enddate = GETDATE()
SELECT 'End date:',
CONVERT(VARCHAR(30),@enddate,21)
SELECT 'Elapsed time (in seconds): ',
DATEDIFF(second, @startdate, @enddate)
GO

```

idxwarcl.sql

```

-----
-- File:      IDXWARCL.SQL
-- Microsoft TPC-C Benchmark Kit Ver. 4.62
-----

```

```

--      Copyright Microsoft, 2005      --
--      --
--      Creates clustered index on warehouse table
--      --
-----
USE tpcc
GO

DECLARE @startdate DATETIME,
        @enddate DATETIME

SELECT @startdate = GETDATE()
SELECT 'Start date:',
       CONVERT(VARCHAR(30),@startdate,21)

IF EXISTS ( SELECT name FROM sysindexes WHERE name = 'warehouse_cl' )
  DROP INDEX warehouse.warehouse_cl

CREATE UNIQUE CLUSTERED INDEX warehouse_cl ON warehouse(w_id)
  WITH FILLFACTOR=100 ON MSSQL_misc_fg

SELECT @enddate = GETDATE()
SELECT 'End date:',
       CONVERT(VARCHAR(30),@enddate,21)
SELECT 'Elapsed time (in seconds): ',
       DATEDIFF(second, @startdate, @enddate)
GO

```

neword.sql

```

--      --
--      File:      NEWORD.SQL
--      Microsoft TPC-C Benchmark Kit Ver. 4.62
--      Copyright Microsoft, 2005
--      --
--      Creates neworder stored procedure
--      --
--      Interface Level:      4.20.000
--      --
-----
SET QUOTED_IDENTIFIER OFF
GO

SET ANSI_NULLS ON
GO

USE tpcc
GO

IF EXISTS ( SELECT name FROM sysobjects WHERE name = 'tpcc_neworder' )
  DROP PROCEDURE tpcc_neworder
GO

CREATE PROCEDURE      tpcc_neworder
        @w_id          int,
        @d_id          tinyint,
        @c_id          int,
        @o_ol_cnt      tinyint,
        @o_all_local   tinyint,
        @i_id1 int = 0, @s_w_id1 int = 0, @ol_qty1 smallint = 0,
        @i_id2 int = 0, @s_w_id2 int = 0, @ol_qty2 smallint = 0,

```

```

        @i_id3 int = 0, @s_w_id3 int = 0, @ol_qty3 smallint = 0,
        @i_id4 int = 0, @s_w_id4 int = 0, @ol_qty4 smallint = 0,
        @i_id5 int = 0, @s_w_id5 int = 0, @ol_qty5 smallint = 0,
        @i_id6 int = 0, @s_w_id6 int = 0, @ol_qty6 smallint = 0,
        @i_id7 int = 0, @s_w_id7 int = 0, @ol_qty7 smallint = 0,
        @i_id8 int = 0, @s_w_id8 int = 0, @ol_qty8 smallint = 0,
        @i_id9 int = 0, @s_w_id9 int = 0, @ol_qty9 smallint = 0,
        @i_id10 int = 0, @s_w_id10 int = 0, @ol_qty10 smallint = 0,
        @i_id11 int = 0, @s_w_id11 int = 0, @ol_qty11 smallint = 0,
        @i_id12 int = 0, @s_w_id12 int = 0, @ol_qty12 smallint = 0,
        @i_id13 int = 0, @s_w_id13 int = 0, @ol_qty13 smallint = 0,
        @i_id14 int = 0, @s_w_id14 int = 0, @ol_qty14 smallint = 0,
        @i_id15 int = 0, @s_w_id15 int = 0, @ol_qty15 smallint = 0

```

```

AS
DECLARE @w_tax          smallmoney,
        @d_tax          smallmoney,
        @c_last         char(16),
        @c_credit       char(2),
        @c_discount     smallmoney,
        @i_price        smallmoney,
        @i_name         char(24),
        @i_data         char(50),
        @o_entry_d      datetime,
        @remote_flag    int,
        @s_quantity     smallint,
        @s_data         char(50),
        @s_dist         char(24),
        @li_no          int,
        @o_id           int,
        @commit_flag    tinyint,
        @li_id          int,
        @li_s_w_id      int,
        @li_qty         smallint,
        @ol_number      int,
        @c_id_local     int

BEGIN

BEGIN TRANSACTION n

-----
-- get district tax and next available order id and update
-- plus initialize local variables
-----
UPDATE district
SET      @d_tax          = d_tax,
        @o_id           = d_next_o_id,
        d_next_o_id     = d_next_o_id + 1,
        @o_entry_d      = GETDATE(),
        @li_no          = 0,
        @commit_flag    = 1
WHERE    d_w_id         = @w_id AND
        d_id            = @d_id

-----
-- process orderlines
-----
WHILE (@li_no < @o_ol_cnt)
BEGIN
  SELECT @li_no = @li_no + 1

```

```

-----
-- set i_id, s_w_id, and qty for this lineitem
-----
SELECT  @li_id = CASE @li_no
        WHEN 1 THEN @i_id1
        WHEN 2 THEN @i_id2
        WHEN 3 THEN @i_id3
        WHEN 4 THEN @i_id4
        WHEN 5 THEN @i_id5
        WHEN 6 THEN @i_id6
        WHEN 7 THEN @i_id7
        WHEN 8 THEN @i_id8
        WHEN 9 THEN @i_id9
        WHEN 10 THEN @i_id10
        WHEN 11 THEN @i_id11
        WHEN 12 THEN @i_id12
        WHEN 13 THEN @i_id13
        WHEN 14 THEN @i_id14
        WHEN 15 THEN @i_id15
END,

@li_s_w_id = CASE @li_no
        WHEN 1 THEN @s_w_id1
        WHEN 2 THEN @s_w_id2
        WHEN 3 THEN @s_w_id3
        WHEN 4 THEN @s_w_id4
        WHEN 5 THEN @s_w_id5
        WHEN 6 THEN @s_w_id6
        WHEN 7 THEN @s_w_id7
        WHEN 8 THEN @s_w_id8
        WHEN 9 THEN @s_w_id9
        WHEN 10 THEN @s_w_id10
        WHEN 11 THEN @s_w_id11
        WHEN 12 THEN @s_w_id12
        WHEN 13 THEN @s_w_id13
        WHEN 14 THEN @s_w_id14
        WHEN 15 THEN @s_w_id15
END,

@li_qty = CASE @li_no
        WHEN 1 THEN @ol_qty1
        WHEN 2 THEN @ol_qty2
        WHEN 3 THEN @ol_qty3
        WHEN 4 THEN @ol_qty4
        WHEN 5 THEN @ol_qty5
        WHEN 6 THEN @ol_qty6
        WHEN 7 THEN @ol_qty7
        WHEN 8 THEN @ol_qty8
        WHEN 9 THEN @ol_qty9
        WHEN 10 THEN @ol_qty10
        WHEN 11 THEN @ol_qty11
        WHEN 12 THEN @ol_qty12
        WHEN 13 THEN @ol_qty13
        WHEN 14 THEN @ol_qty14
        WHEN 15 THEN @ol_qty15
END

-----
-- get item data (no one updates item)
-----
SELECT  @i_price = i_price,
        @i_name = i_name,
        @i_data = i_data

```

```

        FROM item WITH (repeatableread)
        WHERE i_id = @li_id

-----
-- update stock values
-----
UPDATE stock
SET s_ytd = s_ytd + @li_qty,
    @s_quantity = s_quantity - @li_qty +
        CASE WHEN (s_quantity - @li_qty < 10) THEN 91
ELSE 0 END,
    s_order_cnt = s_order_cnt + 1,
    s_remote_cnt = s_remote_cnt +
        CASE WHEN (@li_s_w_id = @w_id) THEN 0 ELSE 1
END,
    @s_data = s_data,
    @s_dist = CASE @d_id
        WHEN 1 THEN s_dist_01
        WHEN 2 THEN s_dist_02
        WHEN 3 THEN s_dist_03
        WHEN 4 THEN s_dist_04
        WHEN 5 THEN s_dist_05
        WHEN 6 THEN s_dist_06
        WHEN 7 THEN s_dist_07
        WHEN 8 THEN s_dist_08
        WHEN 9 THEN s_dist_09
        WHEN 10 THEN s_dist_10
    END
WHERE s_i_id = @li_id AND
    s_w_id = @li_s_w_id

-----
-- if there actually is a stock (and item) with these ids, go to work
-----
IF (@@rowcount > 0)
BEGIN
-----
-- insert order_line data (using data from item and stock)
-----
INSERT INTO order_line VALUES( @o_id,
                                @d_id,
                                @w_id,
                                @li_no,
                                @li_id,
                                'dec 31, 1899',
                                @i_price * @li_qty,
                                @li_s_w_id,
                                @li_qty,
                                @s_dist)

-----
-- send line-item data to client
-----
SELECT  @i_name,
        @s_quantity,
        b_g = CASE WHEN ( (patindex('%ORIGINAL%',@i_data) > 0) AND
        (patindex('%ORIGINAL%',@s_data) > 0) )
        THEN 'B' ELSE 'G' END,
        @i_price,
        @i_price * @li_qty
END
ELSE

```

```

                BEGIN
-----
-- no item (or stock) found - triggers rollback condition
-----
        SELECT  '',0, '',0,0
        SELECT  @commit_flag = 0
        END
    END
-----
-- get customer last name, discount, and credit rating
-----
    SELECT  @c_last = c_last,
            @c_discount = c_discount,
            @c_credit = c_credit,
            @c_id_local = c_id
    FROM    customer WITH (repeatableread)
    WHERE   c_id = @c_id AND
            c_w_id = @w_id AND
            c_d_id = @d_id
-----
-- insert fresh row into orders table
-----
    INSERT INTO orders VALUES ( @o_id,
                                @d_id,
                                @w_id,
                                @c_id_local,
                                0,
                                @o_ol_cnt,
                                @o_all_local,
                                @o_entry_d)
-----
-- insert corresponding row into new-order table
-----
    INSERT INTO new_order VALUES ( @o_id,
                                    @d_id,
                                    @w_id)
-----
-- select warehouse tax
-----
    SELECT  @w_tax = w_tax
    FROM    warehouse WITH (repeatableread)
    WHERE   w_id = @w_id

    IF (@commit_flag = 1)
        COMMIT TRANSACTION n
    ELSE
-----
-- all that work for nuthin!!!
-----
        ROLLBACK TRANSACTION n
-----
-- return order data to client
-----
    SELECT  @w_tax,
            @d_tax,
            @o_id,
            @c_last,
            @c_discount,
            @c_credit,

```

```

        @o_entry_d,
        @commit_flag
    END
    GO

    SET QUOTED_IDENTIFIER OFF
    GO

    SET ANSI_NULLS ON
    GO

```

null-txns.sql

```

-----
-- File:  NULL-TXNS.SQL
-- Microsoft TPC-C Benchmark Kit Ver. 4.62
-- Copyright Microsoft, 2005
-----
-- This script will create stored procs which
-- accept the same parameters and return correctly
-- formed results sets to match the standard TPC-C
-- stored procs. Of course, the advantage is that
-- these stored procs place almost no load on
-- SQL Server and do not require a database.
-----
-- Interface Level: 4.10.000
-----
USE tpce
GO

IF EXISTS ( SELECT name FROM sysobjects WHERE name = 'tpcc_delivery' )
    DROP PROCEDURE tpcc_neworder
GO
IF EXISTS ( SELECT name FROM sysobjects WHERE name = 'tpcc_neworder' )
    DROP PROCEDURE tpcc_neworder
GO
IF EXISTS ( SELECT name FROM sysobjects WHERE name = 'tpcc_orderstatus' )
    DROP PROCEDURE tpcc_neworder
GO
IF EXISTS ( SELECT name FROM sysobjects WHERE name = 'tpcc_payment' )
    DROP PROCEDURE tpcc_neworder
GO
IF EXISTS ( SELECT name FROM sysobjects WHERE name = 'tpcc_stocklevel' )
    DROP PROCEDURE tpcc_neworder
GO
IF EXISTS ( SELECT name FROM sysobjects WHERE name = 'tpcc_version' )
    DROP PROCEDURE tpcc_neworder
GO
IF EXISTS ( SELECT name FROM sysobjects WHERE name = 'order_line_null' )
    DROP PROCEDURE order_line_null
GO

CREATE PROCEDURE tpcc_delivery
    @w_id int,
    @o_carrier_id smallint
AS
DECLARE @d_id tinyint,
        @o_id int,

```

```

@c_id      int,
@total    numeric(12,2),
@oid1     int,
@oid2     int,
@oid3     int,
@oid4     int,
@oid5     int,
@oid6     int,
@oid7     int,
@oid8     int,
@oid9     int,
@oid10    int,
@delaytime varchar(30)

-----
-- uniform random delay of 0 - 1 second; avg = 0.50
-----
SELECT @delaytime = '00:00:0' + CAST(CAST((RAND()*1.00) AS decimal(4,3)) AS
char(5))

WAITFOR delay @delaytime

SELECT 3001, 3001, 3001, 3001, 3001, 3001, 3001, 3001, 3001, 3001
GO

CREATE PROCEDURE tpcc_neworder
    @w_id      int,
    @d_id      tinyint,
    @c_id      int,
    @o_ol_cnt  tinyint,
    @o_all_local tinyint,
    @i_id1 int = 0, @s_w_id1 int = 0, @ol_qty1 smallint = 0,
    @i_id2 int = 0, @s_w_id2 int = 0, @ol_qty2 smallint = 0,
    @i_id3 int = 0, @s_w_id3 int = 0, @ol_qty3 smallint = 0,
    @i_id4 int = 0, @s_w_id4 int = 0, @ol_qty4 smallint = 0,
    @i_id5 int = 0, @s_w_id5 int = 0, @ol_qty5 smallint = 0,
    @i_id6 int = 0, @s_w_id6 int = 0, @ol_qty6 smallint = 0,
    @i_id7 int = 0, @s_w_id7 int = 0, @ol_qty7 smallint = 0,
    @i_id8 int = 0, @s_w_id8 int = 0, @ol_qty8 smallint = 0,
    @i_id9 int = 0, @s_w_id9 int = 0, @ol_qty9 smallint = 0,
    @i_id10 int = 0, @s_w_id10 int = 0, @ol_qty10 smallint = 0,
    @i_id11 int = 0, @s_w_id11 int = 0, @ol_qty11 smallint = 0,
    @i_id12 int = 0, @s_w_id12 int = 0, @ol_qty12 smallint = 0,
    @i_id13 int = 0, @s_w_id13 int = 0, @ol_qty13 smallint = 0,
    @i_id14 int = 0, @s_w_id14 int = 0, @ol_qty14 smallint = 0,
    @i_id15 int = 0, @s_w_id15 int = 0, @ol_qty15 smallint = 0

AS
DECLARE @w_tax      numeric(4,4),
        @d_tax      numeric(4,4),
        @c_last     char(16),
        @c_credit    char(2),
        @c_discount  numeric(4,4),
        @i_price     numeric(5,2),
        @i_name      char(24),
        @o_entry_d   datetime,
        @li_no       int,
        @o_id        int,
        @commit_flag tinyint,
        @li_id       int,
        @li_qty      smallint,
        @delaytime   varchar(30)

```

```

BEGIN
-----
-- uniform random delay of 0 - 0.6 second; avg = 0.3
-----
SELECT @delaytime = '00:00:0' + CAST(CAST((RAND()*0.60) AS decimal(4,3)) AS
char(5))

WAITFOR delay @delaytime

-----
-- process orderlines
-----
SELECT @commit_flag = 1,
       @li_no       = 0

WHILE (@li_no < @o_ol_cnt)
BEGIN
    SELECT @li_id = CASE @li_no
        WHEN 1 THEN @i_id1
        WHEN 2 THEN @i_id2
        WHEN 3 THEN @i_id3
        WHEN 4 THEN @i_id4
        WHEN 5 THEN @i_id5
        WHEN 6 THEN @i_id6
        WHEN 7 THEN @i_id7
        WHEN 8 THEN @i_id8
        WHEN 9 THEN @i_id9
        WHEN 10 THEN @i_id10
        WHEN 11 THEN @i_id11
        WHEN 12 THEN @i_id12
        WHEN 13 THEN @i_id13
        WHEN 14 THEN @i_id14
        WHEN 15 THEN @i_id15
    END

    SELECT @li_no = @li_no + 1

    SELECT @i_price = 23.45, @li_qty = @li_no

    IF (@li_id = 999999)
    BEGIN
        SELECT '',0,'',0,0

        SELECT @commit_flag = 0
    END
    ELSE
    BEGIN
        SELECT 'Item Name blah',
              17,
              'G',
              @i_price,
              @i_price * @li_qty
    END
END

-----
-- return order data to client
-----
SELECT @w_tax = 0.1234,
       @d_tax = 0.0987,
       @o_id = 3001,
       @c_last = 'BAROUGHTABLE',

```

```

        @c_discount = 0.2198,
        @c_credit = 'GC',
        @o_entry_d = GETDATE()

SELECT  @w_tax,
        @d_tax,
        @o_id,
        @c_last,
        @c_discount,
        @c_credit,
        @o_entry_d,
        @commit_flag

END
GO

CREATE PROCEDURE    tpcc_orderstatus
        @w_id        int,
        @d_id        tinyint,

        @c_id        int,
        @c_last      char(16) = ''

AS
DECLARE @c_balance    numeric(12,2),
        @c_first      char(16),
        @c_middle     char(2),
        @o_id         int,
        @o_entry_d    datetime,
        @o_carrier_id smallint,
        @ol_cnt       smallint,
        @delaytime    varchar(30)

-----
-- uniform random delay of 0 - 0.2 second; avg = 0.1
-----
SELECT @delaytime = '00:00:0' + CAST(CAST((RAND()*0.20) AS decimal(4,3)) AS
char(5))

WAITFOR delay @delaytime

SELECT  @c_id        = 113,
        @c_balance   = -10.00,
        @c_first     = '8YCodgytqCj8',
        @c_middle    = 'OE',
        @c_last      = 'OUGHTOUGHTABLE',
        @o_id        = 3456,
        @o_entry_d   = GETDATE(),
        @o_carrier_id = 1

SELECT  @ol_cnt = (RAND() * 11) + 5

SET     ROWCOUNT @ol_cnt

SELECT  ol_supply_w_id,
        ol_i_id,
        ol_quantity,
        ol_amount,
        ol_delivery_d

FROM    order_line_null

SELECT  @c_id,
        @c_last,

```

```

        @c_first,
        @c_middle,
        @o_entry_d,
        @o_carrier_id,
        @c_balance,
        @o_id

GO

CREATE PROCEDURE    tpcc_payment
        @w_id        int,
        @c_w_id      int,
        @h_amount    numeric(6,2),
        @d_id        tinyint,
        @c_d_id      tinyint,
        @c_id        int,
        @c_last      char(16) = ''

AS
DECLARE @w_street_1 char(20),
        @w_street_2 char(20),
        @w_city      char(20),
        @w_state     char(2),
        @w_zip       char(9),
        @w_name      char(10),
        @d_street_1 char(20),
        @d_street_2 char(20),
        @d_city      char(20),
        @d_state     char(2),
        @d_zip       char(9),
        @d_name      char(10),
        @c_first     char(16),
        @c_middle    char(2),
        @c_street_1 char(20),
        @c_street_2 char(20),
        @c_city      char(20),
        @c_state     char(2),
        @c_zip       char(9),
        @c_phone     char(16),
        @c_since     datetime,
        @c_credit    char(2),
        @c_credit_lim numeric(12,2),
        @c_balance   numeric(12,2),
        @c_discount  numeric(4,4),
        @data        char(500),
        @c_data      char(500),
        @datetime    datetime,
        @w_ytd       numeric(12,2),
        @d_ytd       numeric(12,2),
        @cnt         smallint,
        @val         smallint,
        @screen_data char(200),
        @d_id_local  tinyint,
        @w_id_local  int,
        @c_id_local  int,
        @delaytime   varchar(30)

-----
-- uniform random delay of 0 - 0.3 second; avg = 0.15
-----
SELECT @delaytime = '00:00:0' + CAST(CAST((RAND()*0.20) AS decimal(4,3)) AS
char(5))

WAITFOR delay @delaytime

```



```

SELECT @screen_data = ''

-----
-- get customer info and update balances
-----
SELECT @d_street_1 = 'rqSHHakqyV',
       @d_street_2 = 'zZ98nW3BR2s',
       @d_city     = 'ArNr4GNFV9',
       @d_state    = 'aV',
       @d_zip      = '453511111'

-----
-- get warehouse data and update year-to-date
-----
SELECT @w_street_1 = 'rqSHHakqyV',
       @w_street_2 = 'zZ98nW3BR2s',
       @w_city     = 'ArNr4GNFV9',
       @w_state    = 'aV',
       @w_zip      = '453511111'

SELECT @c_id        = 123,
       @c_balance   = -10000.00,
       @c_first     = 'KmR03Xureb',
       @c_middle    = 'OE',
       @c_last      = 'BAROUGHTEBAR',
       @c_street_1  = 'QpGdOHjv8mR9vNI8V',
       @c_street_2  = 'dzKoCOBqbc3yu',
       @c_city      = 'zAKZXdC037FQxq',
       @c_state     = 'QA',
       @c_zip       = '700311111',
       @c_phone     = '2967264064528555',
       @c_credit    = 'GC',
       @c_credit_lim = 50000.00,
       @c_discount  = 0.3069,
       @c_since     = GETDATE(),
       @datetime    = GETDATE()

-----
-- return data to client
-----
SELECT @c_id,
       @c_last,
       @datetime,
       @w_street_1,
       @w_street_2,
       @w_city,
       @w_state,
       @w_zip,
       @d_street_1,
       @d_street_2,
       @d_city,
       @d_state,
       @d_zip,
       @c_first,
       @c_middle,
       @c_street_1,
       @c_street_2,
       @c_city,
       @c_state,
       @c_zip,
       @c_phone,
       @c_since,

```

```

       @c_credit,
       @c_credit_lim,
       @c_discount,
       @c_balance,
       @screen_data
GO

CREATE PROCEDURE tpcc_stocklevel
    @w_id int,
    @d_id tinyint,
    @threshold smallint
AS
DECLARE @delaytime varchar(30)

-----
-- uniform random delay of 0 - 3.6 second; avg = 1.8
-----
SELECT @delaytime = '00:00:0' + CAST(CAST((RAND()*0.20) AS decimal(4,3)) AS
char(5))

WAITFOR delay @delaytime

SELECT 49
GO

CREATE PROCEDURE tpcc_version
AS
DECLARE @version char(8)

BEGIN
    SELECT @version = '4.10.000'

    SELECT @version AS 'Version'
END
GO

CREATE TABLE order_line_null (
    [ol_i_id] [int] NOT NULL ,
    [ol_supply_w_id] [int] NOT NULL ,
    [ol_delivery_d] [datetime] NOT NULL ,
    [ol_quantity] [smallint] NOT NULL ,
    [ol_amount] [numeric](6, 2) NOT NULL
) ON [PRIMARY]
GO

INSERT INTO order_line_null VALUES ( 101, 1, GETDATE(), 1, 123.45 )
INSERT INTO order_line_null VALUES ( 102, 1, GETDATE(), 2, 123.45 )
INSERT INTO order_line_null VALUES ( 103, 1, GETDATE(), 3, 123.45 )
INSERT INTO order_line_null VALUES ( 104, 1, GETDATE(), 4, 123.45 )
INSERT INTO order_line_null VALUES ( 105, 1, GETDATE(), 5, 123.45 )
INSERT INTO order_line_null VALUES ( 106, 1, GETDATE(), 1, 123.45 )
INSERT INTO order_line_null VALUES ( 107, 1, GETDATE(), 2, 123.45 )
INSERT INTO order_line_null VALUES ( 108, 1, GETDATE(), 3, 123.45 )
INSERT INTO order_line_null VALUES ( 109, 1, GETDATE(), 4, 123.45 )
INSERT INTO order_line_null VALUES ( 110, 1, GETDATE(), 5, 123.45 )
INSERT INTO order_line_null VALUES ( 111, 1, GETDATE(), 1, 123.45 )
INSERT INTO order_line_null VALUES ( 112, 1, GETDATE(), 2, 123.45 )
INSERT INTO order_line_null VALUES ( 113, 1, GETDATE(), 3, 123.45 )
INSERT INTO order_line_null VALUES ( 114, 1, GETDATE(), 4, 123.45 )
INSERT INTO order_line_null VALUES ( 115, 1, GETDATE(), 5, 123.45 )
GO

```

ordstat.sql

```
-----
--
-- File:   ORDSTAT.SQL
--         Microsoft TPC-C Benchmark Kit Ver. 4.62
--         Copyright Microsoft, 2005
--
--         Creates order status stored procedure
--
--         Interface Level:   4.20.000
--
-----
SET QUOTED_IDENTIFIER OFF
GO

SET ANSI_NULLS ON
GO

USE tpcc
GO

IF EXISTS ( SELECT name FROM sysobjects WHERE name = 'tpcc_orderstatus' )
  DROP PROCEDURE tpcc_orderstatus
GO

CREATE PROCEDURE tpcc_orderstatus
    @w_id int,
    @d_id tinyint,

    @c_id int,
    @c_last char(16) = ''

AS
DECLARE @c_balance money,
        @c_first char(16),
        @c_middle char(2),
        @o_id int,
        @o_entry_d datetime,
        @o_carrier_id smallint,
        @cnt smallint

BEGIN TRANSACTION o
  IF (@c_id = 0)
    BEGIN
      -----
      -- get customer id and info using last name
      -----
      SELECT @cnt = (count(*)+1)/2
      FROM customer WITH (repeatableread)
      WHERE c_last = @c_last AND
            c_w_id = @w_id AND
            c_d_id = @d_id

      SET rowcount @cnt

      SELECT @c_id = c_id,
             @c_balance = c_balance,
             @c_first = c_first,
             @c_last = c_last,
             @c_middle = c_middle
      FROM customer WITH (repeatableread)
```

```
WHERE c_last = @c_last AND
      c_w_id = @w_id AND
      c_d_id = @d_id
ORDER BY c_w_id, c_d_id, c_last, c_first

SET rowcount 0
END
ELSE
BEGIN
  -----
  -- get customer info if by id
  -----
  SELECT @c_balance = c_balance,
         @c_first = c_first,
         @c_middle = c_middle,
         @c_last = c_last
  FROM customer WITH (repeatableread)
  WHERE c_id = @c_id AND
        c_d_id = @d_id AND
        c_w_id = @w_id

  SELECT @cnt = @@rowcount
END

-----
-- if no such customer
-----
IF (@cnt = 0)
  BEGIN
    RAISERROR('Customer not found',18,1)
    GOTO custnotfound
  END

-----
-- get order info
-----
SELECT @o_id = o_id,
       @o_entry_d = o_entry_d,
       @o_carrier_id = o_carrier_id
FROM orders WITH (serializable)
WHERE o_c_id = @c_id AND
      o_d_id = @d_id AND
      o_w_id = @w_id
ORDER BY o_id ASC

-----
-- select order lines for the current order
-----
SELECT ol_supply_w_id,
       ol_i_id,
       ol_quantity,
       ol_amount,
       ol_delivery_d
FROM order_line WITH (repeatableread)
WHERE ol_o_id = @o_id AND
      ol_d_id = @d_id AND
      ol_w_id = @w_id

custnotfound:

COMMIT TRANSACTION o
-----
```

```

-- return data to client
-----
SELECT  @c_id,
        @c_last,
        @c_first,
        @c_middle,
        @o_entry_d,
        @o_carrier_id,
        @c_balance,
        @o_id
GO

```

payment.sql

```

-----
-- File:      PAYMENT.SQL
-- Microsoft TPC-C Benchmark Kit Ver. 4.62
-- Copyright Microsoft, 2005
--
-- Creates payment stored procedure
--
-- Interface Level:      4.20.000
-----
SET QUOTED_IDENTIFIER OFF
GO

SET ANSI_NULLS ON
GO

USE tpcc
GO

IF EXISTS ( SELECT name FROM sysobjects WHERE name = 'tpcc_payment' )
    DROP PROCEDURE tpcc_payment
GO

CREATE PROCEDURE      tpcc_payment
        @w_id          int,
        @c_w_id        int,
        @h_amount      smallmoney,
        @d_id           tinyint,
        @c_d_id         tinyint,
        @c_id           int,
        @c_last         char(16) = ""
AS
DECLARE @w_street_1   char(20),
        @w_street_2   char(20),
        @w_city        char(20),
        @w_state       char(2),
        @w_zip         char(9),
        @w_name        char(10),
        @d_street_1    char(20),
        @d_street_2    char(20),
        @d_city        char(20),
        @d_state       char(2),
        @d_zip         char(9),
        @d_name        char(10),
        @c_first       char(16),
        @c_middle      char(2),

```

```

        @c_street_1    char(20),
        @c_street_2    char(20),
        @c_city        char(20),
        @c_state       char(2),
        @c_zip         char(9),
        @c_phone       char(16),
        @c_since       datetime,
        @c_credit      char(2),
        @c_credit_lim  money,
        @c_balance     money,
        @c_discount    smallmoney,
        @c_data        char(42),
        @datetime      datetime,
        @w_ytd         money,
        @d_ytd         money,
        @cnt           smallint,
        @val           smallint,
        @screen_data   char(200),
        @d_id_local    tinyint,
        @w_id_local    int,
        @c_id_local    int

SELECT  @screen_data   = ""

BEGIN TRANSACTION p
-- get payment date
SELECT  @datetime = GETDATE()

IF (@c_id = 0)
BEGIN
-- get customer id and info using last name
SELECT  @cnt = COUNT(*)
FROM    customer WITH (repeatableread)
WHERE   c_last = @c_last AND
        c_w_id = @c_w_id AND
        c_d_id = @c_d_id

SELECT  @val = (@cnt + 1) / 2

SET     rowcount @val

SELECT  @c_id = c_id
FROM    customer WITH (repeatableread)
WHERE   c_last = @c_last AND
        c_w_id = @c_w_id AND
        c_d_id = @c_d_id

ORDER  BY c_last, c_first

SET     rowcount 0

END

-- get customer info and update balances
UPDATE  customer
SET     @c_balance = c_balance = c_balance - @h_amount,
        c_payment_cnt = c_payment_cnt + 1,
        c_ytd_payment = c_ytd_payment + @h_amount,
        @c_first = c_first,
        @c_middle = c_middle,
        @c_last = c_last,
        @c_street_1 = c_street_1,
        @c_street_2 = c_street_2,
        @c_city = c_city,

```

```

@c_state      = c_state,
@c_zip        = c_zip,
@c_phone      = c_phone,
@c_credit     = c_credit,
@c_credit_lim = c_credit_lim,
@c_discount   = c_discount,
@c_since      = c_since,
@c_id_local   = c_id
WHERE  c_id    = @c_id AND
       c_w_id  = @c_w_id AND
       c_d_id  = @c_d_id

-- if customer has bad credit get some more info
IF (@c_credit = "BC")
BEGIN
--      compute new info
SELECT  @c_data =      convert(char(5),@c_id) +
                      convert(char(4),@c_d_id) +
                      convert(char(5),@c_w_id) +
                      convert(char(4),@d_id) +
                      convert(char(5),@w_id) +
                      convert(char(19),@h_amount)

--      update customer info
UPDATE  customer
SET     c_data      = @c_data + substring(c_data, 1, 458),
       @screen_data = @c_data + substring(c_data, 1, 158)

WHERE  c_id    = @c_id AND
       c_w_id  = @c_w_id AND
       c_d_id  = @c_d_id
END

-- get district data and update year-to-date
UPDATE  district
SET     d_ytd      = d_ytd + @h_amount,
       @d_street_1 = d_street_1,
       @d_street_2 = d_street_2,
       @d_city     = d_city,
       @d_state    = d_state,
       @d_zip      = d_zip,
       @d_name     = d_name,
       @d_id_local = d_id
WHERE  d_w_id  = @w_id AND
       d_id    = @d_id

-- get warehouse data and update year-to-date
UPDATE  warehouse
SET     w_ytd      = w_ytd + @h_amount,
       @w_street_1 = w_street_1,
       @w_street_2 = w_street_2,
       @w_city     = w_city,
       @w_state    = w_state,
       @w_zip      = w_zip,
       @w_name     = w_name,
       @w_id_local = w_id
WHERE  w_id    = @w_id

-- create history record
INSERT INTO      history VALUES (@c_id_local,
                                @c_d_id,
                                @c_w_id,
                                @d_id_local,

```

```

                                @w_id_local,
                                @datetime,
                                @h_amount,
                                @w_name + ' ' + @d_name)

COMMIT TRANSACTION p

-- return data to client
SELECT  @c_id,
       @c_last,
       @datetime,
       @w_street_1,
       @w_street_2,
       @w_city,
       @w_state,
       @w_zip,
       @d_street_1,
       @d_street_2,
       @d_city,
       @d_state,
       @d_zip,
       @c_first,
       @c_middle,
       @c_street_1,
       @c_street_2,
       @c_city,
       @c_state,
       @c_zip,
       @c_phone,
       @c_since,
       @c_credit,
       @c_credit_lim,
       @c_discount,
       @c_balance,
       @screen_data

GO

SET QUOTED_IDENTIFIER OFF
GO

SET ANSI_NULLS ON
GO



---


random.c


---


//      File:                RANDOM.C
//
//      Microsoft TPC-C Kit Ver. 4.62
//      Copyright Microsoft, 1996, 1997, 1998, 1999,
//      2000, 2001, 2002, 2005
//      Purpose:  Random number generation routines for database loader

// Includes
#include "tpcc.h"
#include "math.h"

// Defines
#define A          16807
#define M          2147483647
#define Q          127773      /* M div A */
#define R          2836       /* M mod A */
#define Thread    __declspec(thread)

```

```

// Globals
long Thread Seed = 0; /* thread local seed */

/*****
 *
 * random -
 * Implements a GOOD pseudo random number generator. This generator
 * will/should? run the complete period before repeating.
 *
 * Copied from:
 * Random Numbers Generators: Good Ones Are Hard to Find.
 * Communications of the ACM - October 1988 Volume 31 Number 10
 *
 * Machine Dependencies:
 * long must be 2 ^ 31 - 1 or greater.
 *****/

/*****
 * seed - load the Seed value used in irand and drand. Should be used before
 * first call to irand or drand.
 *****/

void seed(long val)
{
#ifdef DEBUG
    printf("[%d]DBG: Entering seed()...\n", (int) GetCurrentThreadId());
    printf("Old Seed %ld New Seed %ld\n",Seed, val);
#endif

    if ( val < 0 )
        val = abs(val);

    Seed = val;
}

/*****
 *
 * irand - returns a 32 bit integer pseudo random number with a period of
 * 1 to 2 ^ 32 - 1.
 *
 * parameters:
 * none.
 *
 * returns:
 * 32 bit integer - defined as long ( see above ).
 *
 * side effects:
 * seed get recomputed.
 *****/

long irand()
{
    register long s; /* copy of seed */
    register long test; /* test flag */
    register long hi; /* tmp value for speed */
    register long lo; /* tmp value for speed */

#ifdef DEBUG

```

```

    printf("[%d]DBG: Entering irand()...\n", (int) GetCurrentThreadId());
#endif

    s = Seed;
    hi = s / Q;
    lo = s % Q;

    test = A * lo - R * hi;
    if ( test > 0 )
        Seed = test;
    else
        Seed = test + M;

    return( Seed );
}

/*****
 *
 * drand - returns a double pseudo random number between 0.0 and 1.0.
 * See irand.
 *****/

double drand()
{
#ifdef DEBUG
    printf("[%d]DBG: Entering drand()...\n", (int) GetCurrentThreadId());
#endif

    return( (double)irand() / 2147483647.0 );
}

//=====
// Function : RandomNumber
//
// Description:
//=====
long RandomNumber(long lower, long upper)
{
    long rand_num;

#ifdef DEBUG
    printf("[%d]DBG: Entering RandomNumber()...\n", (int) GetCurrentThreadId());
#endif

    if ( upper == lower ) /* pgd 08-13-96 perf enhancement */
        return lower;

    upper++;

    if ( upper <= lower )
        rand_num = upper;
    else
        rand_num = lower + irand() % (upper - lower); /* pgd 08-13-96
perf enhancement */

#ifdef DEBUG
    printf("[%d]DBG: RandomNumber between %ld & %ld ==> %ld\n",
(int) GetCurrentThreadId(), lower, upper,
rand_num);
#endif

```

```

    return rand_num;
}

#if 0
//Original code pgd 08/13/96
long RandomNumber(long lower,
                  long upper)
{
    long rand_num;

#ifdef DEBUG
    printf("[%ld]DBG: Entering RandomNumber()...\n", (int) GetCurrentThreadId());
#endif

    upper++;

    if ((upper <= lower))
        rand_num = upper;
    else
        rand_num = lower + irand() % ((upper > lower) ? upper - lower :
upper);

#ifdef DEBUG
    printf("[%ld]DBG: RandomNumber between %ld & %ld ==> %ld\n",
          (int) GetCurrentThreadId(), lower, upper,
rand_num);
#endif

    return rand_num;
}
#endif

//=====
// Function   : NURand
//
// Description:
//=====
long NURand(int iConst,
           long x,
           long y,
           long C)
{
    long rand_num;

#ifdef DEBUG
    printf("[%ld]DBG: Entering NURand()...\n", (int) GetCurrentThreadId());
#endif

    rand_num = (((RandomNumber(0,iConst) | RandomNumber(x,y)) + C) % (y-x+1))+x;

#ifdef DEBUG
    printf("[%ld]DBG: NURand: num = %d\n", (int) GetCurrentThreadId(), rand_num);
#endif

    return rand_num;
}

```

removedb.sql

```

--
-- File:      REMOVEDB.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.61
--           Copyright Microsoft, 2005
--
-----
USE master
GO

-----
-- remove any existing database and backup files
-----
EXEC sp_dbremove tpcc, dropdev
GO

EXEC sp_dropdevice 'tpccback1'
EXEC sp_dropdevice 'tpccback2'
EXEC sp_dropdevice 'tpccback3'
EXEC sp_dropdevice 'tpccback4'
GO

```

restore.sql

```

--
-- File:      RESTORE.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.61
--           Copyright Microsoft, 2005
--
-----
DECLARE @startdate  DATETIME,
        @enddate    DATETIME

SELECT @startdate = GETDATE()
SELECT 'Start date:',
       CONVERT(VARCHAR(30),@startdate, 21)

LOAD DATABASE tpcc FROM tpccback1, tpccback2, tpccback3, tpccback4 WITH stats = 1,
replace

SELECT @enddate = GETDATE()
SELECT 'End date: ',
       CONVERT(VARCHAR(30),@enddate, 21)
SELECT 'Elapsed time (in seconds): ',
       DATEDIFF(second, @startdate, @enddate)

GO
use tpcc
go
DROP INDEX orders.orders_nc1
Go

```

RunSQLCfg.sql

```

-----
--
-- File:   RUNSQLCFG.SQL
--         Microsoft TPC-C Benchmark Kit Ver. 4.62
--         Copyright Microsoft, 2005
--
--         Sets suggested runtime server configuration
--         parameters
--
-----
EXEC sp_configure 'show advanced option', 1
GO

RECONFIGURE WITH OVERRIDE
GO

-----
-- change this value to approximately the number of connected users
-----
EXEC sp_configure 'max worker threads',255

-----
-- increase priority of user threads
-----
EXEC sp_configure 'priority boost',1

-----
-- disable automatic checkpointing
-----
EXEC sp_configure 'recovery interval',32767

-----
-- change to a mask appropriate for the number of processors on the server
-----
EXEC sp_configure 'affinity mask',0xf

-----
-- enable fibers
-----
EXEC sp_configure 'lightweight pooling',1
GO

RECONFIGURE WITH OVERRIDE
GO

```

sqlshutdown.sql

```

-----
--
-- File:   SQLSHUTDOWN.SQL
--         Microsoft TPC-C Benchmark Kit Ver. 4.62
--         Copyright Microsoft, 2005
--
--         Checkpoints tpcc database and issues a shutdown
--
-----
USE tpcc
GO

CHECKPOINT
GO

```

```

SHUTDOWN
GO

```

stocklev.sql

```

-----
--
-- File:   STOCKLEV.SQL
--         Microsoft TPC-C Benchmark Kit Ver. 4.62
--         Copyright Microsoft, 2005
--
--         Creates stock level stored procedure
--
--         Interface Level:   4.20.000
--
-----
SET QUOTED_IDENTIFIER OFF
GO

SET ANSI_NULLS ON
GO

USE tpcc
GO

IF EXISTS ( SELECT name FROM sysobjects WHERE name = 'tpcc_stocklevel' )
    DROP PROCEDURE tpcc_stocklevel
GO

CREATE PROCEDURE    tpcc_stocklevel
                   @w_id          int,
                   @d_id          tinyint,
                   @threshold     smallint
AS
DECLARE @o_id_low  int,
        @o_id_high int

SELECT  @o_id_low = (d_next_o_id - 20),
        @o_id_high = (d_next_o_id - 1)
FROM    district
WHERE   d_w_id   = @w_id AND
        d_id    = @d_id

SELECT  COUNT(DISTINCT(s_i_id))
FROM    stock,
        order_line
WHERE   ol_w_id   = @w_id AND
        ol_d_id   = @d_id and
        ol_o_id   BETWEEN @o_id_low AND
                        @o_id_high AND
        s_w_id   = ol_w_id AND
        s_i_id   = ol_i_id AND
        s_quantity < @threshold

OPTION (ORDER GROUP)
GO

SET QUOTED_IDENTIFIER OFF
GO

SET ANSI_NULLS ON
GO

```

strings.c

```
// File: STRINGS.C
// Microsoft TPC-C Kit Ver. 4.51
// Copyright Microsoft, 1996, 1997, 1998, 1999,
2000, 2001, 2002, 2003
// Purpose: Source file for database loader string functions

// Includes
#include "tpcc.h"
#include <string.h>
#include <ctype.h>

//=====
//
// Function name: MakeAddress
//
//=====

void MakeAddress(char *street_1,
                char *street_2,
                char *city,
                char *state,
                char *zip)
{
#ifdef DEBUG
    printf("[%ld]DBG: Entering MakeAddress()\n", (int) GetCurrentThreadId());
#endif

    MakeAlphaString (10, 20, ADDRESS_LEN, street_1);
    MakeAlphaString (10, 20, ADDRESS_LEN, street_2);
    MakeAlphaString (10, 20, ADDRESS_LEN, city);
    MakeAlphaString ( 2,  2, STATE_LEN, state);
    MakeZipNumberString( 9,  9, ZIP_LEN, zip);

#ifdef DEBUG
    printf("[%ld]DBG: MakeAddress: street_1: %s, street_2: %s, city: %s, state: %s,
zip: %s\n",
                (int) GetCurrentThreadId(), street_1, street_2, city,
                state, zip);
#endif

    return;
}

//=====
//
// Function name: LastName
//
//=====

void LastName(int num,
            char *name)
{
    static char *n[] =
    {
        "BAR" , "OUGHT" , "ABLE" , "PRI" , "PRES" ,
        "ESE" , "ANTI" , "CALLY" , "ATION" , "EING"
    }
};
```

```
};

#ifdef DEBUG
    printf("[%ld]DBG: Entering LastName()\n", (int) GetCurrentThreadId());
#endif

    if ((num >= 0) && (num < 1000))
    {
        strcpy(name, n[(num/100)%10]);
        strcat(name, n[(num/10)%10]);
        strcat(name, n[(num/1)%10]);

        if (strlen(name) < LAST_NAME_LEN)
        {
            PaddString(LAST_NAME_LEN, name);
        }
    }
    else
    {
        printf("\nError in LastName()... num <%ld> out of range
(0,999)\n", num);
        exit(-1);
    }

#ifdef DEBUG
    printf("[%ld]DBG: LastName: num = [%d] ==> [%d][%d][%d]\n",
                (int) GetCurrentThreadId(), num, num/100, (num/10)%10,
                num%10);
    printf("[%ld]DBG: LastName: String = %s\n", (int) GetCurrentThreadId(),
name);
#endif

    return;
}

//=====
//
// Function name: MakeAlphaString
//
//=====

//philipdu 08/13/96 Changed MakeAlphaString to use A-Z, a-z, and 0-9 in
//accordance with spec see below:
//The spec says:
//4.3.2.2 The notation random a-string [x .. y]
//(respectively, n-string [x .. y]) represents a string of random alphanumeric
//(respectively, numeric) characters of a random length of minimum x, maximum y,
//and mean (y+x)/2. Alphanumerics are A..Z, a..z, and 0..9. The only other
//requirement is that the character set used "must be able to represent a minimum
//of 128 different characters". We are using 8-bit chars, so this is a non issue.
//It is completely unreasonable to stuff non-printing chars into the text fields.
//-Clevine 08/13/96

int MakeAlphaString( int x, int y, int z, char *str)
{
    int len;
    int i;
    char cc = 'a';
};
```



```

        static char chArray[] =
"0123456789ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz";
        static int chArrayMax = 61;

#ifdef DEBUG
    printf("[%ld]DBG: Entering MakeAlphaString()\n", (int) GetCurrentThreadId());
#endif

    len= RandomNumber(x, y);

    for (i=0; i<len; i++)
        str[i] = chArray[RandomNumber(0, chArrayMax)];
    str[len] = 0;

    return len;
}

int MakeAlphaStringPadded( int minLen, int maxLen, int padLen, char *str)
{
    int len;
    int i;
    char cc = 'a';
    static char chArray[] =
"0123456789ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz";
    static int chArrayMax = 61;

#ifdef DEBUG
    printf("[%ld]DBG: Entering MakeAlphaStringPadded()\n", (int)
GetCurrentThreadId());
#endif

    len= RandomNumber(minLen, maxLen);

    for (i=0; i<len; i++)
        str[i] = chArray[RandomNumber(0, chArrayMax)];
    if (len < padLen)
        memset(str+len, ' ', padLen - len);
    str[padLen] = 0;
    return padLen;
}

//=====
//
// Function name: MakeOriginalAlphaString
//
//=====
int MakeOriginalAlphaString(int x,
                           int y,
                           int z,
                           char *str,
                           int percent)
{
    int len;
    int val;
    int start;

#ifdef DEBUG
    printf("[%ld]DBG: Entering MakeOriginalAlphaString()\n", (int)
GetCurrentThreadId());
#endif

```

```

// verify prcentage is valid
if ((percent < 0) || (percent > 100))
{
    printf("MakeOrigianlAlphaString: Invalid percentage: %d\n",
percent);
    exit(-1);
}

// verify string is at least 8 chars in length
if (x < 8)
{
    printf("MakeOriginalAlphaString: string length must be >= 8\n");
    exit(-1);
}

// Make Alpha String
len = MakeAlphaString(x,y, z, str);

val = RandomNumber(1,100);
if (val <= percent)
{
    start = RandomNumber(0, len - 8);
    strncpy(str + start, "ORIGINAL", 8);
}

#ifdef DEBUG
    printf("[%ld]DBG: MakeOriginalAlphaString: : %s\n",
(int) GetCurrentThreadId(), str);
#endif

    return len;
}

//=====
//
// Function name: MakeNumberString
//
//=====
int MakeNumberString(int x, int y, int z, char *str)
{
    char tmp[16];

    //MakeNumberString is always called MakeZipNumberString(16, 16, 16,
string)

    memset(str, '0', 16);
    itoa(RandomNumber(0, 99999999), tmp, 10);
    memcpy(str, tmp, strlen(tmp));

    itoa(RandomNumber(0, 99999999), tmp, 10);
    memcpy(str+8, tmp, strlen(tmp));

    str[16] = 0;

    return 16;
}

//=====
//

```

```

// Function name: MakeZipNumberString
//
//=====
int MakeZipNumberString(int x, int y, int z, char *str)
{
    char tmp[16];

    //MakeZipNumberString is always called MakeZipNumberString(9, 9, 9,
string)

    strcpy(str, "000011111");

    itoa(RandomNumber(0, 9999), tmp, 10);
    memcpy(str, tmp, strlen(tmp));

    return 9;
}

//=====
//
// Function name: InitString
//
//=====
void InitString(char *str, int len)
{
#ifdef DEBUG
    printf("[%ld]DBG: Entering InitString()\n", (int) GetCurrentThreadId());
#endif

    memset(str, ' ', len);
    str[len] = 0;
}

//=====
//
// Function name: InitAddress
//
// Description:
//
//=====
void InitAddress(char *street_1, char *street_2, char *city, char *state, char *zip)
{
    memset(street_1, ' ', ADDRESS_LEN+1);
    memset(street_2, ' ', ADDRESS_LEN+1);
    memset(city, ' ', ADDRESS_LEN+1);

    street_1[ADDRESS_LEN+1] = 0;
    street_2[ADDRESS_LEN+1] = 0;
    city[ADDRESS_LEN+1] = 0;

    memset(state, ' ', STATE_LEN+1);
    state[STATE_LEN+1] = 0;

    memset(zip, ' ', ZIP_LEN+1);
    zip[ZIP_LEN+1] = 0;
}

//=====
//
// Function name: PaddString

```

```

//
//=====
void PaddString(int max, char *name)
{
    int len;

    len = strlen(name);
    if ( len < max )
        memset(name+len, ' ', max - len);
    name[max] = 0;

    return;
}

```

tables.sql

```

-----
-- File: TABLES.SQL
-- Microsoft TPC-C Benchmark Kit Ver. 4.62
-- Copyright Microsoft, 2005
--
-- Creates TPC-C tables
-----

SET ANSI_NULL_DFLT_OFF ON
GO

USE tpcc
GO

-----
-- Remove all existing TPC-C tables
-----
if exists ( select name from sysobjects where name = 'warehouse' )
    drop table warehouse
go
if exists ( select name from sysobjects where name = 'district' )
    drop table district
go
if exists ( select name from sysobjects where name = 'customer' )
    drop table customer
go
if exists ( select name from sysobjects where name = 'history' )
    drop table history
go
if exists ( select name from sysobjects where name = 'new_order' )
    drop table new_order
go
if exists ( select name from sysobjects where name = 'orders' )
    drop table orders
go
if exists ( select name from sysobjects where name = 'order_line' )
    drop table order_line
go
if exists ( select name from sysobjects where name = 'item' )
    drop table item
go
if exists ( select name from sysobjects where name = 'stock' )
    drop table stock
go

```

```

-----
-- Create new tables
-----
create table warehouse
(
    w_id          int,
    w_ytd         money,
    w_tax         smallmoney,
    w_name        char(10),
    w_street_1    char(20),
    w_street_2    char(20),
    w_city        char(20),
    w_state       char(2),
    w_zip         char(9)
) on MSSQL_misc_fg
go

create table district
(
    d_id          tinyint,
    d_w_id        int,
    d_ytd         money,
    d_next_o_id   int,
    d_tax         smallmoney,
    d_name        char(10),
    d_street_1    char(20),
    d_street_2    char(20),
    d_city        char(20),
    d_state       char(2),
    d_zip         char(9)
) on MSSQL_misc_fg
go

create table customer
(
    c_id          int,
    c_d_id        tinyint,
    c_w_id        int,
    c_discount    smallmoney,
    c_credit_lim  money,
    c_last        char(16),
    c_first       char(16),
    c_credit      char(2),
    c_balance     money,
    c_ytd_payment money,
    c_payment_cnt smallint,
    c_delivery_cnt smallint,
    c_street_1    char(20),
    c_street_2    char(20),
    c_city        char(20),
    c_state       char(2),
    c_zip         char(9),
    c_phone       char(16),
    c_since       datetime,
    c_middle      char(2),
    c_data        char(50)
) on MSSQL_cs_fg
go

-- Use the following table option if using c_data varchar(max)
-- sp_tableoption 'customer','large value types out of row','1'
-- go

```

```

create table history
(
    h_c_id        int,
    h_c_d_id      tinyint,
    h_c_w_id      int,
    h_d_id        tinyint,
    h_w_id        int,
    h_date        datetime,
    h_amount      smallmoney,
    h_data        char(24)
) on MSSQL_misc_fg
go

create table new_order
(
    no_o_id       int,
    no_d_id       tinyint,
    no_w_id       int
) on MSSQL_misc_fg
go

create table orders
(
    o_id          int,
    o_d_id        tinyint,
    o_w_id        int,
    o_c_id        int,
    o_carrier_id  tinyint,
    o_ol_cnt      tinyint,
    o_all_local   tinyint,
    o_entry_d     datetime
) on MSSQL_misc_fg
go

create table order_line
(
    ol_o_id       int,
    ol_d_id       tinyint,
    ol_w_id       int,
    ol_number     tinyint,
    ol_i_id       int,
    ol_delivery_d datetime,
    ol_amount     smallmoney,
    ol_supply_w_id int,
    ol_quantity   smallint,
    ol_dist_info  char(24)
) on MSSQL_misc_fg
go

create table item
(
    i_id          int,
    i_name        char(24),
    i_price       smallmoney,
    i_data        char(50),
    i_im_id       int
) on MSSQL_misc_fg
go

create table stock
(
    s_i_id        int,

```

```

s_w_id          int,
s_quantity      smallint,
s_ytd           int,
s_order_cnt     smallint,
s_remote_cnt    smallint,
s_data          char(50),
s_dist_01       char(24),
s_dist_02       char(24),
s_dist_03       char(24),
s_dist_04       char(24),
s_dist_05       char(24),
s_dist_06       char(24),
s_dist_07       char(24),
s_dist_08       char(24),
s_dist_09       char(24),
s_dist_10       char(24)
) on MSSQL_cs_fg
go

```

time.c

```

// File: TIME.C Microsoft TPC-C Kit Ver. 4.62
// Copyright Microsoft, 1996, 1997, 1998, 1999,
// 2000, 2001, 2002, 2005
// Purpose: Source file for time functions

// Includes
#include "tpcc.h"

// Globals
static long start_sec;

//=====
//
// Function name: TimeNow
//=====
long TimeNow()
{
    long time_now;
    struct _timeb el_time;

#ifdef DEBUG
    printf("[%ld]DBG: Entering TimeNow()\n", (int) GetCurrentThreadId());
#endif

    _ftime(&el_time);

    time_now = ((el_time.time - start_sec) * 1000) + el_time.millitm;

    return time_now;
}

```

tpcc.h

```

// File: TPCC.H Microsoft TPC-C Kit Ver. 4.51
// Copyright Microsoft, 1996, 1997, 1998, 1999,
// 2000, 2001, 2002, 2003, 2005
// Purpose: Header file for TPC-C database loader

// Build number of TPC Benchmark Kit
#define TPCKIT_VER "4.51"

// General headers
#include <windows.h>
#include <winbase.h>
#include <stdlib.h>
#include <stdio.h>
#include <process.h>
#include <stddef.h>
#include <stdarg.h>
#include <string.h>
#include <time.h>
#include <sys\timeb.h>
#include <sys\types.h>
#include <math.h>

// ODBC headers
#include <sql.h>
#include <sqlext.h>
#include <odbc.h>

// General constants
#define MILLI 1000
#define FALSE 0
#define TRUE 1
#define UNDEF -1
#define MINPRINTASCII 32
#define MAXPRINTASCII 126

// Default environment constants
#define SERVER ""
#define DATABASE "tpcc"
#define USER "sa"
#define PASSWORD ""

// Default loader arguments
#define BATCH 10000
#define DEFLDPACKSIZE 32768
#define LOADER_RES_FILE "C:\\MSTPCC.450\\SETUP\\LOGS\\load.out"
#define LOADER_LOG_PATH "C:\\MSTPCC.450\\SETUP\\LOGS\\"
#define LOADER_NURAND_C 123
#define DEF_STARTING_WAREHOUSE 1
#define BUILD_INDEX 1 // build both
// data and indexes
#define INDEX_ORDER 1 // build
// indexes before load
#define SCALE_DOWN 0 // build a normal
// scale database
#define INDEX_SCRIPT_PATH "scripts"

typedef struct
{
    char *server;

```

```

char          *database;
char          *user;
char          *password;
char          tables_all;
        BOOL
        // set if loading all tables
        BOOL
        // set if loading ITEM table specifically
        BOOL
loading WAREHOUSE, DISTRICT, and STOCK
        BOOL
set if loading CUSTOMER and HISTORY
        BOOL
set if loading NEW-ORDER, ORDERS, ORDER-LINE
        long
        long
        long
        long
        char
        char
        char
        long
        long
        long
        long
        long
        long
        long
        char
} TPCCCLR_ARGS;

// String length constants
#define SERVER_NAME_LEN      20
#define DATABASE_NAME_LEN   20
#define USER_NAME_LEN       20
#define PASSWORD_LEN        20
#define TABLE_NAME_LEN     20
#define I_DATA_LEN          50
#define I_NAME_LEN          24
#define BRAND_LEN           1
#define LAST_NAME_LEN       16
#define W_NAME_LEN          10
#define ADDRESS_LEN         20
#define STATE_LEN           2
#define ZIP_LEN              9
#define S_DIST_LEN          24
#define S_DATA_LEN          50
#define D_NAME_LEN          10
#define FIRST_NAME_LEN      16
#define MIDDLE_NAME_LEN     2
#define PHONE_LEN           16
#define CREDIT_LEN          2
#define C_DATA_LEN          500
#define H_DATA_LEN          24
#define DIST_INFO_LEN       24
#define MAX_OL_NEW_ORDER_ITEMS 15
#define MAX_OL_ORDER_STATUS_ITEMS 15
#define STATUS_LEN          25
#define OL_DIST_INFO_LEN    24
#define C_SINCE_LEN         23
#define H_DATE_LEN          23
#define OL_DELIVERY_D_LEN   23
#define O_ENTRY_D_LEN       23

// Functions in random.c

```

```

void          seed();
long          irand();
double        drand();
void          WUCreate();
short        WURand();
long         RandomNumber(long lower, long upper);

// Functions in getargs.c;
void         GetArgsLoader();
void         GetArgsLoaderUsage();

// Functions in time.c
long         TimeNow();

// Functions in strings.c
void         MakeAddress();
void         LastName();
int          MakeAlphaString();
int          MakeAlphaStringPadded();
int          MakeOriginalAlphaString();
int          MakeNumberString();
int          MakeZipNumberString();
void         InitString();
void         InitAddress();
void         PaddString();

```

tpccldr.c

```

//=====
// File: TPCCCLR.C
// Microsoft TPC-C Kit Ver. 4.51
// Copyright Microsoft, 1996, 1997, 1998, 1999,
// 2000, 2001, 2002, 2003
// Purpose: Source file for TPC-C database loader
//=====
// Includes
#include "tpcc.h"
#include "search.h"

// Defines
#define MAXITEMS              100000
#define MAXITEMS_SCALE_DOWN  100
#define CUSTOMERS_PER_DISTRICT 3000
#define CUSTOMERS_SCALE_DOWN  30
#define DISTRICT_PER_WAREHOUSE 10
#define ORDERS_PER_DISTRICT  3000
#define ORDERS_SCALE_DOWN    30
#define MAX_CUSTOMER_THREADS  2
#define MAX_ORDER_THREADS     3
#define MAX_MAIN_THREADS      4
#define MAX_SQL_ERRORS         10

// Functions declarations
void HandleErrorDBC (SQLHDBC hdbc1);
long NURand();
void LoadItem();
void LoadWarehouse();
void Stock();
void District();
void LoadCustomer();
void CustomerBufInit();
void CustomerBufLoad();

```

```

void LoadCustomerTable();
void LoadHistoryTable();
void LoadOrders();
void OrdersBufInit();
void OrdersBufLoad();
void LoadOrdersTable();
void LoadNewOrderTable();
void LoadOrderLineTable();
void GetPermutation();
void CheckForCommit();
void CheckForCommit_Big();
void OpenConnections();
void BuildIndex();
void FormatDate ();

// Shared memory structures
typedef struct
{
    double          ol;
    long            ol_i_id;
    long            ol_supply_w_id;
    short           ol_quantity;
    double          ol_amount;
    char            ol_dist_info[DIST_INFO_LEN+1];
    char            ol_delivery_d[OL_DELIVERY_D_LEN+1];
} ORDER_LINE_STRUCT;

typedef struct
{
    long            o_id;
    short           o_d_id;
    long            o_w_id;
    long            o_c_id;
    short           o_carrier_id;
    short           o_ol_cnt;
    short           o_all_local;
    ORDER_LINE_STRUCT o_ol[15];
} ORDERS_STRUCT;

typedef struct
{
    long            c_id;
    short           c_d_id;
    long            c_w_id;
    char            c_first[FIRST_NAME_LEN+1];
    char            c_middle[MIDDLE_NAME_LEN+1];
    char            c_last[LAST_NAME_LEN+1];
    char            c_street_1[ADDRESS_LEN+1];
    char            c_street_2[ADDRESS_LEN+1];
    char            c_city[ADDRESS_LEN+1];
    char            c_state[STATE_LEN+1];
    char            c_zip[ZIP_LEN+1];
    char            c_phone[PHONE_LEN+1];
    char            c_credit[CREDIT_LEN+1];
    double          c_credit_lim;
    double          c_discount;
    char            c_balance[6];
    double          c_ytd_payment;
    short           c_payment_cnt;
    short           c_delivery_cnt;
    char            c_data[C_DATA_LEN+1];
    double          h_amount;

```

```

char            h_data[H_DATA_LEN+1];
} CUSTOMER_STRUCT;

typedef struct
{
    char            c_last[LAST_NAME_LEN+1];
    char            c_first[FIRST_NAME_LEN+1];
    long            c_id;
} CUSTOMER_SORT_STRUCT;

typedef struct
{
    long            time_start;
} LOADER_TIME_STRUCT;

// Global variables
char            szLastError[300];
HENV            henv;

HDBC            v_hdbc; // for SQL
Server version verification
HDBC            i_hdbc1; // for ITEM table
HDBC            w_hdbc1; // for WAREHOUSE,
DISTRICT, STOCK
HDBC            c_hdbc1; // for CUSTOMER
HDBC            c_hdbc2; // for HISTORY
HDBC            o_hdbc1; // for ORDERS
HDBC            o_hdbc2; // for NEW-ORDER

HDBC            o_hdbc3; // for ORDER-LINE

HSTMT           v_hstmt; // for SQL Server
version verification
HSTMT           i_hstmt1;
HSTMT           w_hstmt1;
HSTMT           c_hstmt1, c_hstmt2;
HSTMT           o_hstmt1, o_hstmt2, o_hstmt3;

int            total_db_errors;

ORDERS_STRUCT  orders_buf[ORDERS_PER_DISTRICT];
CUSTOMER_STRUCT customer_buf[CUSTOMERS_PER_DISTRICT];
long            orders_rows_loaded;
double          new_order_rows_loaded;
double          order_line_rows_loaded;
long            history_rows_loaded;
long            customer_rows_loaded;
double          stock_rows_loaded;
long            district_rows_loaded;
long            item_rows_loaded;
long            warehouse_rows_loaded;
long            main_time_start;
long            main_time_end;
long            max_items;
long            customers_per_district;
long            orders_per_district;
long            first_new_order;
long            last_new_order;

TPCCLDR_ARGS  *aptr, args;

```

```

//=====
//
// Function name: main
//
//=====
int main(int argc, char **argv)
{
    DWORD          dwThreadID[MAX_MAIN_THREADS];
    HANDLE          hThread[MAX_MAIN_THREADS];
    FILE            *fLoader;
    char            buffer[255];
    int             i;

    for (i=0; i<MAX_MAIN_THREADS; i++)
        hThread[i] = NULL;

    printf("\n*****");
    printf("\n*");
    printf("\n* Microsoft SQL Server");
    printf("\n*");
    printf("\n*");
    printf("\n* TPC-C BENCHMARK KIT: Database loader");
    printf("\n*");
    printf("\n* Version %s");
    printf("\n*");
    printf("\n* TPCKIT_VER);
    printf("\n*");
    printf("\n*****\n\n");

    // process command line arguments
    aptr = &args;
    GetArgsLoader(argc, argv, aptr);

    printf("Build interface is ODBC.\n");

    if (aptr->build_index == 0)
        printf("Data load only - no index creation.\n");
    else
        printf("Data load and index creation.\n");

    if (aptr->index_order == 0)
        printf("Clustered indexes will be created after bulk load.\n");
    else
        printf("Clustered indexes will be created before bulk load.\n");

    // set database scale values
    if (aptr->scale_down == 1)
    {
        printf("*** Scaled Down Database ***\n");
        max_items = MAXITEMS_SCALE_DOWN;
        customers_per_district = CUSTOMERS_SCALE_DOWN;
        orders_per_district = ORDERS_SCALE_DOWN;
        first_new_order = 0;
        last_new_order = 30;
    }
    else
    {
        max_items = MAXITEMS;
        customers_per_district = CUSTOMERS_PER_DISTRICT;
        orders_per_district = ORDERS_PER_DISTRICT;
        first_new_order = 2100;
        last_new_order = 3000;
    }

    // open connections to SQL Server
    OpenConnections();
}

```

```

// open file for loader results
fLoader = fopen(aptr->loader_res_file, "w");

if (fLoader == NULL)
{
    printf("Error, loader result file open failed.");
    exit(-1);
}

// start loading data
sprintf(buffer, "TPC-C load started for %ld warehouses.\n", aptr->num_warehouses);
if (aptr->scale_down == 1)
{
    sprintf(buffer, "SCALED DOWN DATABASE.\n");
}

printf("%s", buffer);
fprintf(fLoader, "%s", buffer);

main_time_start = (TimeNow() / MILLI);

// start parallel load threads
if (aptr->tables_all || aptr->table_item)
{
    fprintf(fLoader, "\nStarting loader threads for: item\n");
    hThread[0] = CreateThread(NULL,
                                0,
                                (LPTHREAD_START_ROUTINE) LoadItem,
                                NULL,
                                0,
                                &dwThreadID[0]);
    if (hThread[0] == NULL)
    {
        printf("Error, failed in creating creating thread =
0.\n");
        exit(-1);
    }
    if (aptr->tables_all || aptr->table_warehouse)
    {
        fprintf(fLoader, "Starting loader threads for: warehouse\n");
        hThread[1] = CreateThread(NULL,
                                0,
                                (LPTHREAD_START_ROUTINE) LoadWarehouse,
                                NULL,
                                0,
                                &dwThreadID[1]);
        if (hThread[1] == NULL)
        {

```

```

                printf("Error, failed in creating creating thread =
1.\n");
                exit(-1);
            }
        }
        if (aptr->tables_all || aptr->table_customer)
        {
            fprintf(fLoader, "Starting loader threads for: customer\n");
            hThread[2] = CreateThread(NULL,
                                     0,
(LPTHREAD_START_ROUTINE) LoadCustomer,
NULL,
0,
&dwThreadID[2]);
            if (hThread[2] == NULL)
            {
                printf("Error, failed in creating creating main thread
= 2.\n");
                exit(-1);
            }
        }
        if (aptr->tables_all || aptr->table_orders)
        {
            fprintf(fLoader, "Starting loader threads for: orders\n");
            hThread[3] = CreateThread(NULL,
                                     0,
(LPTHREAD_START_ROUTINE) LoadOrders,
NULL,
0,
&dwThreadID[3]);
            if (hThread[3] == NULL)
            {
                printf("Error, failed in creating creating main thread
= 3.\n");
                exit(-1);
            }
        }
        // Wait for threads to finish...
        for (i=0; i<MAX_MAIN_THREADS; i++)
        {
            if (hThread[i] != NULL)
            {
                WaitForSingleObject( hThread[i], INFINITE );
                CloseHandle(hThread[i]);
                hThread[i] = NULL;
            }
        }
        main_time_end = (TimeNow() / MILLI);

```

```

sprintf(buffer, "\nTPC-C load completed successfully in %ld minutes.\n",
        (main_time_end - main_time_start)/60);

        printf("%s",buffer);
        fprintf(fLoader, "%s", buffer);

        fclose(fLoader);

        SQLFreeEnv(henv);

        exit(0);

        return 0;
    }

//=====
//
// Function name: LoadItem
//
//=====
void LoadItem()
{
    int          i;
    long         i_id;
    long         i_im_id;
    char         i_name[I_NAME_LEN+1];
    double       i_price;
    char         i_data[I_DATA_LEN+1];
    char         name[20];
    long         time_start;
    RETCODE      rc;
    DBINT        rcint;
    char         bcphint[128];
    char         err_log_path[256];

    // Seed with unique number
    seed(11);

    printf("Loading item table...\n");

    //if build index before load
    if ((aptr->build_index == 1) && (aptr->index_order == 1))
        BuildIndex("idxitmcl");

    InitString(i_name, I_NAME_LEN+1);
    InitString(i_data, I_DATA_LEN+1);

    sprintf(name, "%s.%s", aptr->database, "item");

    strcpy(err_log_path, aptr->log_path);
    strcat(err_log_path, "item.err");
    rc = bcp_init(i_hdbc1, name, NULL, err_log_path, DB_IN);
    if (rc != SUCCEEDED)
        HandleErrorDBC(i_hdbc1);

    if ((aptr->build_index == 1) && (aptr->index_order == 1))
    {
        sprintf(bcphint, "tablock, order (i_id), ROWS_PER_BATCH =
100000");
        rc = bcp_control(i_hdbc1, BCPHINTS, (void*) bcphint);
        if (rc != SUCCEEDED)
            HandleErrorDBC(i_hdbc1);
    }
}

```



```

    }
    i = 0;
    rc = bcp_bind(i_hdbc1, (BYTE *) &i_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(i_hdbc1);
    rc = bcp_bind(i_hdbc1, (BYTE *) i_name, 0, I_NAME_LEN, NULL, 0, 0, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(i_hdbc1);
    rc = bcp_bind(i_hdbc1, (BYTE *) &i_price, 0, SQL_VARLEN_DATA, NULL, 0,
SQLFLT8, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(i_hdbc1);
    rc = bcp_bind(i_hdbc1, (BYTE *) i_data, 0, SQL_VARLEN_DATA, "", 1, 0,
++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(i_hdbc1);
    rc = bcp_bind(i_hdbc1, (BYTE *) &i_im_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(i_hdbc1);

    time_start = (TimeNow() / MILLI);

    item_rows_loaded = 0;
    for (i_id = 1; i_id <= max_items; i_id++)
    {
        i_im_id = RandomNumber(1L, 10000L);
        MakeAlphaStringPadded(14, 24, I_NAME_LEN, i_name);
        i_price = ((float) RandomNumber(100L, 10000L))/100.0;
        MakeOriginalAlphaString(26, 50, I_DATA_LEN, i_data, 10);

        rc = bcp_sendrow(i_hdbc1);
        if (rc != SUCCEEDED)
            HandleErrorDBC(i_hdbc1);

        item_rows_loaded++;
        CheckForCommit(i_hdbc1, i_hstmt1, item_rows_loaded, "item",
&time_start);
    }

    rcint = bcp_done(i_hdbc1);
    if (rcint < 0)
        HandleErrorDBC(i_hdbc1);

    printf("Finished loading item table.\n");

    SQLFreeStmt(i_hstmt1, SQL_DROP);
    SQLDisconnect(i_hdbc1);
    SQLFreeConnect(i_hdbc1);

    // if build index after load
    if ((aptr->build_index == 1) && (aptr->index_order == 0))
        BuildIndex("idxitmc1");
}
//=====

```

```

//
// Function : LoadWarehouse
//
// Loads WAREHOUSE table and loads Stock and District as Warehouses are created
//
//=====
void LoadWarehouse()
{
    int i;
    long w_id;
    char w_name[W_NAME_LEN+1];
    char w_street_1[ADDRESS_LEN+1];
    char w_street_2[ADDRESS_LEN+1];
    char w_city[ADDRESS_LEN+1];
    char w_state[STATE_LEN+1];
    char w_zip[ZIP_LEN+1];
    double w_tax;
    double w_ytd;
    char name[20];
    long time_start;
    RETCODE rc;
    DBINT rcint;
    char bcphint[128];
    char err_log_path[256];

    // Seed with unique number
    seed(2);

    printf("Loading warehouse table...\n");

    // if build index before load...
    if ((aptr->build_index == 1) && (aptr->index_order == 1))
        BuildIndex("idxwarcl");

    InitString(w_name, W_NAME_LEN+1);
    InitAddress(w_street_1, w_street_2, w_city, w_state, w_zip);

    sprintf(name, "%s..%s", aptr->database, "warehouse");

    strcpy(err_log_path, aptr->log_path);
    strcat(err_log_path, "warehouse.err");
    rc = bcp_init(w_hdbc1, name, NULL, err_log_path, DB_IN);

    if (rc != SUCCEEDED)
        HandleErrorDBC(w_hdbc1);

    if ((aptr->build_index == 1) && (aptr->index_order == 1))
    {
        sprintf(bcphint, "tablock, order (w_id), ROWS_PER_BATCH = %d",
aptr->num_warehouses);
        rc = bcp_control(w_hdbc1, BCPHINTS, (void*) bcphint);
        if (rc != SUCCEEDED)
            HandleErrorDBC(w_hdbc1);
    }

    i = 0;
    rc = bcp_bind(w_hdbc1, (BYTE *) &w_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(w_hdbc1);
    rc = bcp_bind(w_hdbc1, (BYTE *) &w_ytd, 0, SQL_VARLEN_DATA, NULL, 0,
SQLFLT8, ++i);
    if (rc != SUCCEEDED)

```

```

        HandleErrorDBC(w_hdbc1);
rc = bcp_bind(w_hdbc1, (BYTE *) &w_tax, 0, SQL_VARLEN_DATA, NULL, 0,
SQLFLT8, ++i);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);
rc = bcp_bind(w_hdbc1, (BYTE *) w_name, 0, W_NAME_LEN, NULL, 0, 0, ++i);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);
rc = bcp_bind(w_hdbc1, (BYTE *) w_street_1, 0, ADDRESS_LEN, NULL, 0, 0,
++i);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);
rc = bcp_bind(w_hdbc1, (BYTE *) w_street_2, 0, ADDRESS_LEN, NULL, 0, 0,
++i);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);
rc = bcp_bind(w_hdbc1, (BYTE *) w_city, 0, ADDRESS_LEN, NULL, 0, 0, ++i);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);
rc = bcp_bind(w_hdbc1, (BYTE *) w_state, 0, STATE_LEN, NULL, 0, 0, ++i);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);
rc = bcp_bind(w_hdbc1, (BYTE *) w_zip, 0, ZIP_LEN, NULL, 0, 0, ++i);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

time_start = (TimeNow() / MILLI);

warehouse_rows_loaded = 0;

for (w_id = (long)aptr->starting_warehouse; w_id <= aptr->num_warehouses;
w_id++)
{
    MakeAlphaStringPadded(6,10, W_NAME_LEN, w_name);
    MakeAddress(w_street_1, w_street_2, w_city, w_state, w_zip);
    w_tax = ((float) RandomNumber(0L,2000L))/10000.00;
    w_ytd = 300000.00;
    rc = bcp_sendrow(w_hdbc1);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);
    warehouse_rows_loaded++;
    CheckForCommit(w_hdbc1, i_hstmt1, warehouse_rows_loaded,
"warehouse", &time_start);
}

rcint = bcp_done(w_hdbc1);
if (rcint < 0)
    HandleErrorDBC(w_hdbc1);

printf("Finished loading warehouse table.\n");

// if build index after load...
if ((aptr->build_index == 1) && (aptr->index_order == 0))
    BuildIndex("idxwarcl");

stock_rows_loaded = 0;
district_rows_loaded = 0;

```

```

District();
Stock();
}

//=====
//
// Function : District
//
//=====
void District()
{
    int i;
    short d_id;
    long d_w_id;
    char d_name[D_NAME_LEN+1];
    char d_street_1[ADDRESS_LEN+1];
    char d_street_2[ADDRESS_LEN+1];
    char d_city[ADDRESS_LEN+1];
    char d_state[STATE_LEN+1];
    char d_zip[ZIP_LEN+1];
    double d_tax;
    double d_ytd;
    char name[20];
    long d_next_o_id;
    long time_start;
    long w_id;
    RETCODE rc;
    DBINT rcint;
    char bcp hint[128];
    char err_log_path[256];

    // Seed with unique number
    seed(4);

    printf("Loading district table...\n");

    // build index before load
    if ((aptr->build_index == 1) && (aptr->index_order == 1))
        BuildIndex("idxdiscl");

    InitString(d_name, D_NAME_LEN+1);
    InitAddress(d_street_1, d_street_2, d_city, d_state, d_zip);
    sprintf(name, "%s.%s", aptr->database, "district");

    strcpy(err_log_path, aptr->log_path);
    strcat(err_log_path, "district.err");
    rc = bcp_init(w_hdbc1, name, NULL, err_log_path, DB_IN);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

    if ((aptr->build_index == 1) && (aptr->index_order == 1))
    {
        sprintf(bcp hint, "tablock, order (d_w_id, d_id), ROWS_PER_BATCH
= %u", (aptr->num_warehouses * 10));
        rc = bcp_control(w_hdbc1, BCPHINTS, (void*) bcp hint);
        if (rc != SUCCEED)
            HandleErrorDBC(w_hdbc1);
    }

    i = 0;
    rc = bcp_bind(w_hdbc1, (BYTE *) &d_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, ++i);
    if (rc != SUCCEED)

```

```

        HandleErrorDBC(w_hdbc1);
SQLINT4, rc = bcp_bind(w_hdbc1, (BYTE *) &d_w_id, 0, SQL_VARLEN_DATA, NULL, 0,
++i);
        if (rc != SUCCEEDED)
            HandleErrorDBC(w_hdbc1);
SQLFLT8, rc = bcp_bind(w_hdbc1, (BYTE *) &d_ytd, 0, SQL_VARLEN_DATA, NULL, 0,
++i);
        if (rc != SUCCEEDED)
            HandleErrorDBC(w_hdbc1);
SQLINT4, rc = bcp_bind(w_hdbc1, (BYTE *) &d_next_o_id, 0, SQL_VARLEN_DATA, NULL, 0,
++i);
        if (rc != SUCCEEDED)
            HandleErrorDBC(w_hdbc1);
SQLFLT8, rc = bcp_bind(w_hdbc1, (BYTE *) &d_tax, 0, SQL_VARLEN_DATA, NULL, 0,
++i);
        if (rc != SUCCEEDED)
            HandleErrorDBC(w_hdbc1);
        rc = bcp_bind(w_hdbc1, (BYTE *) d_name, 0, D_NAME_LEN, NULL, 0, 0, ++i);
        if (rc != SUCCEEDED)
            HandleErrorDBC(w_hdbc1);
++i);
        rc = bcp_bind(w_hdbc1, (BYTE *) d_street_1, 0, ADDRESS_LEN, NULL, 0, 0,
++i);
        if (rc != SUCCEEDED)
            HandleErrorDBC(w_hdbc1);
        rc = bcp_bind(w_hdbc1, (BYTE *) d_street_2, 0, ADDRESS_LEN, NULL, 0, 0,
++i);
        if (rc != SUCCEEDED)
            HandleErrorDBC(w_hdbc1);
        rc = bcp_bind(w_hdbc1, (BYTE *) d_city, 0, ADDRESS_LEN, NULL, 0, 0, ++i);
        if (rc != SUCCEEDED)
            HandleErrorDBC(w_hdbc1);
        rc = bcp_bind(w_hdbc1, (BYTE *) d_state, 0, STATE_LEN, NULL, 0, 0, ++i);
        if (rc != SUCCEEDED)
            HandleErrorDBC(w_hdbc1);
        rc = bcp_bind(w_hdbc1, (BYTE *) d_zip, 0, ZIP_LEN, NULL, 0, 0, ++i);
        if (rc != SUCCEEDED)
            HandleErrorDBC(w_hdbc1);

        d_ytd = 30000.0;

        d_next_o_id = orders_per_district+1;

        time_start = (TimeNow() / MILLI);

        for (w_id = aptr->starting_warehouse; w_id <= aptr->num_warehouses;
w_id++)
        {
            d_w_id = w_id;

            for (d_id = 1; d_id <= DISTRICT_PER_WAREHOUSE; d_id++)
            {
                MakeAlphaStringPadded(6,10,D_NAME_LEN, d_name);

                MakeAddress(d_street_1, d_street_2, d_city, d_state,

d_zip);

                d_tax = ((float) RandomNumber(0L,2000L))/10000.00;

                rc = bcp_sendrow(w_hdbc1);
                if (rc != SUCCEEDED)
                    HandleErrorDBC(w_hdbc1);

                district_rows_loaded++;

```

```

        CheckForCommit(w_hdbc1, w_hstmt1,
district_rows_loaded, "district", &time_start);
    }
}

rcint = bcp_done(w_hdbc1);
if (rcint < 0)
    HandleErrorDBC(w_hdbc1);

printf("Finished loading district table.\n");

// if build index after load...
if ((aptr->build_index == 1) && (aptr->index_order == 0))
    BuildIndex("idxdiscl");

return;
}

//=====
//
// Function : Stock
//
//=====
void Stock()
{
    int i;
    long s_i_id;
    long s_w_id;
    short s_quantity;
    char s_dist_01[S_DIST_LEN+1];
    char s_dist_02[S_DIST_LEN+1];
    char s_dist_03[S_DIST_LEN+1];
    char s_dist_04[S_DIST_LEN+1];
    char s_dist_05[S_DIST_LEN+1];
    char s_dist_06[S_DIST_LEN+1];
    char s_dist_07[S_DIST_LEN+1];
    char s_dist_08[S_DIST_LEN+1];
    char s_dist_09[S_DIST_LEN+1];
    char s_dist_10[S_DIST_LEN+1];
    long s_ytd;
    short s_order_cnt;
    short s_remote_cnt;
    char s_data[S_DATA_LEN+1];
    short len;
    char name[20];
    long time_start;
    RETCODE rc;
    DBINT rcint;
    char bcpint[128];
    char err_log_path[256];

    // Seed with unique number
    seed(3);

    // if build index before load...
    if ((aptr->build_index == 1) && (aptr->index_order == 1))
        BuildIndex("idxstkcl");

    sprintf(name, "%s.%s", aptr->database, "stock");

    strcpy(err_log_path, aptr->log_path);
    strcat(err_log_path, "stock.err");
    rc = bcp_init(w_hdbc1, name, NULL, err_log_path, DB_IN);

```

```

    if (rc != SUCCEEDED)
        HandleErrorDBC(w_hdbc1);

    if ((aptr->build_index == 1) && (aptr->index_order == 1))
    {
        sprintf(bcphint, "tablock, order (s_i_id, s_w_id),
ROWS_PER_BATCH = %u", (aptr->num_warehouses * 100000));
        rc = bcp_control(w_hdbc1, BCPHINTS, (void*) bcphint);
        if (rc != SUCCEEDED)
            HandleErrorDBC(w_hdbc1);
    }

    i = 0;
    rc = bcp_bind(w_hdbc1, (BYTE *) &s_i_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(w_hdbc1);
    rc = bcp_bind(w_hdbc1, (BYTE *) &s_w_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(w_hdbc1);
    rc = bcp_bind(w_hdbc1, (BYTE *) &s_quantity, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(w_hdbc1);
    rc = bcp_bind(w_hdbc1, (BYTE *) &s_ytd, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(w_hdbc1);
    rc = bcp_bind(w_hdbc1, (BYTE *) &s_order_cnt, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(w_hdbc1);
    rc = bcp_bind(w_hdbc1, (BYTE *) &s_remote_cnt, 0, SQL_VARLEN_DATA, NULL,
0, SQLINT2, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(w_hdbc1);
    rc = bcp_bind(w_hdbc1, (BYTE *) s_data, 0, SQL_VARLEN_DATA, "", 1, 0,
++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(w_hdbc1);
    rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_01, 0, S_DIST_LEN, NULL, 0, 0,
++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(w_hdbc1);
    rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_02, 0, S_DIST_LEN, NULL, 0, 0,
++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(w_hdbc1);
    rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_03, 0, S_DIST_LEN, NULL, 0, 0,
++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(w_hdbc1);
    rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_04, 0, S_DIST_LEN, NULL, 0, 0,
++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(w_hdbc1);
    rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_05, 0, S_DIST_LEN, NULL, 0, 0,
++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(w_hdbc1);
    rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_06, 0, S_DIST_LEN, NULL, 0, 0,
++i);

```

```

    if (rc != SUCCEEDED)
        HandleErrorDBC(w_hdbc1);
    rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_07, 0, S_DIST_LEN, NULL, 0, 0,
++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(w_hdbc1);
    rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_08, 0, S_DIST_LEN, NULL, 0, 0,
++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(w_hdbc1);
    rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_09, 0, S_DIST_LEN, NULL, 0, 0,
++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(w_hdbc1);
    rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_10, 0, S_DIST_LEN, NULL, 0, 0,
++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(w_hdbc1);

    s_ytd = s_order_cnt = s_remote_cnt = 0;

    time_start = (TimeNow() / MILLI);

    printf("...Loading stock table\n");

    for (s_i_id=1; s_i_id <= max_items; s_i_id++)
    {
        for (s_w_id = (long)aptr->starting_warehouse; s_w_id <= aptr-
>num_warehouses; s_w_id++)
        {
            s_quantity = (short)RandomNumber(10L,100L);
            len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_01);
            len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_02);
            len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_03);
            len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_04);
            len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_05);
            len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_06);
            len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_07);
            len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_08);
            len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_09);
            len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_10);

            len = MakeOriginalAlphaString(26,50, S_DATA_LEN,
s_data,10);

            rc = bcp_sendrow(w_hdbc1);
            if (rc != SUCCEEDED)
                HandleErrorDBC(w_hdbc1);

            stock_rows_loaded++;
            CheckForCommit_Big(w_hdbc1, w_hstmt1,
stock_rows_loaded, "stock", &time_start);
        }
    }

    rcint = bcp_done(w_hdbc1);
    if (rcint < 0)
        HandleErrorDBC(w_hdbc1);

    printf("Finished loading stock table.\n");

```

```

SQLFreeStmt(w_hstmt1, SQL_DROP);
SQLDisconnect(w_hdbc1);
SQLFreeConnect(w_hdbc1);

// if build index after load...
if ((aptr->build_index == 1) && (aptr->index_order == 0))
    BuildIndex("idxstkcl");

return;
}

//=====
//
// Function   : LoadCustomer
//
//=====
void LoadCustomer()
{
    LOADER_TIME_STRUCT    customer_time_start;
    LOADER_TIME_STRUCT    history_time_start;
    long                  w_id;

    short                  d_id;

    DWORD                  dwThreadID[MAX_CUSTOMER_THREADS];
    HANDLE                  hThread[MAX_CUSTOMER_THREADS];
    char                    name[20];

    RETCODE                  rc;
    DBINT                    rcint;
    char                      bcphint[128];
    char                      cmd[256];

    int                      num_procs;
    char                      err_log_path_cust[256];
    char                      err_log_path_hist[256];

    // Seed with unique number
    seed(5);

    printf("Loading customer and history tables...\n");

    // if build index before load...
    if ((aptr->build_index == 1) && (aptr->index_order == 1))
    {
        BuildIndex("idxcuscl");
        // check the number of processors on this system
        // if 8 or more processors, then build index on History.
        // if less than 8 processors, do not build the index
        num_procs = atoi(getenv( "NUMBER_OF_PROCESSORS" ));
        if ( num_procs >= 8 )
            BuildIndex("idxhiscl");
    }

    // Initialize bulk copy
    sprintf(name, "%s.%s", aptr->database, "customer");

    strcpy(err_log_path_cust, aptr->log_path);
    strcat(err_log_path_cust, "customer.err");
    rc = bcp_init(c_hdbc1, name, NULL, err_log_path_cust, DB_IN);
    if (rc != SUCCEED)
        HandleErrorDBC(c_hdbc1);

    if ((aptr->build_index == 1) && (aptr->index_order == 1))
    {
        sprintf(bcpint, "tablock, order (c_w_id, c_d_id, c_id),
ROWS_PER_BATCH = %u", (aptr->num_warehouses * 30000));

```

```

        rc = bcp_control(c_hdbc1, BCPHINTS, (void*) bcpint);
        if (rc != SUCCEED)
            HandleErrorDBC(c_hdbc1);
    }

    sprintf(name, "%s.%s", aptr->database, "history");

    rc = bcp_init(c_hdbc2, name, NULL, "logs\\history.err", DB_IN);
    strcpy(err_log_path_hist, aptr->log_path);
    strcat(err_log_path_hist, "history.err");
    rc = bcp_init(c_hdbc2, name, NULL, err_log_path_hist, DB_IN);
    if (rc != SUCCEED)
        HandleErrorDBC(c_hdbc2);

    sprintf(bcpint, "tablock");
    rc = bcp_control(c_hdbc2, BCPHINTS, (void*) bcpint);
    if (rc != SUCCEED)
        HandleErrorDBC(c_hdbc2);

    customer_rows_loaded    = 0;
    history_rows_loaded     = 0;

    CustomerBufInit();

    customer_time_start.time_start = (TimeNow() / MILLI);
    history_time_start.time_start = (TimeNow() / MILLI);

    for (w_id = (long)aptr->starting_warehouse; w_id <= aptr->num_warehouses;
w_id++)
    {
        for (d_id = 1; d_id <= DISTRICT_PER_WAREHOUSE; d_id++)
        {
            CustomerBufLoad(d_id, w_id);

            // Start parallel loading threads here...
            // Start customer table thread
            printf("...Loading customer table for: d_id = %d, w_id
= %d\n", d_id, w_id);

            hThread[0] = CreateThread(NULL,

0,

(LPTHREAD_START_ROUTINE) LoadCustomerTable,

&customer_time_start,

0,

&dwThreadID[0]);

            if (hThread[0] == NULL)
            {
                printf("Error, failed in creating creating
thread = 0.\n");
                exit(-1);
            }

            // Start History table thread
            printf("...Loading history table for: d_id = %d, w_id
= %d\n", d_id, w_id);

```

```

        hThread[1] = CreateThread(NULL,
0,
(LPTHREAD_START_ROUTINE) LoadHistoryTable,
&history_time_start,
0,
&dwThreadID[1]);

        if (hThread[1] == NULL)
        {
            printf("Error, failed in creating creating
thread = 1.\n");
            exit(-1);
        }

        WaitForSingleObject( hThread[0], INFINITE );
        WaitForSingleObject( hThread[1], INFINITE );

        if (CloseHandle(hThread[0]) == FALSE)
        {
            printf("Error, failed in closing customer
thread handle with errno: %d\n", GetLastError());
        }

        if (CloseHandle(hThread[1]) == FALSE)
        {
            printf("Error, failed in closing history
thread handle with errno: %d\n", GetLastError());
        }
    }

    // flush the bulk connection
    rcint = bcp_done(c_hdbc1);
    if (rcint < 0)
        HandleErrorDBC(c_hdbc1);

    rcint = bcp_done(c_hdbc2);
    if (rcint < 0)
        HandleErrorDBC(c_hdbc2);

    printf("Finished loading customer table.\n");

    // if build index after load...
    if ((aptr->build_index == 1) && (aptr->index_order == 0))
    {
        BuildIndex("idxcuscl");
        // check the number of processors on this system
        // if 8 or more processors, then build index on History.
        // if less than 8 processors, do not build the index
        num_procs = atoi(getenv( "NUMBER_OF_PROCESSORS" ));
        if (num_procs >= 8)
            BuildIndex("idxhiscl");
    }

    // build non-clustered index
    if (aptr->build_index == 1)
        BuildIndex("idxcusnc");

```

```

        // Output the NURAND used for the loader into C_FIRST for C_ID = 1,
        // C_W_ID = 1, and C_D_ID = 1
        sprintf(cmd, "osql -S%s -U%s -P%s -d%s -e -Q\"update customer set c_first
= 'C_LOAD = %d' where c_id = 1 and c_w_id = 1 and c_d_id = 1\" > %snurand_load.log",
        aptr->server,
        aptr->user,
        aptr->password,
        aptr->database,
        LOADER_NURAND_C,
        aptr->log_path);

        system(cmd);

        SQLFreeStmt(c_hstmt1, SQL_DROP);
        SQLDisconnect(c_hdbc1);
        SQLFreeConnect(c_hdbc1);

        SQLFreeStmt(c_hstmt2, SQL_DROP);
        SQLDisconnect(c_hdbc2);
        SQLFreeConnect(c_hdbc2);

    return;
}

//=====
//
// Function : CustomerBufInit
//
//=====
void CustomerBufInit()
{
    long i;

    for (i=0;i<customers_per_district;i++)
    {
        customer_buf[i].c_id = 0;
        customer_buf[i].c_d_id = 0;
        customer_buf[i].c_w_id = 0;

        strcpy(customer_buf[i].c_first,"");
        strcpy(customer_buf[i].c_middle,"");
        strcpy(customer_buf[i].c_last,"");
        strcpy(customer_buf[i].c_street_1,"");
        strcpy(customer_buf[i].c_street_2,"");
        strcpy(customer_buf[i].c_city,"");
        strcpy(customer_buf[i].c_state,"");
        strcpy(customer_buf[i].c_zip,"");
        strcpy(customer_buf[i].c_phone,"");
        strcpy(customer_buf[i].c_credit,"");

        customer_buf[i].c_credit_lim = 0;
        customer_buf[i].c_discount = (float) 0;

        strcpy(customer_buf[i].c_balance,"");

        customer_buf[i].c_ytd_payment = 0;
        customer_buf[i].c_payment_cnt = 0;
        customer_buf[i].c_delivery_cnt = 0;

        strcpy(customer_buf[i].c_data,"");

        customer_buf[i].h_amount = 0;
    }
}

```

```

        strcpy(customer_buf[i].h_data,"");
    }
}

//=====
//
// Function   : CustomerBufLoad
//
// Fills shared buffer for HISTORY and CUSTOMER
//=====
void CustomerBufLoad(int d_id, long w_id)
{
    long i;
    CUSTOMER_SORT_STRUCT c[CUSTOMERS_PER_DISTRICT];

    for (i=0;i<customers_per_district;i++)
    {
        if (i < 1000)
            LastName(i, c[i].c_last);
        else
            LastName(NURand(255,0,999,LOADER_NURAND_C),
c[i].c_last);

        MakeAlphaStringPadded(8,16,FIRST_NAME_LEN, c[i].c_first);

        c[i].c_id = i+1;
    }

    printf("...Loading customer buffer for: d_id = %d, w_id = %d\n",
        d_id, w_id);

    for (i=0;i<customers_per_district;i++)
    {
        customer_buf[i].c_d_id = d_id;
        customer_buf[i].c_w_id = w_id;
        customer_buf[i].h_amount = 10.0;
        customer_buf[i].c_ytd_payment = 10.0;
        customer_buf[i].c_payment_cnt = 1;
        customer_buf[i].c_delivery_cnt = 0;
        customer_buf[i].c_id = c[i].c_id;
        strcpy(customer_buf[i].c_first, c[i].c_first);
        strcpy(customer_buf[i].c_last, c[i].c_last);
        customer_buf[i].c_middle[0] = 'O';
        customer_buf[i].c_middle[1] = 'E';
        MakeAddress(customer_buf[i].c_street_1,
            customer_buf[i].c_street_2,
            customer_buf[i].c_city,
            customer_buf[i].c_state,
            customer_buf[i].c_zip);
        MakeNumberString(16, 16, PHONE_LEN, customer_buf[i].c_phone);

        if (RandomNumber(1L, 100L) > 10)
            customer_buf[i].c_credit[0] = 'G';
        else
            customer_buf[i].c_credit[0] = 'B';
        customer_buf[i].c_credit[1] = 'C';
        customer_buf[i].c_credit_lim = 50000.0;
        customer_buf[i].c_discount = ((float) RandomNumber(0L, 5000L)) /
10000.0;

        strcpy(customer_buf[i].c_balance,"-10.0");
        MakeAlphaStringPadded(300, 500, C_DATA_LEN,
customer_buf[i].c_data);
    }
}

```

```

        // Generate HISTORY data
        MakeAlphaStringPadded(12, 24, H_DATA_LEN,
customer_buf[i].h_data);
    }
}

//=====
//
// Function   : LoadCustomerTable
//
//=====
void LoadCustomerTable(LOADER_TIME_STRUCT *customer_time_start)
{
    long i;

    long c_id;
    short c_d_id;
    long c_w_id;
    char c_first[FIRST_NAME_LEN+1];
    char c_middle[MIDDLE_NAME_LEN+1];
    char c_last[LAST_NAME_LEN+1];
    char c_street_1[ADDRESS_LEN+1];
    char c_street_2[ADDRESS_LEN+1];
    char c_city[ADDRESS_LEN+1];
    char c_state[STATE_LEN+1];
    char c_zip[ZIP_LEN+1];
    char c_phone[PHONE_LEN+1];
    char c_credit[CREDIT_LEN+1];
    double c_credit_lim;
    double c_discount;

    char c_balance[6];
    double c_ytd_payment;
    short c_payment_cnt;
    short c_delivery_cnt;
    char c_data[C_DATA_LEN+1];
    char c_since[C_SINCE_LEN+1];
    RETCODE rc;

    i = 0;
    rc = bcp_bind(c_hdbc1, (BYTE *) &c_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(c_hdbc1);
    rc = bcp_bind(c_hdbc1, (BYTE *) &c_d_id, 0, SQL_VARLEN_DATA, NULL, 0, SQLINT2,
++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(c_hdbc1);
    rc = bcp_bind(c_hdbc1, (BYTE *) &c_w_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(c_hdbc1);
    rc = bcp_bind(c_hdbc1, (BYTE *) &c_discount, 0, SQL_VARLEN_DATA, NULL, 0,
SQLFLT8, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(c_hdbc1);
    rc = bcp_bind(c_hdbc1, (BYTE *) &c_credit_lim, 0, SQL_VARLEN_DATA, NULL, 0,
SQLFLT8, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(c_hdbc1);
    rc = bcp_bind(c_hdbc1, (BYTE *) c_last, 0, LAST_NAME_LEN, NULL, 0, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(c_hdbc1);
    rc = bcp_bind(c_hdbc1, (BYTE *) c_first, 0, FIRST_NAME_LEN, NULL, 0, 0,
++i);
}

```

```

        if (rc != SUCCEEDED)
            HandleErrorDBC(c_hdbc1);
    rc = bcp_bind(c_hdbc1, (BYTE *) c_credit, 0, CREDIT_LEN, NULL, 0, 0, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(c_hdbc1);
    rc = bcp_bind(c_hdbc1, (BYTE *) c_balance, 0, 5, NULL, 0, SQLCHARACTER, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(c_hdbc1);
    rc = bcp_bind(c_hdbc1, (BYTE *) &c_ytd_payment, 0, SQL_VARLEN_DATA, NULL, 0,
SQLPLT8, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(c_hdbc1);
    rc = bcp_bind(c_hdbc1, (BYTE *) &c_payment_cnt, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(c_hdbc1);
    rc = bcp_bind(c_hdbc1, (BYTE *) &c_delivery_cnt, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(c_hdbc1);
    rc = bcp_bind(c_hdbc1, (BYTE *) c_street_1, 0, ADDRESS_LEN, NULL, 0, 0, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(c_hdbc1);
    rc = bcp_bind(c_hdbc1, (BYTE *) c_street_2, 0, ADDRESS_LEN, NULL, 0, 0, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(c_hdbc1);
    rc = bcp_bind(c_hdbc1, (BYTE *) c_city, 0, ADDRESS_LEN, NULL, 0, 0, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(c_hdbc1);
    rc = bcp_bind(c_hdbc1, (BYTE *) c_state, 0, STATE_LEN, NULL, 0, 0, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(c_hdbc1);
    rc = bcp_bind(c_hdbc1, (BYTE *) c_zip, 0, ZIP_LEN, NULL, 0, 0, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(c_hdbc1);
    rc = bcp_bind(c_hdbc1, (BYTE *) c_phone, 0, PHONE_LEN, NULL, 0, 0, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(c_hdbc1);
    rc = bcp_bind(c_hdbc1, (BYTE *) &c_since, 0, C_SINCE_LEN, NULL, 0,
SQLCHARACTER, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(c_hdbc1);
    rc = bcp_bind(c_hdbc1, (BYTE *) c_middle, 0, MIDDLE_NAME_LEN, NULL, 0, 0,
++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(c_hdbc1);
    rc = bcp_bind(c_hdbc1, (BYTE *) c_data, 0, C_DATA_LEN, NULL, 0, 0, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(c_hdbc1);

for (i = 0; i < customers_per_district; i++)
{
    c_id = customer_buf[i].c_id;
    c_d_id = customer_buf[i].c_d_id;
    c_w_id = customer_buf[i].c_w_id;

    strcpy(c_first, customer_buf[i].c_first);
    strcpy(c_middle, customer_buf[i].c_middle);
    strcpy(c_last, customer_buf[i].c_last);
    strcpy(c_street_1, customer_buf[i].c_street_1);
    strcpy(c_street_2, customer_buf[i].c_street_2);
    strcpy(c_city, customer_buf[i].c_city);
    strcpy(c_state, customer_buf[i].c_state);

```

```

    strcpy(c_zip, customer_buf[i].c_zip);
    strcpy(c_phone, customer_buf[i].c_phone);
    strcpy(c_credit, customer_buf[i].c_credit);

    FormatDate(&c_since);

    c_credit_lim = customer_buf[i].c_credit_lim;
    c_discount = customer_buf[i].c_discount;
    strcpy(c_balance, customer_buf[i].c_balance);
    c_ytd_payment = customer_buf[i].c_ytd_payment;
    c_payment_cnt = customer_buf[i].c_payment_cnt;
    c_delivery_cnt = customer_buf[i].c_delivery_cnt;
    strcpy(c_data, customer_buf[i].c_data);

    // Send data to server
    rc = bcp_sendrow(c_hdbc1);
    if (rc != SUCCEEDED)
        HandleErrorDBC(c_hdbc1);

    customer_rows_loaded++;
    CheckForCommit(c_hdbc1, c_hstmt1, customer_rows_loaded,
"customer", &customer_time_start->time_start);
}
}

//=====
//
// Function : LoadHistoryTable
//
//=====
void LoadHistoryTable(LOADER_TIME_STRUCT *history_time_start)
{
    long        i;
    long        c_id;
    short       c_d_id;
    long        c_w_id;
    double      h_amount;
    char        h_data[H_DATA_LEN+1];
    char        h_date[H_DATE_LEN+1];
    RETCODE     rc;

    i = 0;
    rc = bcp_bind(c_hdbc2, (BYTE *) &c_id, 0, SQL_VARLEN_DATA, NULL, 0, SQLINT4,
++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(c_hdbc2);
    rc = bcp_bind(c_hdbc2, (BYTE *) &c_d_id, 0, SQL_VARLEN_DATA, NULL, 0, SQLINT2,
++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(c_hdbc2);
    rc = bcp_bind(c_hdbc2, (BYTE *) &c_w_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(c_hdbc2);
    rc = bcp_bind(c_hdbc2, (BYTE *) &c_d_id, 0, SQL_VARLEN_DATA, NULL, 0, SQLINT2,
++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(c_hdbc2);
    rc = bcp_bind(c_hdbc2, (BYTE *) &c_w_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(c_hdbc2);

```



```

        rc = bcp_bind(c_hdbc2, (BYTE *) &h_date, 0, H_DATE_LEN, NULL, 0,
SQLCHARACTER, ++i);
        if (rc != SUCCEEDED)
            HandleErrorDBC(c_hdbc2);
        rc = bcp_bind(c_hdbc2, (BYTE *) &h_amount, 0, SQL_VARLEN_DATA, NULL, 0, SQLFLT8,
++i);
        if (rc != SUCCEEDED)
            HandleErrorDBC(c_hdbc2);
        rc = bcp_bind(c_hdbc2, (BYTE *) h_data, 0, H_DATA_LEN, NULL, 0, 0, ++i);
        if (rc != SUCCEEDED)
            HandleErrorDBC(c_hdbc2);

        for (i = 0; i < customers_per_district; i++)
        {
            c_id = customer_buf[i].c_id;
            c_d_id = customer_buf[i].c_d_id;
            c_w_id = customer_buf[i].c_w_id;
            h_amount = customer_buf[i].h_amount;
            strcpy(h_data, customer_buf[i].h_data);

            FormatDate(&h_date);

            // send to server
            rc = bcp_sendrow(c_hdbc2);
            if (rc != SUCCEEDED)
                HandleErrorDBC(c_hdbc2);

            history_rows_loaded++;
            CheckForCommit(c_hdbc2, c_hstmt2, history_rows_loaded,
"history", &history_time_start->time_start);
        }
    }

//=====
//
// Function : LoadOrders
//
//=====
void LoadOrders()
{
    LOADER_TIME_STRUCT orders_time_start;
    LOADER_TIME_STRUCT new_order_time_start;
    LOADER_TIME_STRUCT order_line_time_start;
    long w_id;

    short d_id;

    DWORD dwThreadID[MAX_ORDER_THREADS];
    HANDLE hThread[MAX_ORDER_THREADS];
    char name[20];

    RETCODE rc;
    char bcphint[128];
    char err_log_path_ord[256];
    char err_log_path_nord[256];
    char err_log_path_ordl[256];

    // seed with unique number
    seed(6);

    printf("Loading orders...\n");

    // if build index before load...
    if ((aptr->build_index == 1) && (aptr->index_order == 1))
    {
        BuildIndex("idxordc1");

```

```

        BuildIndex("idxnodc1");
        BuildIndex("idxodlcl1");
    }

    // initialize bulk copy
    sprintf(name, "%s..%s", aptr->database, "orders");

    rc = bcp_init(o_hdbc1, name, NULL, "logs\\orders.err", DB_IN);
    strcpy(err_log_path_ord, aptr->log_path);
    strcat(err_log_path_ord, "orders.err");
    rc = bcp_init(o_hdbc1, name, NULL, err_log_path_ord, DB_IN);
    if (rc != SUCCEEDED)
        HandleErrorDBC(o_hdbc1);

    if ((aptr->build_index == 1) && (aptr->index_order == 1))
    {
        sprintf(bcphint, "tablock, order (o_w_id, o_d_id, o_id),
ROWS_PER_BATCH = %u", (aptr->num_warehouses * 30000));
        rc = bcp_control(o_hdbc1, BCPHINTS, (void*) bcphint);
        if (rc != SUCCEEDED)
            HandleErrorDBC(o_hdbc1);
    }

    sprintf(name, "%s..%s", aptr->database, "new_order");

    rc = bcp_init(o_hdbc2, name, NULL, "logs\\neword.err", DB_IN);
    strcpy(err_log_path_nord, aptr->log_path);
    strcat(err_log_path_nord, "neword.err");
    rc = bcp_init(o_hdbc2, name, NULL, err_log_path_nord, DB_IN);
    if (rc != SUCCEEDED)
        HandleErrorDBC(o_hdbc2);

    if ((aptr->build_index == 1) && (aptr->index_order == 1))
    {
        sprintf(bcphint, "tablock, order (no_w_id, no_d_id, no_o_id),
ROWS_PER_BATCH = %u", (aptr->num_warehouses * 9000));
        rc = bcp_control(o_hdbc2, BCPHINTS, (void*) bcphint);
        if (rc != SUCCEEDED)
            HandleErrorDBC(o_hdbc2);
    }

    sprintf(name, "%s..%s", aptr->database, "order_line");

    rc = bcp_init(o_hdbc3, name, NULL, "logs\\ordline.err", DB_IN);
    strcpy(err_log_path_ordl, aptr->log_path);
    strcat(err_log_path_ordl, "ordline.err");
    rc = bcp_init(o_hdbc3, name, NULL, err_log_path_ordl, DB_IN);
    if (rc != SUCCEEDED)
        HandleErrorDBC(o_hdbc3);

    if ((aptr->build_index == 1) && (aptr->index_order == 1))
    {
        sprintf(bcphint, "tablock, order (ol_w_id, ol_d_id, ol_o_id,
ol_number), ROWS_PER_BATCH = %u", (aptr->num_warehouses * 300000));
        rc = bcp_control(o_hdbc3, BCPHINTS, (void*) bcphint);
        if (rc != SUCCEEDED)
            HandleErrorDBC(o_hdbc3);
    }

    orders_rows_loaded = 0;
    new_order_rows_loaded = 0;
    order_line_rows_loaded = 0;

```

```

OrdersBufInit();

orders_time_start.time_start = (TimeNow() / MILLI);
new_order_time_start.time_start = (TimeNow() / MILLI);
order_line_time_start.time_start = (TimeNow() / MILLI);

w_id++)
for (w_id = (long)aptr->starting_warehouse; w_id <= aptr->num_warehouses;
{
    for (d_id = 1; d_id <= DISTRICT_PER_WAREHOUSE; d_id++)
    {
        OrdersBufLoad(d_id, w_id);

        // start parallel loading threads here...
        // start Orders table thread
        printf("...Loading Order Table for: d_id = %d, w_id =
%d\n", d_id, w_id);

        hThread[0] = CreateThread(NULL,

            0,

            (LPTHREAD_START_ROUTINE) LoadOrdersTable,

            &orders_time_start,

            0,

            &dwThreadID[0]);

        if (hThread[0] == NULL)
        {
            printf("Error, failed in creating creating
thread = 0.\n");
            exit(-1);
        }

        // start NewOrder table thread
        printf("...Loading New-Order Table for: d_id = %d,
w_id = %d\n", d_id, w_id);

        hThread[1] = CreateThread(NULL,

            0,

            (LPTHREAD_START_ROUTINE) LoadNewOrderTable,

            &new_order_time_start,

            0,

            &dwThreadID[1]);

        if (hThread[1] == NULL)
        {
            printf("Error, failed in creating creating
thread = 1.\n");
            exit(-1);
        }

        // start Order-Line table thread

```

```

        printf("...Loading Order-Line Table for: d_id = %d,
w_id = %d\n", d_id, w_id);

        hThread[2] = CreateThread(NULL,

            0,

            (LPTHREAD_START_ROUTINE) LoadOrderLineTable,

            &order_line_time_start,

            0,

            &dwThreadID[2]);

        if (hThread[2] == NULL)
        {
            printf("Error, failed in creating creating
thread = 2.\n");
            exit(-1);
        }

        WaitForSingleObject( hThread[0], INFINITE );
        WaitForSingleObject( hThread[1], INFINITE );
        WaitForSingleObject( hThread[2], INFINITE );

        if (CloseHandle(hThread[0]) == FALSE)
        {
            printf("Error, failed in closing Orders
thread handle with errno: %d\n", GetLastError());
        }

        if (CloseHandle(hThread[1]) == FALSE)
        {
            printf("Error, failed in closing NewOrder
thread handle with errno: %d\n", GetLastError());
        }

        if (CloseHandle(hThread[2]) == FALSE)
        {
            printf("Error, failed in closing OrderLine
thread handle with errno: %d\n", GetLastError());
        }
    }

    printf("Finished loading orders.\n");

    return;
}

//=====
//
// Function : OrdersBufInit
//
// Clears shared buffer for ORDERS, NEWORDER, and ORDERLINE
//
//=====
void OrdersBufInit()
{
    int i;
    int j;

```

```

for (i=0;i<orders_per_district;i++)
{
    orders_buf[i].o_id = 0;
    orders_buf[i].o_d_id = 0;
    orders_buf[i].o_w_id = 0;
    orders_buf[i].o_c_id = 0;
    orders_buf[i].o_carrier_id = 0;
    orders_buf[i].o_ol_cnt = 0;
    orders_buf[i].o_all_local = 0;

    for (j=0;j<=14;j++)
    {
        orders_buf[i].o_ol[j].ol = 0;
        orders_buf[i].o_ol[j].ol_i_id = 0;
        orders_buf[i].o_ol[j].ol_supply_w_id = 0;
        orders_buf[i].o_ol[j].ol_quantity = 0;
        orders_buf[i].o_ol[j].ol_amount = 0;
        strcpy(orders_buf[i].o_ol[j].ol_dist_info,"");
    }
}

//=====
//
// Function   : OrdersBufLoad
//
// Fills shared buffer for ORDERS, NEWORDER, and ORDERLINE
//
//=====
void OrdersBufLoad(short d_id, long w_id)
{
    int    cust[ORDERS_PER_DISTRICT+1];
    long   o_id;
    long   ol;

    printf("...Loading Order Buffer for: d_id = %d, w_id = %d\n",
           d_id, w_id);

    GetPermutation(cust, orders_per_district);

    for (o_id=0;o_id<orders_per_district;o_id++)
    {
        // Generate ORDER and NEW-ORDER data
        orders_buf[o_id].o_d_id = d_id;
        orders_buf[o_id].o_w_id = w_id;
        orders_buf[o_id].o_id = o_id+1;
        orders_buf[o_id].o_c_id = cust[o_id+1];
        orders_buf[o_id].o_ol_cnt = (short)RandomNumber(5L, 15L);

        if (o_id < first_new_order)
        {
            orders_buf[o_id].o_carrier_id =
(short)RandomNumber(1L, 10L);
            orders_buf[o_id].o_all_local = 1;
        }
        else
        {
            orders_buf[o_id].o_carrier_id = 0;
            orders_buf[o_id].o_all_local = 1;
        }

        for (ol=0; ol<orders_buf[o_id].o_ol_cnt; ol++)

```

```

{
    orders_buf[o_id].o_ol[ol].ol = ol+1;
    orders_buf[o_id].o_ol[ol].ol_i_id = RandomNumber(1L,
max_items);
    orders_buf[o_id].o_ol[ol].ol_supply_w_id = w_id;
    orders_buf[o_id].o_ol[ol].ol_quantity = 5;
    MakeAlphaString(24, 24, OL_DIST_INFO_LEN,
&orders_buf[o_id].o_ol[ol].ol_dist_info);

    // Generate ORDER-LINE data
    if (o_id < first_new_order)
    {
        orders_buf[o_id].o_ol[ol].ol_amount = 0;
        // Added to insure ol_delivery_d set
properly during load

        FormatDate(&orders_buf[o_id].o_ol[ol].ol_delivery_d);
    }
    else
    {
        orders_buf[o_id].o_ol[ol].ol_amount =
RandomNumber(1,999999)/100.0;
        // Added to insure ol_delivery_d set
properly during load
        // odbc datetime format

        strcpy(orders_buf[o_id].o_ol[ol].ol_delivery_d,"1899-12-31 00:00:00.000");
    }
}

//=====
//
// Function   : LoadOrdersTable
//
//=====
void LoadOrdersTable(LOADER_TIME_STRUCT *orders_time_start)
{
    int    i;
    long   o_id;
    short  o_d_id;
    long   o_w_id;
    long   o_c_id;
    short  o_carrier_id;
    short  o_ol_cnt;
    short  o_all_local;
    char   o_entry_d[O_ENTRY_D_LEN+1];
    RETCODE rc;
    DBINT  rcint;

    // bind ORDER data
    i = 0;
    rc = bcp_bind(o_hdbc1, (BYTE *) &o_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(o_hdbc1);
    rc = bcp_bind(o_hdbc1, (BYTE *) &o_d_id, 0, SQL_VARLEN_DATA, NULL, 0, SQLINT2,
++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(o_hdbc1);

```

```

        rc = bcp_bind(o_hdbc1, (BYTE *) &o_w_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, ++i);
        if (rc != SUCCEEDED)
            HandleErrorDBC(o_hdbc1);
        rc = bcp_bind(o_hdbc1, (BYTE *) &o_c_id, 0, SQL_VARLEN_DATA, NULL, 0, SQLINT4,
++i);
        if (rc != SUCCEEDED)
            HandleErrorDBC(o_hdbc1);
        rc = bcp_bind(o_hdbc1, (BYTE *) &o_carrier_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, ++i);
        if (rc != SUCCEEDED)
            HandleErrorDBC(o_hdbc1);
        rc = bcp_bind(o_hdbc1, (BYTE *) &o_ol_cnt, 0, SQL_VARLEN_DATA, NULL, 0, SQLINT2,
++i);
        if (rc != SUCCEEDED)
            HandleErrorDBC(o_hdbc1);
        rc = bcp_bind(o_hdbc1, (BYTE *) &o_all_local, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, ++i);
        if (rc != SUCCEEDED)
            HandleErrorDBC(o_hdbc1);
        rc = bcp_bind(o_hdbc1, (BYTE *) &o_entry_d, 0, O_ENTRY_D_LEN, NULL, 0,
SQLCHARACTER, ++i);
        if (rc != SUCCEEDED)
            HandleErrorDBC(o_hdbc1);

    for (i = 0; i < orders_per_district; i++)
    {
        o_id      = orders_buf[i].o_id;
        o_d_id    = orders_buf[i].o_d_id;
        o_w_id    = orders_buf[i].o_w_id;
        o_c_id    = orders_buf[i].o_c_id;
        o_carrier_id = orders_buf[i].o_carrier_id;
        o_ol_cnt  = orders_buf[i].o_ol_cnt;
        o_all_local = orders_buf[i].o_all_local;

        FormatDate(&o_entry_d);

        // send data to server
        rc = bcp_sendrow(o_hdbc1);
        if (rc != SUCCEEDED)
            HandleErrorDBC(o_hdbc1);

        orders_rows_loaded++;
        CheckForCommit(o_hdbc1, o_hstmt1, orders_rows_loaded, "orders",
&orders_time_start->time_start);
    }

    if ((o_w_id == aptr->num_warehouses) && (o_d_id == 10))
    {
        rcint = bcp_done(o_hdbc1);
        if (rcint < 0)
            HandleErrorDBC(o_hdbc1);

        SQLFreeStmt(o_hstmt1, SQL_DROP);
        SQLDisconnect(o_hdbc1);
        SQLFreeConnect(o_hdbc1);

        // if build index after load...
        if ((aptr->build_index == 1) && (aptr->index_order == 0))
            BuildIndex("idxordc1");

        // build non-clustered index
        if (aptr->build_index == 1)

```

```

        BuildIndex("idxordnc");
    }
}

//=====
//
// Function : LoadNewOrderTable
//
//=====
void LoadNewOrderTable(LOADER_TIME_STRUCT *new_order_time_start)
{
    long    i;
    long    o_id;
    short   o_d_id;
    long    o_w_id;
    RETCODE rc;
    DBINT   rcint;

    // Bind NEW-ORDER data
    i = 0;
    rc = bcp_bind(o_hdbc2, (BYTE *) &o_id, 0, SQL_VARLEN_DATA, NULL, 0, SQLINT4,
++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(o_hdbc2);
    rc = bcp_bind(o_hdbc2, (BYTE *) &o_d_id, 0, SQL_VARLEN_DATA, NULL, 0, SQLINT2,
++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(o_hdbc2);
    rc = bcp_bind(o_hdbc2, (BYTE *) &o_w_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(o_hdbc2);

    for (i = first_new_order; i < last_new_order; i++)
    {
        o_id = orders_buf[i].o_id;
        o_d_id = orders_buf[i].o_d_id;
        o_w_id = orders_buf[i].o_w_id;

        rc = bcp_sendrow(o_hdbc2);
        if (rc != SUCCEEDED)
            HandleErrorDBC(o_hdbc2);

        new_order_rows_loaded++;
        CheckForCommit_Big(o_hdbc2, o_hstmt2, new_order_rows_loaded,
"new_order", &new_order_time_start->time_start);
    }

    if ((o_w_id == aptr->num_warehouses) && (o_d_id == 10))
    {
        rcint = bcp_done(o_hdbc2);
        if (rcint < 0)
            HandleErrorDBC(o_hdbc2);

        SQLFreeStmt(o_hstmt2, SQL_DROP);
        SQLDisconnect(o_hdbc2);
        SQLFreeConnect(o_hdbc2);

        // if build index after load...
        if ((aptr->build_index == 1) && (aptr->index_order == 0))
            BuildIndex("idxnodc1");
    }
}

```

```

//=====
//
// Function   : LoadOrderLineTable
//
//=====
void LoadOrderLineTable(LOADER_TIME_STRUCT *order_line_time_start)
{
    long          i;
    long          j;
    long          o_id;
    short         o_d_id;
    long          o_w_id;
    double        ol;
    long          ol_i_id;
    long          ol_supply_w_id;
    short         ol_quantity;
    double        ol_amount;
    char          ol_dist_info[DIST_INFO_LEN+1];
    char          ol_delivery_d[OL_DELIVERY_D_LEN+1];
    RETCODE      rc;
    DBINT        rcint;

    // bind ORDER-LINE data
    i = 0;
    rc = bcp_bind(o_hdbc3, (BYTE *) &o_id, 0, SQL_VARLEN_DATA, NULL, 0, SQLINT4,
++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(o_hdbc3);
    rc = bcp_bind(o_hdbc3, (BYTE *) &o_d_id, 0, SQL_VARLEN_DATA, NULL, 0, SQLINT2,
++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(o_hdbc3);
    rc = bcp_bind(o_hdbc3, (BYTE *) &o_w_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(o_hdbc3);
    rc = bcp_bind(o_hdbc3, (BYTE *) &ol, 0, SQL_VARLEN_DATA, NULL, 0, SQLFLT8,
++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(o_hdbc3);
    rc = bcp_bind(o_hdbc3, (BYTE *) &ol_i_id, 0, SQL_VARLEN_DATA, NULL, 0, SQLINT4,
++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(o_hdbc3);
    rc = bcp_bind(o_hdbc3, (BYTE *) &ol_delivery_d, 0, OL_DELIVERY_D_LEN,
NULL, 0, SQLCHARACTER, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(o_hdbc3);
    rc = bcp_bind(o_hdbc3, (BYTE *) &ol_amount, 0, SQL_VARLEN_DATA, NULL, 0,
SQLFLT8, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(o_hdbc3);
    rc = bcp_bind(o_hdbc3, (BYTE *) &ol_supply_w_id, 0, SQL_VARLEN_DATA, NULL,
0, SQLINT4, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(o_hdbc3);
    rc = bcp_bind(o_hdbc3, (BYTE *) &ol_quantity, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, ++i);
    if (rc != SUCCEEDED)
        HandleErrorDBC(o_hdbc3);
    rc = bcp_bind(o_hdbc3, (BYTE *) ol_dist_info, 0, DIST_INFO_LEN, NULL, 0, 0,
++i);
}

```

```

if (rc != SUCCEEDED)
    HandleErrorDBC(o_hdbc3);

for (i = 0; i < orders_per_district; i++)
{
    o_id = orders_buf[i].o_id;
    o_d_id = orders_buf[i].o_d_id;
    o_w_id = orders_buf[i].o_w_id;

    for (j=0; j < orders_buf[i].o_ol_cnt; j++)
    {
        ol = orders_buf[i].o_ol[j].ol;
        ol_i_id = orders_buf[i].o_ol[j].ol_i_id;
        ol_supply_w_id = orders_buf[i].o_ol[j].ol_supply_w_id;
        ol_quantity = orders_buf[i].o_ol[j].ol_quantity;
        ol_amount = orders_buf[i].o_ol[j].ol_amount;

        strcpy(ol_delivery_d, orders_buf[i].o_ol[j].ol_delivery_d);

        strcpy(ol_dist_info, orders_buf[i].o_ol[j].ol_dist_info);

        rc = bcp_sendrow(o_hdbc3);
        if (rc != SUCCEEDED)
            HandleErrorDBC(o_hdbc3);

        order_line_rows_loaded++;

        CheckForCommit_Big(o_hdbc3, o_hstmt3,
order_line_rows_loaded, "order_line", &order_line_time_start->time_start);
    }
}

if ((o_w_id == aptr->num_warehouses) && (o_d_id == 10))
{
    rcint = bcp_done(o_hdbc3);
    if (rcint < 0)
        HandleErrorDBC(o_hdbc3);

    SQLFreeStmt(o_hstmt3, SQL_DROP);
    SQLDisconnect(o_hdbc3);
    SQLFreeConnect(o_hdbc3);

    // if build index after load...
    if ((aptr->build_index == 1) && (aptr->index_order == 0))
        BuildIndex("idxodlcl");
}
}

//=====
//
// Function   : GetPermutation
//
//=====
void GetPermutation(int perm[], int n)
{
    int i, r, t;

    for (i=1; i<=n; i++)
        perm[i] = i;

    for (i=1; i<=n; i++)

```

```

    {
        r = RandomNumber(i,n);
        t = perm[i];
        perm[i] = perm[r];
        perm[r] = t;
    }
}

//=====
//
// Function   : CheckForCommit
//
//=====
void CheckForCommit(HDBC hdbc,
                   HSTMT hstmt,
                   long rows_loaded,
                   char *table_name,
                   long *time_start)
{
    long time_end, time_diff;

    if ( !(rows_loaded % aptr->batch) )
    {
        time_end = (TimeNow() / MILLI);
        time_diff = time_end - *time_start;

        printf("-> Loaded %ld rows into %s in %ld sec - Total = %d (%.2f
rps)\n",
            aptr->batch,
            table_name,
            time_diff,
            rows_loaded,
            (float) aptr->batch / (time_diff ? time_diff
: 1L));

        *time_start = time_end;
    }

    return;
}

//=====
//
// Function   : CheckForCommit_Big
//
//=====
void CheckForCommit_Big(HDBC hdbc,
                       HSTMT hstmt,
                       double rows_loaded,
                       char *table_name,
                       long *time_start)
{
    long time_end, time_diff;

    if ( !(fmod(rows_loaded,aptr->batch) ) )
    {
        time_end = (TimeNow() / MILLI);
        time_diff = time_end - *time_start;

        printf("-> Loaded %ld rows into %s in %ld sec - Total = %.0f
(%.2f rps)\n",

```

```

        aptr->batch,
        table_name,
        time_diff,
        rows_loaded,
        (float) aptr->batch / (time_diff ? time_diff
: 1L));

        *time_start = time_end;
    }

    return;
}

//=====
//
// Function   : OpenConnections
//
//=====
void OpenConnections()
{
    RETCODE rc;

    char szDriverString[300];
    char szDriverStringOut[1024];
    SQLSMALLINT cbDriverStringOut;

    SQLAllocHandle(SQL_HANDLE_ENV, SQL_NULL_HANDLE, &henv );

    SQLSetEnvAttr(henv, SQL_ATTR_ODBC_VERSION, (void*)SQL_OV_ODBC3, 0 );

    SQLAllocHandle(SQL_HANDLE_DBC, henv, &i_hdbc1);
    SQLAllocHandle(SQL_HANDLE_DBC, henv, &w_hdbc1);
    SQLAllocHandle(SQL_HANDLE_DBC, henv, &c_hdbc1);
    SQLAllocHandle(SQL_HANDLE_DBC, henv, &c_hdbc2);
    SQLAllocHandle(SQL_HANDLE_DBC, henv, &o_hdbc1);
    SQLAllocHandle(SQL_HANDLE_DBC, henv, &o_hdbc2);
    SQLAllocHandle(SQL_HANDLE_DBC, henv, &o_hdbc3);

    SQLSetConnectAttr(i_hdbc1, SQL_COPT_SS_BCP, (void *)SQL_BCP_ON,
SQL_IS_INTEGER );
    SQLSetConnectAttr(w_hdbc1, SQL_COPT_SS_BCP, (void *)SQL_BCP_ON,
SQL_IS_INTEGER );
    SQLSetConnectAttr(c_hdbc1, SQL_COPT_SS_BCP, (void *)SQL_BCP_ON,
SQL_IS_INTEGER );
    SQLSetConnectAttr(c_hdbc2, SQL_COPT_SS_BCP, (void *)SQL_BCP_ON,
SQL_IS_INTEGER );
    SQLSetConnectAttr(o_hdbc1, SQL_COPT_SS_BCP, (void *)SQL_BCP_ON,
SQL_IS_INTEGER );
    SQLSetConnectAttr(o_hdbc2, SQL_COPT_SS_BCP, (void *)SQL_BCP_ON,
SQL_IS_INTEGER );
    SQLSetConnectAttr(o_hdbc3, SQL_COPT_SS_BCP, (void *)SQL_BCP_ON,
SQL_IS_INTEGER );

    // Open connections to SQL Server
    // Connection 1
    sprintf( szDriverString, "DRIVER={SQL
Server};SERVER=%s;UID=%s;PWD=%s;DATABASE=%s" ,
            aptr->server,
            aptr->user,
            aptr->password,
            aptr->database );

```

```

rc = SQLSetConnectOption (i_hdbc1, SQL_PACKET_SIZE, aptr->pack_size);
if (rc != SUCCEEDED)
    HandleErrorDBC(i_hdbc1);

rc = SQLDriverConnect ( i_hdbc1,
                        NULL,
                        (SQLCHAR*)&szDriverString[0] ,
                        SQL_NTS,
                        (SQLCHAR*)&szDriverStringOut[0],
                        sizeof(szDriverStringOut),
                        &cbDriverStringOut,
                        SQL_DRIVER_NOPROMPT );

if ( (rc != SUCCEEDED) &&
      (rc != SQL_SUCCESS_WITH_INFO) )
{
    HandleErrorDBC(i_hdbc1);
    printf("TPC-C Loader aborted!\n");
    exit(9);
}

// Connection 2
sprintf( szDriverString , "DRIVER={SQL
Server};SERVER=%s;UID=%s;PWD=%s;DATABASE=%s" ,
                                                aptr->server,
                                                aptr->user,
                                                aptr->password,
                                                aptr->database );

rc = SQLSetConnectOption (w_hdbc1, SQL_PACKET_SIZE, aptr->pack_size);
if (rc != SUCCEEDED)
    HandleErrorDBC(w_hdbc1);

rc = SQLDriverConnect ( w_hdbc1,
                        NULL,
                        (SQLCHAR*)&szDriverString[0] ,
                        SQL_NTS,
                        (SQLCHAR*)&szDriverStringOut[0],
                        sizeof(szDriverStringOut),
                        &cbDriverStringOut,
                        SQL_DRIVER_NOPROMPT );

if ( (rc != SUCCEEDED) &&
      (rc != SQL_SUCCESS_WITH_INFO) )
{
    HandleErrorDBC(w_hdbc1);
    printf("TPC-C Loader aborted!\n");
    exit(9);
}

// Connection 3
sprintf( szDriverString , "DRIVER={SQL
Server};SERVER=%s;UID=%s;PWD=%s;DATABASE=%s" ,
                                                aptr->server,

```

```

                                                aptr->user,
                                                aptr->password,
                                                aptr->database );

rc = SQLSetConnectOption (c_hdbc1, SQL_PACKET_SIZE, aptr->pack_size);
if (rc != SUCCEEDED)
    HandleErrorDBC(c_hdbc1);

rc = SQLDriverConnect ( c_hdbc1,
                        NULL,
                        (SQLCHAR*)&szDriverString[0] ,
                        SQL_NTS,
                        (SQLCHAR*)&szDriverStringOut[0],
                        sizeof(szDriverStringOut),
                        &cbDriverStringOut,
                        SQL_DRIVER_NOPROMPT );

if ( (rc != SUCCEEDED) &&
      (rc != SQL_SUCCESS_WITH_INFO) )
{
    HandleErrorDBC(c_hdbc1);
    printf("TPC-C Loader aborted!\n");
    exit(9);
}

// Connection 4
sprintf( szDriverString , "DRIVER={SQL
Server};SERVER=%s;UID=%s;PWD=%s;DATABASE=%s" ,
                                                aptr->server,
                                                aptr->user,
                                                aptr->password,
                                                aptr->database );

rc = SQLSetConnectOption (c_hdbc2, SQL_PACKET_SIZE, aptr->pack_size);
if (rc != SUCCEEDED)
    HandleErrorDBC(c_hdbc2);

rc = SQLDriverConnect ( c_hdbc2,
                        NULL,
                        (SQLCHAR*)&szDriverString[0] ,
                        SQL_NTS,
                        (SQLCHAR*)&szDriverStringOut[0],
                        sizeof(szDriverStringOut),
                        &cbDriverStringOut,
                        SQL_DRIVER_NOPROMPT );

if ( (rc != SUCCEEDED) &&
      (rc != SQL_SUCCESS_WITH_INFO) )
{
    HandleErrorDBC(c_hdbc2);
    printf("TPC-C Loader aborted!\n");
    exit(9);
}

// Connection 5

```

```

        sprintf( szDriverString , "DRIVER={SQL
Server};SERVER=%s;UID=%s;PWD=%s;DATABASE=%s" ,
                                aptr->server,
                                aptr->user,
                                aptr->password,
                                aptr->database );

rc = SQLSetConnectOption (o_hdbc1, SQL_PACKET_SIZE, aptr->pack_size);
if (rc != SUCCEEDED)
    HandleErrorDBC(o_hdbc1);

rc = SQLDriverConnect ( o_hdbc1,
                        NULL,
                        (SQLCHAR*)&szDriverString[0] ,
                        SQL_NTS,
                        (SQLCHAR*)&szDriverStringOut[0],
                        sizeof(szDriverStringOut),
                        &cbDriverStringOut,
                        SQL_DRIVER_NOPROMPT );
if ( (rc != SUCCEEDED) &&
      (rc != SQL_SUCCESS_WITH_INFO) )
{
    HandleErrorDBC(o_hdbc1);
    printf("TPC-C Loader aborted!\n");
    exit(9);
}

// Connection 6
sprintf( szDriverString , "DRIVER={SQL
Server};SERVER=%s;UID=%s;PWD=%s;DATABASE=%s" ,
                                aptr->server,
                                aptr->user,
                                aptr->password,
                                aptr->database );

rc = SQLSetConnectOption (o_hdbc2, SQL_PACKET_SIZE, aptr->pack_size);
if (rc != SUCCEEDED)
    HandleErrorDBC(o_hdbc2);

rc = SQLDriverConnect ( o_hdbc2,
                        NULL,
                        (SQLCHAR*)&szDriverString[0] ,
                        SQL_NTS,
                        (SQLCHAR*)&szDriverStringOut[0],
                        sizeof(szDriverStringOut),
                        &cbDriverStringOut,
                        SQL_DRIVER_NOPROMPT );
if ( (rc != SUCCEEDED) &&
      (rc != SQL_SUCCESS_WITH_INFO) )
{
    HandleErrorDBC(o_hdbc2);
    printf("TPC-C Loader aborted!\n");
    exit(9);
}

```

```

}

// Connection 7
sprintf( szDriverString , "DRIVER={SQL
Server};SERVER=%s;UID=%s;PWD=%s;DATABASE=%s" ,
                                aptr->server,
                                aptr->user,
                                aptr->password,
                                aptr->database );

rc = SQLSetConnectOption (o_hdbc3, SQL_PACKET_SIZE, aptr->pack_size);
if (rc != SUCCEEDED)
    HandleErrorDBC(o_hdbc3);

rc = SQLDriverConnect ( o_hdbc3,
                        NULL,
                        (SQLCHAR*)&szDriverString[0] ,
                        SQL_NTS,
                        (SQLCHAR*)&szDriverStringOut[0],
                        sizeof(szDriverStringOut),
                        &cbDriverStringOut,
                        SQL_DRIVER_NOPROMPT );
if ( (rc != SUCCEEDED) &&
      (rc != SQL_SUCCESS_WITH_INFO) )
{
    HandleErrorDBC(o_hdbc3);
    printf("TPC-C Loader aborted!\n");
    exit(9);
}

}

//=====
//
// Function name: BuildIndex
//
//=====
void BuildIndex(char *index_script)
{
    char cmd[256];

    printf("Starting index creation: %s\n",index_script);

    sprintf(cmd, "osql -S%s -U%s -P%s -e -i%s\\%s.sql > %s%s.log",
            aptr->server,
            aptr->user,
            aptr->password,
            aptr->index_script_path,
            index_script,
            aptr->log_path,
            index_script);

    system(cmd);

    printf("Finished index creation: %s\n",index_script);
}

//=====
//

```



```

// Function name: HandleErrorDBC
//
//=====
void HandleErrorDBC (SQLHDBC hdbc1)
{
    SQLCHAR          SqlState[6], Msg[SQL_MAX_MESSAGE_LENGTH];
    SQLLEN           NativeError;
    SQLSMALLINT i, MsgLen;
    SQLRETURN rc2;
    char             timebuf[128];
    char             datebuf[128];
    char             err_log_path[256];
    FILE             *fpl;

    i = 1;
    while (( rc2 = SQLGetDiagRec(SQL_HANDLE_DBC , hdbc1, i, SqlState ,
    &NativeError,
                                Msg, sizeof(Msg) , &MsgLen )) !=
SQL_NO_DATA )
    {
        sprintf( szLastError , "%s" , Msg );
        _strtime(timebuf);
        _strdate(datebuf);

        printf( "[%s : %s] %s\n==>SQLState: %s\n" , datebuf, timebuf,
szLastError, SqlState);

        strcpy(err_log_path,aptr->log_path);
        strcat(err_log_path,"tpccldr.err");
        fpl = fopen(err_log_path,"a+");
        if (fpl == NULL)
            printf("ERROR: Unable to open errorlog file.\n");
        else
        {
            fprintf(fpl, "[%s : %s] %s\nSQLState: %s\n" , datebuf,
timebuf, szLastError, SqlState);
            fclose(fpl);
        }

        i++;
    }
}

//=====
//
// Function : HandleErrorSTMT
//
//=====
void HandleErrorSTMT (HSTMT hstmt1)
{
    SQLCHAR          SqlState[6], Msg[SQL_MAX_MESSAGE_LENGTH];
    SQLLEN           NativeError;
    SQLSMALLINT i, MsgLen;
    SQLRETURN rc2;
    char             timebuf[128];
    char             datebuf[128];
    char             err_log_path[256];
    FILE             *fpl;

    i = 1;

```

```

        while (( rc2 = SQLGetDiagRec(SQL_HANDLE_STMT , hstmt1, i, SqlState ,
    &NativeError,
                                Msg, sizeof(Msg) , &MsgLen )) !=
SQL_NO_DATA )
    {
        if (total_db_errors >= MAX_SQL_ERRORS)
        {
            printf(">>>> Maximum SQL errors of %d exceeded.
Terminating TPCCLDR.<<<<\n",total_db_errors);
            exit(9);
        }
        total_db_errors++;

        sprintf( szLastError , "%s" , Msg );
        _strtime(timebuf);
        _strdate(datebuf);

        printf( "[%s : %s] %s\nSQLState: %s\n" , datebuf, timebuf,
szLastError, SqlState);

        strcpy(err_log_path,aptr->log_path);
        strcat(err_log_path,"tpccldr.err");
        fpl = fopen(err_log_path,"a+");
        if (fpl == NULL)
            printf("ERROR: Unable to open errorlog file.\n");
        else
        {
            fprintf(fpl, "[%s : %s] %s\nSQLState: %s\n" , datebuf,
timebuf, szLastError, SqlState);
            fclose(fpl);
        }

        i++;
    }
}

//=====
//
// Function : FormatDate
//
//=====
void FormatDate ( char* szTimeCOutput )
{
    struct tm when;
    time_t now;

    time( &now );
    when = *localtime( &now );

    mktime( &when );

    // odbc datetime format
    strftime( szTimeCOutput , 30 , "%Y-%m-%d %H:%M:%S.000" , &when );

    return;
}

```

VerifyTpccLoad.sql

```

-- File:  VerifyTPCCLoad.SQL
--      Microsoft TPC-C Benchmark Kit Ver. 4.62
--      Copyright Microsoft, 2005
-----
SET NOCOUNT ON
PRINT ' '
SELECT CONVERT(CHAR(30), GETDATE(), 21)
PRINT ' '

USE      tpcc
GO

IF EXISTS (SELECT name
           FROM sysobjects
           WHERE name = 'TPCC_INFO' AND
                 type = 'U')
    DROP TABLE TPCC_INFO
GO
PRINT 'WAREHOUSE TABLE'
SELECT count_big(*)
FROM warehouse
GO

PRINT 'DISTRICT TABLE = (10 * No of warehouses)'
SELECT count_big(*)
FROM district
GO

PRINT 'ITEM TABLE = 100,000'
SELECT count_big(*)
FROM item
GO

PRINT 'CUSTOMER TABLE = (30,000 * No of warehouses)'
SELECT count_big(*)
FROM customer
GO

PRINT 'ORDERS TABLE = (30,000 * No of warehouses)'
SELECT count_big(*)
FROM orders
GO

PRINT 'HISTORY TABLE = (30,000 * No of warehouses)'
SELECT count_big(*)
FROM history
GO

PRINT 'STOCK TABLE = (100,000 * No of warehouses)'
SELECT count_big(*)
FROM stock
GO

PRINT 'ORDER_LINE TABLE = (300,000 * No of warehouses + some change)'
SELECT count_big(*)
FROM order_line
GO

PRINT 'NEW_ORDER TABLE = (9000 * No of warehouses)'
SELECT count_big(*)
FROM new_order
GO

```

```

CREATE TABLE TPCC_INFO
(
    INFO_DATE          datetime,
    NUM_WAREHOUSE      bigint,
    WAREHOUSE_TARGET  bigint,
    NUM_DISTRICT       bigint,
    DISTRICT_TARGET   bigint,
    NUM_ITEM           bigint,
    ITEM_TARGET        bigint,
    NUM_CUSTOMER       bigint,
    CUSTOMER_TARGET    bigint,
    NUM_ORDERS         bigint,
    ORDERS_TARGET      bigint,
    ORDERS_TARGET_LOW  bigint,
    ORDERS_TARGET_HIGH bigint,
    NUM_ORDER_LINE     bigint,
    ORDER_LINE_TARGET  bigint,
    ORDER_LINE_TARGET_LOW  bigint,
    ORDER_LINE_TARGET_HIGH  bigint,
    NUM_NEW_ORDER      bigint,
    NEW_ORDER_TARGET  bigint,
    NEW_ORDER_TARGET_LOW  bigint,
    NEW_ORDER_TARGET_HIGH  bigint,
    NUM_HISTORY        bigint,
    HISTORY_TARGET     bigint,
    NUM_STOCK          bigint,
    STOCK_TARGET       bigint)
GO

DECLARE @NUM_WAREHOUSE      bigint,
        @WAREHOUSE_TARGET  bigint,
        @NUM_DISTRICT       bigint,
        @DISTRICT_TARGET   bigint,
        @NUM_ITEM           bigint,
        @ITEM_TARGET        bigint,
        @NUM_CUSTOMER       bigint,
        @CUSTOMER_TARGET    bigint,
        @NUM_ORDERS         bigint,
        @ORDERS_TARGET      bigint,
        @ORDERS_TARGET_LOW  bigint,
        @ORDERS_TARGET_HIGH  bigint,
        @NUM_ORDER_LINE     bigint,
        @ORDER_LINE_TARGET  bigint,
        @ORDER_LINE_TARGET_LOW  bigint,
        @ORDER_LINE_TARGET_HIGH  bigint,
        @NUM_NEW_ORDER      bigint,
        @NEW_ORDER_TARGET  bigint,
        @NEW_ORDER_TARGET_LOW  bigint,
        @NEW_ORDER_TARGET_HIGH  bigint,
        @NUM_HISTORY        bigint,
        @HISTORY_TARGET     bigint,
        @NUM_STOCK          bigint,
        @STOCK_TARGET       bigint

-- set the local variables prior to inserting them into the TPCC_INFO table
SELECT @NUM_WAREHOUSE      = COUNT_BIG(*)
FROM warehouse

SELECT @NUM_DISTRICT       = COUNT_BIG(*)
FROM district

SELECT @NUM_ITEM           = COUNT_BIG(*)
FROM item

```

```

SELECT @NUM_CUSTOMER      = COUNT_BIG(*)
FROM   customer

SELECT @NUM_ORDERS        = COUNT_BIG(*)
FROM   orders

SELECT @NUM_ORDER_LINE    = COUNT_BIG(*)
FROM   order_line

SELECT @NUM_NEW_ORDER     = COUNT_BIG(*)
FROM   new_order

SELECT @NUM_HISTORY       = COUNT_BIG(*)
FROM   history

SELECT @NUM_STOCK         = COUNT_BIG(*)
FROM   stock

--- now calculate and set the target values
SELECT @WAREHOUSE_TARGET = @NUM_WAREHOUSE,
       @DISTRICT_TARGET  = @NUM_WAREHOUSE * 10,
       @ITEM_TARGET      = 100000,
       @CUSTOMER_TARGET  = @NUM_WAREHOUSE * 30000,
       @ORDERS_TARGET    = @NUM_WAREHOUSE * 30000,
       @ORDERS_TARGET_LOW = @ORDERS_TARGET - FLOOR(@ORDERS_TARGET * .01),
       @ORDERS_TARGET_HIGH = @ORDERS_TARGET + FLOOR(@ORDERS_TARGET * .01),
       @ORDER_LINE_TARGET = @NUM_WAREHOUSE * 300000,
       @ORDER_LINE_TARGET_LOW = @ORDER_LINE_TARGET - FLOOR(@ORDER_LINE_TARGET *
.01),
       @ORDER_LINE_TARGET_HIGH = @ORDER_LINE_TARGET + FLOOR(@ORDER_LINE_TARGET *
.01),
       @NEW_ORDER_TARGET = @NUM_WAREHOUSE * 9000,
       @NEW_ORDER_TARGET_LOW = @NEW_ORDER_TARGET - FLOOR(@NEW_ORDER_TARGET *
.01),
       @NEW_ORDER_TARGET_HIGH = @NEW_ORDER_TARGET + FLOOR(@NEW_ORDER_TARGET *
.01),
       @HISTORY_TARGET    = @NUM_WAREHOUSE * 30000,
       @STOCK_TARGET      = @NUM_WAREHOUSE * 100000

--- insert the values into TPCC_INFO
INSERT INTO TPCC_INFO VALUES (GETDATE(),
                              @NUM_WAREHOUSE,
                              @WAREHOUSE_TARGET,
                              @NUM_DISTRICT,
                              @DISTRICT_TARGET,
                              @NUM_ITEM,
                              @ITEM_TARGET,
                              @NUM_CUSTOMER,
                              @CUSTOMER_TARGET,
                              @NUM_ORDERS,
                              @ORDERS_TARGET,
                              @ORDERS_TARGET_LOW,
                              @ORDERS_TARGET_HIGH,
                              @NUM_ORDER_LINE,
                              @ORDER_LINE_TARGET,
                              @ORDER_LINE_TARGET_LOW,
                              @ORDER_LINE_TARGET_HIGH,
                              @NUM_NEW_ORDER,
                              @NEW_ORDER_TARGET,
                              @NEW_ORDER_TARGET_LOW,
                              @NEW_ORDER_TARGET_HIGH,
                              @NUM_HISTORY,

```

```

                              @HISTORY_TARGET,
                              @NUM_STOCK,
                              @STOCK_TARGET)

GO

--- output the row counts from the build
PRINT ''
PRINT ''
PRINT '-----'
PRINT '|   WAREHOUSE TABLE   |'
PRINT '-----'
SELECT TOP 1
  CONVERT(CHAR(30),INFO_DATE,21) AS 'Date',
  NUM_WAREHOUSE                  AS 'Warehouse Rows',
  WAREHOUSE_TARGET              AS 'Warehouse Target',
  CASE WHEN (NUM_WAREHOUSE = WAREHOUSE_TARGET)
    THEN 'OK!'
    ELSE 'ERROR!!!'
  END                            AS 'Warehouse Message'
FROM TPCC_INFO
GO

PRINT ''
PRINT ''
PRINT '-----'
PRINT '|   DISTRICT TABLE   |'
PRINT '-----'
SELECT TOP 1
  CONVERT(CHAR(30),INFO_DATE,21) AS 'Date',
  NUM_DISTRICT                  AS 'District Rows',
  DISTRICT_TARGET              AS 'District Target',
  CASE WHEN (NUM_DISTRICT = DISTRICT_TARGET)
    THEN 'OK!'
    ELSE 'ERROR!!!'
  END                            AS 'District Message'
FROM TPCC_INFO
GO

PRINT ''
PRINT ''
PRINT '-----'
PRINT '|   ITEM TABLE   |'
PRINT '-----'
SELECT TOP 1
  CONVERT(CHAR(30),INFO_DATE,21) AS 'Date',
  NUM_ITEM                      AS 'Item Rows',
  ITEM_TARGET                  AS 'Item Target',
  CASE WHEN (NUM_ITEM = ITEM_TARGET)
    THEN 'OK!'
    ELSE 'ERROR!!!'
  END                            AS 'Item Message'
FROM TPCC_INFO
GO

PRINT ''
PRINT ''
PRINT '-----'
PRINT '|   CUSTOMER TABLE   |'
PRINT '-----'
SELECT TOP 1
  CONVERT(CHAR(30),INFO_DATE,21) AS 'Date',
  NUM_CUSTOMER                  AS 'Customer Rows',
  CUSTOMER_TARGET              AS 'Customer Target',

```

```

CASE WHEN (NUM_CUSTOMER = CUSTOMER_TARGET)
THEN 'OK!'
ELSE 'ERROR!!!'
END AS 'Customer Message'
FROM TPCC_INFO
GO

PRINT ''
PRINT ''
PRINT '-----'
PRINT '| ORDERS TABLE |'
PRINT '-----'
SELECT TOP 1
CONVERT (CHAR(30),INFO_DATE,21) AS 'Date',
NUM_ORDERS AS 'Orders Rows',
ORDERS_TARGET AS 'Orders Target',
CASE WHEN (NUM_ORDERS = ORDERS_TARGET)
THEN 'OK!'
WHEN (NUM_ORDERS BETWEEN ORDERS_TARGET_LOW AND ORDERS_TARGET_HIGH)
THEN 'OK! (within 1%)'
ELSE 'ERROR!!!'
END AS 'Orders Message'
FROM TPCC_INFO
GO

PRINT ''
PRINT ''
PRINT '-----'
PRINT '| ORDER LINE TABLE |'
PRINT '-----'
SELECT TOP 1
CONVERT (CHAR(30),INFO_DATE,21) AS 'Date',
NUM_ORDER_LINE AS 'Order Line Rows',
ORDER_LINE_TARGET AS 'Order Line Target',
CASE WHEN (NUM_ORDER_LINE = ORDER_LINE_TARGET)
THEN 'OK!'
WHEN (NUM_ORDER_LINE BETWEEN ORDER_LINE_TARGET_LOW AND
ORDER_LINE_TARGET_HIGH)
THEN 'OK! (within 1%)'
ELSE 'ERROR!!!'
END AS 'Orders Message'
FROM TPCC_INFO
GO

PRINT ''
PRINT ''
PRINT '-----'
PRINT '| NEW ORDER TABLE |'
PRINT '-----'
SELECT TOP 1
CONVERT (CHAR(30),INFO_DATE,21) AS 'Date',
NUM_NEW_ORDER AS 'New Order Rows',
NEW_ORDER_TARGET AS 'New Order Target',
CASE WHEN (NUM_NEW_ORDER = NEW_ORDER_TARGET)
THEN 'OK!'
WHEN (NUM_NEW_ORDER BETWEEN NEW_ORDER_TARGET_LOW AND
NEW_ORDER_TARGET_HIGH)
THEN 'OK! (within 1%)'
ELSE 'ERROR!!!'
END AS 'New Order Message'
FROM TPCC_INFO
GO

```

```

PRINT ''
PRINT ''
PRINT '-----'
PRINT '| HISTORY TABLE |'
PRINT '-----'
SELECT TOP 1
CONVERT (CHAR(30),INFO_DATE,21) AS 'Date',
NUM_HISTORY AS 'History Rows',
HISTORY_TARGET AS 'History Target',
CASE WHEN (NUM_HISTORY = HISTORY_TARGET)
THEN 'OK!'
ELSE 'ERROR!!!'
END AS 'New Order Message'
FROM TPCC_INFO
GO

PRINT ''
PRINT ''
PRINT '-----'
PRINT '| STOCK TABLE |'
PRINT '-----'
SELECT TOP 1
CONVERT (CHAR(30),INFO_DATE,21) AS 'Date',
NUM_STOCK AS 'Stock Rows',
STOCK_TARGET AS 'Stock Target',
CASE WHEN (NUM_STOCK = STOCK_TARGET)
THEN 'OK!'
ELSE 'ERROR!!!'
END AS 'Stock Message'
FROM TPCC_INFO
GO

-----
-- Check Indexes
-----
USE tpcc
GO

PRINT ''
PRINT ''
PRINT '-----'
PRINT '| TPC-C INDEXES |'
PRINT '-----'
EXEC sp_helpindex warehouse
EXEC sp_helpindex district
EXEC sp_helpindex item
EXEC sp_helpindex customer
EXEC sp_helpindex orders
EXEC sp_helpindex order_line
EXEC sp_helpindex new_order
EXEC sp_helpindex history
EXEC sp_helpindex stock
GO

```

version.sql

```

-----
--
-- File: VERSION.SQL
-- Microsoft TPC-C Benchmark Kit Ver. 4.62
-- Copyright Microsoft, 2005
--

```

```
-- Extracts current version of SQL Server --
--
-----
USE master
GO

SELECT CONVERT(char(20), SERVERPROPERTY('ProductVersion')),
       CONVERT(char(20), SERVERPROPERTY('ProductLevel')),
       CONVERT(char(29), SERVERPROPERTY('Edition'))

GO

SELECT CONVERT(char(30), GETDATE(), 21)
GO
```

Neworder_new.sql

```
SET QUOTED_IDENTIFIER OFF
GO
SET ANSI_NULLS OFF
GO
-- 8666: full showplan text info (to see if rowset sharing)
dbcc traceon(8666)
go
-- prevent sort over tvf
dbcc traceon(8710)
go

use tpcc
go

drop procedure tpcc_neworder_new
go
-- neworder_new v2.5 6/23/05 PeterCa
-- lq stock/order_line/client. upd district & ins neworder.
-- cust/warehouse select together, ins order separate
-- uses rownumber to distinct w any transform
-- uses in-memory sort for distinct on iid,wid
-- uses charindex
-- will rollback if (@i_idX,@s_w_idX pairs not unique) OR (@i_idX not unique).
create proc tpcc_neworder_new
    @w_id int,
    @d_id tinyint,
    @c_id int,
    @o_ol_cnt tinyint,
    @o_all_local tinyint,
    @i_id1 int = 0, @s_w_id1 int = 0, @ol_qty1 smallint = 0,
    @i_id2 int = 0, @s_w_id2 int = 0, @ol_qty2 smallint = 0,
    @i_id3 int = 0, @s_w_id3 int = 0, @ol_qty3 smallint = 0,
    @i_id4 int = 0, @s_w_id4 int = 0, @ol_qty4 smallint = 0,
    @i_id5 int = 0, @s_w_id5 int = 0, @ol_qty5 smallint = 0,
    @i_id6 int = 0, @s_w_id6 int = 0, @ol_qty6 smallint = 0,
    @i_id7 int = 0, @s_w_id7 int = 0, @ol_qty7 smallint = 0,
    @i_id8 int = 0, @s_w_id8 int = 0, @ol_qty8 smallint = 0,
    @i_id9 int = 0, @s_w_id9 int = 0, @ol_qty9 smallint = 0,
    @i_id10 int = 0, @s_w_id10 int = 0, @ol_qty10 smallint = 0,
    @i_id11 int = 0, @s_w_id11 int = 0, @ol_qty11 smallint = 0,
    @i_id12 int = 0, @s_w_id12 int = 0, @ol_qty12 smallint = 0,
    @i_id13 int = 0, @s_w_id13 int = 0, @ol_qty13 smallint = 0,
    @i_id14 int = 0, @s_w_id14 int = 0, @ol_qty14 smallint = 0,
    @i_id15 int = 0, @s_w_id15 int = 0, @ol_qty15 smallint = 0
```

```
as
begin
declare @o_id int,
        @d_tax smallmoney,
        @o_entry_d datetime,
        @commit_flag tinyint

begin transaction n

-- get district tax and next available order id and update
-- insert corresponding row into new-order table
-- plus initialize local variables

update district
set @d_tax = d_tax,
    @o_id = d_next_o_id,
    d_next_o_id = d_next_o_id + 1,
    @o_entry_d = getdate(),
    @commit_flag = 1
output deleted.d_next_o_id,@d_id,@w_id into new_order
where d_w_id = @w_id and
      d_id = @d_id

-- update stock from stock join (item join (params))
-- output to orderline, output to client
-- NOTE: @@rowcount != @ol_o_cnt
-- if (@i_idX,@s_w_idX pairs not unique) OR (@i_idX not unique).
update stock
set s_ytd = s_ytd + info.ol_qty,
    s_quantity = s_quantity - info.ol_qty +
        case when (s_quantity - info.ol_qty < 10) then 91 else
            s_order_cnt = s_order_cnt + 1,
            s_remote_cnt = s_remote_cnt +
                case when (info.w_id = @w_id) then 0 else 1 end

0 end,

output @o_id,@d_id,@w_id,info.lino,
       info.i_id,"dec 31, 1899",
       info.i_price * info.ol_qty,
       info.w_id,info.ol_qty,
       case @d_id when 1 then inserted.s_dist_01
                 when 2 then inserted.s_dist_02
                 when 3 then inserted.s_dist_03
                 when 4 then inserted.s_dist_04
                 when 5 then inserted.s_dist_05
                 when 6 then inserted.s_dist_06
                 when 7 then inserted.s_dist_07
                 when 8 then inserted.s_dist_08
                 when 9 then inserted.s_dist_09
                 when 10 then inserted.s_dist_10
       end
into order_line

output info.i_name,inserted.s_quantity,
       case when ((charindex("ORIGINAL",info.i_data) > 0) and
                  (charindex("ORIGINAL",inserted.s_data) > 0)
       )
       then "B" else "G" end,
       info.i_price,info.i_price*info.ol_qty

from
```

```

stock inner join
(select iid,wid,
    lino,ol_qty,
    i_price,
    i_name,
    i_data
from
    (select iid,wid,lino,qty,
        row_number() over (partition by iid,wid order by iid,wid) from
        (select @i_id1,@s_w_id1,1,@ol_qty1 union all
        select @i_id2,@s_w_id2,2,@ol_qty2 union all
        select @i_id3,@s_w_id3,3,@ol_qty3 union all
        select @i_id4,@s_w_id4,4,@ol_qty4 union all
        select @i_id5,@s_w_id5,5,@ol_qty5 union all
        select @i_id6,@s_w_id6,6,@ol_qty6 union all
        select @i_id7,@s_w_id7,7,@ol_qty7 union all
        select @i_id8,@s_w_id8,8,@ol_qty8 union all
        select @i_id9,@s_w_id9,9,@ol_qty9 union all
        select @i_id10,@s_w_id10,10,@ol_qty10 union all
        select @i_id11,@s_w_id11,11,@ol_qty11 union all
        select @i_id12,@s_w_id12,12,@ol_qty12 union all
        select @i_id13,@s_w_id13,13,@ol_qty13 union all
        select @i_id14,@s_w_id14,14,@ol_qty14 union all
        select @i_id15,@s_w_id15,15,@ol_qty15) as uo1(iid,wid,lino,qty)
    ) as ol(iid,wid,lino,ol_qty,rownum)
inner join
    item (repeatableread) on i_id = iid -- filters out invalid items
    and rownum=1
) as info(i_id,w_id,lino,ol_qty,i_price,i_name,i_data)
on
    s_i_id      = info.i_id and
    s_w_id      = info.w_id

if (@@rowcount <> @o_ol_cnt) -- must have an invalid item
    select @commit_flag = 0 -- 2.4.2.3 requires rest to proceed

-- insert fresh row into orders table
insert into orders values (
    @o_id,
    @d_id,
    @w_id,
    @c_id,
    0,
    @o_ol_cnt,
    @o_all_local,
    @o_entry_d)

-- get customer last name, discount, and credit rating
-- get warehouse tax
-- return order_data to client

select w_tax,@d_tax,@o_id,
    c_last,c_discount,c_credit,
    @o_entry_d,@commit_flag
from
    warehouse(repeatableread),customer(repeatableread)
where
    w_id      = @w_id and
    c_id      = @c_id and
    c_w_id    = @w_id and
    c_d_id    = @d_id

-- @@rowcount checks that previous select found a valid customer

```

```

if (@@commit_flag = 1) and (@@rowcount = 1)
    commit transaction n
else -- all that work for nothing.
    rollback transaction n

end
go
set showplan_text on
go
{call tpcc_neworder_new(1,1,1,10,1,
1,1,1,2,1,1,3,1,1,4,1,1,5,1,1,6,1,1,7,1,1,8,1,1,9,1,1,10,1,1)}
go

```

Appendix C: Tunable Parameters

Microsoft SQL Server 2005 Startup Parameters

```
start sqlservr.exe -c -x -T3502 -T677 -T8011 -T8012 -
T8018 -T8019 -T661 -T8710 -T834
```

Where:

```
-c Start SQL Server independently of the
Windows NT Service Control Manager
-x Disables the keeping of CPU time and cache-
hit ratio statistics
-T3502-Prints a message to the SQL Server log at the
start and end of each checkpoint
-T8011-Disable diagnostics for resource monitor
-T8012-Disable ring buffer for scheduler
-T8018-Disable exceptions rung buffer
-T8019-Disable stack collection for exception ring
buffer
-T661-Disable ghost writer
-T677-Disable AM debug info
-T8710-Disable HP checks.
-T834-Enable large page support
File locations:
sqlservr.exe- C:\Program Files\Microsoft SQL
Server\MSSQL.1\MSSQL\Binn
ERRORLOG-C:\Program Files\Microsoft SQL
Server\MSSQL.1\MSSQL\LOG
```

Microsoft SQL Server 2005 Installation Procedures

```
Microsoft SQL Server 2005 Enterprise
Edition(x64) Installation Procedures.
Type of installation: custom
During the custom installation, use the default
```

settings for all except the following two areas:
Services accounts:
SQL Server - local system account
Set the sort order/collation as SQL Collation binary
sort order/Latin_1_General.
After initial setup the TCP ports for IPAll were
configured to 2001-2008, which correspond to client
TCP ports.

Microsoft SQL Server Configuration Parameters

sp_configure name	maximum	config_value	run_value	minimum
Ad Hoc Distributed Queries				0
1	0	0		
affinity I/O mask				-2147483648
2147483647	0	0		
affinity mask				-2147483648
2147483647	255	255		
affinity64 I/O mask				-2147483648
2147483647	0	0		
affinity64 mask				-2147483648
2147483647	0	0		
Agent XPs				0
1	0	0		
allow updates				0
1	0	0		
awe enabled				0
1	0	0		
blocked process threshold				0
86400	0	0		
c2 audit mode				0
1	0	0		
clr enabled				0
1	0	0		
cost threshold for parallelism				0
32767	5	5		
cross db ownership chaining				0
1	0	0		
cursor threshold				-1
2147483647	-1	-1		
Database Mail XPs				0
1	0	0		
default full-text language				0
2147483647	1033	1033		
default language				0
9999	0	0		
default trace enabled				0
1	1	1		
disallow results from triggers				0
1	0	0		

fill factor (%)				0
100	0	0		
ft crawl bandwidth (max)				0
32767	100	100		
ft crawl bandwidth (min)				0
32767	0	0		
ft notify bandwidth (max)				0
32767	100	100		
ft notify bandwidth (min)				0
32767	0	0		
in-doubt xact resolution				0
2	0	0		
index create memory (KB)				704
2147483647	704	704		
lightweight pooling				0
1	1	1		
locks				5000
2147483647	0	0		
max degree of parallelism				0
64	1	1		
max full-text crawl range				0
256	4	4		
max server memory (MB)				16
2147483647	125500	125500		
max text repl size (B)				0
2147483647	65536	65536		
max worker threads				128
32767	720	720		
media retention				0
365	0	0		
min memory per query (KB)				512
2147483647	512	512		
min server memory (MB)				0
2147483647	0	0		
nested triggers				0
1	1	1		
network packet size (B)				512
32767	2048	2048		
Ole Automation Procedures				0
1	0	0		
open objects				0
2147483647	0	0		
PH timeout (s)				1
3600	60	60		
precompute rank				0
1	0	0		
priority boost				0
1	1	1		
query governor cost limit				0
2147483647	0	0		
query wait (s)				-1
2147483647	-1	-1		
recovery interval (min)				0
32767	32767	32767		
remote access				0
1	1	1		
remote admin connections				0
1	0	0		
remote login timeout (s)				0
2147483647	20	20		
remote proc trans				0
1	0	0		

```

remote query timeout (s)          0
2147483647          600          600
Replication XPs                    0
1          0          0
scan for startup proc             0
1          0          0
server trigger recursion          0
1          1          1
set working set size              0
1          0          0
show advanced options             0
1          1          1
SMO and DMO XPs                   0
1          1          1
SQL Mail XPs                       0
1          0          0
transform noise words              0
1          0          0
two digit year cutoff             1753
9999          2049          2049
user connections                   0
32767          0          0
user options                       0
32767          0          0
Web Assistant Procedures           0
1          0          0
xp_cmdshell                        0
1          0          0

```

Database Server System Configuration

System Information report written at: 09/19/05
21:55:42
System Name: BOBCAT
[System Summary]

```

Item      Value
OS Name   Microsoft(R) Windows(R) Server 2003
Enterprise x64 Edition
Version   5.2.3790 Service Pack 1 Build 3790
Other OS Description   Not Available
OS Manufacturer   Microsoft Corporation
System Name       BOBCAT
System Manufacturer HP
System Model      ProLiant DL585 G1
System Type       x64-based PC
Processor AMD64 Family 15 Model 33 Stepping 2
AuthenticAMD ~2400 Mhz
Processor AMD64 Family 15 Model 33 Stepping 2
AuthenticAMD ~2400 Mhz
Processor AMD64 Family 15 Model 33 Stepping 2
AuthenticAMD ~2400 Mhz
Processor AMD64 Family 15 Model 33 Stepping 2
AuthenticAMD ~2400 Mhz
Processor AMD64 Family 15 Model 33 Stepping 2
AuthenticAMD ~2400 Mhz

```

```

Processor AMD64 Family 15 Model 33 Stepping 2
AuthenticAMD ~2400 Mhz
Processor AMD64 Family 15 Model 33 Stepping 2
AuthenticAMD ~2400 Mhz
Processor AMD64 Family 15 Model 33 Stepping 2
AuthenticAMD ~2400 Mhz
BIOS Version/Date   HP A01, 8/26/2005
SMBIOS Version      2.3
Windows Directory   C:\WINDOWS
System Directory    C:\WINDOWS\system32
Boot Device          \Device\HarddiskVolume35
Locale               United States
Hardware Abstraction Layer   Version =
"5.2.3790.1830 (srv03_spl_rtm.050324-1447) "
User Name Not Available
Time Zone Central Daylight Time
Total Physical Memory 130,903.27 MB
Available Physical Memory 2.32 GB
Total Virtual Memory 128.97 GB
Available Virtual Memory 6.18 GB
Page File Space      4.00 GB
Page File C:\pagefile.sys

```

[Hardware Resources]

[Conflicts/Sharing]

```

Resource Device
I/O Port 0x0000A000-0x0000BFFF PCI standard
PCI-to-PCI bridge
I/O Port 0x0000A000-0x0000BFFF Smart Array
642 Controller (Non-Miniport)

Memory Address 0xF7800000-0xF79FFFFF PCI standard
PCI-to-PCI bridge
Memory Address 0xF7800000-0xF79FFFFF PCI standard
PCI-to-PCI bridge

I/O Port 0x00000000-0x000003AF PCI bus
I/O Port 0x00000000-0x000003AF Direct memory
access controller

I/O Port 0x000003C0-0x000003DF PCI bus
I/O Port 0x000003C0-0x000003DF PCI standard
PCI-to-PCI bridge
I/O Port 0x000003C0-0x000003DF RAGE XL PCI
(Microsoft Corporation)

Memory Address 0xF7E00000-0xF7FFFFFF PCI standard
PCI-to-PCI bridge
Memory Address 0xF7E00000-0xF7FFFFFF PCI standard
PCI-to-PCI bridge

I/O Port 0x00009000-0x00009FFF PCI standard
PCI-to-PCI bridge
I/O Port 0x00009000-0x00009FFF PCI standard
PCI-to-PCI bridge
I/O Port 0x00009000-0x00009FFF Smart Array
6400 Controller (Non-Miniport)

```

```

I/O Port 0x00006000-0x00007FFF PCI standard
PCI-to-PCI bridge
I/O Port 0x00006000-0x00007FFF PCI standard
PCI-to-PCI bridge
I/O Port 0x00006000-0x00007FFF Smart Array
6400 Controller (Non-Miniport)

Memory Address 0xF7A00000-0xF7FFFFFF PCI bus
Memory Address 0xF7A00000-0xF7FFFFFF PCI standard
PCI-to-PCI bridge
Memory Address 0xF7A00000-0xF7FFFFFF PCI standard
PCI-to-PCI bridge

I/O Port 0x0000B000-0x0000BFFF PCI standard
PCI-to-PCI bridge
I/O Port 0x0000B000-0x0000BFFF Smart Array
6400 Controller (Non-Miniport)

I/O Port 0x00005000-0x00005FFF PCI standard
PCI-to-PCI bridge
I/O Port 0x00005000-0x00005FFF Smart Array
51

I/O Port 0x00000A0-0x00000A1 Motherboard
resources
I/O Port 0x00000A0-0x00000A1 Programmable
interrupt controller

IRQ 19 AMD PCI to USB Open Host Controller
IRQ 19 AMD PCI to USB Open Host Controller

Memory Address 0xA0000-0xBFFFF PCI bus
Memory Address 0xA0000-0xBFFFF PCI standard
PCI-to-PCI bridge
Memory Address 0xA0000-0xBFFFF RAGE XL PCI
(Microsoft Corporation)

Memory Address 0xF7B00000-0xF7BFFFFFF PCI standard
PCI-to-PCI bridge
Memory Address 0xF7B00000-0xF7BFFFFFF PCI standard
PCI-to-PCI bridge

I/O Port 0x00007000-0x00007FFF PCI standard
PCI-to-PCI bridge
I/O Port 0x00007000-0x00007FFF Smart Array
6400 Controller (Non-Miniport)

Memory Address 0xF5F00000-0xF79FFFFF PCI bus
Memory Address 0xF5F00000-0xF79FFFFF PCI standard
PCI-to-PCI bridge

Memory Address 0xF5E00000-0xF5EFFFFFF PCI bus
Memory Address 0xF5E00000-0xF5EFFFFFF PCI standard
PCI-to-PCI bridge

I/O Port 0x000003B0-0x000003BB PCI bus
I/O Port 0x000003B0-0x000003BB PCI standard
PCI-to-PCI bridge
I/O Port 0x000003B0-0x000003BB RAGE XL PCI
(Microsoft Corporation)

I/O Port 0x00004000-0x00004FFF PCI standard
PCI-to-PCI bridge

```



```

0x0000B400-0x0000B4FF      Smart Array 6400
Controller U320 Expansion Module (Non-Miniport)  OK

0x0000C000-0x0000DFFF      PCI standard PCI-to-PCI
bridge OK
0x0000C000-0x0000DFFF      PCI standard PCI-to-PCI
bridge OK
0x0000C000-0x0000DFFF      Smart Array 6400
Controller (Non-Miniport)  OK
0x0000C400-0x0000C4FF      Smart Array 6400
Controller U320 Expansion Module (Non-Miniport)  OK

0x0000D000-0x0000DFFF      PCI standard PCI-to-PCI
bridge OK
0x0000D000-0x0000DFFF      Smart Array 6400
Controller (Non-Miniport)  OK
0x0000D400-0x0000D4FF      Smart Array 6400
Controller U320 Expansion Module (Non-Miniport)  OK

[IRQs]

Resource Device Status
IRQ 9      Microsoft ACPI-Compliant System  OK

IRQ 19     AMD PCI to USB Open Host Controller  OK

IRQ 19     AMD PCI to USB Open Host Controller  OK

IRQ 7      Base System Device  OK
IRQ 10     Base System Device  OK
IRQ 0      System timer  OK
IRQ 1      Standard 101/102-Key or Microsoft Natural
PS/2 Keyboard  OK
IRQ 12     PS/2 Compatible Mouse  OK
IRQ 4      Communications Port (COM1)  OK
IRQ 6      Standard floppy disk controller  OK

IRQ 14     Primary IDE Channel  OK
IRQ 18     Smart Array 5i  OK
IRQ 25     Broadcom NetXtreme Gigabit Ethernet #2  OK

IRQ 24     Broadcom NetXtreme Gigabit Ethernet  OK

IRQ 28     Smart Array 6400 Controller (Non-Miniport)
OK
IRQ 29     Smart Array 6400 Controller U320 Expansion
Module (Non-Miniport)  OK
IRQ 30     Smart Array 6400 Controller (Non-Miniport)
OK
IRQ 31     Smart Array 6400 Controller U320 Expansion
Module (Non-Miniport)  OK
IRQ 32     Smart Array 6400 Controller (Non-Miniport)
OK
IRQ 33     Smart Array 6400 Controller U320 Expansion
Module (Non-Miniport)  OK
IRQ 36     Smart Array 6400 Controller (Non-Miniport)
OK
IRQ 37     Smart Array 6400 Controller U320 Expansion
Module (Non-Miniport)  OK
IRQ 40     Smart Array 6400 Controller (Non-Miniport)
OK

```

```

IRQ 41     Smart Array 6400 Controller U320 Expansion
Module (Non-Miniport)  OK
IRQ 42     Smart Array 642 Controller (Non-Miniport)
OK
IRQ 44     Smart Array 6400 Controller (Non-Miniport)
OK
IRQ 45     Smart Array 6400 Controller U320 Expansion
Module (Non-Miniport)  OK
IRQ 46     Smart Array 6400 Controller (Non-Miniport)
OK
IRQ 47     Smart Array 6400 Controller U320 Expansion
Module (Non-Miniport)  OK

[Memory]

Resource Device Status
0xA0000-0xBFFFF  PCI bus  OK
0xA0000-0xBFFFF  PCI standard PCI-to-PCI bridge
OK
0xA0000-0xBFFFF  RAGE XL PCI (Microsoft
Corporation)  OK
0xF5E00000-0xF5EFFFFF  PCI bus  OK
0xF5E00000-0xF5EFFFFF  PCI standard PCI-to-PCI
bridge OK
0xF5F00000-0xF79FFFFF  PCI bus  OK
0xF5F00000-0xF79FFFFF  PCI standard PCI-to-PCI
bridge OK
0xF76F0000-0xF76F0FFF  AMD PCI to USB Open
Host Controller  OK
0xF76E0000-0xF76E0FFF  AMD PCI to USB Open
Host Controller  OK
0xF76B0000-0xF76B01FF  Base System Device  OK

0xF76A0000-0xF76A07FF  Base System Device  OK

0xF7690000-0xF7691FFF  Base System Device  OK

0xF7600000-0xF767FFFF  Base System Device  OK

0xF6000000-0xF6FFFFFFF  RAGE XL PCI (Microsoft
Corporation)  OK
0xF5F00000-0xF5F0FFFF  RAGE XL PCI (Microsoft
Corporation)  OK
0xF7700000-0xF777FFFF  PCI standard PCI-to-PCI
bridge OK
0xF77C0000-0xF777FFFF  Smart Array 5i  OK

0xF5E00000-0xF5E03FFF  Smart Array 5i  OK

0xF77B0000-0xF77BFFFF  Broadcom NetXtreme
Gigabit Ethernet #2 OK
0xF77A0000-0xF77AFFFF  Broadcom NetXtreme
Gigabit Ethernet OK
0xF7800000-0xF79FFFFF  PCI standard PCI-to-PCI
bridge OK
0xF7800000-0xF79FFFFF  PCI standard PCI-to-PCI
bridge OK
0xF78F0000-0xF78F1FFF  Smart Array 6400
Controller (Non-Miniport)  OK
0xF7870000-0xF7871FFF  Smart Array 6400
Controller U320 Expansion Module (Non-Miniport)  OK

```

```

0xF7900000-0xF79FFFFF  PCI standard PCI-to-PCI
bridge OK
0xF79F0000-0xF79F1FFF  Smart Array 6400
Controller (Non-Miniport)  OK
0xF7970000-0xF7971FFF  Smart Array 6400
Controller U320 Expansion Module (Non-Miniport)  OK

0xF7A00000-0xF7FFFFFFF  PCI bus  OK
0xF7A00000-0xF7FFFFFFF  PCI standard PCI-to-PCI
bridge OK
0xF7A00000-0xF7FFFFFFF  PCI standard PCI-to-PCI
bridge OK
0xF7AF0000-0xF7AF1FFF  Smart Array 6400
Controller (Non-Miniport)  OK
0xF7A70000-0xF7A71FFF  Smart Array 6400
Controller U320 Expansion Module (Non-Miniport)  OK

0xF7B00000-0xF7BFFFFF  PCI standard PCI-to-PCI
bridge OK
0xF7B00000-0xF7BFFFFF  PCI standard PCI-to-PCI
bridge OK
0xF7BF0000-0xF7BF1FFF  Smart Array 6400
Controller (Non-Miniport)  OK
0xF7B70000-0xF7B71FFF  Smart Array 6400
Controller U320 Expansion Module (Non-Miniport)  OK

0xF7C00000-0xF7DFFFFF  PCI standard PCI-to-PCI
bridge OK
0xF7D00000-0xF7DFFFFF  PCI standard PCI-to-PCI
bridge OK
0xF7DF0000-0xF7DF1FFF  Smart Array 6400
Controller (Non-Miniport)  OK
0xF7D70000-0xF7D71FFF  Smart Array 6400
Controller U320 Expansion Module (Non-Miniport)  OK

0xF7CF0000-0xF7CF1FFF  Smart Array 642
Controller (Non-Miniport)  OK
0xF7C80000-0xF7CBFFFF  Smart Array 642
Controller (Non-Miniport)  OK
0xF7E00000-0xF7FFFFFFF  PCI standard PCI-to-PCI
bridge OK
0xF7E00000-0xF7FFFFFFF  PCI standard PCI-to-PCI
bridge OK
0xF7EF0000-0xF7EF1FFF  Smart Array 6400
Controller (Non-Miniport)  OK
0xF7E70000-0xF7E71FFF  Smart Array 6400
Controller U320 Expansion Module (Non-Miniport)  OK

0xF7F00000-0xF7FFFFFFF  PCI standard PCI-to-PCI
bridge OK
0xF7FF0000-0xF7FF1FFF  Smart Array 6400
Controller (Non-Miniport)  OK
0xF7F70000-0xF7F71FFF  Smart Array 6400
Controller U320 Expansion Module (Non-Miniport)  OK

[Components]

[Multimedia]

```

[Audio Codecs]

CODEC	Manufacturer	Description	Status	File	Version	Size	Creation Date
c:\windows\system32\msgsm32.acm Microsoft Corporation							
		C:\WINDOWS\system32\MSGSM32.ACM	OK				
		5.2.3790.1830 (srv03_spl_rtm.050324-1447)					
		34.50 KB (35,328 bytes)					3/25/2005
6:00 AM							
c:\windows\system32\tssoft32.acm DSP GROUP, INC.							
		C:\WINDOWS\system32\TSSOFT32.ACM	OK				
		1.01 13.50 KB (13,824 bytes)					
		3/25/2005 6:00 AM					
c:\windows\system32\msadp32.acm Microsoft Corporation							
		C:\WINDOWS\system32\MSADP32.ACM	OK				
		5.2.3790.1830 (srv03_spl_rtm.050324-1447)					
		23.50 KB (24,064 bytes)					3/25/2005
6:00 AM							
c:\windows\system32\msg711.acm Microsoft Corporation							
		C:\WINDOWS\system32\MSG711.ACM	OK				
		5.2.3790.1830 (srv03_spl_rtm.050324-1447)					
		13.50 KB (13,824 bytes)					3/25/2005
6:00 AM							
c:\windows\system32\imaadp32.acm Microsoft Corporation							
		C:\WINDOWS\system32\IMAADP32.ACM	OK				
		5.2.3790.1830 (srv03_spl_rtm.050324-1447)					
		24.00 KB (24,576 bytes)					3/25/2005
6:00 AM							
[Video Codecs]							
CODEC	Manufacturer	Description	Status	File	Version	Size	Creation Date
c:\windows\system32\iyuv_32.dll Microsoft Corporation							
		C:\WINDOWS\system32\IYUV_32.DLL	OK				
		5.2.3790.1830 (srv03_spl_rtm.050324-1447)					
		52.50 KB (53,760 bytes)					3/24/2005
11:19 AM							
c:\windows\system32\msrle32.dll Microsoft Corporation							
		C:\WINDOWS\system32\MSRLE32.DLL	OK				
		5.2.3790.1830 (srv03_spl_rtm.050324-1447)					
		15.50 KB (15,872 bytes)					3/25/2005
6:00 AM							
c:\windows\system32\msvidc32.dll Microsoft Corporation							
		C:\WINDOWS\system32\MSVIDC32.DLL	OK				
		5.2.3790.1830 (srv03_spl_rtm.050324-1447)					
		43.00 KB (44,032 bytes)					3/25/2005
6:00 AM							
c:\windows\system32\msyuv.dll Microsoft Corporation							
		C:\WINDOWS\system32\MSYUV.DLL	OK				
		5.2.3790.1830					

```
(srv03_spl_rtm.050324-1447) 21.00 KB (21,504 bytes)
3/24/2005 11:21 AM
c:\windows\system32\tsbyuv.dll Microsoft Corporation
C:\WINDOWS\system32\TSBYUV.DLL
5.2.3790.1830 (srv03_spl_rtm.050324-1447)
12.50 KB (12,800 bytes) 3/24/2005
11:34 AM

[CD-ROM]

Item Value
Drive D:
Description CD-ROM Drive
Media Loaded No
Media Type CD-ROM
Name TEAC CD-224E
Manufacturer (Standard CD-ROM drives)
Status OK
Transfer Rate Not Available
SCSI Target ID 0
PNP Device ID IDE\CDROMTEAC_CD-224E
9.9A\5&2DC47F1C&0&0.0.0
Driver c:\windows\system32\drivers\cdrom.sys
(5.2.3790.1830 (srv03_spl_rtm.050324-1447), 75.50 KB (77,312 bytes), 3/25/2005 6:00 AM)

[Sound Device]

Item Value
Name RAGE XL PCI (Microsoft Corporation)
PNP Device ID PCI\VEN_1002&DEV_4752&SUBSYS_001E0E11&REV_27\4&12365AD0&0&1818
Adapter Type ATI RAGE XL PCI (B41), ATI Technologies, Inc. compatible
Adapter Description RAGE XL PCI (Microsoft Corporation)
Adapter RAM 8.00 MB (8,388,608 bytes)
Installed Drivers ati2drad.dll
Driver Version 6.14.3655.6024
INF File atiixpad.inf (ati2mpad section)
Color Planes 1
Color Table Entries 65536
Resolution 800 x 600 x 60 hertz
Bits/Pixel 16
Memory Address 0xF6000000-0xF6FFFFFF
I/O Port 0x00004400-0x000044FF
Memory Address 0xF5FF0000-0xF5FF0FFF
I/O Port 0x000003B0-0x000003BB
I/O Port 0x000003C0-0x000003DF
Memory Address 0xA0000-0xBF000
Driver c:\windows\system32\drivers\ati2mpad.sys
(6.14.3655.6024, 318.75 KB (326,400 bytes), 7/18/2005 10:55 AM)

[Infrared]
```

```
Item Value
[Input]

[Keyboard]

Item Value
Description Standard 101/102-Key or Microsoft Natural PS/2 Keyboard
Name Enhanced (101- or 102-key)
Layout 00000409
PNP Device ID ACPI\PNP0303\4&1C7DEDE8&0
Number of Function Keys 12
I/O Port 0x00000060-0x00000060
I/O Port 0x00000064-0x00000064
IRQ Channel IRQ 1
Driver c:\windows\system32\drivers\i8042prt.sys
(5.2.3790.1830 (srv03_spl_rtm.050324-1447), 91.00 KB (93,184 bytes), 3/25/2005 6:00 AM)

[Pointing Device]

Item Value
Hardware Type PS/2 Compatible Mouse
Number of Buttons 5
Status OK
PNP Device ID ACPI\PNP0F13\4&1C7DEDE8&0
Power Management Supported No
Double Click Threshold 6
Handedness Right Handed Operation
IRQ Channel IRQ 12
Driver c:\windows\system32\drivers\i8042prt.sys
(5.2.3790.1830 (srv03_spl_rtm.050324-1447), 91.00 KB (93,184 bytes), 3/25/2005 6:00 AM)

[Modem]

Item Value

[Network]

[Adapter]

Item Value
Name [00000001] Broadcom NetXtreme Gigabit Ethernet
Adapter Type Ethernet 802.3
Product Type Broadcom NetXtreme Gigabit Ethernet
Installed Yes
PNP Device ID PCI\VEN_14E4&DEV_1648&SUBSYS_00D00E11&REV_10\4&82820FC&0&3138
Last Reset 9/19/2005 5:23 PM
Index 1
Service Name b57nd
IP Address 130.120.208.14
IP Subnet 255.255.0.0
Default IP Gateway Not Available
```

```

DHCP Enabled          No
DHCP Server           Not Available
DHCP Lease Expires   Not Available
DHCP Lease Obtained  Not Available
MAC Address           00:0E:7F:B0:AB:FA
Memory Address        0xF77A0000-0xF77AFFFF
IRQ Channel           IRQ 24
Driver                c:\windows\system32\drivers\b57amd64.sys
(7.98.0.0 built by: WinDDK, 187.00 KB (191,488
bytes), 7/18/2005 10:56 AM)

Name                  [00000002] Broadcom NetXtreme Gigabit
Ethernet
Adapter Type         Ethernet 802.3
Product Type         Broadcom NetXtreme Gigabit
Ethernet
Installed Yes
PNP Device ID
PCI\VEN_14E4&DEV_1648&SUBSYS_00D00E11&REV_1
0\4&82820FC&0&3038
Last Reset           9/19/2005 5:23 PM
Index                2
Service Name         b57nd
IP Address            130.168.208.14
IP Subnet 255.255.0.0
Default IP Gateway   Not Available
DHCP Enabled         No
DHCP Server          Not Available
DHCP Lease Expires   Not Available
DHCP Lease Obtained Not Available
MAC Address          00:0E:7F:B0:AB:FB
Memory Address        0xF77B0000-0xF77BFFFF
IRQ Channel           IRQ 25
Driver                c:\windows\system32\drivers\b57amd64.sys
(7.98.0.0 built by: WinDDK, 187.00 KB (191,488
bytes), 7/18/2005 10:56 AM)

Name                  [00000003] RAS Async Adapter
Adapter Type         Not Available
Product Type         RAS Async Adapter
Installed Yes
PNP Device ID        Not Available
Last Reset           9/19/2005 5:23 PM
Index                3
Service Name         AsyncMac
IP Address            Not Available
IP Subnet Not Available
Default IP Gateway   Not Available
DHCP Enabled         No
DHCP Server          Not Available
DHCP Lease Expires   Not Available
DHCP Lease Obtained Not Available
MAC Address          Not Available

Name                  [00000004] WAN Miniport (L2TP)
Adapter Type         Not Available
Product Type         WAN Miniport (L2TP)
Installed Yes
PNP Device ID        ROOT\MS_L2TPMINIPORT\0000
Last Reset           9/19/2005 5:23 PM
Index                4
Service Name         Rasl2tp
IP Address            Not Available

```

```

IP Subnet Not Available
Default IP Gateway   Not Available
DHCP Enabled         No
DHCP Server          Not Available
DHCP Lease Expires   Not Available
DHCP Lease Obtained Not Available
MAC Address          Not Available
Driver                c:\windows\system32\drivers\rasl2tp.sys
(5.2.3790.1830 (srv03_spl_rtm.050324-1447), 132.00 KB
(135,168 bytes), 3/25/2005 6:00 AM)

Name                  [00000005] WAN Miniport (PPTP)
Adapter Type         Wide Area Network (WAN)
Product Type         WAN Miniport (PPTP)
Installed Yes
PNP Device ID        ROOT\MS_PPTPMINIPORT\0000
Last Reset           9/19/2005 5:23 PM
Index                5
Service Name         PptpMiniport
IP Address            Not Available
IP Subnet Not Available
Default IP Gateway   Not Available
DHCP Enabled         No
DHCP Server          Not Available
DHCP Lease Expires   Not Available
DHCP Lease Obtained Not Available
MAC Address          50:50:54:50:30:30
Driver                c:\windows\system32\drivers\raspptp.sys
(5.2.3790.1830 (srv03_spl_rtm.050324-1447), 117.50 KB
(120,320 bytes), 3/25/2005 6:00 AM)

Name                  [00000006] WAN Miniport (PPPOE)
Adapter Type         Wide Area Network (WAN)
Product Type         WAN Miniport (PPPOE)
Installed Yes
PNP Device ID        ROOT\MS_PPPOEMINIPORT\0000
Last Reset           9/19/2005 5:23 PM
Index                6
Service Name         RasPppoe
IP Address            Not Available
IP Subnet Not Available
Default IP Gateway   Not Available
DHCP Enabled         No
DHCP Server          Not Available
DHCP Lease Expires   Not Available
DHCP Lease Obtained Not Available
MAC Address          33:50:6F:45:30:30
Driver                c:\windows\system32\drivers\rasppoe.sys
(5.2.3790.1830 (srv03_spl_rtm.050324-1447), 67.50 KB
(69,120 bytes), 3/25/2005 6:00 AM)

Name                  [00000007] Direct Parallel
Adapter Type         Not Available
Product Type         Direct Parallel
Installed Yes
PNP Device ID        ROOT\MS_PTMINIPORT\0000
Last Reset           9/19/2005 5:23 PM
Index                7
Service Name         Raspti
IP Address            Not Available
IP Subnet Not Available
Default IP Gateway   Not Available
DHCP Enabled         No

```

```

DHCP Server          Not Available
DHCP Lease Expires   Not Available
DHCP Lease Obtained Not Available
MAC Address          Not Available
Driver                c:\windows\system32\drivers\raspti.sys
(5.2.3790.1830 (srv03_spl_rtm.050324-1447), 30.50 KB
(31,232 bytes), 3/25/2005 6:00 AM)

Name                  [00000008] WAN Miniport (IP)
Adapter Type         Not Available
Product Type         WAN Miniport (IP)
Installed Yes
PNP Device ID        ROOT\MS_NDISWANIP\0000
Last Reset           9/19/2005 5:23 PM
Index                8
Service Name         NdisWan
IP Address            Not Available
IP Subnet Not Available
Default IP Gateway   Not Available
DHCP Enabled         No
DHCP Server          Not Available
DHCP Lease Expires   Not Available
DHCP Lease Obtained Not Available
MAC Address          Not Available
Driver                c:\windows\system32\drivers\ndiswan.sys
(5.2.3790.1830 (srv03_spl_rtm.050324-1447), 157.50 KB
(161,280 bytes), 3/25/2005 6:00 AM)

[Protocol]

Item      Value
Name      MSAFD Tcpip [TCP/IP]
Connectionless Service No
Guarantees Delivery Yes
Guarantees Sequencing Yes
Maximum Address Size 16 bytes
Maximum Message Size 0 bytes
Message Oriented No
Minimum Address Size 16 bytes
Pseudo Stream Oriented No
Supports Broadcasting No
Supports Connect Data No
Supports Disconnect Data No
Supports Encryption No
Supports Expedited Data Yes
Supports Graceful Closing Yes
Supports Guaranteed Bandwidth No
Supports Multicasting No

Name      MSAFD Tcpip [UDP/IP]
Connectionless Service Yes
Guarantees Delivery No
Guarantees Sequencing No
Maximum Address Size 16 bytes
Maximum Message Size 63.93 KB (65,467 bytes)

Message Oriented Yes
Minimum Address Size 16 bytes
Pseudo Stream Oriented No
Supports Broadcasting Yes
Supports Connect Data No
Supports Disconnect Data No
Supports Encryption No

```

```

Supports Expedited Data      No
Supports Graceful Closing    No
Supports Guaranteed Bandwidth No
Supports Multicasting        Yes

Name      RSVP UDP Service Provider
Connectionless Service      Yes
Guarantees Delivery No
Guarantees Sequencing       No
Maximum Address Size        16 bytes
Maximum Message Size        63.93 KB (65,467 bytes)

Message Oriented      Yes
Minimum Address Size   16 bytes
Pseudo Stream Oriented No
Supports Broadcasting  Yes
Supports Connect Data  No
Supports Disconnect Data No
Supports Encryption Yes
Supports Expedited Data No
Supports Graceful Closing No
Supports Guaranteed Bandwidth No
Supports Multicasting  Yes

Name      RSVP TCP Service Provider
Connectionless Service      No
Guarantees Delivery Yes
Guarantees Sequencing       Yes
Maximum Address Size        16 bytes
Maximum Message Size        0 bytes
Message Oriented      No
Minimum Address Size   16 bytes
Pseudo Stream Oriented No
Supports Broadcasting  No
Supports Connect Data  No
Supports Disconnect Data No
Supports Encryption Yes
Supports Expedited Data Yes
Supports Graceful Closing Yes
Supports Guaranteed Bandwidth No
Supports Multicasting  No

[WinSock]

Item      Value
File      c:\windows\system32\wsock32.dll
Size      24.50 KB (25,088 bytes)
Version   5.2.3790.1830 (srv03_spl_rtm.050324-1447)

[Ports]

[Serial]

Item      Value
Name      Communications Port (COM1)
Status    OK
PNP Device ID  ACPI\PNP0501\0
Maximum Input Buffer Size Not Available
Maximum Output Buffer Size Not Available
Settable Baud Rate Not Available

```

```

Settable Data Bits Not Available
Settable Flow Control Not Available
Settable Parity Not Available
Settable Parity Check Not Available
Settable Stop Bits Not Available
Settable RLSD Not Available
Supports RLSD Not Available
Supports 16 Bit Mode Not Available
Supports Special Characters Not Available
Baud Rate 9600
Bits/Byte 8
Stop Bits 1
Parity None
Busy No
Abort Read/Write on Error Not Available
Binary Mode Enabled Not Available
Continue XMit on XOff Not Available
CTS Outflow Control Not Available
Discard NULL Bytes Not Available
DSR Outflow Control Not Available
DSR Sensitivity Not Available
DTR Flow Control Type Not Available
EOF Character Not Available
Error Replace Character Not Available
Error Replacement Enabled Not Available
Event Character Not Available
Parity Check Enabled Yes
RTS Flow Control Type Not Available
XOff Character 19
XOffXMit Threshold 512
XOn Character 17
XOnXMit Threshold 2048
XOnXOff InFlow Control Not Available
XOnXOff OutFlow Control Not Available
IRQ Channel IRQ 4
I/O Port 0x000003F8-0x000003FF
Driver c:\windows\system32\drivers\serial.sys
(5.2.3790.1830 (srv03_spl_rtm.050324-1447), 118.50 KB
(121,344 bytes), 3/25/2005 6:00 AM)

[Parallel]

Item      Value

[Storage]

[Drives]

Item      Value
Drive A:
Description 3 1/2 Inch Floppy Drive

Drive C:
Description Local Fixed Disk
Compressed No
File System NTFS
Size 33.91 GB (36,410,552,320 bytes)
Free Space 20.04 GB (21,520,728,064 bytes)

Volume Name
Volume Serial Number 68ED1DA5

```

```

Drive D:
Description CD-ROM Disc

Drive E:
Description Local Fixed Disk
Compressed Not Available
File System Not Available
Size Not Available
Free Space Not Available
Volume Name Not Available
Volume Serial Number Not Available

Drive R:
Description Local Fixed Disk
Compressed No
File System NTFS
Size 421.57 GB (452,653,576,192 bytes)
Free Space 421.48 GB (452,560,195,584 bytes)

Volume Name tempDB
Volume Serial Number 6C7BD900

Drive V:
Description Network Connection
Provider Name Not Available

Drive W:
Description Local Fixed Disk
Compressed No
File System NTFS
Size 421.57 GB (452,653,576,192 bytes)
Free Space 107.32 GB (115,231,514,624 bytes)

Volume Name back1
Volume Serial Number DCBA8D6F

Drive X:
Description Local Fixed Disk
Compressed No
File System NTFS
Size 421.57 GB (452,653,576,192 bytes)
Free Space 107.32 GB (115,231,580,160 bytes)

Volume Name back2
Volume Serial Number 7CC767BC

Drive Y:
Description Local Fixed Disk
Compressed No
File System NTFS
Size 421.57 GB (452,653,576,192 bytes)
Free Space 107.32 GB (115,231,580,160 bytes)

Volume Name back3
Volume Serial Number 48202221

Drive Z:
Description Local Fixed Disk
Compressed No
File System NTFS
Size 421.57 GB (452,653,576,192 bytes)

```

Free Space 107.32 GB (115,231,580,160 bytes)

Volume Name back4
Volume Serial Number 400A5C08

[Disks]

Item Value
Description \\.\PHYSICALDRIVE23
Manufacturer Not Available
Model Not Available
Bytes/Sector 512
Media Loaded Yes
Media Type Fixed hard disk
Partitions 1
SCSI Bus Not Available
SCSI Logical Unit Not Available
SCSI Port Not Available
SCSI Target ID Not Available
Sectors/Track 63
Size 820.39 GB (880,886,361,600 bytes)
Total Cylinders 107,095
Total Sectors 1,720,481,175
Total Tracks 27,309,225
Tracks/Cylinder 255
Partition Disk #23, Partition #0
Partition Size 820.39 GB (880,885,628,928 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE24
Manufacturer Not Available
Model Not Available
Bytes/Sector 512
Media Loaded Yes
Media Type Fixed hard disk
Partitions 1
SCSI Bus Not Available
SCSI Logical Unit Not Available
SCSI Port Not Available
SCSI Target ID Not Available
Sectors/Track 63
Size 71.28 GB (76,536,230,400 bytes)
Total Cylinders 9,305
Total Sectors 149,484,825
Total Tracks 2,372,775
Tracks/Cylinder 255
Partition Disk #24, Partition #0
Partition Size 71.28 GB (76,535,562,240 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE25
Manufacturer Not Available
Model Not Available
Bytes/Sector 512
Media Loaded Yes
Media Type Fixed hard disk
Partitions 1
SCSI Bus Not Available
SCSI Logical Unit Not Available
SCSI Port Not Available
SCSI Target ID Not Available

Sectors/Track 63
Size 35.15 GB (37,745,809,920 bytes)
Total Cylinders 4,589
Total Sectors 73,722,285
Total Tracks 1,170,195
Tracks/Cylinder 255
Partition Disk #25, Partition #0
Partition Size 35.15 GB (37,745,590,272 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE26
Manufacturer Not Available
Model Not Available
Bytes/Sector 512
Media Loaded Yes
Media Type Fixed hard disk
Partitions 1
SCSI Bus Not Available
SCSI Logical Unit Not Available
SCSI Port Not Available
SCSI Target ID Not Available
Sectors/Track 63
Size 421.57 GB (452,653,608,960 bytes)
Total Cylinders 55,032
Total Sectors 884,089,080
Total Tracks 14,033,160
Tracks/Cylinder 255
Partition Disk #26, Partition #0
Partition Size 421.57 GB (452,653,576,704 bytes)

Partition Starting Offset 32,256 bytes

Description \\.\PHYSICALDRIVE8
Manufacturer Not Available
Model Not Available
Bytes/Sector 512
Media Loaded Yes
Media Type Fixed hard disk
Partitions 1
SCSI Bus Not Available
SCSI Logical Unit Not Available
SCSI Port Not Available
SCSI Target ID Not Available
Sectors/Track 63
Size 71.28 GB (76,536,230,400 bytes)
Total Cylinders 9,305
Total Sectors 149,484,825
Total Tracks 2,372,775
Tracks/Cylinder 255
Partition Disk #8, Partition #0
Partition Size 71.28 GB (76,535,562,240 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE9
Manufacturer Not Available
Model Not Available
Bytes/Sector 512
Media Loaded Yes
Media Type Fixed hard disk
Partitions 1
SCSI Bus Not Available

SCSI Logical Unit Not Available
SCSI Port Not Available
SCSI Target ID Not Available
Sectors/Track 63
Size 35.15 GB (37,745,809,920 bytes)
Total Cylinders 4,589
Total Sectors 73,722,285
Total Tracks 1,170,195
Tracks/Cylinder 255
Partition Disk #9, Partition #0
Partition Size 35.15 GB (37,745,590,272 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE10
Manufacturer Not Available
Model Not Available
Bytes/Sector 512
Media Loaded Yes
Media Type Fixed hard disk
Partitions 1
SCSI Bus Not Available
SCSI Logical Unit Not Available
SCSI Port Not Available
SCSI Target ID Not Available
Sectors/Track 63
Size 421.57 GB (452,653,608,960 bytes)
Total Cylinders 55,032
Total Sectors 884,089,080
Total Tracks 14,033,160
Tracks/Cylinder 255
Partition Disk #10, Partition #0
Partition Size 421.57 GB (452,653,576,704 bytes)

Partition Starting Offset 32,256 bytes

Description \\.\PHYSICALDRIVE6
Manufacturer Not Available
Model Not Available
Bytes/Sector 512
Media Loaded Yes
Media Type Fixed hard disk
Partitions 1
SCSI Bus Not Available
SCSI Logical Unit Not Available
SCSI Port Not Available
SCSI Target ID Not Available
Sectors/Track 63
Size 71.28 GB (76,536,230,400 bytes)
Total Cylinders 9,305
Total Sectors 149,484,825
Total Tracks 2,372,775
Tracks/Cylinder 255
Partition Disk #6, Partition #0
Partition Size 71.28 GB (76,535,562,240 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE7
Manufacturer Not Available
Model Not Available
Bytes/Sector 512
Media Loaded Yes

Media Type Fixed hard disk
 Partitions 1
 SCSI Bus Not Available
 SCSI Logical Unit Not Available
 SCSI Port Not Available
 SCSI Target ID Not Available
 Sectors/Track 63
 Size 35.15 GB (37,745,809,920 bytes)
 Total Cylinders 4,589
 Total Sectors 73,722,285
 Total Tracks 1,170,195
 Tracks/Cylinder 255
 Partition Disk #7, Partition #0
 Partition Size 35.15 GB (37,745,590,272 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE11
 Manufacturer Not Available
 Model Not Available
 Bytes/Sector 512
 Media Loaded Yes
 Media Type Fixed hard disk
 Partitions 1
 SCSI Bus Not Available
 SCSI Logical Unit Not Available
 SCSI Port Not Available
 SCSI Target ID Not Available
 Sectors/Track 63
 Size 71.28 GB (76,536,230,400 bytes)
 Total Cylinders 9,305
 Total Sectors 149,484,825
 Total Tracks 2,372,775
 Tracks/Cylinder 255
 Partition Disk #11, Partition #0
 Partition Size 71.28 GB (76,535,562,240 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE12
 Manufacturer Not Available
 Model Not Available
 Bytes/Sector 512
 Media Loaded Yes
 Media Type Fixed hard disk
 Partitions 1
 SCSI Bus Not Available
 SCSI Logical Unit Not Available
 SCSI Port Not Available
 SCSI Target ID Not Available
 Sectors/Track 63
 Size 35.15 GB (37,745,809,920 bytes)
 Total Cylinders 4,589
 Total Sectors 73,722,285
 Total Tracks 1,170,195
 Tracks/Cylinder 255
 Partition Disk #12, Partition #0
 Partition Size 35.15 GB (37,745,590,272 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE27
 Manufacturer Not Available

Model Not Available
 Bytes/Sector 512
 Media Loaded Yes
 Media Type Fixed hard disk
 Partitions 1
 SCSI Bus Not Available
 SCSI Logical Unit Not Available
 SCSI Port Not Available
 SCSI Target ID Not Available
 Sectors/Track 63
 Size 71.28 GB (76,536,230,400 bytes)
 Total Cylinders 9,305
 Total Sectors 149,484,825
 Total Tracks 2,372,775
 Tracks/Cylinder 255
 Partition Disk #27, Partition #0
 Partition Size 71.28 GB (76,535,562,240 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE28
 Manufacturer Not Available
 Model Not Available
 Bytes/Sector 512
 Media Loaded Yes
 Media Type Fixed hard disk
 Partitions 1
 SCSI Bus Not Available
 SCSI Logical Unit Not Available
 SCSI Port Not Available
 SCSI Target ID Not Available
 Sectors/Track 63
 Size 35.15 GB (37,745,809,920 bytes)
 Total Cylinders 4,589
 Total Sectors 73,722,285
 Total Tracks 1,170,195
 Tracks/Cylinder 255
 Partition Disk #28, Partition #0
 Partition Size 35.15 GB (37,745,590,272 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE29
 Manufacturer Not Available
 Model Not Available
 Bytes/Sector 512
 Media Loaded Yes
 Media Type Fixed hard disk
 Partitions 1
 SCSI Bus Not Available
 SCSI Logical Unit Not Available
 SCSI Port Not Available
 SCSI Target ID Not Available
 Sectors/Track 63
 Size 71.28 GB (76,536,230,400 bytes)
 Total Cylinders 9,305
 Total Sectors 149,484,825
 Total Tracks 2,372,775
 Tracks/Cylinder 255
 Partition Disk #29, Partition #0
 Partition Size 71.28 GB (76,535,562,240 bytes)

Partition Starting Offset 65,536 bytes

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE30
 Manufacturer Not Available
 Model Not Available
 Bytes/Sector 512
 Media Loaded Yes
 Media Type Fixed hard disk
 Partitions 1
 SCSI Bus Not Available
 SCSI Logical Unit Not Available
 SCSI Port Not Available
 SCSI Target ID Not Available
 Sectors/Track 63
 Size 35.15 GB (37,745,809,920 bytes)
 Total Cylinders 4,589
 Total Sectors 73,722,285
 Total Tracks 1,170,195
 Tracks/Cylinder 255
 Partition Disk #30, Partition #0
 Partition Size 35.15 GB (37,745,590,272 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE31
 Manufacturer Not Available
 Model Not Available
 Bytes/Sector 512
 Media Loaded Yes
 Media Type Fixed hard disk
 Partitions 1
 SCSI Bus Not Available
 SCSI Logical Unit Not Available
 SCSI Port Not Available
 SCSI Target ID Not Available
 Sectors/Track 63
 Size 421.57 GB (452,653,608,960 bytes)
 Total Cylinders 55,032
 Total Sectors 884,089,080
 Total Tracks 14,033,160
 Tracks/Cylinder 255
 Partition Disk #31, Partition #0
 Partition Size 421.57 GB (452,653,576,704 bytes)

Partition Starting Offset 32,256 bytes

Description \\.\PHYSICALDRIVE4
 Manufacturer Not Available
 Model Not Available
 Bytes/Sector 512
 Media Loaded Yes
 Media Type Fixed hard disk
 Partitions 1
 SCSI Bus Not Available
 SCSI Logical Unit Not Available
 SCSI Port Not Available
 SCSI Target ID Not Available
 Sectors/Track 63
 Size 71.28 GB (76,536,230,400 bytes)
 Total Cylinders 9,305
 Total Sectors 149,484,825
 Total Tracks 2,372,775
 Tracks/Cylinder 255
 Partition Disk #4, Partition #0

Partition Size 71.28 GB (76,535,562,240 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE5
Manufacturer Not Available
Model Not Available
Bytes/Sector 512
Media Loaded Yes
Media Type Fixed hard disk
Partitions 1
SCSI Bus Not Available
SCSI Logical Unit Not Available
SCSI Port Not Available
SCSI Target ID Not Available
Sectors/Track 63
Size 35.15 GB (37,745,809,920 bytes)
Total Cylinders 4,589
Total Sectors 73,722,285
Total Tracks 1,170,195
Tracks/Cylinder 255
Partition Disk #5, Partition #0
Partition Size 35.15 GB (37,745,590,272 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE32
Manufacturer Not Available
Model Not Available
Bytes/Sector 512
Media Loaded Yes
Media Type Fixed hard disk
Partitions 1
SCSI Bus Not Available
SCSI Logical Unit Not Available
SCSI Port Not Available
SCSI Target ID Not Available
Sectors/Track 63
Size 71.28 GB (76,536,230,400 bytes)
Total Cylinders 9,305
Total Sectors 149,484,825
Total Tracks 2,372,775
Tracks/Cylinder 255
Partition Disk #32, Partition #0
Partition Size 71.28 GB (76,535,562,240 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE33
Manufacturer Not Available
Model Not Available
Bytes/Sector 512
Media Loaded Yes
Media Type Fixed hard disk
Partitions 1
SCSI Bus Not Available
SCSI Logical Unit Not Available
SCSI Port Not Available
SCSI Target ID Not Available
Sectors/Track 63
Size 35.15 GB (37,745,809,920 bytes)
Total Cylinders 4,589
Total Sectors 73,722,285

Total Tracks 1,170,195
Tracks/Cylinder 255
Partition Disk #33, Partition #0
Partition Size 35.15 GB (37,745,590,272 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE21
Manufacturer Not Available
Model Not Available
Bytes/Sector 512
Media Loaded Yes
Media Type Fixed hard disk
Partitions 1
SCSI Bus Not Available
SCSI Logical Unit Not Available
SCSI Port Not Available
SCSI Target ID Not Available
Sectors/Track 63
Size 71.28 GB (76,536,230,400 bytes)
Total Cylinders 9,305
Total Sectors 149,484,825
Total Tracks 2,372,775
Tracks/Cylinder 255
Partition Disk #21, Partition #0
Partition Size 71.28 GB (76,535,562,240 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE22
Manufacturer Not Available
Model Not Available
Bytes/Sector 512
Media Loaded Yes
Media Type Fixed hard disk
Partitions 1
SCSI Bus Not Available
SCSI Logical Unit Not Available
SCSI Port Not Available
SCSI Target ID Not Available
Sectors/Track 63
Size 35.15 GB (37,745,809,920 bytes)
Total Cylinders 4,589
Total Sectors 73,722,285
Total Tracks 1,170,195
Tracks/Cylinder 255
Partition Disk #22, Partition #0
Partition Size 35.15 GB (37,745,590,272 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE13
Manufacturer Not Available
Model Not Available
Bytes/Sector 512
Media Loaded Yes
Media Type Fixed hard disk
Partitions 1
SCSI Bus Not Available
SCSI Logical Unit Not Available
SCSI Port Not Available
SCSI Target ID Not Available
Sectors/Track 63

Size 71.28 GB (76,536,230,400 bytes)
Total Cylinders 9,305
Total Sectors 149,484,825
Total Tracks 2,372,775
Tracks/Cylinder 255
Partition Disk #13, Partition #0
Partition Size 71.28 GB (76,535,562,240 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE14
Manufacturer Not Available
Model Not Available
Bytes/Sector 512
Media Loaded Yes
Media Type Fixed hard disk
Partitions 1
SCSI Bus Not Available
SCSI Logical Unit Not Available
SCSI Port Not Available
SCSI Target ID Not Available
Sectors/Track 63
Size 35.15 GB (37,745,809,920 bytes)
Total Cylinders 4,589
Total Sectors 73,722,285
Total Tracks 1,170,195
Tracks/Cylinder 255
Partition Disk #14, Partition #0
Partition Size 35.15 GB (37,745,590,272 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE15
Manufacturer Not Available
Model Not Available
Bytes/Sector 512
Media Loaded Yes
Media Type Fixed hard disk
Partitions 1
SCSI Bus Not Available
SCSI Logical Unit Not Available
SCSI Port Not Available
SCSI Target ID Not Available
Sectors/Track 63
Size 421.57 GB (452,653,608,960 bytes)
Total Cylinders 55,032
Total Sectors 884,089,080
Total Tracks 14,033,160
Tracks/Cylinder 255
Partition Disk #15, Partition #0
Partition Size 421.57 GB (452,653,576,704 bytes)

Partition Starting Offset 32,256 bytes

Description \\.\PHYSICALDRIVE0
Manufacturer Not Available
Model Not Available
Bytes/Sector 512
Media Loaded Yes
Media Type Fixed hard disk
Partitions 1
SCSI Bus Not Available
SCSI Logical Unit Not Available

SCSI Port Not Available
 SCSI Target ID Not Available
 Sectors/Track 63
 Size 71.28 GB (76,536,230,400 bytes)
 Total Cylinders 9,305
 Total Sectors 149,484,825
 Total Tracks 2,372,775
 Tracks/Cylinder 255
 Partition Disk #0, Partition #0
 Partition Size 71.28 GB (76,535,562,240 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE1
 Manufacturer Not Available
 Model Not Available
 Bytes/Sector 512
 Media Loaded Yes
 Media Type Fixed hard disk
 Partitions 1
 SCSI Bus Not Available
 SCSI Logical Unit Not Available
 SCSI Port Not Available
 SCSI Target ID Not Available
 Sectors/Track 63
 Size 35.15 GB (37,745,809,920 bytes)
 Total Cylinders 4,589
 Total Sectors 73,722,285
 Total Tracks 1,170,195
 Tracks/Cylinder 255
 Partition Disk #1, Partition #0
 Partition Size 35.15 GB (37,745,590,272 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE2
 Manufacturer Not Available
 Model Not Available
 Bytes/Sector 512
 Media Loaded Yes
 Media Type Fixed hard disk
 Partitions 1
 SCSI Bus Not Available
 SCSI Logical Unit Not Available
 SCSI Port Not Available
 SCSI Target ID Not Available
 Sectors/Track 63
 Size 71.28 GB (76,536,230,400 bytes)
 Total Cylinders 9,305
 Total Sectors 149,484,825
 Total Tracks 2,372,775
 Tracks/Cylinder 255
 Partition Disk #2, Partition #0
 Partition Size 71.28 GB (76,535,562,240 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE3
 Manufacturer Not Available
 Model Not Available
 Bytes/Sector 512
 Media Loaded Yes
 Media Type Fixed hard disk

Partitions 1
 SCSI Bus Not Available
 SCSI Logical Unit Not Available
 SCSI Port Not Available
 SCSI Target ID Not Available
 Sectors/Track 63
 Size 35.15 GB (37,745,809,920 bytes)
 Total Cylinders 4,589
 Total Sectors 73,722,285
 Total Tracks 1,170,195
 Tracks/Cylinder 255
 Partition Disk #3, Partition #0
 Partition Size 35.15 GB (37,745,590,272 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE16
 Manufacturer Not Available
 Model Not Available
 Bytes/Sector 512
 Media Loaded Yes
 Media Type Fixed hard disk
 Partitions 1
 SCSI Bus Not Available
 SCSI Logical Unit Not Available
 SCSI Port Not Available
 SCSI Target ID Not Available
 Sectors/Track 63
 Size 71.28 GB (76,536,230,400 bytes)
 Total Cylinders 9,305
 Total Sectors 149,484,825
 Total Tracks 2,372,775
 Tracks/Cylinder 255
 Partition Disk #16, Partition #0
 Partition Size 71.28 GB (76,535,562,240 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE17
 Manufacturer Not Available
 Model Not Available
 Bytes/Sector 512
 Media Loaded Yes
 Media Type Fixed hard disk
 Partitions 1
 SCSI Bus Not Available
 SCSI Logical Unit Not Available
 SCSI Port Not Available
 SCSI Target ID Not Available
 Sectors/Track 63
 Size 35.15 GB (37,745,809,920 bytes)
 Total Cylinders 4,589
 Total Sectors 73,722,285
 Total Tracks 1,170,195
 Tracks/Cylinder 255
 Partition Disk #17, Partition #0
 Partition Size 35.15 GB (37,745,590,272 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE18
 Manufacturer Not Available
 Model Not Available

Bytes/Sector 512
 Media Loaded Yes
 Media Type Fixed hard disk
 Partitions 1
 SCSI Bus Not Available
 SCSI Logical Unit Not Available
 SCSI Port Not Available
 SCSI Target ID Not Available
 Sectors/Track 63
 Size 71.28 GB (76,536,230,400 bytes)
 Total Cylinders 9,305
 Total Sectors 149,484,825
 Total Tracks 2,372,775
 Tracks/Cylinder 255
 Partition Disk #18, Partition #0
 Partition Size 71.28 GB (76,535,562,240 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE19
 Manufacturer Not Available
 Model Not Available
 Bytes/Sector 512
 Media Loaded Yes
 Media Type Fixed hard disk
 Partitions 1
 SCSI Bus Not Available
 SCSI Logical Unit Not Available
 SCSI Port Not Available
 SCSI Target ID Not Available
 Sectors/Track 63
 Size 35.15 GB (37,745,809,920 bytes)
 Total Cylinders 4,589
 Total Sectors 73,722,285
 Total Tracks 1,170,195
 Tracks/Cylinder 255
 Partition Disk #19, Partition #0
 Partition Size 35.15 GB (37,745,590,272 bytes)

Partition Starting Offset 65,536 bytes

Description \\.\PHYSICALDRIVE20
 Manufacturer Not Available
 Model Not Available
 Bytes/Sector 512
 Media Loaded Yes
 Media Type Fixed hard disk
 Partitions 1
 SCSI Bus Not Available
 SCSI Logical Unit Not Available
 SCSI Port Not Available
 SCSI Target ID Not Available
 Sectors/Track 63
 Size 421.57 GB (452,653,608,960 bytes)
 Total Cylinders 55,032
 Total Sectors 884,089,080
 Total Tracks 14,033,160
 Tracks/Cylinder 255
 Partition Disk #20, Partition #0
 Partition Size 421.57 GB (452,653,576,704 bytes)

Partition Starting Offset 32,256 bytes

```

Description      Disk drive
Manufacturer     (Standard disk drives)
Model            COMPAQ LOGICAL VOLUME SCSI Disk Device
Bytes/Sector     512
Media Loaded     Yes
Media Type       Fixed hard disk
Partitions       1
SCSI Bus         0
SCSI Logical Unit 0
SCSI Port 1
SCSI Target ID  4
Sectors/Track   32
Size            33.91 GB (36,414,750,720 bytes)
Total Cylinders  8,716
Total Sectors    71,122,560
Total Tracks     2,222,580
Tracks/Cylinder  255
Partition Disk #34, Partition #0
Partition Size   33.91 GB (36,410,556,416 bytes)

Partition Starting Offset 16,384 bytes

[SCSI]

Item      Value
Name     Smart Array 5i
Manufacturer      Compaq
Status          OK
PNP Device ID    PCI\VEN_0E11&DEV_B178&SUBSYS_40800E11&REV_0
1\4&82820FC&0&2038
Memory Address  0xF77C0000-0xF77FFFFF
I/O Port       0x00005000-0x00005FFF
Memory Address  0xF5EF0000-0xF5EF3FFF
IRQ Channel     IRQ 18
Driver          c:\windows\system32\drivers\hpcisss.sys
(5.11.0.64 Build 2 (x86-64) (NT.041115-0204), 30.50
KB (31,232 bytes), 3/25/2005 6:00 AM)

Name      Smart Array 6400 Controller (Non-Miniport)

Manufacturer      Hewlett-Packard
Status            OK
PNP Device ID     PCI\VEN_0E11&DEV_0046&SUBSYS_409C0E11&REV_0
1\5&2C344C1F&0&203840
Memory Address    0xF78F0000-0xF78F1FFF
I/O Port          0x00006000-0x00007FFF
IRQ Channel       IRQ 28
Driver            c:\windows\system32\drivers\hpcqissb.sys
(5.14.2.64 Build 1 (AMD64) built by: kadambi, 55.00
KB (56,320 bytes), 7/15/2005 9:50 AM)

Name      Smart Array 6400 Controller U320 Expansion
Module (Non-Miniport)
Manufacturer      Hewlett-Packard
Status            OK
PNP Device ID     PCI\VEN_0E11&DEV_0046&SUBSYS_409D0E11&REV_0
1\5&2C344C1F&0&283840
Memory Address    0xF7870000-0xF7871FFF
I/O Port          0x00006400-0x000064FF
IRQ Channel       IRQ 29

```

```

Driver          c:\windows\system32\drivers\hpcqissb.sys
(5.14.2.64 Build 1 (AMD64) built by: kadambi, 55.00
KB (56,320 bytes), 7/15/2005 9:50 AM)

Name      Smart Array 6400 Controller (Non-Miniport)

Manufacturer      Hewlett-Packard
Status            OK
PNP Device ID     PCI\VEN_0E11&DEV_0046&SUBSYS_409C0E11&REV_0
1\5&2363B0A8&0&204040
Memory Address    0xF79F0000-0xF79F1FFF
I/O Port          0x00007000-0x00007FFF
IRQ Channel       IRQ 30
Driver          c:\windows\system32\drivers\hpcqissb.sys
(5.14.2.64 Build 1 (AMD64) built by: kadambi, 55.00
KB (56,320 bytes), 7/15/2005 9:50 AM)

Name      Smart Array 6400 Controller U320 Expansion
Module (Non-Miniport)
Manufacturer      Hewlett-Packard
Status            OK
PNP Device ID     PCI\VEN_0E11&DEV_0046&SUBSYS_409D0E11&REV_0
1\5&2363B0A8&0&284040
Memory Address    0xF7970000-0xF7971FFF
I/O Port          0x00007400-0x000074FF
IRQ Channel       IRQ 31
Driver          c:\windows\system32\drivers\hpcqissb.sys
(5.14.2.64 Build 1 (AMD64) built by: kadambi, 55.00
KB (56,320 bytes), 7/15/2005 9:50 AM)

Name      Smart Array 6400 Controller (Non-Miniport)

Manufacturer      Hewlett-Packard
Status            OK
PNP Device ID     PCI\VEN_0E11&DEV_0046&SUBSYS_409C0E11&REV_0
1\5&56DD264&0&206848
Memory Address    0xF7AF0000-0xF7AF1FFF
I/O Port          0x00008000-0x0000DFFF
IRQ Channel       IRQ 32
Driver          c:\windows\system32\drivers\hpcqissb.sys
(5.14.2.64 Build 1 (AMD64) built by: kadambi, 55.00
KB (56,320 bytes), 7/15/2005 9:50 AM)

Name      Smart Array 6400 Controller U320 Expansion
Module (Non-Miniport)
Manufacturer      Hewlett-Packard
Status            OK
PNP Device ID     PCI\VEN_0E11&DEV_0046&SUBSYS_409D0E11&REV_0
1\5&56DD264&0&286848
Memory Address    0xF7A70000-0xF7A71FFF
I/O Port          0x00008400-0x000084FF
IRQ Channel       IRQ 33
Driver          c:\windows\system32\drivers\hpcqissb.sys
(5.14.2.64 Build 1 (AMD64) built by: kadambi, 55.00
KB (56,320 bytes), 7/15/2005 9:50 AM)

Name      Smart Array 6400 Controller (Non-Miniport)

Manufacturer      Hewlett-Packard

```

```

Status          OK
PNP Device ID   PCI\VEN_0E11&DEV_0046&SUBSYS_409C0E11&REV_0
1\5&25998046&0&207050
Memory Address  0xF7BF0000-0xF7BF1FFF
I/O Port       0x00009000-0x00009FFF
IRQ Channel     IRQ 36
Driver          c:\windows\system32\drivers\hpcqissb.sys
(5.14.2.64 Build 1 (AMD64) built by: kadambi, 55.00
KB (56,320 bytes), 7/15/2005 9:50 AM)

Name      Smart Array 6400 Controller U320 Expansion
Module (Non-Miniport)
Manufacturer      Hewlett-Packard
Status            OK
PNP Device ID     PCI\VEN_0E11&DEV_0046&SUBSYS_409D0E11&REV_0
1\5&25998046&0&287050
Memory Address  0xF7B70000-0xF7B71FFF
I/O Port       0x00009400-0x000094FF
IRQ Channel     IRQ 37
Driver          c:\windows\system32\drivers\hpcqissb.sys
(5.14.2.64 Build 1 (AMD64) built by: kadambi, 55.00
KB (56,320 bytes), 7/15/2005 9:50 AM)

Name      Smart Array 6400 Controller (Non-Miniport)

Manufacturer      Hewlett-Packard
Status            OK
PNP Device ID     PCI\VEN_0E11&DEV_0046&SUBSYS_409C0E11&REV_0
1\5&1B3A307E&0&204858
Memory Address  0xF7DF0000-0xF7DF1FFF
I/O Port       0x0000B000-0x0000BFFF
IRQ Channel     IRQ 40
Driver          c:\windows\system32\drivers\hpcqissb.sys
(5.14.2.64 Build 1 (AMD64) built by: kadambi, 55.00
KB (56,320 bytes), 7/15/2005 9:50 AM)

Name      Smart Array 6400 Controller U320 Expansion
Module (Non-Miniport)
Manufacturer      Hewlett-Packard
Status            OK
PNP Device ID     PCI\VEN_0E11&DEV_0046&SUBSYS_409D0E11&REV_0
1\5&1B3A307E&0&284858
Memory Address  0xF7D70000-0xF7D71FFF
I/O Port       0x0000B400-0x0000B4FF
IRQ Channel     IRQ 41
Driver          c:\windows\system32\drivers\hpcqissb.sys
(5.14.2.64 Build 1 (AMD64) built by: kadambi, 55.00
KB (56,320 bytes), 7/15/2005 9:50 AM)

Name      Smart Array 642 Controller (Non-Miniport)

Manufacturer      Hewlett-Packard
Status            OK
PNP Device ID     PCI\VEN_0E11&DEV_0046&SUBSYS_409B0E11&REV_0
1\4&2534A57B&0&5058
Memory Address  0xF7CF0000-0xF7CF1FFF
I/O Port       0x0000A000-0x0000BFFF
Memory Address  0xF7C80000-0xF7CBFFFF

```

```

IRQ Channel      IRQ 42
Driver c:\windows\system32\drivers\hpcqciissb.sys
(5.14.2.64 Build 1 (AMD64) built by: kadambi, 55.00
KB (56,320 bytes), 7/15/2005 9:50 AM)

Name      Smart Array 6400 Controller (Non-Miniport)

Manufacturer      Hewlett-Packard
Status OK
PNP Device ID
PCI\VEN_0E11&DEV_0046&SUBSYS_409C0E11&REV_0
1\5&30FCE3FC&0&205860
Memory Address 0xF7EF0000-0xF7EF1FFF
I/O Port 0x0000C000-0x0000DFFF
IRQ Channel      IRQ 44
Driver c:\windows\system32\drivers\hpcqciissb.sys
(5.14.2.64 Build 1 (AMD64) built by: kadambi, 55.00
KB (56,320 bytes), 7/15/2005 9:50 AM)

Name      Smart Array 6400 Controller U320 Expansion
Module (Non-Miniport)
Manufacturer      Hewlett-Packard
Status OK
PNP Device ID
PCI\VEN_0E11&DEV_0046&SUBSYS_409D0E11&REV_0
1\5&30FCE3FC&0&285860
Memory Address 0xF7E70000-0xF7E71FFF
I/O Port 0x0000C400-0x0000C4FF
IRQ Channel      IRQ 45
Driver c:\windows\system32\drivers\hpcqciissb.sys
(5.14.2.64 Build 1 (AMD64) built by: kadambi, 55.00
KB (56,320 bytes), 7/15/2005 9:50 AM)

Name      Smart Array 6400 Controller (Non-Miniport)

Manufacturer      Hewlett-Packard
Status OK
PNP Device ID
PCI\VEN_0E11&DEV_0046&SUBSYS_409C0E11&REV_0
1\5&282C4885&0&206060
Memory Address 0xF7FF0000-0xF7FF1FFF
I/O Port 0x0000D000-0x0000DFFF
IRQ Channel      IRQ 46
Driver c:\windows\system32\drivers\hpcqciissb.sys
(5.14.2.64 Build 1 (AMD64) built by: kadambi, 55.00
KB (56,320 bytes), 7/15/2005 9:50 AM)

Name      Smart Array 6400 Controller U320 Expansion
Module (Non-Miniport)
Manufacturer      Hewlett-Packard
Status OK
PNP Device ID
PCI\VEN_0E11&DEV_0046&SUBSYS_409D0E11&REV_0
1\5&282C4885&0&286060
Memory Address 0xF7F70000-0xF7F71FFF
I/O Port 0x0000D400-0x0000D4FF
IRQ Channel      IRQ 47
Driver c:\windows\system32\drivers\hpcqciissb.sys
(5.14.2.64 Build 1 (AMD64) built by: kadambi, 55.00
KB (56,320 bytes), 7/15/2005 9:50 AM)

[IDE]

```

```

Item      Value
Name      AMD-8111 PCI Bus Master IDE Controller
Manufacturer      Advanced Micro Devices
Status OK
PNP Device ID
PCI\VEN_1022&DEV_7469&SUBSYS_32040E11&REV_0
3\3&20FEA912&0&21
I/O Port 0x00002000-0x0000200F
Driver c:\windows\system32\drivers\amdide.sys
(5.2.3790.1830 (srv03_spl_rtm.050324-1447), 8.00 KB
(8,192 bytes), 3/25/2005 6:00 AM)

Name      Primary IDE Channel
Manufacturer      (Standard IDE ATA/ATAPI
controllers)
Status OK
PNP Device ID
PCI\IDE\IDECHANNEL\4&21637DBD&0&0

I/O Port 0x000001F0-0x000001F7
I/O Port 0x000003F6-0x000003F6
IRQ Channel      IRQ 14
Driver c:\windows\system32\drivers\atapi.sys
(5.2.3790.1830 (srv03_spl_rtm.050324-1447), 145.00 KB
(148,480 bytes), 3/25/2005 6:00 AM)

[Printing]

Name      Driver      Port Name Server Name

[Problem Devices]

Device      PNP Device ID      Error Code
Base System Device
PCI\VEN_0E11&DEV_B203&SUBSYS_B2060E11&REV_0
1\4&12365AD0&0&1018 The drivers for this device are
not installed.
Base System Device
PCI\VEN_0E11&DEV_B204&SUBSYS_B2060E11&REV_0
1\4&12365AD0&0&1218 The drivers for this device are
not installed.

[USB]

Device      PNP Device ID
AMD PCI to USB Open Host Controller
PCI\VEN_1022&DEV_7464&SUBSYS_32020E11&REV_0
B\4&12365AD0&0&0018
AMD PCI to USB Open Host Controller
PCI\VEN_1022&DEV_7464&SUBSYS_32020E11&REV_0
B\4&12365AD0&0&0118

[Software Environment]

[System Drivers]

Name      Description      File      Type
Started      Start Mode      State
Status      Error Control      Accept Pause
Accept Stop

```

```

abiosdsk  Abiosdsk  Not Available      Kernel Driver
No      Disabled      Stopped      OK
Ignore  No      No

acpi      Microsoft ACPI Driver
c:\windows\system32\drivers\acpi.sys
Kernel Driver      Yes      Boot
Running      OK      Normal      No      Yes

acpiec   ACPIEC
c:\windows\system32\drivers\acpiec.sys
Kernel Driver      No      Disabled
Stopped      OK      Normal      No      No

adpu160m adpu160m  Not Available      Kernel Driver
No      Disabled      Stopped      OK
Normal      No      No

adpu320  adpu320  Not Available      Kernel Driver
No      Disabled      Stopped      OK
Normal      No      No

afd      AFD
c:\windows\system32\drivers\afd.sys
Kernel Driver      Yes      System
Running      OK      Normal      No      Yes

aic78u2  aic78u2  Not Available      Kernel Driver
No      Disabled      Stopped      OK
Normal      No      No

aic78xx  aic78xx  Not Available      Kernel Driver
No      Disabled      Stopped      OK
Normal      No      No

aliide   AliIde   Not Available      Kernel Driver
No      Disabled      Stopped      OK
Normal      No      No

amdide   AmdIde   c:\windows\system32\drivers\amdide.sys
Kernel Driver      Yes      Boot
Running      OK      Normal      No      Yes

arc      arc      Not Available      Kernel Driver
No      Disabled      Stopped      OK
Normal      No      No

asynctac RAS Asynchronous Media Driver
c:\windows\system32\drivers\asynctac.sys
Kernel Driver      No      Manual
Stopped      OK      Normal      No      No

atapi    Standard IDE/ESDI Hard Disk Controller
c:\windows\system32\drivers\atapi.sys
Kernel Driver      Yes      Boot
Running      OK      Normal      No      Yes

atdisk   Atdisk   Not Available      Kernel Driver
No      Disabled      Stopped      OK
Ignore      No      No

ati2mpad ati2mpad
c:\windows\system32\drivers\ati2mpad.sys
Kernel Driver      Yes      Manual
Running      OK      Ignore      No      Yes

atmarpc  ATM ARP Client Protocol
c:\windows\system32\drivers\atmarpc.sys
Kernel Driver      No      Manual

```

	Stopped	OK	Normal	No	No		Kernel Driver	Yes	Boot			Running	OK	Normal	No	Yes
audstub	Audio Stub Driver						Running	OK	Normal	No	Yes	hpqcissb	Smart Array Controllers Non-Miniport Bus Driver			
	c:\windows\system32\drivers\audstub.sys						dmboot	dmboot					c:\windows\system32\drivers\hpqcissb.sys			
	Kernel Driver	Yes	Manual					c:\windows\system32\drivers\dmboot.sys					Kernel Driver	Yes	Boot	
	Running	OK	Normal	No	Yes			Stopped	OK	Normal	No	No	Running	OK	Normal	Yes
b57nd	Broadcom NetXtreme Gigabit Ethernet						dmio	Logical Disk Manager Driver				hpqcissd	Smart Array Controllers Non-Miniport Disk Driver			
	c:\windows\system32\drivers\b57amd64.sys							c:\windows\system32\drivers\dmio.sys					c:\windows\system32\drivers\hpqcissd.sys			
	Kernel Driver	Yes	Manual					Kernel Driver	Yes	Boot			Kernel Driver	Yes	Boot	
	Running	OK	Normal	No	Yes			Running	OK	Normal	No	Yes	Running	OK	Normal	Yes
beep	Beep						dmload	dmload				http	HTTP			
	c:\windows\system32\drivers\beep.sys							c:\windows\system32\drivers\dmload.sys					c:\windows\system32\drivers\http.sys			
	Kernel Driver	Yes	System					Kernel Driver	Yes	Boot			Kernel Driver	No	Manual	
	Running	OK	Normal	No	Yes			Running	OK	Normal	No	Yes	Stopped	OK	Normal	No
cdac15ba	CdaCl5BA						dpti2o	dpti2o	Not Available	Kernel Driver		i2omgmt	i2omgmt	Not Available	Kernel Driver	
	c:\windows\system32\drivers\cdac15ba.sys							No	Disabled	Stopped	OK		No	System	Stopped	OK
	Kernel Driver	Yes	Auto					Normal	No	No			Normal	No	No	
	Running	OK	Normal	No	Yes			Normal	No	No			Running	OK	Normal	Yes
cdad10ba	CdaD10BA						elxstor	elxstor	Not Available	Kernel Driver		i8042prt	i8042 Keyboard and PS/2 Mouse Port Driver			
	c:\windows\system32\drivers\cdad10ba.sys							No	Disabled	Stopped	OK		c:\windows\system32\drivers\i8042prt.sys			
	Kernel Driver	Yes	Auto					Normal	No	No			Kernel Driver	Yes	System	
	Running	OK	Normal	No	Yes			Normal	No	No			Running	OK	Normal	Yes
cdfs	Cdfs						fastfat	Fastfat				iirsp	iirsp	Not Available	Kernel Driver	
	c:\windows\system32\drivers\cdfs.sys							File System Driver	No	Disabled			No	Disabled	Stopped	OK
	File System Driver	Yes	Disabled					Stopped	OK	Normal	No	No	Normal	No	No	
	Running	OK	Normal	No	Yes			Stopped	OK	Normal	No	No	Normal	No	No	
cdrom	CD-ROM Driver						fdc	Floppy Disk Controller Driver				imapi	CD-Burning Filter Driver			
	c:\windows\system32\drivers\cdrom.sys							c:\windows\system32\drivers\fdc.sys					c:\windows\system32\drivers\imapi.sys			
	Kernel Driver	Yes	System					Kernel Driver	Yes	Manual			Kernel Driver	No	System	
	Running	OK	Normal	No	Yes			Running	OK	Normal	No	Yes	Stopped	OK	Normal	No
changer	Changer	Not Available	Kernel Driver				fips	Fips				intelide	IntelIde	Not Available	Kernel Driver	
	No	System	Stopped	OK				c:\windows\system32\drivers\fips.sys					No	Disabled	Stopped	OK
	Ignore	No	No					Kernel Driver	Yes	System			Normal	No	No	
	Kernel Driver	Yes	System					Running	OK	Normal	No	Yes	Running	OK	Normal	Yes
	Running	OK	Normal	No	Yes			Running	OK	Normal	No	Yes	Running	OK	Normal	Yes
clusdisk	Cluster Disk Driver						flpydisk	Floppy Disk Driver				ip6fw	IPv6 Windows Firewall Driver			
	c:\windows\system32\drivers\clusdisk.sys							c:\windows\system32\drivers\flpydisk.sys					c:\windows\system32\drivers\ip6fw.sys			
	Kernel Driver	No	Disabled					Kernel Driver	Yes	Manual			Kernel Driver	No	Manual	
	Stopped	OK	Normal	No	No			Running	OK	Normal	No	Yes	Stopped	OK	Normal	No
cmdide	CmdIde	Not Available	Kernel Driver				fltmgr	FltMgr				ipfilterdriver	IP Traffic Filter Driver			
	No	Disabled	Stopped	OK				c:\windows\system32\drivers\fltmgr.sys					c:\windows\system32\drivers\ipfltdrv.sys			
	Normal	No	No					File System Driver	Yes	Boot			Kernel Driver	No	Manual	
	Kernel Driver	Yes	System					Running	OK	Normal	No	Yes	Stopped	OK	Normal	No
	Running	OK	Normal	No	Yes			Running	OK	Normal	No	Yes	Running	OK	Normal	No
cpqcissm	cpqcissm	Not Available	Kernel Driver				ftdisk	Volume Manager Driver				ipnat	IP Network Address Translator			
	No	Disabled	Stopped	OK				c:\windows\system32\drivers\ftdisk.sys					c:\windows\system32\drivers\ipnat.sys			
	Normal	No	No					Kernel Driver	Yes	Boot			Kernel Driver	No	Manual	
	Kernel Driver	Yes	System					Running	OK	Normal	No	Yes	Stopped	OK	Normal	No
	Running	OK	Normal	No	Yes			Running	OK	Normal	No	Yes	Running	OK	Normal	No
crdisk	CRC Disk Filter Driver						gpc	Generic Packet Classifier				ipsec	IPSEC driver			
	c:\windows\system32\drivers\crdisk.sys							c:\windows\system32\drivers\msgpc.sys					c:\windows\system32\drivers\ipsec.sys			
	Kernel Driver	Yes	Boot					Kernel Driver	Yes	Manual			Kernel Driver	Yes	System	
	Running	OK	Normal	No	Yes			Running	OK	Normal	No	Yes	Running	OK	Normal	No
	Running	OK	Normal	No	Yes			Running	OK	Normal	No	Yes	Running	OK	Normal	No
dfsdriver	DfsDriver						hpcisss	hpcisss				isapnp	PnP ISA/EISA Bus Driver			
	c:\windows\system32\drivers\dfs.sys							c:\windows\system32\drivers\hpcisss.sys					c:\windows\system32\drivers\isapnp.sys			
	File System Driver	Yes	Boot					Kernel Driver	Yes	Boot			Kernel Driver	Yes	Boot	
	Running	OK	Normal	No	Yes			Running	OK	Normal	No	Yes	Running	OK	Normal	Yes
	Running	OK	Normal	No	Yes			Running	OK	Normal	No	Yes	Running	OK	Normal	Yes
disk	Disk Driver															
	c:\windows\system32\drivers\disk.sys															

	Kernel Driver	Yes	Boot			Running	OK	Normal	No	Yes		Stopped	OK	Ignore	No	No	
	Running	OK	Critical	No	Yes												
kbdclass	Keyboard Class Driver					mup	Mup					partmgr	Partition Manager				
	c:\windows\system32\drivers\kbdclass.sys						c:\windows\system32\drivers\mup.sys						c:\windows\system32\drivers\partmgr.sys				
	Kernel Driver	Yes	System				File System Driver	Yes	Boot				Kernel Driver	Yes	Boot		
	Running	OK	Normal	No	Yes		Running	OK	Normal	No	Yes		Running	OK	Normal	No	Yes
ksecdd	KSecDD					ndis	NDIS System Driver					pci	PCI Bus Driver				
	c:\windows\system32\drivers\ksecdd.sys						c:\windows\system32\drivers\ndis.sys						c:\windows\system32\drivers\pci.sys				
	Kernel Driver	Yes	Boot				Kernel Driver	Yes	Boot				Kernel Driver	Yes	Boot		
	Running	OK	Normal	No	Yes		Running	OK	Normal	No	Yes		Running	OK	Critical	No	Yes
ksthunk	Kernel Streaming WOW64 Thunk Service					ndistapi	Remote Access NDIS TAPI Driver					pciide	PCIIde	Not Available		Kernel Driver	
	c:\windows\system32\drivers\ksthunk.sys						c:\windows\system32\drivers\ndistapi.sys						No	Disabled	Stopped	OK	
	Kernel Driver	Yes	Manual				Kernel Driver	Yes	Manual				Normal	No	No		
	Running	OK	Normal	No	Yes		Running	OK	Normal	No	Yes		Running	OK	Normal	No	Yes
lp6nds35	lp6nds35	Not Available		Kernel Driver		ndisuiio	NDIS Usermode I/O Protocol					pcmcia	Pcmcia				
	No	Disabled	Stopped	OK			c:\windows\system32\drivers\ndisuiio.sys						c:\windows\system32\drivers\pcmcia.sys				
	Normal	No	No				Kernel Driver	No	Manual				Kernel Driver	No	Disabled		
	Running	OK	Ignore	No	Yes		Stopped	OK	Normal	No	No		Stopped	OK	Normal	No	No
mnmdd	mnmdd					ndiswan	Remote Access NDIS WAN Driver					pdcomp	PDCOMP	Not Available		Kernel Driver	
	c:\windows\system32\drivers\mnmdd.sys						c:\windows\system32\drivers\ndiswan.sys						No	Manual	Stopped	OK	
	Kernel Driver	Yes	System				Kernel Driver	Yes	Manual				Ignore	No	No		
	Running	OK	Ignore	No	Yes		Running	OK	Normal	No	Yes		Ignore	No	No		
modem	Modem					ndproxy	NDIS Proxy					pdreli	PDRELI	Not Available		Kernel Driver	
	c:\windows\system32\drivers\modem.sys						c:\windows\system32\drivers\ndproxy.sys						No	Manual	Stopped	OK	
	Kernel Driver	No	Manual				Kernel Driver	Yes	Manual				Ignore	No	No		
	Stopped	OK	Ignore	No	No		Running	OK	Normal	No	Yes		Ignore	No	No		
mouclass	Mouse Class Driver					netbios	NetBIOS Interface					pdrframe	PDRFRAME	Not Available		Kernel Driver	
	c:\windows\system32\drivers\mouclass.sys						c:\windows\system32\drivers\netbios.sys						No	Manual	Stopped	OK	
	Kernel Driver	Yes	System				File System Driver	Yes	System				Ignore	No	No		
	Running	OK	Normal	No	Yes		Running	OK	Normal	No	Yes		Ignore	No	No		
mountmgr	Mount Point Manager					netbt	NetBios over Tcpip					pptpminiport	WAN Miniport (PPTP)				
	c:\windows\system32\drivers\mountmgr.sys						c:\windows\system32\drivers\netbt.sys						c:\windows\system32\drivers\raspttp.sys				
	Kernel Driver	Yes	Boot				Kernel Driver	Yes	System				Kernel Driver	Yes	Manual		
	Running	OK	Normal	No	Yes		Running	OK	Normal	No	Yes		Running	OK	Normal	No	Yes
mraid35x	mraid35x	Not Available		Kernel Driver		nfrd960	nfrd960	Not Available		Kernel Driver		ptilink	Direct Parallel Link Driver				
	No	Disabled	Stopped	OK			No	Disabled	Stopped	OK			c:\windows\system32\drivers\ptilink.sys				
	Normal	No	No				Normal	No	No				Kernel Driver	Yes	Manual		
mrxdav	WebDav Client Redirector					npfs	Npfs						Running	OK	Normal	No	Yes
	c:\windows\system32\drivers\mrxdav.sys						c:\windows\system32\drivers\npfs.sys						q12300	q12300	Not Available		Kernel Driver
	File System Driver	No	Manual				File System Driver	Yes	System				No	Disabled	Stopped	OK	
	Stopped	OK	Normal	No	No		Running	OK	Normal	No	Yes		Normal	No	No		
mrxsmb	MRXSMB					ntfs	Ntfs					rasacd	Remote Access Auto Connection Driver				
	c:\windows\system32\drivers\mrxsmb.sys						c:\windows\system32\drivers\ntfs.sys						c:\windows\system32\drivers\rasacd.sys				
	File System Driver	Yes	System				File System Driver	Yes	Disabled				Kernel Driver	Yes	System		
	Running	OK	Normal	No	Yes		Running	OK	Normal	No	Yes		Running	OK	Normal	No	Yes
msfs	Msfs					null	Null					rasl2tp	WAN Miniport (L2TP)				
	c:\windows\system32\drivers\msfs.sys						c:\windows\system32\drivers\null.sys						c:\windows\system32\drivers\rasl2tp.sys				
	File System Driver	Yes	System				Kernel Driver	Yes	System				Kernel Driver	Yes	Manual		
	Running	OK	Normal	No	Yes		Running	OK	Normal	No	Yes		Running	OK	Normal	No	Yes
mssmbios	Microsoft System Management BIOS Driver					parport	Parport					raspppoe	Remote Access PPPOE Driver				
	c:\windows\system32\drivers\mssmbios.sys						c:\windows\system32\drivers\parport.sys						c:\windows\system32\drivers\raspppoe.sys				
	Kernel Driver	Yes	Manual				Kernel Driver	No	Manual				Kernel Driver	Yes	Manual		

	Running	OK	Normal	No	Yes		Running	OK	Normal	No	Yes		Stopped	OK	Ignore	No	No
raspti	Direct Parallel c:\windows\system32\drivers\raspti.sys Kernel Driver Yes Manual Running OK Normal No Yes						symc8xx symc8xx Not Available Kernel Driver No Disabled Stopped OK Normal No No						vgasave VGA Display Controller. c:\windows\system32\drivers\vga.sys Kernel Driver Yes System Running OK Ignore No Yes				
rdbss	Rdbss c:\windows\system32\drivers\rdbss.sys File System Driver Yes System Running OK Normal No Yes						symmpi symmpi Not Available Kernel Driver No Disabled Stopped OK Normal No No						viaide ViaIde Not Available Kernel Driver No Disabled Stopped OK Normal No No				
rdpcdd	RDPCDD c:\windows\system32\drivers\rdpcdd.sys Kernel Driver Yes System Running OK Ignore No Yes						sym_u3 sym_u3 Not Available Kernel Driver No Disabled Stopped OK Normal No No						volsnap Storage volumes c:\windows\system32\drivers\volsnap.sys Kernel Driver Yes Boot Running OK Normal No Yes				
rdpdr	Terminal Server Device Redirector Driver c:\windows\system32\drivers\rdpdr.sys Kernel Driver Yes Manual Running OK Normal No Yes						tcpip TCP/IP Protocol Driver c:\windows\system32\drivers\tcpip.sys Kernel Driver Yes System Running OK Normal No Yes						wanarp Remote Access IP ARP Driver c:\windows\system32\drivers\wanarp.sys Kernel Driver Yes Manual Running OK Normal No Yes				
rdpwd	RDPWD c:\windows\system32\drivers\rdpwd.sys Kernel Driver Yes Manual Running OK Ignore No Yes						tdpipe TDPIPE c:\windows\system32\drivers\tdpipe.sys Kernel Driver No Manual Stopped OK Ignore No No						wdica WDICA Not Available Kernel Driver No Manual Stopped OK Ignore No No				
redbook	Digital CD Audio Playback Filter Driver c:\windows\system32\drivers\redbook.sys Kernel Driver Yes System Running OK Normal No Yes						tdtcp TDTCP c:\windows\system32\drivers\tdtcp.sys Kernel Driver Yes Manual Running OK Ignore No Yes						wlbs Network Load Balancing c:\windows\system32\drivers\wlbs.sys Kernel Driver No Manual Stopped OK Normal No No				
secdrv	Security Driver c:\windows\system32\drivers\secdrv.sys Kernel Driver Yes Auto Running OK Normal No Yes						termdd Terminal Device Driver c:\windows\system32\drivers\termdd.sys Kernel Driver Yes System Running OK Normal No Yes						[Signed Drivers]				
serenum	Serenum Filter Driver c:\windows\system32\drivers\serenum.sys Kernel Driver Yes Manual Running OK Normal No Yes						toside TosIde Not Available Kernel Driver No Disabled Stopped OK Normal No No						Device Name Signed Device Class Driver Version Driver Date Manufacturer INF Name Driver Name Device ID				
serial	Serial port driver c:\windows\system32\drivers\serial.sys Kernel Driver Yes System Running OK Ignore No Yes						udfs Udfs c:\windows\system32\drivers\udfs.sys File System Driver No Disabled Stopped OK Normal No No						Microsoft System Management BIOS Driver Yes SYSTEM 5.2.3790.1830 10/1/2002 (Standard system devices) machine.inf Not Available ROOT\SYSTEM\0002				
sfloppy	Sfloppy c:\windows\system32\drivers\sfloppy.sys Kernel Driver No System Stopped OK Ignore No No						ultra ultra Not Available Kernel Driver No Disabled Stopped OK Normal No No						Microcode Update Device Yes SYSTEM 5.2.3790.1830 10/1/2002 (Standard system devices) machine.inf Not Available ROOT\SYSTEM\0001				
simbad	Simbad Not Available Kernel Driver No Disabled Stopped OK Normal No No						update Microcode Update Driver c:\windows\system32\drivers\update.sys Kernel Driver Yes Manual Running OK Normal No Yes						Plug and Play Software Device Enumerator Yes SYSTEM 5.2.3790.1830 10/1/2002 (Standard system devices) machine.inf Not Available ROOT\SYSTEM\0000				
srv	Srv c:\windows\system32\drivers\srv.sys File System Driver Yes Manual Running OK Normal No Yes						usbhub USB2 Enabled Hub c:\windows\system32\drivers\usbhub.sys Kernel Driver Yes Manual Running OK Normal No Yes						Terminal Server Mouse Driver Yes SYSTEM 5.2.3790.1830 10/1/2002 (Standard system devices) machine.inf Not Available ROOT\RDP_MOU\0000				
swenum	Software Bus Driver c:\windows\system32\drivers\swenum.sys Kernel Driver Yes Manual						usbohci Microsoft USB Open Host Controller Miniport Driver c:\windows\system32\drivers\usbohci.sys Kernel Driver Yes Manual Running OK Normal No Yes						Terminal Server Keyboard Driver Yes SYSTEM 5.2.3790.1830 10/1/2002 (Standard system devices) machine.inf Not Available ROOT\RDP_KBD\0000				
							vga vga c:\windows\system32\drivers\vgapnp.sys Kernel Driver No Manual						Direct Parallel Yes NET 5.2.3790.1830 10/1/2002 Microsoft netrassa.inf Not Available ROOT\MS_PTMINIPORT\0000				

WAN Miniport (PPTP)	Yes	NET	5.2.3790.1830
10/1/2002 Microsoft	netrasa.inf	Not	
Available	ROOT\MS_PPTPMINIPORT\0000		
WAN Miniport (PPPOE)	Yes	NET	
5.2.3790.1830	10/1/2002 Microsoft		
netrasa.inf	Not Available		
ROOT\MS_PPPOEMINIPORT\0000			
WAN Miniport (IP)	Yes	NET	5.2.3790.1830
10/1/2002 Microsoft	netrasa.inf	Not	
Available	ROOT\MS_NDISWANIP\0000		
WAN Miniport (L2TP)	Yes	NET	5.2.3790.1830
10/1/2002 Microsoft	netrasa.inf	Not	
Available	ROOT\MS_L2TPMINIPORT\0000		
Video Codecs	Yes	MEDIA	5.2.3790.1830
10/1/2002 (Standard system devices)	wave.inf	Not Available	
ROOT\MEDIA\MS_MMVID			
Legacy Video Capture Devices	Yes	MEDIA	
5.2.3790.1830	10/1/2002 (Standard system devices)	wave.inf	Not Available
ROOT\MEDIA\MS_MMVCD			
Media Control Devices	Yes	MEDIA	
5.2.3790.1830	10/1/2002 (Standard system devices)	wave.inf	Not Available
ROOT\MEDIA\MS_MMCIC			
Legacy Audio Drivers	Yes	MEDIA	
5.2.3790.1830	10/1/2002 (Standard system devices)	wave.inf	Not Available
ROOT\MEDIA\MS_MMDRV			
Audio Codecs	Yes	MEDIA	5.2.3790.1830
10/1/2002 (Standard system devices)	wave.inf	Not Available	
ROOT\MEDIA\MS_MMACM			
Remote Access IP ARP Driver	Not Available		
LEGACYDRIVER	Not Available	Not	
Available	Not Available	Not	
Available	ROOT\LEGACY_WANARP\0000		
volsnap	Not Available	LEGACYDRIVER	Not
Available	Not Available	Not Available	Not
Available	Not Available	Not Available	Not
Available	Not Available	Not Available	Not
ROOT\LEGACY_VOLSNAP\0000			
VGA Display Controller	Not Available		
LEGACYDRIVER	Not Available	Not	
Available	Not Available	Not Available	Not
Available	ROOT\LEGACY_VGASAVE\0000		
TDTCP	Not Available	LEGACYDRIVER	Not
Available	Not Available	Not Available	Not
Available	Not Available	Not Available	Not
Available	Not Available	ROOT\LEGACY_TDTCP\0000	
TCP/IP Protocol Driver	Not Available		
LEGACYDRIVER	Not Available	Not	
Available	Not Available	Not Available	Not
Available	ROOT\LEGACY_TCPIP\0000		
Security Driver	Not Available	LEGACYDRIVER	
Not Available	Not Available	Not	
Available	Not Available	Not Available	Not
Available	Not Available	Not Available	Not
Available	Not Available	ROOT\LEGACY_SECDRV\0000	
RDPWD	Not Available	LEGACYDRIVER	Not
Available	Not Available	Not Available	Not
Available	Not Available	ROOT\LEGACY_RDPWD\0000	
RDP added	Not Available	LEGACYDRIVER	Not
Available	Not Available	Not Available	Not

Available	Not Available	ROOT\LEGACY_RDP added\0000	
Remote Access Auto Connection Driver	Not Available		
LEGACYDRIVER	Not Available	Not	
Available	Not Available	Not Available	Not
Available	ROOT\LEGACY_RASACD\0000		
Partition Manager	Not Available	LEGACYDRIVER	
Not Available	Not Available	Not Available	Not
Available	Not Available	Not Available	Not
Available	ROOT\LEGACY_PARTMGR\0000		
Null	Not Available	LEGACYDRIVER	Not
Available	Not Available	Not Available	Not
Available	Not Available	ROOT\LEGACY_NULL\0000	
NetBios over Tcpip	Not Available	LEGACYDRIVER	
Not Available	Not Available	Not Available	Not
Available	Not Available	Not Available	Not
Available	ROOT\LEGACY_NETBT\0000		
NDProxy	Not Available	LEGACYDRIVER	Not
Available	Not Available	Not Available	Not
Available	Not Available	Not Available	Not
Available	Not Available	Not Available	Not
Available	ROOT\LEGACY_NDPProxy\0000		
NDIS Usermode I/O Protocol	Not Available		
LEGACYDRIVER	Not Available	Not	
Available	Not Available	Not Available	Not
Available	ROOT\LEGACY_NDISUIO\0000		
Remote Access NDIS TAPI Driver	Not Available		
LEGACYDRIVER	Not Available	Not	
Available	Not Available	Not Available	Not
Available	ROOT\LEGACY_NDIS TAPI\0000		
NDIS System Driver	Not Available	LEGACYDRIVER	
Not Available	Not Available	Not Available	Not
Available	Not Available	Not Available	Not
Available	ROOT\LEGACY_NDIS\0000		
mountmgr	Not Available	LEGACYDRIVER	Not
Available	Not Available	Not Available	Not
Available	Not Available	Not Available	Not
Available	Not Available	Not Available	Not
Available	ROOT\LEGACY_MOUNTMGR\0000		
mnmdd	Not Available	LEGACYDRIVER	Not
Available	Not Available	Not Available	Not
Available	Not Available	Not Available	Not
Available	Not Available	ROOT\LEGACY_MNMDD\0000	
ksecdd	Not Available	LEGACYDRIVER	Not
Available	Not Available	Not Available	Not
Available	Not Available	Not Available	Not
Available	Not Available	ROOT\LEGACY_KSE added\0000	
IPSEC driver	Not Available	LEGACYDRIVER	
Not Available	Not Available	Not	
Available	Not Available	Not Available	Not
Available	ROOT\LEGACY_IPSEC\0000		
IP Network Address Translator	Not Available		
LEGACYDRIVER	Not Available	Not	
Available	Not Available	Not Available	Not
Available	Not Available	Not Available	Not
Available	ROOT\LEGACY_IPNAT\0000		
Generic Packet Classifier	Not Available		
LEGACYDRIVER	Not Available	Not	
Available	Not Available	Not Available	Not
Available	ROOT\LEGACY_GPC\0000		
Fips	Not Available	LEGACYDRIVER	Not
Available	Not Available	Not Available	Not
Available	Not Available	Not Available	Not
Available	Not Available	ROOT\LEGACY_FIPS\0000	

dmload	Not Available	LEGACYDRIVER	Not
Available	Not Available	Not Available	Not
Available	Not Available	Not Available	Not
Available	Not Available	ROOT\LEGACY_DMLOAD\0000	
dmboot	Not Available	LEGACYDRIVER	Not
Available	Not Available	Not Available	Not
Available	Not Available	Not Available	Not
Available	Not Available	ROOT\LEGACY_DMBOOT\0000	
CRC Disk Filter Driver	Not Available		
LEGACYDRIVER	Not Available	Not	
Available	Not Available	Not Available	Not
Available	ROOT\LEGACY_CRCDISK\0000		
CdaD10BA	Not Available	LEGACYDRIVER	Not
Available	Not Available	Not Available	Not
Available	Not Available	Not Available	Not
Available	Not Available	Not Available	Not
Available	Not Available	Not Available	Not
Available	ROOT\LEGACY_CDAD10BA\0000		
CdaC15BA	Not Available	LEGACYDRIVER	Not
Available	Not Available	Not Available	Not
Available	Not Available	Not Available	Not
Available	Not Available	Not Available	Not
Available	ROOT\LEGACY_CDAC15BA\0000		
Beep	Not Available	LEGACYDRIVER	Not
Available	Not Available	Not Available	Not
Available	Not Available	Not Available	Not
Available	Not Available	ROOT\LEGACY_BEEP\0000	
AFD	Not Available	LEGACYDRIVER	Not
Available	Not Available	Not Available	Not
Available	Not Available	Not Available	Not
Available	Not Available	ROOT\LEGACY_AFD\0000	
Generic volume	Yes	VOLUME	5.2.3790.1830
10/1/2002 Microsoft	volume.inf	Not	
Available			
STORAGE\VOLUME\1&30A96598&0&SIGNATURE94D494			
D40FFSET4000LENGTH87A3D0000			
Generic volume	Yes	VOLUME	5.2.3790.1830
10/1/2002 Microsoft	volume.inf	Not	
Available			
STORAGE\VOLUME\1&30A96598&0&SIGNATURE78850B			
520FFSET10000LENGTH8C9D00000			
Generic volume	Yes	VOLUME	5.2.3790.1830
10/1/2002 Microsoft	volume.inf	Not	
Available			
STORAGE\VOLUME\1&30A96598&0&SIGNATURE78850B			
510FFSET10000LENGTH11D1E00000			
Generic volume	Yes	VOLUME	5.2.3790.1830
10/1/2002 Microsoft	volume.inf	Not	
Available			
STORAGE\VOLUME\1&30A96598&0&SIGNATURE78850B			
500FFSET7E00LENGTH6964417200			
Generic volume	Yes	VOLUME	5.2.3790.1830
10/1/2002 Microsoft	volume.inf	Not	
Available			
STORAGE\VOLUME\1&30A96598&0&SIGNATURE78850B			
570FFSET10000LENGTH8C9D00000			
Generic volume	Yes	VOLUME	5.2.3790.1830
10/1/2002 Microsoft	volume.inf	Not	
Available			
STORAGE\VOLUME\1&30A96598&0&SIGNATURE78850B			
560FFSET10000LENGTH11D1E00000			
Generic volume	Yes	VOLUME	5.2.3790.1830
10/1/2002 Microsoft	volume.inf	Not	
Available			
STORAGE\VOLUME\1&30A96598&0&SIGNATURE78850B			
550FFSET10000LENGTH8C9D00000			

```

Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available STORAGE\VOLUME\1&30A96598&0&SIGNATURE78850B
5BOFFSET10000LENGTHH1D1E00000
Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available STORAGE\VOLUME\1&30A96598&0&SIGNATURE3E3F08
8AOFFSET7E00LENGT6964417200
Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available STORAGE\VOLUME\1&30A96598&0&SIGNATURE78850B
5AOFFSET10000LENGTH8C9D00000
Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available STORAGE\VOLUME\1&30A96598&0&SIGNATURE78850B
59OFFSET10000LENGTHH1D1E00000
Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available STORAGE\VOLUME\1&30A96598&0&SIGNATURE593ED9
E8OFFSET10000LENGTHCD18E00000
Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available STORAGE\VOLUME\1&30A96598&0&SIGNATURE593ED9
E9OFFSET10000LENGTH8C9D00000
Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available STORAGE\VOLUME\1&30A96598&0&SIGNATURE593ED9
E6OFFSET10000LENGTHH1D1E00000
Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available STORAGE\VOLUME\1&30A96598&0&SIGNATURE593ED9
E7OFFSET7E00LENGT6964417200
Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available STORAGE\VOLUME\1&30A96598&0&SIGNATURE593ED9
E4OFFSET10000LENGTH8C9D00000
Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available STORAGE\VOLUME\1&30A96598&0&SIGNATURE593ED9
E5OFFSET10000LENGTHH1D1E00000
Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available STORAGE\VOLUME\1&30A96598&0&SIGNATURE593ED9
E2OFFSET10000LENGTH8C9D00000
Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available STORAGE\VOLUME\1&30A96598&0&SIGNATURE593ED9
E3OFFSET10000LENGTHH1D1E00000
Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available

```

```

STORAGE\VOLUME\1&30A96598&0&SIGNATURE593ED9
E0OFFSET7E00LENGT6964417200
Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available STORAGE\VOLUME\1&30A96598&0&SIGNATURE593ED9
E1OFFSET10000LENGTH8C9D00000
Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available STORAGE\VOLUME\1&30A96598&0&SIGNATURE593ED9
1FOFFSET10000LENGTHH1D1E00000
Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available STORAGE\VOLUME\1&30A96598&0&SIGNATURE593ED9
1COFFSET10000LENGTH8C9D00000
Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available STORAGE\VOLUME\1&30A96598&0&SIGNATURE593ED9
1DOFFSET10000LENGTHH1D1E00000
Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available STORAGE\VOLUME\1&30A96598&0&SIGNATURE593ED9
1AOFFSET7E00LENGT6964417200
Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available STORAGE\VOLUME\1&30A96598&0&SIGNATURE593ED9
1BOFFSET10000LENGTH8C9D00000
Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available STORAGE\VOLUME\1&30A96598&0&SIGNATURE593ED9
18OFFSET10000LENGTHH1D1E00000
Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available STORAGE\VOLUME\1&30A96598&0&SIGNATURE593ED9
19OFFSET10000LENGTH8C9D00000
Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available STORAGE\VOLUME\1&30A96598&0&SIGNATURE593ED9
16OFFSET10000LENGTHH1D1E00000
Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available STORAGE\VOLUME\1&30A96598&0&SIGNATURE593ED9
17OFFSET10000LENGTH8C9D00000
Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available STORAGE\VOLUME\1&30A96598&0&SIGNATURE593ED9
14OFFSET10000LENGTHH1D1E00000
Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available STORAGE\VOLUME\1&30A96598&0&SIGNATURE593ED9
15OFFSET10000LENGTH8C9D00000

```

```

Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available STORAGE\VOLUME\1&30A96598&0&SIGNATURE593ED9
12OFFSET10000LENGTHH1D1E00000
Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available STORAGE\VOLUME\1&30A96598&0&SIGNATURE593ED9
13OFFSET10000LENGTH8C9D00000
Generic volume Yes VOLUME 5.2.3790.1830
10/1/2002 Microsoft volume.inf Not
Available STORAGE\VOLUME\1&30A96598&0&SIGNATURE593ED9
10OFFSET10000LENGTHH1D1E00000
Volume Manager Yes SYSTEM 5.2.3790.1830
10/1/2002 (Standard system devices)
machine.inf Not Available
ROOT\FTDISK\0000
Logical Disk Manager Yes SYSTEM
5.2.3790.1830 10/1/2002 (Standard
system devices) machine.inf Not Available
ROOT\DMIO\0000
ACPI Fixed Feature Button Yes SYSTEM
5.2.3790.1830 10/1/2002 (Standard
system devices) machine.inf Not Available
ACPI\FIXEDBUTTON\2&DABA3FF&0
AMD-8131 HyperTransport (tm) IOAPIC Controller Yes
SYSTEM 5.2.3790.1830 10/1/2002 AMD
machine.inf Not Available
PCI\VEN_1022&DEV_7451&SUBSYS_00000000&REV_0
1\3&33B859B7&0&61
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&3
45E2707&0&0100004000000000
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&3
45E2707&0&0000004000000000
Smart Array 6400 Controller U320 Expansion Module
(Non-Miniport) No SCSIADAPTER
5.14.2.64 2/25/2005 Hewlett-Packard
oem2.inf Not Available
PCI\VEN_0E11&DEV_0046&SUBSYS_409D0E11&REV_0
1\5&282C4885&0&286060
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&2
670E50&0&0200004000000000
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&2
670E50&0&0100004000000000
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&2
670E50&0&0000004000000000

```



```

Smart Array 6400 Controller (Non-Miniport) No
SCSIADAPTER 5.14.2.64 2/25/2005
Hewlett-Packard oem2.inf Not Available
PCI\VEN_0E11&DEV_0046&SUBSYS_409C0E11&REV_0
1\5&282C4885&0&206060
PCI standard PCI-to-PCI bridge Yes
SYSTEM 5.2.3790.1830 10/1/2002
(Standard system devices) machine.inf
Not Available
PCI\VEN_1014&DEV_01A7&SUBSYS_00000000&REV_0
2\4&62BA2CA&0&5860
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&1
EC6BF6&0&0100004000000000
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&1
EC6BF6&0&0000004000000000
Smart Array 6400 Controller U320 Expansion Module
(Non-Miniport) No SCSIADAPTER
5.14.2.64 2/25/2005 Hewlett-Packard
oem2.inf Not Available
PCI\VEN_0E11&DEV_0046&SUBSYS_409D0E11&REV_0
1\5&30FCE3FC&0&285860
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&1
5200E66&0&0200004000000000
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&1
5200E66&0&0100004000000000
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&1
5200E66&0&0000004000000000
Smart Array 6400 Controller (Non-Miniport) No
SCSIADAPTER 5.14.2.64 2/25/2005
Hewlett-Packard oem2.inf Not Available
PCI\VEN_0E11&DEV_0046&SUBSYS_409C0E11&REV_0
1\5&30FCE3FC&0&205860
PCI standard PCI-to-PCI bridge Yes
SYSTEM 5.2.3790.1830 10/1/2002
(Standard system devices) machine.inf
Not Available
PCI\VEN_1014&DEV_01A7&SUBSYS_00000000&REV_0
2\4&62BA2CA&0&5860
PCI standard PCI-to-PCI bridge Yes
SYSTEM 5.2.3790.1830 10/1/2002
(Standard system devices) machine.inf
Not Available
PCI\VEN_1022&DEV_7450&SUBSYS_00000000&REV_1
2\3&33B859B7&0&60
AMD-8131 HyperTransport(tm) IOAPIC Controller Yes
SYSTEM 5.2.3790.1830 10/1/2002 AMD
machine.inf Not Available

```

```

PCI\VEN_1022&DEV_7451&SUBSYS_00000000&REV_0
1\3&33B859B7&0&59
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\5&C
633B0D&0&0000014001000000
Smart Array 642 Controller (Non-Miniport) No
SCSIADAPTER 5.14.2.64 2/25/2005
Hewlett-Packard oem2.inf Not Available
PCI\VEN_0E11&DEV_0046&SUBSYS_409B0E11&REV_0
1\4&2534A57B&0&5058
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&3
A915E4E&0&0100004000000000
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&3
A915E4E&0&0000004000000000
Smart Array 6400 Controller U320 Expansion Module
(Non-Miniport) No SCSIADAPTER
5.14.2.64 2/25/2005 Hewlett-Packard
oem2.inf Not Available
PCI\VEN_0E11&DEV_0046&SUBSYS_409D0E11&REV_0
1\5&1B3A307E&0&284858
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&A
B01D09&0&0200004000000000
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&A
B01D09&0&0100004000000000
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&A
B01D09&0&0000004000000000
Smart Array 6400 Controller (Non-Miniport) No
SCSIADAPTER 5.14.2.64 2/25/2005
Hewlett-Packard oem2.inf Not Available
PCI\VEN_0E11&DEV_0046&SUBSYS_409C0E11&REV_0
1\5&1B3A307E&0&204858
PCI standard PCI-to-PCI bridge Yes
SYSTEM 5.2.3790.1830 10/1/2002
(Standard system devices) machine.inf
Not Available
PCI\VEN_1014&DEV_01A7&SUBSYS_00000000&REV_0
2\4&2534A57B&0&4858
PCI standard PCI-to-PCI bridge Yes
SYSTEM 5.2.3790.1830 10/1/2002
(Standard system devices) machine.inf
Not Available
PCI\VEN_1022&DEV_7450&SUBSYS_00000000&REV_1
2\3&33B859B7&0&58
AMD-8131 HyperTransport(tm) IOAPIC Controller Yes
SYSTEM 5.2.3790.1830 10/1/2002 AMD
machine.inf Not Available

```

```

PCI\VEN_1022&DEV_7451&SUBSYS_00000000&REV_0
1\3&33B859B7&0&51
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&9
BFB032&0&0100004000000000
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&9
BFB032&0&0000004000000000
Smart Array 6400 Controller U320 Expansion Module
(Non-Miniport) No SCSIADAPTER
5.14.2.64 2/25/2005 Hewlett-Packard
oem2.inf Not Available
PCI\VEN_0E11&DEV_0046&SUBSYS_409D0E11&REV_0
1\5&25998046&0&287050
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&3
B81CB25&0&0200004000000000
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&3
B81CB25&0&0100004000000000
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&3
B81CB25&0&0000004000000000
Smart Array 6400 Controller (Non-Miniport) No
SCSIADAPTER 5.14.2.64 2/25/2005
Hewlett-Packard oem2.inf Not Available
PCI\VEN_0E11&DEV_0046&SUBSYS_409C0E11&REV_0
1\5&25998046&0&207050
PCI standard PCI-to-PCI bridge Yes
SYSTEM 5.2.3790.1830 10/1/2002
(Standard system devices) machine.inf
Not Available
PCI\VEN_1014&DEV_01A7&SUBSYS_00000000&REV_0
2\4&9630B56&0&7050
PCI standard PCI-to-PCI bridge Yes
SYSTEM 5.2.3790.1830 10/1/2002
(Standard system devices) machine.inf
Not Available
PCI\VEN_1022&DEV_7450&SUBSYS_00000000&REV_1
2\3&33B859B7&0&50
AMD-8131 HyperTransport(tm) IOAPIC Controller Yes
SYSTEM 5.2.3790.1830 10/1/2002 AMD
machine.inf Not Available
PCI\VEN_1022&DEV_7451&SUBSYS_00000000&REV_0
1\3&33B859B7&0&49
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&1
EC08C08&0&0100004000000000
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available

```

```

HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&1
EC08C08&0000000400000000
Smart Array 6400 Controller U320 Expansion Module
(Non-Miniport) No SCSIADAPTER
5.14.2.64 2/25/2005 Hewlett-Packard
oem2.inf Not Available
PCI\VEN_0E11&DEV_0046&SUBSYS_409D0E11&REV_0
1\5&56DD264&0&286848
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&1
BB4D19C&0&0200004000000000
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&1
BB4D19C&0&0100004000000000
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&1
BB4D19C&0&0000004000000000
Smart Array 6400 Controller (Non-Miniport) No
SCSIADAPTER 5.14.2.64 2/25/2005
Hewlett-Packard oem2.inf Not Available
PCI\VEN_0E11&DEV_0046&SUBSYS_409C0E11&REV_0
1\5&56DD264&0&206848
PCI standard PCI-to-PCI bridge Yes
SYSTEM 5.2.3790.1830 10/1/2002
(Standard system devices) machine.inf
Not Available
PCI\VEN_1014&DEV_01A7&SUBSYS_00000000&REV_0
2\4&25F4D2AC&0&6848
PCI standard PCI-to-PCI bridge Yes
SYSTEM 5.2.3790.1830 10/1/2002
(Standard system devices) machine.inf
Not Available
PCI\VEN_1022&DEV_7450&SUBSYS_00000000&REV_1
2\3&33B859B7&0&48
PCI bus Yes SYSTEM 5.2.3790.1830
10/1/2002 (Standard system devices)
machine.inf Not Available
ACPI\PNP0A03\8
AMD Miscellaneous Configuration Yes
SYSTEM 5.2.3790.1830 10/1/2002 AMD
machine.inf Not Available
PCI\VEN_1022&DEV_1103&SUBSYS_00000000&REV_0
0\3&20FEA912&0&DB
AMD DRAM and HyperTransport(tm) Trace Mode
Configuration Yes SYSTEM 5.2.3790.1830
10/1/2002 AMD machine.inf Not
Available
PCI\VEN_1022&DEV_1102&SUBSYS_00000000&REV_0
0\3&20FEA912&0&DA
AMD Address Map Configuration Yes SYSTEM
5.2.3790.1830 10/1/2002 AMD
machine.inf Not Available
PCI\VEN_1022&DEV_1101&SUBSYS_00000000&REV_0
0\3&20FEA912&0&D9
AMD HyperTransport(tm) Configuration Yes
SYSTEM 5.2.3790.1830 10/1/2002 AMD
machine.inf Not Available

```

```

PCI\VEN_1022&DEV_1100&SUBSYS_00000000&REV_0
0\3&20FEA912&0&D8
AMD Miscellaneous Configuration Yes
SYSTEM 5.2.3790.1830 10/1/2002 AMD
machine.inf Not Available
PCI\VEN_1022&DEV_1103&SUBSYS_00000000&REV_0
0\3&20FEA912&0&D3
AMD DRAM and HyperTransport(tm) Trace Mode
Configuration Yes SYSTEM 5.2.3790.1830
10/1/2002 AMD machine.inf Not
Available
PCI\VEN_1022&DEV_1102&SUBSYS_00000000&REV_0
0\3&20FEA912&0&D2
AMD Address Map Configuration Yes SYSTEM
5.2.3790.1830 10/1/2002 AMD
machine.inf Not Available
PCI\VEN_1022&DEV_1101&SUBSYS_00000000&REV_0
0\3&20FEA912&0&D1
AMD HyperTransport(tm) Configuration Yes
SYSTEM 5.2.3790.1830 10/1/2002 AMD
machine.inf Not Available
PCI\VEN_1022&DEV_1100&SUBSYS_00000000&REV_0
0\3&20FEA912&0&D0
AMD Miscellaneous Configuration Yes
SYSTEM 5.2.3790.1830 10/1/2002 AMD
machine.inf Not Available
PCI\VEN_1022&DEV_1103&SUBSYS_00000000&REV_0
0\3&20FEA912&0&CB
AMD DRAM and HyperTransport(tm) Trace Mode
Configuration Yes SYSTEM 5.2.3790.1830
10/1/2002 AMD machine.inf Not
Available
PCI\VEN_1022&DEV_1102&SUBSYS_00000000&REV_0
0\3&20FEA912&0&CA
AMD Address Map Configuration Yes SYSTEM
5.2.3790.1830 10/1/2002 AMD
machine.inf Not Available
PCI\VEN_1022&DEV_1101&SUBSYS_00000000&REV_0
0\3&20FEA912&0&C9
AMD HyperTransport(tm) Configuration Yes
SYSTEM 5.2.3790.1830 10/1/2002 AMD
machine.inf Not Available
PCI\VEN_1022&DEV_1100&SUBSYS_00000000&REV_0
0\3&20FEA912&0&C8
AMD Miscellaneous Configuration Yes
SYSTEM 5.2.3790.1830 10/1/2002 AMD
machine.inf Not Available
PCI\VEN_1022&DEV_1103&SUBSYS_00000000&REV_0
0\3&20FEA912&0&C3
AMD DRAM and HyperTransport(tm) Trace Mode
Configuration Yes SYSTEM 5.2.3790.1830
10/1/2002 AMD machine.inf Not
Available
PCI\VEN_1022&DEV_1102&SUBSYS_00000000&REV_0
0\3&20FEA912&0&C2
AMD Address Map Configuration Yes SYSTEM
5.2.3790.1830 10/1/2002 AMD
machine.inf Not Available
PCI\VEN_1022&DEV_1101&SUBSYS_00000000&REV_0
0\3&20FEA912&0&C1
AMD HyperTransport(tm) Configuration Yes
SYSTEM 5.2.3790.1830 10/1/2002 AMD
machine.inf Not Available

```

```

PCI\VEN_1022&DEV_1100&SUBSYS_00000000&REV_0
0\3&20FEA912&0&C0
AMD-8131 HyperTransport(tm) IOAPIC Controller Yes
SYSTEM 5.2.3790.1830 10/1/2002 AMD
machine.inf Not Available
PCI\VEN_1022&DEV_7451&SUBSYS_00000000&REV_0
1\3&20FEA912&0&41
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&1
E3DCC80&0&0100004000000000
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&1
E3DCC80&0&0000004000000000
Smart Array 6400 Controller U320 Expansion Module
(Non-Miniport) No SCSIADAPTER
5.14.2.64 2/25/2005 Hewlett-Packard
oem2.inf Not Available
PCI\VEN_0E11&DEV_0046&SUBSYS_409D0E11&REV_0
1\5&2363B0A8&0&284040
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&2
7E47DD0&0&0100004000000000
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&2
7E47DD0&0&0000004000000000
Smart Array 6400 Controller (Non-Miniport) No
SCSIADAPTER 5.14.2.64 2/25/2005
Hewlett-Packard oem2.inf Not Available
PCI\VEN_0E11&DEV_0046&SUBSYS_409C0E11&REV_0
1\5&2363B0A8&0&204040
PCI standard PCI-to-PCI bridge Yes
SYSTEM 5.2.3790.1830 10/1/2002
(Standard system devices) machine.inf
Not Available
PCI\VEN_1014&DEV_01A7&SUBSYS_00000000&REV_0
2\4&24B9E852&0&4040
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&7
8F08CD&0&0100004000000000
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&7
8F08CD&0&0000004000000000
Smart Array 6400 Controller U320 Expansion Module
(Non-Miniport) No SCSIADAPTER
5.14.2.64 2/25/2005 Hewlett-Packard
oem2.inf Not Available
PCI\VEN_0E11&DEV_0046&SUBSYS_409D0E11&REV_0
1\5&2C344C1F&0&283840
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available

```

```

HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&5
F1DC7&0&0100004000000000
Smart Array Logical Volume No DISKDRIVE
5.6.2.32 7/14/2004 Hewlett-Packard
oem1.inf Not Available
HPQCISS\DISK&VEN_HP&PROD_LOGICAL_VOLUME\6&5
F1DC7&0&0000004000000000
Smart Array 6400 Controller (Non-Miniport) No
SCSIADAPTER 5.14.2.64 2/25/2005
Hewlett-Packard oem2.inf Not Available
PCI\VEN_0E11&DEV_0046&SUBSYS_409C0E11&REV_0
1\5&2C344C1F&0&203840
PCI standard PCI-to-PCI bridge Yes
SYSTEM 5.2.3790.1830 10/1/2002
(Standard system devices) machine.inf
Not Available
PCI\VEN_1014&DEV_01A7&SUBSYS_00000000&REV_0
2\4&24B9E852&0&3840
PCI standard PCI-to-PCI bridge Yes
SYSTEM 5.2.3790.1830 10/1/2002
(Standard system devices) machine.inf
Not Available
PCI\VEN_1022&DEV_7450&SUBSYS_00000000&REV_1
2\3&20FEA912&0&40
AMD-8131 HyperTransport(tm) IOAPIC Controller Yes
SYSTEM 5.2.3790.1830 10/1/2002 AMD
machine.inf Not Available
PCI\VEN_1022&DEV_7451&SUBSYS_00000000&REV_0
1\3&20FEA912&0&39
Broadcom NetXtreme Gigabit Ethernet Yes NET
7.98.0.0 10/1/2002 Broadcom net57amd.inf
Not Available
PCI\VEN_14E4&DEV_1648&SUBSYS_00D00E11&REV_1
0\4&82820FC&0&3138
Broadcom NetXtreme Gigabit Ethernet Yes NET
7.98.0.0 10/1/2002 Broadcom net57amd.inf
Not Available
PCI\VEN_14E4&DEV_1648&SUBSYS_00D00E11&REV_1
0\4&82820FC&0&3038
Disk drive Yes DISKDRIVE 5.2.3790.1830
10/1/2002 (Standard disk drives)
disk.inf Not Available
SCSI\DISK&VEN_COMPAQ&PROD_LOGICAL_VOLUME&RE
V_2_58\5&208597A6&0&040
HP Virtual LUN Yes SYSTEM 5.2.3790.1830
10/1/2002 Compaq scsidev.inf Not
Available
SCSI\OTHER&VEN_COMPAQ&PROD_SCSI_COMMUNICATE
&REV_CISS\5&208597A6&0&000
Smart Array 51 Yes SCSIADAPTER
5.2.3790.1830 10/1/2002 Compaq
pnpscsi.inf Not Available
PCI\VEN_0E11&DEV_B178&SUBSYS_40800E11&REV_0
1\4&82820FC&0&2038
PCI standard PCI-to-PCI bridge Yes
SYSTEM 5.2.3790.1830 10/1/2002
(Standard system devices) machine.inf
Not Available
PCI\VEN_1022&DEV_7450&SUBSYS_00000000&REV_1
2\3&20FEA912&0&38
AMD-8111 System Management Controller Yes
SYSTEM 5.2.3790.1830 10/1/2002 AMD
machine.inf Not Available

```

```

PCI\VEN_1022&DEV_746B&SUBSYS_32050E11&REV_0
5\3&20FEA912&0&23
CD-ROM Drive Yes CDROM 5.2.3790.1830
10/1/2002 (Standard CD-ROM drives)
cdrom.inf Not Available
IDE\CDROMTEAC_CD-
224E_____9.9A_____5&2DC47F1C&0
&0.0.0
Primary IDE Channel Yes HDC 5.2.3790.1830
10/1/2002 (Standard IDE ATA/ATAPI
controllers) mshdc.inf Not Available
PCIIDE\IDECHANNEL\4&21637DBD&0&0
AMD-8111 PCI Bus Master IDE Controller Yes HDC
5.2.3790.1830 10/1/2002 Advanced
Micro Devices mshdc.inf Not Available
PCI\VEN_1022&DEV_7469&SUBSYS_32040E11&REV_0
3\3&20FEA912&0&21
Floppy disk drive Yes FLOPPYDISK
5.2.3790.1830 10/1/2002 (Standard
floppy disk drives) flpydisk.inf Not Available
FDC\GENERIC_FLOPPY_DRIVE\6&2F72E85F&0&0
Standard floppy disk controller Yes FDC
5.2.3790.1830 10/1/2002 (Standard
floppy disk controllers)fdc.inf Not Available
ACPI\PNP0700\5&1C430410&0
Communications Port Yes PORTS 5.2.3790.1830
10/1/2002 (Standard port types)
mports.inf Not Available
ACPI\PNP0501\0
Extended IO Bus Yes SYSTEM 5.2.3790.1830
10/1/2002 (Standard system devices)
machine.inf Not Available
ACPI\PNP0A06\4&1C7DEDE8&0
PS/2 Compatible Mouse Yes MOUSE
5.2.3790.1830 10/1/2002 Microsoft
mmouse.inf Not Available
ACPI\PNP0F13\4&1C7DEDE8&0
Standard 101/102-Key or Microsoft Natural PS/2
Keyboard Yes KEYBOARD 5.2.3790.1830
10/1/2002 (Standard keyboards)
keyboard.inf Not Available
ACPI\PNP0303\4&1C7DEDE8&0
System speaker Yes SYSTEM 5.2.3790.1830
10/1/2002 (Standard system devices)
machine.inf Not Available
ACPI\PNP0800\4&1C7DEDE8&0
Direct memory access controller Yes
SYSTEM 5.2.3790.1830 10/1/2002
(Standard system devices) machine.inf
Not Available
ACPI\PNP0200\4&1C7DEDE8&0
System timer Yes SYSTEM 5.2.3790.1830
10/1/2002 (Standard system devices)
machine.inf Not Available
ACPI\PNP0100\4&1C7DEDE8&0
Programmable interrupt controller Yes
SYSTEM 5.2.3790.1830 10/1/2002
(Standard system devices) machine.inf
Not Available
ACPI\PNP0000\4&1C7DEDE8&0
Motherboard resources Yes SYSTEM
5.2.3790.1830 10/1/2002 (Standard

```

```

system devices) machine.inf Not Available
ACPI\PNP0C02\0
PCI standard ISA bridge Yes SYSTEM
5.2.3790.1830 10/1/2002 (Standard
system devices) machine.inf Not Available
PCI\VEN_1022&DEV_7468&SUBSYS_00000000&REV_0
5\3&20FEA912&0&20
Plug and Play Monitor Yes MONITOR
5.2.3790.1830 10/1/2002 (Standard
monitor types) monitor.inf Not Available
DISPLAY\AVO0000\5&38B1FFCB&0&80000001&01&03
RAGE XL PCI (Microsoft Corporation) Yes
DISPLAY 6.14.10.6025 12/3/2004 ATI
Technologies, Inc. atiixpad.inf Not Available
PCI\VEN_1002&DEV_4752&SUBSYS_001E0E11&REV_2
7\4&12365AD0&0&1818
Base System Device Not Available UNKNOWN Not
Available Not Available Not Available Not
Available Not Available
PCI\VEN_0E11&DEV_B204&SUBSYS_B2060E11&REV_0
1\4&12365AD0&0&1218
Base System Device Not Available UNKNOWN Not
Available Not Available Not Available Not
Available Not Available
PCI\VEN_0E11&DEV_B203&SUBSYS_B2060E11&REV_0
1\4&12365AD0&0&1018
USB Root Hub Yes USB 5.2.3790.1830
10/1/2002 (Standard USB Host Controller)
usbport.inf Not Available
USB\ROOT_HUB\5&194CD4CC&0
AMD PCI to USB Open Host Controller Yes USB
5.2.3790.1830 10/1/2002 Advanced
Micro Devices (AMD) usbport.inf Not Available
PCI\VEN_1022&DEV_7464&SUBSYS_32020E11&REV_0
B\4&12365AD0&0&0118
USB Root Hub Yes USB 5.2.3790.1830
10/1/2002 (Standard USB Host Controller)
usbport.inf Not Available
USB\ROOT_HUB\5&9B4CD91&0
AMD PCI to USB Open Host Controller Yes USB
5.2.3790.1830 10/1/2002 Advanced
Micro Devices (AMD) usbport.inf Not Available
PCI\VEN_1022&DEV_7464&SUBSYS_32020E11&REV_0
B\4&12365AD0&0&0018
PCI standard PCI-to-PCI bridge Yes
SYSTEM 5.2.3790.1830 10/1/2002
(Standard system devices) machine.inf
Not Available
PCI\VEN_1022&DEV_7460&SUBSYS_00000000&REV_0
7\3&20FEA912&0&18
PCI bus Yes SYSTEM 5.2.3790.1830
10/1/2002 (Standard system devices)
machine.inf Not Available
ACPI\PNP0A03\7
Processor Yes PROCESSOR 5.2.3790.1830
10/1/2002 (Standard processor types)
cpu.inf Not Available
ACPI\AUTHENTICAMD_-
_AMD64_FAMILY_15_MODEL_33\7
Processor Yes PROCESSOR 5.2.3790.1830
10/1/2002 (Standard processor types)
cpu.inf Not Available

```

```

ACPI\AUTHENTICAMD -
_AMD64_FAMILY_15_MODEL_33\6
Processor Yes PROCESSOR 5.2.3790.1830
10/1/2002 (Standard processor types)
cpu.inf Not Available
ACPI\AUTHENTICAMD -
_AMD64_FAMILY_15_MODEL_33\5
Processor Yes PROCESSOR 5.2.3790.1830
10/1/2002 (Standard processor types)
cpu.inf Not Available
ACPI\AUTHENTICAMD -
_AMD64_FAMILY_15_MODEL_33\4
Processor Yes PROCESSOR 5.2.3790.1830
10/1/2002 (Standard processor types)
cpu.inf Not Available
ACPI\AUTHENTICAMD -
_AMD64_FAMILY_15_MODEL_33\3
Processor Yes PROCESSOR 5.2.3790.1830
10/1/2002 (Standard processor types)
cpu.inf Not Available
ACPI\AUTHENTICAMD -
_AMD64_FAMILY_15_MODEL_33\2
Processor Yes PROCESSOR 5.2.3790.1830
10/1/2002 (Standard processor types)
cpu.inf Not Available
ACPI\AUTHENTICAMD -
_AMD64_FAMILY_15_MODEL_33\1
Processor Yes PROCESSOR 5.2.3790.1830
10/1/2002 (Standard processor types)
cpu.inf Not Available
ACPI\AUTHENTICAMD -
_AMD64_FAMILY_15_MODEL_33\0
Microsoft ACPI-Compliant System Yes
SYSTEM 5.2.3790.1830 10/1/2002
Microsoft acpi.inf Not Available
ACPI_HAL\PNP0C08\0
ACPI Multiprocessor x64-based PC Yes
COMPUTER 5.2.3790.1830 10/1/2002
(Standard computers) hal.inf Not
Available ROOT\ACPI_HAL\0000
Not Available Not Available Not Available
Available Not Available Not Available Not
Available Not Available Not Available
HTREE\ROOT\0

[Environment Variables]

Variable Value User Name
ClusterLog C:\WINDOWS\Cluster\cluster.log
<SYSTEM>
ComSpec %SystemRoot%\system32\cmd.exe <SYSTEM>
FP_NO_HOST_CHECK NO <SYSTEM>
NUMBER_OF_PROCESSORS 8 <SYSTEM>
OS Windows_NT <SYSTEM>
Path
%SystemRoot%\system32;%SystemRoot%;%SystemR
oot%\System32\Wbem; C:\Program Files\Microsoft SQL
Server\MSSQL.1\MSSQL\Binn\;C:\Program Files\Microsoft
SQL Server\MSSQL.1\MSSQL\Binn\;C:\Program Files
(x86)\Microsoft SQL Server\80\Tools\Binn\;C:\Program
Files\Microsoft SQL Server\90\Tools\Binn\;C:\Program
Files (x86)\Microsoft SQL
Server\90\Tools\Binn\;C:\Program Files

```

```

(x86)\Microsoft SQL Server\90\DTS\Binn\;C:\Program
Files (x86)\Microsoft SQL
Server\90\Tools\Binn\WShell\Common7\IDE\;C:\Program
Files (x86)\Microsoft Visual Studio
8\Common7\IDE\PrivateAssemblies\ <SYSTEM>
PATHEXT
.COM;.EXE;.BAT;.CMD;.VBS;.VBE;.JS;.JSE;.WSF
;.WSH <SYSTEM>
PROCESSOR_ARCHITECTURE AMD64 <SYSTEM>
PROCESSOR_IDENTIFIER AMD64 Family 15 Model
33 Stepping 2, AuthenticAMD <SYSTEM>
PROCESSOR_LEVEL 15 <SYSTEM>
PROCESSOR_REVISION 2102 <SYSTEM>
TEMP %SystemRoot%\TEMP <SYSTEM>
TMP %SystemRoot%\TEMP <SYSTEM>
windir %SystemRoot% <SYSTEM>
lib C:\Program Files\SQLXML 4.0\bin\
<SYSTEM>
TEMP %USERPROFILE%\Local Settings\Temp NT
AUTHORITY\SYSTEM
TMP %USERPROFILE%\Local Settings\Temp NT
AUTHORITY\SYSTEM
TEMP %USERPROFILE%\Local Settings\Temp NT
AUTHORITY\LOCAL SERVICE
TMP %USERPROFILE%\Local Settings\Temp NT
AUTHORITY\LOCAL SERVICE
TEMP %USERPROFILE%\Local Settings\Temp NT
AUTHORITY\NETWORK SERVICE
TMP %USERPROFILE%\Local Settings\Temp NT
AUTHORITY\NETWORK SERVICE
TEMP %USERPROFILE%\Local Settings\Temp
BOBCAT\Administrator
TMP %USERPROFILE%\Local Settings\Temp
BOBCAT\Administrator

[Print Jobs]

Document Size Owner Notify Status
Time Submitted Start Time
Until Time Elapsed Time
Pages Printed Job ID Priority
Parameters Driver Print
Processor Host Print Queue Data Type Name

[Network Connections]

Local Name Remote Name Type
Status User Name

[Running Tasks]

Name Path Process ID Priority Min
Working Set Max Working Set Start Time
Version Size File Date
system idle process Not Available 0 0
Not Available Not Available Not
Available Not Available Not Available Not
system Not Available 4 8 0
1413120 Not Available Not Available
Not Available Not Available

```

```

smss.exe Not Available 676 11
204800 1413120 9/19/2005 5:25 PM Not
Available Not Available Not Available
cgrss.exe Not Available 816 13 Not
Available Not Available 9/19/2005 5:25 PM Not
Available Not Available Not Available
winlogon.exe c:\windows\system32\winlogon.exe
856 13 204800 1413120
9/19/2005 5:25 PM 5.2.3790.1830
(srv03_spl_rtm.050324-1447) 901.00 KB (922,624
bytes) 3/25/2005 6:00 AM
services.exe c:\windows\system32\services.exe
916 9 204800 1413120
9/19/2005 5:25 PM 5.2.3790.1830
(srv03_spl_rtm.050324-1447) 216.50 KB (221,696
bytes) 3/25/2005 6:00 AM
lsass.exe c:\windows\system32\lsass.exe 928 9
204800 1413120 9/19/2005 5:25 PM
5.2.3790.1830 (srv03_spl_rtm.050324-1447)
14.00 KB (14,336 bytes) 3/25/2005
6:00 AM
svchost.exe c:\windows\system32\svchost.exe
412 8 204800 1413120
9/19/2005 5:25 PM 5.2.3790.1830
(srv03_spl_rtm.050324-1447) 24.50 KB (25,088 bytes)
3/25/2005 6:00 AM
svchost.exe Not Available 484 8
Not Available Not Available
9/19/2005 5:25 PM Not Available Not
Available Not Available
svchost.exe Not Available 532 8
Not Available Not Available
9/19/2005 5:25 PM Not Available Not
Available Not Available
svchost.exe Not Available 580 8
Not Available Not Available
9/19/2005 5:25 PM Not Available Not
Available Not Available
svchost.exe c:\windows\system32\svchost.exe
616 8 204800 1413120
9/19/2005 5:25 PM 5.2.3790.1830
(srv03_spl_rtm.050324-1447) 24.50 KB (25,088 bytes)
3/25/2005 6:00 AM
msdtc.exe Not Available 1132 8 Not
Available Not Available 9/19/2005 5:25 PM Not
Available Not Available Not Available
svchost.exe c:\windows\system32\svchost.exe
1272 8 204800 1413120
9/19/2005 5:25 PM 5.2.3790.1830
(srv03_spl_rtm.050324-1447) 24.50 KB (25,088 bytes)
3/25/2005 6:00 AM
msftesql.exe c:\program files\microsoft sql
server\mssql.1\mssql\bin\msftesql.exe 1372 8
204800 1413120 9/19/2005 5:25 PM
12.0.5626.1 152.20 KB (155,856
bytes) 8/26/2005 5:17 PM
svchost.exe c:\windows\system32\svchost.exe
1672 8 204800 1413120
9/19/2005 5:25 PM 5.2.3790.1830
(srv03_spl_rtm.050324-1447) 24.50 KB (25,088 bytes)
3/25/2005 6:00 AM
wmiprvse.exe Not Available 1808 8
Not Available Not Available

```

```

9/19/2005 5:26 PM Not Available Not
Available Not Available
logon.scr Not Available 1508 4 Not
Available Not Available 9/19/2005 5:35 PM Not
Available Not Available Not Available
csrss.exe Not Available 1380 13 Not
Available Not Available 9/19/2005 5:44 PM Not
Available Not Available Not Available
winlogon.exe c:\windows\system32\winlogon.exe
1356 13 204800 1413120
9/19/2005 5:44 PM 5.2.3790.1830
(srv03_spl_rtm.050324-1447) 901.00 KB (922,624
bytes) 3/25/2005 6:00 AM
rdpclip.exe c:\windows\system32\rdpclip.exe
1312 8 204800 1413120
9/19/2005 5:44 PM 5.2.3790.1830
(srv03_spl_rtm.050324-1447) 99.00 KB (101,376
bytes) 7/18/2005 4:04 PM
explorer.exe c:\windows\explorer.exe 692
8 204800 1413120 9/19/2005
5:44 PM 6.00.3790.1830 (srv03_spl_rtm.050324-1447)
1.30 MB (1,364,480 bytes) 3/25/2005
6:00 AM
sqlservr.exe c:\program files\microsoft sql
server\mssql.1\mssql\bin\sqlservr.exe 1612 13
204800 1413120 9/19/2005 5:44 PM
2005.090.1314.00 41.55 MB (43,563,736
bytes) 9/3/2005 12:12 PM
cmd.exe c:\windows\system32\cmd.exe 1920 8
204800 1413120 9/19/2005 9:01 PM
5.2.3790.1830 (srv03_spl_rtm.050324-1447)
538.50 KB (551,424 bytes) 3/25/2005
6:00 AM
osql.exe c:\program files\microsoft sql
server\90\tools\bin\osql.exe 2684 8
204800 1413120 9/19/2005 9:02 PM
2005.090.1314.00 81.71 KB (83,672 bytes)
9/3/2005 12:08 PM
helpsvcs.exe c:\windows\pchealth\helpctr\binaries\helpsv
c.exe 2888 8 204800 1413120
9/19/2005 9:53 PM 5.2.3790.1830
(srv03_spl_rtm.050324-1447) 1.52 MB (1,591,296
bytes) 7/18/2005 4:05 PM
wmiprvse.exe Not Available 2292 8
Not Available Not Available
9/19/2005 9:53 PM Not Available Not
Available Not Available
helpctr.exe c:\windows\pchealth\helpctr\binaries\helpctr
r.exe 192 8 204800 1413120
9/19/2005 9:53 PM 5.2.3790.1830
(srv03_spl_rtm.050324-1447) 1.30 MB (1,363,456
bytes) 7/18/2005 4:05 PM
[Loaded Modules]
Name Version Size File Date Manufacturer
Path
winlogon 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
901.00 KB (922,624 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\winlogon.exe

```

```

ntdll 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
1.20 MB (1,257,472 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\ntdll.dll
kernel32 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
1.43 MB (1,500,160 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\kernel32.dll
advapi32 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
1.00 MB (1,051,136 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\advapi32.dll
rpcrt4 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
1.63 MB (1,714,176 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\rpcrt4.dll
crypt32 5.131.3790.1830 (srv03_spl_rtm.050324-1447)
1.36 MB (1,428,992 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\crypt32.dll
msasn1 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
152.50 KB (156,160 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\msasn1.dll
msvcrt 7.0.3790.1830 (srv03_spl_rtm.050324-1447)
508.00 KB (520,192 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\msvcrt.dll
user32 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
1.04 MB (1,085,952 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\user32.dll
gdi32 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
592.00 KB (606,208 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\gdi32.dll
nddeapi 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
25.00 KB (25,600 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\nddeapi.dll
profmap 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
36.00 KB (36,864 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\profmap.dll
netapi32 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
589.00 KB (603,136 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\netapi32.dll
userenv 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
1.02 MB (1,069,056 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\userenv.dll
psapi 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
29.00 KB (29,696 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\psapi.dll
regapi 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
108.50 KB (111,104 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\regapi.dll
secur32 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
120.00 KB (122,880 bytes) 3/25/2005

```

```

6:00 AM Microsoft Corporation
c:\windows\system32\secur32.dll
setupapi 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
1.45 MB (1,523,200 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\setupapi.dll
version 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
28.00 KB (28,672 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\version.dll
winsta 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
89.00 KB (91,136 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\winsta.dll
ws2_32 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
176.50 KB (180,736 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\ws2_32.dll
ws2help 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
30.50 KB (31,232 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\ws2help.dll
msgina 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
1.14 MB (1,193,472 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\msgina.dll
shsvcs 6.00.3790.1830 (srv03_spl_rtm.050324-1447)
193.50 KB (198,144 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\shsvcs.dll
shlwapi 6.00.3790.1830 (srv03_spl_rtm.050324-1447)
606.50 KB (621,056 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\shlwapi.dll
sfc 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
6.00 KB (6,144 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\sfc.dll
sfc_os 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
183.50 KB (187,904 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\sfc_os.dll
wintrust 5.131.3790.1830 (srv03_spl_rtm.050324-1447)
297.50 KB (304,640 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\wintrust.dll
imagehlp 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
57.50 KB (58,880 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\imagehlp.dll
ole32 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
2.43 MB (2,543,616 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\ole32.dll
comctl32 6.0 (srv03_spl_rtm.050324-1447)
1.51 MB (1,584,128 bytes) 7/18/2005
10:52 AM Microsoft Corporation
c:\windows\winsxs\amd64_microsoft.windows.c
ommon-controls_6595b64144ccf1df_6.0.3790.1830_x-
ww_aced72af\comctl32.dll
winscard 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
230.00 KB (235,520 bytes) 3/25/2005

```

6:00 AM Microsoft Corporation
c:\windows\system32\winscard.dll
wtsapi32 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
29.00 KB (29,696 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\wtsapi32.dll
winmm 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
303.50 KB (310,784 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\winmm.dll
sxs 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
1.91 MB (2,003,968 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\sxs.dll
shell32 6.00.3790.1830 (srv03_spl_rtm.050324-1447)
10.01 MB (10,492,416 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\shell32.dll
rsaenh 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
241.96 KB (247,768 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\rsaenh.dll
wldap32 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
390.00 KB (399,360 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\wldap32.dll
cscdll 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
151.50 KB (155,136 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\cscdll.dll
dimntfy 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
28.00 KB (28,672 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\dimntfy.dll
wlnotify 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
148.00 KB (151,552 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\wlnotify.dll
mpr 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
115.00 KB (117,760 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\mpr.dll
oleaut32 5.2.3790.1830 1.06 MB (1,116,160
bytes) 3/25/2005 6:00 AM Microsoft Corporation
c:\windows\system32\oleaut32.dll
winspool 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
247.00 KB (252,928 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\winspool.drv
comctl32 5.82 (srv03_spl_rtm.050324-1447)
934.50 KB (956,928 bytes) 7/18/2005
10:52 AM Microsoft Corporation
c:\windows\winsxs\amd64_microsoft.windows.c
ommon-controls_6595b64144ccfd5f_5.82.3790.1830_x-
ww_4d792d2a\comctl32.dll
uxtheme 6.00.3790.1830 (srv03_spl_rtm.050324-1447)
494.50 KB (506,368 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\uxtheme.dll
clbcatq 2001.12.4720.1830 (srv03_spl_rtm.050324-
1447) 865.00 KB (885,760 bytes) 7/18/2005
4:04 PM Microsoft Corporation
c:\windows\system32\clbcatq.dll

comres 2001.12.4720.1830 (srv03_spl_rtm.050324-
1447) 779.50 KB (798,208 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\comres.dll
wbemprox 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
38.00 KB (38,912 bytes) 7/18/2005
4:04 PM Microsoft Corporation
c:\windows\system32\wbem\wbemprox.dll
wbemcomn 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
524.00 KB (536,576 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\wbem\wbemcomn.dll
xpsp2res 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
2.77 MB (2,899,456 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\xpsp2res.dll
wbemsvc 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
58.00 KB (59,392 bytes) 7/18/2005
4:04 PM Microsoft Corporation
c:\windows\system32\wbem\wbemsvc.dll
fastprox 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
866.50 KB (887,296 bytes) 7/18/2005
4:04 PM Microsoft Corporation
c:\windows\system32\wbem\fastprox.dll
msvcp60 7.0.3790.1830 (srv03_spl_rtm.050324-1447)
919.50 KB (941,568 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\msvcp60.dll
ntdsapi 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
127.50 KB (130,560 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\ntdsapi.dll
dnsapi 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
297.50 KB (304,640 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\dnsapi.dll
services 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
216.50 KB (221,696 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\services.exe
ncobjapi 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
80.00 KB (81,920 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\ncobjapi.dll
scesrv 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
594.50 KB (608,768 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\scesrv.dll
authz 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
167.00 KB (171,008 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\authz.dll
umpnpmgr 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
205.00 KB (209,920 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\umpnpmgr.dll
eventlog 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
127.00 KB (130,048 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\eventlog.dll
lsass 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
14.00 KB (14,336 bytes) 3/25/2005

6:00 AM Microsoft Corporation
c:\windows\system32\lsass.exe
lsasrv 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
1.50 MB (1,568,256 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\lsasrv.dll
samlib 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
69.00 KB (70,656 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\samlib.dll
samsrv 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
1.01 MB (1,059,328 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\samsrv.dll
cryptdll 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
47.00 KB (48,128 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\cryptdll.dll
msprvs 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
47.50 KB (48,640 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\msprvs.dll
kerberos 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
698.00 KB (714,752 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\kerberos.dll
msvl_0 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
253.00 KB (259,072 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\msvl_0.dll
iphlpapi 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
177.00 KB (181,248 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\iphlpapi.dll
netlogon 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
666.00 KB (681,984 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\netlogon.dll
w32time 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
400.50 KB (410,112 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\w32time.dll
schannel 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
248.00 KB (253,952 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\schannel.dll
wdigest 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
130.50 KB (133,632 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\wdigest.dll
rassfm 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
36.00 KB (36,864 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\rassfm.dll
kdcsvc 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
409.00 KB (418,816 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\kdcsvc.dll
ntdsa 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
2.81 MB (2,948,096 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\ntdsa.dll

esent 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
2.26 MB (2,366,976 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\esent.dll
ntdsatq 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
51.00 KB (52,224 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\ntdsatq.dll
mswsock 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
478.00 KB (489,472 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\mswsock.dll
scecli 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
308.00 KB (315,392 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\scecli.dll
ws03res 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
794.00 KB (813,056 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\ws03res.dll
hnetcfg 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
561.00 KB (574,464 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\hnetcfg.dll
wshtcpip 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
29.00 KB (29,696 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\wshtcpip.dll
pstorsvc 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
36.00 KB (36,864 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\pstorsvc.dll
psbase 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
124.00 KB (126,976 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\psbase.dll
dssenh 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
226.96 KB (232,408 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\dssenh.dll
svchost 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
24.50 KB (25,088 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\svchost.exe
rpcss 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
672.00 KB (688,128 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\rpcss.dll
ntmarta 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
222.50 KB (227,840 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\ntmarta.dll
wkssvc 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
221.00 KB (226,304 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\wkssvc.dll
wiarpc 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
57.00 KB (58,368 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\wiarpc.dll
aelupsvc 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
31.50 KB (32,256 bytes) 3/25/2005

6:00 AM Microsoft Corporation
c:\windows\system32\aelupsvc.dll
apphelp 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
241.00 KB (246,784 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\apphelp.dll
dmserver 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
36.50 KB (37,376 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\dmserver.dll
es 2001.12.4720.1830 (srv03_spl_rtm.050324-1447)
357.00 KB (365,568 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\es.dll
srvsvc 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
156.50 KB (160,256 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\srvsvc.dll
cryptsvc 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
114.00 KB (116,736 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\cryptsvc.dll
certcli 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
372.00 KB (380,928 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\certcli.dll
atl 3.05.2284 96.50 KB (98,816 bytes)
3/25/2005 6:00 AM Microsoft Corporation
c:\windows\system32\atl.dll
vssapi 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
1.26 MB (1,320,960 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\vssapi.dll
wmisvc 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
227.00 KB (232,448 bytes) 7/18/2005
4:04 PM Microsoft Corporation
c:\windows\system32\wmisvc.dll
comsvcs 2001.12.4720.1830 (srv03_spl_rtm.050324-1447)
2.06 MB (2,156,544 bytes) 7/18/2005
4:04 PM Microsoft Corporation
c:\windows\system32\comsvcs.dll
sens 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
63.50 KB (65,024 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\sens.dll
browser 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
125.50 KB (128,512 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\browser.dll
netrap 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
26.00 KB (26,624 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\netrap.dll
wbemcore 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
1.24 MB (1,299,968 bytes) 7/18/2005
4:04 PM Microsoft Corporation
c:\windows\system32\wbem\wbemcore.dll
esscli 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
626.50 KB (641,536 bytes) 7/18/2005
4:04 PM Microsoft Corporation
c:\windows\system32\wbem\esscli.dll
wmiutils 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
171.00 KB (175,104 bytes) 7/18/2005

4:04 PM Microsoft Corporation
c:\windows\system32\wbem\wmiutils.dll
repdrvfs 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
353.50 KB (361,984 bytes) 7/18/2005
4:04 PM Microsoft Corporation
c:\windows\system32\wbem\repdrvfs.dll
wmiprvsd 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
743.00 KB (760,832 bytes) 7/18/2005
4:04 PM Microsoft Corporation
c:\windows\system32\wbem\wmiprvsd.dll
wbemess 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
532.50 KB (545,280 bytes) 7/18/2005
4:04 PM Microsoft Corporation
c:\windows\system32\wbem\wbemess.dll
ncprov 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
73.00 KB (74,752 bytes) 7/18/2005
4:04 PM Microsoft Corporation
c:\windows\system32\wbem\ncprov.dll
netman 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
457.00 KB (467,968 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\netman.dll
mprapi 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
154.50 KB (158,208 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\mprapi.dll
activeds 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
348.50 KB (356,864 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\activeds.dll
adslfdc 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
240.50 KB (246,272 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\adslfdc.dll
credui 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
202.00 KB (206,848 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\credui.dll
rtutils 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
66.00 KB (67,584 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\rtutils.dll
netshell 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
2.32 MB (2,437,120 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\netshell.dll
clusapi 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
127.00 KB (130,048 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\clusapi.dll
rasapi32 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
410.00 KB (419,840 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\rasapi32.dll
rasman 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
95.50 KB (97,792 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\rasman.dll
tapi32 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
332.50 KB (340,480 bytes) 3/25/2005
6:00 AM Microsoft Corporation
c:\windows\system32\tapi32.dll

```

wininet 6.00.3790.1830 (srv03_spl_rtm.050324-1447)
1.13 MB (1,186,304 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\wininet.dll
wzcsapi 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
49.00 KB (50,176 bytes) 3/24/2005
Microsoft Corporation
11:35 AM c:\windows\system32\wzcsapi.dll
wzcsvc 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
492.00 KB (503,808 bytes) 3/24/2005
Microsoft Corporation
11:35 AM c:\windows\system32\wzcsvc.dll
wmi 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
5.50 KB (5,632 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\wmi.dll
dhcpcsvc 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
219.00 KB (224,256 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\dhcpcsvc.dll
rasdlg 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
859.50 KB (880,128 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\rasdlg.dll
rasadhlp 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
12.00 KB (12,288 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\rasadhlp.dll
netcfgx 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
1.29 MB (1,354,240 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\netcfgx.dll
winipsec 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
52.50 KB (53,760 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\winipsec.dll
wbemcons 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
65.50 KB (67,072 bytes) 7/18/2005
Microsoft Corporation
4:04 PM c:\windows\system32\wbem\wbemcons.dll
pchsvc 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
76.00 KB (77,824 bytes) 7/18/2005
Microsoft Corporation
4:05 PM c:\windows\pchealth\helpctr\binaries\pchsvc
.dll
ersvc 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
31.00 KB (31,744 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\ersvc.dll
msftesql 12.0.5626.1 152.20 KB (155,856
bytes) 8/26/2005 5:17 PM Microsoft Corporation
c:\program files\microsoft sql
server\mssql.1\mssql\bin\msftesql.exe
msfte 12.0.5626.1 3.63 MB (3,803,344
bytes) 8/26/2005 5:17 PM Microsoft Corporation
c:\program files\microsoft sql
server\mssql.1\mssql\bin\msfte.dll
dbghelp 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
1.22 MB (1,274,368 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\dbghelp.dll
msftepxy 12.0.5626.1 121.70 KB (124,624
bytes) 8/26/2005 5:17 PM Microsoft Corporation

```

```

c:\program files\microsoft sql
server\mssql.1\mssql\bin\msftepxy.dll
termsrv 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
354.50 KB (363,008 bytes) 7/18/2005
Microsoft Corporation
4:04 PM c:\windows\system32\termsrv.dll
icaapi 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
27.50 KB (28,160 bytes) 7/18/2005
Microsoft Corporation
4:04 PM c:\windows\system32\icaapi.dll
mstlsapi 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
187.00 KB (191,488 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\mstlsapi.dll
rdpwsx 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
170.13 KB (174,216 bytes) 7/18/2005
Microsoft Corporation
4:04 PM c:\windows\system32\rdpwsx.dll
rdpsnd 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
25.00 KB (25,600 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\rdpsnd.dll
scredir 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
38.50 KB (39,424 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\scredir.dll
cscui 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
441.00 KB (451,584 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\cscui.dll
msacm32 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
31.00 KB (31,744 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\msacm32.drv
msacm32 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
112.00 KB (114,688 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\msacm32.dll
imaadp32 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
24.00 KB (24,576 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\imaadp32.acm
msadp32 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
23.50 KB (24,064 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\msadp32.acm
msg711 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
13.50 KB (13,824 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\msg711.acm
msgsm32 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
34.50 KB (35,328 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\msgsm32.acm
tssoft32 1.01 13.50 KB (13,824 bytes)
3/25/2005 6:00 AM DSP GROUP, INC.
c:\windows\system32\tssoft32.acm
tsd32 1.03 24.50 KB (25,088 bytes)
3/25/2005 6:00 AM DSP GROUP, INC.
c:\windows\system32\tsd32.dll
rdpclip 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
99.00 KB (101,376 bytes) 7/18/2005

```

```

4:04 PM Microsoft Corporation
c:\windows\system32\rdpclip.exe
wsock32 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
24.50 KB (25,088 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\wsock32.dll
urlmon 6.00.3790.1830 (srv03_spl_rtm.050324-1447)
1.02 MB (1,074,176 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\urlmon.dll
explorer 6.00.3790.1830 (srv03_spl_rtm.050324-1447)
1.30 MB (1,364,480 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\explorer.exe
browseui 6.00.3790.1830 (srv03_spl_rtm.050324-1447)
1.53 MB (1,601,536 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\browseui.dll
shdocvw 6.00.3790.1830 (srv03_spl_rtm.050324-1447)
2.30 MB (2,416,128 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\shdocvw.dll
cryptui 5.131.3790.1830 (srv03_spl_rtm.050324-1447)
705.50 KB (722,432 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\cryptui.dll
themeui 6.00.3790.1830 (srv03_spl_rtm.050324-1447)
530.50 KB (543,232 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\themeui.dll
msimg32 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
6.50 KB (6,656 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\msimg32.dll
linkinfo 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
30.00 KB (30,720 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\linkinfo.dll
ntshrui 6.00.3790.1830 (srv03_spl_rtm.050324-1447)
184.00 KB (188,416 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\ntshrui.dll
webcheck 6.00.3790.1830 (srv03_spl_rtm.050324-1447)
439.00 KB (449,536 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\webcheck.dll
stobject 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
142.50 KB (145,920 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\stobject.dll
batmeter 6.00.3790.1830 (srv03_spl_rtm.050324-1447)
41.50 KB (42,496 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\batmeter.dll
powrprof 6.00.3790.1830 (srv03_spl_rtm.050324-1447)
32.50 KB (33,280 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\powrprof.dll
drprov 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
24.00 KB (24,576 bytes) 3/25/2005
Microsoft Corporation
6:00 AM c:\windows\system32\drprov.dll

```


ntlanman 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
 71.50 KB (73,216 bytes) 3/25/2005
 Microsoft Corporation
 c:\windows\system32\ntlanman.dll
 netui0 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
 130.00 KB (133,120 bytes) 3/25/2005
 Microsoft Corporation
 c:\windows\system32\netui0.dll
 netui1 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
 338.50 KB (346,624 bytes) 3/25/2005
 Microsoft Corporation
 c:\windows\system32\netui1.dll
 davclnt 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
 38.00 KB (38,912 bytes) 3/25/2005
 Microsoft Corporation
 c:\windows\system32\davclnt.dll
 browselc 6.00.3790.1830 (srv03_spl_rtm.050324-1447)
 63.00 KB (64,512 bytes) 3/25/2005
 Microsoft Corporation
 c:\windows\system32\browselc.dll
 shdoclc 6.00.3790.1830 (srv03_spl_rtm.050324-1447)
 589.50 KB (603,648 bytes) 3/25/2005
 Microsoft Corporation
 c:\windows\system32\shdoclc.dll
 mlang 6.00.3790.1830 (srv03_spl_rtm.050324-1447)
 686.00 KB (702,464 bytes) 3/25/2005
 Microsoft Corporation
 c:\windows\system32\mlang.dll
 mprui 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
 67.50 KB (69,120 bytes) 3/25/2005
 Microsoft Corporation
 c:\windows\system32\mprui.dll
 netui2 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
 542.00 KB (555,008 bytes) 3/25/2005
 Microsoft Corporation
 c:\windows\system32\netui2.dll
 comdlg32 6.00.3790.1830 (srv03_spl_rtm.050324-1447)
 446.50 KB (457,216 bytes) 3/25/2005
 Microsoft Corporation
 c:\windows\system32\comdlg32.dll
 netmsg 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
 179.00 KB (183,296 bytes) 3/25/2005
 Microsoft Corporation
 c:\windows\system32\netmsg.dll
 netplwiz 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
 938.50 KB (961,024 bytes) 3/25/2005
 Microsoft Corporation
 c:\windows\system32\netplwiz.dll
 diskcopy 6.00.3790.1830 (srv03_spl_rtm.050324-1447)
 1.44 MB (1,507,840 bytes) 3/25/2005
 Microsoft Corporation
 c:\windows\system32\diskcopy.dll
 zipfldr 6.00.3790.1830 (srv03_spl_rtm.050324-1447)
 449.50 KB (460,288 bytes) 3/25/2005
 Microsoft Corporation
 c:\windows\system32\zipfldr.dll
 actxprxy 6.00.3790.1830 (srv03_spl_rtm.050324-1447)
 220.50 KB (225,792 bytes) 3/25/2005
 Microsoft Corporation
 c:\windows\system32\actxprxy.dll
 mydocs 6.00.3790.1830 (srv03_spl_rtm.050324-1447)
 101.00 KB (103,424 bytes) 3/25/2005

6:00 AM Microsoft Corporation
 c:\windows\system32\mydocs.dll
 wshex 5.6.0.8827 80.00 KB (81,920 bytes)
 3/25/2005 6:00 AM Microsoft Corporation
 c:\windows\system32\wshex.dll
 mmcshext 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
 75.50 KB (77,312 bytes) 3/25/2005
 Microsoft Corporation
 c:\windows\system32\mmcshext.dll
 hhsetup 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
 78.00 KB (79,872 bytes) 3/25/2005
 Microsoft Corporation
 c:\windows\system32\hhsetup.dll
 sqlservr 2005.090.1314.00 41.55 MB (43,563,736
 bytes) 9/3/2005 12:12 PM Microsoft Corporation
 c:\program files\microsoft sql
 server\mssql.1\mssql\bin\sqlservr.exe
 msvcr80 8.00.50727.26 803.50 KB (822,784
 bytes) 8/30/2005 8:50 PM Microsoft Corporation
 c:\windows\winsxs\amd64_microsoft.vc80.crt_
 1fc8b3b9a1e18e3b_8.0.50727.26_x-
 ww_3fe85033\msvcr80.dll
 msvcp80 8.00.50727.26 1.05 MB (1,097,728
 bytes) 8/30/2005 8:53 PM Microsoft Corporation
 c:\windows\winsxs\amd64_microsoft.vc80.crt_
 1fc8b3b9a1e18e3b_8.0.50727.26_x-
 ww_3fe85033\msvcp80.dll
 opensds0 2005.090.1314.00 22.21 KB (22,744 bytes)
 9/3/2005 12:07 PM Microsoft Corporation
 c:\program files\microsoft sql
 server\mssql.1\mssql\bin\opensds0.dll
 instapi 2005.090.1314.00 40.71 KB (41,688 bytes)
 9/3/2005 12:03 PM Microsoft Corporation
 c:\program files\microsoft sql
 server\90\shared\instapi.dll
 sqlevn70 2005.090.1314.00 1.57 MB (1,641,688
 bytes) 9/3/2005 12:09 PM Microsoft Corporation
 c:\program files\microsoft sql
 server\mssql.1\mssql\bin\resources\1033\sqlevn70.rll
 sqlos 2005.090.1314.00 15.71 KB (16,088 bytes)
 9/3/2005 12:10 PM Microsoft Corporation
 c:\program files\microsoft sql
 server\mssql.1\mssql\bin\sqlos.dll
 mscoree 2.0.50727.26 (RTM.050727-2600)
 441.00 KB (451,584 bytes) 8/30/2005
 Microsoft Corporation
 c:\windows\system32\mscoree.dll
 xolehlp 2001.12.4720.1830 (srv03_spl_rtm.050324-
 1447) 10.50 KB (10,752 bytes) 7/18/2005
 Microsoft Corporation
 c:\windows\system32\xolehlp.dll
 msdtcprx 2001.12.4720.1830 (srv03_spl_rtm.050324-
 1447) 805.50 KB (824,832 bytes) 7/18/2005
 Microsoft Corporation
 c:\windows\system32\msdtcprx.dll
 mtxcclu 2001.12.4720.1830 (srv03_spl_rtm.050324-
 1447) 141.50 KB (144,896 bytes) 3/25/2005
 Microsoft Corporation
 c:\windows\system32\mtxcclu.dll
 resutils 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
 98.50 KB (100,864 bytes) 3/25/2005

6:00 AM Microsoft Corporation
 c:\windows\system32\resutils.dll
 winnrr 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
 30.00 KB (30,720 bytes) 3/25/2005
 Microsoft Corporation
 c:\windows\system32\winnrr.dll
 security 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
 6.00 KB (6,144 bytes) 3/25/2005
 Microsoft Corporation
 c:\windows\system32\security.dll
 dbghelp 6.4.0004.3 (vbl_core(jshay).041001-1326)
 1.37 MB (1,434,328 bytes) 9/3/2005
 Microsoft Corporation
 c:\program
 files\microsoft sql server\90\shared\dbghelp.dll
 sqlncli 2005.090.1314.00 3.01 MB (3,152,144
 bytes) 9/3/2005 12:12 PM Microsoft Corporation
 c:\windows\system32\sqlncli.dll
 sqlnclir 2005.090.1314.00 201.21 KB (206,040
 bytes) 9/3/2005 12:08 PM Microsoft Corporation
 c:\windows\system32\sqlnclir.rll
 cmd 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
 538.50 KB (551,424 bytes) 3/25/2005
 Microsoft Corporation
 c:\windows\system32\cmd.exe
 osql 2005.090.1314.00 81.71 KB (83,672 bytes)
 9/3/2005 12:08 PM Microsoft Corporation
 c:\program files\microsoft sql
 server\90\tools\bin\osql.exe
 odbcs32 3.526.1830.0 (srv03_spl_rtm.050324-1447)
 408.00 KB (417,792 bytes) 3/25/2005
 Microsoft Corporation
 c:\windows\system32\odbc32.dll
 odbcbint 3.526.1830.0 (srv03_spl_rtm.050324-1447)
 96.00 KB (98,304 bytes) 3/25/2005
 Microsoft Corporation
 c:\windows\system32\odbcbint.dll
 osql 2005.090.1314.00 15.21 KB (15,576 bytes)
 9/3/2005 12:07 PM Microsoft Corporation
 c:\program files\microsoft sql
 server\90\tools\bin\resources\1033\osql.rll
 helpsvc 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
 1.52 MB (1,591,296 bytes) 7/18/2005
 Microsoft Corporation
 c:\windows\pchealth\helpctr\binaries\helpsv
 c.exe
 hcappres 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
 7.50 KB (7,680 bytes) 7/18/2005
 Microsoft Corporation
 c:\windows\pchealth\helpctr\binaries\hcappr
 es.dll
 msxml3 8.70.1104.0 2.04 MB (2,141,184
 bytes) 3/25/2005 6:00 AM Microsoft Corporation
 c:\windows\system32\msxml3.dll
 helpctr 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
 1.30 MB (1,363,456 bytes) 7/18/2005
 Microsoft Corporation
 c:\windows\pchealth\helpctr\binaries\helpctr
 r.exe
 itss 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
 208.00 KB (212,992 bytes) 3/25/2005
 Microsoft Corporation
 c:\windows\system32\itss.dll

```

pchshell 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
155.00 KB (158,720 bytes) 7/18/2005
Microsoft Corporation
c:\windows\pchealth\helpctr\binaries\pchshell.dll
mshtml 6.00.3790.1830 (srv03_spl_rtm.050324-1447)
5.65 MB (5,928,448 bytes) 3/25/2005
Microsoft Corporation
c:\windows\system32\mshtml.dll
msls31 3.10.349.0 357.00 KB (365,568
bytes) 3/25/2005 6:00 AM Microsoft Corporation
c:\windows\system32\msls31.dll
msimtf 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
380.50 KB (389,632 bytes) 3/25/2005
Microsoft Corporation
c:\windows\system32\msimtf.dll
msctf 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
617.50 KB (632,320 bytes) 3/25/2005
Microsoft Corporation
c:\windows\system32\msctf.dll
jscript 5.6.0.8827 974.50 KB (997,888
bytes) 3/25/2005 6:00 AM Microsoft Corporation
c:\windows\system32\jscript.dll
imm32 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
208.00 KB (212,992 bytes) 3/25/2005
Microsoft Corporation
c:\windows\system32\imm32.dll
mshtml 6.00.3790.1830 (srv03_spl_rtm.050324-1447)
905.50 KB (927,232 bytes) 3/25/2005
Microsoft Corporation
c:\windows\system32\mshtml.dll
vbscript 5.6.0.8827 646.50 KB (662,016
bytes) 3/25/2005 6:00 AM Microsoft Corporation
c:\windows\system32\vbscript.dll
msinfo 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
636.00 KB (651,264 bytes) 7/18/2005
Microsoft Corporation
c:\windows\pchealth\helpctr\binaries\msinfo
.dll
mfc42u 6.50.9146.0 1.39 MB (1,462,272
bytes) 3/25/2005 6:00 AM Microsoft Corporation
c:\windows\system32\mfc42u.dll
riched32 5.2.3790.1830 (srv03_spl_rtm.050324-1447)
7.00 KB (7,168 bytes) 3/25/2005
Microsoft Corporation
c:\windows\system32\riched32.dll
riched20 5.31.23.1224 1.10 MB (1,157,120
bytes) 3/25/2005 6:00 AM Microsoft Corporation
c:\windows\system32\riched20.dll

[Services]
Display Name Name State Start Mode
Service Type Path Error Control
Start Name Tag ID
Application Experience Lookup Service AeLookupSvc
Running Auto Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
Alerter Alserter Stopped Disabled Share Process
c:\windows\system32\svchost.exe -k
localservice Normal NT
AUTHORITY\LocalService 0

```

```

Application Layer Gateway Service ALG
Stopped Manual Own Process
c:\windows\system32\alg.exe Normal NT
AUTHORITY\LocalService 0
Application Management AppMgmt Stopped
Manual Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
ASP.NET State Service aspnet_state
Stopped Manual Own Process
c:\windows\microsoft.net\framework64\v2.0.5
0727\aspnet_state.exe Normal NT
AUTHORITY\NetworkService 0
Windows Audio AudioSrv Stopped Disabled
Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
Background Intelligent Transfer Service BITS
Stopped Manual Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
Computer Browser Browser Running Auto
Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
Indexing Service CsiSvc Stopped Disabled
Share Process
c:\windows\system32\cisvc.exe Normal
LocalSystem 0
ClipBook ClipSrv Stopped Disabled Own Process
c:\windows\system32\clipsrv.exe
Normal LocalSystem 0
.NET Runtime Optimization Service v2.0.50727_X86
clr_optimization_v2.0.50727_32
Stopped Manual Own Process
c:\windows\microsoft.net\framework\v2.0.507
27\mscorsvw.exe Ignore LocalSystem 0
.NET Runtime Optimization Service v2.0.50727_x64
clr_optimization_v2.0.50727_64
Stopped Manual Own Process
c:\windows\microsoft.net\framework64\v2.0.5
0727\mscorsvw.exe Ignore LocalSystem 0
COM+ System Application COMSysApp Stopped
Manual Own Process
c:\windows\system32\dlhst.exe
/processid:{02d4b3f1-fd88-11d1-960d-00805fc79235}
Normal LocalSystem 0
Cryptographic Services CryptSvc Running
Auto Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
DCOM Server Process Launcher DcomLaunch
Running Auto Share Process
c:\windows\system32\svchost.exe -k
dcomlaunch Normal LocalSystem 0
Distributed File System Dfs Stopped
Manual Own Process
c:\windows\system32\dfsrv.exe
Normal LocalSystem 0

```

```

DHCP Client Dhcp Stopped Disabled
Share Process
c:\windows\system32\svchost.exe -k
networkservice Normal NT
AUTHORITY\NetworkService 0
Logical Disk Manager Administrative Service
dmdadmin Stopped Manual Share Process
c:\windows\system32\dmdadmin.exe /com
Normal LocalSystem 0
Logical Disk Manager dmserver Running
Auto Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
DNS Client Dnscache Running Auto
Share Process
c:\windows\system32\svchost.exe -k
networkservice Normal NT
AUTHORITY\NetworkService 0
Error Reporting Service ERSvc Running
Auto Share Process
c:\windows\system32\svchost.exe -k winerr
Ignore LocalSystem 0
Event Log Eventlog Running Auto Share Process
c:\windows\system32\services.exe
Normal LocalSystem 0
COM+ Event System EventSystem Running
Auto Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
Help and Support helpsvc Running Auto
Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
Human Interface Device Access HidServ Stopped
Disabled Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
HTTP SSL HTTPFilter Stopped Manual
Share Process
c:\windows\system32\lsass.exe Normal
LocalSystem 0
IAS Jet Database Access IASJet Stopped
Manual Share Process
c:\windows\syswow64\svchost.exe -k iasjet
Normal LocalSystem 0
IMAPI CD-Burning COM Service ImapiService
Stopped Disabled Own Process
c:\windows\system32\imapi.exe Normal
LocalSystem 0
Intersite Messaging IsmServ Stopped Disabled Own
Process c:\windows\system32\ismserv.exe
Normal LocalSystem 0
Kerberos Key Distribution Center kdc
Stopped Disabled Share Process
c:\windows\system32\lsass.exe Normal
LocalSystem 0
Server lanmanserver Running Auto
Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
Workstation lanmanworkstation Running
Auto Share Process

```

```

c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
License Logging LicenseService Stopped
Disabled Own Process
c:\windows\system32\llssrv.exe
Normal NT AUTHORITY\NetworkService 0

TCP/IP NetBIOS Helper LmHosts Running
Auto Share Process
c:\windows\system32\svchost.exe -k
localservice Normal NT
AUTHORITY\LocalService 0
Messenger Messenger Stopped Disabled Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
NetMeeting Remote Desktop Sharing nmmsrvc
Stopped Disabled Own Process
c:\windows\system32\nmmsrvc.exe
Normal LocalSystem 0
Distributed Transaction Coordinator MSDTC
Running Auto Own Process
c:\windows\system32\msdtc.exe Normal NT
AUTHORITY\NetworkService 0
SQL Server FullText Search (MSSQLSERVER)
msftesql Running Auto Own Process
"c:\program files\microsoft sql
server\mssql.1\mssql\bin\msftesql.exe" -s:mssql.1 -
f:mssqlserver Normal LocalSystem 0

Windows Installer MSIServer Stopped Manual
Share Process
c:\windows\system32\msiexec.exe /v
Normal LocalSystem 0
SQL Server (MSSQLSERVER) MSSQLSERVER
Stopped Manual Own Process
"c:\program files\microsoft sql
server\mssql.1\mssql\bin\sqlservr.exe" -smssqlserver
Normal LocalSystem 0
SQL Server Active Directory Helper
MSSQLServerADHelper Stopped Disabled Own
Process "c:\program files\microsoft sql
server\90\shared\sqladhlp90.exe" Normal NT
AUTHORITY\NetworkService 0
Network DDE NetDDE Stopped Disabled
Share Process
c:\windows\system32\netdde.exe
Normal LocalSystem 0
Network DDE DSDM NetDDEdsdm Stopped
Disabled Share Process
c:\windows\system32\netdde.exe
Normal LocalSystem 0
Net Logon Netlogon Stopped Manual Share Process
c:\windows\system32\lsass.exe Normal
LocalSystem 0
Network Connections Netman Running Manual
Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
Network Location Awareness (NLA) Nla
Running Manual Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0

```

```

File Replication Ntfrs Stopped Manual Own
Process c:\windows\system32\ntfrs.exe Ignore
LocalSystem 0
NT LM Security Support Provider NtLmSsp
Running Manual Share Process
c:\windows\system32\lsass.exe Normal
LocalSystem 0
Removable Storage NtmsSvc Stopped Manual
Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
Office Source Engine ose Stopped
Manual Own Process "c:\program
files (x86)\common files\microsoft shared\source
engine\ose.exe" Normal LocalSystem 0

Plug and Play PlugPlay Running Auto
Share Process
c:\windows\system32\services.exe
Normal LocalSystem 0
IPSEC Services PolicyAgent Stopped
Disabled Share Process
c:\windows\system32\lsass.exe Normal
LocalSystem 0
Protected Storage ProtectedStorage Running
Auto Share Process
c:\windows\system32\lsass.exe Normal
LocalSystem 0
Remote Access Auto Connection Manager RasAuto
Stopped Manual Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
Remote Access Connection Manager RasMan
Stopped Manual Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
Remote Desktop Help Session Manager RDSessMgr
Stopped Manual Own Process
c:\windows\system32\sessmgr.exe
Normal LocalSystem 0
Routing and Remote Access RemoteAccess
Stopped Disabled Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
Remote Registry RemoteRegistry Stopped
Disabled Share Process
c:\windows\system32\svchost.exe -k regsvcs
Normal NT AUTHORITY\LocalService 0

Remote Procedure Call (RPC) Locator RpcLocator
Stopped Manual Own Process
c:\windows\system32\locator.exe
Normal NT AUTHORITY\NetworkService 0

Remote Procedure Call (RPC) RpcSs Running
Auto Share Process
c:\windows\system32\svchost.exe -k rpcss
Normal NT AUTHORITY\NetworkService 0

Resultant Set of Policy Provider RSoPProv
Stopped Manual Share Process
c:\windows\system32\rsopprov.exe
Normal LocalSystem 0

```

```

Special Administration Console Helper sacsvr
Stopped Manual Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
Security Accounts Manager SamSs Running
Auto Share Process
c:\windows\system32\lsass.exe Normal
LocalSystem 0
Smart Card SCardSvr Stopped Manual
Share Process
c:\windows\system32\scardsvr.exe
Ignore NT AUTHORITY\LocalService 0

Task Scheduler Schedule Stopped Disabled
Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
Secondary Logon seclogon Stopped Disabled
Share Process
c:\windows\system32\svchost.exe -k netsvcs
Ignore LocalSystem 0
System Event Notification SENS Running
Auto Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
Windows Firewall/Internet Connection Sharing (ICS)
SharedAccess Stopped Disabled
Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
Shell Hardware Detection ShellHWDetection
Running Auto Share Process
c:\windows\system32\svchost.exe -k netsvcs
Ignore LocalSystem 0
Print Spooler Spooler Stopped Disabled Own
Process c:\windows\system32\spoolsv.exe
Normal LocalSystem 0
SQL Server Browser SQLBrowser Stopped
Disabled Own Process "c:\program
files (x86)\microsoft sql
server\90\shared\sqlbrowser.exe" Normal
LocalSystem 0
SQL Server Agent (MSSQLSERVER)
SQLSERVERAGENT Stopped Manual Own
Process "c:\program files\microsoft sql
server\mssql.1\mssql\bin\sqlagent90.exe" -i
mssqlserver Normal LocalSystem 0

SQL Server VSS Writer SQLWriter Stopped
Manual Own Process "c:\program
files\microsoft sql server\90\shared\sqlwriter.exe"
Normal LocalSystem 0
Windows Image Acquisition (WIA) stisvc
Stopped Disabled Share Process
c:\windows\system32\svchost.exe -k imgsvc
Normal NT AUTHORITY\LocalService 0

Microsoft Software Shadow Copy Provider swprv
Stopped Manual Own Process
c:\windows\system32\svchost.exe -k swprv
Normal LocalSystem 0
Performance Logs and Alerts SysmonLog Stopped
Auto Own Process

```

```

c:\windows\system32\smlogsvc.exe
Normal NT Authority\NetworkService 0
Telephony TapiSrv Stopped Manual Share Process
c:\windows\system32\svchost.exe -k tapisrv
Normal LocalSystem 0
Terminal Services TermService Running
Manual Share Process
c:\windows\system32\svchost.exe -k termsvcs
Normal LocalSystem 0
Themes Themes Stopped Disabled Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
Telnet TlntSvr Stopped Disabled Own Process
c:\windows\system32\tlntsvr.exe
Normal NT AUTHORITY\LocalService 0
Distributed Link Tracking Server TrkSvr
Stopped Disabled Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
Distributed Link Tracking Client TrkWks
Stopped Disabled Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
Terminal Services Session Directory Tssdis
Stopped Disabled Own Process
c:\windows\system32\tssdis.exe
Normal LocalSystem 0
Windows User Mode Driver Framework UMWdf
Stopped Manual Own Process
c:\windows\system32\wdmfr.exe
Normal NT AUTHORITY\LocalService 0
Uninterruptible Power Supply UPS Stopped
Manual Own Process
c:\windows\system32\ups.exe Normal NT
AUTHORITY\LocalService 0
Virtual Disk Service vds Stopped
Manual Own Process
c:\windows\system32\vds.exe Normal
LocalSystem 0
Volume Shadow Copy VSS Stopped Manual Own
Process c:\windows\system32\vssvc.exe Normal
LocalSystem 0
Windows Time W32Time Running Auto
Share Process
c:\windows\system32\svchost.exe -k
localservice Normal NT
AUTHORITY\LocalService 0
WebClient WebClient Stopped Disabled Share Process
c:\windows\system32\svchost.exe -k
localservice Normal NT
AUTHORITY\LocalService 0
WinHTTP Web Proxy Auto-Discovery Service
WinHttpAutoProxySvc Stopped Manual
Share Process
c:\windows\system32\svchost.exe -k
localservice Normal NT
AUTHORITY\LocalService 0
Windows Management Instrumentation winmgmt
Running Auto Share Process

```

```

c:\windows\system32\svchost.exe -k netsvcs
Ignore LocalSystem 0
Portable Media Serial Number Service WmdmPmSN
Stopped Manual Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
Windows Management Instrumentation Driver Extensions
Wmi Stopped Manual Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
WMI Performance Adapter WmiApSrv Stopped
Manual Own Process
c:\windows\system32\wbem\wmiaprv.exe
Normal LocalSystem 0
Automatic Updates wuauerv Stopped Disabled
Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
Wireless Configuration WZCSVC Stopped
Disabled Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
Network Provisioning Service xmlprov Stopped
Manual Share Process
c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0

[Program Groups]

Group Name Name User Name
Accessories Default User:Accessories
Default User
Accessories\Accessibility Default
User:Accessories\Accessibility Default User
Accessories\Entertainment Default
User:Accessories\Entertainment Default User
Startup Default User:Startup Default User

Accessories All Users:Accessories All
Users
Accessories\Accessibility All
Users:Accessories\Accessibility All Users
Accessories\Communications All
Users:Accessories\Communications All Users
Accessories\Entertainment All
Users:Accessories\Entertainment All Users
Accessories\System Tools All
Users:Accessories\System Tools All Users
Administrative Tools All
Users:Administrative Tools All Users
Microsoft SQL Server 2005 CTP All Users:Microsoft SQL
Server 2005 CTP All Users
Microsoft SQL Server 2005 CTP\Analysis Services All
Users:Microsoft SQL Server 2005 CTP\Analysis Services
All Users
Microsoft SQL Server 2005 CTP\Configuration Tools All
Users:Microsoft SQL Server 2005 CTP\Configuration
Tools All Users
Microsoft SQL Server 2005 CTP\Documentation and
Tutorials All Users:Microsoft SQL Server 2005
CTP\Documentation and Tutorials All Users

```

```

Microsoft SQL Server 2005 CTP\Documentation and
Tutorials\Tutorials All Users:Microsoft SQL Server
2005 CTP\Documentation and Tutorials\Tutorials All
Users
Microsoft SQL Server 2005 CTP\Performance Tools All
Users:Microsoft SQL Server 2005 CTP\Performance Tools
All Users
Microsoft Visual Studio 2005 All Users:Microsoft
Visual Studio 2005 All Users
Microsoft Visual Studio 2005\Visual Studio Tools All
Users:Microsoft Visual Studio 2005\Visual Studio
Tools All Users
Startup All Users:Startup All Users
Accessories NT AUTHORITY\SYSTEM:Accessories
NT AUTHORITY\SYSTEM
Accessories\Accessibility NT
AUTHORITY\SYSTEM:Accessories\Accessibility NT
AUTHORITY\SYSTEM
Accessories\Entertainment NT
AUTHORITY\SYSTEM:Accessories\Entertainment NT
AUTHORITY\SYSTEM
Startup NT AUTHORITY\SYSTEM:Startup NT
AUTHORITY\SYSTEM
Accessories BOBCAT\Administrator:Accessories
BOBCAT\Administrator
Accessories\Accessibility
BOBCAT\Administrator:Accessories\Accessibil
ity
BOBCAT\Administrator
Accessories\Entertainment
BOBCAT\Administrator:Accessories\Entertainm
ent
BOBCAT\Administrator
Administrative Tools
BOBCAT\Administrator:Administrative Tools
BOBCAT\Administrator
Startup BOBCAT\Administrator:Startup
BOBCAT\Administrator

[Startup Programs]

Program Command User Name Location
desktop desktop.ini NT AUTHORITY\SYSTEM
Startup
desktop desktop.ini BOBCAT\Administrator
Startup
desktop desktop.ini .DEFAULT Startup
desktop desktop.ini All Users Common
Startup

[OLE Registration]

Object Local Server
Sound (OLE2) sndrec32.exe
Media Clip mplay32.exe
Video Clip mplay32.exe /avi
MIDI Sequence mplay32.exe /mid
Sound Not Available
Media Clip Not Available
WordPad Document "%programfiles%\windows
nt\accessories\wordpad.exe"
Bitmap Image mspaint.exe

[Windows Error Reporting]

```

```

Time      Type      Details

[Internet Settings]

[Internet Explorer]

[ Following are sub-categories of this main category ]
[Summary]

Item      Value
Version   6.0.3790.1830
Build     63790.1830
Application Path C:\Program Files\Internet Explorer
Language  English (United States)
Active Printer Not Available

Cipher Strength 128-bit
Content Advisor Disabled
IEAK Install No

[File Versions]

File      Version  Size  Date  Path
Company
actxprxy.dll 6.0.3790.1830 221 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

advpack.dll 6.0.3790.1830 146 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

asctrls.ocx 6.0.3790.1830 147 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

browselc.dll 6.0.3790.1830 63 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

browseui.dll 6.0.3790.1830 1,564 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

cdfview.dll 6.0.3790.1830 216 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

comctl32.dll 5.82.3790.1830 935 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

dxtrans.dll 6.3.3790.1830 320 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

dxtmsft.dll 6.3.3790.1830 549 KB
3/25/2005 7:00:00 AM

```

```

C:\WINDOWS\system32 Microsoft Corporation

iecont.dll <File Missing> Not Available
Not Available Not Available Not
Available
iecontlc.dll <File Missing> Not Available
Not Available Not Available Not
Available
iedkcs32.dll 16.0.3790.1830 417 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

iepeers.dll 6.0.3790.1830 361 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

iesetup.dll 6.0.3790.1830 71 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

ieuunit.inf Not Available 24 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Not Available
ieexplore.exe 6.0.3790.1830 94 KB
3/25/2005 7:00:00 AM C:\Program
Files\Internet Explorer Microsoft Corporation

imgutil.dll 6.0.3790.1830 61 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

inetcpl.cpl 6.0.3790.1830 428 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

inetcplc.dll 6.0.3790.1830 110 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

inseng.dll 6.0.3790.1830 147 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

mlang.dll 6.0.3790.1830 686 KB 3/25/2005
7:00:00 AM C:\WINDOWS\system32 Microsoft
Corporation
msencode.dll <File Missing> Not Available
Not Available Not Available Not
Available
mshta.exe 6.0.3790.1830 38 KB 3/25/2005
7:00:00 AM C:\WINDOWS\system32 Microsoft
Corporation
mshtml.dll 6.0.3790.1830 5,790 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

mshtml.tlb 6.0.3790.1830 1,320 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

mshtmlmled.dll 6.0.3790.1830 906 KB
3/25/2005 7:00:00 AM

```

```

C:\WINDOWS\system32 Microsoft Corporation

mshtmlmled.dll 6.0.3790.1830 56 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

msident.dll 6.0.3790.1830 69 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

msidentmled.dll 6.0.3790.1830 16 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

msieftp.dll 6.0.3790.1830 369 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

msrating.dll 6.0.3790.1830 240 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

mstime.dll 6.0.3790.1830 878 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

occache.dll 6.0.3790.1830 126 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

proctexe.ocx <File Missing> Not Available
Not Available Not Available Not
Available
sendmail.dll 6.0.3790.1830 64 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

shdoclc.dll 6.0.3790.1830 590 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

shdocvw.dll 6.0.3790.1830 2,360 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

shfolder.dll 6.0.3790.1830 34 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

shlwapi.dll 6.0.3790.1830 607 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

tdc.ocx 1.3.0.3130 91 KB 3/25/2005
7:00:00 AM C:\WINDOWS\system32 Microsoft
Corporation
url.dll 6.0.3790.1830 40 KB 3/25/2005
7:00:00 AM C:\WINDOWS\system32 Microsoft
Corporation
urlmon.dll 6.0.3790.1830 1,049 KB
3/25/2005 7:00:00 AM
C:\WINDOWS\system32 Microsoft Corporation

```

```

webcheck.dll      6.0.3790.1830      439 KB
                  3/25/2005 7:00:00 AM
                  C:\WINDOWS\system32\Microsoft Corporation

wininet.dll      6.0.3790.1830      1,159 KB
                  3/25/2005 7:00:00 AM
                  C:\WINDOWS\system32\Microsoft Corporation

```

[Connectivity]

```

Item      Value
Connection Preference      Never dial

```

LAN Settings

```

AutoConfigProxy      wininet.dll
AutoProxyDetectMode Disabled
AutoConfigURL
Proxy      Disabled
ProxyServer
ProxyOverride

```

[Cache]

```

[ Following are sub-categories of this main category ]
[Summary]

```

```

Item      Value
Page Refresh Type      Automatic
Temporary Internet Files Folder      C:\Documents
and Settings\Administrator\Local Settings\Temporary
Internet Files
Total Disk Space      Not Available
Available Disk Space      Not Available
Maximum Cache Size      Not Available
Available Cache Size      Not Available

```

[List of Objects]

```

Program File      Status      CodeBase
No cached object information available

```

[Content]

```

[ Following are sub-categories of this main category ]
[Summary]

```

```

Item      Value
Content Advisor      Disabled

```

[Personal Certificates]

```

Issued To Issued By Validity Signature Algorithm
No personal certificate information available

```

[Other People Certificates]

```

Issued To Issued By Validity Signature Algorithm

```

No other people certificate information available

[Publishers]

```

Name
No publisher information available

```

[Security]

```

Zone      Security Level
My Computer      Custom
Local intranet      Custom
Trusted sites      Custom
Internet High
Restricted sites      Custom

```

Microsoft SQL Server Registry Parameters

```

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server
Class Name:      <NO CLASS>
Last Write Time: 9/15/2005 - 8:52 PM
Value 0
Name:      SsrpActiveServer
Type:      REG_SZ
Data:
Value 1
Name:      InstalledInstances
Type:      REG_MULTI_SZ
Data:      MSSQLSERVER

```

```

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\90
Class Name:      <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name:      SharedCode
Type:      REG_SZ
Data:      C:\Program Files\Microsoft SQL
Server\90\Shared\

```

```

Value 1
Name:      VerSpecificRootDir
Type:      REG_SZ
Data:      C:\Program Files\Microsoft SQL
Server\90\

```

```

Value 2
Name:      EnableErrorReporting
Type:      REG_DWORD
Data:      0

```

```

Value 3
Name:      ErrorReportingDir
Type:      REG_SZ
Data:      C:\Program Files\Microsoft SQL
Server\90\Shared\ErrorDumps\

```

```

Value 4
Name:      CustomerFeedback
Type:      REG_DWORD
Data:      0

```

```

Value 5
Name:      TimeOfReporting
Type:      REG_DWORD
Data:      0xf0

```

```

Value 6
Name:      CollectorParameters
Type:      REG_SZ
Data:

```

```

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\90\Bootstrap
Class Name:      <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name:      BootstrapDir
Type:      REG_SZ
Data:      C:\Program Files\Microsoft SQL
Server\90\Setup\Bootstrap\

```

```

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\90\Bootstrap\MSIRefCount
Class Name:      <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name:      Uninstall
Type:      REG_SZ
Data:      {11111111-1111-1111-1111-
111111111111},{79F1B65E-8FC0-4D03-954D-
F9E71C85AEC7},{73D8B59D-0BFF-4B5B-A031-FAB3AC629E56}

```

```

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\90\Bootstrap\Setup
Class Name:      <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name:      PatchLevel
Type:      REG_SZ
Data:      9.00.1314.06

```

```

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\90\Cost
Class Name:      <NO CLASS>

```

Last Write Time: 9/15/2005 - 8:53 PM

Value 0

Name: SQLSetup
Type: REG_SZ
Data: 8388608

Value 1

Name: MSXML6
Type: REG_SZ
Data: 15728640

Value 2

Name: ToolsSetup
Type: REG_SZ
Data: 26214400

Value 3

Name: PPESku
Type: REG_SZ
Data: 157286400

Value 4

Name: owc11
Type: REG_SZ
Data: 4194304

Value 5

Name: sqlxml4
Type: REG_SZ
Data: 8388608

Value 6

Name: bol
Type: REG_SZ
Data: 178257920

Key Name:

HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\90\Machines

Class Name: <NO CLASS>

Last Write Time: 9/15/2005 - 8:53 PM

Value 0

Name: OriginalMachineName
Type: REG_SZ
Data: BOBCAT

Key Name:

HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\90\NodeConfiguration

Class Name: <NO CLASS>

Last Write Time: 9/15/2005 - 8:51 PM

Key Name:

HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\90\NodeConfiguration\Node0

Class Name: <NO CLASS>

Last Write Time: 9/15/2005 - 8:51 PM

Value 0

Name: CPUMask
Type: REG_DWORD
Data: 0x1

Key Name:

HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\90\NodeConfiguration\Node1

Class Name: <NO CLASS>

Last Write Time: 9/15/2005 - 8:51 PM

Value 0

Name: CPUMask
Type: REG_DWORD
Data: 0x2

Key Name:

HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\90\NodeConfiguration\Node2

Class Name: <NO CLASS>

Last Write Time: 9/15/2005 - 8:51 PM

Value 0

Name: CPUMask
Type: REG_DWORD
Data: 0x4

Key Name:

HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\90\NodeConfiguration\Node3

Class Name: <NO CLASS>

Last Write Time: 9/15/2005 - 8:51 PM

Value 0

Name: CPUMask
Type: REG_DWORD
Data: 0x8

Key Name:

HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\90\NodeConfiguration\Node4

Class Name: <NO CLASS>

Last Write Time: 9/19/2005 - 12:13 PM

Value 0

Name: CPUMask
Type: REG_DWORD
Data: 0x10

Key Name:

HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\90\NodeConfiguration\Node5

Class Name: <NO CLASS>

Last Write Time: 9/19/2005 - 12:14 PM

Value 0

Name: CPUMask
Type: REG_DWORD
Data: 0x20

Key Name:

HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\90\NodeConfiguration\Node6

Class Name: <NO CLASS>

Last Write Time: 9/19/2005 - 12:14 PM

Value 0

Name: CPUMask

Type: REG_DWORD

Data: 0x40

Key Name:

HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\90\NodeConfiguration\Node7

Class Name: <NO CLASS>

Last Write Time: 9/19/2005 - 12:14 PM

Value 0

Name: CPUMask
Type: REG_DWORD
Data: 0x80

Key Name:

HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\90\Tools

Class Name: <NO CLASS>

Last Write Time: 9/15/2005 - 8:53 PM

Key Name:

HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\90\Tools\ClientSetup

Class Name: <NO CLASS>

Last Write Time: 9/15/2005 - 8:53 PM

Value 0

Name: SQLBinRoot
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL Server\90\Shared\

Value 1

Name: SQLPath
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL Server\90\Tools

Value 2

Name: Path
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL Server\90\Tools\bin\

Value 3

Name: checksum
Type: REG_BINARY
Data:

00000000 38 37 33 66 66 66 30 65 - 62 38 32 62 30
34 37 62 873fff0eb82b047b
00000010 31 30 35 31 36 38 32 31 - 30 30 63 65 63
61 37 65 1051682100ceca7e
00000020 33 34 35 65 61 66 63 62 - 34 64 38 64 30
36 64 61 345eafcb4d806da
00000030 33 66 38 31 64 30 61 35 - 30 30 32 36 64
34 61 63 3f81d0a50026d4ac
00000040 33 37 66 62 39 30 62 61 - 39 65 65 65 36
36 66 33 37fb90ba9eee66f3
00000050 37 31 66 66 31 61 35 38 - 38 34 64 61 36
32 31 63 71ff1a5884da621c
00000060 63 34 32 62 66 33 33 61 - 63 65 64 31 32
62 66 39 c42bf33aced12bf9

00000070 30 37 39 36 30 39 61 31 - 63 30 37 64 64
39 65 31 079609a1c07dd9e1
00000080 31 32 35 61 65 66 35 65 - 31 61 39 63 32
37 32 37 125aef5e1a9c2727
00000090 37 64 39 65 63 63 31 62 - 66 33 31 63 35
37 37 62 7d9ecc1bf31c577b
000000a0 31 65 37 36 61 66 33 66 - 39 39 39 39 37
35 65 66 1e76af3f999975ef
00

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\90\Tools\ClientSetup\CurrentVersion
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: Language
Type: REG_DWORD
Data: 0x409

Value 1
Name: CurrentVersion
Type: REG_SZ
Data: 9.00.1314.06

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\90\Tools\Service Manager
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: Services
Type: REG_MULTI_SZ
Data: ;

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\90\Tools\Setup
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:53 PM
Value 0
Name: Version
Type: REG_SZ
Data: 9.00.1314.06

Value 1
Name: Language
Type: REG_DWORD
Data: 0x409

Value 2
Name: ProductCode
Type: REG_SZ
Data: {73D8B59D-0BFF-4B5B-A031-FAB3AC629E56}

Value 3
Name: FeatureList
Type: REG_SZ

Data: Client_Components=3
SQL_Documentation=3 Connectivity=3 SQL_Tools90=3
SQL_WarehouseDevWorkbench=3 SDK=3 SQLXML=3
Tools_Legacy=3 TOOLS_BC_DEP=3 SQL_BooksOnline=3

Value 4
Name: PatchLevel
Type: REG_SZ
Data: 9.00.1314.06

Value 5
Name: SQLPath
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL
Server\90\Tools\

Value 6
Name: checksum
Type: REG_BINARY
Data: 00000000 38 37 33 66 66 66 30 65 - 62 38 32 62 30
34 37 62 873fff0eb82b047b
00000010 31 30 35 31 36 38 32 31 - 30 30 63 65 63
61 37 65 1051682100ceca7e
00000020 33 34 35 65 61 66 63 62 - 34 64 38 64 30
36 64 61 345eafcb4d8d06da
00000030 33 66 38 31 64 30 61 35 - 30 30 32 36 64
34 61 63 3f81d0a50026d4ac
00000040 33 37 66 62 39 30 62 61 - 39 65 65 65 36
36 66 33 37fb90ba9eee66f3
00000050 37 31 66 66 31 61 35 38 - 38 34 64 61 36
32 31 63 71ffa5884da621c
00000060 63 34 32 62 66 33 33 61 - 63 65 64 31 32
62 66 39 c42bf33aced12bf9
00000070 30 37 39 36 30 39 61 31 - 63 30 37 64 64
39 65 31 079609a1c07dd9e1
00000080 31 32 35 61 65 66 35 65 - 31 61 39 63 32
37 32 37 125aef5e1a9c2727
00000090 37 64 39 65 63 63 31 62 - 66 33 31 63 35
37 37 62 7d9ecc1bf31c577b
000000a0 31 65 37 36 61 66 33 66 - 39 39 39 39 37
35 65 66 1e76af3f999975ef
00

Value 7
Name: Edition
Type: REG_SZ
Data: Enterprise Edition (64-bit)

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\90\Tools\Shortcut
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\90\Tools\Shortcut\SQL Server Error and Usage
Reporting
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0

Name: 1033
Type: REG_SZ
Data:

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\90\Uninstall Info
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:53 PM

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\90\Uninstall Info\{73D8B59D-0BFF-4B5B-A031-
FAB3AC629E56}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:53 PM
Value 0
Name: Product
Type: REG_SZ
Data: Client_Components

Value 1
Name: SetupHive
Type: REG_SZ
Data: 90\Tools

Value 2
Name: RemoveList
Type: REG_SZ
Data: Client_Components,Connectivity,SQL_Tools90,SQL_Wareho
useDevWorkbench,SDK,SQLXML,Tools_Legacy,TOOLS_BC_DEP,
SQL_Documentation,SQL_BooksOnline,SQL_DatabaseSamples
,SQL_AdventureWorksSamples,SQL_AdventureWorksDWSampl
e,SQL_AdventureWorksASSamples,SQL_Samples

Value 3
Name: ModifyPath
Type: REG_SZ
Data: "C:\Program Files\Microsoft SQL
Server\90\Setup Bootstrap\setup.exe" /resumsetup
/productcode {73D8B59D-0BFF-4B5B-A031-FAB3AC629E56}
/I {73D8B59D-0BFF-4B5B-A031-FAB3AC629E56}

Value 4
Name: UninstallPath
Type: REG_SZ
Data: "C:\Program Files\Microsoft SQL
Server\90\Setup Bootstrap\setup.exe" /resumsetup
/productcode {73D8B59D-0BFF-4B5B-A031-FAB3AC629E56}
/X {73D8B59D-0BFF-4B5B-A031-FAB3AC629E56}

Value 5
Name: Status
Type: REG_DWORD
Data: 0

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\90\Uninstall Info\{79F1B65E-8FC0-4D03-954D-
F9E71C85AEC7}

Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM
 Value 0
 Name: Product
 Type: REG_SZ
 Data: SQL_Engine

Value 1
 Name: SetupHive
 Type: REG_SZ
 Data: MSSQL.1

Value 2
 Name: RemoveList
 Type: REG_SZ
 Data: SQL_Engine,SQL_Data_Files,SQL_Replication,SQL_FullText,SQL_SharedTools,SQL_BC_DEP

Value 3
 Name: ModifyPath
 Type: REG_SZ
 Data: "C:\Program Files\Microsoft SQL Server\90\Setup Bootstrap\setup.exe" /resumsetup /productcode {79F1B65E-8FC0-4D03-954D-F9E71C85AEC7} /I {79F1B65E-8FC0-4D03-954D-F9E71C85AEC7}

Value 4
 Name: UninstallPath
 Type: REG_SZ
 Data: "C:\Program Files\Microsoft SQL Server\90\Setup Bootstrap\setup.exe" /resumsetup /productcode {79F1B65E-8FC0-4D03-954D-F9E71C85AEC7} /X {79F1B65E-8FC0-4D03-954D-F9E71C85AEC7}

Value 5
 Name: Status
 Type: REG_DWORD
 Data: 0

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\BC
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:48 PM

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\BC\CurrentVersion
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:48 PM

Value 0
 Name: Version
 Type: REG_SZ
 Data: 8.05.1041

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\BC\MSIRefCount
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:50 PM

Value 0
 Name: Uninstall
 Type: REG_SZ
 Data: {11111111-1111-1111-1111-111111111111},{79F1B65E-8FC0-4D03-954D-F9E71C85AEC7},{73D8B59D-0BFF-4B5B-A031-FAB3AC629E56}

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\ExceptionMessageBox
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Value 0
 Name: ShowFeedbackButton
 Type: REG_DWORD
 Data: 0x1

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\Instance Names
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\Instance Names\SQL
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Value 0
 Name: MSSQLSERVER
 Type: REG_SZ
 Data: MSSQL.1

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Value 0
 Name: <NO NAME>
 Type: REG_SZ
 Data: MSSQLSERVER

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\CPE
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Value 0
 Name: ErrorDumpDir
 Type: REG_SZ
 Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\LOG\

Value 1
 Name: EnableErrorReporting
 Type: REG_DWORD
 Data: 0

Value 2
 Name: CustomerFeedback
 Type: REG_DWORD
 Data: 0

Value 3
 Name: TimeOfReporting
 Type: REG_DWORD
 Data: 0x3c

Value 4
 Name: CollectorParameters
 Type: REG_SZ
 Data: SQL MSSQL.1

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{01C6B350-12C7-11CE-BD31-00AA004BBB1F}
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Value 0
 Name: <NO NAME>
 Type: REG_SZ
 Data: infosoft.dll

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{12CE94A0-DEFB-11D2-B31D-00600893A857}
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Value 0
 Name: <NO NAME>
 Type: REG_SZ
 Data: chsbrkr.dll

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{1305C72E-2073-452E-A72D-667032B3B4FE}
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Value 0
 Name: <NO NAME>
 Type: REG_SZ
 Data: msir5jp.dll

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{1680E7C3-9430-4A51-9B82-1E7E7AEE5258}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: chtbrkr.dll

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{173C97E2-AEBE-437C-9445-01B237ABF2F6}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: langwrbk.dll

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{188D6CC5-CB03-4C01-912E-47D21295D77E}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: langwrbk.dll

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{2A6EB050-7F1C-11CE-BE57-00AA0051FE20}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: infosoft.dll

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{41B9BE05-B3AF-460C-BF0B-2CDD44A093B1}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: xmlfilt.dll

Value 1
Name: ThreadingModel
Type: REG_SZ

Data: Both

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{52F1DED5-C51B-11D2-9A7C-00004F6888ED}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: msfte.dll

Value 1
Name: ThreadingModel
Type: REG_SZ
Data: Both

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{66B37110-8BF2-11CE-BE59-00AA0051FE20}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: infosoft.dll

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{68C6D24E-77E0-11D5-8528-00C04F68155C}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: msfte.dll

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{6D36CE10-7F1C-11CE-BE57-00AA0051FE20}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: infosoft.dll

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{6DE705A5-6467-43DC-9CE3-CCFE08B3F645}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0

Name: <NO NAME>
Type: REG_SZ
Data: nls400.dll

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{737FC9B5-BC66-4953-B7DB-B79A72A592A5}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: korwrbrkr.dll

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{73D009FB-7D05-45AC-94C2-BDD1029942D4}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: langwrbk.dll

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{860D28D0-8BF4-11CE-BE59-00AA0051FE20}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: infosoft.dll

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{9478F640-7F1C-11CE-BE57-00AA0051FE20}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: infosoft.dll

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{95679344-48B8-42CD-9B79-2F5784D70258}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: langwrbk.dll

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{97E8EFC5-42DA-43ED-9CEC-84FDE3620F1A}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: korwbrkr.dll

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{9EA69E16-AD5E-43ED-B90E-73D58771D3F6}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: nls400.dll

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{A9FFAE02-D834-47B3-8434-0D75DC0804BD}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: msir5jp.dll

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{B0516FF0-7F1C-11CE-BE57-00AA0051FE20}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: infosoft.dll

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{C731071F-AC80-11D1-8DF3-00C04FB6EF4F}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: msfte.dll

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{C7310720-AC80-11D1-8DF3-00C04FB6EF4F}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: msfte.dll

Value 1
Name: ThreadingModel
Type: REG_SZ
Data: Both

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{CCA22CF4-59FE-11D1-BBFF-00C04FB97FDA}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: thawbrkr.dll

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{CEDC01C7-59FE-11D1-BBFF-00C04FB97FDA}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: thawbrkr.dll

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{D99F7670-7F1A-11CE-BE57-00AA0051FE20}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: infosoft.dll

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{E0CA5340-4534-11CF-B952-00AA0051FE20}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: nlhtml.dll

Value 1
Name: ThreadingModel
Type: REG_SZ
Data: Both

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{EED4C20-7F1B-11CE-BE57-00AA0051FE20}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: infosoft.dll

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{F07F3920-7B8C-11CF-9BE8-00AA004B9986}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: offfilt.dll

Value 1
Name: ThreadingModel
Type: REG_SZ
Data: Both

Value 2
Name: Flags
Type: REG_DWORD
Data: 0x1

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\CLSID\{FD86B5D0-12C6-11CE-BD31-00AA004BBB1F}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: infosoft.dll

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\ascx
Class Name: <NO CLASS>

Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {E0CA5340-4534-11CF-B952-00AA0051FE20}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\asm
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\asp
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {E0CA5340-4534-11CF-B952-00AA0051FE20}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\aspx
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {E0CA5340-4534-11CF-B952-00AA0051FE20}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\bat
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\c
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>

Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\cmd
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\cpp
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\cxx
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\def
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\dic
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\doc
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {F07F3920-7B8C-11CF-9BE8-00AA004B9986}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\dot
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {F07F3920-7B8C-11CF-9BE8-00AA004B9986}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\h
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\hhc
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {E0CA5340-4534-11CF-B952-00AA0051FE20}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\hpp
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\htm
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {E0CA5340-4534-11CF-B952-
00AA0051FE20}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\html
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {E0CA5340-4534-11CF-B952-
00AA0051FE20}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\htm
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {E0CA5340-4534-11CF-B952-
00AA0051FE20}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\htx
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {E0CA5340-4534-11CF-B952-
00AA0051FE20}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\hxx
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-
00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\ibq

Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-
00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\idl
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-
00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\inc
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-
00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\inf
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-
00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\ini
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-
00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\inx
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0

Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-
00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\js
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-
00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\log
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-
00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\m3u
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-
00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\mht
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-
00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\obd
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ

```

Data: {F07F3920-7B8C-11CF-9BE8-00AA004B9986}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\.obt
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {F07F3920-7B8C-11CF-9BE8-00AA004B9986}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\.odc
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {E0CA5340-4534-11CF-B952-00AA0051FE20}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\.pl
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\.pot
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {F07F3920-7B8C-11CF-9BE8-00AA004B9986}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\.ppt
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {F07F3920-7B8C-11CF-9BE8-00AA004B9986}

```

```

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\.rc
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\.reg
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\.rtf
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\.stm
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {E0CA5340-4534-11CF-B952-00AA0051FE20}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\.txt
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-00C04FB6EF4F}

```

```

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\.url
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\.vbs
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\.wtx
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\.xlb
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {F07F3920-7B8C-11CF-9BE8-00AA004B9986}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\.xlc
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {F07F3920-7B8C-11CF-9BE8-00AA004B9986}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Filters\.xls

```

Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {F07F3920-7B8C-11CF-9BE8-00AA004B9986}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters*.xlt
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {F07F3920-7B8C-11CF-9BE8-00AA004B9986}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters*.xml
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {41B9BE05-B3AF-460C-BF0B-2CDD44A093B1}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\CLSID
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\CLSID\{00020810-0000-0000-C000-000000000046}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {F07F3920-7B8C-11CF-9BE8-00AA004B9986}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\CLSID\{00020811-0000-0000-C000-000000000046}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {F07F3920-7B8C-11CF-9BE8-00AA004B9986}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\CLSID\{00020820-0000-0000-C000-000000000046}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {F07F3920-7B8C-11CF-9BE8-00AA004B9986}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\CLSID\{00020821-0000-0000-C000-000000000046}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {F07F3920-7B8C-11CF-9BE8-00AA004B9986}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\CLSID\{00020900-0000-0000-C000-000000000046}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {F07F3920-7B8C-11CF-9BE8-00AA004B9986}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\CLSID\{00020906-0000-0000-C000-000000000046}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {F07F3920-7B8C-11CF-9BE8-00AA004B9986}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\CLSID\{25336920-03F9-11CF-8FD0-00AA00686F13}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ

Data: {E0CA5340-4534-11CF-B952-00AA0051FE20}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\CLSID\{59850400-6664-101B-B21C-00AA004BA90B}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {F07F3920-7B8C-11CF-9BE8-00AA004B9986}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\CLSID\{5B941D80-BF96-11CD-B579-08002B30BFEB}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\CLSID\{64818D10-4F9B-11CF-86EA-00AA00B929E8}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {F07F3920-7B8C-11CF-9BE8-00AA004B9986}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\CLSID\{64818D11-4F9B-11CF-86EA-00AA00B929E8}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {F07F3920-7B8C-11CF-9BE8-00AA004B9986}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\CLSID\{7F73B8F6-C19C-11D0-AA66-00C04FC2EDDC}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0

Name: <NO NAME>
Type: REG_SZ
Data: {E0CA5340-4534-11CF-B952-00AA0051FE20}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\CLSID\{87DB1ADA-AA39-11D1-829F-00A0C906B239}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\CLSID\{89BCB7A4-6119-101A-BCB7-00DD010655AF}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\CLSID\{8C9E8E1C-90F0-11D1-BA0F-00A0C906B239}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\CLSID\{95876EB0-90F0-11D1-BA0F-00A0C906B239}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\CLSID\{961C1130-89AD-11CF-88A1-00AA004B9986}
Class Name: <NO CLASS>

Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\CLSID\{9ED4692C-90F0-11D1-BA0F-00A0C906B239}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {C7310720-AC80-11D1-8DF3-00C04FB6EF4F}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\CLSID\{BD70C020-2D24-11D0-9110-00004C752752}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {E0CA5340-4534-11CF-B952-00AA0051FE20}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Filters\CLSID\{EA7BAE70-FB3B-11CD-A903-00AA00510EA3}
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: <NO NAME>
Type: REG_SZ
Data: {F07F3920-7B8C-11CF-9BE8-00AA004B9986}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\GlobalAdminBlob
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: Blob0
Type: REG_BINARY
Data:
00000000 00 00 00 80 60 02 00 00 - 05 00 15 00 46
00 54 00F.T.
00000010 45 00 5f 00 52 00 65 00 - 74 00 61 00 69
00 6c 00 E_.R.e.t.a.i.l.
00000020 54 00 72 00 61 00 63 00 - 69 00 6e 00 67
00 50 00 T.r.a.c.i.n.g.P.

00000030 61 00 74 00 68 00 00 00 - 08 00 37 00 43
00 3a 00 a.t.h.....7.C.:.
00000040 5c 00 50 00 72 00 6f 00 - 67 00 72 00 61
00 6d 00 \.P.r.o.g.r.a.m.
00000050 20 00 46 00 69 00 6c 00 - 65 00 73 00 5c
00 4d 00 .F.i.l.l.e.s.\.M.
00000060 69 00 63 00 72 00 6f 00 - 73 00 6f 00 66
00 74 00 i.c.r.o.s.o.f.t.
00000070 20 00 53 00 51 00 4c 00 - 20 00 53 00 65
00 72 00 .S.Q.L. .S.e.r.
00000080 76 00 65 00 72 00 5c 00 - 4d 00 53 00 53
00 51 00 v.e.r.\.M.S.S.Q.
00000090 4c 00 2e 00 31 00 5c 00 - 4d 00 53 00 53
00 51 00 L...l.\.M.S.S.Q.
000000a0 4c 00 5c 00 4c 00 4f 00 - 47 00 00 00 14
00 46 00 L.\.L.O.G....F.
000000b0 54 00 45 00 5f 00 53 00 - 51 00 4c 00 44
00 75 00 T.E...S.Q.L.D.u.
000000c0 6d 00 70 00 65 00 72 00 - 44 00 75 00 6d
00 70 00 m.p.e.r.D.u.m.p.
000000d0 44 00 69 00 72 00 00 00 - 08 00 37 00 43
00 3a 00 D.i.r.....7.C.:.
000000e0 5c 00 50 00 72 00 6f 00 - 67 00 72 00 61
00 6d 00 \.P.r.o.g.r.a.m.
000000f0 20 00 46 00 69 00 6c 00 - 65 00 73 00 5c
00 4d 00 .F.i.l.l.e.s.\.M.
00000100 69 00 63 00 72 00 6f 00 - 73 00 6f 00 66
00 74 00 i.c.r.o.s.o.f.t.
00000110 20 00 53 00 51 00 4c 00 - 20 00 53 00 65
00 72 00 .S.Q.L. .S.e.r.
00000120 76 00 65 00 72 00 5c 00 - 4d 00 53 00 53
00 51 00 v.e.r.\.M.S.S.Q.
00000130 4c 00 2e 00 31 00 5c 00 - 4d 00 53 00 53
00 51 00 L...l.\.M.S.S.Q.
00000140 4c 00 5c 00 4c 00 4f 00 - 47 00 00 00 12
00 46 00 L.\.L.O.G....F.
00000150 54 00 45 00 5f 00 53 00 - 51 00 4c 00 44
00 75 00 T.E...S.Q.L.D.u.
00000160 6d 00 70 00 65 00 72 00 - 46 00 6c 00 61
00 67 00 m.p.e.r.F.l.a.g.
00000170 73 00 00 00 08 00 06 00 - 30 00 78 00 30
00 38 00 s.....0.x.0.8.
00000180 30 00 30 00 00 00 15 00 - 46 00 54 00 45
00 5f 00 0.0....F.T.E..
00000190 53 00 51 00 4c 00 44 00 - 75 00 6d 00 70
00 65 00 S.Q.L.D.u.m.p.e.
000001a0 72 00 46 00 75 00 6c 00 - 6c 00 50 00 61
00 74 00 r.F.u.l.l.P.a.t.
000001b0 68 00 00 00 08 00 3d 00 - 43 00 3a 00 5c
00 50 00 h.....C.:.\.P.
000001c0 72 00 6f 00 67 00 72 00 - 61 00 6d 00 20
00 46 00 r.o.g.r.a.m. .F.
000001d0 69 00 6c 00 65 00 73 00 - 5c 00 4d 00 69
00 63 00 i.l.l.e.s.\.M.i.c.
000001e0 72 00 6f 00 73 00 6f 00 - 66 00 74 00 20
00 53 00 r.o.s.o.f.t. .S.
000001f0 51 00 4c 00 20 00 53 00 - 65 00 72 00 76
00 65 00 Q.L. .S.e.r.v.e.
00000200 72 00 5c 00 39 00 30 00 - 5c 00 53 00 68
00 61 00 r.\.9.0.\.S.h.a.
00000210 72 00 65 00 64 00 5c 00 - 73 00 71 00 6c
00 64 00 r.e.d.\.s.g.l.d.

00000220 75 00 6d 00 70 00 65 00 - 72 00 2e 00 65
00 78 00 u.m.p.e.r...e.x.
00000230 65 00 00 00 11 00 46 00 - 54 00 45 00 5f
00 45 00 e....P.T.E...E.
00000240 72 00 72 00 6f 00 72 00 - 43 00 6f 00 75
00 6e 00 r.r.o.r.C.o.u.n.
00000250 74 00 4d 00 61 00 78 00 - 00 00 13 00 00
00 00 00 t.M.a.x.....

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Language
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Language\chs
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: NoiseFile
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL
Server\MSSQL.1\MSSQL\FTData\noisechs.txt

Value 1
Name: TaurusFile
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL
Server\MSSQL.1\MSSQL\FTData\tschs.xml

Value 2
Name: Locale
Type: REG_DWORD
Data: 0x804

Value 3
Name: WBreakerClass
Type: REG_SZ
Data: {12CE94A0-DEFB-11D2-B31D-
00600893A857}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Language\cht
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: NoiseFile
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL
Server\MSSQL.1\MSSQL\FTData\noisecht.txt

Value 1
Name: TaurusFile
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL
Server\MSSQL.1\MSSQL\FTData\tscht.xml

Value 2
Name: Locale
Type: REG_DWORD
Data: 0x404

Value 3
Name: WBreakerClass
Type: REG_SZ
Data: {1680E7C3-9430-4A51-9B82-
1E7E7ABE5258}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Language\deu
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM

Value 0
Name: NoiseFile
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL
Server\MSSQL.1\MSSQL\FTData\noiseu.txt

Value 1
Name: TaurusFile
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL
Server\MSSQL.1\MSSQL\FTData\tsdeu.xml

Value 2
Name: Locale
Type: REG_DWORD
Data: 0x407

Value 3
Name: WBreakerClass
Type: REG_SZ
Data: {9EA69E16-AD5E-43ED-B90E-
73D58771D3F6}

Value 4
Name: StemmerClass
Type: REG_SZ
Data: {6DE705A5-6467-43DC-9CE3-
CCFE08B3F645}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Language\eng
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM

Value 0
Name: NoiseFile
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL
Server\MSSQL.1\MSSQL\FTData\noiseeng.txt

Value 1
Name: TaurusFile
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL
Server\MSSQL.1\MSSQL\FTData\tseng.xml

Value 2
Name: StemmerClass
Type: REG_SZ
Data: {D99F7670-7F1A-11CE-BE57-
00AA0051FE20}

Value 3
Name: Locale
Type: REG_DWORD
Data: 0x809

Value 4
Name: WBreakerClass
Type: REG_SZ
Data: {173C97E2-AEBE-437C-9445-
01B237ABF2F6}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Language\enu
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM

Value 0
Name: NoiseFile
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL
Server\MSSQL.1\MSSQL\FTData\noiseenu.txt

Value 1
Name: TaurusFile
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL
Server\MSSQL.1\MSSQL\FTData\tsenu.xml

Value 2
Name: StemmerClass
Type: REG_SZ
Data: {EEED4C20-7F1B-11CE-BE57-
00AA0051FE20}

Value 3
Name: Locale
Type: REG_DWORD
Data: 0x409

Value 4
Name: WBreakerClass
Type: REG_SZ
Data: {188D6CC5-CB03-4C01-912E-
47D21295D77E}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\MSSQL.1\MSSearch\Language\esn
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM

Value 0
Name: NoiseFile
Type: REG_SZ

Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\FTData\noiseesn.txt

Value 1
Name: TsaurusFile
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\FTData\tsesn.xml

Value 2
Name: StemmerClass
Type: REG_SZ
Data: {B0516FF0-7F1C-11CE-BE57-00AA0051FE20}

Value 3
Name: Locale
Type: REG_DWORD
Data: 0xc0a

Value 4
Name: WBreakerClass
Type: REG_SZ
Data: {73D009FB-7D05-45AC-94C2-EDD1029942D4}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Language\fra
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: NoiseFile
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\FTData\noisefra.txt

Value 1
Name: TsaurusFile
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\FTData\tsfra.xml

Value 2
Name: StemmerClass
Type: REG_SZ
Data: {2A6EB050-7F1C-11CE-BE57-00AA0051FE20}

Value 3
Name: Locale
Type: REG_DWORD
Data: 0x40c

Value 4
Name: WBreakerClass
Type: REG_SZ
Data: {95679344-48B8-42CD-9B79-2F5784D70258}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Language\ita
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0

Name: NoiseFile
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\FTData\noiseita.txt

Value 1
Name: TsaurusFile
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\FTData\tsitaxml

Value 2
Name: Locale
Type: REG_DWORD
Data: 0x410

Value 3
Name: WBreakerClass
Type: REG_SZ
Data: {FD86B5D0-12C6-11CE-BD31-00AA004BBB1F}

Value 4
Name: StemmerClass
Type: REG_SZ
Data: {6D36CE10-7F1C-11CE-BE57-00AA0051FE20}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Language\jpn
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: NoiseFile
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\FTData\noisejpn.txt

Value 1
Name: TsaurusFile
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\FTData\tsjpn.xml

Value 2
Name: Locale
Type: REG_DWORD
Data: 0x411

Value 3
Name: WBreakerClass
Type: REG_SZ
Data: {A9FFAE02-D834-47B3-8434-0D75DC0804BD}

Value 4
Name: StemmerClass
Type: REG_SZ
Data: {1305C72E-2073-452E-A72D-667032B3B4FE}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Language\kor
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: NoiseFile
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\FTData\noisekor.txt

Value 1
Name: TsaurusFile
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\FTData\tskor.xml

Value 2
Name: Locale
Type: REG_DWORD
Data: 0x412

Value 3
Name: WBreakerClass
Type: REG_SZ
Data: {737FC9B5-BC66-4953-B7DB-B79A72A592A5}

Value 4
Name: StemmerClass
Type: REG_SZ
Data: {97E8EFC5-42DA-43ED-9CEC-84FDE3620F1A}

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Language\Neutral
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: NoiseFile
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\FTData\noiseneu.txt

Value 1
Name: TsaurusFile
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\FTData\tsglobal.xml

Value 2
Name: Locale
Type: REG_DWORD
Data: 0

Value 3
 Name: WBreakerClass
 Type: REG_SZ
 Data: {C731071F-AC80-11D1-8DF3-00C04FB6EF4F}

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Language\nld
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Value 0
 Name: NoiseFile
 Type: REG_SZ
 Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\FTData\noisnld.txt

Value 1
 Name: TsaursFile
 Type: REG_SZ
 Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\FTData\tsnld.xml

Value 2
 Name: Locale
 Type: REG_DWORD
 Data: 0x413

Value 3
 Name: WBreakerClass
 Type: REG_SZ
 Data: {66B37110-8BF2-11CE-BE59-00AA0051FE20}

Value 4
 Name: StemmerClass
 Type: REG_SZ
 Data: {860D28D0-8BF4-11CE-BE59-00AA0051FE20}

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Language\svs
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Value 0
 Name: NoiseFile
 Type: REG_SZ
 Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\FTData\noisevs.txt

Value 1
 Name: TsaursFile
 Type: REG_SZ
 Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\FTData\tssve.xml

Value 2
 Name: Locale
 Type: REG_DWORD

Data: 0x41d

Value 3
 Name: WBreakerClass
 Type: REG_SZ
 Data: {01C6B350-12C7-11CE-BD31-00AA004BBB1F}

Value 4
 Name: StemmerClass
 Type: REG_SZ
 Data: {9478F640-7F1C-11CE-BE57-00AA0051FE20}

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Language\tha
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Value 0
 Name: NoiseFile
 Type: REG_SZ
 Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\FTData\noisehta.txt

Value 1
 Name: TsaursFile
 Type: REG_SZ
 Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\FTData\tstha.xml

Value 2
 Name: Locale
 Type: REG_DWORD
 Data: 0x41e

Value 3
 Name: WBreakerClass
 Type: REG_SZ
 Data: {CCA22CF4-59FE-11D1-BBFF-00C04FB97FDA}

Value 4
 Name: StemmerClass
 Type: REG_SZ
 Data: {CEDC01C7-59FE-11D1-BBFF-00C04FB97FDA}

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Language\zh-hk
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Value 0
 Name: NoiseFile
 Type: REG_SZ
 Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\FTData\noisecht.txt

Value 1
 Name: TsaursFile

Type: REG_SZ
 Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\FTData\tscht.xml

Value 2
 Name: Locale
 Type: REG_DWORD
 Data: 0xc04

Value 3
 Name: WBreakerClass
 Type: REG_SZ
 Data: {1680E7C3-9430-4A51-9B82-1E7E7AEE5258}

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Language\zh-mo
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Value 0
 Name: NoiseFile
 Type: REG_SZ
 Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\FTData\noisecht.txt

Value 1
 Name: TsaursFile
 Type: REG_SZ
 Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\FTData\tscht.xml

Value 2
 Name: Locale
 Type: REG_DWORD
 Data: 0x1404

Value 3
 Name: WBreakerClass
 Type: REG_SZ
 Data: {1680E7C3-9430-4A51-9B82-1E7E7AEE5258}

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Language\zh-sg
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Value 0
 Name: NoiseFile
 Type: REG_SZ
 Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\FTData\noisechs.txt

Value 1
 Name: TsaursFile
 Type: REG_SZ
 Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\FTData\tschs.xml

Value 2

Name: Locale
 Type: REG_DWORD
 Data: 0x1004

Value 3
 Name: WBreakerClass
 Type: REG_SZ
 Data: {12CE94A0-DEFB-11D2-B31D-00600893A857}

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Plugins
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSearch\Plugins\MicrosoftIndexer
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Value 0
 Name: <NO NAME>
 Type: REG_SZ
 Data: {68C6D24E-77E0-11D5-8528-00C04F68155C}

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSQLServer
 Class Name: <NO CLASS>
 Last Write Time: 9/29/2005 - 11:51 AM

Value 0
 Name: AuditLevel
 Type: REG_DWORD
 Data: 0x2

Value 1
 Name: DebugClassID
 Type: REG_SZ
 Data: {4E488723-3831-4DC0-9F24-800D0E42BC48}

Value 2
 Name: DefaultLogin
 Type: REG_SZ
 Data: guest

Value 3
 Name: LoginMode
 Type: REG_DWORD
 Data: 0x2

Value 4
 Name: Map_
 Type: REG_SZ
 Data: \

Value 5
 Name: Map#
 Type: REG_SZ

Data: -

Value 6
 Name: Map\$
 Type: REG_SZ
 Data:

Value 7
 Name: SetHostName
 Type: REG_DWORD
 Data: 0

Value 8
 Name: Tapeloadwaittime
 Type: REG_DWORD
 Data: 0xffffffff

Value 9
 Name: BackupDirectory
 Type: REG_SZ
 Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\Backup

Value 10
 Name: SysDb
 Type: REG_DWORD
 Data: 0x1

Value 11
 Name: FullTextDefaultPath
 Type: REG_SZ
 Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\FTData

Value 12
 Name: uptime_pid
 Type: REG_DWORD
 Data: 0x568

Value 13
 Name: uptime_time_utc
 Type: REG_BINARY
 Data: fe 13 7c 1a 16 c5 c5 01 -
 p. |..ÅÅ.

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSQLServer\CurrentVersion
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Value 0
 Name: Language
 Type: REG_DWORD
 Data: 0x409

Value 1
 Name: CurrentVersion
 Type: REG_SZ
 Data: 9.00.1314.06

Value 2

Name: RegisteredOwner
 Type: REG_SZ
 Data:

Value 3
 Name: SerialNumber
 Type: REG_SZ
 Data:

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSQLServer\Parameters
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Value 0
 Name: SQLArg0
 Type: REG_SZ
 Data: -dC:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\DATA\master.mdf

Value 1
 Name: SQLArg1
 Type: REG_SZ
 Data: -eC:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\LOG\ERRORLOG

Value 2
 Name: SQLArg2
 Type: REG_SZ
 Data: -lC:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\DATA\mastlog.ldf

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSQLServer\SuperSocketNetLib
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Value 0
 Name: ForceEncryption
 Type: REG_DWORD
 Data: 0

Value 1
 Name: HideInstance
 Type: REG_DWORD
 Data: 0

Value 2
 Name: Certificate
 Type: REG_SZ
 Data:

Value 3
 Name: DisplayName
 Type: REG_SZ
 Data: SQL Server Network Configuration

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL

Server\MSSQL.1\MSSQLServer\SuperSocketNetLib\AdminCon
 nection
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM
 Value 0
 Name: DisplayName
 Type: REG_SZ
 Data: Dedicated Administrative
 Connection

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
 Server\MSSQL.1\MSSQLServer\SuperSocketNetLib\AdminCon
 nection\Tcp
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM
 Value 0
 Name: TcpDynamicPorts
 Type: REG_SZ
 Data: 1434

Value 1
 Name: DisplayName
 Type: REG_SZ
 Data: TCP/IP

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
 Server\MSSQL.1\MSSQLServer\SuperSocketNetLib\Np
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM
 Value 0
 Name: Enabled
 Type: REG_DWORD
 Data: 0

Value 1
 Name: PipeName
 Type: REG_SZ
 Data: \\.\pipe\sql\query

Value 2
 Name: DisplayName
 Type: REG_SZ
 Data: Named Pipes

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
 Server\MSSQL.1\MSSQLServer\SuperSocketNetLib\Sm
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM
 Value 0
 Name: Enabled
 Type: REG_DWORD
 Data: 0x1

Value 1
 Name: DisplayName
 Type: REG_SZ
 Data: Shared Memory

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
 Server\MSSQL.1\MSSQLServer\SuperSocketNetLib\Tcp
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM
 Value 0
 Name: Enabled
 Type: REG_DWORD
 Data: 0x1

Value 1
 Name: ListenOnAllIPs
 Type: REG_DWORD
 Data: 0x1

Value 2
 Name: NoDelay
 Type: REG_DWORD
 Data: 0

Value 3
 Name: KeepAlive
 Type: REG_DWORD
 Data: 0x7530

Value 4
 Name: DisplayName
 Type: REG_SZ
 Data: TCP/IP

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
 Server\MSSQL.1\MSSQLServer\SuperSocketNetLib\Tcp\IP1
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM
 Value 0
 Name: Enabled
 Type: REG_DWORD
 Data: 0

Value 1
 Name: Active
 Type: REG_DWORD
 Data: 0x1

Value 2
 Name: TcpPort
 Type: REG_SZ
 Data: 1433

Value 3
 Name: TcpDynamicPorts
 Type: REG_SZ
 Data:

Value 4
 Name: DisplayName
 Type: REG_SZ
 Data: Specific IP Address

Value 5
 Name: IpAddress
 Type: REG_SZ
 Data: 130.120.208.14

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
 Server\MSSQL.1\MSSQLServer\SuperSocketNetLib\Tcp\IP2
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM
 Value 0
 Name: Enabled
 Type: REG_DWORD
 Data: 0

Value 1
 Name: Active
 Type: REG_DWORD
 Data: 0x1

Value 2
 Name: TcpPort
 Type: REG_SZ
 Data: 1433

Value 3
 Name: TcpDynamicPorts
 Type: REG_SZ
 Data:

Value 4
 Name: DisplayName
 Type: REG_SZ
 Data: Specific IP Address

Value 5
 Name: IpAddress
 Type: REG_SZ
 Data: 130.168.208.14

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
 Server\MSSQL.1\MSSQLServer\SuperSocketNetLib\Tcp\IP3
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM
 Value 0
 Name: Enabled
 Type: REG_DWORD
 Data: 0

Value 1
 Name: Active
 Type: REG_DWORD
 Data: 0x1

Value 2
 Name: TcpPort
 Type: REG_SZ
 Data: 1433

Value 3

Name: TcpDynamicPorts
 Type: REG_SZ
 Data:

Value 4
 Name: DisplayName
 Type: REG_SZ
 Data: Specific IP Address

Value 5
 Name: IpAddress
 Type: REG_SZ
 Data: 127.0.0.1

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSQLServer\SuperSocketNetLib\Tcp\IPAL1
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 9:12 PM
 Value 0
 Name: TcpPort
 Type: REG_SZ
 Data: 2001,2002,2003,2004,2005,2006,2007,2008

Value 1
 Name: TcpDynamicPorts
 Type: REG_SZ
 Data:

Value 2
 Name: DisplayName
 Type: REG_SZ
 Data: Any IP Address

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\MSSQLServer\SuperSocketNetLib\Via
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM
 Value 0
 Name: Enabled
 Type: REG_DWORD
 Data: 0

Value 1
 Name: DefaultServerPort
 Type: REG_SZ
 Data: 0:1433

Value 2
 Name: ListenInfo
 Type: REG_SZ
 Data: 0:1433

Value 3
 Name: DisplayName
 Type: REG_SZ
 Data: VIA

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\Providers
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM
 Value 0
 Name: AllowInProcess
 Type: REG_DWORD
 Data: 0x1

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\Providers\ADSDSOObject
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM
 Value 0
 Name: AllowInProcess
 Type: REG_DWORD
 Data: 0x1

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\Providers\DBOLEDB
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM
 Value 0
 Name: AllowInProcess
 Type: REG_DWORD
 Data: 0x1

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\Providers\Microsoft.Jet.OLEDB.4.0
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM
 Value 0
 Name: AllowInProcess
 Type: REG_DWORD
 Data: 0x1

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\Providers\MSDAORA
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM
 Value 0
 Name: AllowInProcess
 Type: REG_DWORD
 Data: 0x1

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\Providers\MSDASQL
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM
 Value 0
 Name: AllowInProcess
 Type: REG_DWORD
 Data: 0x1

Type: REG_DWORD
 Data: 0x1

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\Providers\MSIDXS
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM
 Value 0
 Name: AllowInProcess
 Type: REG_DWORD
 Data: 0x1

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\Providers\MSQLImpProv
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM
 Value 0
 Name: AllowInProcess
 Type: REG_DWORD
 Data: 0x1

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\Providers\MSSEARCHSQL
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM
 Value 0
 Name: AllowInProcess
 Type: REG_DWORD
 Data: 0x1

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\Providers\SQLNCLI
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM
 Value 0
 Name: AllowInProcess
 Type: REG_DWORD
 Data: 0x1

Value 1
 Name: DisallowAdhocAccess
 Type: REG_DWORD
 Data: 0

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\Replication
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM
 Value 0
 Name: IsInstalled
 Type: REG_DWORD
 Data: 0x1

Value 1
 Name: DistributionDB
 Type: REG_SZ
 Data:

Value 2
 Name: WorkingDirectory
 Type: REG_SZ
 Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\REPLDATA

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\Security
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\Setup
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Value 0
 Name: AGTGroup
 Type: REG_SZ
 Data: S-1-5-21-2508075538-524758343-2297538768-1025

Value 1
 Name: SQLGroup
 Type: REG_SZ
 Data: S-1-5-21-2508075538-524758343-2297538768-1026

Value 2
 Name: FTSGroup
 Type: REG_SZ
 Data: S-1-5-21-2508075538-524758343-2297538768-1027

Value 3
 Name: Version
 Type: REG_SZ
 Data: 9.00.1314.06

Value 4
 Name: Language
 Type: REG_DWORD
 Data: 0x409

Value 5
 Name: Resume
 Type: REG_DWORD
 Data: 0

Value 6
 Name: ProductCode
 Type: REG_SZ
 Data: {79F1B65E-8FC0-4D03-954D-F9E71C85AEC7}

Value 7

Name: SqlProgramDir
 Type: REG_SZ
 Data: C:\Program Files\Microsoft SQL Server\

Value 8
 Name: checksum
 Type: REG_BINARY
 Data:
 00000000 38 37 33 66 66 66 30 65 - 62 38 32 62 30
 34 37 62 873fff0eb82b047b
 00000010 31 30 35 31 36 38 32 31 - 30 30 63 66 30
 37 64 37 1051682100cf07d7
 00000020 35 37 33 32 64 39 64 63 - 34 34 33 33 30
 66 62 66 5732d9dc44330fbf
 00000030 64 66 61 64 66 63 66 35 - 62 37 30 36 34
 65 36 61 dfadfcf5b7064e6a
 00000040 66 66 39 32 38 63 63 34 - 61 30 35 37 31
 33 39 33 ff928cc4a0571393
 00000050 37 64 32 32 31 36 37 38 - 37 62 36 66 39
 62 64 61 7d2216787b6f9bda
 00000060 34 30 35 35 62 34 30 30 - 65 32 30 34 33
 64 37 63 4055b400e2043d7c
 00000070 66 63 32 30 32 35 33 33 - 32 31 36 36 34
 66 37 39 fc20253321664f79
 00000080 32 64 62 66 64 31 36 35 - 61 33 32 38 36
 61 65 37 2dbfd165a3286ae7
 00000090 65 36 61 36 62 66 32 62 - 66 64 63 34 36
 38 35 64 e6a6bf2bdc4685d
 000000a0 64 30 31 62 64 34 39 61 - 62 39 34 35 64
 39 66 38 d01bd49ab945d9f8
 00

Value 9
 Name: Edition
 Type: REG_SZ
 Data: Enterprise Edition (64-bit)

Value 10
 Name: SqlCluster
 Type: REG_DWORD
 Data: 0

Value 11
 Name: FeatureList
 Type: REG_SZ
 Data: SQL_Engine=3 SQL_Data_Files=3
 SQL_Replication=3 SQL_FullText=3 SQL_SharedTools=3
 SQL_BC_DEP=3

Value 12
 Name: PatchLevel
 Type: REG_SZ
 Data: 9.00.1314.06

Value 13
 Name: Collation
 Type: REG_SZ
 Data: Latin1_General_BIN

Value 14
 Name: FirstStart
 Type: REG_DWORD

Data: 0

Value 15
 Name: SQLDataRoot
 Type: REG_SZ
 Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL

Value 16
 Name: SQLPath
 Type: REG_SZ
 Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL

Value 17
 Name: SQLBinRoot
 Type: REG_SZ
 Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\Binn

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\SQLServerAgent
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Value 0
 Name: JobHistoryMaxRowsPerJob
 Type: REG_DWORD
 Data: 0x64

Value 1
 Name: SysAdminOnly
 Type: REG_DWORD
 Data: 0x1

Value 2
 Name: DownloadedMaxRows
 Type: REG_DWORD
 Data: 0x64

Value 3
 Name: ErrorLogFile
 Type: REG_SZ
 Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\LOG\SQLAGENT.OUT

Value 4
 Name: ErrorLoggingLevel
 Type: REG_DWORD
 Data: 0x3

Value 5
 Name: JobHistoryMaxRows
 Type: REG_DWORD
 Data: 0x3e8

Value 6
 Name: MSXServerName
 Type: REG_SZ
 Data:

Value 7

Name: NonAlertableErrors
 Type: REG_SZ
 Data: 1204,4002

Value 8
 Name: RestartServer
 Type: REG_DWORD
 Data: 0x1

Value 9
 Name: ServerHost
 Type: REG_SZ
 Data:

Value 10
 Name: WorkingDirectory
 Type: REG_SZ
 Data: C:\Program Files\Microsoft SQL Server\MSSQL.1\MSSQL\JOBS\

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\MSSQL.1\SQLServerSCP
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\Services
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\Services\Analysis Server
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Value 0
 Name: Name
 Type: REG_SZ
 Data: MSSQLServerOLAPService

Value 1
 Name: LName
 Type: REG_SZ
 Data: MSOLAP\$

Value 2
 Name: Type
 Type: REG_DWORD
 Data: 0x5

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\Services\Full Text
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Value 0
 Name: LName
 Type: REG_SZ
 Data: msftesql\$

Value 1
 Name: Name
 Type: REG_SZ
 Data: msftesql

Value 2
 Name: Type
 Type: REG_DWORD
 Data: 0x3

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\Services\Notification Services
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Value 0
 Name: LName
 Type: REG_SZ
 Data: NS\$

Value 1
 Name: Name
 Type: REG_SZ
 Data: NsService

Value 2
 Name: Type
 Type: REG_DWORD
 Data: 0x8

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\Services\Report Server
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Value 0
 Name: Name
 Type: REG_SZ
 Data: ReportServer

Value 1
 Name: LName
 Type: REG_SZ
 Data: ReportServer\$

Value 2
 Name: Type
 Type: REG_DWORD
 Data: 0x6

Value 3
 Name: GroupPrefix
 Type: REG_SZ
 Data: SQLServer2005ReportServerUser\$BOBCAT\$

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\Services\ReportServer

Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Value 0
 Name: LName
 Type: REG_SZ
 Data: ReportServer\$

Value 1
 Name: Name
 Type: REG_SZ
 Data: ReportServer

Value 2
 Name: Type
 Type: REG_DWORD
 Data: 0x6

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\Services\SQL Agent
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Value 0
 Name: Name
 Type: REG_SZ
 Data: SQLSERVERAGENT

Value 1
 Name: LName
 Type: REG_SZ
 Data: SQLAgent\$

Value 2
 Name: Type
 Type: REG_DWORD
 Data: 0x2

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\Services\SQL Browser
 Class Name: <NO CLASS>
 Last Write Time: 9/15/2005 - 8:51 PM

Value 0
 Name: LName
 Type: REG_SZ
 Data:

Value 1
 Name: Name
 Type: REG_SZ
 Data: SQLBrowser

Value 2
 Name: Type
 Type: REG_DWORD
 Data: 0x7

Key Name:
 HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL Server\Services\SQL Server


```

Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
  Name: Name
  Type: REG_SZ
  Data: MSSQLServer

Value 1
  Name: LName
  Type: REG_SZ
  Data: MSSQL$

Value 2
  Name: Type
  Type: REG_DWORD
  Data: 0x1

```

```

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\Services\SSIS Server
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
  Name: GroupPrefix
  Type: REG_SZ
  Data: SQLServer2005DTSUser$BOBCAT

```

```

Value 1
  Name: LName
  Type: REG_SZ
  Data:

```

```

Value 2
  Name: Name
  Type: REG_SZ
  Data: MsDtsServer

```

```

Value 3
  Name: Type
  Type: REG_DWORD
  Data: 0x4

```

```

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\SQLXML4
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:52 PM

```

```

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\SQLXML4\CurrentVersion
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:52 PM
Value 0
  Name: Version
  Type: REG_SZ
  Data: 9.00.1314.06

```

```

Key Name:
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Microsoft SQL
Server\SQLXML4\MSIRefCount
Class Name: <NO CLASS>
Last Write Time: 9/15/2005 - 8:52 PM
Value 0
  Name: Uninstall
  Type: REG_SZ
  Data: {11111111-1111-1111-1111-
111111111111},{73D8B59D-0BFF-4B5B-A031-FAB3AC629E56}

```

Server Bus Performance Driver Registry Parameters

```

Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
hpgcissb
Class Name: <NO CLASS>
Last Write Time: 9/26/2005 - 10:13 AM
Value 0
  Name: Type
  Type: REG_DWORD
  Data: 0x1

```

```

Value 1
  Name: Start
  Type: REG_DWORD
  Data: 0

```

```

Value 2
  Name: ErrorControl
  Type: REG_DWORD
  Data: 0x1

```

```

Value 3
  Name: Tag
  Type: REG_DWORD
  Data: 0x102

```

```

Value 4
  Name: ImagePath
  Type: REG_EXPAND_SZ
  Data: system32\DRIVERS\hpgcissb.sys

```

```

Value 5
  Name: DisplayName
  Type: REG_SZ
  Data: Smart Array Controllers Non-
Miniport Bus Driver

```

```

Value 6
  Name: Group
  Type: REG_SZ

```

```
Data: port
```

```

Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
hpgcissb\Parameters
Class Name: <NO CLASS>
Last Write Time: 9/13/2005 - 10:34 AM
Value 0
  Name: CompletionMode
  Type: REG_DWORD
  Data: 0x2

```

```

Value 1
  Name: CosTimerRate
  Type: REG_DWORD
  Data: 0x2

```

```

Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
hpgcissb\Parameters\Controller8
Class Name: <NO CLASS>
Last Write Time: 7/20/2005 - 4:44 PM
Value 0
  Name: CompletionMode
  Type: REG_DWORD
  Data: 0x1

```

```

Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
hpgcissb\Security
Class Name: <NO CLASS>
Last Write Time: 7/18/2005 - 4:23 PM
Value 0
  Name: Security
  Type: REG_BINARY
  Data:

```

```

00000000 01 00 14 80 b8 00 00 00 - c4 00 00 00 14
00 00 00 .....Ä.....
00000010 30 00 00 00 02 00 1c 00 - 01 00 00 00 02
80 14 00 0.....
00000020 ff 01 0f 00 01 01 00 00 - 00 00 00 01 00
00 00 00 Ÿ.....
00000030 02 00 88 00 06 00 00 00 - 00 00 14 00 fd
01 02 00 .....Ÿ...
00000040 01 01 00 00 00 00 05 - 12 00 00 00 00
00 18 00 .....
00000050 ff 01 0f 00 01 02 00 00 - 00 00 00 05 20
00 00 00 Ÿ.....
00000060 20 02 00 00 00 00 14 00 - 8d 01 02 00 01
01 00 00 .....
00000070 00 00 00 05 04 00 00 00 - 00 00 14 00 8d
01 02 00 .....
00000080 01 01 00 00 00 00 05 - 06 00 00 00 00
00 14 00 .....
00000090 00 01 00 00 01 01 00 00 - 00 00 00 05 0b
00 00 00 .....
000000a0 00 00 18 00 fd 01 02 00 - 01 02 00 00 00
00 00 05 ...Ÿ.....
000000b0 20 00 00 00 23 02 00 00 - 01 01 00 00 00
00 00 05 ...#.....

```

000000c0 12 00 00 00 01 01 00 00 - 00 00 00 05 12
00 00 00

Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
hpgcissb\Enum
Class Name: <NO CLASS>
Last Write Time: 9/26/2005 - 10:13 AM
Value 0
Name: 0
Type: REG_SZ
Data:
PCI\VEN_0E11&DEV_0046&SUBSYS_409C0E11&REV_01\5&2c344c
1f&0&203840

Value 1
Name: Count
Type: REG_DWORD
Data: 0xf

Value 2
Name: NextInstance
Type: REG_DWORD
Data: 0xf

Value 3
Name: 1
Type: REG_SZ
Data:
PCI\VEN_0E11&DEV_0046&SUBSYS_409D0E11&REV_01\5&2c344c
1f&0&283840

Value 4
Name: 2
Type: REG_SZ
Data:
PCI\VEN_0E11&DEV_0046&SUBSYS_409C0E11&REV_01\5&2363b0
a8&0&204040

Value 5
Name: 3
Type: REG_SZ
Data:
PCI\VEN_0E11&DEV_0046&SUBSYS_409D0E11&REV_01\5&2363b0
a8&0&284040

Value 6
Name: 4
Type: REG_SZ
Data:
PCI\VEN_0E11&DEV_0046&SUBSYS_409C0E11&REV_01\5&56dd26
4&0&206848

Value 7
Name: 5
Type: REG_SZ
Data:
PCI\VEN_0E11&DEV_0046&SUBSYS_409D0E11&REV_01\5&56dd26
4&0&286848

Value 8

Name: 6
Type: REG_SZ
Data:
PCI\VEN_0E11&DEV_0046&SUBSYS_409C0E11&REV_01\5&259980
46&0&207050

Value 9
Name: 7
Type: REG_SZ
Data:
PCI\VEN_0E11&DEV_0046&SUBSYS_409D0E11&REV_01\5&259980
46&0&287050

Value 10
Name: 8
Type: REG_SZ
Data:
PCI\VEN_0E11&DEV_0046&SUBSYS_409B0E11&REV_01\4&2534a5
7b&0&5058

Value 11
Name: 9
Type: REG_SZ
Data:
PCI\VEN_0E11&DEV_0046&SUBSYS_409C0E11&REV_01\5&1b3a30
7e&0&204858

Value 12
Name: 10
Type: REG_SZ
Data:
PCI\VEN_0E11&DEV_0046&SUBSYS_409D0E11&REV_01\5&1b3a30
7e&0&284858

Value 13
Name: 11
Type: REG_SZ
Data:
PCI\VEN_0E11&DEV_0046&SUBSYS_409C0E11&REV_01\5&30fce3
fc&0&205860

Value 14
Name: 12
Type: REG_SZ
Data:
PCI\VEN_0E11&DEV_0046&SUBSYS_409D0E11&REV_01\5&30fce3
fc&0&285860

Value 15
Name: 13
Type: REG_SZ
Data:
PCI\VEN_0E11&DEV_0046&SUBSYS_409C0E11&REV_01\5&282c48
85&0&206060

Value 16
Name: 14
Type: REG_SZ
Data:
PCI\VEN_0E11&DEV_0046&SUBSYS_409D0E11&REV_01\5&282c48
85&0&286060

Server Disk Device Performance Driver Registry Parameters

Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
hpgcissd
Class Name: <NO CLASS>
Last Write Time: 9/26/2005 - 10:13 AM
Value 0
Name: Type
Type: REG_DWORD
Data: 0x1

Value 1
Name: Start
Type: REG_DWORD
Data: 0

Value 2
Name: ErrorControl
Type: REG_DWORD
Data: 0x1

Value 3
Name: Tag
Type: REG_DWORD
Data: 0x102

Value 4
Name: ImagePath
Type: REG_EXPAND_SZ
Data: system32\DRIVERS\hpgcissd.sys

Value 5
Name: DisplayName
Type: REG_SZ
Data: Smart Array Controllers Non-
Miniport Disk Driver

Value 6
Name: Group
Type: REG_SZ
Data: Primary Disk

Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
hpgcissd\Security
Class Name: <NO CLASS>
Last Write Time: 7/18/2005 - 4:30 PM
Value 0
Name: Security

```

Type:          REG_BINARY
Data:
00000000  01 00 14 80 b8 00 00 00 - c4 00 00 00 14
00 00 00  .....Ä.....
00000010  30 00 00 00 02 00 1c 00 - 01 00 00 00 02
80 14 00  0.....
00000020  ff 01 0f 00 01 01 00 00 - 00 00 00 01 00
00 00 00  ÿ.....
00000030  02 00 88 00 06 00 00 00 - 00 00 14 00 fd
01 02 00  .....ÿ....
00000040  01 01 00 00 00 00 00 05 - 12 00 00 00 00
00 18 00  .....
00000050  ff 01 0f 00 01 02 00 00 - 00 00 00 05 20
00 00 00  ÿ.....
00000060  20 02 00 00 00 00 14 00 - 8d 01 02 00 01
01 00 00  .....ÿ.....
00000070  00 00 00 05 04 00 00 00 - 00 00 14 00 8d
01 02 00  .....
00000080  01 01 00 00 00 00 05 - 06 00 00 00 00
00 14 00  .....
00000090  00 01 00 00 01 01 00 00 - 00 00 00 05 0b
00 00 00  .....
000000a0  00 00 18 00 fd 01 02 00 - 01 02 00 00 00
00 00 05  .....ÿ.....
000000b0  20 00 00 00 23 02 00 00 - 01 01 00 00 00
00 00 05  ...#.....
000000c0  12 00 00 00 01 01 00 00 - 00 00 00 05 12
00 00 00  .....

```

```

Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
hpqcissd\Enum
Class Name:      <NO CLASS>
Last Write Time: 9/26/2005 - 10:13 AM
Value 0
Name:            0
Type:            REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&5f1dc7&0&0
0000400000000000

Value 1
Name:            Count
Type:            REG_DWORD
Data:            0x22

Value 2
Name:            NextInstance
Type:            REG_DWORD
Data:            0x22

Value 3
Name:            1
Type:            REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&5f1dc7&0&1
0000400000000000

Value 4
Name:            2
Type:            REG_SZ

```

```

Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&78f08cd&0&0
0000040000000000

Value 5
Name:            3
Type:            REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&78f08cd&0&0
1000040000000000

Value 6
Name:            4
Type:            REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&27e47dd0&0&0
0000040000000000

Value 7
Name:            5
Type:            REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&27e47dd0&0&0
010000400000000000

Value 8
Name:            6
Type:            REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&1e3dcc80&0&0
0000040000000000

Value 9
Name:            7
Type:            REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&1e3dcc80&0&0
010000400000000000

Value 10
Name:            8
Type:            REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&1bb4d19c&0&0
000000400000000000

Value 11
Name:            9
Type:            REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&1bb4d19c&0&0
010000400000000000

Value 12
Name:            10
Type:            REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&1bb4d19c&0&0
020000400000000000

Value 13
Name:            11
Type:            REG_SZ

```

```

Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&1ec08c08&0&0
000000400000000000

Value 14
Name:            12
Type:            REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&1ec08c08&0&0
010000400000000000

Value 15
Name:            13
Type:            REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&3b81cb25&0&0
000000400000000000

Value 16
Name:            14
Type:            REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&3b81cb25&0&0
010000400000000000

Value 17
Name:            15
Type:            REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&3b81cb25&0&0
020000400000000000

Value 18
Name:            16
Type:            REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&9bfb032&0&0
000004000000000000

Value 19
Name:            17
Type:            REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&9bfb032&0&0
100004000000000000

Value 20
Name:            18
Type:            REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&ab01d09&0&0
000004000000000000

Value 21
Name:            19
Type:            REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&ab01d09&0&0
100004000000000000

Value 22
Name:            20
Type:            REG_SZ

```

```

Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&ab01d09&0&0
200004000000000

Value 23
Name:          21
Type:         REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&3a915e4e&0&0
0000040000000000

Value 24
Name:          22
Type:         REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&3a915e4e&0&0
0100004000000000

Value 25
Name:          23
Type:         REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\5&c633b0d&0&0
0000140010000000

Value 26
Name:          24
Type:         REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&15200e66&0&0
0000004000000000

Value 27
Name:          25
Type:         REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&15200e66&0&0
0100004000000000

Value 28
Name:          26
Type:         REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&15200e66&0&0
0200004000000000

Value 29
Name:          27
Type:         REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&1ec6bfb6&0&0
0000004000000000

Value 30
Name:          28
Type:         REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&1ec6bfb6&0&0
0100004000000000

Value 31
Name:          29
Type:         REG_SZ

```

```

Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&2670e50&0&0
0000040000000000

Value 32
Name:          30
Type:         REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&2670e50&0&0
1000040000000000

Value 33
Name:          31
Type:         REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&2670e50&0&0
2000040000000000

Value 34
Name:          32
Type:         REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&345b2707&0&0
0000004000000000

Value 35
Name:          33
Type:         REG_SZ
Data:
HPQCISS\Disk&VEN_HP&PROD_LOGICAL_VOLUME\6&345b2707&0&0
0100004000000000

```

Boot.ini ***Parameters***

```

[boot loader]
timeout=30
default=multi(0)disk(0)rdisk(0)partition(1)\WINDOWS
[operating systems]
multi(0)disk(0)rdisk(0)partition(1)\WINDOWS="Windows
Server 2003 Enterprise x64 Edition" /noexecute=optout
/fastdetect

```

Web Client ***Hardware*** ***Configuration***

```

System Information report written at: 10/27/2005
09:14:14 AM
[System Information]

```

[Following are sub-categories of this main category]

[System Summary]

Item	Value
OS Name	Microsoft Windows 2000 Server
Version	5.0.2195 Service Pack 4 Build 2195
OS Manufacturer	Microsoft Corporation
System Name	CL26
System Manufacturer	HP
System Model	ProLiant DL360 G4
System Type	X86-based PC
Processor x86 Family 15 Model 4 Stepping 1	
GenuineIntel ~3600 Mhz	
Processor x86 Family 15 Model 4 Stepping 1	
GenuineIntel ~3600 Mhz	
Processor x86 Family 15 Model 4 Stepping 1	
GenuineIntel ~3600 Mhz	
Processor x86 Family 15 Model 4 Stepping 1	
GenuineIntel ~3600 Mhz	
BIOS Version	12/02/04
Windows Directory	C:\WINNT
System Directory	C:\WINNT\system32
Boot Device	\Device\Harddisk0\Partition1
Locale	United States
User Name	CL26\Administrator
Time Zone	Central Daylight Time
Total Physical Memory	1,048,056 KB
Available Physical Memory	757,940 KB
Total Virtual Memory	2,782,844 KB
Available Virtual Memory	2,294,480 KB
Page File Space	1,734,788 KB
Page File	C:\pagefile.sys

[Hardware Resources]

[Following are sub-categories of this main category]

[Conflicts/Sharing]

Resource	Device
IRQ 16	PCI standard PCI-to-PCI bridge
IRQ 16	PCI standard PCI-to-PCI bridge
IRQ 16	PCI standard PCI-to-PCI bridge
IRQ 16	Standard Universal PCI to USB Host Controller
IRQ 5	Universal Serial Bus (USB) Controller
IRQ 5	Base System Device
IRQ 5	Base System Device

[DMA]

Channel	Device	Status
7	Direct memory access controller	OK
2	Standard floppy disk controller	OK

[Forced Hardware]

Device PNP Device ID
No Forced Hardware

```

[I/O]

Address Range      Device      Status
0x0000-0x0CF7    PCI bus    OK
0x0000-0x0CF7    Direct memory access controller
                  OK
0x0D00-0xFFFF    PCI bus    OK
0x4000-0x4FFF    PCI standard PCI-to-PCI bridge
                  OK
0x4000-0x4FFF    Smart Array 6i      OK
0x2000-0x201F    Standard Universal PCI to USB
Host Controller   OK
0x2020-0x203F    Standard Universal PCI to USB
Host Controller   OK
0x3000-0x30FF    ATI Technologies Inc. RAGE XL PCI
                  OK
0x03B0-0x03BB    ATI Technologies Inc. RAGE XL PCI
                  OK
0x03C0-0x03DF    ATI Technologies Inc. RAGE XL PCI
                  OK
0x1800-0x18FF    Base System Device OK
0x3400-0x34FF    Base System Device OK
0x0A79-0x0A79    ISAPNP Read Data Port      OK
0x0279-0x0279    ISAPNP Read Data Port      OK
0x0274-0x0277    ISAPNP Read Data Port      OK
0x0070-0x0077    Motherboard resources       OK
0x0408-0x040F    Motherboard resources       OK
0x04D0-0x04D1    Motherboard resources       OK
0x0020-0x003F    Motherboard resources       OK
0x00A0-0x00BF    Motherboard resources       OK
0x0090-0x009F    Motherboard resources       OK
0x0050-0x0053    Motherboard resources       OK
0x0700-0x071F    Motherboard resources       OK
0x0800-0x083F    Motherboard resources       OK
0x0900-0x097F    Motherboard resources       OK
0x0010-0x001F    Motherboard resources       OK
0x0C80-0x0C83    Motherboard resources       OK
0x0CD4-0x0CD7    Motherboard resources       OK
0x0F50-0x0F58    Motherboard resources       OK
0x02F8-0x02FF    Motherboard resources       OK
0x0040-0x0043    System timer                OK
0x0080-0x008F    Direct memory access controller
                  OK
0x00C0-0x00DF    Direct memory access controller
                  OK
0x0061-0x0061    System speaker              OK
0x0060-0x0060    Standard 101/102-Key or Microsoft
Natural PS/2 Keyboard        OK
0x0064-0x0064    Standard 101/102-Key or Microsoft
Natural PS/2 Keyboard        OK
0x002E-0x002F    Extended IO Bus            OK
0x004E-0x004F    Extended IO Bus            OK
0x0220-0x0225F    Extended IO Bus            OK
0x0280-0x029F    Extended IO Bus            OK
0x03F8-0x03FF    Communications Port (COM1)  OK
0x03F2-0x03F5    Standard floppy disk controller
                  OK
0x03F7-0x03F7    Standard floppy disk controller
                  OK
0x0500-0x050F    Standard Dual Channel PCI IDE
Controller                   OK
0x01F0-0x01F7    Primary IDE Channel        OK
0x03F6-0x03F6    Primary IDE Channel        OK

```

```

0x0170-0x0177    Secondary IDE Channel      OK
0x0376-0x0376    Secondary IDE Channel      OK

[IRQs]

IRQ Number      Device
9               Microsoft ACPI-Compliant System
16              PCI standard PCI-to-PCI bridge
16              PCI standard PCI-to-PCI bridge
16              PCI standard PCI-to-PCI bridge
16              Standard Universal PCI to USB Host
Controller
24              Smart Array 6i
25              HP NC7782 Gigabit Server Adapter
26              HP NC7782 Gigabit Server Adapter #2
19              Standard Universal PCI to USB Host
Controller
5               Universal Serial Bus (USB) Controller
5               Base System Device
5               Base System Device
1               Standard 101/102-Key or Microsoft Natural
PS/2 Keyboard
12              PS/2 Compatible Mouse
4               Communications Port (COM1)
6               Standard floppy disk controller
14              Primary IDE Channel

[Memory]

Range      Device      Status
0xA0000-0xBFFFF    PCI bus    OK
0xA0000-0xBFFFF    ATI Technologies Inc. RAGE XL PCI
                  OK
0x40000000-0xFEBFFFF    PCI bus    OK
0xFDF00000-0xFDFFFFF    PCI standard PCI-to-PCI
bridge     OK
0xFDF00000-0xFDF1FFF    Smart Array 6i      OK
0xFDF80000-0xFDFBFFFF    Smart Array 6i      OK
0xFDF70000-0xFDF7FFF    HP NC7782 Gigabit
Server Adapter      OK
0xFDF60000-0xFDF6FFF    HP NC7782 Gigabit
Server Adapter #2  OK
0xFBFE0000-0xFBFE000F    Intel(R) 6300ESB
                  OK
Watchdog Timer - 25AB
0xFBEE0000-0xFBEE03FF    Universal Serial Bus
(USB) Controller   OK
0xFC000000-0xFCFFFFFF    ATI Technologies Inc.
RAGE XL PCI        OK
0xFBFF0000-0xFBFF0FFF    ATI Technologies Inc.
RAGE XL PCI        OK
0xFBFE0000-0xFBFE01FF    Base System Device OK
0xFBFD0000-0xFBFD07FF    Base System Device OK
0xFBFC0000-0xFBFC1FFF    Base System Device OK
0xFBFB0000-0xFBFB7FFF    Base System Device OK
0xE0000000-0xE0FFFFFF    Motherboard resources
                  OK
0xFBFFFC00-0xFBFFFFFF    Standard Dual Channel
PCI IDE Controller OK

[Components]

[ Following are sub-categories of this main category ]

```

```

[Multimedia]

[ Following are sub-categories of this main category ]

[Audio Codecs]

Codec      Manufacturer      Description
Status     File              Version  Size
Creation Date

c:\winnt\system32\lhacm.acm  Microsoft Corporation
                  OK
C:\WINNT\system32\LHACM.ACM  4.4.3385
33.27 KB (34,064 bytes)    9/13/2002
5:46:04 PM
c:\winnt\system32\msg723.acm  Microsoft Corporation
                  OK
C:\WINNT\system32\MSG723.ACM  4.4.3385
106.77 KB (109,328 bytes)  9/13/2002
5:46:03 PM
c:\winnt\system32\imaadp32.acm  Microsoft
Corporation      OK
C:\WINNT\system32\MAADP32.ACM
5.00.2195.6612      16.27 KB (16,656 bytes)
8/16/2005 1:51:42 PM
c:\winnt\system32\msadp32.acm  Microsoft Corporation
                  OK
C:\WINNT\system32\MSADP32.ACM  5.00.2134.1
14.77 KB (15,120 bytes)    12/7/1999
7:00:00 AM
c:\winnt\system32\msg711.acm  Microsoft Corporation
                  OK
C:\WINNT\system32\MSG711.ACM  5.00.2134.1
10.27 KB (10,512 bytes)   12/7/1999
7:00:00 AM
c:\winnt\system32\tsssoft32.acm  DSP GROUP,
INC.             OK
C:\WINNT\system32\tSSOFT32.ACM
1.01      9.27 KB (9,488 bytes)
12/7/1999 7:00:00 AM
c:\winnt\system32\iac25_32.ax  Intel Corporation
Indeo® audio software      OK
C:\WINNT\system32\IAC25_32.AX  2.05.53
195.00 KB (199,680 bytes)  12/7/1999
7:00:00 AM
c:\winnt\system32\msgsm32.acm  Microsoft Corporation
                  OK
C:\WINNT\system32\MSGSM32.ACM  5.00.2134.1
22.27 KB (22,800 bytes)   12/7/1999
7:00:00 AM

[Video Codecs]

Codec      Manufacturer      Description
Status     File              Version  Size
Creation Date

c:\winnt\system32\irs0_32.dll  Intel Corporation
Indeo® video 5.10      OK
C:\WINNT\system32\IR50_32.DLL
R.5.10.15.2.55      737.50 KB (755,200
bytes)  12/7/1999 7:00:00 AM

```

```

c:\winnt\system32\msh261.drv Microsoft Corporation
                        OK
                        C:\WINNT\system32\MSH261.DRV 4.4.3385
                        163.77 KB (167,696 bytes) 9/13/2002
5:46:04 PM
c:\winnt\system32\msh263.drv Microsoft Corporation
                        OK
                        C:\WINNT\system32\MSH263.DRV 4.4.3385
                        252.27 KB (258,320 bytes) 9/13/2002
5:45:39 PM
c:\winnt\system32\msvidc32.dll Microsoft
Corporation OK
                        C:\WINNT\system32\MSVIDC32.DLL
                        5.00.2134.1 27.27 KB (27,920 bytes)
                        12/7/1999 7:00:00 AM
c:\winnt\system32\msrle32.dll Microsoft Corporation
                        OK
                        C:\WINNT\system32\MSRLE32.DLL
                        5.00.2195.6612 10.77 KB (11,024 bytes)
                        8/16/2005 1:51:49 PM
c:\winnt\system32\ir32_32.dll Intel(R) Corporation
                        OK
                        C:\WINNT\system32\IR32_32.DLL Not Available
                        194.50 KB (199,168 bytes) 12/7/1999
7:00:00 AM
c:\winnt\system32\iccvld.dll Radius Inc.
                        OK C:\WINNT\system32\ICCVLD.DLL
                        1.10.0.6 108.00 KB (110,592 bytes)
                        12/7/1999 7:00:00 AM

```

[CD-ROM]

```

Item Value
Drive D:
Description CD-ROM Drive
Media Loaded False
Media Type CD-ROM
Name COMPAQ CD-ROM SN-124
Manufacturer (Standard CD-ROM drives)
Status OK
Transfer Rate Not Available
SCSI Target ID 0
PNP Device ID IDE\CDROMCOMPAQ_CD-ROM_SN-
124 N104 \5&180B77CF&0&0.0.0

```

[Sound Device]

```

Item Value
No sound devices

```

[Display]

```

Item Value
Name ATI Technologies Inc. RAGE XL PCI
PNP Device ID PCI\VEN_1002&DEV_4752&SUBSYS_001E0E11&REV_2
7\4&2183A681&0&18F0
Adapter Type ATI RAGE XL PCI, ATI Technologies
Inc. compatible
Adapter Description ATI Technologies Inc. RAGE XL PCI
Adapter RAM 8.00 MB (8,388,608 bytes)
Installed Drivers atidrab.dll

```

```

Driver Version 5.00.2179.1
INF File display.inf (atirage3 section)
Color Planes 1
Color Table Entries 65536
Resolution 800 x 600 x 60 hertz
Bits/Pixel 16

```

[Infrared]

```

Item Value
No infrared devices

```

[Input]

[Following are sub-categories of this main category]

[Keyboard]

```

Item Value
Description Standard 101/102-Key or Microsoft
Natural PS/2 Keyboard
Name Enhanced (101- or 102-key)
Layout 00000409
PNP Device ID ACPI\PNP0303\4&1F443D2A&0
NumberOfFunctionKeys 12

```

[Pointing Device]

```

Item Value
Hardware Type USB Human Interface Device
Number of Buttons 5
Status OK
PNP Device ID USB\VID_049F&PID_0048\5&20E9BADC&0&1
Power Management Supported False
Double Click Threshold 6
Handedness Right Handed Operation

Hardware Type PS/2 Compatible Mouse
Number of Buttons 5
Status OK
PNP Device ID ACPI\PNP0F13\4&1F443D2A&0
Power Management Supported False
Double Click Threshold 6
Handedness Right Handed Operation

```

[Modem]

```

Item Value
No modems

```

[Network]

[Following are sub-categories of this main category]

[Adapter]

```

Item Value

```

```

Name [00000000] RAS Async Adapter
Adapter Type Not Available
Product Name RAS Async Adapter
Installed True
PNP Device ID Not Available
Last Reset 10/26/2005 3:10:27 PM
Index 0
Service Name AsyncMac
IP Address Not Available
IP Subnet Not Available
Default IP Gateway Not Available
DHCP Enabled False
DHCP Server Not Available
DHCP Lease Expires Not Available
DHCP Lease Obtained Not Available
MAC Address Not Available
Service Name Not Available

```

```

Name [00000001] WAN Miniport (L2TP)
Adapter Type Not Available
Product Name WAN Miniport (L2TP)
Installed True
PNP Device ID ROOT\MS_L2TPMINIPORT\0000
Last Reset 10/26/2005 3:10:27 PM
Index 1
Service Name Rasl2tp
IP Address Not Available
IP Subnet Not Available
Default IP Gateway Not Available
DHCP Enabled False
DHCP Server Not Available
DHCP Lease Expires Not Available
DHCP Lease Obtained Not Available
MAC Address Not Available
Service Name Rasl2tp
Driver c:\winnt\system32\drivers\rasl2tp.sys
(52112, 5.00.2195.6655)

```

```

Name [00000002] WAN Miniport (PPTP)
Adapter Type Wide Area Network (WAN)
Product Name WAN Miniport (PPTP)
Installed True
PNP Device ID ROOT\MS_PPTPMINIPORT\0000
Last Reset 10/26/2005 3:10:27 PM
Index 2
Service Name PptpMiniport
IP Address Not Available
IP Subnet Not Available
Default IP Gateway Not Available
DHCP Enabled False
DHCP Server Not Available
DHCP Lease Expires Not Available
DHCP Lease Obtained Not Available
MAC Address 50:50:54:50:30:30
Service Name PptpMiniport
Driver c:\winnt\system32\drivers\raspptp.sys
(48464, 5.00.2195.6711)

```

```

Name [00000003] Direct Parallel
Adapter Type Not Available
Product Name Direct Parallel
Installed True
PNP Device ID ROOT\MS_PTMINIPORT\0000

```

Last Reset 10/26/2005 3:10:27 PM
 Index 3
 Service Name Raspti
 IP Address Not Available
 IP Subnet Not Available
 Default IP Gateway Not Available
 DHCP Enabled False
 DHCP Server Not Available
 DHCP Lease Expires Not Available
 DHCP Lease Obtained Not Available
 MAC Address Not Available
 Service Name Raspti
 Driver c:\winnt\system32\drivers\raspti.sys
 (16880, 5.00.2146.1)

Name [00000004] WAN Miniport (IP)
 Adapter Type Not Available
 Product Name WAN Miniport (IP)
 Installed True
 PNP Device ID ROOT\MS_NDISWANIP\0000
 Last Reset 10/26/2005 3:10:27 PM
 Index 4
 Service Name NdisWan
 IP Address Not Available
 IP Subnet Not Available
 Default IP Gateway Not Available
 DHCP Enabled False
 DHCP Server Not Available
 DHCP Lease Expires Not Available
 DHCP Lease Obtained Not Available
 MAC Address Not Available
 Service Name NdisWan
 Driver c:\winnt\system32\drivers\ndiswan.sys
 (93360, 5.00.2195.6699)

Name [00000005] Compaq NC7780 Gigabit Server
 Adapter
 Adapter Type Not Available
 Product Name Compaq NC7780 Gigabit Server
 Adapter
 Installed True
 PNP Device ID Not Available
 Last Reset 10/26/2005 3:10:27 PM
 Index 5
 Service Name q57w2k
 IP Address 130.172.11.26
 IP Subnet 255.255.0.0
 Default IP Gateway Not Available
 DHCP Enabled True
 DHCP Server 130.168.253.2
 DHCP Lease Expires 9/16/2002 7:03:07 PM
 DHCP Lease Obtained 9/15/2002 7:03:07 PM
 MAC Address 00:13:21:B1:B5:9A
 Service Name Not Available

Name [00000006] Compaq NC7780 Gigabit Server
 Adapter
 Adapter Type Not Available
 Product Name Compaq NC7780 Gigabit Server
 Adapter
 Installed True
 PNP Device ID Not Available
 Last Reset 10/26/2005 3:10:27 PM

Index 6
 Service Name q57w2k
 IP Address 130.168.40.26
 IP Subnet 255.255.0.0
 Default IP Gateway Not Available
 DHCP Enabled False
 DHCP Server Not Available
 DHCP Lease Expires Not Available
 DHCP Lease Obtained Not Available
 MAC Address 00:13:21:B1:B5:99
 Service Name Not Available

Name [00000007] Compaq NC3123 Fast Ethernet NIC
 Adapter Type Not Available
 Product Name Compaq NC3123 Fast Ethernet NIC
 Installed True
 PNP Device ID Not Available
 Last Reset 10/26/2005 3:10:27 PM
 Index 7
 Service Name N100
 IP Address 130.168.40.26
 IP Subnet 255.255.0.0
 Default IP Gateway Not Available
 DHCP Enabled True
 DHCP Server 130.168.253.2
 DHCP Lease Expires 9/16/2002 3:58:55 PM
 DHCP Lease Obtained 9/15/2002 3:58:55 PM
 MAC Address 00:13:21:B1:B5:99
 Service Name Not Available

Name [00000008] Compaq NC7781 Gigabit Server
 Adapter
 Adapter Type Not Available
 Product Name Compaq NC7781 Gigabit Server
 Adapter
 Installed True
 PNP Device ID Not Available
 Last Reset 10/26/2005 3:10:27 PM
 Index 8
 Service Name q57w2k
 IP Address 130.168.40.26
 IP Subnet 255.255.0.0
 Default IP Gateway Not Available
 DHCP Enabled False
 DHCP Server Not Available
 DHCP Lease Expires Not Available
 DHCP Lease Obtained Not Available
 MAC Address 00:13:21:B1:B5:99
 Service Name Not Available

Name [00000009] Compaq NC7781 Gigabit Server
 Adapter
 Adapter Type Not Available
 Product Name Compaq NC7781 Gigabit Server
 Adapter
 Installed True
 PNP Device ID Not Available
 Last Reset 10/26/2005 3:10:27 PM
 Index 9
 Service Name q57w2k
 IP Address 130.172.11.26
 IP Subnet 255.255.0.0
 Default IP Gateway Not Available

DHCP Enabled False
 DHCP Server Not Available
 DHCP Lease Expires Not Available
 DHCP Lease Obtained Not Available
 MAC Address 00:13:21:B1:B5:9A
 Service Name Not Available

Name [00000010] HP NC7782 Gigabit Server Adapter
 Adapter Type Ethernet 802.3
 Product Name HP NC7782 Gigabit Server Adapter
 Installed True
 PNP Device ID PCI\VEN_14E4&DEV_1648&SUBSYS_00D00E11&REV_1
 0\4&19638ECB&0&10E0
 Last Reset 10/26/2005 3:10:27 PM
 Index 10
 Service Name q57w2k
 IP Address 130.172.11.26
 IP Subnet 255.255.0.0
 Default IP Gateway Not Available
 DHCP Enabled False
 DHCP Server Not Available
 DHCP Lease Expires Not Available
 DHCP Lease Obtained Not Available
 MAC Address 00:13:21:B1:B5:9A
 Service Name q57w2k
 IRQ Number 25
 Driver c:\winnt\system32\drivers\q57w2k.sys
 (192247, 7.80.0.0)

Name [00000011] HP NC7782 Gigabit Server Adapter
 Adapter Type Ethernet 802.3
 Product Name HP NC7782 Gigabit Server Adapter
 Installed True
 PNP Device ID PCI\VEN_14E4&DEV_1648&SUBSYS_00D00E11&REV_1
 0\4&19638ECB&0&11E0
 Last Reset 10/26/2005 3:10:27 PM
 Index 11
 Service Name q57w2k
 IP Address 130.168.40.26
 IP Subnet 255.255.0.0
 Default IP Gateway Not Available
 DHCP Enabled False
 DHCP Server Not Available
 DHCP Lease Expires Not Available
 DHCP Lease Obtained Not Available
 MAC Address 00:13:21:B1:B5:99
 Service Name q57w2k
 IRQ Number 26
 Driver c:\winnt\system32\drivers\q57w2k.sys
 (192247, 7.80.0.0)

[Protocol]

Item	Value
Name	MSAFD Tcpip [TCP/IP]
ConnectionlessService	False
GuaranteesDelivery	True
GuaranteesSequencing	True
MaximumAddressSize	16 bytes
MaximumMessageSize	0 bytes

MessageOriented False
 MinimumAddressSize 16 bytes
 PseudoStreamOriented False
 SupportsBroadcasting False
 SupportsConnectData False
 SupportsDisconnectData False
 SupportsEncryption False
 SupportsExpeditedData True
 SupportsGracefulClosing True
 SupportsGuaranteedBandwidth False
 SupportsMulticasting False

Name MSAFD Tcpip [UDP/IP]
 ConnectionlessService True
 GuaranteesDelivery False
 GuaranteesSequencing False
 MaximumAddressSize 16 bytes
 MaximumMessageSize 65467 bytes
 MessageOriented True
 MinimumAddressSize 16 bytes
 PseudoStreamOriented False
 SupportsBroadcasting True
 SupportsConnectData False
 SupportsDisconnectData False
 SupportsEncryption False
 SupportsExpeditedData False
 SupportsGracefulClosing False
 SupportsGuaranteedBandwidth False
 SupportsMulticasting True

Name RSVP UDP Service Provider
 ConnectionlessService True
 GuaranteesDelivery False
 GuaranteesSequencing False
 MaximumAddressSize 16 bytes
 MaximumMessageSize 65467 bytes
 MessageOriented True
 MinimumAddressSize 16 bytes
 PseudoStreamOriented False
 SupportsBroadcasting True
 SupportsConnectData False
 SupportsDisconnectData False
 SupportsEncryption True
 SupportsExpeditedData False
 SupportsGracefulClosing False
 SupportsGuaranteedBandwidth False
 SupportsMulticasting True

Name RSVP TCP Service Provider
 ConnectionlessService False
 GuaranteesDelivery True
 GuaranteesSequencing True
 MaximumAddressSize 16 bytes
 MaximumMessageSize 0 bytes
 MessageOriented False
 MinimumAddressSize 16 bytes
 PseudoStreamOriented False
 SupportsBroadcasting False
 SupportsConnectData False
 SupportsDisconnectData False
 SupportsEncryption True
 SupportsExpeditedData True
 SupportsGracefulClosing True

SupportsGuaranteedBandwidth False
 SupportsMulticasting False

Name MSAFD NetBIOS
 [\Device\NetBT_Tcpip_{37E5A54E-FF18-486C-B3AD-E80449420A01}] SEQPACKET 8
 ConnectionlessService False
 GuaranteesDelivery True
 GuaranteesSequencing True
 MaximumAddressSize 20 bytes
 MaximumMessageSize 64000 bytes
 MessageOriented True
 MinimumAddressSize 20 bytes
 PseudoStreamOriented False
 SupportsBroadcasting False
 SupportsConnectData False
 SupportsDisconnectData False
 SupportsEncryption False
 SupportsExpeditedData False
 SupportsGracefulClosing False
 SupportsGuaranteedBandwidth False
 SupportsMulticasting False

Name MSAFD NetBIOS
 [\Device\NetBT_Tcpip_{37E5A54E-FF18-486C-B3AD-E80449420A01}] DATAGRAM 8
 ConnectionlessService True
 GuaranteesDelivery False
 GuaranteesSequencing False
 MaximumAddressSize 20 bytes
 MaximumMessageSize 64000 bytes
 MessageOriented True
 MinimumAddressSize 20 bytes
 PseudoStreamOriented False
 SupportsBroadcasting True
 SupportsConnectData False
 SupportsDisconnectData False
 SupportsEncryption False
 SupportsExpeditedData False
 SupportsGracefulClosing False
 SupportsGuaranteedBandwidth False
 SupportsMulticasting False

Name MSAFD NetBIOS
 [\Device\NetBT_Tcpip_{4D85C014-5E76-48CF-93EA-317E0F725486}] SEQPACKET 7
 ConnectionlessService False
 GuaranteesDelivery True
 GuaranteesSequencing True
 MaximumAddressSize 20 bytes
 MaximumMessageSize 64000 bytes
 MessageOriented True
 MinimumAddressSize 20 bytes
 PseudoStreamOriented False
 SupportsBroadcasting False
 SupportsConnectData False
 SupportsDisconnectData False
 SupportsEncryption False
 SupportsExpeditedData False
 SupportsGracefulClosing False
 SupportsGuaranteedBandwidth False
 SupportsMulticasting False

Name MSAFD NetBIOS
 [\Device\NetBT_Tcpip_{4D85C014-5E76-48CF-93EA-317E0F725486}] DATAGRAM 7
 ConnectionlessService True
 GuaranteesDelivery False
 GuaranteesSequencing False
 MaximumAddressSize 20 bytes
 MaximumMessageSize 64000 bytes
 MessageOriented True
 MinimumAddressSize 20 bytes
 PseudoStreamOriented False
 SupportsBroadcasting True
 SupportsConnectData False
 SupportsDisconnectData False
 SupportsEncryption False
 SupportsExpeditedData False
 SupportsGracefulClosing False
 SupportsGuaranteedBandwidth False
 SupportsMulticasting False

Name MSAFD NetBIOS
 [\Device\NetBT_Tcpip_{2D8AA674-9F13-43EE-9055-F9ECADD87F7F}] SEQPACKET 6
 ConnectionlessService False
 GuaranteesDelivery True
 GuaranteesSequencing True
 MaximumAddressSize 20 bytes
 MaximumMessageSize 64000 bytes
 MessageOriented True
 MinimumAddressSize 20 bytes
 PseudoStreamOriented False
 SupportsBroadcasting False
 SupportsConnectData False
 SupportsDisconnectData False
 SupportsEncryption False
 SupportsExpeditedData False
 SupportsGracefulClosing False
 SupportsGuaranteedBandwidth False
 SupportsMulticasting False

Name MSAFD NetBIOS
 [\Device\NetBT_Tcpip_{2D8AA674-9F13-43EE-9055-F9ECADD87F7F}] DATAGRAM 6
 ConnectionlessService True
 GuaranteesDelivery False
 GuaranteesSequencing False
 MaximumAddressSize 20 bytes
 MaximumMessageSize 64000 bytes
 MessageOriented True
 MinimumAddressSize 20 bytes
 PseudoStreamOriented False
 SupportsBroadcasting True
 SupportsConnectData False
 SupportsDisconnectData False
 SupportsEncryption False
 SupportsExpeditedData False
 SupportsGracefulClosing False
 SupportsGuaranteedBandwidth False
 SupportsMulticasting False

Name MSAFD NetBIOS
 [\Device\NetBT_Tcpip_{EFD5741D-3A14-456C-98EB-17ABC580A075}] SEQPACKET 5

ConnectionlessService False
 GuaranteesDelivery True
 GuaranteesSequencing True
 MaximumAddressSize 20 bytes
 MaximumMessageSize 64000 bytes
 MessageOriented True
 MinimumAddressSize 20 bytes
 PseudoStreamOriented False
 SupportsBroadcasting False
 SupportsConnectData False
 SupportsDisconnectData False
 SupportsEncryption False
 SupportsExpeditedData False
 SupportsGracefulClosing False
 SupportsGuaranteedBandwidth False
 SupportsMulticasting False

Name MSAFD NetBIOS
 [\Device\NetBT_Tcpip_{EPD5741D-3A14-456C-98EB-17ABC580A075}] DATAGRAM 5
 ConnectionlessService True
 GuaranteesDelivery False
 GuaranteesSequencing False
 MaximumAddressSize 20 bytes
 MaximumMessageSize 64000 bytes
 MessageOriented True
 MinimumAddressSize 20 bytes
 PseudoStreamOriented False
 SupportsBroadcasting True
 SupportsConnectData False
 SupportsDisconnectData False
 SupportsEncryption False
 SupportsExpeditedData False
 SupportsGracefulClosing False
 SupportsGuaranteedBandwidth False
 SupportsMulticasting False

Name MSAFD NetBIOS
 [\Device\NetBT_Tcpip_{4249431A-469E-4735-A292-01AA526741FC}] SEQPACKET 4
 ConnectionlessService False
 GuaranteesDelivery True
 GuaranteesSequencing True
 MaximumAddressSize 20 bytes
 MaximumMessageSize 64000 bytes
 MessageOriented True
 MinimumAddressSize 20 bytes
 PseudoStreamOriented False
 SupportsBroadcasting False
 SupportsConnectData False
 SupportsDisconnectData False
 SupportsEncryption False
 SupportsExpeditedData False
 SupportsGracefulClosing False
 SupportsGuaranteedBandwidth False
 SupportsMulticasting False

Name MSAFD NetBIOS
 [\Device\NetBT_Tcpip_{4249431A-469E-4735-A292-01AA526741FC}] DATAGRAM 4
 ConnectionlessService True
 GuaranteesDelivery False
 GuaranteesSequencing False

MaximumAddressSize 20 bytes
 MaximumMessageSize 64000 bytes
 MessageOriented True
 MinimumAddressSize 20 bytes
 PseudoStreamOriented False
 SupportsBroadcasting True
 SupportsConnectData False
 SupportsDisconnectData False
 SupportsEncryption False
 SupportsExpeditedData False
 SupportsGracefulClosing False
 SupportsGuaranteedBandwidth False
 SupportsMulticasting False

Name MSAFD NetBIOS
 [\Device\NetBT_Tcpip_{3B09DDE7-7EB8-4941-8121-52DC6359F5A6}] SEQPACKET 3
 ConnectionlessService False
 GuaranteesDelivery True
 GuaranteesSequencing True
 MaximumAddressSize 20 bytes
 MaximumMessageSize 64000 bytes
 MessageOriented True
 MinimumAddressSize 20 bytes
 PseudoStreamOriented False
 SupportsBroadcasting False
 SupportsConnectData False
 SupportsDisconnectData False
 SupportsEncryption False
 SupportsExpeditedData False
 SupportsGracefulClosing False
 SupportsGuaranteedBandwidth False
 SupportsMulticasting False

Name MSAFD NetBIOS
 [\Device\NetBT_Tcpip_{3B09DDE7-7EB8-4941-8121-52DC6359F5A6}] DATAGRAM 3
 ConnectionlessService True
 GuaranteesDelivery False
 GuaranteesSequencing False
 MaximumAddressSize 20 bytes
 MaximumMessageSize 64000 bytes
 MessageOriented True
 MinimumAddressSize 20 bytes
 PseudoStreamOriented False
 SupportsBroadcasting True
 SupportsConnectData False
 SupportsDisconnectData False
 SupportsEncryption False
 SupportsExpeditedData False
 SupportsGracefulClosing False
 SupportsGuaranteedBandwidth False
 SupportsMulticasting False

Name MSAFD NetBIOS
 [\Device\NetBT_Tcpip_{684FA660-D082-4A8C-AC8C-C9D449B21686}] SEQPACKET 0
 ConnectionlessService False
 GuaranteesDelivery True
 GuaranteesSequencing True
 MaximumAddressSize 20 bytes
 MaximumMessageSize 64000 bytes
 MessageOriented True

MinimumAddressSize 20 bytes
 PseudoStreamOriented False
 SupportsBroadcasting False
 SupportsConnectData False
 SupportsDisconnectData False
 SupportsEncryption False
 SupportsExpeditedData False
 SupportsGracefulClosing False
 SupportsGuaranteedBandwidth False
 SupportsMulticasting False

Name MSAFD NetBIOS
 [\Device\NetBT_Tcpip_{684FA660-D082-4A8C-AC8C-C9D449B21686}] DATAGRAM 0
 ConnectionlessService True
 GuaranteesDelivery False
 GuaranteesSequencing False
 MaximumAddressSize 20 bytes
 MaximumMessageSize 64000 bytes
 MessageOriented True
 MinimumAddressSize 20 bytes
 PseudoStreamOriented False
 SupportsBroadcasting True
 SupportsConnectData False
 SupportsDisconnectData False
 SupportsEncryption False
 SupportsExpeditedData False
 SupportsGracefulClosing False
 SupportsGuaranteedBandwidth False
 SupportsMulticasting False

Name MSAFD NetBIOS
 [\Device\NetBT_Tcpip_{D90E04F2-3AD9-4F98-9464-751E106D7E6A}] SEQPACKET 1
 ConnectionlessService False
 GuaranteesDelivery True
 GuaranteesSequencing True
 MaximumAddressSize 20 bytes
 MaximumMessageSize 64000 bytes
 MessageOriented True
 MinimumAddressSize 20 bytes
 PseudoStreamOriented False
 SupportsBroadcasting False
 SupportsConnectData False
 SupportsDisconnectData False
 SupportsEncryption False
 SupportsExpeditedData False
 SupportsGracefulClosing False
 SupportsGuaranteedBandwidth False
 SupportsMulticasting False

Name MSAFD NetBIOS
 [\Device\NetBT_Tcpip_{D90E04F2-3AD9-4F98-9464-751E106D7E6A}] DATAGRAM 1
 ConnectionlessService True
 GuaranteesDelivery False
 GuaranteesSequencing False
 MaximumAddressSize 20 bytes
 MaximumMessageSize 64000 bytes
 MessageOriented True
 MinimumAddressSize 20 bytes
 PseudoStreamOriented False
 SupportsBroadcasting True

```

SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption False
SupportsExpeditedData False
SupportsGracefulClosing False
SupportsGuaranteedBandwidth False
SupportsMulticasting False

```

```

Name MSAFD NetBIOS
[Device\NetBT_Tcpip_{3F1BA297-E685-416B-82D7-70E771CC8745}] SEQPACKET 2
ConnectionlessService False
GuaranteesDelivery True
GuaranteesSequencing True
MaximumAddressSize 20 bytes
MaximumMessageSize 64000 bytes
MessageOriented True
MinimumAddressSize 20 bytes
PseudoStreamOriented False
SupportsBroadcasting False
SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption False
SupportsExpeditedData False
SupportsGracefulClosing False
SupportsGuaranteedBandwidth False
SupportsMulticasting False

```

```

Name MSAFD NetBIOS
[Device\NetBT_Tcpip_{3F1BA297-E685-416B-82D7-70E771CC8745}] DATAGRAM 2
ConnectionlessService True
GuaranteesDelivery False
GuaranteesSequencing False
MaximumAddressSize 20 bytes
MaximumMessageSize 64000 bytes
MessageOriented True
MinimumAddressSize 20 bytes
PseudoStreamOriented False
SupportsBroadcasting True
SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption False
SupportsExpeditedData False
SupportsGracefulClosing False
SupportsGuaranteedBandwidth False
SupportsMulticasting False

```

[WinSock]

```

Item Value
File c:\winnt\system32\winsock.dll
Version 3.10
Size 2.80 KB (2,864 bytes)

File c:\winnt\system32\wsock32.dll
Version 5.00.2195.6603
Size 21.27 KB (21,776 bytes)

```

[Ports]

[Following are sub-categories of this main category]

[Serial]

```

Item Value
Name COM1
Status OK
PNP Device ID ACPI\PNP0501\0
Maximum Input Buffer Size 0
Maximum Output Buffer Size False
Settable Baud Rate True
Settable Data Bits True
Settable Flow Control True
Settable Parity True
Settable Parity Check True
Settable Stop Bits True
Settable RLSD True
Supports RLSD True
Supports 16 Bit Mode False
Supports Special Characters False
Baud Rate 9600
Bits/Byte 8
Stop Bits 1
Parity None
Busy 0
Abort Read/Write on Error 0
Binary Mode Enabled -1
Continue XMit on XOff 0
CTS Outflow Control 0
Discard NULL Bytes 0
DSR Outflow Control 0
DSR Sensitivity 0
DTR Flow Control Type Enable
EOF Character 0
Error Replace Character 0
Error Replacement Enabled 0
Event Character 0
Parity Check Enabled 0
RTS Flow Control Type Enable
XOff Character 19
XOffXMit Threshold 512
XOn Character 17
XOnXMit Threshold 2048
XOnXOff InFlow Control 0
XOnXOff OutFlow Control 0
IRQ Number 4
I/O Port 0x03F8-0x03FF
Driver c:\winnt\system32\drivers\serial.sys
(62736, 5.00.2195.6655)

```

[Parallel]

```

Item Value
No parallel port information

```

[Storage]

[Following are sub-categories of this main category]

[Drives]

```

Item Value
Drive A:
Description 3 1/2 Inch Floppy Drive

```

```

Drive C:
Description Local Fixed Disk
Compressed False
File System NTFS
Size 33.90 GB (36,405,055,488 bytes)
Free Space 30.63 GB (32,884,482,048 bytes)
Volume Name
Volume Serial Number C8B488FA
Partition Disk #0, Partition #0
Partition Size 33.90 GB (36,405,057,024 bytes)
Starting Offset 32256 bytes
Drive Description Disk drive
Drive Manufacturer (Standard disk drives)
Drive Model HP LOGICAL VOLUME SCSI Disk
Device
Drive BytesPerSector 512
Drive MediaLoaded True
Drive MediaType Fixed hard disk media
Drive Partitions 1
Drive SCSIIBus 0
Drive SCSILogicalUnit 0
Drive SCSIPort 2
Drive SCSTargetId 4
Drive SectorsPerTrack 63
Drive Size 36413314560 bytes
Drive TotalCylinders 4427
Drive TotalSectors 71119755
Drive TotalTracks 1128885
Drive TracksPerCylinder 255

```

[SCSI]

```

Item Value
Name Smart Array 6i
Caption Smart Array 6i
Driver cpqcissm
Status OK
PNP Device ID
PCI\VEN_0E11&DEV_0046&SUBSYS_40910E11&REV_0
1\4&19638ECB&0&08E0
Device ID
PCI\VEN_0E11&DEV_0046&SUBSYS_40910E11&REV_0
1\4&19638ECB&0&08E0
Device Map Not Available
Index Not Available
Max Number Controlled Not Available
IRQ Number 24
I/O Port 0x4000-0x4FFF
Driver c:\winnt\system32\drivers\cpqcissm.sys
(16512, 5.64.0.32 Build 7 (x86))

```

[Printing]

```

Name Port Name Server Name
No printing information

```

[Problem Devices]

```

Device      PNP Device ID      Error Code
Universal Serial Bus (USB) Controller
PCI\VEN_8086&DEV_25AD&SUBSYS_32010E11&REV_0
2\3&61AAA01&0&EF      28
Base System Device
PCI\VEN_0E11&DEV_B203&SUBSYS_B2060E11&REV_0
1\4&2183A681&0&20F0 28
Base System Device
PCI\VEN_0E11&DEV_B204&SUBSYS_B2060E11&REV_0
1\4&2183A681&0&22F0 28
    
```

[USB]

```

Device      PNP Device ID
Standard Universal PCI to USB Host Controller
PCI\VEN_8086&DEV_25A9&SUBSYS_32010E11&REV_0
2\3&61AAA01&0&E8
USB Root Hub      USB\ROOT_HUB\4&312B1C17&0
USB Human Interface Device
USB\VID_049F&PID_0048\5&20E9BADC&0&1
HID-compliant mouse
HID\VID_049F&PID_0048\6&360717A3&0&0000
Standard Universal PCI to USB Host Controller
PCI\VEN_8086&DEV_25AA&SUBSYS_32010E11&REV_0
2\3&61AAA01&0&E9
USB Root Hub      USB\ROOT_HUB\4&24B43ADC&0
    
```

[Software Environment]

[Following are sub-categories of this main category]

[Drivers]

Name	Description	File	Type	Started	Start Mode	State	Status	Error Control	Accept Pause
abiosdsk	Abiosdsk	Not Available	Kernel Driver	False	Disabled	Stopped	OK	Ignore	False
abp480n5	abp480n5	Not Available	Kernel Driver	False	Disabled	Stopped	OK	Normal	False
acpi	Microsoft ACPI Driver	c:\winnt\system32\drivers\acpi.sys	Kernel Driver	True	Boot	Running	OK	Normal	False
acpiec	ACPIEC	c:\winnt\system32\drivers\acpiec.sys	Kernel Driver	False	Disabled	Stopped	OK	Normal	False
adpu160m	adpu160m	Not Available	Kernel Driver	False	Disabled	Stopped	OK	Normal	False
afd	AFD Networking Support Environment	c:\winnt\system32\drivers\afd.sys	Kernel Driver	True	Auto	Running	OK	Normal	False

Running	OK	Normal	False
True			
ahal54x	Ahal54x	Not Available	Kernel Driver
False	Disabled	Stopped	OK
Normal	False	False	
aic116x	aic116x	Not Available	Kernel Driver
False	Disabled	Stopped	OK
Normal	False	False	
aic78u2	aic78u2	Not Available	Kernel Driver
False	Disabled	Stopped	OK
Normal	False	False	
aic78xx	aic78xx	Not Available	Kernel Driver
False	Disabled	Stopped	OK
Normal	False	False	
alkernel	Altiris Kernel Driver	c:\winnt\system32\drivers\alkernel.sys	Kernel Driver
True	Running	OK	Normal
ami0nt	ami0nt	Not Available	Kernel Driver
False	Disabled	Stopped	OK
Normal	False	False	
amsint	amsint	Not Available	Kernel Driver
False	Disabled	Stopped	OK
Normal	False	False	
asc	asc	Not Available	Kernel Driver
False	Disabled	Stopped	OK
Normal	False	False	
asc3350p	asc3350p	Not Available	Kernel Driver
False	Disabled	Stopped	OK
Normal	False	False	
asc3550	asc3550	Not Available	Kernel Driver
False	Disabled	Stopped	OK
Normal	False	False	
asynccmac	RAS Asynchronous Media Driver	c:\winnt\system32\drivers\asynccmac.sys	Kernel Driver
Stopped	OK	Normal	False
False			
atapi	Standard IDE/ESDI Hard Disk Controller	c:\winnt\system32\drivers\atapi.sys	Kernel Driver
Running	OK	Normal	False
True			
atdisk	Atdisk	Not Available	Kernel Driver
False	Disabled	Stopped	OK
Ignore	False	False	
atirage3	atirage3	c:\winnt\system32\drivers\atimpab.sys	Kernel Driver
Running	OK	Ignore	False
True			
atmarpc	ATM ARP Client Protocol	c:\winnt\system32\drivers\atmarpc.sys	Kernel Driver
Stopped	OK	Normal	False
False			
audstub	Audio Stub Driver	c:\winnt\system32\drivers\audstub.sys	Kernel Driver
Running	OK	Normal	False
True			

beep	Beep	c:\winnt\system32\drivers\beep.sys	Kernel Driver
Running	OK	Normal	False
True			
buslogic	BusLogic	Not Available	Kernel Driver
False	Disabled	Stopped	OK
Normal	False	False	
cd20xrnt	cd20xrnt	Not Available	Kernel Driver
False	Disabled	Stopped	OK
Normal	False	False	
cdaudio	Cdaudio	c:\winnt\system32\drivers\cdaudio.sys	Kernel Driver
Stopped	OK	Ignore	False
False			
cdfs	Cdfs	c:\winnt\system32\drivers\cdfs.sys	File System Driver
Running	OK	Normal	False
True			
cdrom	CD-ROM Driver	c:\winnt\system32\drivers\cdrom.sys	Kernel Driver
Running	OK	Normal	False
True			
changer	Changer	Not Available	Kernel Driver
False	System	Stopped	OK
Ignore	False	False	
cpqarray	Cpqarray	Not Available	Kernel Driver
False	Disabled	Stopped	OK
Normal	False	False	
cpqarray2	cpqarray2	Not Available	Kernel Driver
False	Disabled	Stopped	OK
Normal	False	False	
cpqcissm	cpqcissm	c:\winnt\system32\drivers\cpqcissm.sys	Kernel Driver
Running	OK	Normal	False
True			
cpqfcalm	cpqfcalm	Not Available	Kernel Driver
False	Disabled	Stopped	OK
Normal	False	False	
cpqfws2e	cpqfws2e	Not Available	Kernel Driver
False	Disabled	Stopped	OK
Normal	False	False	
dac960nt	dac960nt	Not Available	Kernel Driver
False	Disabled	Stopped	OK
Normal	False	False	
deckzpsx	deckzpsx	Not Available	Kernel Driver
False	Disabled	Stopped	OK
Normal	False	False	
dfsdriver	DfsDriver	c:\winnt\system32\drivers\dfs.sys	File System Driver
Running	OK	Normal	False
True			
disk	Disk Driver	c:\winnt\system32\drivers\disk.sys	Kernel Driver
Running	OK	Normal	False
True			
diskperf	Diskperf	c:\winnt\system32\drivers\diskperf.sys	

	Kernel Driver	True	Boot
	Running	OK	Normal
	True	False	False
dmboot	dmboot		
	c:\winnt\system32\drivers\dmboot.sys		
	Kernel Driver	False	Disabled
	Stopped	OK	Normal
	False	False	False
dmio	Logical Disk Manager Driver		
	c:\winnt\system32\drivers\dmio.sys		
	Kernel Driver	True	Boot
	Running	OK	Normal
	True	False	False
dmload	dmload		
	c:\winnt\system32\drivers\dmload.sys		
	Kernel Driver	True	Boot
	Running	OK	Normal
	True	False	False
efs	efs c:\winnt\system32\drivers\efs.sys		
	File System Driver	True	Disabled
	Running	OK	Normal
	True	False	False
fastfat	Fastfat		
	c:\winnt\system32\drivers\fastfat.sys		
	File System Driver	True	Disabled
	Running	OK	Normal
	True	False	False
fd16_700	Fd16_700	Not Available	Kernel Driver
	False	Disabled	Stopped
	Normal	False	OK
fdc	Floppy Disk Controller Driver		
	c:\winnt\system32\drivers\fdc.sys		
	Kernel Driver	True	Manual
	Running	OK	Normal
	True	False	False
fips	Fips		
	c:\winnt\system32\drivers\fips.sys		
	Kernel Driver	True	Auto
	Running	OK	Normal
	True	False	False
fireport	fireport	Not Available	Kernel Driver
	False	Disabled	Stopped
	Normal	False	OK
flashpnt	flashpnt	Not Available	Kernel Driver
	False	Disabled	Stopped
	Normal	False	OK
flpydisk	Floppy Disk Driver		
	c:\winnt\system32\drivers\flpydisk.sys		
	Kernel Driver	True	Manual
	Running	OK	Normal
	True	False	False
ftdisk	Volume Manager Driver		
	c:\winnt\system32\drivers\ftdisk.sys		
	Kernel Driver	True	Boot
	Running	OK	Normal
	True	False	False
gpc	Generic Packet Classifier		
	c:\winnt\system32\drivers\msgpc.sys		
	Kernel Driver	True	Manual
	Running	OK	Normal
	True	False	False
hidusb	Microsoft HID Class Driver		
	c:\winnt\system32\drivers\hidusb.sys		

	Kernel Driver	True	Auto
	Running	OK	Ignore
	True	False	False
i8042prt	i8042 Keyboard and PS/2 Mouse Port Driver		
	c:\winnt\system32\drivers\i8042prt.sys		
	Kernel Driver	True	System
	Running	OK	Normal
	True	False	False
ini910u	ini910u	Not Available	Kernel Driver
	False	Disabled	Stopped
	Normal	False	OK
intelide	IntelIde	Not Available	Kernel Driver
	False	Disabled	Stopped
	Normal	False	OK
ipfilterdriver	IP Traffic Filter Driver		
	c:\winnt\system32\drivers\ipfltdrv.sys		
	Kernel Driver	False	Manual
	Stopped	OK	Normal
	False	False	False
ipinip	IP in IP Tunnel Driver		
	c:\winnt\system32\drivers\ipinip.sys		
	Kernel Driver	False	Manual
	Stopped	OK	Normal
	False	False	False
ipnat	IP Network Address Translator		
	c:\winnt\system32\drivers\ipnat.sys		
	Kernel Driver	False	Manual
	Stopped	OK	Normal
	False	False	False
ipsecc	IPSEC driver		
	c:\winnt\system32\drivers\ipsecc.sys		
	Kernel Driver	True	Manual
	Running	OK	Normal
	True	False	False
ipsraidn	ipsraidn	Not Available	Kernel Driver
	False	Disabled	Stopped
	Normal	False	OK
irenum	IR Enumerator Service		
	c:\winnt\system32\drivers\irenum.sys		
	Kernel Driver	False	Manual
	Stopped	OK	Normal
	False	False	False
isapnp	PnP ISA/EISA Bus Driver		
	c:\winnt\system32\drivers\isapnp.sys		
	Kernel Driver	True	Boot
	Running	OK	Critical
	True	False	False
kbdclass	Keyboard Class Driver		
	c:\winnt\system32\drivers\kbdclass.sys		
	Kernel Driver	True	System
	Running	OK	Normal
	True	False	False
ksecdd	KSecDD		
	c:\winnt\system32\drivers\ksecdd.sys		
	Kernel Driver	True	Boot
	Running	OK	Normal
	True	False	False
lbrtfdc	lbrtfdc	Not Available	Kernel Driver
	False	System	Stopped
	Ignore	False	OK
lp6nds35	lp6nds35	Not Available	Kernel Driver
	False	Disabled	Stopped
	Normal	False	OK

mmdd	mmdd		
	c:\winnt\system32\drivers\mmdd.sys		
	Kernel Driver	True	System
	Running	OK	Ignore
	True	False	False
modem	Modem		
	c:\winnt\system32\drivers\modem.sys		
	Kernel Driver	False	Manual
	Stopped	OK	Ignore
	False	False	False
mouclass	Mouse Class Driver		
	c:\winnt\system32\drivers\mouclass.sys		
	Kernel Driver	True	System
	Running	OK	Normal
	True	False	False
mouhid	Mouse HID Driver		
	c:\winnt\system32\drivers\mouhid.sys		
	Kernel Driver	True	Manual
	Running	OK	Ignore
	True	False	False
mountmgr	MountMgr		
	c:\winnt\system32\drivers\mountmgr.sys		
	Kernel Driver	True	Boot
	Running	OK	Normal
	True	False	False
mrraid35x	mrraid35x	Not Available	Kernel Driver
	False	Disabled	Stopped
	Normal	False	OK
mrxsm	MRXSMB		
	c:\winnt\system32\drivers\mrxsm.sys		
	File System Driver	True	System
	Running	OK	Normal
	True	False	False
msfs	Msfs		
	c:\winnt\system32\drivers\msfs.sys		
	File System Driver	True	System
	Running	OK	Normal
	True	False	False
mskssrv	Microsoft Streaming Service Proxy		
	c:\winnt\system32\drivers\mskssrv.sys		
	Kernel Driver	False	Manual
	Stopped	OK	Normal
	False	False	False
mspclock	Microsoft Streaming Clock Proxy		
	c:\winnt\system32\drivers\mspclock.sys		
	Kernel Driver	False	Manual
	Stopped	OK	Normal
	False	False	False
mspqm	Microsoft Streaming Quality Manager Proxy		
	c:\winnt\system32\drivers\mspqm.sys		
	Kernel Driver	False	Manual
	Stopped	OK	Normal
	False	False	False
mup	Mup c:\winnt\system32\drivers\mup.sys		
	File System Driver	True	Boot
	Running	OK	Normal
	True	False	False
n100	Compaq Ethernet or Fast Ethernet NIC NT		
	Driver c:\winnt\system32\drivers\n100nt5.sys		
	Kernel Driver	False	Manual
	Stopped	OK	Normal
	False	False	False

```

ncrc710 Ncrc710 Not Available Kernel Driver
False Disabled Stopped OK
Normal False False
ndis NDIS System Driver
c:\winnt\system32\drivers\ndis.sys
Kernel Driver True Boot
Running OK Normal False
True
ndistapi Remote Access NDIS TAPI Driver
c:\winnt\system32\drivers\ndistapi.sys
Kernel Driver True Manual
Running OK Normal False
True
ndisuio NDIS Usermode I/O Protocol
c:\winnt\system32\drivers\ndisuio.sys
Kernel Driver False Manual
Stopped OK Normal False
False
ndiswan Remote Access NDIS WAN Driver
c:\winnt\system32\drivers\ndiswan.sys
Kernel Driver True Manual
Running OK Normal False
True
ndproxy NDIS Proxy
c:\winnt\system32\drivers\ndproxy.sys
Kernel Driver True Manual
Running OK Normal False
True
netbios NetBIOS Interface
c:\winnt\system32\drivers\netbios.sys
File System Driver True System
Running OK Normal False
True
netbt NetBios over Tcpip
c:\winnt\system32\drivers\netbt.sys
Kernel Driver True System
Running OK Normal False
True
netdetect NetDetect
c:\winnt\system32\drivers\netdetect.sys
Kernel Driver False Manual
Stopped OK Normal False
False
npfs Npfs
c:\winnt\system32\drivers\npfs.sys
File System Driver True System
Running OK Normal False
True
ntfs Ntfs
c:\winnt\system32\drivers\ntfs.sys
File System Driver True Disabled
Running OK Normal False
True
null Null
c:\winnt\system32\drivers\null.sys
Kernel Driver True System
Running OK Normal False
True
nwlkflt IPX Traffic Filter Driver
c:\winnt\system32\drivers\nwlkflt.sys
Kernel Driver False Manual
Stopped OK Normal False
False

```

```

nwlkfwfd IPX Traffic Forwarder Driver
c:\winnt\system32\drivers\nwlkfwfd.sys
Kernel Driver False Manual
Stopped OK Normal False
False
openhci Microsoft USB Open Host Controller Driver
c:\winnt\system32\drivers\openhci.sys
Kernel Driver False Manual
Stopped OK Normal False
False
parallel Parallel
c:\winnt\system32\drivers\parallel.sys
Kernel Driver False Auto
Stopped OK Ignore False
False
parport Parport
c:\winnt\system32\drivers\parport.sys
Kernel Driver False Auto
Stopped OK Ignore False
False
partmgr PartMgr
c:\winnt\system32\drivers\partmgr.sys
Kernel Driver True Boot
Running OK Normal False
True
parvdm ParVdm
c:\winnt\system32\drivers\parvdm.sys
Kernel Driver False Auto
Stopped OK Ignore False
False
pci PCI Bus Driver
c:\winnt\system32\drivers\pci.sys
Kernel Driver True Boot
Running OK Critical False
True
pcidump PCIDump Not Available Kernel Driver
False System Stopped OK
Ignore False False
pciide PCIIDE
c:\winnt\system32\drivers\pciide.sys
Kernel Driver True Boot
Running OK Normal False
True
pcmcia Pcmcia
c:\winnt\system32\drivers\pcmcia.sys
Kernel Driver False Disabled
Stopped OK Normal False
False
pdcomp PDCOMP Not Available Kernel Driver
False Manual Stopped OK
Ignore False False
pdframe PDRFRAME Not Available Kernel Driver
False Manual Stopped OK
Ignore False False
pdreli PDRELI Not Available Kernel Driver
False Manual Stopped OK
Ignore False False
pdrframe PDRFRAME Not Available Kernel Driver
False Manual Stopped OK
Ignore False False
pptpminiport WAN Miniport (PPTP)
c:\winnt\system32\drivers\raspptp.sys
Kernel Driver True Manual

```

```

Running OK Normal False
True
ptilink Direct Parallel Link Driver
c:\winnt\system32\drivers\ptilink.sys
Kernel Driver True Manual
Running OK Normal False
True
q57w2k HP NC7782 Gigabit Server Adapter
c:\winnt\system32\drivers\q57w2k.sys
Kernel Driver True Manual
Running OK Normal False
True
ql1080 ql1080 Not Available Kernel Driver
False Disabled Stopped OK
Normal False False
ql10wnt ql10wnt Not Available Kernel Driver
False Disabled Stopped OK
Normal False False
ql1240 ql1240 Not Available Kernel Driver
False Disabled Stopped OK
Normal False False
ql12100 ql12100 Not Available Kernel Driver
False Disabled Stopped OK
Normal False False
rasacd Remote Access Auto Connection Driver
c:\winnt\system32\drivers\rasacd.sys
Kernel Driver True System
Running OK Normal False
True
rasl2tp WAN Miniport (L2TP)
c:\winnt\system32\drivers\rasl2tp.sys
Kernel Driver True Manual
Running OK Normal False
True
raspti Direct Parallel
c:\winnt\system32\drivers\raspti.sys
Kernel Driver True Manual
Running OK Normal False
True
rca Microsoft Streaming Network Raw Channel
Access c:\winnt\system32\drivers\rca.sys
Kernel Driver False Manual
Stopped OK Normal False
False
rdbss Rdbss
c:\winnt\system32\drivers\rdbss.sys
File System Driver True System
Running OK Normal False
True
rdpdr Terminal Server Device Redirector Driver
c:\winnt\system32\drivers\rdpdr.sys
Kernel Driver True Manual
Running OK Normal False
True
rdpwd RDPWD
c:\winnt\system32\drivers\rdpwd.sys
Kernel Driver True Manual
Running OK Ignore False
True
redbook Digital CD Audio Playback Filter Driver
c:\winnt\system32\drivers\redbook.sys
Kernel Driver False System

```

```

Stopped OK Normal False
False
serenum Serenum Filter Driver
c:\winnt\system32\drivers\serenum.sys
Kernel Driver True Manual
Running OK Normal False
True
serial Serial port driver
c:\winnt\system32\drivers\serial.sys
Kernel Driver True System
Running OK Ignore False
True
sfloppy SFloppy
c:\winnt\system32\drivers\sfloppy.sys
Kernel Driver False System
Stopped OK Ignore False
False
sglfb sglfb Not Available Kernel Driver
False System Stopped OK
Normal False False
simbad Simbad Not Available Kernel Driver
False Disabled Stopped OK
Normal False False
sparrow Sparrow Not Available Kernel Driver
False Disabled Stopped OK
Normal False False
spud Special Purpose Utility Driver
c:\winnt\system32\drivers\spud.sys
Kernel Driver True Manual
Running OK Normal False
True
srv Srv c:\winnt\system32\drivers\srv.sys
File System Driver True Manual
Running OK Normal False
True
swenum Software Bus Driver
c:\winnt\system32\drivers\swenum.sys
Kernel Driver True Manual
Running OK Normal False
True
symc810 symc810 Not Available Kernel Driver
False Disabled Stopped OK
Normal False False
symc8xx symc8xx Not Available Kernel Driver
False Disabled Stopped OK
Normal False False
sym_hi sym_hi Not Available Kernel Driver
False Disabled Stopped OK
Normal False False
tcpip TCP/IP Protocol Driver
c:\winnt\system32\drivers\tcpip.sys
Kernel Driver True System
Running OK Normal False
True
tdasync TDASYNC
c:\winnt\system32\drivers\tdasync.sys
Kernel Driver False Manual
Stopped OK Ignore False
False
tdipx TDIPX
c:\winnt\system32\drivers\tdipx.sys
Kernel Driver False Manual

```

```

Stopped OK Ignore False
tdnetb TDNETB
c:\winnt\system32\drivers\tdnetb.sys
Kernel Driver False Manual
Stopped OK Ignore False
False
tdpipe TDPIPE
c:\winnt\system32\drivers\tdpipe.sys
Kernel Driver False Manual
Stopped OK Ignore False
False
tdspix TDSPX
c:\winnt\system32\drivers\tdspix.sys
Kernel Driver False Manual
Stopped OK Ignore False
False
tdtcp TDTCP
c:\winnt\system32\drivers\tdtcp.sys
Kernel Driver True Manual
Running OK Ignore False
True
termdd Terminal Device Driver
c:\winnt\system32\drivers\termdd.sys
Kernel Driver True Auto
Running OK Normal False
True
tga tga Not Available Kernel Driver
False System Stopped OK
Ignore False False
udfs Udfs
c:\winnt\system32\drivers\udfs.sys
File System Driver False Disabled
Stopped OK Normal False
False
uhcd Microsoft USB Universal Host Controller
Driver c:\winnt\system32\drivers\uhcd.sys
Kernel Driver True Manual
Running OK Normal False
True
ultra66 ultra66 Not Available Kernel Driver
False Disabled Stopped OK
Normal False False
update Microcode Update Driver
c:\winnt\system32\drivers\update.sys
Kernel Driver True Manual
Running OK Normal False
True
usbhub Microsoft USB Standard Hub Driver
c:\winnt\system32\drivers\usbhub.sys
Kernel Driver True Manual
Running OK Normal False
True
vgasave VgaSave c:\winnt\system32\drivers\vga.sys
Kernel Driver True System
Running OK Ignore False
True
wanarp Remote Access IP ARP Driver
c:\winnt\system32\drivers\wanarp.sys
Kernel Driver True Manual
Running OK Normal False
True

```

```

wdica WDICA Not Available Kernel Driver
False Manual Stopped OK
Ignore False False

[Environment Variables]

Variable Value User Name
ComSpec %SystemRoot%\system32\cmd.exe <SYSTEM>
Os2LibPath %SystemRoot%\system32\os2\dll;
<SYSTEM>
Path
%SystemRoot%\system32;%SystemRoot%;%SystemR
oot%\System32\Wbem;C:\Program Files\Microsoft SQL
Server\90\Tools\bin\ <SYSTEM>
windir %SystemRoot% <SYSTEM>
OS Windows_NT <SYSTEM>
PROCESSOR_ARCHITECTURE x86 <SYSTEM>
PROCESSOR_LEVEL 15 <SYSTEM>
PROCESSOR_IDENTIFIER x86 Family 15 Model 4
Stepping 1, GenuineIntel <SYSTEM>
PROCESSOR_REVISION 0401 <SYSTEM>
NUMBER_OF_PROCESSORS 4 <SYSTEM>
PATHEXT
.COM;.EXE;.BAT;.CMD;.VBS;.VBE;.JS;.JSE;.WSF
;.WSH <SYSTEM>
TEMP %SystemRoot%\TEMP <SYSTEM>
TMP %SystemRoot%\TEMP <SYSTEM>
lib C:\Program Files\SQLXML 4.0\bin\
<SYSTEM>
TEMP %USERPROFILE%\Local Settings\Temp
CL26\Administrator
TMP %USERPROFILE%\Local Settings\Temp
CL26\Administrator

[Jobs]
[ Following are sub-categories of this main category
]

[Print]

Document Size Owner Notify Status
Time Submitted Start Time
Until Time Elapsed Time
Pages Printed Job ID Priority
Parameters Driver Name
Print Processor Host Print Queue
Data Type Name
Unknown Unknown Unknown Unknown
Unknown Unknown Unknown Unknown
Unknown Unknown Unknown Unknown
Unknown Unknown Unknown Unknown

[Network Connections]

Local Name Remote Name Type
Status User Name
No network connections information

[Running Tasks]

```

Name	Path	Process ID	Priority	Min
Working Set	Version	Max Working Set	File Date	Start Time
system idle process	Not Available	Not Available	0	0
Available	Not Available	Unknown	Unknown	Not
system	Not Available	8	8	0
smss.exe	c:\winnt\system32\smss.exe	192	11	
	204800	1413120	10/26/2005	8:10:39 PM
	5.00.2195.6601	44.77 KB	(45,840 bytes)	
	12/7/1999	7:00:00 AM		
csrss.exe	Not Available	216	13	Not
Available	Not Available	10/26/2005	8:10:41 PM	
	Unknown	Unknown	Unknown	
winlogon.exe	c:\winnt\system32\winlogon.exe			
	212	13	204800	1413120
	10/26/2005	8:10:42 PM		
	5.00.2195.6714	176.77 KB	(181,008 bytes)	
	8/16/2005	1:52:00 PM		
services.exe	c:\winnt\system32\services.exe			
	268	9	204800	1413120
	10/26/2005	8:10:43 PM		
	5.00.2195.6700	87.27 KB	(89,360 bytes)	
	12/7/1999	7:00:00 AM		
lsass.exe	c:\winnt\system32\lsass.exe	280	9	
	204800	1413120	10/26/2005	8:10:43 PM
	5.00.2195.6695	32.77 KB	(33,552 bytes)	
	12/7/1999	7:00:00 AM		
termsrv.exe	c:\winnt\system32\termsrv.exe	392		
	10	204800	1413120	10/26/2005
	8:10:43 PM	5.00.2195.6696	139.27 KB	
	(142,608 bytes)	8/16/2005	1:51:58 PM	
aclnt.exe	c:\program			
files\altiris\aclnt\aclnt.exe		464	8	
	204800	1413120	10/26/2005	8:10:44 PM
	6.1.401	4.63 MB	(4,857,932 bytes)	
	6/5/2003	1:55:46 PM		
regsvcs.exe	c:\winnt\system32\regsvcs.exe	492		
	8	204800	1413120	10/26/2005
	8:10:44 PM	5.00.2195.6701	66.77 KB	
	(68,368 bytes)	8/16/2005	1:51:54 PM	
rsys.exe	c:\benchcraft\rsys.exe	516	8	
	204800	1413120	10/26/2005	8:10:44 PM
	Not Available	32.00 KB	(32,768 bytes)	
	9/13/2002	6:30:57 PM		
svchost.exe	c:\winnt\system32\svchost.exe	544		
	8	204800	1413120	10/26/2005
	8:10:44 PM	5.00.2134.1	7.77 KB	
	(7,952 bytes)	12/7/1999	7:00:00 AM	
svchost.exe	c:\winnt\system32\svchost.exe	656		
	8	204800	1413120	10/26/2005
	8:10:48 PM	5.00.2134.1	7.77 KB	
	(7,952 bytes)	12/7/1999	7:00:00 AM	
mstask.exe	c:\winnt\system32\mstask.exe	684		
	8	204800	1413120	10/26/2005
	8:10:48 PM	4.71.2195.6704	116.77 KB	
	(119,568 bytes)	8/16/2005	1:51:49 PM	
winmgmt.exe	c:\winnt\system32\wbem\winmgmt.exe	728		
	8	204800	1413120	10/26/2005

8:10:48 PM	1.50.1085.0100	192.10 KB		
(196,706 bytes)	8/16/2005	1:52:03 PM		
inetinfo.exe	c:\winnt\system32\inetinfo.exe	744		
	8	204800	1413120	10/26/2005
	8:10:49 PM	5.00.0984	14.27 KB	(14,608 bytes)
	8/16/2005	1:52:12 PM		
dfssvc.exe	c:\winnt\system32\dfssvc.exe	732		
	8	204800	1413120	10/26/2005
	8:10:53 PM	5.00.2195.6664	88.77 KB	
	(90,896 bytes)	8/16/2005	1:51:38 PM	
svchost.exe	c:\winnt\system32\svchost.exe			
	1060	8	204800	1413120
	10/26/2005	8:11:04 PM	5.00.2134.1	
	7.77 KB	(7,952 bytes)	12/7/1999	
7:00:00 AM				
dllhost.exe	Not Available	580	8	
	Not Available	Not Available		
	10/26/2005	8:13:42 PM	Unknown	
	Unknown	Unknown		
logon.scr	c:\winnt\system32\logon.scr	792	4	
	204800	1413120	10/26/2005	8:25:54 PM
	5.00.2195.6601	127.77 KB	(130,832 bytes)	
	8/16/2005	1:51:44 PM		
csrss.exe	Not Available	6288	13	Not
Available	Not Available	10/27/2005	9:12:55 AM	
	Unknown	Unknown	Unknown	
winlogon.exe	c:\winnt\system32\winlogon.exe			
	6276	13	204800	1413120
	10/27/2005	9:12:55 AM		
	5.00.2195.6714	176.77 KB	(181,008 bytes)	
	8/16/2005	1:52:00 PM		
rdpclip.exe	c:\winnt\system32\rdpclip.exe			
	2004	8	204800	1413120
	10/27/2005	9:12:57 AM	5.00.2174.1	
	39.77 KB	(40,720 bytes)	9/13/2002	
5:45:10 PM				
explorer.exe	c:\winnt\explorer.exe			
	5732	8	204800	1413120
	10/27/2005	9:12:57 AM		
	5.00.3700.6690	237.77 KB	(243,472 bytes)	
	8/16/2005	1:52:01 PM		
aclntusr.exe	c:\program			
files\altiris\aclnt\aclntusr.exe		4228	8	
	204800	1413120	10/27/2005	9:12:59 AM
	6, 1, 401	180.00 KB	(184,320 bytes)	
	6/5/2003	1:55:47 PM		
tardis.exe	c:\program files\tardis 2000			
v1.4\tardis.exe		5116	8	204800
	1413120	10/27/2005	9:12:59 AM	5,
	0, 1, 4	308.00 KB	(315,392 bytes)	9/13/2002
	6:21:25 PM			
mmc.exe	c:\winnt\system32\mmc.exe	2852	8	
	204800	1413120	10/27/2005	9:13:02 AM
	5.00.2195.6601	589.27 KB	(603,408 bytes)	
	8/16/2005	1:51:45 PM		
rsvp.exe	c:\winnt\system32\rsvp.exe	2284	8	
	204800	1413120	10/27/2005	9:14:03 AM
	5.00.2195.6663	172.77 KB	(176,912 bytes)	
	8/16/2005	1:51:55 PM		
[Loaded Modules]				

Name	Version	Size	File Date	Manufacturer
traffic.dll	5.00.2195.6613	30.77 KB		
(31,504 bytes)	8/16/2005	1:51:58 PM		
	Microsoft Corporation			
c:\winnt\system32\traffic.dll				
rsvp.exe	5.00.2195.6663	172.77 KB	(176,912 bytes)	
	8/16/2005	1:51:55 PM		Microsoft Corporation
c:\winnt\system32\rsvp.exe				
wbemprox.dll	1.50.1085.0100	40.10 KB	(41,061 bytes)	
	8/16/2005	1:52:03 PM		Microsoft Corporation
c:\winnt\system32\wbem\wbemprox.dll				
mlang.dll	5.00.3700.6655	510.77 KB	(523,024 bytes)	
	8/16/2005	1:51:45 PM		Microsoft Corporation
c:\winnt\system32\mlang.dll				
cabinet.dll	5.00.2147.1	54.77 KB	(56,080 bytes)	
	12/7/1999	7:00:00 AM		Microsoft Corporation
c:\winnt\system32\cabinet.dll				
msinfo32.dll	5.00.2195.6601	312.27 KB	(319,760 bytes)	
	8/16/2005	1:52:05 PM		Microsoft Corporation
c:\program				
files\common files\microsoft				
shared\msinfo\msinfo32.dll				
mmcndmgr.dll	5.00.2195.6601	816.27 KB	(835,856 bytes)	
	8/16/2005	1:51:45 PM		Microsoft Corporation
c:\winnt\system32\mmcndmgr.dll				
msvcps50.dll	5.00.7051	552.50 KB	(565,760 bytes)	
	12/7/1999	7:00:00 AM		Microsoft Corporation
c:\winnt\system32\msvcps50.dll				
mmc.exe	5.00.2195.6601	589.27 KB	(603,408 bytes)	
	8/16/2005	1:51:45 PM		Microsoft Corporation
c:\winnt\system32\mmc.exe				
rapilib.dll	5.00.2195.6601	24.77 KB	(25,360 bytes)	
	8/16/2005	1:51:54 PM		Microsoft Corporation
c:\winnt\system32\rapilib.dll				
rsvsp.dll	5.00.2195.6611	75.27 KB	(77,072 bytes)	
	8/16/2005	1:51:55 PM		Microsoft Corporation
c:\winnt\system32\rsvsp.dll				
tardis.exe	5, 0, 1, 4	308.00 KB	(315,392 bytes)	
	9/13/2002	6:21:25 PM		H.C.Mingham-Smith Ltd.
c:\program				
files\tardis 2000 v1.4\tardis.exe				
aclntusr.exe	6, 1, 401	180.00 KB	(184,320 bytes)	
	6/5/2003	1:55:47 PM		Microsoft Corporation
c:\program				
files\altiris\aclnt\aclntusr.exe				
shdoclc.dll	5.00.3700.6668	324.50 KB	(332,288 bytes)	
	8/16/2005	1:51:56 PM		Microsoft Corporation
c:\winnt\system32\shdoclc.dll				
faxshell.dll	5.00.2134.1	8.27 KB	(8,464 bytes)	
	12/7/1999	7:00:00 AM		Microsoft Corporation
c:\winnt\system32\faxshell.dll				
msacm32.dll	5.00.2134.1	65.27 KB	(66,832 bytes)	
	12/7/1999	7:00:00 AM		Microsoft Corporation
c:\winnt\system32\msacm32.dll				

avifil32.dll 5.00.2195.6612 76.77 KB
(78,608 bytes) 8/16/2005 1:51:34 PM
Microsoft Corporation
c:\winnt\system32\avifil32.dll
msvfw32.dll 5.00.2195.6612 113.77 KB
(116,496 bytes) 8/16/2005 1:51:49 PM
Microsoft Corporation
c:\winnt\system32\msvfw32.dll
docprop2.dll 5.00.2178.1 297.77 KB
(304,912 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\docprop2.dll
linkinfo.dll 5.00.2134.1 15.77 KB
(16,144 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\linkinfo.dll
powrprof.dll 5.00.3502.6601 13.27 KB
(13,584 bytes) 8/16/2005 1:51:53 PM
Microsoft Corporation
c:\winnt\system32\powrprof.dll
batmeter.dll 5.00.3502.6601 20.27 KB
(20,752 bytes) 8/16/2005 1:51:34 PM
Microsoft Corporation
c:\winnt\system32\batmeter.dll
stobject.dll 5.00.2195.6601 79.27 KB
(81,168 bytes) 8/16/2005 1:51:57 PM
Microsoft Corporation
c:\winnt\system32\stobject.dll
msi.dll 3.1.4000.2435 2.76 MB (2,890,240
bytes) 8/16/2005 1:51:47 PM
Microsoft Corporation
c:\winnt\system32\msi.dll
webcheck.dll 5.00.3502.6601 251.77 KB
(257,808 bytes) 8/16/2005 1:51:59 PM
Microsoft Corporation
c:\winnt\system32\webcheck.dll
ntshrui.dll 5.00.2134.1 46.77 KB
(47,888 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\ntshrui.dll
mydocs.dll 5.00.3502.6601 55.77 KB
(57,104 bytes) 8/16/2005 1:51:50 PM
Microsoft Corporation
c:\winnt\system32\mydocs.dll
browseui.dll 5.00.3700.6661 789.27 KB
(808,208 bytes) 8/16/2005 1:51:34 PM
Microsoft Corporation
c:\winnt\system32\browseui.dll
shdocvw.dll 5.00.3700.6668 1.06 MB
(1,107,728 bytes) 8/16/2005 1:51:56 PM
Microsoft Corporation
c:\winnt\system32\shdocvw.dll
explorer.exe 5.00.3700.6690 237.77 KB
(243,472 bytes) 8/16/2005 1:52:01 PM
Microsoft Corporation
c:\winnt\explorer.exe
rdpclip.exe 5.00.2174.1 39.77 KB
(40,720 bytes) 9/13/2002 5:45:10 PM
Microsoft Corporation
c:\winnt\system32\rdpclip.exe
wzcsapi.dll 5.00.2195.6604 29.27 KB
(29,968 bytes) 8/16/2005 1:52:10 PM
Microsoft Corporation
c:\winnt\system32\wzcsapi.dll

wzcdlg.dll 5.00.2195.6604 51.27 KB
(52,496 bytes) 8/16/2005 1:52:10 PM
Microsoft Corporation
c:\winnt\system32\wzcdlg.dll
cscui.dll 5.00.2195.6705 237.27 KB (242,960
bytes) 8/16/2005 1:51:37 PM
Microsoft Corporation
c:\winnt\system32\cscui.dll
logon.scr 5.00.2195.6601 127.77 KB (130,832
bytes) 8/16/2005 1:51:44 PM
Microsoft Corporation
c:\winnt\system32\logon.scr
h323.tsp 5.00.2195.6699 248.77 KB (254,736
bytes) 8/16/2005 1:51:40 PM
Microsoft Corporation
c:\winnt\system32\h323.tsp
ipconf.tsp 5.00.2143.1 10.77 KB
(11,024 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\ipconf.tsp
ndptsp.tsp 5.00.2143.1 38.27 KB
(39,184 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\ndptsp.tsp
kmddsp.tsp 5.00.2150.1 17.77 KB
(18,192 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\kmddsp.tsp
uniplat.dll 5.00.2195.6601 14.27 KB
(14,608 bytes) 8/16/2005 1:51:58 PM
Microsoft Corporation
c:\winnt\system32\uniplat.dll
unimdm.tsp 5.00.2195.6601 199.27 KB
(204,048 bytes) 8/16/2005 1:51:58 PM
Microsoft Corporation
c:\winnt\system32\unimdm.tsp
tapisrv.dll 5.00.2195.6666 169.27 KB
(173,328 bytes) 8/16/2005 1:51:58 PM
Microsoft Corporation
c:\winnt\system32\tapisrv.dll
dfssvc.exe 5.00.2195.6664 88.77 KB
(90,896 bytes) 8/16/2005 1:51:38 PM
Microsoft Corporation
c:\winnt\system32\dfssvc.exe
dbnetlib.dll 2000.080.0194.00 84.06 KB
(86,082 bytes) 9/13/2002 6:19:43 PM
Microsoft Corporation
c:\winnt\system32\dbnetlib.dll
odbccp32.dll 3.520.6526.0 100.27 KB
(102,672 bytes) 9/13/2002 6:19:39 PM
Microsoft Corporation
c:\winnt\system32\odbccp32.dll
sqlsrv32.rll 2000.080.0194.00 88.00 KB
(90,112 bytes) 9/13/2002 6:19:44 PM
Microsoft Corporation
c:\winnt\system32\sqlsrv32.rll
mtxdm.dll 2000.2.3504.0 22.77 KB (23,312 bytes)
8/16/2005 1:51:50 PM
Microsoft Corporation
c:\winnt\system32\mtxdm.dll
sqlunirl.dll 2000.080.0194.00 176.06 KB
(180,290 bytes) 8/6/2000 1:51:56 AM
Microsoft Corporation
c:\winnt\system32\sqlunirl.dll
sqlsrv32.dll 2000.080.0194.00 460.08 KB
(471,119 bytes) 9/13/2002 6:19:44 PM
Microsoft Corporation
c:\winnt\system32\sqlsrv32.dll

tpcc_com_all.dll 1, 0, 0, 1 104.00 KB
(106,496 bytes) 9/13/2002 6:29:44 PM
c:\inetpub\wwwroot\tpcc_com_all.dll
tpcc_odbc.dll Not Available 20.00 KB
(20,480 bytes) 6/1/2005 11:49:37 PM
Not Available c:\inetpub\wwwroot\tpcc_odbc.dll
msvcr70.dll 7.00.9466.0 336.00 KB
(344,064 bytes) 6/1/2005 11:48:32 PM
Microsoft Corporation
c:\winnt\system32\msvcr70.dll
mfc42.dll 6.00.9586.0 992.05 KB (1,015,859
bytes) 8/16/2005 1:51:44 PM
Microsoft Corporation
c:\winnt\system32\mfc42.dll
wam.dll 5.00.0984 70.77 KB (72,464 bytes)
8/16/2005 1:52:13 PM
Microsoft Corporation
c:\winnt\system32\inetsrv\wam.dll
odbcint.dll 3.520.6526.0 88.00 KB
(90,112 bytes) 9/13/2002 6:19:39 PM
Microsoft Corporation
c:\winnt\system32\odbcint.dll
odbc32.dll 3.520.6526.0 216.27 KB
(221,456 bytes) 9/13/2002 6:19:39 PM
Microsoft Corporation
c:\winnt\system32\odbc32.dll
mtxoci.dll 2000.2.3504.0 103.27 KB
(105,744 bytes) 8/16/2005 1:51:50 PM
Microsoft Corporation
c:\winnt\system32\mtxoci.dll
resutils.dll 5.00.2195.6702 39.77 KB
(40,720 bytes) 8/16/2005 1:51:54 PM
Microsoft Corporation
c:\winnt\system32\resutils.dll
clusapi.dll 5.00.2195.6683 54.27 KB
(55,568 bytes) 8/16/2005 1:51:35 PM
Microsoft Corporation
c:\winnt\system32\clusapi.dll
mtxclu.dll 2000.2.3504.0 51.27 KB
(52,496 bytes) 8/16/2005 1:51:50 PM
Microsoft Corporation
c:\winnt\system32\mtxclu.dll
msdtcprx.dll 2000.2.3504.0 690.77 KB
(707,344 bytes) 8/16/2005 1:51:46 PM
Microsoft Corporation
c:\winnt\system32\msdtcprx.dll
comsvcs.dll 2000.2.3504.0 1.38 MB
(1,448,208 bytes) 8/16/2005 1:51:36 PM
Microsoft Corporation
c:\winnt\system32\comsvcs.dll
iislog.dll 5.00.0984 75.27 KB (77,072 bytes)
8/16/2005 1:52:12 PM
Microsoft Corporation
c:\winnt\system32\inetsrv\iislog.dll
inetsloc.dll 5.00.0984 20.27 KB (20,752 bytes)
8/16/2005 1:51:42 PM
Microsoft Corporation
c:\winnt\system32\inetsloc.dll
isatq.dll 5.00.0984 61.27 KB (62,736 bytes)
8/16/2005 1:52:12 PM
Microsoft Corporation
c:\winnt\system32\inetsrv\isatq.dll
security.dll 5.00.2154.1 5.77 KB
(5,904 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\security.dll

svcxext.dll 5.00.0984 39.77 KB (40,720 bytes)
 8/16/2005 1:52:13 PM Microsoft Corporation
 c:\winnt\system32\inetsrv\svcxext.dll
 admx.exe 5.00.0984 27.77 KB (28,432 bytes)
 8/16/2005 1:52:11 PM Microsoft Corporation
 c:\winnt\system32\inetsrv\admx.exe
 wamreg.dll 5.00.0984 45.77 KB (46,864 bytes)
 8/16/2005 1:52:13 PM Microsoft Corporation
 c:\winnt\system32\inetsrv\wamreg.dll
 metadata.dll 5.00.0984 68.77 KB (70,416 bytes)
 8/16/2005 1:52:13 PM Microsoft Corporation
 c:\winnt\system32\inetsrv\metadata.dll
 iismap.dll 5.00.0984 56.27 KB (57,616 bytes)
 8/16/2005 1:51:42 PM Microsoft Corporation
 c:\winnt\system32\iismap.dll
 nsepm.dll 5.00.0984 43.27 KB (44,304 bytes)
 8/16/2005 1:52:13 PM Microsoft Corporation
 c:\winnt\system32\inetsrv\nsepm.dll
 admwprox.dll 5.00.0984 31.77 KB (32,528 bytes)
 9/13/2002 5:45:33 PM Microsoft Corporation
 c:\winnt\system32\admwprox.dll
 coadmin.dll 5.00.0984 39.77 KB (40,720 bytes)
 8/16/2005 1:52:12 PM Microsoft Corporation
 c:\winnt\system32\inetsrv\coadmin.dll
 iisadmin.dll 5.00.0984 15.77 KB (16,144 bytes)
 8/16/2005 1:52:12 PM Microsoft Corporation
 c:\winnt\system32\inetsrv\iisadmin.dll
 rpcpref.dll 5.00.0984 4.27 KB (4,368 bytes)
 8/16/2005 1:52:13 PM Microsoft Corporation
 c:\winnt\system32\inetsrv\rpcpref.dll
 iisrtr.dll 5.00.0984 121.27 KB (124,176 bytes)
 8/16/2005 1:51:42 PM Microsoft Corporation
 c:\winnt\system32\iisrtr.dll
 inetinfo.exe 5.00.0984 14.27 KB (14,608 bytes)
 8/16/2005 1:52:12 PM Microsoft Corporation
 c:\winnt\system32\inetsrv\inetinfo.exe
 netui.dll 5.00.2134.1 210.27 KB (215,312 bytes)
 12/7/1999 7:00:00 AM Microsoft Corporation
 c:\winnt\system32\netui.dll
 netui0.dll 5.00.2195.6601 70.27 KB (71,952 bytes)
 8/16/2005 1:51:51 PM Microsoft Corporation
 c:\winnt\system32\netui0.dll
 ntlanman.dll 5.00.2195.6601 35.27 KB (36,112 bytes)
 12/7/1999 7:00:00 AM Microsoft Corporation
 c:\winnt\system32\ntlanman.dll
 wshnetbs.dll 5.00.2134.1 7.77 KB (7,952 bytes)
 12/7/1999 7:00:00 AM Microsoft Corporation
 c:\winnt\system32\wshnetbs.dll
 perfos.dll 5.00.2155.1 21.27 KB (21,776 bytes)
 12/7/1999 7:00:00 AM

Microsoft Corporation
 c:\winnt\system32\perfos.dll
 provthrd.dll 1.50.1085.0000 68.07 KB (69,708 bytes)
 9/13/2002 5:45:53 PM Microsoft Corporation
 c:\winnt\system32\wbem\provthrd.dll
 ntevt.dll 1.50.1085.0072 192.06 KB (196,671 bytes)
 8/16/2005 1:52:03 PM Microsoft Corporation
 c:\winnt\system32\wbem\ntevt.dll
 framedyn.dll 1.50.1085.0076 164.07 KB (168,009 bytes)
 8/16/2005 1:52:02 PM Microsoft Corporation
 c:\winnt\system32\wbem\framedyn.dll
 cimwin32.dll 1.50.1085.0103 1.04 MB (1,089,637 bytes)
 8/16/2005 1:52:02 PM Microsoft Corporation
 c:\winnt\system32\wbem\cimwin32.dll
 wbemsvc.dll 1.50.1085.0007 40.07 KB (41,036 bytes)
 8/16/2005 1:52:03 PM Microsoft Corporation
 c:\winnt\system32\wbem\wbemsvc.dll
 wbemess.dll 1.50.1085.0100 364.09 KB (372,825 bytes)
 8/16/2005 1:52:03 PM Microsoft Corporation
 c:\winnt\system32\wbem\wbemess.dll
 fastprox.dll 1.50.1085.0100 152.10 KB (155,749 bytes)
 8/16/2005 1:52:02 PM Microsoft Corporation
 c:\winnt\system32\wbem\fastprox.dll
 wbemcore.dll 1.50.1085.0100 632.09 KB (647,257 bytes)
 8/16/2005 1:52:03 PM Microsoft Corporation
 c:\winnt\system32\wbem\wbemcore.dll
 wbemcom.dll 1.50.1085.0100 692.09 KB (708,696 bytes)
 8/16/2005 1:52:03 PM Microsoft Corporation
 c:\winnt\system32\wbem\wbemcom.dll
 winmgmt.exe 1.50.1085.0100 192.10 KB (196,706 bytes)
 8/16/2005 1:52:03 PM Microsoft Corporation
 c:\winnt\system32\wbem\winmgmt.exe
 msidle.dll 5.00.2920.0000 6.27 KB (6,416 bytes)
 12/7/1999 7:00:00 AM Microsoft Corporation
 c:\winnt\system32\msidle.dll
 mstask.exe 4.71.2195.6704 116.77 KB (119,568 bytes)
 8/16/2005 1:51:49 PM Microsoft Corporation
 c:\winnt\system32\mstask.exe
 wmi.dll 5.00.2191.1 6.27 KB (6,416 bytes)
 12/7/1999 7:00:00 AM Microsoft Corporation
 c:\winnt\system32\wmi.dll
 netshell.dll 5.00.2195.6604 466.27 KB (477,456 bytes)
 8/16/2005 1:51:51 PM Microsoft Corporation
 c:\winnt\system32\netshell.dll
 netman.dll 5.00.2195.6660 93.27 KB (95,504 bytes)
 8/16/2005 1:51:51 PM Microsoft Corporation
 c:\winnt\system32\netman.dll
 ntmsdba.dll 5.00.2195.6655 169.27 KB (173,328 bytes)
 8/16/2005 1:51:52 PM

Microsoft Corporation
 c:\winnt\system32\ntmsdba.dll
 ipbootp.dll 5.00.2168.1 33.77 KB (34,576 bytes)
 12/7/1999 7:00:00 AM Microsoft Corporation
 c:\winnt\system32\ipbootp.dll
 cryptui.dll 5.131.2195.6628 433.27 KB (443,664 bytes)
 8/16/2005 1:51:37 PM Microsoft Corporation
 c:\winnt\system32\cryptui.dll
 rastls.dll 5.00.2195.6680 98.27 KB (100,624 bytes)
 8/16/2005 1:51:54 PM Microsoft Corporation
 c:\winnt\system32\rastls.dll
 raschap.dll 5.00.2195.6663 59.27 KB (60,688 bytes)
 8/16/2005 1:51:54 PM Microsoft Corporation
 c:\winnt\system32\raschap.dll
 rasppp.dll 5.00.2195.6626 194.27 KB (198,928 bytes)
 8/16/2005 1:51:54 PM Microsoft Corporation
 c:\winnt\system32\rasppp.dll
 rastapi.dll 5.00.2195.6604 52.77 KB (54,032 bytes)
 12/7/1999 7:00:00 AM Microsoft Corporation
 c:\winnt\system32\rastapi.dll
 rasdlg.dll 5.00.2195.6625 516.77 KB (529,168 bytes)
 12/7/1999 7:00:00 AM Microsoft Corporation
 c:\winnt\system32\rasdlg.dll
 netcfgx.dll 5.00.2195.6604 534.77 KB (547,600 bytes)
 8/16/2005 1:51:50 PM Microsoft Corporation
 c:\winnt\system32\netcfgx.dll
 rasman.dll 5.00.2195.6696 149.77 KB (153,360 bytes)
 8/16/2005 1:51:54 PM Microsoft Corporation
 c:\winnt\system32\rasman.dll
 sens.dll 5.00.2195.6627 37.27 KB (38,160 bytes)
 8/16/2005 1:51:55 PM Microsoft Corporation
 c:\winnt\system32\sens.dll
 ntmsvc.dll 5.00.2195.6655 391.77 KB (401,168 bytes)
 8/16/2005 1:51:52 PM Microsoft Corporation
 c:\winnt\system32\ntmsvc.dll
 txfaux.dll 2000.2.3504.0 388.27 KB (397,584 bytes)
 8/16/2005 1:51:58 PM Microsoft Corporation
 c:\winnt\system32\txfaux.dll
 es.dll 2000.2.3504.0 227.77 KB (233,232 bytes)
 8/16/2005 1:51:39 PM Microsoft Corporation
 c:\winnt\system32\es.dll
 clbcatq.dll 2000.2.3504.0 498.27 KB (510,224 bytes)
 8/16/2005 1:51:35 PM Microsoft Corporation
 c:\winnt\system32\clbcatq.dll
 rpcss.dll 5.00.2195.6702 233.77 KB (239,376 bytes)
 8/16/2005 1:51:55 PM Microsoft Corporation
 c:\winnt\system32\rpcss.dll
 svchost.exe 5.00.2134.1 7.77 KB (7,952 bytes)
 12/7/1999 7:00:00 AM Microsoft Corporation
 c:\winnt\system32\svchost.exe

```

rsys.exe Not Available 32.00 KB (32,768 bytes)
9/13/2002 6:30:57 PM Not Available
c:\benchcraft\rsys.exe
regsvcs.exe 5.00.2195.6701 66.77 KB
(68,368 bytes) 8/16/2005 1:51:54 PM
Microsoft Corporation
c:\winnt\system32\regsvcs.exe
ntmarta.dll 5.00.2195.6666 100.27 KB
(102,672 bytes) 8/16/2005 1:51:52 PM
Microsoft Corporation
c:\winnt\system32\ntmarta.dll
psapi.dll 5.00.2134.1 28.27 KB (28,944 bytes)
12/7/1999 7:00:00 AM Microsoft
Corporation c:\winnt\system32\psapi.dll
riched20.dll 5.30.23.1215 421.77 KB
(431,888 bytes) 8/16/2005 1:51:54 PM
Microsoft Corporation
c:\winnt\system32\riched20.dll
riched32.dll 5.00.2134.1 3.77 KB
(3,856 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\riched32.dll
comdlg32.dll 5.00.3700.6693 235.77 KB
(241,424 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\comdlg32.dll
aclient.exe 6.1.401 4.63 MB (4,857,932
bytes) 6/5/2003 1:55:46 PM Altiris, Inc.
c:\program
files\altiris\aclient\aclient.exe
rdpwsx.dll 5.00.2195.6697 97.90 KB
(100,248 bytes) 8/16/2005 1:51:54 PM
Microsoft Corporation
c:\winnt\system32\rdpwsx.dll
mstlsapi.dll 5.00.2195.6659 25.77 KB
(26,384 bytes) 8/16/2005 1:51:49 PM
Microsoft Corporation
c:\winnt\system32\mstlsapi.dll
icaapi.dll 5.00.2195.6654 122.77 KB
(125,712 bytes) 8/16/2005 1:51:41 PM
Microsoft Corporation
c:\winnt\system32\icaapi.dll
regapi.dll 5.00.2195.6602 35.27 KB
(36,112 bytes) 8/16/2005 1:51:54 PM
Microsoft Corporation
c:\winnt\system32\regapi.dll
termsrv.exe 5.00.2195.6696 139.27 KB
(142,608 bytes) 8/16/2005 1:51:58 PM
Microsoft Corporation
c:\winnt\system32\termsrv.exe
iissuba.dll 5.00.0984 9.77 KB (10,000 bytes)
12/7/1999 7:00:00 AM Microsoft
Corporation c:\winnt\system32\iissuba.dll
dssenh.dll 5.00.2195.6612 143.77 KB
(147,216 bytes) 8/16/2005 1:52:09 PM
Microsoft Corporation
c:\winnt\system32\dssenh.dll
oakley.dll 5.00.2195.6662 435.77 KB
(446,224 bytes) 8/16/2005 1:51:52 PM
Microsoft Corporation
c:\winnt\system32\oakley.dll
mfc42u.dll 6.00.9586.0 988.05 KB
(1,011,764 bytes) 8/16/2005 1:51:44 PM

```

```

Microsoft Corporation
c:\winnt\system32\mfc42u.dll
polagent.dll 5.00.2195.6655 109.27 KB
(111,888 bytes) 8/16/2005 1:51:53 PM
Microsoft Corporation
c:\winnt\system32\polagent.dll
scecli.dll 5.00.2195.6704 111.77 KB
(114,448 bytes) 8/16/2005 1:51:55 PM
Microsoft Corporation
c:\winnt\system32\scecli.dll
mswsock.dll 5.00.2195.6603 62.77 KB
(64,272 bytes) 8/16/2005 1:51:50 PM
Microsoft Corporation
c:\winnt\system32\mswsock.dll
ntdsatq.dll 5.00.2195.6620 31.27 KB
(32,016 bytes) 8/16/2005 1:51:51 PM
Microsoft Corporation
c:\winnt\system32\ntdsatq.dll
ntdsa.dll 5.00.2195.6697 1016.27 KB (1,040,656
bytes) 8/16/2005 1:51:51 PM Microsoft
Corporation c:\winnt\system32\ntdsa.dll
kdcsvc.dll 5.00.2195.6627 144.77 KB
(148,240 bytes) 8/16/2005 1:51:44 PM
Microsoft Corporation
c:\winnt\system32\kdcsvc.dll
sfmapi.dll 5.00.2134.1 38.77 KB
(39,696 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\sfmapi.dll
rassfm.dll 5.00.2195.6604 21.27 KB
(21,776 bytes) 8/16/2005 1:51:54 PM
Microsoft Corporation
c:\winnt\system32\rassfm.dll
rsabase.dll 5.00.2195.6619 129.27 KB
(132,368 bytes) 6/19/2003 12:05:04 PM
Microsoft Corporation
c:\winnt\system32\rsabase.dll
schannel.dll 5.00.2195.6705 144.27 KB
(147,728 bytes) 5/4/2001 12:05:02 PM
Microsoft Corporation
c:\winnt\system32\schannel.dll
netlogon.dll 5.00.2195.6695 363.27 KB
(371,984 bytes) 8/16/2005 1:51:50 PM
Microsoft Corporation
c:\winnt\system32\netlogon.dll
kerberos.dll 5.00.2195.6666 207.77 KB
(212,752 bytes) 8/16/2005 1:51:44 PM
Microsoft Corporation
c:\winnt\system32\kerberos.dll
msprivs.dll 5.00.2195.6695 46.00 KB
(47,104 bytes) 8/16/2005 1:51:48 PM
Microsoft Corporation
c:\winnt\system32\msprivs.dll
samsvr.dll 5.00.2195.6697 380.77 KB
(389,904 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\samsvr.dll
lsasrv.dll 5.00.2195.6695 506.77 KB
(518,928 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\lsasrv.dll

```

```

lsass.exe 5.00.2195.6695 32.77 KB (33,552 bytes)
12/7/1999 7:00:00 AM Microsoft
Corporation c:\winnt\system32\lsass.exe
esent.dll 6.1.3940.31 1.08 MB (1,135,376
bytes) 8/16/2005 1:51:39 PM Microsoft
Corporation c:\winnt\system32\esent.dll
xactsrv.dll 5.00.2195.6662 90.27 KB
(92,432 bytes) 8/16/2005 1:52:00 PM
Microsoft Corporation
c:\winnt\system32\xactsrv.dll
ntleapi.dll 5.00.2195.6601 6.77 KB
(6,928 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\ntleapi.dll
wmiexec.dll 5.00.2195.6611 72.77 KB
(74,512 bytes) 8/16/2005 1:52:00 PM
Microsoft Corporation
c:\winnt\system32\wmiexec.dll
browser.dll 5.00.2195.6693 67.27 KB
(68,880 bytes) 8/16/2005 1:51:34 PM
Microsoft Corporation
c:\winnt\system32\browser.dll
trkwns.dll 5.00.2195.6623 88.27 KB
(90,384 bytes) 8/16/2005 1:51:58 PM
Microsoft Corporation
c:\winnt\system32\trkwns.dll
psbase.dll 5.00.2195.6661 112.77 KB
(115,472 bytes) 8/16/2005 1:51:53 PM
Microsoft Corporation
c:\winnt\system32\psbase.dll
cryptsvc.dll 5.00.2195.6661 74.27 KB
(76,048 bytes) 8/16/2005 1:51:37 PM
Microsoft Corporation
c:\winnt\system32\cryptsvc.dll
cfgmgr32.dll 5.00.2134.1 16.77 KB
(17,168 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\cfgmgr32.dll
dmserver.dll 2195.6605.297.3 11.77 KB
(12,048 bytes) 8/16/2005 1:51:38 PM
VERITAS Software Corp.
c:\winnt\system32\dmserver.dll
seclogon.dll 5.00.2195.6707 16.77 KB
(17,168 bytes) 8/16/2005 1:51:55 PM
Microsoft Corporation
c:\winnt\system32\seclogon.dll
cryptdll.dll 5.00.2195.6607 43.27 KB
(44,304 bytes) 8/16/2005 1:51:37 PM
Microsoft Corporation
c:\winnt\system32\cryptdll.dll
wkssvc.dll 5.00.2195.6692 95.77 KB
(98,064 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\wkssvc.dll
srvsrv.dll 5.00.2195.6697 81.77 KB
(83,728 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\srvsrv.dll
eventlog.dll 5.00.2195.6716 46.77 KB
(47,888 bytes) 8/16/2005 1:51:40 PM
Microsoft Corporation
c:\winnt\system32\eventlog.dll

```

```

scesrv.dll 5.00.2195.6704 248.77 KB
(254,736 bytes) 8/16/2005 1:51:55 PM
Microsoft Corporation
c:\winnt\system32\scesrv.dll
umpnpgmr.dll 5.00.2182.1 86.27 KB
(88,336 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\umpnpgmr.dll
services.exe 5.00.2195.6700 87.27 KB
(89,360 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\services.exe
wininet.dll 5.00.3700.6713 455.77 KB
(466,704 bytes) 8/16/2005 1:52:00 PM
Microsoft Corporation
c:\winnt\system32\wininet.dll
cryptnet.dll 5.131.2195.6601 42.27 KB
(43,280 bytes) 8/16/2005 1:51:37 PM
Microsoft Corporation
c:\winnt\system32\cryptnet.dll
msv1_0.dll 5.00.2195.6680 114.77 KB
(117,520 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\msv1_0.dll
ntdsapi.dll 5.00.2195.6666 56.27 KB
(57,616 bytes) 8/16/2005 1:51:51 PM
Microsoft Corporation
c:\winnt\system32\ntdsapi.dll
rasadhlp.dll 5.00.2168.1 7.27 KB
(7,440 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\rasadhlp.dll
winrnr.dll 5.00.2160.1 18.77 KB
(19,216 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\winrnr.dll
rnr20.dll 5.00.2195.6603 35.77 KB (36,624 bytes)
8/16/2005 1:51:55 PM Microsoft
Corporation c:\winnt\system32\rnr20.dll
dhcpcsvc.dll 5.00.2195.6685 90.77 KB
(92,944 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\dhcpcsvc.dll
tapi32.dll 5.00.2195.6664 123.77 KB
(126,736 bytes) 8/16/2005 1:51:57 PM
Microsoft Corporation
c:\winnt\system32\tapi32.dll
rasman.dll 5.00.2195.6604 54.77 KB
(56,080 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\rasman.dll
rasapi32.dll 5.00.2195.6625 192.77 KB
(197,392 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\rasapi32.dll
rtutils.dll 5.00.2168.1 43.77 KB
(44,816 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\rtutils.dll
adslfdc.dll 5.00.2195.6701 130.77 KB
(133,904 bytes) 8/16/2005 1:51:33 PM
Microsoft Corporation
c:\winnt\system32\adslfdc.dll

```

```

activeds.dll 5.00.2195.6601 177.77 KB
(182,032 bytes) 8/16/2005 1:51:31 PM
Microsoft Corporation
c:\winnt\system32\activeds.dll
oleaut32.dll 2.40.4522 612.27 KB (626,960
bytes) 12/7/1999 7:00:00 AM Microsoft
Corporation c:\winnt\system32\oleaut32.dll
mprapi.dll 5.00.2181.1 79.27 KB
(81,168 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\mprapi.dll
icmp.dll 5.00.2134.1 7.27 KB (7,440 bytes)
12/7/1999 7:00:00 AM Microsoft
Corporation c:\winnt\system32\icmp.dll
iphlpapi.dll 5.00.2195.6602 68.27 KB
(69,904 bytes) 8/16/2005 1:51:43 PM
Microsoft Corporation
c:\winnt\system32\iphlpapi.dll
wshtcpip.dll 5.00.2195.6601 17.27 KB
(17,680 bytes) 8/16/2005 1:52:00 PM
Microsoft Corporation
c:\winnt\system32\wshtcpip.dll
msafd.dll 5.00.2195.6602 106.27 KB (108,816
bytes) 8/16/2005 1:51:46 PM Microsoft
Corporation c:\winnt\system32\msafd.dll
mpr.dll 5.00.2195.6611 53.77 KB (55,056 bytes)
8/16/2005 1:51:45 PM Microsoft
Corporation c:\winnt\system32\mpr.dll
winspool.drv 5.00.2195.6659 111.27 KB
(113,936 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\winspool.drv
winscard.dll 5.00.2195.6609 77.27 KB
(79,120 bytes) 8/16/2005 1:52:00 PM
Microsoft Corporation
c:\winnt\system32\winscard.dll
atl.dll 3.00.9435 73.06 KB (74,810 bytes)
8/16/2005 1:51:33 PM Microsoft
Corporation c:\winnt\system32\atl.dll
certcli.dll 5.00.2195.6619 132.27 KB
(135,440 bytes) 8/16/2005 1:51:35 PM
Microsoft Corporation
c:\winnt\system32\certcli.dll
wlnotify.dll 5.00.2195.6706 56.27 KB
(57,616 bytes) 8/16/2005 1:52:00 PM
Microsoft Corporation
c:\winnt\system32\wlnotify.dll
csd.dll 5.00.2195.6713 98.77 KB
(101,136 bytes) 8/16/2005 1:51:37 PM
Microsoft Corporation
c:\winnt\system32\csd.dll
lz32.dll 5.00.2195.6611 9.77 KB (10,000 bytes)
8/16/2005 1:51:44 PM Microsoft
Corporation c:\winnt\system32\lz32.dll
version.dll 5.00.2195.6623 15.77 KB
(16,144 bytes) 8/16/2005 1:51:59 PM
Microsoft Corporation
c:\winnt\system32\version.dll
rsaenh.dll 5.00.2195.6611 131.77 KB
(134,928 bytes) 8/16/2005 1:52:09 PM
Microsoft Corporation
c:\winnt\system32\rsaenh.dll

```

```

mscat32.dll 5.131.2134.1 7.77 KB
(7,952 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\mscat32.dll
ole32.dll 5.00.2195.6692 972.77 KB (996,112
bytes) 8/16/2005 1:51:52 PM Microsoft
Corporation c:\winnt\system32\ole32.dll
imagehlp.dll 5.00.2195.6613 125.77 KB
(128,784 bytes) 5/4/2001 12:05:02 PM
Microsoft Corporation
c:\winnt\system32\imagehlp.dll
msasn1.dll 5.00.2195.6666 51.77 KB
(53,008 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\msasn1.dll
crypt32.dll 5.131.2195.6661 468.27 KB
(479,504 bytes) 8/16/2005 1:51:37 PM
Microsoft Corporation
c:\winnt\system32\crypt32.dll
wintrust.dll 5.131.2195.6624 162.27 KB
(166,160 bytes) 8/16/2005 1:52:00 PM
Microsoft Corporation
c:\winnt\system32\wintrust.dll
shlwapi.dll 5.00.3502.6601 282.77 KB
(289,552 bytes) 8/16/2005 1:51:56 PM
Microsoft Corporation
c:\winnt\system32\shlwapi.dll
shell32.dll 5.00.3700.6705 2.27 MB
(2,383,632 bytes) 8/16/2005 1:51:56 PM
Microsoft Corporation
c:\winnt\system32\shell32.dll
msgina.dll 5.00.2195.6669 326.27 KB
(334,096 bytes) 8/16/2005 1:51:46 PM
Microsoft Corporation
c:\winnt\system32\msgina.dll
comctl32.dll 5.81 537.77 KB (550,672
bytes) 12/7/1999 7:00:00 AM Microsoft
Corporation c:\winnt\system32\comctl32.dll
setupapi.dll 5.00.2195.6622 556.77 KB
(570,128 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\setupapi.dll
winmm.dll 5.00.2161.1 184.77 KB (189,200
bytes) 12/7/1999 7:00:00 AM Microsoft
Corporation c:\winnt\system32\winmm.dll
winsta.dll 5.00.2195.6701 38.27 KB
(39,184 bytes) 8/16/2005 1:52:00 PM
Microsoft Corporation
c:\winnt\system32\winsta.dll
wsock32.dll 5.00.2195.6603 21.27 KB
(21,776 bytes) 8/16/2005 1:52:00 PM
Microsoft Corporation
c:\winnt\system32\wsock32.dll
dnsapi.dll 5.00.2195.6680 131.77 KB
(134,928 bytes) 8/16/2005 1:51:38 PM
Microsoft Corporation
c:\winnt\system32\dnsapi.dll
wldap32.dll 5.00.2195.6666 158.27 KB
(162,064 bytes) 8/16/2005 1:52:00 PM
Microsoft Corporation
c:\winnt\system32\wldap32.dll
ws2help.dll 5.00.2134.1 17.77 KB
(18,192 bytes) 12/7/1999 7:00:00 AM

```

```

Microsoft Corporation
c:\winnt\system32\ws2help.dll
ws2_32.dll 5.00.2195.6601 68.27 KB
(69,904 bytes) 8/16/2005 1:52:00 PM
Microsoft Corporation
c:\winnt\system32\ws2_32.dll
samlib.dll 5.00.2195.6666 48.77 KB
(49,936 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\samlib.dll
netrap.dll 5.00.2134.1 11.27 KB
(11,536 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\netrap.dll
netapi32.dll 5.00.2195.6601 304.27 KB
(311,568 bytes) 8/16/2005 1:51:50 PM
Microsoft Corporation
c:\winnt\system32\netapi32.dll
profmap.dll 5.00.2195.6610 29.27 KB
(29,968 bytes) 8/16/2005 1:51:53 PM
Microsoft Corporation
c:\winnt\system32\profmap.dll
secur32.dll 5.00.2195.6695 47.77 KB
(48,912 bytes) 8/16/2005 1:51:55 PM
Microsoft Corporation
c:\winnt\system32\secur32.dll
sfc.dll 5.00.2195.6673 92.80 KB (95,024 bytes)
8/16/2005 1:51:55 PM
Microsoft
Corporation c:\winnt\system32\sfc.dll
nddeapi.dll 5.00.2195.6661 15.77 KB
(16,144 bytes) 8/16/2005 1:51:50 PM
Microsoft Corporation
c:\winnt\system32\nddeapi.dll
userenv.dll 5.00.2195.6711 380.77 KB
(389,904 bytes) 8/16/2005 1:51:59 PM
Microsoft Corporation
c:\winnt\system32\userenv.dll
user32.dll 5.00.2195.6688 393.77 KB
(403,216 bytes) 8/16/2005 1:51:59 PM
Microsoft Corporation
c:\winnt\system32\user32.dll
gdi32.dll 5.00.2195.6660 228.27 KB (233,744
bytes) 8/16/2005 1:51:40 PM
Microsoft
Corporation c:\winnt\system32\gdi32.dll
rpctr4.dll 5.00.2195.6701 443.77 KB
(454,416 bytes) 8/16/2005 1:51:55 PM
Microsoft Corporation
c:\winnt\system32\rpctr4.dll
advapi32.dll 5.00.2195.6710 378.27 KB
(387,344 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\advapi32.dll
kernel32.dll 5.00.2195.6688 725.77 KB
(743,184 bytes) 12/7/1999 7:00:00 AM
Microsoft Corporation
c:\winnt\system32\kernel32.dll
msvcrt.dll 6.10.9844.0 280.05 KB
(286,773 bytes) 6/19/2003 12:05:04 PM
Microsoft Corporation
c:\winnt\system32\msvcrt.dll
winlogon.exe 5.00.2195.6714 176.77 KB
(181,008 bytes) 8/16/2005 1:52:00 PM

```

```

Microsoft Corporation
c:\winnt\system32\winlogon.exe
sfcfiles.dll 5.00.2195.6717 948.27 KB
(971,024 bytes) 8/16/2005 1:51:55 PM
Microsoft Corporation
c:\winnt\system32\sfcfiles.dll
ntdll.dll 5.00.2195.6685 480.27 KB (491,792
bytes) 5/4/2001 12:05:02 PM
Microsoft
Corporation c:\winnt\system32\ntdll.dll
smss.exe 5.00.2195.6601 44.77 KB (45,840 bytes)
12/7/1999 7:00:00 AM
Microsoft
Corporation c:\winnt\system32\smss.exe

[Services]

Display Name Name State Start Mode
Service Type Path Error Control
Start Name Tag ID
Altiris Client Service AClient Running
Auto Own Process c:\program
files\altiris\aclient\aclient.exe -service
Normal LocalSystem 0
Alerter Alerter Stopped Manual Share Process
c:\winnt\system32\services.exe
Normal LocalSystem 0
Application Management AppMgmt Stopped
Manual Share Process
c:\winnt\system32\services.exe
Normal LocalSystem 0
ASP.NET State Service aspnet_state
Stopped Manual Own Process
c:\winnt\microsoft.net\framework\v2.0.50215
\aspnet_state.exe Normal .\ASPNET 0
Background Intelligent Transfer Service BITS
Stopped Manual Share Process
c:\winnt\system32\svchost.exe -k bitsgroup
Normal LocalSystem 0
Computer Browser Browser Running Auto
Share Process
c:\winnt\system32\services.exe
Normal LocalSystem 0
Indexing Service cisvc Stopped Manual
Share Process
c:\winnt\system32\cisvc.exe Normal
LocalSystem 0
ClipBook ClipSrv Stopped Manual Own Process
c:\winnt\system32\clipsrv.exe Normal
LocalSystem 0
.NET Runtime Optimization Service v2.0.50215_X86
clr_optimization_v2.0.50215_32
Stopped Manual Own Process
c:\winnt\microsoft.net\framework\v2.0.50215
\mscorsvw.exe Ignore LocalSystem 0
Distributed File System Dfs Running
Auto Own Process
c:\winnt\system32\dfssvc.exe Normal
LocalSystem 0
DHCP Client Dhcp Stopped Disabled
Share Process
c:\winnt\system32\services.exe
Normal LocalSystem 0
Logical Disk Manager Administrative Service
dmadmin Stopped Manual Share Process

```

```

c:\winnt\system32\dmadmin.exe /com
Normal LocalSystem 0
Logical Disk Manager dmserver Running
Auto Share Process
c:\winnt\system32\services.exe
Normal LocalSystem 0
DNS Client Dnscache Stopped Manual
Share Process
c:\winnt\system32\services.exe
Normal LocalSystem 0
Event Log Eventlog Running Auto Share Process
c:\winnt\system32\services.exe
Normal LocalSystem 0
COM+ Event System EventSystem Running
Manual Share Process
c:\winnt\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
Fax Service Fax Stopped Manual Own
Process c:\winnt\system32\faxsvc.exe Normal
LocalSystem 0
IIS Admin Service IISADMIN Running Auto
Share Process
c:\winnt\system32\inetrv\inetinfo.exe
Normal LocalSystem 0
InterSite Messaging IsmSrv Stopped Disabled Own
Process c:\winnt\system32\ismssrv.exe Normal
LocalSystem 0
Kerberos Key Distribution Center kdc
Stopped Disabled Share Process
c:\winnt\system32\lsass.exe Normal
LocalSystem 0
Server lanmanserver Running Auto
Share Process
c:\winnt\system32\services.exe
Normal LocalSystem 0
Workstation lanmanworkstation Running
Auto Share Process
c:\winnt\system32\services.exe
Normal LocalSystem 0
License Logging Service LicenseService
Stopped Manual Own Process
c:\winnt\system32\llssrv.exe Normal
LocalSystem 0
TCP/IP NetBIOS Helper Service LmHosts Stopped
Disabled Share Process
c:\winnt\system32\services.exe
Normal LocalSystem 0
Messenger Messenger Stopped Manual Share Process
c:\winnt\system32\services.exe
Normal LocalSystem 0
NetMeeting Remote Desktop Sharing nmmsrv
Stopped Manual Own Process
c:\winnt\system32\mmmsrv.exe Normal
LocalSystem 0
Distributed Transaction Coordinator MSDTC
Stopped Manual Own Process
c:\winnt\system32\msdtc.exe Normal
LocalSystem 0
Windows Installer MSIServer Stopped Manual
Share Process
c:\winnt\system32\msiexec.exe /v
Normal LocalSystem 0

```

Network DDE	NetDDE	Stopped	Manual	
Share Process				
c:\winnt\system32\netdde.exe	Normal			
LocalSystem	0			
Network DDE DSDM	NetDDEdsdm	Stopped		
Manual Share Process				
c:\winnt\system32\netdde.exe	Normal			
LocalSystem	0			
Net Logon	Netlogon	Stopped	Manual	Share Process
c:\winnt\system32\lsass.exe	Normal			
LocalSystem	0			
Network Connections	Netman	Running	Manual	
Share Process				
c:\winnt\system32\svchost.exe	-k netsvcs			
Normal	LocalSystem	0		
File Replication	NtFrs	Stopped	Manual	Own
Process	c:\winnt\system32\ntfrs.exe	Ignore		
LocalSystem	0			
NT LM Security Support Provider	NtLmSsp			
Stopped	Manual	Share Process		
c:\winnt\system32\lsass.exe	Normal			
LocalSystem	0			
Removable Storage	NtmsSvc	Running	Auto	
Share Process				
c:\winnt\system32\svchost.exe	-k netsvcs			
Normal	LocalSystem	0		
Plug and Play	PlugPlay	Running	Auto	
Share Process				
c:\winnt\system32\services.exe				
Normal	LocalSystem	0		
IPSEC Policy Agent	PolicyAgent	Running		
Auto	Share Process			
c:\winnt\system32\lsass.exe	Normal			
LocalSystem	0			
Protected Storage	ProtectedStorage	Running		
Auto	Share Process			
c:\winnt\system32\services.exe				
Normal	LocalSystem	0		
Remote Access Auto Connection Manager	RasAuto	Stopped	Manual	Share Process
Stopped	Manual	Share Process		
c:\winnt\system32\svchost.exe	-k netsvcs			
Normal	LocalSystem	0		
Remote Access Connection Manager	RasMan	Running	Manual	Share Process
Running	Manual	Share Process		
c:\winnt\system32\svchost.exe	-k netsvcs			
Normal	LocalSystem	0		
Routing and Remote Access	RemoteAccess	Stopped	Disabled	Share Process
Stopped	Disabled	Share Process		
c:\winnt\system32\svchost.exe	-k netsvcs			
Normal	LocalSystem	0		
Remote Registry Service	RemoteRegistry	Running	Auto	Own Process
Running	Auto	Own Process		
c:\winnt\system32\regsvc.exe	Normal			
LocalSystem	0			
Remote Command Service	RMSYS	Running	Auto	Own Process
Auto	Own Process			
c:\benchmark\rsys.exe	Normal			
LocalSystem	0			
Remote Procedure Call (RPC) Locator	RpcLocator	Stopped	Manual	Own Process
Stopped	Manual	Own Process		
c:\winnt\system32\locator.exe	Normal			
LocalSystem	0			

Remote Procedure Call (RPC)	RpcSs	Running		
Auto	Share Process			
c:\winnt\system32\svchost.exe	-k rpcss			
Normal	LocalSystem	0		
QoS RSVP	RSVP	Running	Manual	Own Process
c:\winnt\system32\rsvp.exe	-s Normal			
LocalSystem	0			
Security Accounts Manager	SamSs	Running		
Auto	Share Process			
c:\winnt\system32\lsass.exe	Normal			
LocalSystem	0			
Smart Card Helper	SCardDrv	Stopped	Manual	
Share Process				
c:\winnt\system32\scardsvr.exe				
Ignore	LocalSystem	0		
Smart Card	SCardSvr	Stopped	Manual	
Share Process				
c:\winnt\system32\scardsvr.exe				
Ignore	LocalSystem	0		
Task Scheduler	Schedule	Running	Auto	
Share Process				
c:\winnt\system32\mstask.exe	Normal			
LocalSystem	0			
RunAs Service	seclogon	Running	Auto	
Share Process				
c:\winnt\system32\services.exe				
Ignore	LocalSystem	0		
System Event Notification	SENS	Running		
Auto	Share Process			
c:\winnt\system32\svchost.exe	-k netsvcs			
Normal	LocalSystem	0		
Internet Connection Sharing	SharedAccess	Stopped	Manual	Share Process
Stopped	Manual	Share Process		
c:\winnt\system32\svchost.exe	-k netsvcs			
Normal	LocalSystem	0		
Print Spooler	Spooler	Stopped	Manual	Own Process
Process	c:\winnt\system32\spoolsv.exe	Normal		
LocalSystem	0			
Performance Logs and Alerts	SysmonLog	Stopped		
Manual	Own Process			
c:\winnt\system32\smlogsvc.exe				
Normal	LocalSystem	0		
Telephony	TapiSrv	Running	Manual	Share Process
c:\winnt\system32\svchost.exe	-k tapisrv			
Normal	LocalSystem	0		
Terminal Services	TermService	Running		
Auto	Own Process			
c:\winnt\system32\termsrv.exe	Normal			
LocalSystem	0			
Telnet	TlntSvr	Stopped	Manual	Own Process
c:\winnt\system32\tlntsvr.exe	Normal			
LocalSystem	0			
Distributed Link Tracking Server	TrkSvr	Stopped	Manual	Share Process
Stopped	Manual	Share Process		
c:\winnt\system32\services.exe				
Normal	LocalSystem	0		
Distributed Link Tracking Client	TrkWks	Running	Auto	Share Process
Running	Auto	Share Process		
c:\winnt\system32\services.exe				
Normal	LocalSystem	0		
Uninterruptible Power Supply	UPS	Stopped		
Manual	Own Process			

c:\winnt\system32\ups.exe	Normal			
LocalSystem	0			
Utility Manager	UtilMan	Stopped	Manual	Own Process
c:\winnt\system32\utilman.exe	Normal			
LocalSystem	0			
Windows Time	W32Time	Stopped	Manual	
Share Process				
c:\winnt\system32\services.exe				
Normal	LocalSystem	0		
World Wide Web Publishing Service	W3SVC	Stopped	Auto	Share Process
c:\winnt\system32\inetrv\inetinfo.exe				
Normal	LocalSystem	0		
Windows Management Instrumentation	WinMgmt	Running	Auto	Own Process
c:\winnt\system32\wbem\winmgmt.exe				
Ignore	LocalSystem	0		
Windows Management Instrumentation Driver Extensions				
Wmi	Running	Manual	Share Process	
c:\winnt\system32\services.exe				
Normal	LocalSystem	0		
Automatic Updates	wuauclt	Stopped	Auto	
Share Process				
c:\winnt\system32\svchost.exe	-k wugroup			
Normal	LocalSystem	0		
Wireless Configuration	WZCSVC	Stopped		
Manual	Share Process			
c:\winnt\system32\svchost.exe	-k netsvcs			
Normal	LocalSystem	0		

[Program Groups]

Group Name	Name	User Name
Accessories	Default	User:Accessories
	Default User	
Accessories\Accessibility		Default
User:Accessories\Accessibility		Default User
Accessories\Entertainment		Default
User:Accessories\Entertainment		Default User
Accessories\System Tools		Default
User:Accessories\System Tools		Default User
Startup	Default User:Startup	Default User
Accessories	All Users:Accessories	All Users
Accessories\Communications		All
User:Accessories\Communications		All Users
Accessories\Entertainment		All
User:Accessories\Entertainment		All Users
Accessories\Microsoft Script Debugger		All
User:Accessories\Microsoft Script Debugger		All Users
Accessories\System Tools		All
User:Accessories\System Tools		All Users
Administrative Tools		All
User:Administrative Tools		All Users
HP System Tools		All Users:HP System Tools
HP System Tools\HP Array Diagnostic Utility		All Users
User:HP System Tools\HP Array Diagnostic Utility		All Users
Microsoft SQL Server 2005 CTP		All Users:Microsoft SQL Server 2005 CTP
All Users		

Microsoft SQL Server 2005 CTP\Configuration Tools All Users:Microsoft SQL Server 2005 CTP\Configuration Tools All Users
 Microsoft SQL Server 2005 CTP\Documentation and Tutorials All Users:Microsoft SQL Server 2005 CTP\Documentation and Tutorials All Users
 Microsoft SQL Server 2005 CTP\Documentation and Tutorials All Users:Microsoft SQL Server 2005 CTP\Documentation and Tutorials All Users
 Startup All Users:Startup All Users
 Tardis All Users:Tardis All Users
 Accessories CL26\Administrator:Accessories CL26\Administrator
 Accessories\Accessibility CL26\Administrator:Accessories\Accessibility CL26\Administrator
 Accessories\Entertainment CL26\Administrator:Accessories\Entertainment CL26\Administrator
 Accessories\System Tools CL26\Administrator:Accessories\System Tools CL26\Administrator
 Administrative Tools CL26\Administrator:Administrative Tools CL26\Administrator
 Startup CL26\Administrator:Startup CL26\Administrator

[Startup Programs]

Program	Command	User Name	Location
Tardis 2000	c:\progra-1\tardis-1.4\tardis.exe	All Users	Common Startup
ACLntUsr	c:\program files\altiris\aclient\aclntusr.exe	All Users	
ion\Run	HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\Run		

[OLE Registration]

Object	Local Server
Sound (OLE2)	sndrec32.exe
Media Clip	mplay32.exe
Video Clip	mplay32.exe /avi
MIDI Sequence	mplay32.exe /mid
Sound	Not Available
Media Clip	Not Available
Image Document	"C:\Program Files\Windows NT\Accessories\ImageVue\KodakImg.exe"
WordPad Document	"%ProgramFiles%\Windows NT\Accessories\WORDPAD.EXE"
Windows Media Services DRM Storage object	Not Available
DDSContainerCtl Class	Not Available
Bitmap Image	mspaint.exe

[Internet Explorer 5]

[Following are sub-categories of this main category]

[Summary]

Item	Value
Version	5.00.3700.1000
Build	53700.1000
Product ID	51876-270-9567332-05753
Application Path	C:\Program Files\Internet Explorer
Language	English (United States)
Active Printer	Not Available

Cipher Strength	168-bit
Content Advisor	Disabled
IEAK Install	No

[File Versions]

File	Version	Size	Date	Path
advapi32.dll	5.0.2195.6710	378 KB	6/19/2003 12:05:04 PM	C:\WINNT\system32\Microsoft Corporation
advpack.dll	5.0.3502.6601	87 KB	6/19/2003 12:05:04 PM	C:\WINNT\system32\Microsoft Corporation
browsei.c.dll	5.0.3700.6661	35 KB	6/19/2003 12:05:04 PM	C:\WINNT\system32\Microsoft Corporation
browseui.dll	5.0.3700.6661	789 KB	6/19/2003 12:05:04 PM	C:\WINNT\system32\Microsoft Corporation
ckcnv.exe	5.0.2189.1	9 KB	12/7/1999 8:00:00 AM	C:\WINNT\system32\Microsoft Corporation
comctl32.dll	5.81.3502.6601	538 KB	6/19/2003 12:05:04 PM	C:\WINNT\system32\Microsoft Corporation
crypt32.dll	5.131.2195.6661	468 KB	6/19/2003 12:05:04 PM	C:\WINNT\system32\Microsoft Corporation
ehnsig.dll	<File Missing>	Not Available	Not Available	Not Available
iemigrat.dll	<File Missing>	Not Available	Not Available	Not Available
iesetup.dll	5.0.3502.6601	57 KB	6/19/2003 12:05:04 PM	C:\WINNT\system32\Microsoft Corporation
iexplore.exe	5.0.2920.0	59 KB	12/7/1999 8:00:00 AM	C:\Program Files\Internet Explorer
imagehlp.dll	5.0.2195.6613	126 KB	6/19/2003 12:05:04 PM	C:\WINNT\system32\Microsoft Corporation
imghelp.dll	<File Missing>	Not Available	Not Available	Not Available
inseng.dll	5.0.3502.6601	72 KB	6/19/2003 12:05:04 PM	C:\WINNT\system32\Microsoft Corporation
jobexec.dll	5.0.0.1	47 KB	12/7/1999 8:00:00 AM	C:\WINNT\system32\Microsoft Corporation

jscript.dll	5.1.0.8513	476 KB	6/19/2003 12:05:04 PM	C:\WINNT\system32\Microsoft Corporation
jsproxy.dll	5.0.2920.0	13 KB	12/7/1999 8:00:00 AM	C:\WINNT\system32\Microsoft Corporation
msaahtml.dll	<File Missing>	Not Available	Not Available	Not Available
mshtml.dll	5.0.3700.6699	2299 KB	6/19/2003 12:05:04 PM	C:\WINNT\system32\Microsoft Corporation
msoss.dll	<File Missing>	Not Available	Not Available	Not Available
msxml.dll	8.0.6730.0	502 KB	6/19/2003 12:05:04 PM	C:\WINNT\system32\Microsoft Corporation
occache.dll	5.0.3502.6601	86 KB	6/19/2003 12:05:04 PM	C:\WINNT\system32\Microsoft Corporation
ole32.dll	5.0.2195.6692	973 KB	6/19/2003 12:05:04 PM	C:\WINNT\system32\Microsoft Corporation
oleaut32.dll	2.40.4522.0	612 KB	6/19/2003 12:05:04 PM	C:\WINNT\system32\Microsoft Corporation
olepro32.dll	5.0.4522.0	160 KB	6/19/2003 12:05:04 PM	C:\WINNT\system32\Microsoft Corporation
rsabase.dll	5.0.2195.6619	129 KB	6/19/2003 12:05:04 PM	C:\WINNT\system32\Microsoft Corporation
rsaenh.dll	5.0.2195.6611	132 KB	6/19/2003 12:05:04 PM	C:\WINNT\system32\Microsoft Corporation
rsapi32.dll	<File Missing>	Not Available	Not Available	Not Available
rsasig.dll	<File Missing>	Not Available	Not Available	Not Available
schannel.dll	5.1.2195.6705	144 KB	6/19/2003 12:05:04 PM	C:\WINNT\system32\Microsoft Corporation
shdoc401.dll	<File Missing>	Not Available	Not Available	Not Available
shdocv.dll	5.0.3700.6668	1082 KB	6/19/2003 12:05:04 PM	C:\WINNT\system32\Microsoft Corporation
shell32.dll	5.0.3700.6705	2328 KB	6/19/2003 12:05:04 PM	C:\WINNT\system32\Microsoft Corporation
shlwapi.dll	5.0.3502.6601	283 KB	6/19/2003 12:05:04 PM	C:\WINNT\system32\Microsoft Corporation
url.dll	5.0.3502.6601	82 KB	6/19/2003 12:05:04 PM	C:\WINNT\system32\Microsoft Corporation
urlmon.dll	5.0.3700.6705	443 KB	6/19/2003 12:05:04 PM	C:\WINNT\system32\Microsoft Corporation

```

vbscript.dll      5.1.0.7426      428 KB
                  6/19/2003 12:05:04 PM
                  C:\WINNT\system32 Microsoft Corporation
webcheck.dll     5.0.3502.6601  252 KB
                  6/19/2003 12:05:04 PM
                  C:\WINNT\system32 Microsoft Corporation
win.com          5.0.2134.1      24 KB
8:00:00 AM      C:\WINNT\system32 Microsoft
Corporation
wininet.dll      5.0.3700.6713   456 KB
                  6/19/2003 12:05:04 PM
                  C:\WINNT\system32 Microsoft Corporation
winsock.dll      3.10.0.103      3 KB
                  12/7/1999 8:00:00 AM
wintrust.dll     5.131.2195.6624 162 KB
                  6/19/2003 12:05:04 PM
                  C:\WINNT\system32 Microsoft Corporation
wsock.vxd <File Missing> Not Available Not
Available Not Available Not Available
wsock32.dll      5.0.2195.6603   21 KB
                  6/19/2003 12:05:04 PM
                  C:\WINNT\system32 Microsoft Corporation
wsock32n.dll <File Missing> Not Available
Not Available Not Available Not
Available

```

[Connectivity]

```

Item      Value
Connection Preference      Never dial
EnableHttp1.1      1
ProxyHttp1.1      0

```

LAN Settings

```

AutoConfigProxy      wininet.dll
AutoProxyDetectMode Disabled
AutoConfigURL
Proxy      Disabled
ProxyServer
ProxyOverride

```

[Cache]

[Following are sub-categories of this main category]

[Summary]

```

Item      Value
Page Refresh Type      Automatic
Temporary Internet Files Folder      C:\Documents
and Settings\Administrator\Local Settings\Temporary
Internet Files
Total Disk Space      34718 MB
Available Disk Space      31361 MB
Maximum Cache Size      542 MB
Available Cache Size      542 MB

```

[List of Objects]

```

Program File      Status      CodeBase

```

No cached object information available

[Content]

[Following are sub-categories of this main category]

[Summary]

```

Item      Value
Content Advisor      Disabled

```

[Personal Certificates]

```

Issued To Issued By Validity Signature Algorithm
Administrator Administrator 9/13/2002 to
8/20/2102 sha1RSA

```

[Other People Certificates]

```

Issued To Issued By Validity Signature Algorithm
No other people certificate information available

```

[Publishers]

```

Name
No publisher information available

```

[Security]

```

Zone      Security Level
Local intranet      Medium-low
Trusted sites      Low
Internet      Medium
Restricted sites      High

```

Microsoft COM Component Configuration Parameters

The component services tool in Windows 2000 Server was used to change the queue settings for the TPCC COM+ single queue component. The single queue component was set to enable object pooling, object construction, just in time activation, and component supports events and statistics. The min and max pool size for the single queue component on the client was 82. Delivery threads were set under the TPCC key in the registry at 8. The construction string was Dummy String.

Internet Information Server Registry Parameters

Windows Registry Editor Version 5.00

```
[HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\InetInfo]
```

```
[HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\InetInfo\Parameters]
"ListenBackLog"=dword:00000019
"DispatchEntries"=hex(7):4c,00,44,00,41,00,50,00,53,0
0,56,00,43,00,00,00,00,00
"PoolThreadLimit"=dword:000007fe
"ThreadTimeout"=dword:00015180

```

```
[HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\InetInfo\Performance]
"Library"="infectrs.dll"
"Open"="OpenINFOPerformanceData"
"Close"="CloseINFOPerformanceData"
"Collect"="CollectINFOPerformanceData"
"Last Counter"=dword:00000842
"Last Help"=dword:00000843
"First Counter"=dword:00000802
"First Help"=dword:00000803
"Library Validation
Code"=hex:de,d0,18,8b,93,a2,c5,01,10,25,00,00,00,00,0
0,00
"WbemAdapFileTime"=hex:00,a0,38,ed,84,36,c3,01
"WbemAdapFileSize"=dword:00002510
"WbemAdapStatus"=dword:00000000

```

World Wide Web Service Registry Parameters

Windows Registry Editor Version 5.00

```
[HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\W3SVC]
"Type"=dword:00000020
"Start"=dword:00000002
"ErrorControl"=dword:00000001
"ImagePath"=hex(2):43,00,3a,00,5c,00,57,00,49,00,4e,0
0,4e,00,54,00,5c,00,53,00,\

```

```

79,00,73,00,74,00,65,00,6d,00,33,00,32,00,5c,00,69,00,
,6e,00,65,00,74,00,73,\

00,72,00,76,00,5c,00,69,00,6e,00,65,00,74,00,69,00,6e,
,00,66,00,6f,00,2e,00,\
65,00,78,00,65,00,00,00
"DisplayName"="World Wide Web Publishing Service"
"DependOnService"=hex(7):49,00,49,00,53,00,41,00,44,0
,0,4d,00,49,00,4e,00,00,00,\
00,00
"DependOnGroup"=hex(7):00,00
"ObjectName"="LocalSystem"
"Description"="Provides Web connectivity and
administration through the Internet Information
Services snap-in."
"FailureActions"=hex:ff,ff,ff,ff,80,3a,0e,00,90,3a,0e
,00,03,00,00,00,98,3a,0e,\

00,00,00,00,00,00,00,00,00,00,00,00,00,00,00,00,00,00,
,00,00,00,00,00,00,00

[HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services
\W3SVC\ASP]
"NOTE"="This is for backward compatibility only."

[HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services
\W3SVC\ASP\Parameters]

[HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services
\W3SVC\Parameters]
"MajorVersion"=dword:00000005
"MinorVersion"=dword:00000000
"InstallPath"="C:\\WINNT\\System32\\inetsrv"
"CertMapList"="C:\\WINNT\\System32\\inetsrv\\iisrmap
.dll"
"AccessDeniedMessage"="Error: Access is Denied."
"Filter DLLs"=""
"LogFileDirectory"="C:\\WINNT\\System32\\LogFiles"
"AcceptExOutstanding"=dword:00000028

[HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services
\W3SVC\Parameters\ADCLaunch]

[HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services
\W3SVC\Parameters\ADCLaunch\AdvancedDataFactory]

[HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services
\W3SVC\Parameters\ADCLaunch\RDSServer.DataFactory]

[HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services
\W3SVC\Parameters\Script Map]

[HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services
\W3SVC\Parameters\Virtual Roots]
"/"="c:\\inetpub\\wwwroot,,207"
"/Scripts"="c:\\inetpub\\scripts,,1"
"/IISHelp"="c:\\winnt\\help\\iishelp,,1"
"/IISAdmin"="C:\\WINNT\\System32\\inetsrv\\iisadmin,,
1"
"/IISSamples"="c:\\inetpub\\iissamples,,1"
"/MSADC"="c:\\program files\\common
files\\system\\msadc,,1"

```

```

"/_vti_bin"="C:\\Program Files\\Common
Files\\Microsoft Shared\\Web Server
Extensions\\40\\isapi,,1"
"/Printers"="C:\\WINNT\\web\\printers,,201"

[HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services
\W3SVC\Performance]
"Library"="w3ctrs.dll"
"Open"="OpenW3PerformanceData"
"Close"="CloseW3PerformanceData"
"Collect"="CollectW3PerformanceData"
"Last Counter"=dword:000008e6
"Last Help"=dword:000008e7
"First Counter"=dword:00000844
"First Help"=dword:00000845
"Library Validation
Code"=hex:52,4c,7b,a6,7a,5b,c2,01,10,1d,00,00,00,00,0
0,00
"WbemAdapFileTime"=hex:00,a0,38,ed,84,36,c3,01
"WbemAdapFileSize"=dword:00001d10
"WbemAdapStatus"=dword:00000000

[HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services
\W3SVC\Security]
"Security"=hex:01,00,14,80,a0,00,00,00,ac,00,00,00,14
,00,00,00,30,00,00,00,02,\

00,1c,00,01,00,00,00,02,80,14,00,ff,01,0f,00,01,01,00
,00,00,00,00,01,00,00,\

00,00,02,00,70,00,04,00,00,00,00,00,18,00,fd,01,02,00
,01,01,00,00,00,00,00,\

05,12,00,00,00,74,00,6f,00,00,00,1c,00,ff,01,0f,00,01
,02,00,00,00,00,00,05,\

20,00,00,00,20,02,00,00,72,00,73,00,00,00,18,00,8d,01
,02,00,01,01,00,00,00,\

00,00,05,0b,00,00,00,20,02,00,00,00,00,1c,00,fd,01,02
,00,01,02,00,00,00,00,\

00,05,20,00,00,00,23,02,00,00,72,00,73,00,01,01,00,00
,00,00,00,05,12,00,00,\

00,01,01,00,00,00,00,00,05,12,00,00,00

[HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services
\W3SVC\Enum]
"0"="Root\LEGACY_W3SVC\0000"
"Count"=dword:00000001
"Next Instance"=dword:00000001

```

Tcp/ip Registry Parameters

```

Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
Tcpip
Class Name:      Class

```

```

Last Write Time: 9/26/2005 - 10:13 AM
Value 0
Name:
Type:
Type:      REG_DWORD
Data:      0x1

Value 1
Name:      Start
Type:      REG_DWORD
Data:      0x1

Value 2
Name:      ErrorControl
Type:      REG_DWORD
Data:      0x1

Value 3
Name:      Tag
Type:      REG_DWORD
Data:      0x4

Value 4
Name:      ImagePath
Type:      REG_EXPAND_SZ
Data:      system32\DRIVERS\tcpip.sys

Value 5
Name:      DisplayName
Type:      REG_SZ
Data:      TCP/IP Protocol Driver

Value 6
Name:      Group
Type:      REG_SZ
Data:      PNP_TDI

Value 7
Name:      DependOnService
Type:      REG_MULTI_SZ
Data:      IPSec

Value 8
Name:      DependOnGroup
Type:      REG_MULTI_SZ

Value 9
Name:      Description
Type:      REG_SZ
Data:      TCP/IP Protocol Driver

Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
Tcpip\Linkage
Class Name:      <NO CLASS>
Last Write Time: 7/18/2005 - 4:03 PM
Value 0
Name:      Bind
Type:      REG_MULTI_SZ
Data:      \Device\{52582010-323D-4AD3-9502-
90DAFDBAE634}

```



```

3339A1E07E0C} \Device\{2956B01A-D74B-4A7D-BF1E-
\Device\NdisWanIp
Value 1
Name: Route
Type: REG_MULTI_SZ
Data: "{52582010-323D-4AD3-9502-
90DAFD8AE634}"
3339A1E07E0C}"
" {2956B01A-D74B-4A7D-BF1E-
"NdisWanIp"
Value 2
Name: Export
Type: REG_MULTI_SZ
Data: \Device\Tcpip_{52582010-323D-4AD3-
9502-90DAFD8AE634}
\Device\Tcpip_{2956B01A-D74B-4A7D-
BF1E-3339A1E07E0C}
\Device\Tcpip_{678971D5-6B4E-4E81-
A47F-42EDB771884E}
\Device\Tcpip_{901EACFC-1F0D-4181-
A9AD-58E9EA8C141F}
Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
Tcpip\Parameters
Class Name: Class
Last Write Time: 9/15/2005 - 8:51 PM
Value 0
Name: NV Hostname
Type: REG_SZ
Data: Bobcat
Value 1
Name: DataBasePath
Type: REG_EXPAND_SZ
Data: %SystemRoot%\System32\drivers\etc
Value 2
Name: NameServer
Type: REG_SZ
Data:
Value 3
Name: ForwardBroadcasts
Type: REG_DWORD
Data: 0
Value 4
Name: IPEnableRouter
Type: REG_DWORD
Data: 0
Value 5
Name: Domain
Type: REG_SZ
Data:
Value 6
Name: Hostname

```

```

Type: REG_SZ
Data: Bobcat
Value 7
Name: SearchList
Type: REG_SZ
Data:
Value 8
Name: UseDomainNameDevolution
Type: REG_DWORD
Data: 0x1
Value 9
Name: EnableICMPRedirect
Type: REG_DWORD
Data: 0x1
Value 10
Name: DeadGWDetectDefault
Type: REG_DWORD
Data: 0x1
Value 11
Name: DontAddDefaultGatewayDefault
Type: REG_DWORD
Data: 0
Value 12
Name: EnableSecurityFilters
Type: REG_DWORD
Data: 0
Value 13
Name: ReservedPorts
Type: REG_MULTI_SZ
Data: 1433-1434
3343-3343
Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
Tcpip\Parameters\Adapters
Class Name: <NO CLASS>
Last Write Time: 7/18/2005 - 4:03 PM
Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
Tcpip\Parameters\Adapters\NdisWanIp
Class Name: <NO CLASS>
Last Write Time: 7/18/2005 - 4:03 PM
Value 0
Name: LLInterface
Type: REG_SZ
Data: WANARP
Value 1
Name: IpConfig
Type: REG_MULTI_SZ
Data:
Tcpip\Parameters\Interfaces\{678971D5-6B4E-4E81-A47F-
42EDB771884E}

```

```

Tcpip\Parameters\Interfaces\{901EACFC-1F0D-4181-A9AD-
58E9EA8C141F}
Value 2
Name: NumInterfaces
Type: REG_DWORD
Data: 0x2
Value 3
Name: IpInterfaces
Type: REG_BINARY
Data:
00000000 d5 71 89 67 4e 6b 81 4e - a4 7f 42 ed b7
71 88 4e 0q.gNk.NC.Bi.q.N
00000010 fc ac 1e 90 0d 1f 81 41 - a9 ad 58 e9 ea
8c 14 1f û-....A°-Xêê...
Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
Tcpip\Parameters\Adapters\{2956B01A-D74B-4A7D-BF1E-
3339A1E07E0C}
Class Name: <NO CLASS>
Last Write Time: 7/18/2005 - 4:02 PM
Value 0
Name: LLInterface
Type: REG_SZ
Data:
Value 1
Name: IpConfig
Type: REG_MULTI_SZ
Data:
Tcpip\Parameters\Interfaces\{2956B01A-D74B-4A7D-BF1E-
3339A1E07E0C}
Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
Tcpip\Parameters\Adapters\{52582010-323D-4AD3-9502-
90DAFD8AE634}
Class Name: <NO CLASS>
Last Write Time: 7/18/2005 - 4:02 PM
Value 0
Name: LLInterface
Type: REG_SZ
Data:
Value 1
Name: IpConfig
Type: REG_MULTI_SZ
Data:
Tcpip\Parameters\Interfaces\{52582010-323D-4AD3-9502-
90DAFD8AE634}
Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
Tcpip\Parameters\DNSRegisteredAdapters
Class Name: DynRootClass
Last Write Time: 7/18/2005 - 4:02 PM

```

Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
Tcpip\Parameters\Interfaces
Class Name: <NO CLASS>
Last Write Time: 7/18/2005 - 4:03 PM

Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
Tcpip\Parameters\Interfaces\{2956B01A-D74B-4A7D-BF1E-
3339A1E07E0C}
Class Name: <NO CLASS>
Last Write Time: 7/18/2005 - 4:49 PM

Value 0
Name: UseZeroBroadcast
Type: REG_DWORD
Data: 0

Value 1
Name: EnableDeadGWDetect
Type: REG_DWORD
Data: 0x1

Value 2
Name: EnabledDHCP
Type: REG_DWORD
Data: 0

Value 3
Name: IPAddress
Type: REG_MULTI_SZ
Data: 130.168.208.14

Value 4
Name: SubnetMask
Type: REG_MULTI_SZ
Data: 255.255.0.0

Value 5
Name: DefaultGateway
Type: REG_MULTI_SZ
Data:

Value 6
Name: DefaultGatewayMetric
Type: REG_MULTI_SZ
Data:

Value 7
Name: NameServer
Type: REG_SZ
Data:

Value 8
Name: Domain
Type: REG_SZ
Data:

Value 9
Name: RegistrationEnabled
Type: REG_DWORD
Data: 0x1

Value 10
Name: RegisterAdapterName
Type: REG_DWORD
Data: 0

Value 11
Name: TCPAllowedPorts
Type: REG_MULTI_SZ
Data: 0

Value 12
Name: UDPAllowedPorts
Type: REG_MULTI_SZ
Data: 0

Value 13
Name: RawIPAllowedProtocols
Type: REG_MULTI_SZ
Data: 0

Value 14
Name: NTEContextList
Type: REG_MULTI_SZ
Data: 0x00000002

Value 15
Name: DhcpClassIdBin
Type: REG_BINARY
Data:

Value 16
Name: DhcpServer
Type: REG_SZ
Data: 255.255.255.255

Value 17
Name: Lease
Type: REG_DWORD
Data: 0xe10

Value 18
Name: LeaseObtainedTime
Type: REG_DWORD
Data: 0x42dc1935

Value 19
Name: T1
Type: REG_DWORD
Data: 0x42dc203d

Value 20
Name: T2
Type: REG_DWORD
Data: 0x42dc2583

Value 21
Name: LeaseTerminatesTime
Type: REG_DWORD
Data: 0x42dc2745

Value 22
Name: IPAutoconfigurationAddress
Type: REG_SZ

Data: 0.0.0.0

Value 23
Name: IPAutoconfigurationMask
Type: REG_SZ
Data: 255.255.0.0

Value 24
Name: IPAutoconfigurationSeed
Type: REG_DWORD
Data: 0

Value 25
Name: AddressType
Type: REG_DWORD
Data: 0

Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
Tcpip\Parameters\Interfaces\{52582010-323D-4AD3-9502-
90DAFD8AE634}
Class Name: <NO CLASS>
Last Write Time: 8/16/2005 - 10:34 AM

Value 0
Name: UseZeroBroadcast
Type: REG_DWORD
Data: 0

Value 1
Name: EnableDeadGWDetect
Type: REG_DWORD
Data: 0x1

Value 2
Name: EnabledDHCP
Type: REG_DWORD
Data: 0

Value 3
Name: IPAddress
Type: REG_MULTI_SZ
Data: 130.120.208.14

Value 4
Name: SubnetMask
Type: REG_MULTI_SZ
Data: 255.255.0.0

Value 5
Name: DefaultGateway
Type: REG_MULTI_SZ
Data:

Value 6
Name: DefaultGatewayMetric
Type: REG_MULTI_SZ
Data:

Value 7
Name: NameServer
Type: REG_SZ
Data:

Value 8
Name: Domain
Type: REG_SZ
Data:

Value 9
Name: RegistrationEnabled
Type: REG_DWORD
Data: 0x1

Value 10
Name: RegisterAdapterName
Type: REG_DWORD
Data: 0

Value 11
Name: TCPSAllowedPorts
Type: REG_MULTI_SZ
Data: 0

Value 12
Name: UDPSAllowedPorts
Type: REG_MULTI_SZ
Data: 0

Value 13
Name: RawIPAllowedProtocols
Type: REG_MULTI_SZ
Data: 0

Value 14
Name: NTEContextList
Type: REG_MULTI_SZ
Data: 0x00000003

Value 15
Name: DhcpClassIdBin
Type: REG_BINARY
Data:

Value 16
Name: DhcpServer
Type: REG_SZ
Data: 255.255.255.255

Value 17
Name: Lease
Type: REG_DWORD
Data: 0xe10

Value 18
Name: LeaseObtainedTime
Type: REG_DWORD
Data: 0x42dc1947

Value 19
Name: T1
Type: REG_DWORD
Data: 0x42dc204f

Value 20
Name: T2

Type: REG_DWORD
Data: 0x42dc2595

Value 21
Name: LeaseTerminatesTime
Type: REG_DWORD
Data: 0x42dc2757

Value 22
Name: IPAutoconfigurationAddress
Type: REG_SZ
Data: 0.0.0.0

Value 23
Name: IPAutoconfigurationMask
Type: REG_SZ
Data: 255.255.0.0

Value 24
Name: IPAutoconfigurationSeed
Type: REG_DWORD
Data: 0

Value 25
Name: AddressType
Type: REG_DWORD
Data: 0

Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
Tcpip\Parameters\Interfaces\{678971D5-6B4E-4E81-A47F-
42EDB771884E}
Class Name: <NO CLASS>
Last Write Time: 7/18/2005 - 4:03 PM

Value 0
Name: UseZeroBroadcast
Type: REG_DWORD
Data: 0

Value 1
Name: EnabledDHCP
Type: REG_DWORD
Data: 0

Value 2
Name: IPAddress
Type: REG_MULTI_SZ
Data: 0.0.0.0

Value 3
Name: SubnetMask
Type: REG_MULTI_SZ
Data: 0.0.0.0

Value 4
Name: DefaultGateway
Type: REG_MULTI_SZ
Data:

Value 5
Name: EnableDeadGWDetect
Type: REG_DWORD
Data:

Data: 0x1

Value 6
Name: DontAddDefaultGateway
Type: REG_DWORD
Data: 0

Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
Tcpip\Parameters\Interfaces\{901EACFC-1F0D-4181-A9AD-
58E9EA8C141F}
Class Name: <NO CLASS>
Last Write Time: 7/18/2005 - 4:03 PM

Value 0
Name: UseZeroBroadcast
Type: REG_DWORD
Data: 0

Value 1
Name: EnabledDHCP
Type: REG_DWORD
Data: 0

Value 2
Name: IPAddress
Type: REG_MULTI_SZ
Data: 0.0.0.0

Value 3
Name: SubnetMask
Type: REG_MULTI_SZ
Data: 0.0.0.0

Value 4
Name: DefaultGateway
Type: REG_MULTI_SZ
Data:

Value 5
Name: EnableDeadGWDetect
Type: REG_DWORD
Data: 0x1

Value 6
Name: DontAddDefaultGateway
Type: REG_DWORD
Data: 0

Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
Tcpip\Parameters\PersistentRoutes
Class Name: <NO CLASS>
Last Write Time: 7/18/2005 - 4:02 PM

Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
Tcpip\Parameters\Winsock
Class Name: <NO CLASS>
Last Write Time: 7/18/2005 - 4:02 PM

Value 0
Name: UseDelayedAcceptance

```

Type:          REG_DWORD
Data:          0

Value 1
Name:          HelperDllName
Type:          REG_EXPAND_SZ
Data:          %SystemRoot%\System32\wshtcpip.dll

Value 2
Name:          MaxSockAddrLength
Type:          REG_DWORD
Data:          0x10

Value 3
Name:          MinSockAddrLength
Type:          REG_DWORD
Data:          0x10

Value 4
Name:          Mapping
Type:          REG_BINARY
Data:          00000000 0b 00 00 00 03 00 00 00 - 02 00 00 00 01
00 00 00 .....
00000010 06 00 00 00 02 00 00 00 - 01 00 00 00 00
00 00 00 .....
00000020 02 00 00 00 00 00 00 00 - 06 00 00 00 00
00 00 00 .....
00000030 00 00 00 00 06 00 00 00 - 00 00 00 00 01
00 00 00 .....
00000040 06 00 00 00 02 00 00 00 - 02 00 00 00 11
00 00 00 .....
00000050 02 00 00 00 02 00 00 00 - 00 00 00 00 02
00 00 00 .....
00000060 00 00 00 00 11 00 00 00 - 00 00 00 00 00
00 00 00 .....
00000070 11 00 00 00 00 00 00 00 - 02 00 00 00 11
00 00 00 .....
02 00 00 00 03 00 00 00 - 00 00 00 00
.....

Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
Tcpip\Performance
Class Name:    <NO CLASS>
Last Write Time: 7/19/2005 - 9:05 AM
Value 0
Name:          Close
Type:          REG_SZ
Data:          CloseTcpIpPerformanceData

Value 1
Name:          Collect
Type:          REG_SZ
Data:          CollectTcpIpPerformanceData

Value 2
Name:          Library
Type:          REG_SZ
Data:          Perfctrs.dll

Value 3

```

```

Name:          Open
Type:          REG_SZ
Data:          OpenTcpIpPerformanceData

Value 4
Name:          Object List
Type:          REG_SZ
Data:          502 510 546 548 582 638 658 1530
1532 1534

Value 5
Name:          WbemAdapFileSignature
Type:          REG_BINARY
Data:          00000000 24 d6 dd 1d 85 49 fe ed - 25 5a 30 3c 4a
5f b1 76 $0f..Ipi%Z0<J_+v

Value 6
Name:          WbemAdapFileTime
Type:          REG_BINARY
Data:          00 a0 a0 2b 32 31 c5 01 -
. +21Å.

Value 7
Name:          WbemAdapFileSize
Type:          REG_DWORD
Data:          0xcc00

Value 8
Name:          WbemAdapStatus
Type:          REG_DWORD
Data:          0

Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
Tcpip\Security
Class Name:    <NO CLASS>
Last Write Time: 7/18/2005 - 4:02 PM
Value 0
Name:          Security
Type:          REG_BINARY
Data:          00000000 01 00 14 80 b8 00 00 00 - c4 00 00 00 14
00 00 00 .....Å.....
00000010 30 00 00 00 02 00 1c 00 - 01 00 00 00 02
80 14 00 0.....
00000020 ff 01 0f 00 01 01 00 00 - 00 00 00 01 00
00 00 00 ý.....
00000030 02 00 88 00 06 00 00 00 - 00 00 14 00 fd
01 02 00 .....ý...
00000040 01 01 00 00 00 00 05 - 12 00 00 00 00
00 18 00 .....
00000050 ff 01 0f 00 01 02 00 00 - 00 00 00 05 20
00 00 00 ý.....
00000060 20 02 00 00 00 00 14 00 - 8d 01 02 00 01
01 00 00 .....
00000070 00 00 00 05 04 00 00 00 - 00 00 14 00 8d
01 02 00 .....
00000080 01 01 00 00 00 00 05 - 06 00 00 00 00
00 14 00 .....

```

```

00000090 00 01 00 00 01 01 00 00 - 00 00 00 05 0b
00 00 00 .....
000000a0 00 00 18 00 fd 01 02 00 - 01 02 00 00 00
00 00 05 ....ý.....
000000b0 20 00 00 00 23 02 00 00 - 01 01 00 00 00
00 00 05 ...#.....
000000c0 12 00 00 00 01 01 00 00 - 00 00 00 05 12
00 00 00 .....

Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
Tcpip\ServiceProvider
Class Name:    <NO CLASS>
Last Write Time: 7/18/2005 - 4:02 PM
Value 0
Name:          Class
Type:          REG_DWORD
Data:          0x8

Value 1
Name:          DnsPriority
Type:          REG_DWORD
Data:          0x7d0

Value 2
Name:          HostsPriority
Type:          REG_DWORD
Data:          0x1f4

Value 3
Name:          LocalPriority
Type:          REG_DWORD
Data:          0x1f3

Value 4
Name:          ProviderPath
Type:          REG_EXPAND_SZ
Data:          %SystemRoot%\System32\wsock32.dll

Value 5
Name:          NetbtPriority
Type:          REG_DWORD
Data:          0x7d1

Value 6
Name:          Name
Type:          REG_SZ
Data:          TCP/IP

Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
Tcpip\Enum
Class Name:    <NO CLASS>
Last Write Time: 9/26/2005 - 10:13 AM
Value 0
Name:          0
Type:          REG_SZ
Data:          Root\LEGACY_TCPIP\0000

Value 1

```

Name: Count
Type: REG_DWORD
Data: 0x1

Value 2
Name: NextInstance
Type: REG_DWORD
Data: 0x1

TPCC Application Registry Parameters

Windows Registry Editor Version 5.00

```
[HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\TPCC]
"Path"="C:\\Inetpub\\wwwroot\\"
"NumberOfDeliveryThreads"=dword:00000008
"MaxConnections"=dword:00007530
"MaxPendingDeliveries"=dword:000007d0
"DB_Protocol"="ODBC"
"TxnMonitor"="COM"
"DbName"="tpcc"
"DbUser"="sa"
"DbPassword"=""
"COM_SinglePool"="YES"
"CallNoDuplicatesNewOrder"=dword:00000001
"yyDbServer"="twin"
"DbServer"="bobcat"
"ConnectDelay"=dword:00000001
```

Benchcraft Profile

Profile: Twin_16400_8c1
File Path: C:\David_585\Twin_16400_8c1.xml
Version: 5

Number of Engines: 16

Name: RTE2
Description:
Directory: c:\blog\rte2.log
Machine: n26
Parameter Set: 2.2
Index: 1600000000
Seed: 4678
Configured Users: 10250
Pipe Name: DRIVER53164609
Connect Rate: 10

Start Rate: 0
Max. Concurrency: 0
Concurrency Rate: 0
CLIENT_NURAND: 25
CPU: 0
Additional Options:

Name: RTE1
Description:
Directory: c:\blog\rte1.log
Machine: n25
Parameter Set: 2.2
Index: 700000000
Seed: 4678
Configured Users: 10250
Pipe Name: DRIVER44265281
Connect Rate: 10
Start Rate: 0
Max. Concurrency: 0
Concurrency Rate: 0
CLIENT_NURAND: 25
CPU: 0
Additional Options:

Name: RTE3
Description:
Directory: c:\blog\rte3.log
Machine: n27
Parameter Set: 2.2
Index: 200000000
Seed: 4678
Configured Users: 10250
Pipe Name: DRIVER3439676359
Connect Rate: 10
Start Rate: 0
Max. Concurrency: 0
Concurrency Rate: 0
CLIENT_NURAND: 25
CPU: 0
Additional Options:

Name: RTE4
Description:
Directory: c:\blog\rte4.log
Machine: n28
Parameter Set: 2.2
Index: 300000000
Seed: 4678
Configured Users: 10250
Pipe Name: DRIVER4439706187
Connect Rate: 10
Start Rate: 0
Max. Concurrency: 0
Concurrency Rate: 0
CLIENT_NURAND: 25
CPU: 0
Additional Options:

Name: RTE5
Description:
Directory: c:\blog\rte5.log
Machine: n29
Parameter Set: 2.2

Index: 400000000
Seed: 4678
Configured Users: 10250
Pipe Name: DRIVER5346413218
Connect Rate: 10
Start Rate: 0
Max. Concurrency: 0
Concurrency Rate: 0
CLIENT_NURAND: 25
CPU: 0
Additional Options:

Name: RTE6
Description:
Directory: c:\blog\rte6.log
Machine: n30
Parameter Set: 2.2
Index: 500000000
Seed: 4678
Configured Users: 10250
Pipe Name: DRIVER62226046
Connect Rate: 10
Start Rate: 0
Max. Concurrency: 0
Concurrency Rate: 0
CLIENT_NURAND: 25
CPU: 0
Additional Options:

Name: RTE7
Description:
Directory: c:\blog\rte7.log
Machine: n25
Parameter Set: 2.2
Index: 600000000
Seed: 4678
Configured Users: 10250
Pipe Name: DRIVER72289718
Connect Rate: 10
Start Rate: 0
Max. Concurrency: 0
Concurrency Rate: 0
CLIENT_NURAND: 25
CPU: 1
Additional Options:

Name: RTE8
Description:
Directory: c:\blog\rte8.log
Machine: n26
Parameter Set: 2.2
Index: 170000000
Seed: 4678
Configured Users: 10250
Pipe Name: DRIVER82325578
Connect Rate: 10
Start Rate: 0
Max. Concurrency: 0
Concurrency Rate: 0
CLIENT_NURAND: 25
CPU: 1
Additional Options:

Name: RTE9
Description:
Directory: c:\blog\rte9.log
Machine: n27
Parameter Set: 2.2
Index: 800000000
Seed: 4678
Configured Users: 10250
Pipe Name: DRIVER92360187
Connect Rate: 10
Start Rate: 0
Max. Concurrency: 0
Concurrency Rate: 0
CLIENT_NURAND: 25
CPU: 1
Additional Options:

Name: RTE10
Description:
Directory: c:\blog\rte10.log
Machine: n28
Parameter Set: 2.2
Index: 900000000
Seed: 4678
Configured Users: 10250
Pipe Name: DRIVER102399796
Connect Rate: 10
Start Rate: 0
Max. Concurrency: 0
Concurrency Rate: 0
CLIENT_NURAND: 25
CPU: 1
Additional Options:

Name: RTE11
Description:
Directory: c:\blog\rte11.log
Machine: N29
Parameter Set: 2.2
Index: 1000000000
Seed: 4678
Configured Users: 10250
Pipe Name: DRIVER1122682203
Connect Rate: 10
Start Rate: 0
Max. Concurrency: 0
Concurrency Rate: 0
CLIENT_NURAND: 25
CPU: 1
Additional Options:

Name: RTE12
Description:
Directory: c:\blog\rte12.log
Machine: N30
Parameter Set: 2.2
Index: 1100000000
Seed: 4678
Configured Users: 10250
Pipe Name: DRIVER1222731546
Connect Rate: 10
Start Rate: 0
Max. Concurrency: 0

Concurrency Rate: 0
CLIENT_NURAND: 25
CPU: 1
Additional Options:

Name: RTE13
Description:
Directory: c:\blog\rte13.log
Machine: n45
Parameter Set: 2.2
Index: 1200000000
Seed: 4678
Configured Users: 10250
Pipe Name: DRIVER13-1439076421
Connect Rate: 10
Start Rate: 0
Max. Concurrency: 0
Concurrency Rate: 0
CLIENT_NURAND: 25
CPU: 0
Additional Options:

Name: RTE14
Description:
Directory: c:\blog\rte14.log
Machine: n45
Parameter Set: 2.2
Index: 1300000000
Seed: 4678
Configured Users: 10250
Pipe Name: DRIVER14-1438943656
Connect Rate: 10
Start Rate: 0
Max. Concurrency: 0
Concurrency Rate: 0
CLIENT_NURAND: 25
CPU: 1
Additional Options:

Name: RTE15
Description:
Directory: c:\blog\rte15.log
Machine: n46
Parameter Set: 2.2
Index: 1400000000
Seed: 4678
Configured Users: 10250
Pipe Name: DRIVER15-1438852265
Connect Rate: 10
Start Rate: 0
Max. Concurrency: 0
Concurrency Rate: 0
CLIENT_NURAND: 25
CPU: 0
Additional Options:

Name: RTE16
Description:
Directory: c:\blog\rte16.log
Machine: n46
Parameter Set: 2.2
Index: 1500000000
Seed: 4678

Configured Users: 10250
Pipe Name: DRIVER16-1438790906
Connect Rate: 10
Start Rate: 0
Max. Concurrency: 0
Concurrency Rate: 0
CLIENT_NURAND: 25
CPU: 1
Additional Options:

Number of User groups: 16

Driver Engine: RTE1
IIS Server: cr25
SQL Server: bobcat
Database: tpcc
User: sa
Protocol: HTML
w_id Range: 1 - 1025
w_id Min Warehouse: 1
w_id Max Warehouse: 16400
Scale: Normal
User Count: 10250
District id: 1
Scale Down: No

Driver Engine: RTE2
IIS Server: cr26
SQL Server: bobcat
Database: tpcc
User: sa
Protocol: HTML
w_id Range: 1026 - 2050
w_id Min Warehouse: 1
w_id Max Warehouse: 16400
Scale: Normal
User Count: 10250
District id: 1
Scale Down: No

Driver Engine: RTE3
IIS Server: cr27
SQL Server: bobcat
Database: tpcc
User: sa
Protocol: HTML
w_id Range: 2051 - 3075
w_id Min Warehouse: 1
w_id Max Warehouse: 16400
Scale: Normal
User Count: 10250
District id: 1
Scale Down: No

Driver Engine: RTE4
IIS Server: cr28
SQL Server: bobcat
Database: tpcc
User: sa
Protocol: HTML
w_id Range: 3076 - 4100
w_id Min Warehouse: 1
w_id Max Warehouse: 16400

Scale: Normal
 User Count: 10250
 District id: 1
 Scale Down: No

Driver Engine: RTE5
 IIS Server: cr29
 SQL Server: bobcatb
 Database: tpcc
 User: sa
 Protocol: HTML
 w_id Range: 4101 - 5125
 w_id Min Warehouse: 1
 w_id Max Warehouse: 16400
 Scale: Normal
 User Count: 10250
 District id: 1
 Scale Down: No

Driver Engine: RTE6
 IIS Server: cr30
 SQL Server: bobcatb
 Database: tpcc
 User: sa
 Protocol: HTML
 w_id Range: 5126 - 6150
 w_id Min Warehouse: 1
 w_id Max Warehouse: 16400
 Scale: Normal
 User Count: 10250
 District id: 1
 Scale Down: No

Driver Engine: RTE7
 IIS Server: cr25
 SQL Server: bobcat
 Database: tpcc
 User: sa
 Protocol: HTML
 w_id Range: 6151 - 7175
 w_id Min Warehouse: 1
 w_id Max Warehouse: 16400
 Scale: Normal
 User Count: 10250
 District id: 1
 Scale Down: No

Driver Engine: RTE8
 IIS Server: cr26
 SQL Server: bobcat
 Database: tpcc
 User: sa
 Protocol: HTML
 w_id Range: 7176 - 8200
 w_id Min Warehouse: 1
 w_id Max Warehouse: 16400
 Scale: Normal
 User Count: 10250
 District id: 1
 Scale Down: No

Driver Engine: RTE9
 IIS Server: cr27

SQL Server: bobcat
 Database: tpcc
 User: sa
 Protocol: HTML
 w_id Range: 8201 - 9225
 w_id Min Warehouse: 1
 w_id Max Warehouse: 16400
 Scale: Normal
 User Count: 10250
 District id: 1
 Scale Down: No

Driver Engine: RTE10
 IIS Server: cr28
 SQL Server: bobcat
 Database: tpcc
 User: sa
 Protocol: HTML
 w_id Range: 9226 - 10250
 w_id Min Warehouse: 1
 w_id Max Warehouse: 16400
 Scale: Normal
 User Count: 10250
 District id: 1
 Scale Down: No

Driver Engine: RTE11
 IIS Server: cr29
 SQL Server: bobcatb
 Database: tpcc
 User: sa
 Protocol: HTML
 w_id Range: 10251 - 11275
 w_id Min Warehouse: 1
 w_id Max Warehouse: 16400
 Scale: Normal
 User Count: 10250
 District id: 1
 Scale Down: No

Driver Engine: RTE12
 IIS Server: cr30
 SQL Server: bobcatb
 Database: tpcc
 User: sa
 Protocol: HTML
 w_id Range: 11276 - 12300
 w_id Min Warehouse: 1
 w_id Max Warehouse: 16400
 Scale: Normal
 User Count: 10250
 District id: 1
 Scale Down: No

Driver Engine: RTE13
 IIS Server: cr5
 SQL Server: bobcatb
 Database: tpcc
 User: sa
 Protocol: HTML
 w_id Range: 12301 - 13325
 w_id Min Warehouse: 1
 w_id Max Warehouse: 16400

Scale: Normal
 User Count: 10250
 District id: 1
 Scale Down: No

Driver Engine: RTE14
 IIS Server: cr5
 SQL Server: bobcatb
 Database: tpcc
 User: sa
 Protocol: HTML
 w_id Range: 13326 - 14350
 w_id Min Warehouse: 1
 w_id Max Warehouse: 16400
 Scale: Normal
 User Count: 10250
 District id: 1
 Scale Down: No

Driver Engine: RTE15
 IIS Server: cr6
 SQL Server: bobcatb
 Database: tpcc
 User: sa
 Protocol: HTML
 w_id Range: 14351 - 15375
 w_id Min Warehouse: 1
 w_id Max Warehouse: 16400
 Scale: Normal
 User Count: 10250
 District id: 1
 Scale Down: No

Driver Engine: RTE16
 IIS Server: cr6
 SQL Server: bobcatb
 Database: tpcc
 User: sa
 Protocol: HTML
 w_id Range: 15376 - 16400
 w_id Min Warehouse: 1
 w_id Max Warehouse: 16400
 Scale: Normal
 User Count: 10250
 District id: 1
 Scale Down: No

Number of Parameter Sets: 66

Key	RT	RT	Menu	Default Parameter Set	
				Txn	Think
Time	Delay	Fence	Delay	Weight	Time
			New Order	10.00	
12.05	18.01	0.10	Payment	10.00	0.10
12.05	3.01	0.10	Delivery	1.00	0.10
5.05	2.01	0.10		5.00	0.10

5.05	2.01		Stock Level	1.00		
			0.10	20.00	0.10	
10.05	2.01		Order Status	1.00		
			0.10	5.00	0.10	
Tuned Distribution						
Key	RT	RT	Menu	Txn	Think	
Time	Delay	Fence	Delay	Weight	Time	
12.05	18.01		New Order	44.75		
			0.10	5.00	0.10	
12.05	3.01		Payment	43.10		
			0.10	5.00	0.10	
5.05	2.01		Delivery	4.05		
			0.10	5.00	0.10	
5.05	2.01		Stock Level	4.05		
			0.10	20.00	0.10	
10.05	2.01		Order Status	4.05		
			0.10	5.00	0.10	
No Think						
Key	RT	RT	Menu	Txn	Think	
Time	Delay	Fence	Delay	Weight	Time	
0.00	0.00		New Order	10.00		
			0.00	5.00	0.00	
0.00	0.00		Payment	10.00		
			0.00	5.00	0.00	
0.00	0.00		Delivery	1.00		
			0.00	5.00	0.00	
0.00	0.00		Stock Level	1.00		
			0.00	20.00	0.00	
0.00	0.00		Order Status	1.00		
			0.00	5.00	0.00	
95%						
Key	RT	RT	Menu	Txn	Think	
Time	Delay	Fence	Delay	Weight	Time	
13.00	18.01		New Order	44.75		
			0.10	5.00	0.10	
13.00	3.01		Payment	43.10		
			0.10	5.00	0.10	
6.00	2.01		Delivery	4.05		
			0.10	5.00	0.10	
6.00	2.01		Stock Level	4.05		
			0.10	20.00	0.10	
11.00	2.01		Order Status	4.05		
			0.10	5.00	0.10	
90%						
Key	RT	RT	Menu	Txn	Think	
Time	Delay	Fence	Delay	Weight	Time	

16.00	18.01		New Order	44.83		
			0.10	5.00	0.10	
16.00	3.01		Payment	43.05		
			0.10	5.00	0.10	
9.00	2.01		Delivery	4.04		
			0.10	5.00	0.10	
9.00	2.01		Stock Level	4.04		
			0.10	20.00	0.10	
14.00	2.01		Order Status	4.04		
			0.10	5.00	0.10	
3.0						
Key	RT	RT	Menu	Txn	Think	
Time	Delay	Fence	Delay	Weight	Time	
36.15	0.00		New Order	44.75		
			0.10	5.00	0.10	
36.15	0.00		Payment	43.10		
			0.10	5.00	0.10	
15.15	0.00		Delivery	4.05		
			0.10	5.00	0.10	
15.15	0.00		Stock Level	4.05		
			0.10	20.00	0.10	
30.15	0.00		Order Status	4.05		
			0.10	5.00	0.10	
4.0						
4.0 tt						
Key	RT	RT	Menu	Txn	Think	
Time	Delay	Fence	Delay	Weight	Time	
48.20	18.01		New Order	44.75		
			0.10	5.00	0.10	
48.20	3.01		Payment	43.10		
			0.10	5.00	0.10	
20.20	2.01		Delivery	4.05		
			0.10	5.00	0.10	
20.20	2.01		Stock Level	4.05		
			0.10	20.00	0.10	
40.20	2.01		Order Status	4.05		
			0.10	5.00	0.10	
3.8						
3.8 tt						
Key	RT	RT	Menu	Txn	Think	
Time	Delay	Fence	Delay	Weight	Time	
45.70	18.01		New Order	44.75		
			0.10	5.00	0.10	
45.70	3.01		Payment	43.10		
			0.10	5.00	0.10	
19.10	2.01		Delivery	4.05		
			0.10	5.00	0.10	
19.10	2.01		Stock Level	4.05		
			0.10	20.00	0.10	
38.10	2.01		Order Status	4.05		
			0.10	5.00	0.10	
3.6						

3.6 tt						
Key	RT	RT	Menu	Txn	Think	
Time	Delay	Fence	Delay	Weight	Time	
43.30	18.01		New Order	44.75		
			0.10	5.00	0.10	
43.30	3.01		Payment	43.10		
			0.10	5.00	0.10	
18.10	2.01		Delivery	4.05		
			0.10	5.00	0.10	
18.10	2.01		Stock Level	4.05		
			0.10	20.00	0.10	
36.18	2.01		Order Status	4.05		
			0.10	5.00	0.10	
3.4						
3.4 tt						
Key	RT	RT	Menu	Txn	Think	
Time	Delay	Fence	Delay	Weight	Time	
40.90	18.01		New Order	44.75		
			0.10	5.00	0.10	
40.90	3.01		Payment	43.10		
			0.10	5.00	0.10	
17.10	2.01		Delivery	4.05		
			0.10	5.00	0.10	
17.10	2.01		Stock Level	4.05		
			0.10	20.00	0.10	
17.10	2.01		Order Status	4.05		
			0.10	5.00	0.10	
3.2						
3.2 tt						
Key	RT	RT	Menu	Txn	Think	
Time	Delay	Fence	Delay	Weight	Time	
38.50	18.01		New Order	44.75		
			0.10	5.00	0.10	
38.50	3.01		Payment	43.10		
			0.10	5.00	0.10	
16.10	2.01		Delivery	4.05		
			0.10	5.00	0.10	
16.10	2.01		Stock Level	4.05		
			0.10	20.00	0.10	
32.10	2.01		Order Status	4.05		
			0.10	5.00	0.10	
2.8						
2.8 tt						
Key	RT	RT	Menu	Txn	Think	
Time	Delay	Fence	Delay	Weight	Time	
33.74	18.01		New Order	44.75		
			0.10	5.00	0.10	
33.74	3.01		Payment	43.10		
			0.10	5.00	0.10	
14.14	2.01		Delivery	4.05		
			0.10	5.00	0.10	

14.14	2.01		Stock Level	4.05		
			0.10	20.00	0.10	
28.14	2.01		Order Status	4.05		
			0.10	5.00	0.10	
			2.6			
			2.6 tt			
Key	RT	RT	Menu	Txn	Think	
Time	Delay	Fence	Delay	Weight	Time	
31.30	18.01		New Order	44.75		
			0.10	5.00	0.10	
31.30	3.01		Payment	43.10		
			0.10	5.00	0.10	
13.10	2.01		Delivery	4.05		
			0.10	5.00	0.10	
13.10	2.01		Stock Level	4.05		
			0.10	20.00	0.10	
26.10	2.01		Order Status	4.05		
			0.10	5.00	0.10	
			2.4			
			2.4 tt			
Key	RT	RT	Menu	Txn	Think	
Time	Delay	Fence	Delay	Weight	Time	
28.90	18.01		New Order	44.75		
			0.10	5.00	0.10	
28.90	3.01		Payment	43.10		
			0.10	5.00	0.10	
12.10	2.01		Delivery	4.05		
			0.10	5.00	0.10	
12.10	2.01		Stock Level	4.05		
			0.10	20.00	0.10	
24.10	2.01		Order Status	4.05		
			0.10	5.00	0.10	
			2.2			
			2.2 tt			
Key	RT	RT	Menu	Txn	Think	
Time	Delay	Fence	Delay	Weight	Time	
28.90	18.01		New Order	44.75		
			0.10	5.00	0.10	
28.90	3.01		Payment	43.10		
			0.10	5.00	0.10	
12.10	2.01		Delivery	4.05		
			0.10	5.00	0.10	
12.10	2.01		Stock Level	4.05		
			0.10	20.00	0.10	
24.12	2.01		Order Status	4.05		
			0.10	5.00	0.10	
			2.0			
			2.0 tt			
Key	RT	RT	Menu	Txn	Think	
Time	Delay	Fence	Delay	Weight	Time	

24.10	18.01		New Order	44.75		
			0.10	5.00	0.10	
24.10	3.01		Payment	43.10		
			0.10	5.00	0.10	
10.10	2.01		Delivery	4.05		
			0.10	5.00	0.10	
10.10	2.01		Stock Level	4.05		
			0.10	20.00	0.10	
20.10	2.01		Order Status	4.05		
			0.10	5.00	0.10	
			5.0			
			5.0 tt			
Key	RT	RT	Menu	Txn	Think	
Time	Delay	Fence	Delay	Weight	Time	
60.25	18.01		New Order	44.75		
			0.10	5.00	0.10	
60.25	3.01		Payment	43.10		
			0.10	5.00	0.10	
25.25	2.01		Delivery	4.05		
			0.10	5.00	0.10	
25.25	2.01		Stock Level	4.05		
			0.10	20.00	0.10	
50.25	2.01		Order Status	4.05		
			0.10	5.00	0.10	
			4.5			
			4.5 tt			
Key	RT	RT	Menu	Txn	Think	
Time	Delay	Fence	Delay	Weight	Time	
54.20	18.01		New Order	44.75		
			0.10	5.00	0.10	
54.20	3.01		Payment	43.10		
			0.10	5.00	0.10	
22.70	2.01		Delivery	4.05		
			0.10	5.00	0.10	
22.70	2.01		Stock Level	4.05		
			0.10	20.00	0.10	
45.20	2.01		Order Status	4.05		
			0.10	5.00	0.10	
			3.5			
			3.5 tt			
Key	RT	RT	Menu	Txn	Think	
Time	Delay	Fence	Delay	Weight	Time	
42.10	18.01		New Order	44.75		
			0.10	5.00	0.10	
42.10	3.01		Payment	43.10		
			0.10	5.00	0.10	
17.60	2.01		Delivery	4.05		
			0.10	5.00	0.10	
17.60	2.01		Stock Level	4.05		
			0.10	20.00	0.10	
35.10	2.01		Order Status	4.05		
			0.10	5.00	0.10	
			1.8			

			1.8 tt			
Key	RT	RT	Menu	Txn	Think	
Time	Delay	Fence	Delay	Weight	Time	
21.60	18.01		New Order	44.75		
			0.10	5.00	0.10	
21.60	3.01		Payment	43.10		
			0.10	5.00	0.10	
9.09	2.01		Delivery	4.05		
			0.10	5.00	0.10	
9.09	2.01		Stock Level	4.05		
			0.10	20.00	0.10	
18.09	2.01		Order Status	4.05		
			0.10	5.00	0.10	
			4.2			
			4.2 tt			
Key	RT	RT	Menu	Txn	Think	
Time	Delay	Fence	Delay	Weight	Time	
54.20	18.01		New Order	44.75		
			0.10	5.00	0.10	
54.20	3.01		Payment	43.10		
			0.10	5.00	0.10	
22.70	2.01		Delivery	4.05		
			0.10	5.00	0.10	
22.70	2.01		Stock Level	4.05		
			0.10	20.00	0.10	
45.20	2.01		Order Status	4.05		
			0.10	5.00	0.10	
			1.6			
			1.6 tt			
Key	RT	RT	Menu	Txn	Think	
Time	Delay	Fence	Delay	Weight	Time	
19.20	18.01		New Order	44.75		
			0.10	5.00	0.10	
19.20	3.01		Payment	43.10		
			0.10	5.00	0.10	
8.08	2.01		Delivery	4.05		
			0.10	5.00	0.10	
8.08	2.01		Stock Level	4.05		
			0.10	20.00	0.10	
16.08	2.01		Order Status	4.05		
			0.10	5.00	0.10	
			1.4			
			1.4 tt			
Key	RT	RT	Menu	Txn	Think	
Time	Delay	Fence	Delay	Weight	Time	
16.87	18.01		New Order	44.75		
			0.10	5.00	0.10	
16.87	3.01		Payment	43.10		
			0.10	5.00	0.10	
7.07	2.01		Delivery	4.05		
			0.10	5.00	0.10	

7.07	2.01		Stock Level	4.05		
			0.10	20.00	0.10	
14.07	2.01		Order Status	4.05		
			0.10	5.00	0.10	
			1.2			
			1.2 tt			
Key	RT	RT	Menu	Txn	Think	
				Weight	Time	
Time	Delay	Fence	Delay			
14.46	18.01		New Order	44.83		
			0.10	5.00	0.10	
14.46	3.01		Payment	43.05		
			0.10	5.00	0.10	
6.06	2.01		Delivery	4.04		
			0.10	5.00	0.10	
6.06	2.01		Stock Level	4.04		
			0.10	20.00	0.10	
12.06	2.01		Order Status	4.04		
			0.10	5.00	0.10	
			3.5			
			3.5 tt			
Key	RT	RT	Menu	Txn	Think	
				Weight	Time	
Time	Delay	Fence	Delay			
42.10	18.01		New Order	44.75		
			0.10	5.00	0.10	
42.10	3.01		Payment	43.10		
			0.10	5.00	0.10	
17.60	2.01		Delivery	4.05		
			0.10	5.00	0.10	
17.60	2.01		Stock Level	4.05		
			0.10	20.00	0.10	
35.10	2.01		Order Status	4.05		
			0.10	5.00	0.10	
			1.9			
			1.9 tt			
Key	RT	RT	Menu	Txn	Think	
				Weight	Time	
Time	Delay	Fence	Delay			
22.89	18.01		New Order	44.75		
			0.10	5.00	0.10	
22.89	3.01		Payment	43.10		
			0.10	5.00	0.10	
9.59	2.01		Delivery	4.05		
			0.10	5.00	0.10	
9.59	2.01		Stock Level	4.05		
			0.10	20.00	0.10	
19.09	2.01		Order Status	4.05		
			0.10	5.00	0.10	
			1.1			
			1.1 tt			
Key	RT	RT	Menu	Txn	Think	
				Weight	Time	
Time	Delay	Fence	Delay			

13.25	18.01		New Order	44.83		
			0.10	5.00	0.10	
13.25	3.01		Payment	43.05		
			0.10	5.00	0.10	
5.55	2.01		Delivery	4.04		
			0.10	5.00	0.10	
5.55	2.01		Stock Level	4.04		
			0.10	20.00	0.10	
11.05	2.01		Order Status	4.04		
			0.10	5.00	0.10	
			1.05 better			
			1.05 tt better			
Key	RT	RT	Menu	Txn	Think	
				Weight	Time	
Time	Delay	Fence	Delay			
12.65	18.01		New Order	44.92		
			0.10	5.00	0.10	
12.65	3.01		Payment	43.01		
			0.10	5.00	0.10	
5.30	2.01		Delivery	4.02		
			0.10	5.00	0.10	
5.30	2.01		Stock Level	4.03		
			0.10	20.00	0.10	
10.55	2.01		Order Status	4.02		
			0.10	5.00	0.10	
			1.09			
			1.09 tt			
Key	RT	RT	Menu	Txn	Think	
				Weight	Time	
Time	Delay	Fence	Delay			
13.13	18.01		New Order	44.83		
			0.10	5.00	0.10	
13.13	3.01		Payment	43.05		
			0.10	5.00	0.10	
5.50	2.01		Delivery	4.04		
			0.10	5.00	0.10	
5.50	2.01		Stock Level	4.04		
			0.10	20.00	0.10	
10.95	2.01		Order Status	4.04		
			0.10	5.00	0.10	
			1.08			
			1.08 tt			
Key	RT	RT	Menu	Txn	Think	
				Weight	Time	
Time	Delay	Fence	Delay			
13.01	18.01		New Order	44.83		
			0.10	5.00	0.10	
13.01	3.01		Payment	43.05		
			0.10	5.00	0.10	
5.45	2.01		Delivery	4.04		
			0.10	5.00	0.10	
5.45	2.01		Stock Level	4.04		
			0.10	20.00	0.10	
10.85	2.01		Order Status	4.04		
			0.10	5.00	0.10	
			1.07			

						1.07 tt
Key	RT	RT	Menu	Txn	Think	
				Weight	Time	
Time	Delay	Fence	Delay			
12.89	18.01		New Order	44.83		
			0.10	5.00	0.10	
12.89	3.01		Payment	43.05		
			0.10	5.00	0.10	
5.40	2.01		Delivery	4.04		
			0.10	5.00	0.10	
5.40	2.01		Stock Level	4.04		
			0.10	20.00	0.10	
10.75	2.01		Order Status	4.04		
			0.10	5.00	0.10	
			1.06			
			1.06 tt			
Key	RT	RT	Menu	Txn	Think	
				Weight	Time	
Time	Delay	Fence	Delay			
12.77	18.01		New Order	44.83		
			0.10	5.00	0.10	
12.77	3.01		Payment	43.05		
			0.10	5.00	0.10	
5.35	2.01		Delivery	4.04		
			0.10	5.00	0.10	
5.35	2.01		Stock Level	4.04		
			0.10	20.00	0.10	
10.65	2.01		Order Status	4.04		
			0.10	5.00	0.10	
			1.15			
			1.15 tt			
Key	RT	RT	Menu	Txn	Think	
				Weight	Time	
Time	Delay	Fence	Delay			
13.85	18.01		New Order	44.75		
			0.10	5.00	0.10	
13.85	3.01		Payment	43.10		
			0.10	5.00	0.10	
5.80	2.01		Delivery	4.05		
			0.10	5.00	0.10	
5.80	2.01		Stock Level	4.05		
			0.10	20.00	0.10	
11.55	2.01		Order Status	4.05		
			0.10	5.00	0.10	
			1.25			
			1.25 tt			
Key	RT	RT	Menu	Txn	Think	
				Weight	Time	
Time	Delay	Fence	Delay			
15.06	18.01		New Order	44.83		
			0.10	5.00	0.10	
15.06	3.01		Payment	43.05		
			0.10	5.00	0.10	
6.31	2.01		Delivery	4.04		
			0.10	5.00	0.10	

6.31	2.01		Stock Level	4.04					
			0.10	20.00	0.10				
12.56	2.01		Order Status	4.04					
			0.10	5.00	0.10				
			1.3						
			1.3 tt						
Key	RT	RT	Menu	Txn	Think				
Time	Delay	Fence	Delay	Weight	Time				
15.66	18.01		New Order	44.83					
			0.10	5.00	0.10				
15.66	3.01		Payment	43.05					
			0.10	5.00	0.10				
6.56	2.01		Delivery	4.04					
			0.10	5.00	0.10				
6.56	2.01		Stock Level	4.04					
			0.10	20.00	0.10				
13.06	2.01		Order Status	4.04					
			0.10	5.00	0.10				
			1.12						
			1.12 tt						
Key	RT	RT	Menu	Txn	Think				
Time	Delay	Fence	Delay	Weight	Time				
13.49	18.01		New Order	44.75					
			0.10	5.00	0.10				
13.49	3.01		Payment	43.10					
			0.10	5.00	0.10				
5.65	2.01		Delivery	4.05					
			0.10	5.00	0.10				
5.65	2.01		Stock Level	4.05					
			0.10	20.00	0.10				
11.25	2.01		Order Status	4.05					
			0.10	5.00	0.10				
			1.18						
			1.18 tt						
Key	RT	RT	Menu	Txn	Think				
Time	Delay	Fence	Delay	Weight	Time				
14.21	18.01		New Order	44.75					
			0.10	5.00	0.10				
14.21	3.01		Payment	43.10					
			0.10	5.00	0.10				
5.95	2.01		Delivery	4.05					
			0.10	5.00	0.10				
5.95	2.01		Stock Level	4.05					
			0.10	20.00	0.10				
11.85	2.01		Order Status	4.05					
			0.10	5.00	0.10				
			1.22						
			1.22 tt						
Key	RT	RT	Menu	Txn	Think				
Time	Delay	Fence	Delay	Weight	Time				

14.70	18.01		New Order	44.75					
			0.10	5.00	0.10				
14.70	3.01		Payment	43.10					
			0.10	5.00	0.10				
6.16	2.01		Delivery	4.05					
			0.10	5.00	0.10				
6.16	2.01		Stock Level	4.05					
			0.10	20.00	0.10				
12.26	2.01		Order Status	4.05					
			0.10	5.00	0.10				
			1.28						
			1.28 tt						
Key	RT	RT	Menu	Txn	Think				
Time	Delay	Fence	Delay	Weight	Time				
15.42	18.01		New Order	44.75					
			0.10	5.00	0.10				
15.42	3.01		Payment	43.10					
			0.10	5.00	0.10				
6.46	2.01		Delivery	4.05					
			0.10	5.00	0.10				
6.46	2.01		Stock Level	4.05					
			0.10	20.00	0.10				
12.86	2.01		Order Status	4.05					
			0.10	5.00	0.10				
			1.04						
			1.04 tt						
Key	RT	RT	Menu	Txn	Think				
Time	Delay	Fence	Delay	Weight	Time				
12.53	18.01		New Order	44.83					
			0.10	5.00	0.10				
12.53	3.01		Payment	43.05					
			0.10	5.00	0.10				
5.25	2.01		Delivery	4.04					
			0.10	5.00	0.10				
5.25	2.01		Stock Level	4.04					
			0.10	20.00	0.10				
10.45	2.01		Order Status	4.04					
			0.10	5.00	0.10				
			1.03						
			1.03 tt						
Key	RT	RT	Menu	Txn	Think				
Time	Delay	Fence	Delay	Weight	Time				
12.41	18.01		New Order	44.83					
			0.10	5.00	0.10				
12.41	3.01		Payment	43.05					
			0.10	5.00	0.10				
5.20	2.01		Delivery	4.04					
			0.10	5.00	0.10				
5.20	2.01		Stock Level	4.04					
			0.10	20.00	0.10				
10.35	2.01		Order Status	4.04					
			0.10	5.00	0.10				
			1.02						

			1.02 tt						
Key	RT	RT	Menu	Txn	Think				
Time	Delay	Fence	Delay	Weight	Time				
12.29	18.01		New Order	44.83					
			0.10	5.00	0.10				
12.29	3.01		Payment	43.05					
			0.10	5.00	0.10				
5.15	2.01		Delivery	4.04					
			0.10	5.00	0.10				
5.15	2.01		Stock Level	4.04					
			0.10	20.00	0.10				
10.25	2.01		Order Status	4.04					
			0.10	5.00	0.10				
			1.01						
			1.01 tt						
Key	RT	RT	Menu	Txn	Think				
Time	Delay	Fence	Delay	Weight	Time				
12.17	18.01		New Order	44.83					
			0.10	5.00	0.10				
12.17	3.01		Payment	43.05					
			0.10	5.00	0.10				
5.10	2.01		Delivery	4.04					
			0.10	5.00	0.10				
5.10	2.01		Stock Level	4.04					
			0.10	20.00	0.10				
10.15	2.01		Order Status	4.04					
			0.10	5.00	0.10				
			1.005_best						
			1.005 tt_best						
Key	RT	RT	Menu	Txn	Think				
Time	Delay	Fence	Delay	Weight	Time				
12.11	18.01		New Order	44.88					
			0.10	5.00	0.10				
12.11	3.01		Payment	43.02					
			0.10	5.00	0.10				
5.07	2.01		Delivery	4.03					
			0.10	5.00	0.10				
5.07	2.01		Stock Level	4.03					
			0.10	20.00	0.10				
10.10	2.01		Order Status	4.03					
			0.10	5.00	0.10				
			1.001_best						
			1.001 tt_best						
Key	RT	RT	Menu	Txn	Think				
Time	Delay	Fence	Delay	Weight	Time				
12.06	18.01		New Order	44.91					
			0.10	5.00	0.10				
12.06	3.01		Payment	43.04					
			0.10	5.00	0.10				
5.06	2.01		Delivery	4.01					
			0.10	5.00	0.10				

5.06	2.01		Stock Level	4.02				
			0.10	20.00	0.10			
10.06	2.01		Order Status	4.02				
			0.10	5.00	0.10			
			1.03 better					
			1.03 tt more aggressive					
Key	RT	RT	Menu		Txn	Think		
				Weight	Time			
Time	Delay	Fence	Delay					
12.41	18.01		New Order	44.92				
			0.10	5.00	0.10			
12.41	3.01		Payment	43.01				
			0.10	5.00	0.10			
5.20	2.01		Delivery	4.02				
			0.10	5.00	0.10			
5.20	2.01		Stock Level	4.03				
			0.10	20.00	0.10			
10.35	2.01		Order Status	4.02				
			0.10	5.00	0.10			
			1.005 better					
			1.005 tt more aggressive					
Key	RT	RT	Menu		Txn	Think		
				Weight	Time			
Time	Delay	Fence	Delay					
12.11	18.01		New Order	44.90				
			0.10	5.00	0.10			
12.11	3.01		Payment	43.05				
			0.10	5.00	0.10			
5.07	2.01		Delivery	4.01				
			0.10	5.00	0.10			
5.07	2.01		Stock Level	4.03				
			0.10	20.00	0.10			
10.10	2.01		Order Status	4.01				
			0.10	5.00	0.10			
			1.02 better					
			1.02 tt more aggressive					
Key	RT	RT	Menu		Txn	Think		
				Weight	Time			
Time	Delay	Fence	Delay					
12.29	18.01		New Order	44.92				
			0.10	5.00	0.10			
12.29	3.01		Payment	43.01				
			0.10	5.00	0.10			
5.15	2.01		Delivery	4.02				
			0.10	5.00	0.10			
5.15	2.01		Stock Level	4.03				
			0.10	20.00	0.10			
10.25	2.01		Order Status	4.02				
			0.10	5.00	0.10			
			1.01 best					
			1.01 tt best					
Key	RT	RT	Menu		Txn	Think		
				Weight	Time			
Time	Delay	Fence	Delay					

12.17	18.01		New Order	44.90				
			0.10	5.00	0.10			
12.17	3.01		Payment	43.05				
			0.10	5.00	0.10			
5.10	2.01		Delivery	4.01				
			0.10	5.00	0.10			
5.10	2.01		Stock Level	4.03				
			0.10	20.00	0.10			
10.15	2.01		Order Status	4.01				
			0.10	5.00	0.10			
			1.02 best					
			1.02 tt best					
Key	RT	RT	Menu		Txn	Think		
				Weight	Time			
Time	Delay	Fence	Delay					
12.29	18.01		New Order	44.96				
			0.00	5.00	0.00			
12.29	3.01		Payment	43.00				
			0.00	5.00	0.00			
5.15	2.01		Delivery	4.00				
			0.00	5.00	0.00			
5.15	2.01		Stock Level	4.03				
			0.00	20.00	0.00			
10.25	2.01		Order Status	4.01				
			0.00	5.00	0.00			
			1.03 best					
			1.03 tt best					
Key	RT	RT	Menu		Txn	Think		
				Weight	Time			
Time	Delay	Fence	Delay					
12.41	18.01		New Order	44.96				
			0.10	5.00	0.10			
12.41	3.01		Payment	43.01				
			0.10	5.00	0.10			
5.20	2.01		Delivery	4.01				
			0.10	5.00	0.10			
5.20	2.01		Stock Level	4.01				
			0.10	20.00	0.10			
10.35	2.01		Order Status	4.01				
			0.10	5.00	0.10			
			5.5					
			5.5 tt					
Key	RT	RT	Menu		Txn	Think		
				Weight	Time			
Time	Delay	Fence	Delay					
66.28	18.01		New Order	44.83				
			0.10	5.00	0.10			
66.28	3.01		Payment	43.05				
			0.10	5.00	0.10			
27.77	2.01		Delivery	4.04				
			0.10	5.00	0.10			
27.77	2.01		Stock Level	4.04				
			0.10	20.00	0.10			
55.27	2.01		Order Status	4.04				
			0.10	5.00	0.10			
			6.0					

			6.0 tt					
Key	RT	RT	Menu		Txn	Think		
				Weight	Time			
Time	Delay	Fence	Delay					
72.30	18.01		New Order	44.83				
			0.10	5.00	0.10			
72.30	3.01		Payment	43.05				
			0.10	5.00	0.10			
30.30	2.01		Delivery	4.04				
			0.10	5.00	0.10			
30.30	2.01		Stock Level	4.04				
			0.10	20.00	0.10			
60.30	2.01		Order Status	4.04				
			0.10	5.00	0.10			
			6.5					
			6.5 tt					
Key	RT	RT	Menu		Txn	Think		
				Weight	Time			
Time	Delay	Fence	Delay					
79.53	18.01		New Order	44.83				
			0.10	5.00	0.10			
79.53	3.01		Payment	43.05				
			0.10	5.00	0.10			
33.33	2.01		Delivery	4.04				
			0.10	5.00	0.10			
33.33	2.01		Stock Level	4.04				
			0.10	20.00	0.10			
66.33	2.01		Order Status	4.04				
			0.10	5.00	0.10			
			7.0					
			7.0 tt					
Key	RT	RT	Menu		Txn	Think		
				Weight	Time			
Time	Delay	Fence	Delay					
84.35	18.01		New Order	44.83				
			0.10	5.00	0.10			
84.35	3.01		Payment	43.05				
			0.10	5.00	0.10			
35.35	2.01		Delivery	4.04				
			0.10	5.00	0.10			
35.35	2.01		Stock Level	4.04				
			0.10	20.00	0.10			
70.35	2.01		Order Status	4.04				
			0.10	5.00	0.10			
			7.5					
			7.5 tt					
Key	RT	RT	Menu		Txn	Think		
				Weight	Time			
Time	Delay	Fence	Delay					
90.38	18.01		New Order	44.83				
			0.10	5.00	0.10			
90.38	3.01		Payment	43.05				
			0.10	5.00	0.10			
37.88	2.01		Delivery	4.04				
			0.10	5.00	0.10			

37.88	2.01		Stock Level	4.04					
			0.10	20.00	0.10				
75.38	2.01		Order Status	4.04					
			0.10	5.00	0.10				
			8.0						
			8.0 tt						
Key	RT	RT	Menu	Txn	Think				
Time	Delay	Fence	Delay	Weight	Time				
96.40	18.01		New Order	44.83					
			0.10	5.00	0.10				
96.40	3.01		Payment	43.05					
			0.10	5.00	0.10				
40.40	2.01		Delivery	4.04					
			0.10	5.00	0.10				
40.40	2.01		Stock Level	4.04					
			0.10	20.00	0.10				
80.40	2.01		Order Status	4.04					
			0.10	5.00	0.10				
			8.5						
			8.5 tt						
Key	RT	RT	Menu	Txn	Think				
Time	Delay	Fence	Delay	Weight	Time				
102.43	18.01		New Order	44.83					
			0.10	5.00	0.10				
192.43	3.01		Payment	43.05					
			0.10	5.00	0.10				
42.92	2.01		Delivery	4.04					
			0.10	5.00	0.10				
42.92	2.01		Stock Level	4.04					
			0.10	20.00	0.10				
85.42	2.01		Order Status	4.04					
			0.10	5.00	0.10				
			9.0						
			9.0 tt						
Key	RT	RT	Menu	Txn	Think				
Time	Delay	Fence	Delay	Weight	Time				
108.45	18.01		New Order	44.83					
			0.10	5.00	0.10				
108.45	3.01		Payment	43.05					
			0.10	5.00	0.10				
45.45	2.01		Delivery	4.04					
			0.10	5.00	0.10				
45.45	2.01		Stock Level	4.04					
			0.10	20.00	0.10				
90.45	2.01		Order Status	4.04					
			0.10	5.00	0.10				
			9.5						
			9.5 tt						
Key	RT	RT	Menu	Txn	Think				
Time	Delay	Fence	Delay	Weight	Time				

114.47	18.01		New Order	44.83					
			0.10	5.00	0.10				
114.47	3.01		Payment	43.05					
			0.10	5.00	0.10				
47.98	2.01		Delivery	4.04					
			0.10	5.00	0.10				
47.98	2.01		Stock Level	4.04					
			0.10	20.00	0.10				
95.47	2.01		Order Status	4.04					
			0.10	5.00	0.10				
			10						
			10 tt						
Key	RT	RT	Menu	Txn	Think				
Time	Delay	Fence	Delay	Weight	Time				
120.50	18.01		New Order	44.83					
			0.10	5.00	0.10				
120.50	3.01		Payment	43.05					
			0.10	5.00	0.10				
50.50	2.01		Delivery	4.04					
			0.10	5.00	0.10				
50.50	2.01		Stock Level	4.04					
			0.10	20.00	0.10				
100.50	2.01		Order Status	4.04					
			0.10	5.00	0.10				
			1.02 better						
			1.02 more aggressive						
Key	RT	RT	Menu	Txn	Think				
Time	Delay	Fence	Delay	Weight	Time				
12.05	18.01		New Order	44.92					
			0.10	5.00	0.10				
12.05	3.01		Payment	43.01					
			0.10	5.00	0.10				
5.05	2.01		Delivery	4.02					
			0.10	5.00	0.10				
5.05	2.01		Stock Level	4.03					
			0.10	20.00	0.10				
10.05	2.01		Order Status	4.02					
			0.10	5.00	0.10				
			1.01 better						
			1.01 more aggressive						
Key	RT	RT	Menu	Txn	Think				
Time	Delay	Fence	Delay	Weight	Time				
12.17	18.01		New Order	44.92					
			0.10	5.00	0.10				
12.17	3.01		Payment	43.01					
			0.10	5.00	0.10				
5.10	2.01		Delivery	4.02					
			0.10	5.00	0.10				
5.10	2.01		Stock Level	4.03					
			0.10	20.00	0.10				
10.15	2.01		Order Status	4.02					
			0.10	5.00	0.10				
			1.001 better						

				1.001 more aggressive					
Key	RT	RT	Menu	Txn	Think				
Time	Delay	Fence	Delay	Weight	Time				
12.06	18.01		New Order	44.92					
			0.10	5.00	0.10				
12.06	3.01		Payment	43.01					
			0.10	5.00	0.10				
5.06	2.01		Delivery	4.02					
			0.10	5.00	0.10				
5.06	2.01		Stock Level	4.03					
			0.10	20.00	0.10				
10.06	2.01		Order Status	4.02					
			0.10	5.00	0.10				
			FullSpeed						
			1.000 tt						
Key	RT	RT	Menu	Txn	Think				
Time	Delay	Fence	Delay	Weight	Time				
12.05	18.01		New Order	44.92					
			0.10	5.00	0.10				
12.05	3.01		Payment	43.01					
			0.10	5.00	0.10				
5.05	2.01		Delivery	4.02					
			0.10	5.00	0.10				
5.05	2.01		Stock Level	4.03					
			0.10	20.00	0.10				
10.05	2.01		Order Status	4.02					
			0.10	5.00	0.10				
			1.003 best						
			1.003 best						
Key	RT	RT	Menu	Txn	Think				
Time	Delay	Fence	Delay	Weight	Time				
12.09	18.01		New Order	44.90					
			0.10	5.00	0.10				
12.09	3.01		Payment	43.05					
			0.10	5.00	0.10				
5.07	2.01		Delivery	4.01					
			0.10	5.00	0.10				
5.07	2.01		Stock Level	4.03					
			0.10	20.00	0.10				
10.08	2.01		Order Status	4.01					
			0.10	5.00	0.10				

Appendix D: 60-Day Space

TPC-C 60 Day Space Requirements						
Warehouses	16,400				TpmC	206,181.00
Table	Rows	Data KB	Index KB	Extra 5% KB	8hr Space	Total Space KB
Warehouse	16,800	1,792	120	96		2008
District	168,000	18,672	160	942		19774
Customer	504,000,000	366,545,456	22,870,128	19,470,779		408886363
History	504,000,000	29,430,664	110,048		6,481,559	29540712
New_order	151,200,000	2,693,992	6,808	135,040		2835840
Orders	504,000,000	16,457,144	37,536		9,851,741	16494680
Order_line	5,039,988,259	330,491,040	778,424		121,058,626	331269464
Item	100,000	9,416	136	478		10030
Stock	1,680,000,000	537,600,000	1,133,704	26,936,685		565670389
Total		1,283,248,176	24,937,064	46,544,019	137,391,927	1,354,729,259
MB						
Dynamic Space	367,557	Sum of Data for Order, Orderline and History				
Static Space	955,420	Sum of Data+Index+5%-Dynamic Space				
Free Space	na	Total Allocated Spac - (Dynamic + Static Space)				
Daily Growth	73,935	(Dynamic Space/(W*62.5))*tpmc				
Daily Spread	-	(Free Space -1.5*Daily Growth) Zero Assumed				
60 Day Space MB	5,391,520					
60 Day Space GB	5,265.16	GB				
Log Size	701,000.00	MB				
KB Per New Order	6.47	KB				
8 hr log MB	625,778	MB				
8 hr log GB	611.1116	GB				
Space Usage	GB Needed	Disks Measured	GB Priced	Disk Size	Formatted Size	
60 Day Space DB	5,265.16	392	13296.64	36.4GB	33.920	
			0.00			
			0.00			
Total DB			13296.64			

MSSQL_misc_fg	MSSQL_cs_fg
2008	
19774	
	408886363
36022271	
2835840	
26346421	
452328090	
10030	
	565670389
517,564,433	974,556,752
files= 14	14
size= 5,056,000	9,472,000
Total= 70,784,000	132,608,000
8K blocks 566,272,000	1,060,864,000
OK	OK

8-hr log + mirror	1,222.2233	12	1640.76	146.8GB	136.73
OS, Swap	3	2	67.84	36.4GB	33.920
Total Storage	6,490.38	GB	15,005.24	GB	

Appendix E:
Third Party Letters

Microsoft Corporation
One Microsoft Way
Redmond, WA 98052-6399

Tel 425 882 8080
Fax 425 936 7329
<http://www.microsoft.com/>

Microsoft

October 13, 2005

Hewlett-Packard Company
David Adams
20555 SH 249
MS 150402
Houston, TX 77040

Mr. Adams:

Here is the information you requested regarding pricing for several Microsoft products to be used in conjunction with your TPC-C benchmark testing.

All pricing shown is in US Dollars (\$).

Part Number	Description	Unit Price	Quantity	Price
810-03134	SQL Server 2005 Enterprise x64 Edition <i>Per Processor License</i> <i>Discount Schedule: Open Program - Level C</i> <i>Unit Price reflects a 6% discount from the retail unit price of \$24,999.</i>	\$23,432	4	\$93,728
P72-00274	Windows Server 2003 Enterprise x64 Edition <i>Server License Only - No CALs</i> <i>Discount Schedule: Open Program - No Level</i> <i>Unit Price reflects a 42% discount from the retail unit price of \$3,999.</i>	\$2,334	1	\$2,334
C11-00821	Windows 2000 Server <i>Server License Only - No CALs</i> <i>Discount Schedule: No Level</i> <i>Unit Price reflects a 8% discount from the retail unit price of \$799.</i>	\$738	8	\$5,904
254-00170	Visual C++ Standard Edition <i>No Discounts Applied</i>	\$109	1	\$109
N/A	Microsoft Problem Resolution Services <i>Professional Support</i> <i>(1 Incident)</i>	\$245	1	\$245

Some products may not be currently orderable but will be available through Microsoft's normal distribution channels by November 7, 2005.

Defect support is included in the purchase price. Additional support is available from Microsoft PSS on an incident by incident basis at \$245 per call.

This quote is valid for the next 90 days.

If we can be of any further assistance, please contact Jamie Reding at (425) 703-0510 or jamiere@microsoft.com.

Reference ID: PCdada0511101370.
Please include this Reference ID in any correspondence regarding this price quote.