
**HP Integrity Superdome - Itanium2/1.6 GHz/18MB iL3
- 64p/128c**
using
HP-UX 11i v3 64-bit
and
**Oracle Database 10g Release 2 Enterprise Edition with
Partitioning and Oracle Automatic Storage
Management**

TPC Benchmark™ H Full Disclosure Report

First Edition

June 18, 2007



First Edition - June 18, 2007

Hewlett-Packard Company, the sponsor of this benchmark test, believes that the information in this document is accurate as of the publication date. The information in this document is subject to change without notice. The sponsors assume no responsibility for any errors that may appear in this document. The pricing information in this document is believed to accurately reflect the current prices as of the publication date. However, the sponsors provide no warranty of the pricing information in this document.

Benchmark results are highly dependent upon workload, specific application requirements, and system design and implementation. Relative system performance will vary as a result of these and other factors. Therefore, TPC Benchmark H should not be used as a substitute for a specific customer application benchmark when critical capacity planning and/or product evaluation decisions are contemplated.

All performance data contained in this report was obtained in a rigorously controlled environment. Results obtained in other operating environments may vary significantly. No warranty of system performance or price/performance is expressed or implied in this report.

© Copyright Hewlett-Packard Company, 2007.

All rights reserved. Permission is hereby granted to reproduce this document in whole or in part provided the copyright notice printed above is set forth in full text on the title page of each item reproduced.

Printed in U.S.A., June 18, 2007.

HP, HP-UX, HP C/HP-UX, HP 9000 are registered trademarks of Hewlett-Packard Company.

ORACLE 10g, SQL*DBA, SQL*Loader, SQL*Net, SQL*Plus, Pro *C, and PL/SQL are trademarks of the Oracle Corporation

UNIX is a registered trademark in the United States, and other countries, licensed exclusively through X/Open Company Limited.

TPC Benchmark and TPC-H are registered trademarks of the Transaction Processing Performance Council.

All other brand or product names mentioned herein must be considered trademarks or registered trademarks of their respective owners.

Overview

This report documents the methodology and results of the TPC Benchmark™ H test conducted on the HP Integrity Superdome - Itanium2/1.6 GHz/18MB iL3 - 64p/128c, in conformance with the requirements of the TPC Benchmark™ H Standard Specification, Revision 2.6.0. The operating system used for the benchmark was HP-UX 11i v3 64-bit; the DBMS was Oracle Database 10g Release 2 Enterprise Edition with Partitioning and Oracle Automatic Storage Management.

Standard and Executive Summary Statements

The pages following this preface contain the Executive Summary and Numerical Quantities Summary of the benchmark results.

Auditor

The benchmark configuration, environment and methodology used to produce and validate the test results and the pricing model used to calculate the cost per QphH was audited by Francois Raab, InfoSizing, to verify compliance with the relevant TPC specifications.

TPC Benchmark H Overview

The TPC Benchmark™ H (TPC-H) is a decision support benchmark. It consists of a suite of business oriented ad-hoc queries and concurrent data modifications. The queries and the data populating the database have been chosen to have broad industry-wide relevance while maintaining a sufficient degree of ease of implementation. This benchmark illustrates decision support systems that

- Examine large volumes of data;
- Execute queries with a high degree of complexity;
- Give answers to critical business questions.

TPC-H evaluates the performance of various decision support systems by the execution of sets of queries against a standard database under controlled conditions. The TPC-H queries:

- Give answers to real-world business questions;
- Simulate generated ad-hoc queries(e.g., via a point and click GUI interface);
- Are far more complex than most OLTP transactions;
- Include a rich breadth of operators and selectivity constraints;
- Generate intensive activity on the part of the database server component of the system under test;
- Are executed against a database complying to specific population and scaling requirements;
- Are implemented with constraints derived from staying closely synchronized with an on-line production database.

The TPC-H operations are modeled as follows:

- The database is continuously available 24 hours a day, 7 days a week, for ad-hoc queries from multiple end users and updates against all tables, except possibly during infrequent (e.g., once a month) maintenance sessions;
- The TPC-H database tracks, possibly with some delay, the state of the OLTP database through ongoing updates which batch together a number of modifications impacting some part of the decision support database;
- Due to the world-wide nature of the business data stored in the TPC-H database, the queries and the updates may be executed against the database at any time, especially in relation to each other. In addition, this mix of queries and updates is subject to specific ACIDity requirements, since queries and updates may execute concurrently;

- To achieve the optimal compromise between performance and operational requirements the database administrator can set, once and for all, the locking levels and the concurrent scheduling rules for queries and updates.

The minimum database required to run the benchmark holds business data from 10,000 suppliers. It contains almost ten million rows representing a raw storage capacity of about 1 GB. Compliant benchmark implementations may also use one of the larger permissible database populations (e.g. 30000 GB), as defined in Clause 4.1.3.

The performance metrics reported by TPC-H measure multiple aspects of the capability of the system to process queries. The TPC-H metric at the selected size (QphH@Size) is the performance metric. To be compliant with the TPC-H standard, all references to TPC-H results for a given configuration must include all required reporting components (see Clause 5.4.7). The TPC believes that comparisons of TPC-H results measured against different database sizes are misleading and discourages such comparisons.

The TPC-H database must be implemented using a commercially available database management system (DBMS), and the queries executed via an interface using dynamic SQL. The specification provides for variants of SQL, as implementers are not required to have implemented a specific SQL standard in full. TPC-D uses terminology and metrics that are similar to other benchmarks, originated by the TPC and others. Such similarity in terminology does not in any way imply that TPC-H results are comparable to other benchmarks. The only benchmark results comparable to TPC-H are other TPC-H results compliant with the same revision.

Despite the fact that this benchmark offers a rich environment representative of many decision support systems, this benchmark does not reflect the entire range of decision support requirements. In addition, the extent to which a customer can achieve the results reported by a vendor is highly dependent on how closely TPC-H approximates the customer application. The relative performance of systems derived from this benchmark does not necessarily hold for other workloads or environments. Extrapolations to any other environment are not recommended.

Benchmark results are highly dependent upon workload, specific application requirements, and systems design and implementation. Relative system performance will vary as a result of these and other factors. Therefore, TPC-H should not be used as a substitute for a specific customer application benchmarking when critical capacity planning and/or product evaluation decisions are contemplated.


Benchmark sponsors are permitted several possible system designs, provided that they adhere to the model described in Clause 6. A full disclosure report (FDR) of the implementation details, as specified in Clause 8, must be made available along with the reported results.

General Implementation Guidelines

The purpose of TPC benchmarks is to provide relevant, objective performance data to industry users. To achieve that purpose, TPC benchmark specifications require that benchmark tests be implemented with systems, products, technologies and pricing that:

- Are generally available to users;
- Are relevant to the market segment that the individual TPC benchmark models or represents (e.g. TPC-H models and represents complex, high data volume, decision support environments);
- Would plausibly be implemented by a significant number of users in the market segment the benchmark models or represents.

Hewlett-Packard Company does not warrant or represent that a user can or will achieve performance similar to the benchmark results contained in this report. No warranty of system performance or price/performance is expressed or implied by this report

	HP Integrity Superdome - Itanium2/1.6 GHz/18MB iL3 - 64p/128c	TPC-H Rev 2.6.0
		Report Date: June 18, 2007
Total System Cost	Composite Query per Hour Metric	Price/Performance
\$7,048,382 USD	150,960.5 QphH@30000GB	\$46.69 USD QphH@30000GB
Database Size	Database Manager	Operating System
30000 GB*	Oracle Database 10g Release 2 Enterprise Edition with Partitioning and Oracle Automatic Storage Management	HP-UX 11i v3 64-bit
Other Software		Availability Date
		None
		June 18, 2007
		
Database Load Time = 16:06:11	Load Includes Backup: N	Total Data Storage/Database Size = 14.96
RAID (Base Tables Only): N	RAID (Base Tables and Auxiliary Data Structures): N	RAID (All): Y
System Configuration		
Number of Nodes:	1	
Processors/Cores/Threads/Type:	64/128/128 / Intel Itanium2 9040 1.6GHz, 9MB iL3 cache per core	
Memory:	1024 GB	
Disk Drives:	1 HP Surestore Disk System 2120 with 4 36GB disks and 256 HP StorageWorks MSA1000 (with a total of 3072 146GB 15K RPM disks)	
Total Disk Storage	448656GB (In this number one GB is defined as 1024*1024*1024 bytes)	
Lan Controllers	1 PCI 1000BT Lan Adapter	

*Database Size includes only raw data (e.g. no temp, index, redundant storage space, etc.)

	HP Integrity Superdome - Itanium2/1.6 GHz/18MB iL3 - 64p/128c	TPC-H Rev 2.6.0				
		Report Date: June 18, 2007				
Description	Part Number	Source	Reference Price	Qty	Extended Price	3 yr. Maint. Price
Server Hardware						
Superdome left chassis	A9834A, Opt 429	1	235,950	1	235,950	
Superdome right chassis	A9835A, Opt 429	1	249,950	1	249,950	
Superdome sx2000 Cell Board	A9837A	1	19,250	16	308,000	
24x7x4hr - 3 Year Svc & Support Price (Hardware and Software)						\$1,379,874
512GB Memory Bundle (128x4GB dimms)	A9857A	1	1,299,950	2	2,599,900	
12-Slot PCI-X I/O Chassis	A9836A	1	16,950	16	271,200	
Dual-Core Intel Itanium2 9040/1.6GHz/18MB L3	AB406A	1	23,000	64	1,472,000	
PCI 1000BT Lan Adapter	A6847A	1	1,325	1	1,325	
PCI-X 4GB Fibre Channel Adapter (dual port)	AB379B	1	3,495	128	447,360	
PCI Dual Channel Ultra320 SCSI Adapter	A7173A	1	795	1	795	
HPDisk System 2120	A7382A	1	995	1	995	
1-36GB LP 15K HDD	A7527A	1	966	4	3,864	
HP Universal Rack 10642 G2 Pallet Rack	AF001A	1	1,249	1	1,249	
Modular Power Dist Unit for std racks	A5137AZ	1	145	1	145	
200-240 volts North America	A5137AZ, Opt AW4	1	94	1	94	
HP Tape Array 5300 (DVD and DAT tape)	C7508B	1	729	1	729	
HP rx2620 Server (inc mem/disk/monitor/keyboard/mouse)	AB333A	1	5,315	1	5,315	
I/O Chassis Enclosure for 12-Slot PCI-X Chassis	A9852A	1	25,750	4	103,000	
Graphite I/O expansion power subsystem	A5861D	1	34,860	2	69,720	
				Subtotal	5,771,591	1,379,874
Server Software						
Oracle Database 10g Release 2 Enterprise Edition		2	10,000	64	640,000	
Named User Plus for 3 years						
Partitioning, Named User Plus for 3 years		2	2,500	64	160,000	
Oracle Database Server Support Package for 3 years:		2	6,000	1		6,000
HPUX 11i v3 Foundation Operating Environment	B9429AC	1	2,370	128	303,360	
HP-UX 11i v3 HP9000/Integrity FOE Media	BA489AA, Opt AJR	1	565	1	565	
					1,103,925	6,000
Storage						
5m Fibre Channel Cables	221692-B22	1	82	256	20,992	
HP StorageWorks MSA 1000 (256 + 26 spares)	201723-B22	1	6,499	282	1,832,718	
3 Yr Support Price for MSA1000 and disks						Included
146GB 15K Ultra320 Hard Drive (3072 + 308 spares)	347708- B22	1	689	3,380	2,328,820	
HP Universal Rack 10642 G2 Pallet Rack	AF001A	1	1,249	28	35,222	
Modular Power Dist Unit for std racks	A5137AZ	1	145	113	16,356	
200-240 volts North America	A5137AZ, Opt AW4	1	94	113	10,603	
ProLiant Cluster HA/200 for MSA1000	252409-B22	1	4,007	1	4,007	
				Subtotal	4,248,718	0
				Total	11,124,234	1,385,874
Oracle Mandatory E-Business Discount on (Licenses and Support)					(161,200)	
45.3% Large Configuration Discount and Support Prepayment*					(4,555,394)	(745,132)
				Grand Total	6,407,640	640,742
Source: 1=HP, 2=Oracle					3-yr Cost of Ownership:	7,048,382
*All discounts are based on US list prices and for similar quantities and configurations					QphH@30000GB:	150,960.5
Audited By: Francois Raab for InfoSizing (www.sizing.com)					\$/QphH@30000GB:	46.69
Prices used in TPC benchmarks reflect actual prices a customer would pay for a one-time purchase of the stated components. Individually negotiated discounts are not permitted. Special prices based on assumptions about past or future purchases are not permitted. All discounts reflect standard pricing policies for the listed components. For complete details, see the pricing sections of the TPC benchmark specifications. If you find the stated prices are not available according to these terms, please inform the TPC at pricing@tpc.org . Thank you.						



HP Integrity Superdome - Itanium2/1.6 GHz/18MB iL3 - 64p/128c

TPC-H Rev 2.6.0

Report Date: June 18, 2007

Measurement Results

Database Scaling (SF/size)	30000
Total Data Storage/Database Size	14.96
Start of Database Load Time	2007-05-24 17:50:48
End of Database Load Time	2007-05-25 09:56:59
Database Load Time	16:06:11
Query Streams for Throughput Test (S)	10
TPC-H Power	201,316.1
TPC-H Throughput	113,200.5
TPC-H Composite Query-per-Hour Metric (QphH@30000GB)	150,960.5
Total System Price Over 3 Years	7,048,382
TPC-H Price/Performance Metric (\$/QphH@30000GB)	\$47

Measurement Intervals

Measurement Interval in Throughput Test (Ts)	209,893
--	---------

Duration of Stream Execution:

Power Stream	Seed	RF1 Start Time RF1 End Time	Query Start Time Query End Time	RF2 Start Time RF2 End Time	Duration (sec)
	525095659	05/28/07 03:48:02 05/28/07 03:53:27	05/28/07 03:53:27 05/28/07 09:47:51	05/28/07 09:47:52 05/28/07 09:56:42	22,120

Throughput Stream	Seed	Query Start Time Query End Time	Duration (sec)	RF1 Start Time RF1 End Time	RF2 Start Time RF2 End Time
1	525095660	05/28/07 09:56:43 05/30/07 16:47:05	197,422	05/30/07 18:18:03 05/30/07 18:20:52	05/30/07 18:20:52 05/30/07 18:29:18
2	525095661	05/28/07 09:56:43 05/30/07 18:18:03	202,880	05/30/07 18:29:18 05/30/07 18:32:37	05/30/07 18:32:37 05/30/07 18:41:05
3	525095662	05/28/07 09:56:43 05/30/07 16:11:41	195,298	05/30/07 18:41:05 05/30/07 18:44:24	05/30/07 18:44:24 05/30/07 18:52:56
4	525095663	05/28/07 09:56:43 05/30/07 14:44:42	190,079	05/30/07 18:52:56 05/30/07 18:56:13	05/30/07 18:56:13 05/30/07 19:04:45
5	525095664	05/28/07 09:56:43 05/30/07 16:05:09	194,906	05/30/07 19:04:45 05/30/07 19:08:03	05/30/07 19:08:03 05/30/07 19:16:34
6	525095665	05/28/07 09:56:43 05/30/07 17:25:55	199,752	05/30/07 19:16:34 05/30/07 19:19:50	05/30/07 19:19:50 05/30/07 19:28:10
7	52509566	05/28/07 09:56:43 05/30/07 12:35:55	182,352	05/30/07 19:28:10 05/30/07 19:31:26	05/30/07 19:31:26 05/30/07 19:39:52
8	525095667	05/28/07 09:56:43 05/30/07 15:53:47	194,223	05/30/07 19:39:52 05/30/07 19:43:11	05/30/07 19:43:11 05/30/07 19:51:37
9	525095668	05/28/07 09:56:43 05/30/07 14:33:27	189,403	05/30/07 19:51:37 05/30/07 19:54:55	05/30/07 19:54:55 05/30/07 20:03:18
10	525095669	05/28/07 09:56:43 05/30/07 16:57:27	198,021	05/30/07 20:03:18 05/30/07 20:06:34	05/30/07 20:06:34 05/30/07 20:14:56



HP Integrity Superdome - Itanium2/1.6 GHz/18MB iL3 - 64p/128c

TPC-H Rev 2.6.0

Report Date June 18, 2007

TPC-H Timing Intervals (in seconds)

Duration of stream execution:

Stream ID	Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8a	Q9	Q10	Q11	Q12
Stream 00	2722.3	183.4	155.0	135.1	817.2	97.3	883.1	414.7	2810.1	452.5	610.0	610.5
Stream 01	12827.2	1141.3	914.1	730.5	7797.0	254.8	7500.9	2718.7	26315.6	7854.8	2857.4	9240.7
Stream 02	17099.3	793.4	1022.8	1384.7	6324.3	392.4	7493.8	2534.4	25624.7	7392.4	21656.7	3276.5
Stream 03	18062.8	1091.5	264.2	1452.4	7788.6	166.6	8526.9	4504.9	18377.5	6881.5	24750.3	1020.8
Stream 04	19428.7	1452.8	1052.3	983.9	4118.0	121.4	9420.4	3092.8	15784.6	7202.2	11824.9	1741.1
Stream 05	18436.1	1287.4	1364.9	975.0	8323.2	374.9	8199.2	3576.5	20021.0	6501.2	6265.1	3264.5
Stream 06	17492.9	1599.6	1463.8	1319.3	8287.5	300.9	7467.0	2604.6	20728.2	3144.7	17432.3	4108.4
Stream 07	15535.2	1136.9	1212.3	1476.5	8031.1	162.9	10687.7	2225.7	17129.6	6211.9	7530.5	5343.7
Stream 08	19562.8	710.3	1095.4	997.5	6984.9	374.3	8157.5	2587.6	19921.0	6498.3	9178.6	4057.3
Stream 09	17139.7	1414.6	1156.4	958.4	7725.4	358.0	8924.2	3831.6	21261.8	6387.6	7647.3	5005.5
Stream 10	15567.9	1191.0	1170.0	242.7	1302.5	232.2	9360.4	692.4	22650.3	7035.0	3920.9	1764.4
Average	17115.3	1181.9	1071.6	1052.1	6668.2	273.8	8573.8	2836.9	20781.4	6510.9	11306.4	3882.3
Maximum	19562.8	1599.6	1463.8	1476.5	8323.2	392.4	10687.7	4504.9	26315.6	7854.8	24750.3	9240.7

Stream ID	Q13	Q14	Q15a	Q16	Q17	Q18	Q19	Q20	Q21	Q22	RF1	RF2
Stream 00	1360.2	96.0	132.3	622.4	668.1	3348.7	668.4	804.3	3374.6	298.4	324.5	530.5
Stream 01	13143.0	249.9	1168.0	4609.2	930.7	44337.2	3842.5	1071.3	46509.8	1407.4	168.6	506.1
Stream 02	9135.3	364.7	1004.7	5658.7	5561.9	50840.8	3904.7	14415.4	15067.4	1931.2	199.0	507.9
Stream 03	8126.3	236.3	939.8	3446.1	1331.9	38816.9	1578.6	11177.8	35087.3	1669.4	199.2	512.0
Stream 04	10750.2	330.4	1102.2	4137.3	1875.4	54792.2	4112.7	1293.7	33398.5	2063.9	196.7	511.7
Stream 05	13953.5	263.5	832.3	4785.1	1120.2	40482.2	1721.3	2983.0	48115.0	2060.9	198.1	510.7
Stream 06	12707.8	322.8	1185.9	6319.9	3233.1	53230.9	2874.1	3798.9	28317.3	1810.4	196.0	499.7
Stream 07	12605.3	309.8	1148.0	5289.9	2844.1	48074.3	1791.9	3088.7	28335.6	2180.9	196.5	505.5
Stream 08	10764.8	307.0	1214.9	4876.6	1205.7	47239.9	3812.8	10288.6	32389.6	1998.4	199.6	506.0
Stream 09	12122.9	300.8	923.6	4839.3	2924.9	43725.9	1553.5	2737.4	36834.9	1630.0	197.7	502.6
Stream 10	10160.4	364.5	1958.2	5673.7	2560.1	71268.9	1476.3	3702.5	34395.9	1331.0	196.6	501.6
Average	11347.0	305.0	1147.8	4963.6	2358.8	49280.9	2666.8	5455.7	33845.1	1808.3	194.8	506.4
Maximum	13953.5	364.7	1958.2	6319.9	5561.9	71268.9	4112.7	14415.4	48115.0	2180.9	199.6	512.0



HP Integrity Superdome - Itanium2/1.6 GHz/18MB iL3 - 64p/128c

TPC-H Rev 2.6.0

Report Date June 18, 2007

TPC-H Timing Intervals (in seconds)

Duration of stream execution:

Stream ID	Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8a	Q9	Q10	Q11	Q12
Stream 00	2722.3	183.4	155.0	135.1	817.2	97.3	883.1	414.7	2810.1	452.5	610.0	610.5
Stream 01	12827.2	1141.3	914.1	730.5	7797.0	254.8	7500.9	2718.7	26315.6	7854.8	2857.4	9240.7
Stream 02	17099.3	793.4	1022.8	1384.7	6324.3	392.4	7493.8	2534.4	25624.7	7392.4	21656.7	3276.5
Stream 03	18062.8	1091.5	264.2	1452.4	7788.6	166.6	8526.9	4504.9	18377.5	6881.5	24750.3	1020.8
Stream 04	19428.7	1452.8	1052.3	983.9	4118.0	121.4	9420.4	3092.8	15784.6	7202.2	11824.9	1741.1
Stream 05	18436.1	1287.4	1364.9	975.0	8323.2	374.9	8199.2	3576.5	20021.0	6501.2	6265.1	3264.5
Stream 06	17492.9	1599.6	1463.8	1319.3	8287.5	300.9	7467.0	2604.6	20728.2	3144.7	17432.3	4108.4
Stream 07	15535.2	1136.9	1212.3	1476.5	8031.1	162.9	10687.7	2225.7	17129.6	6211.9	7530.5	5343.7
Stream 08	19562.8	710.3	1095.4	997.5	6984.9	374.3	8157.5	2587.6	19921.0	6498.3	9178.6	4057.3
Stream 09	17139.7	1414.6	1156.4	958.4	7725.4	358.0	8924.2	3831.6	21261.8	6387.6	7647.3	5005.5
Stream 10	15567.9	1191.0	1170.0	242.7	1302.5	232.2	9360.4	692.4	22650.3	7035.0	3920.9	1764.4
Average	17115.3	1181.9	1071.6	1052.1	6668.2	273.8	8573.8	2836.9	20781.4	6510.9	11306.4	3882.3
Maximum	19562.8	1599.6	1463.8	1476.5	8323.2	392.4	10687.7	4504.9	26315.6	7854.8	24750.3	9240.7

Stream ID	Q13	Q14	Q15a	Q16	Q17	Q18	Q19	Q20	Q21	Q22	RF1	RF2
Stream 00	1360.2	96.0	132.3	622.4	668.1	3348.7	668.4	804.3	3374.6	298.4	324.5	530.5
Stream 01	13143.0	249.9	1168.0	4609.2	930.7	44337.2	3842.5	1071.3	46509.8	1407.4	168.6	506.1
Stream 02	9135.3	364.7	1004.7	5658.7	5561.9	50840.8	3904.7	14415.4	15067.4	1931.2	199.0	507.9
Stream 03	8126.3	236.3	939.8	3446.1	1331.9	38816.9	1578.6	11177.8	35087.3	1669.4	199.2	512.0
Stream 04	10750.2	330.4	1102.2	4137.3	1875.4	54792.2	4112.7	1293.7	33398.5	2063.9	196.7	511.7
Stream 05	13953.5	263.5	832.3	4785.1	1120.2	40482.2	1721.3	2983.0	48115.0	2060.9	198.1	510.7
Stream 06	12707.8	322.8	1185.9	6319.9	3233.1	53230.9	2874.1	3798.9	28317.3	1810.4	196.0	499.7
Stream 07	12605.3	309.8	1148.0	5289.9	2844.1	48074.3	1791.9	3088.7	28335.6	2180.9	196.5	505.5
Stream 08	10764.8	307.0	1214.9	4876.6	1205.7	47239.9	3812.8	10288.6	32389.6	1998.4	199.6	506.0
Stream 09	12122.9	300.8	923.6	4839.3	2924.9	43725.9	1553.5	2737.4	36834.9	1630.0	197.7	502.6
Stream 10	10160.4	364.5	1958.2	5673.7	2560.1	71268.9	1476.3	3702.5	34395.9	1331.0	196.6	501.6
Average	11347.0	305.0	1147.8	4963.6	2358.8	49280.9	2666.8	5455.7	33845.1	1808.3	194.8	506.4
Maximum	13953.5	364.7	1958.2	6319.9	5561.9	71268.9	4112.7	14415.4	48115.0	2180.9	199.6	512.0



Benchmark Sponsor: **Sharada Bose**
Performance Manager BCS
Hewlett-Packard
Pruneridge Avenue, MS4105
94065 Cupertino, CA 95014

June 15, 2007

I verified the TPC Benchmark™ H performance of the following configuration:

Platform: **HP Integrity Superdome Enterprise Server**
Database Manager: Oracle Database 10g R2 Enterprise Edition w/ Partitioning
Operating System: HP-UX 11i v3 64-bit

The results were:

CPU (Speed)	Memory	Disks	QphH@30000GB
HP Integrity Superdome Enterprise Server			
64 x Itanium2 9040 (1.6GHz, dual-core)	9 MB Cache/core 1024 GB Main	3072 x 146GB ext. 4 x 36GB int.	150,960.5

In my opinion, this performance result was produced in compliance with the TPC's requirements for the benchmark. The following verification items were given special attention:

- The database records were defined with the proper layout and size
- The database population was generated using DBGEN
- The database was properly scaled to 30,000GB and populated accordingly
- The compliance of the database auxiliary data structures was verified

- The database load time was correctly measured and reported
- The required ACID properties were verified and met
- The query input variables were generated by QGEN
- The query text was produced using minor modifications and one query variant
- The execution of the queries against the SF1 database produced compliant answers
- A compliant implementation specific layer was used to drive the tests
- The throughput tests involved 10 query streams
- The ratio between the longest and the shortest query was such that no query timing was adjusted
- The execution times for queries and refresh functions were correctly measured and reported
- The repeatability of the measured results was verified
- The required amount of database log was configured
- The system pricing was verified for major components and maintenance
- The major pages from the FDR were verified for accuracy

Additional Audit Notes:

The measured configuration used four (4) internal 18GB disks for the operating system and ancillary file system. In the priced configuration these are replaced by four (4) internal 36GB disk drives. Based on their usage, the substitution of these drives has no impact on the reported performance.

Following the recent TAB resolution regarding DBGEN bug 548, additional queries were run to verify that the DBGEN population data has the required properties.

Respectfully Yours,



François Raab
President

Overview	ii
TPC Benchmark H Overview	ii
General Implementation Guidelines.....	iii
1 General Items.....	1
1.1 Benchmark Sponsor	1
1.2 Parameter Settings.....	1
1.3 Configuration Diagrams	1
2 Clause 1 Logical Database Design Related Items.....	5
2.1 Database Definition Statements	5
2.2 Physical Organization.....	5
2.3 Horizontal Partitioning	5
2.4 Replication.....	5
3 Clause 2 Queries and Refresh Functions.....	6
3.1 Query Language.....	6
3.2 Verifying Method for Random Number Generation	6
3.3 Generating Values for Substitution Parameters.....	6
3.4 Query Text and Output Data from Qualification Database.....	6
3.5 Query Substitution Parameters and Seeds Used.....	6
3.6 Query Isolation Level	6
3.7 Source Code of Refresh Functions.....	6
4 Clause 3 Database System Properties.....	7
4.1 ACID Properties.....	7
4.2 Atomicity.....	7
4.3 Consistency.....	7
4.4 Isolation.....	8
4.5 Durability.....	9
5 Clause 4 Scaling and Database Population.....	10
5.1 Ending Cardinality of Tables	10
5.2 Distribution of Tables and Logs Across Media.....	10
5.3 Database Partition/Replication Mapping	10
5.4 RAID Feature.....	11
5.5 DBGEN Modification	11
5.6 Database Load Time.....	11
5.7 Data Storage Ratio	11
5.8 Database Load Mechanism Details and Illustration	11
5.9 Qualification Database Configuration	11
6 Clause 5 Performance Metrics and Execution-Rules.....	12
6.1 System Activity Between Load and Performance Tests	12
6.2 Steps in the Power Test	12
6.3 Timing Intervals for Each Query and Refresh Functions.....	12
6.4 Number of Streams for the Throughput Test	12
6.5 Start and End Date/Time of Each Query Stream.....	12
6.6 Total Elapsed Time of the Measurement Interval	12
6.7 Refresh Function Start Date/Time and Finish Date/Time.....	12

6.8	Timing Intervals for Each Query and Each Refresh Function for Each Stream.....	14
6.9	Performance Metrics	14
6.10	The Performance Metric and Numerical Quantities from Both Runs.....	14
6.11	System Activity Between Performance Tests	14
7	Clause 6 SUT and Driver Implementation Related Items.....	15
7.1	Driver	15
7.2	Implementation-Specific Layer (ISL).....	15
7.3	Profile-Directed Optimization.....	15
8	Clause 7 Pricing	16
8.1	Hardware and Software Used in the Priced System	16
8.2	Total Three Year Price	16
8.3	Availability Date	16
9	Clause 8 Auditor's Information and Attestation Letter	17
9.1	Auditor's Report.....	17
Appendix A	Parameter Settings.....	18
A.1	30 TB-init.ora.....	18
A.2	system.....	18
A.3	env.....	19
A.4	profile	20
A.5	initasm.ora	20
Appendix B	Build Programs and Scripts	21
B.1	dbcre.sh	21
B.2	sctso.sh	21
B.3	dapop.sh.....	23
B.4	ixcre.sh	34
B.5	anl.sh	35
B.6	loadasm.....	35
C. 1	Acid Scripts	38
C.1	a_query.sql.....	38
C.2	a_query2.sql.....	38
C.3	atom.sh	38
C.4	atrans.sql.....	39
C.5	atranspl.c.....	40
C.6	atranspl.h	45
C.7	ckpt.sh	46
C.8	cnt_hist.sql.....	47
C.9	consist.sh	47
C.10	consist.sql	48
C.11	count_tx.sh.....	49
C.12	d_hist.sql.....	49
C.13	end_acid.sh	49
C.14	iso.sh	50
C.15	iso1.sh.....	50
C.16	iso2.sh.....	51
C.17	iso3.sh.....	52
C.18	iso4.sh.....	53
C.19	iso5.sh.....	53
C.20	iso6.sh.....	54
C.21	q1.sql.....	55
C.22	q21.sql.....	56

C.23	randkey.c	56
C.24	randpsup.c.....	58
C.25	run_acid.sh.....	59
C.26	sample.sh.....	60
C.27	sample.sql	60
Appendix D	Query text and Output	61
D.1	qryqual.....	61
Appendix E	Seed and Input Parameters	71
E.1	Seed.....	71
E.2	qp1.0.....	71
E.3	qp1.1.....	71
E.4	qp1.2.....	71
E.5	qp1.3.....	71
E.6	qp1.4.....	71
E.7	qp1.5.....	72
qpl.6	72
E.8	qp1.7.....	72
E.9	qp1.8.....	72
E.10	qp1.9.....	73
E.11	qp1.10.....	73
E.12	qp2.0.....	73
E.13	qp2.1.....	73
E.14	qp2.2.....	73
E.15	qp2.3.....	74
E.16	qp2.4.....	74
E.17	qp2.5.....	74
E.18	qp2.6.....	74
E.19	qp2.7.....	75
E.20	qp2.8.....	75
E.21	qp2.9.....	75
E.22	qp2.10.....	75
Appendix F	Benchmark Scripts.....	76
F.1	dbtables.sql	76
F.2	firstten.sql	77
F.3	gen_seed.sh.....	77
F.4	gtime.c.....	77
F.5	qexecpl.c.....	77
F.6	qexecpl.h.....	84
F.7	runTPCHAll.....	86
F.8	runTPCHpt.....	87
F.9	runTPCHus.....	89
F.10	runuf1.sh.....	89
F.11	runuf2.sh.....	91
F.12	scnt.sh.....	91
F.13	set_queue.....	92
F.14	tshut.....	92
F.15	tshut.asm.....	92
F.16	tstart.....	92
F.17	tstart.asm.....	92
F.18	ri_check.sql.....	92
Appendix G	Price Quotes.....	94

1 General Items

1.1 Benchmark Sponsor

A statement identifying the benchmark sponsor(s) and other participating companies must be provided.

Hewlett-Packard Company is the test sponsor of this TPC Benchmark H benchmark.

1.2 Parameter Settings

Settings must be provided for all customer-tunable parameters and options which have been changed from the defaults found in actual products, including but not limited to:

Database Tuning Options

Optimizer/Query execution options

Query processing tool/language configuration parameters

Recovery/commit options

Consistency/locking options

Operating system and configuration parameters

Configuration parameters and options for any other software component incorporated into the pricing structure;

Compiler optimization options.

Appendix A contains the HP-UX and Oracle 10g Release 2 parameters used in this benchmark.

1.3 Configuration Diagrams

Diagrams of both measured and priced configurations must be provided, accompanied by a description of the differences.

Measured Configuration:

- 64 1.6GHz Intel Itanium2 9040 CPUs each with 9MB iL3 cache per core.
- 1,024 GB Memory
- 128 PCI Fibre Channel 4GB Adapter (dual-port) Cards
- 2 I/O Expansion Cabinet
- 1 HP 1000 BaseSX PCI Lan Adapters
- 256 HP StorageWorks MSA1000 (with a total of 3072 146GB Disks)
- 1 High Availability Storage Systems (with a total of 4 18GB 10K Disks)
- 1 DVD ROM
- 1 SCSI Card

Priced Configuration:

- 64 1.6GHz Intel Itanium2 9040 CPUs each with 9MB iL3 cache per core.
- 1,024 GB Memory
- 128 PCI Fibre Channel 4GB Adapter (dual-port)
- 2 I/O Expansion Cabinet
- 1 HP 1000 BaseSX PCI Lan Adapters
- 256 HP StorageWorks MSA1000 (with a total of 3072 146GB Disks)

- 1 HP Surestore Disk System 2120 (with a total of 4 36GB 15K 80U4 HDD Disks)
- 1 DVD ROM
- 1 SCSI Cards
- The difference between measured and priced is a High Availability Storage System for the root disk which currently is obsolete. For the priced system a Surestore Disk System 2120 was substituted.



Terminal



Keyboard



Mouse

HP Integrity Superdome Enterprise Server



WITH:

- 64p/128c – 1.6GHz Itanium2 Processors
- 1,024GB Memory
- 128 4GB Fibre Channel Adapters (dual-port)
- 2 I/O Expansion Cabinet
- 1 HP 1000 BaseSX PCI Lan Adapter
- 1 DVD ROM
- 1 SCSI Card
- 1 HP Surestore Disk System 2120 with 4 36GB Disks

Priced Configuration

256 HP StorageWorks MSA1000
with 3072 146GB 15k RPM Disks

(26 Cabinets with 10 msa1000 in each)







Terminal Keyboard Mouse

HP Integrity Superdome Enterprise Server



WITH:

- 64p/128c – 1.6GHz Itanium2 Processors
- 1,024GB Memory
- 128 4GB Fibre Channel Adapters (dual-port)
- 2 I/O Expansion Cabinet
- 1 HP 1000 BaseSX PCI Lan Adapter
- 1 DVD ROM
- 1 SCSI Card
- 1 High Availability Storage System with 4 18GB Disks

Measured Configuration

256 HP StorageWorks MSA1000
with 3072 146GB 15k RPM Disks

(26 Cabinets with 10 msa1000 in each)



2 Clause 1 Logical Database Design Related Items

2.1 Database Definition Statements

Listings must be provided for all table definition statements and all other statements used to set up the test and qualification databases.

Appendix B describes the scripts that define, create, and analyze the tables and indices for the TPC-H database.

2.2 Physical Organization

The physical organization of tables and indices, within the test and qualification databases, must be disclosed. If the column ordering of any table is different from that specified in Clause 1.4, it must be noted.

No record clustering or index clustering was used. Columns were reordered in the tables – please refer to the table create statements for the ordering.

2.3 Horizontal Partitioning

Horizontal partitioning of tables and rows in the test and qualification databases (see Clause 1.5.4) must be disclosed.

Horizontal partitioning was used for all base and index tables except NATION and REGION. The details of this partitioning can be understood by examining the syntax of the table and index definition statements in Appendix B. Similar partitioning was used in the qualification database size.

Section 5.2 describes the distribution of tables and logs across all media.

2.4 Replication

Any replication of physical objects must be disclosed and must conform to the requirements of Clause 1.5.6.

No replication was used.

3 Clause 2 Queries and Refresh Functions

3.1 Query Language

The query language used to implement the queries must be identified.

SQL was the query language used to implement all queries.

3.2 Verifying Method for Random Number Generation

The method of verification for the random number generation must be described unless the supplied DBGEN and QGEN were used.

TPC supplied versions 2.6.0 of DBGEN and QGEN were used for this TPC-H benchmark.

3.3 Generating Values for Substitution Parameters

The method used to generate values for substitution parameters must be disclosed. If QGEN is not used for this purpose, then the source code of any non-commercial tool used must be disclosed. If QGEN is used, the version number, release number, modification number, and patch level of QGEN must be disclosed.

QGEN version 2.6.0 was used to generate the substitution parameters.

3.4 Query Text and Output Data from Qualification Database

The executable query text used for query validation must be disclosed along with the corresponding output data generated during the execution of the query text against the qualification database. If minor modifications (see Clause 2.2.3) have been applied to any functional query definition or approved variants in order to obtain executable query text, these modifications must be disclosed and justified. The justification for a particular minor query modification can apply collectively to all queries for which it has been used. The output data for the power and throughput tests must be made available electronically upon request.

- Appendix C contains the actual query text and query output.

3.5 Query Substitution Parameters and Seeds Used

The query substitution parameters used for all performance tests must be disclosed in tabular format, along with the seeds used to generate these parameters.

Appendix E contains the seed and query substitution parameters.

3.6 Query Isolation Level

The isolation level used to run the queries must be disclosed. If the isolation level does not map closely to the levels defined in Clause 3.4, additional descriptive detail must be provided.

The queries and transactions were run with the isolation level set to "Level 3" (repeatable read).

3.7 Source Code of Refresh Functions

The details of how the refresh functions were implemented must be disclosed (including source code of any non-commercial program used).

The refresh function is part of the implementation-specific layer/driver code included in Appendix F.

4 Clause 3 Database System Properties

4.1 ACID Properties

The ACID (Atomicity, Consistency, Isolation, and Durability) properties of transaction processing systems must be supported by the system under test during the timed portion of this benchmark. Since TPC-H is not a transaction processing benchmark, the ACID properties must be evaluated outside the timed portion of the test.

Source code for ACID test is included in Appendix C.

4.2 Atomicity

The system under test must guarantee that transactions are atomic; the system will either perform all individual operations on the data, or will assure that no partially completed operations leave any effects on the data.

Completed Transaction

Perform the ACID Transaction for a randomly selected set of input data and verify that the appropriate rows have been changed in the ORDERS, LINEITEM, and HISTORY tables.

1. The total price from the ORDERS table and the extended price from the LINEITEM table were retrieved for a randomly selected order key.
2. The ACID Transaction was performed using the order key from step 1.
3. The ACID Transaction committed.
4. The total price from the ORDERS table and the extended price from the LINEITEM table were retrieved for the same order key. It was verified that the appropriate rows had been changed.

Aborted Transaction

Perform the ACID Transaction for a randomly selected set of input data, substituting a ROLLBACK of the transaction for the COMMIT of the transaction. Verify that the appropriate rows have not been changed in the ORDERS, LINEITEM, and HISTORY tables.

5. The total price from the ORDERS table and the extended price from the LINEITEM table were retrieved for a randomly selected order key.
6. The ACID Transaction was performed using the order key from step 1. The transaction was stopped prior to the commit.
7. The ACID Transaction was ROLLED BACK.
8. The total price from the ORDERS table and the extended price from the LINEITEM table were retrieved for the same order key. It was verified that the appropriate rows had not been changed.

4.3 Consistency

Consistency is the property of the application that requires any execution of transactions to take the database from one consistent state to another.

Consistency Test

Verify that ORDERS and LINEITEM tables are initially consistent, submit the prescribed number of ACID Transactions with randomly selected input parameters, and re-verify the consistency of the ORDERS and LINEITEM.

9. The consistency of the ORDERS and LINEITEM tables was verified based on a sample of order keys.
10. 100 ACID Transactions were submitted from each of 11 execution streams.
11. The consistency of the ORDERS and LINEITEM tables was re-verified.

4.4 Isolation

Operations of concurrent transactions must yield results, which are indistinguishable from the results, which would be obtained by forcing each transaction to be serially executed to completion in some order.

Read-Write Conflict with Commit

Demonstrate isolation for the read-write conflict of a read-write transaction and a read-only transaction when the read-write transaction is committed.

12. An ACID Transaction was started for a randomly selected O_KEY, L_KEY, and DELTA. The ACID Transaction was suspended prior to COMMIT.
13. An ACID Query was started for the same O_KEY used in step 1. The ACID Query blocked and did not see any uncommitted changes made by the ACID Transaction.
14. The ACID Transaction was resumed, and COMMITTED.
15. The ACID Query completed. It returned the data as committed by the ACID Transaction.

Read-Write Conflict with Rollback

Demonstrate isolation for the read-write conflict of a read-write transaction and a read-only transaction when the read-write transaction is rolled back.

16. An ACID Transaction was started for a randomly selected O_KEY, L_KEY, and DELTA. The ACID Transaction was suspended prior to ROLLBACK.
17. An ACID Query was started for the same O_KEY used in step 1. The ACID Query did not see the uncommitted changes made by the ACID Transaction.
18. The ACID Transaction was ROLLED BACK.
19. The ACID Query completed.

Write-Write Conflict with Commit

Demonstrate isolation for the write-write conflict of two update transactions when the first transaction is committed.

20. An ACID Transaction, T1, was started for a randomly selected O_KEY, L_KEY, and DELTA. The ACID transaction T1 was suspended prior to COMMIT.
21. Another ACID Transaction, T2, was started using the same O_KEY and L_KEY and a randomly selected DELTA.
22. T2 waited.
23. T1 was allowed to COMMIT and T2 completed.
24. It was verified that $T2.L_EXTENDEDPRICE = T1.L_EXTENDEDPRICE + (DELTA1 * (T1.L_EXTENDEDPRICE / T1.L_QUANTITY))$

Write-Write Conflict with Rollback

Demonstrate isolation for the write-write conflict of two update transactions when the first transaction is rolled back.

25. An ACID Transaction, T1, was started for a randomly selected O_KEY, L_KEY, and DELTA. The ACID transaction T1 was suspended prior to ROLLBACK.
26. Another ACID Transaction, T2, was started using the same O_KEY and L_KEY and a randomly selected DELTA.
27. T2 waited.
28. T1 was allowed to ROLLBACK and T2 completed.
29. It was verified that $T2.L_EXTENDEDPRICE = T1.L_EXTENDEDPRICE$.

Concurrent Progress of Read and Write on Different Tables

Demonstrate the ability of read and write transactions affecting different database tables to make progress concurrently.

30. An ACID Transaction, T1, was started for a randomly selected O_KEY, L_KEY, and DELTA. T1 was suspended prior to COMMIT.

31. Another ACID transaction, T2 was started using random values for PS_PARTKEY and PS_SUPPKEY, all columns of the PARTSUPP table for which PS_PARTKEY and PS_SUPPKEY are equal are returned.
32. ACID Transaction T2 completed.
33. T1 was allowed to COMMIT.
34. It was verified that the appropriate rows in the ORDER, LINEITEM, and HISTORY tables have been changed.

Read-Only Query Conflict with Update Transactions

Demonstrates that the continuous submission of arbitrary (read-only) queries against one or more tables of the database does not indefinitely delay update transactions affecting those tables from making progress.

35. A Transaction, T1, was started which executed Q21 against the qualification database, was started using a randomly selected DELTA.
36. An ACID Transaction, T2, was started for a randomly selected O_KEY, L_KEY and DELTA.
37. T2 completed and appropriate rows in the ORDERS, LINEITEM and HISTORY tables had been changed.
38. Transaction T1 completed executing Q21.

4.5 Durability

The tested system must guarantee durability: the ability to preserve the effects of committed transactions and insure database consistency after recovery from any one of the failures listed in Clause 3.5.3.

Failure of a Durable Medium

Guarantee the database and committed updates are preserved across a permanent irrecoverable failure of any single durable medium containing TPC-H database tables or recovery log tables.

39. The disks containing TPC-H tables and log files were on RAID 1/0 protected disk groups. During the durability test, one disk was removed from each RAID group containing the data and the log. The test continued uninterrupted, because of the RAID protection.

System Crash

Guarantee the database and committed updates are preserved across an instantaneous interruption (system crash/system hang) in processing which requires the system to reboot to recover.

The system crash and memory failure tests were combined. Power to the server was turned off during the durability test. When power was restored, the system rebooted and the database was restarted. The durability success file and the HISTORY table were compared and the counts were verified.

Memory Failure

Guarantee the database and committed updates are preserved across failure of all or part of memory (loss of contents).

See the previous section.

5 Clause 4 Scaling and Database Population

5.1 Ending Cardinality of Tables

The cardinality (e.g., the number of rows) of each table of the test database, as it existed at the completion of the database load (see clause 4.2.5) must be disclosed.

Table	Cardinality
ORDER	45,000,000,000
LINEITEM	179,999,978,268
CUSTOMER	4,500,000,000
PART	6,000,000,000
SUPPLIER	300,000,000
PARTSUPP	24,000,000,000
NATION	25
REGION	5

5.2 Distribution of Tables and Logs Across Media

Distribution of tables and logs across media:

Each MSA array (with 12 disks) was configured as a single Raid-1/0 array group. Each array group was divided into 4 luns.

LUN1 for Oracle/ASM use (eg. tables, indexes, logs)

LUN2 for flat-file data

LUN3 for swap

LUN4 for ACID/quall database tests and miscellaneous usage.

OS root and the Oracle home directory were configured on two external disks.

256 LUNs, one from each MSA1000 array, were allocated for Oracle ASM use and a single disk group was built across all LUNs. All tables, indexes, temp space and other Oracle files were configured in this disk group.

5.3 Database Partition/Replication Mapping

The mapping of database partitions/replications must be explicitly described.

Horizontal partitioning was used for all base and index tables except NATION and REGION. The details of this partitioning can be understood by examining the syntax of the table and index definition statements in Appendix B. Similar partitioning was used in the qualification database size.

Section 5.2 describes the distribution of tables and logs across all media..

5.4 RAID Feature

Implementation may use some form of RAID to ensure high availability. If used for data, auxiliary storage (e.g. indexes) or temporary space, the level of RAID must be disclosed for each device.

RAID1/0 was used for all data.

5.5 DBGEN Modification

Any modifications to the DBGEN (see clause 4.2.1) source code must be disclosed. In the event that a program other than DBGEN was used to populate the database, it must be disclosed in its entirety.

The supplied DBGEN version 2.6.0 was not modified to generate the database population for this benchmark.

5.6 Database Load Time

The database load time for the test database (see clause 4.3) must be disclosed.

The database load time was 16:06:11.

5.7 Data Storage Ratio

The data storage ratio must be disclosed. It is computed as the ratio between the total amount of priced disk space, and the chosen test database size as defined in Clause 4.1.3.

The data storage ratio is computed from the following information:

Type	Quantity	Disk Size	Total
1 HP Surestore Disk System 2120	4	36	144
256 HP StorageWorks MSA1000	3072	146	448,512.0
TOTAL			448,656.0
Scale Factor			30,000
Storage Ratio			14.96

5.8 Database Load Mechanism Details and Illustration


The details of the database load must be described, including a block diagram illustrating the overall process.

The database was loaded using data generation stored on the flat files all on the tested and priced configuration

5.9 Qualification Database Configuration

Any differences between the configuration of the qualification database and the test database must be disclosed.

The qualification database used identical scripts to create and load the data with changes to adjust for the database scale factor.



6 Clause 5 Performance Metrics and Execution-Rules

6.1 System Activity Between Load and Performance Tests

Any system activity on the SUT that takes place between the conclusion of the load test and the beginning of the performance test must be fully disclosed.

Auditor requested queries were run against the database to verify the correctness of the database load.

All scripts and queries used are included in Appendix E.

6.2 Steps in the Power Test

The details of the steps followed to implement the power test (e.g., system boot, database restart, etc.) must be disclosed.

The following steps were used to implement the power test:

1. RF1 Refresh Transaction
2. Stream 00 Execution
3. RF2 Refresh Transaction

6.3 Timing Intervals for Each Query and Refresh Functions

The timing intervals for each query for both refresh functions must be reported for the power test.

The timing intervals for each query and both update functions are given in the Numerical Quantities Summary earlier in this document.

6.4 Number of Streams for the Throughput Test

The number of execution streams used for the throughput test must be disclosed.

10 streams were used for the throughput test.

6.5 Start and End Date/Time of Each Query Stream

The start time and finish time for each query stream must be reported for the throughput test.

The throughput test start time and finish time for each stream are given in the Numerical Quantities Summary earlier in this document.

6.6 Total Elapsed Time of the Measurement Interval

The total elapsed time of the measurement interval must be reported for the throughput test.

The total elapsed time of the throughput test is given in the Numerical Quantities Summary earlier in this document.

6.7 Refresh Function Start Date/Time and Finish Date/Time

Start and finish time for each update function in the update stream must be reported for the throughput test.

Power Stream	Seed	RF1 Start Time RF1 End Time	RF2 Start Time RF2 End Time
	525095659	05/28/07 03:48:02 05/28/07 03:53:27	05/28/07 09:47:52 05/28/07 09:56:42

Throughput Stream	RF1 Start Time RF1 End Time	RF2 Start Time RF2 End Time
1	05/30/07 18:18:03 05/30/07 18:20:52	05/30/07 18:20:52 05/30/07 18:29:18
2	05/30/07 18:29:18 05/30/07 18:32:37	05/30/07 18:32:37 05/30/07 18:41:05
3	05/30/07 18:41:05 05/30/07 18:44:24	05/30/07 18:44:24 05/30/07 18:52:56
4	05/30/07 18:52:56 05/30/07 18:56:13	05/30/07 18:56:13 05/30/07 19:04:45
5	05/30/07 19:04:45 05/30/07 19:08:03	05/30/07 19:08:03 05/30/07 19:16:34
6	05/30/07 19:16:34 05/30/07 19:19:50	05/30/07 19:19:50 05/30/07 19:28:10
7	05/30/07 19:28:10 05/30/07 19:31:26	05/30/07 19:31:26 05/30/07 19:39:52
8	05/30/07 19:39:52 05/30/07 19:43:11	05/30/07 19:43:11 05/30/07 19:51:37
9	05/30/07 19:51:37 05/30/07 19:54:55	05/30/07 19:54:55 05/30/07 20:03:18
10	05/30/07 20:03:18 05/30/07 20:06:34	05/30/07 20:06:34 05/30/07 20:14:56

6.8 Timing Intervals for Each Query and Each Refresh Function for Each Stream

The timing intervals for each query of each stream and for each refresh function must be reported for the throughput test.

The timing intervals for each query and each update function are given in the Numerical Quantities Summary earlier in this document.

6.9 Performance Metrics

The computed performance metric, related numerical quantities and price performance metric must be reported.

The performance metrics, and the numbers, on which they are based, is given in the Numerical Quantities Summary earlier in this document.

6.10 The Performance Metric and Numerical Quantities from Both Runs

The performance metric and numerical quantities from both runs must be disclosed.

Performance results from the first two executions of the TPC-H benchmark indicated the following percent difference for the metric points:

	QppH@30000GB	QthH@30000GB	QphH@30000GB
Reported Run	201,316.1	113,200.5	150,960.5
Reproducibility Run	208,505.1	113,134.8	153,587.7
% Difference	3.6%	0.1%	1.7%

6.11 System Activity Between Performance Tests

Any activity on the SUT that takes place between the conclusion of the Reported Run and the beginning of Reproducibility Run must be disclosed.

The database was restarted between the two runs.

7 Clause 6 SUT and Driver Implementation Related Items

7.1 Driver

A detailed description of how the driver performs its functions must be supplied, including any related source code or scripts. This description should allow an independent reconstruction of the driver.

All stream executions are performed by a single script. QGEN is used to produce query text.

For each power-test run:

- The SQL for RF1 is submitted to the database
- Then the queries as generated by QGEN are submitted in the order defined by Clause 5.3.5.4
- The SQL for RF2 is submitted to the database.

7.2 Implementation-Specific Layer (ISL)

If an implementation specific layer is used, then a detailed description of how it performs its functions must be provided. All related source code, scripts and configuration files must be disclosed. The information provided should be sufficient for an independent reconstruction of the implementation specific layer.

The source code for the "qexec" utility can be found in Appendix E.

7.3 Profile-Directed Optimization

If profile-directed optimization as described in Clause 5.2. is used, such use must be disclosed..

Profile-directed optimization subject to the requirements of 5.2.9 and 5.2.10 was not used.

8 Clause 7 Pricing

8.1 Hardware and Software Used in the Priced System

A detailed list of hardware and software used in the priced system must be reported. Each item must have vendor part number, description, and release/revision level, and either general availability status or committed delivery date. If package pricing is used, contents of the package must be disclosed. Pricing source(s) and effective date(s) of price(s) must also be reported.

A detailed list of hardware and software used in the priced system is included in the pricing sheet in the executive summary. All prices are currently effective.

8.2 Total Three Year Price

The total 3-year price of the entire configuration must be reported including: hardware, software, and maintenance charges. Separate component pricing is recommended. The basis of all discounts used must be disclosed.

A detailed pricing sheet of all the hardware and software used in this configuration and the 3-year maintenance costs, demonstrating the computation of the total 3-year price of the configuration, is included in the executive summary at the beginning of this document.

8.3 Availability Date

The committed delivery date for general availability of products used in the priced calculations must be reported. When the priced system includes products with different availability dates, the reported availability date for the priced system must be the date at which all components are committed to be available.

Availability Dates:

Server Hardware	Now
Server Software	Now
Storage	Now
Database Manager (Oracle Database 10g Release 2 Enterprise Edition with Partitioning and Oracle Automatic Storage Management)	Now

9 Clause 8 Auditor's Information and Attestation Letter

9.1 Auditor's Report

The auditor's agency name, address, phone number, and Attestation letter with a brief audit summary report indicating compliance must be included in the full disclosure report. A statement should be included specifying who to contact in order to obtain further information regarding the audit process.

This implementation of the TPC Benchmark H was audited by Francois Raab for InfoSizing. Further information regarding the audit process may be obtained from:

Francois Raab
InfoSizing
1373 N. Franklin Street
Colorado Springs, CO 80903
(719) 473-7555
(719) 473-7554

The auditor's attestation letter is included at the front of this report.

Appendix A Parameter Settings

A.1 30 TB-init.ora

```

statistics_level      = basic
instance_type        = rdbms
aq_tm_processes     = 0
audit_trail         = FALSE
compatible          = 10.1.0.2
control_files        = (+DG1/control1,+DG1/control2)
cpu_count            = 64
db_block_checksum   = false
db_block_size        = 32768
db_cache_size        = 50g
db_file_multiblock_read_count = 64
db_files             = 2400
db_name              = 30tb
db_writer_processes = 16
dml_locks            = 40000
global_names          = FALSE
hpux_sched_noage    = 180
instance_name        = tpch
job_queue_processes = 0
log_buffer           = 268435456
log_checkpoints_to_alert = true
log_checkpoint_interval = 18000
max_dump_file_size  = unlimited
nls_date_format     = YYYY-MM-DD
open_cursors         = 1024
optimizer_features_enable = 10.2.0.1.1
optimizer_index_cost_adj = 200
optimizer_mode        = CHOOSE
parallel_adaptive_multi_user = true
parallel_execution_message_size = 65535
parallel_max_servers  = 1680
parallel_min_servers = 864
parallel_threads_per_cpu = 3
pga_aggregate_target = 500g
processes            = 5000
recovery_parallelism = 32
replication_dependency_tracking = false
session_cached_cursors = 0
shared_pool_size     = 50g
undo_management     = auto
undo_retention       = 200000

```

A.2 system

```

*
* Created on Sun Jun 10 20:46:07 2007
*
version 1
configuration current "" [466cc57f]
*
* Module entries
*
module mpt      best  1.0.[45A7EE38]
module dmpfhpalua best  0.1.[458A95BE]
module dmpfhdsalua best  0.1.[458A95BE]
module dmpjbod   best  0.1.[458A95BE]
module dmpapf    best  0.1.[458A95BD]
module dmpapg    best  0.1.[458A95BD]
module dmpap    best  0.1.[458A95BD]

```

module dmpaaa	best	0.1.[458A95BD]
module dmpaa	best	0.1.[458A95BC]
module vols	best	1.0.[458A8F52]
module vol	best	1.0.[458A8F5C]
module vxdump	best	1.0.[458A8F54]
module sasd	best	1.0.[45A7EED6]
module ciss	best	1.0.[45A7EE2A]
module prm	best	1.0.[45D4D130]
module oncksupp	best	1.0.[45A7E361]
module lvm	best	1.0.[45A7EDE7]
module vxportal	static	41.0.[45A7EE8C]
module vxfs	static	41.0.[45A7EE8C]
module igelan	best	1.0.[45A7EDB2]
module iether	best	1.0.[45A7EDC6]
module gelan	best	1.0.[45A7ED9E]
module fcd	best	1.0.[45A7EE1B]
module td	best	1.0.[45A7EE48]
module fcpdev	best	1.0.[45D4D120]
module fcpararray	best	1.0.[45D4D120]
module fcp	best	1.0.[45D4D120]
module cifs	auto	1.0.[4654BCAB]
module fsm	auto	1.0.[454BAC38]
module fsmdr	auto	1.0.[454BAC47]
module cachefs	best	1.0.[45A7E3E6]
module autofs	best	1.0.[45A7E3E6]
module rpcmod	best	1.0.[45A7E3E8]
module krb5	best	1.0.[45A7E3E7]
module kgssapi	best	1.0.[45A7E3E6]
module klmmod	best	1.0.[45A7E3E7]
module rpcsec_gss	best	1.0.[45A7E3E9]
module rpcsec	best	1.0.[45A7E3E8]
module rpc	best	1.0.[45A7E3E8]
module nfs_client	best	1.0.[45A7E3E7]
module nfs_client_pv2	best	1.0.[45A7E3E8]
module nfs_client_pv3	best	1.0.[45A7E3E8]
module nfs_client_pv4	best	1.0.[45A7E3E8]
module nfssrv	best	1.0.[45A7E3E8]
module nfswrp	best	1.0.[45A7E3E8]
module pkct	best	1.0.[45A7E362]
module ptm	best	1.0.[45A7E367]
module pts	best	1.0.[45A7E367]
module ptem	best	1.0.[45A7E367]
module ldterm	best	1.0.[45A7E35E]
module rng	loaded	0.1.[45D4D131]
module cdfs	auto	0.1.[45D4D11C]
module dev_config	best	1.0.[45D4D11D]
module dmem	best	1.0.[45D4D11E]
module diag2	best	1.0.[45D4D11D]
module asyndsk	best	1.0.[45D4D11B]
module tgt	best	1.0.[45D4D135]
module stape	best	1.0.[45D4D134]
module sdisk	best	1.0.[45D4D132]
module sctl	best	1.0.[45D4D132]
module schgr	best	1.0.[45D4D132]
module esvroot	best	1.0.[45D4D120]
module estp	best	1.0.[45D4D120]
module estape	best	1.0.[45D4D120]
module eslpt	best	1.0.[45D4D120]
module esdisk	best	1.0.[45D4D11F]
module esctl	best	1.0.[45D4D11F]
module eschgr	best	1.0.[45D4D11F]
module side_multi	best	1.0.[45D4D133]
module side	best	1.0.[45D4D133]
module c8xx	best	1.0.[45D4D11C]
module procsm	best	1.0.[45D4D130]
module rmp3f01	best	1.0.[45D4D131]
module pdh	best	1.0.[45D4D12C]
module ia64_psm	best	1.0.[45D4D123]
module wxb_hp	best	1.0.[45D4D13C]
module sac	best	1.0.[45D4D131]
module acpi_node	best	1.0.[45D4D11A]

```

module ipmi      best   1.0.[45D4D125]
module ptys      best   1.0.[45D4D130]
module ptym      best   1.0.[45D4D130]
module ff's best 1.0.[45D4D120]
module pipemod   best   1.0.[45D4D12C]
module pipedev   best   1.0.[45D4D12C]
module tirdwr    best   1.0.[45D4D135]
module timod     best   1.0.[45D4D135]
module sc best   1.0.[45D4D131]
module echo      best   1.0.[45D4D11F]
module sad       best   1.0.[45D4D131]
module strlog    best   1.0.[45D4D134]
module clone     best   1.0.[45D4D11D]
module hpstreams best   1.0.[45D4D123]
module nms       best   1.0.[45D4D12A]
module int100    best   1.0.[45D4D124]
module btlan     best   1.0.[45D4D11C]
module token_arp best   1.0.[45D4D136]
module dlpi      best   1.0.[45D4D11E]
module netdiag1 best   1.0.[45D4D12A]
module tels      best   1.0.[45D4D135]
module telm     best   1.0.[45D4D135]
module tun       best   1.0.[45D4D136]
module uipc     best   1.0.[45D4D137]
module inet      best   1.0.[45D4D124]
module sba       best   1.0.[45D4D131]
module root      best   1.0.[45D4D131]
module pci_slot  best   1.0.[45D4D12B]
module lbabest   1.0.[45D4D128]
module cell      best   1.0.[45D4D11D]
module asio0     best   1.0.[45D4D11B]
*
*Dump entries
*
dump lvol
*
*Tunables entries
*
tunable o_sync_is_o_dsync 1
tunable nkthread 11488
tunable filecache_max 3%
tunable process_id_min 0
tunable cmc_plat_poll 15
tunable create_fastlinks 1
tunable hfs_max_revra_blocks 20
tunable hfs_revra_per_disk 256
tunable maxdsiz_64bit 0x80000000
tunable maxfiles_lim 4096
tunable maxssiz_64bit 268435456
tunable maxtsiz_64bit 4294967296
tunable msgmnb 65536
tunable msgql 5120
tunable ninode 120000
tunable npty 200
tunable nswapdev 100
tunable semmns 8192
tunable semume 512
tunable shmmmax 0x400000000000
tunable shmmni 2048
tunable timezone 480
tunable max_thread_proc 2048
tunable vxfs_ifree_timelag 3600000
tunable vps_ceiling 64
tunable swchunk 65536
tunable shmseg 512
tunable semvmx 32768
tunable semmmu 4092
tunable semmni 4096
tunable nstrpty 200
tunable nproc 7168
tunable nfile 2000000

```

```

tunable msgmni 512
tunable maxuprc 3277
tunable maxtsiz 1073741824
tunable maxssiz 0x10000000
tunable maxfiles 4096
tunable maxdsiz 0x40000000
tunable max_async_ports 2048
tunable hfs_ra_per_disk 256
tunable hfs_max_ra_blocks 20
tunable STRMSGSZ 65535
tunable pagezero_daemon_enabled 0
tunable filecache_min 1%
tunable as_isolation_level 1

```

A.3 env

```

#####
# MACHINE PARAMETERS #####
#export RAC_NODES="titant titan2"
#####
# PATHS #####
export KIT_DIR=/dbms/oracle10i/kit
export SCHEMA_DIR=$KIT_DIR/schema
export PERL=/opt/perl/bin/perl
export UTILS=$KIT_DIR/utils
export TEST_DB=/tmp
export QUAL_DB=$TEST_DB
export DBGEN=$KIT_DIR/dbgen
export ACID_DIR=$KIT_DIR/acid
export QEXEC=$KIT_DIR/utils
export QUERIES=$KIT_DIR/queries
export ANSWERS=$KIT_DIR/answers
export ANS2VAL=/dbms/oracle10i/kit/acid/answers2validate
export ACID_OUT=$KIT_DIR/out
export DSS_CONFIG=$DBGEN
export DSS_QUERY=$KIT_DIR/queries
export DSS_PATH=$ADE_VIEW_ROOT
export MAINT=$KIT_DIR/maintenance
export CC=/opt/ansic/bin/cc
export FRAME=$KIT_DIR/frame
export FRAME_DIR=/dbms/oracle10i/frame
export SCALE_FACTOR=30000
export UPDATE_1_DOP=64
export UPDATE_2_DOP=128
#####
# FRAME STUFF #####
export FRAME_PATH=$KIT_DIR/frame

#export ORACORE3INCL=/vobs/oracore3/include
#export ORACORE3PUBL=/vobs/oracore3/public
export ORACORE3INCL=$ORACLE_HOME/rdbms/demo
export ORACORE3PUBL=$ORACLE_HOME/rdbms/public
#export RDBMSPUBL=/vobs/rdbms/public
export RDBMSPUBL=$ORACLE_HOME/rdbms/public
#export NETWORKPUBL=/vobs/network_src/public
export NETWORKPUBL=$ORACLE_HOME/network/public
export RDBMSDEMO=$ORACLE_HOME/rdbms/demo
export PLSQLDEMO=$ORACLE_HOME/plsql/demo
export PLSQLPUBL=$ORACLE_HOME/plsql/public
export O=$ORACLE_HOME
export
PATH=./:$BUMPX_DIR:$UTILS:$DBGEN:$MAINT:$ACI
D_DIR:$FRAME/bin:$FRAME/bin:$REGR_TEST:$PATH
#
#####
# ENVIRONMENT VARIABLES #####
export WORKLOAD=TPCH
export HOST=
#export OPTLEVEL=X02
export GETOPT=-DSTDLIB_HAS_GETOPT

```

```

export PLATFORM=
#export INITORA=$KIT_DIR/schema/test_db/testdb.ora
#export INITORA=$KIT_DIR/schema/test_db/sf100.ora

export REF_DATA_SET_DIR=/tmp/ref_30000

#####
##### ALIASES #####
#####

#####
##### RULES - do not change these #####
case "$SCALE_FACTOR" in
    1) export NUM_STREAMS=2;;
    10) export NUM_STREAMS=3;;
    100) export NUM_STREAMS=5;;
    300) export NUM_STREAMS=6;;
    1000) export NUM_STREAMS=7;;
    3000) export NUM_STREAMS=8;;
    10000) export NUM_STREAMS=9;;
    30000) export NUM_STREAMS=10;;
esac
DATABASE_USER=tpch/tpch

```

A.4 profile

```

stty erase '^H' kill '^X' intr '^C' eof '^D' susp '^Z'
export EDITOR=/usr/bin/vi
export ORACLE_HOME=/oracle

#export ORACLE_SID=ASM
#echo 'ORACLE_SID is ASM'

export ORACLE_SID=tpch
echo 'ORACLE_SID is tpch'

#export ORACLE_SID=qual
#echo 'ORACLE_SID is qual'

export KIT_DIR=dbms/oracle10i/kit

```

```

export
SHLIB_PATH=$ORACLE_HOME/lib:$ORACLE_HOME/lib32:$OR
ACLE_HOME/rdbms/lib:$ORACLE_HOME/network/lib
export
LD_LIBRARY_PATH=$ORACLE_HOME/lib:$ORACLE_HOME/lib6
4:$ORACLE_HOME/rdbms/lib:$ORACLE_HOME/network/lib64
export SAVEHIST=2049
export FRAME_PATH=dbms/oracle10i/frame
export O=$ORACLE_HOME
export ORACLE_PATH=dbms/oracle10i/frame/tools
export PS1="`whoami`(`hostname`)> "
export skgxp_trace_path=/tmp/srq_tpch1
export SYNC_BUF_CONF=256
#export SYNC_BUF_CONF=6000 #MAX_CONCURRENT in
async.h is 5000
echo "export SYNC_BUF_CONF=$SYNC_BUF_CONF"

```

```

export
PATH=./:$ORACLE_HOME/bin:/usr/local/bin:$ORACLE_HOME:$O
RACLE_HOME/lib:/opt/perf_tools/bin/:tools:/tpch/run_power:/tpch:/db
ms/oracle10i/frame/bin:/dbms/oracle10i/frame:/dbms/oracle10i/tools/bin
:/tools/Tusc:/dbms/tpcd_v8/bumpx/bumpx:/dbms/tpcd_v8/bumpx/dbgen
:/dbms/tpcd_v8/out/scripts:/opt/ansic/bin:/opt/langtools/bin:/usr/sbi
n:/bin:/usr/bin:/usr/local/bin:/usr/contrib/bin:/etc:/usr/include:/dbms/ora
cle10i/kit:/dbms/oracle10i/kit/bumpx:/dbms/oracle10i/local/TestIO:/usr/
ccs/bin:/opt/caliper/bin:/opt/rdma/bin:~/bin

alias ltt="ls -ltr |tail -30"
alias cd_frame="cd /dbms/oracle10i/frame"
alias cd_stats="cd /dbms/oracle10i/frame/stats"
alias cd_q="cd /dbms/oracle10i/frame/queries/queries_tpch"
alias cd_log="cd /oracle/rdbms/log"
alias cd_u="cd /dbms/oracle10i/frame/queries/queries_tpch/updates"
alias ltm="ls -lt |more"
alias cdlog="cd /oracle/rdbms/log"
alias cdtools="cd /dbms/oracle10i/tools/bin"
alias cdq="cd /tpch/tpch/run_power"
alias pso="ps -ef | grep ora | grep -v sleep"
alias pso_hc="ps -fu oracle | sort -n -k2"
alias setterm="TERM=dterm;export TERM"
alias taillog="tail -f /oracle/rdbms/log/alert_tpch.log"
#alias taillog="tail -f /oracle/rdbms/log/alert_$ORACLE_SID.log"
alias cdlog="cd $ORACLE_HOME/rdbms/log"
alias detail="tail -n 1 "
export LFRAME_PATH=/dbms/oracle10i/frame
export PATH=$LFRAME_PATH/bin:$PATH

umask 002
iosum(){}
if [ "$1" -eq "" ]; then
    echo usage: iosum iterations
else
    sar -d 5 $1 | ${FRAME_PATH}/bin/io.pl
fi
}
```

A.5 initasm.ora

```

instance_type=asm
shared_pool_size=4G
db_cache_size=2g
asm_diskgroups=DG1
ASM.instance_number=1
instance_number=1
processes=500
ASM_DISKSTRING='/dbms/links/roradsk*'
#lock_sga=TRUE
background_dump_dest=/opt/app/admin/ASM/log'
core_dump_dest='/opt/app/admin/ASM/log'
user_dump_dest='/opt/app/admin/ASM/log'

```

Appendix B Build Programs and Scripts

B.1 dbcres.sh

```
#!/bin/ksh

echo START CREATE DB at `date`
export ORACLE_SID=tpch

sqlplus /NOLOG <<!
connect / as sysdba
set timing on
set echo on

shutdown abort;

startup pfile=/oracle/dbs/30TB_init.ora nomount;
create database
controlfile reuse
logfile '+DG1' size 120000m reuse,
'+DG1' size 120000m reuse
datafile '+DG1' size 5000m reuse
sysaux datafile '+DG1' size 5000m reuse
undo tablespace ts_undo1
    datafile '+DG1' size 32000m reuse
maxdatafiles 3000
maxinstances 2
;

set termout off
set echo off
spool /tmp/cat
@?/rdbms/admin/catalog.sql;
@?/rdbms/admin/catparr.sql;
@?/rdbms/admin/catproc.sql;
connect system/manager
@?/sqlplus/admin/pupbld.sql;
@?/rdbms/admin/utlxplan.sql;
spool off
!
echo END CREATE DB at `date`
```

```
(( i = $i + 1 ))
done

sqlplus / as sysdba <<! &
set timing on
set echo on

--drop tablespace ts_default including contents;
create tablespace ts_default
datafile '+DG1' size 15000m reuse
extent management local autoallocate nologging;
!

sqlplus / as sysdba <<! &
set timing on
set echo on

--drop tablespace ts_temp including contents;
create temporary tablespace ts_temp
tempfile '+DG1' size 64000m reuse
extent management local
uniform size 20M
;
!

wait

(( i = 1 ))
while (( i <= 256 ))
do

sqlplus / as sysdba <<! &

set timing on
set echo on
alter tablespace ts_temp
    add tempfile '+DG1' size 64000m reuse;
!
(( i = $i + 1 ))
done

wait

(( i = 1 ))
while (( i <= 255 ))
do

sqlplus / as sysdba <<! &

set timing on
set echo on
alter tablespace ts_temp
    add tempfile '+DG1' size 64000m reuse;
!
(( i = $i + 1 ))
done

wait
```

B.2 sctso.sh

```
#!/bin/ksh

echo CREATE TABLESPACES at `date`
export ORACLE_SID=tpch

(( i = 1 ))
while (( i <= 30 ))
do
sqlplus / as sysdba <<! &
set timing on
set echo on

alter tablespace ts_undo1
add datafile '+DG1' size 128000m reuse;
;
!
```

```

extent management dictionary
default storage (initial 128m next 128m maxextents unlimited
pctincrease 0)
nologging
;
!
(( i = $i + 1 ))
done
wait

(( i = 1 ))
while (( i <= 84 ))
do
sqlplus / as sysdba <<! &
set timing on
set echo on
--drop tablespace ts_l${i} including contents;
alter tablespace ts_l${i}
add datafile '+DG1' size 128000m reuse;
alter tablespace ts_l${i}
add datafile '+DG1' size 128000m reuse;
;
!
(( i = $i + 1 ))
done
wait

(( i = 1 ))
while (( i <= 84 ))
do
sqlplus / as sysdba <<! &
set timing on
set echo on
--drop tablespace ts_o${i} including contents;
create tablespace ts_o${i}
datafile '+DG1' size 84000m reuse
extent management dictionary
default storage (initial 96m next 96m maxextents unlimited pctincrease
0)
nologging
;
!
(( i = $i + 1 ))
done
wait

sqlplus / as sysdba <<! &
set timing on
set echo on
--drop tablespace ts_c including contents;
create tablespace ts_c
datafile '+DG1' size 90000m reuse
extent management dictionary
default storage (initial 64m next 64m maxextents unlimited pctincrease
0)
nologging;
!

wait
(( i = 1 ))

while (( i <= 8 ))
do
sqlplus / as sysdba <<! &
set timing on
set echo on
alter tablespace ts_c
add datafile '+DG1' size 90000m reuse;
!

```

```

(( i = $i + 1 ))
done
wait

sqlplus / as sysdba <<! &
set timing on
set echo on
--drop tablespace ts_p including contents;
create tablespace ts_p
datafile '+DG1' size 95000m reuse
extent management dictionary
default storage (initial 64m next 64m maxextents unlimited pctincrease
0)
nologging;
!

```

```

wait

(( i = 1 ))
while (( i <= 8 ))
do
sqlplus / as sysdba <<! &
set timing on
set echo on
alter tablespace ts_p
add datafile '+DG1' size 95000m reuse;
!
(( i = $i + 1 ))
done
wait

sqlplus / as sysdba <<! &
set timing on
set echo on
alter tablespace ts_p
add datafile '+DG1' size 95000m reuse;
!
(( i = $i + 1 ))
done
wait

sqlplus / as sysdba <<! &
set timing on
set echo on
--drop tablespace ts_psupp including contents;
create tablespace ts_psupp
datafile '+DG1' size 128000m reuse
extent management dictionary
default storage (initial 512m next 512m maxextents unlimited
pctincrease 0)
nologging
;
!
wait

(( i = 1 ))
while (( i <= 35 ))
do
sqlplus / as sysdba <<! &
set timing on
set echo on
alter tablespace ts_psupp
add datafile '+DG1' size 128000m reuse;
!
(( i = $i + 1 ))
done
wait

sqlplus / as sysdba <<! &
set timing on
set echo on

```

```

--drop tablespace ts_s including contents;
create tablespace ts_s
datafile '+DG1' size 54000M reuse
extent management dictionary
default storage (initial 8m next 8m maxextents unlimited pctincrease 0)
nologging;
!
!

sqlplus / as sysdba <<! &
set timing on
set echo on

--drop tablespace ts_okey including contents;
create tablespace ts_okey
datafile '+DG1' size 32000m reuse
extent management local
uniform size 5M
nologging;
!
wait
(( i = 1 ))
while (( i <= 35 ))
do
sqlplus / as sysdba <<! &
set timing on
set echo on

alter tablespace ts_okey
add datafile '+DG1' size 32000m reuse;
!
(( i = $i + 1 ))
done

wait
sqlplus / as sysdba <<! &
set timing on
set echo on

--drop tablespace ts_custkey including contents;
create bigfile tablespace ts_custkey
datafile '+DG1' size 150000m reuse
extent management local
uniform size 5M
nologging;
!
sqlplus / as sysdba <<! &
set timing on
set echo on

--drop tablespace ts_lokey including contents;
create tablespace ts_lokey
datafile '+DG1' size 128000m reuse
extent management local
uniform size 5M
nologging;
!
wait
(( i = 1 ))
while (( i <= 44 ))
do
sqlplus / as sysdba <<! &
set timing on
set echo on

alter tablespace ts_lokey
add datafile '+DG1' size 128000m reuse;
!
(( i = $i + 1 ))
done

wait
echo END CREATE TABLESPACES at `date`
```

B.3 dapop.sh

```

#!/bin/ksh

echo START TABLE CREATION at `date`
export ORACLE_SID=tpch;

/dbms/oracle10i/frame/bin/tshut
/dbms/oracle10i/frame/bin/tshut.asm
/dbms/oracle10i/frame/bin/tstart.asm
/dbms/oracle10i/frame/bin/tstart

sqlplus /NOLOG <<!
connect / as sysdba
set timing on
set echo on
set termout on

drop user tpch cascade;
grant DBA
to tpch identified by tpch;

alter user tpch default tablespace ts_default;
alter user tpch temporary tablespace ts_temp;

connect tpch/tpch;
drop directory data_dir1;
drop directory data_dir2;
drop directory data_dir3;
drop directory data_dir4;
drop directory data_dir5;
drop directory data_dir6;
drop directory data_dir7;
drop directory data_dir8;
drop directory data_dir9;
drop directory data_dir10;
drop directory data_dir11;
drop directory data_dir12;
drop directory data_dir13;
drop directory data_dir14;
drop directory data_dir15;
drop directory data_dir16;

create directory data_dir1 as '/flat1/';
create directory data_dir2 as '/flat2/';
create directory data_dir3 as '/flat3/';
create directory data_dir4 as '/flat4/';
create directory data_dir5 as '/flat5/';
create directory data_dir6 as '/flat6/';
```

```

create directory data_dir7 as '/flat7/';
create directory data_dir8 as '/flat8/';
create directory data_dir9 as '/flat9/';
create directory data_dir10 as '/flat10/';
create directory data_dir11 as '/flat11/';
create directory data_dir12 as '/flat12/';
create directory data_dir13 as '/flat13/';
create directory data_dir14 as '/flat14/';
create directory data_dir15 as '/flat15/';
create directory data_dir16 as '/flat16/';
create directory badfiles as '/flat13/BadFiles/';

drop table l_et;
create table l_et(
    l_orderkey      number ,
    l_partkey       number ,
    l_suppkey       number ,
    l_linenumber    number ,
    l_quantity      number ,
    l_extendedprice number ,
    l_discount      number ,
    l_tax           number ,
    l_returnflag    char(1) ,
    l_linestatus     char(1) ,
    l_shipdate      date ,
    l_commitdate    date ,
    l_receiptdate   date ,
    l_shipinstruct  char(25) ,
    l_shipmode      char(10) ,
    l_comment        varchar(44)
)
organization external (
type ORACLE_LOADER
default directory data_dir1
access parameters
(
    records delimited by newline
    badfile badfiles:'line_bad'
    logfile badfiles:'line_log'
    discardfile badfiles:'line_discard.out'
        fields terminated by '|'
        missing field values are null
)
location (
    data_dir1:'lineitem.tbl.1',
    data_dir1:'lineitem.tbl.2',
    data_dir1:'lineitem.tbl.3',
    data_dir1:'lineitem.tbl.4',
    data_dir1:'lineitem.tbl.5',
    data_dir2:'lineitem.tbl.6',
    data_dir2:'lineitem.tbl.7',
    data_dir2:'lineitem.tbl.8',
    data_dir2:'lineitem.tbl.9',
    data_dir2:'lineitem.tbl.10',
    data_dir3:'lineitem.tbl.11',
    data_dir3:'lineitem.tbl.12',
    data_dir3:'lineitem.tbl.13',
    data_dir3:'lineitem.tbl.14',
    data_dir3:'lineitem.tbl.15',
    data_dir4:'lineitem.tbl.16',
    data_dir4:'lineitem.tbl.17',
    data_dir4:'lineitem.tbl.18',
    data_dir4:'lineitem.tbl.19',
    data_dir4:'lineitem.tbl.20',
    data_dir5:'lineitem.tbl.21',
    data_dir5:'lineitem.tbl.22',
    data_dir5:'lineitem.tbl.23',
    data_dir5:'lineitem.tbl.24',
    data_dir5:'lineitem.tbl.25',
    data_dir6:'lineitem.tbl.26',
    data_dir6:'lineitem.tbl.27',
    data_dir6:'lineitem.tbl.28',
    data_dir6:'lineitem.tbl.29',
    data_dir6:'lineitem.tbl.30',
    data_dir7:'lineitem.tbl.31',
    data_dir7:'lineitem.tbl.32',
    data_dir7:'lineitem.tbl.33',
    data_dir7:'lineitem.tbl.34',
    data_dir7:'lineitem.tbl.35',
    data_dir8:'lineitem.tbl.36',
    data_dir8:'lineitem.tbl.37',
    data_dir8:'lineitem.tbl.38',
    data_dir8:'lineitem.tbl.39',
    data_dir8:'lineitem.tbl.40',
    data_dir9:'lineitem.tbl.41',
    data_dir9:'lineitem.tbl.42',
    data_dir9:'lineitem.tbl.43',
    data_dir9:'lineitem.tbl.44',
    data_dir9:'lineitem.tbl.45',
    data_dir10:'lineitem.tbl.46',
    data_dir10:'lineitem.tbl.47',
    data_dir10:'lineitem.tbl.48',
    data_dir10:'lineitem.tbl.49',
    data_dir10:'lineitem.tbl.50',
    data_dir11:'lineitem.tbl.51',
    data_dir11:'lineitem.tbl.52',
    data_dir11:'lineitem.tbl.53',
    data_dir11:'lineitem.tbl.54',
    data_dir11:'lineitem.tbl.55',
    data_dir12:'lineitem.tbl.56',
    data_dir12:'lineitem.tbl.57',
    data_dir12:'lineitem.tbl.58',
    data_dir12:'lineitem.tbl.59',
    data_dir12:'lineitem.tbl.60',
    data_dir13:'lineitem.tbl.61',
    data_dir13:'lineitem.tbl.62',
    data_dir13:'lineitem.tbl.63',
    data_dir13:'lineitem.tbl.64',
    data_dir13:'lineitem.tbl.65',
    data_dir14:'lineitem.tbl.66',
    data_dir14:'lineitem.tbl.67',
    data_dir14:'lineitem.tbl.68',
    data_dir14:'lineitem.tbl.69',
    data_dir14:'lineitem.tbl.70',
    data_dir15:'lineitem.tbl.71',
    data_dir15:'lineitem.tbl.72',
    data_dir15:'lineitem.tbl.73',
    data_dir15:'lineitem.tbl.74',
    data_dir15:'lineitem.tbl.75',
    data_dir16:'lineitem.tbl.76',
    data_dir16:'lineitem.tbl.77',
    data_dir16:'lineitem.tbl.78',
    data_dir16:'lineitem.tbl.79',
    data_dir16:'lineitem.tbl.80',
    data_dir1:'lineitem.tbl.81',
    data_dir2:'lineitem.tbl.82',
    data_dir3:'lineitem.tbl.83',
    data_dir4:'lineitem.tbl.84'
))
reject limit unlimited parallel;

drop table o_et;
create table o_et(
    o_orderkey      number ,
    o_custkey       number ,
    o_orderstatus   char(1) ,
    o_totalprice    number ,
    o_orderdate     date ,
    o_orderpriority char(15) ,
    o_clerk         char(15) ,
    o_shippriority  number ,

```

```

o_comment      varchar(79)
)
organization external (
type ORACLE_LOADER
default directory data_dir1
access parameters
(
    records delimited by newline
nobadfile
nologfile
    fields terminated by '|'
    missing field values are null
)
location (
data_dir1:'orders.tbl.1',
data_dir1:'orders.tbl.2',
data_dir1:'orders.tbl.3',
data_dir1:'orders.tbl.4',
data_dir1:'orders.tbl.5',
data_dir2:'orders.tbl.6',
data_dir2:'orders.tbl.7',
data_dir2:'orders.tbl.8',
data_dir2:'orders.tbl.9',
data_dir2:'orders.tbl.10',
data_dir3:'orders.tbl.11',
data_dir3:'orders.tbl.12',
data_dir3:'orders.tbl.13',
data_dir3:'orders.tbl.14',
data_dir3:'orders.tbl.15',
data_dir4:'orders.tbl.16',
data_dir4:'orders.tbl.17',
data_dir4:'orders.tbl.18',
data_dir4:'orders.tbl.19',
data_dir4:'orders.tbl.20',
data_dir5:'orders.tbl.21',
data_dir5:'orders.tbl.22',
data_dir5:'orders.tbl.23',
data_dir5:'orders.tbl.24',
data_dir5:'orders.tbl.25',
data_dir6:'orders.tbl.26',
data_dir6:'orders.tbl.27',
data_dir6:'orders.tbl.28',
data_dir6:'orders.tbl.29',
data_dir6:'orders.tbl.30',
data_dir7:'orders.tbl.31',
data_dir7:'orders.tbl.32',
data_dir7:'orders.tbl.33',
data_dir7:'orders.tbl.34',
data_dir7:'orders.tbl.35',
data_dir8:'orders.tbl.36',
data_dir8:'orders.tbl.37',
data_dir8:'orders.tbl.38',
data_dir8:'orders.tbl.39',
data_dir8:'orders.tbl.40',
data_dir9:'orders.tbl.41',
data_dir9:'orders.tbl.42',
data_dir9:'orders.tbl.43',
data_dir9:'orders.tbl.44',
data_dir9:'orders.tbl.45',
data_dir10:'orders.tbl.46',
data_dir10:'orders.tbl.47',
data_dir10:'orders.tbl.48',
data_dir10:'orders.tbl.49',
data_dir10:'orders.tbl.50',
data_dir11:'orders.tbl.51',
data_dir11:'orders.tbl.52',
data_dir11:'orders.tbl.53',
data_dir11:'orders.tbl.54',
data_dir11:'orders.tbl.55',
data_dir12:'orders.tbl.56',
data_dir12:'orders.tbl.57',
data_dir12:'orders.tbl.58',
data_dir12:'orders.tbl.59',
data_dir12:'orders.tbl.60',
data_dir13:'orders.tbl.61',
data_dir13:'orders.tbl.62',
data_dir13:'orders.tbl.63',
data_dir13:'orders.tbl.64',
data_dir13:'orders.tbl.65',
data_dir14:'orders.tbl.66',
data_dir14:'orders.tbl.67',
data_dir14:'orders.tbl.68',
data_dir14:'orders.tbl.69',
data_dir14:'orders.tbl.70',
data_dir15:'orders.tbl.71',
data_dir15:'orders.tbl.72',
data_dir15:'orders.tbl.73',
data_dir15:'orders.tbl.74',
data_dir15:'orders.tbl.75',
data_dir16:'orders.tbl.76',
data_dir16:'orders.tbl.77',
data_dir16:'orders.tbl.78',
data_dir16:'orders.tbl.79',
data_dir16:'orders.tbl.80',
data_dir5:'orders.tbl.81',
data_dir6:'orders.tbl.82',
data_dir7:'orders.tbl.83',
data_dir8:'orders.tbl.84'
))
reject limit unlimited parallel;

drop table ps_et;
create table ps_et(
    ps_partkey      number ,
    ps_suppkey      number ,
    ps_availqty     number ,
    ps_supplycost   number ,
    ps_comment       varchar(199)
)
organization external (
type ORACLE_LOADER
default directory data_dir1
access parameters
(
    records delimited by newline
nobadfile
nologfile
    fields terminated by '|'
    missing field values are null
)
location (
data_dir1:'partsupp.tbl.1',
data_dir1:'partsupp.tbl.2',
data_dir1:'partsupp.tbl.3',
data_dir1:'partsupp.tbl.4',
data_dir2:'partsupp.tbl.5',
data_dir2:'partsupp.tbl.6',
data_dir2:'partsupp.tbl.7',
data_dir2:'partsupp.tbl.8',
data_dir3:'partsupp.tbl.9',
data_dir3:'partsupp.tbl.10',
data_dir3:'partsupp.tbl.11',
data_dir3:'partsupp.tbl.12',
data_dir4:'partsupp.tbl.13',
data_dir4:'partsupp.tbl.14',
data_dir4:'partsupp.tbl.15',
data_dir4:'partsupp.tbl.16',
data_dir5:'partsupp.tbl.17',
data_dir5:'partsupp.tbl.18',
data_dir5:'partsupp.tbl.19',
data_dir5:'partsupp.tbl.20',
data_dir6:'partsupp.tbl.21',

```

```

data_dir6:'partsupp.tbl.22',
data_dir6:'partsupp.tbl.23',
data_dir6:'partsupp.tbl.24',
data_dir7:'partsupp.tbl.25',
data_dir7:'partsupp.tbl.26',
data_dir7:'partsupp.tbl.27',
data_dir7:'partsupp.tbl.28',
data_dir8:'partsupp.tbl.29',
data_dir8:'partsupp.tbl.30',
data_dir8:'partsupp.tbl.31',
data_dir8:'partsupp.tbl.32',
data_dir9:'partsupp.tbl.33',
data_dir9:'partsupp.tbl.34',
data_dir9:'partsupp.tbl.35',
data_dir9:'partsupp.tbl.36',
data_dir10:'partsupp.tbl.37',
data_dir10:'partsupp.tbl.38',
data_dir10:'partsupp.tbl.39',
data_dir10:'partsupp.tbl.40',
data_dir11:'partsupp.tbl.41',
data_dir11:'partsupp.tbl.42',
data_dir11:'partsupp.tbl.43',
data_dir11:'partsupp.tbl.44',
data_dir12:'partsupp.tbl.45',
data_dir12:'partsupp.tbl.46',
data_dir12:'partsupp.tbl.47',
data_dir12:'partsupp.tbl.48',
data_dir13:'partsupp.tbl.49',
data_dir13:'partsupp.tbl.50',
data_dir13:'partsupp.tbl.51',
data_dir13:'partsupp.tbl.52',
data_dir14:'partsupp.tbl.53',
data_dir14:'partsupp.tbl.54',
data_dir14:'partsupp.tbl.55',
data_dir14:'partsupp.tbl.56',
data_dir15:'partsupp.tbl.57',
data_dir15:'partsupp.tbl.58',
data_dir15:'partsupp.tbl.59',
data_dir15:'partsupp.tbl.60',
data_dir16:'partsupp.tbl.61',
data_dir16:'partsupp.tbl.62',
data_dir16:'partsupp.tbl.63',
data_dir16:'partsupp.tbl.64'
))
reject limit unlimited parallel;

drop table p_et;
create table p_et(
    p_partkey      number ,
    p_name         varchar(55) ,
    p_mfgr         char(25) ,
    p_brand        char(10) ,
    p_type         varchar(25) ,
    p_size         number ,
    p_container    char(10) ,
    p_retailprice  number ,
    p_comment      varchar(23)
)
organization external (
    type ORACLE_LOADER
    default directory data_dir1
    access parameters
    (
        records delimited by newline
        nobadfile
        nologfile
        fields terminated by '|'
        missing field values are null
    )
    location (
        data_dir1:'part.tbl.1',
        data_dir1:'part.tbl.2',
        data_dir1:'part.tbl.3',
        data_dir1:'part.tbl.4',
        data_dir2:'part.tbl.5',
        data_dir2:'part.tbl.6',
        data_dir2:'part.tbl.7',
        data_dir2:'part.tbl.8',
        data_dir3:'part.tbl.9',
        data_dir3:'part.tbl.10',
        data_dir3:'part.tbl.11',
        data_dir3:'part.tbl.12',
        data_dir4:'part.tbl.13',
        data_dir4:'part.tbl.14',
        data_dir4:'part.tbl.15',
        data_dir4:'part.tbl.16',
        data_dir5:'part.tbl.17',
        data_dir5:'part.tbl.18',
        data_dir5:'part.tbl.19',
        data_dir5:'part.tbl.20',
        data_dir6:'part.tbl.21',
        data_dir6:'part.tbl.22',
        data_dir6:'part.tbl.23',
        data_dir6:'part.tbl.24',
        data_dir7:'part.tbl.25',
        data_dir7:'part.tbl.26',
        data_dir7:'part.tbl.27',
        data_dir7:'part.tbl.28',
        data_dir8:'part.tbl.29',
        data_dir8:'part.tbl.30',
        data_dir8:'part.tbl.31',
        data_dir8:'part.tbl.32',
        data_dir9:'part.tbl.33',
        data_dir9:'part.tbl.34',
        data_dir9:'part.tbl.35',
        data_dir9:'part.tbl.36',
        data_dir10:'part.tbl.37',
        data_dir10:'part.tbl.38',
        data_dir10:'part.tbl.39',
        data_dir11:'part.tbl.40',
        data_dir11:'part.tbl.41',
        data_dir11:'part.tbl.42',
        data_dir11:'part.tbl.43',
        data_dir11:'part.tbl.44',
        data_dir12:'part.tbl.45',
        data_dir12:'part.tbl.46',
        data_dir12:'part.tbl.47',
        data_dir12:'part.tbl.48',
        data_dir13:'part.tbl.49',
        data_dir13:'part.tbl.50',
        data_dir13:'part.tbl.51',
        data_dir13:'part.tbl.52',
        data_dir14:'part.tbl.53',
        data_dir14:'part.tbl.54',
        data_dir14:'part.tbl.55',
        data_dir14:'part.tbl.56',
        data_dir15:'part.tbl.57',
        data_dir15:'part.tbl.58',
        data_dir15:'part.tbl.59',
        data_dir15:'part.tbl.60',
        data_dir16:'part.tbl.61',
        data_dir16:'part.tbl.62',
        data_dir16:'part.tbl.63',
        data_dir16:'part.tbl.64'
    )))
reject limit unlimited parallel;

drop table c_et;
create table c_et(
    c_custkey      number ,
    c_name         varchar(25) ,
)

```

```

c_address      varchar(40) ,
c_nationkey    number ,
c_phone        char(15) ,
c_acctbal      number ,
c_mktsegment   char(10) ,
c_comment       varchar(117)
)
organization external (
type ORACLE_LOADER
default directory data_dir1
access parameters
(
      records delimited by newline
  nobadfile
  nologfile
      fields terminated by '|'
      missing field values are null
)
location (
data_dir1:'customer.tbl.1',
data_dir1:'customer.tbl.2',
data_dir1:'customer.tbl.3',
data_dir1:'customer.tbl.4',
data_dir2:'customer.tbl.5',
data_dir2:'customer.tbl.6',
data_dir2:'customer.tbl.7',
data_dir2:'customer.tbl.8',
data_dir3:'customer.tbl.9',
data_dir3:'customer.tbl.10',
data_dir3:'customer.tbl.11',
data_dir3:'customer.tbl.12',
data_dir4:'customer.tbl.13',
data_dir4:'customer.tbl.14',
data_dir4:'customer.tbl.15',
data_dir4:'customer.tbl.16',
data_dir5:'customer.tbl.17',
data_dir5:'customer.tbl.18',
data_dir5:'customer.tbl.19',
data_dir5:'customer.tbl.20',
data_dir6:'customer.tbl.21',
data_dir6:'customer.tbl.22',
data_dir6:'customer.tbl.23',
data_dir6:'customer.tbl.24',
data_dir7:'customer.tbl.25',
data_dir7:'customer.tbl.26',
data_dir7:'customer.tbl.27',
data_dir7:'customer.tbl.28',
data_dir8:'customer.tbl.29',
data_dir8:'customer.tbl.30',
data_dir8:'customer.tbl.31',
data_dir8:'customer.tbl.32',
data_dir9:'customer.tbl.33',
data_dir9:'customer.tbl.34',
data_dir9:'customer.tbl.35',
data_dir9:'customer.tbl.36',
data_dir10:'customer.tbl.37',
data_dir10:'customer.tbl.38',
data_dir10:'customer.tbl.39',
data_dir10:'customer.tbl.40',
data_dir11:'customer.tbl.41',
data_dir11:'customer.tbl.42',
data_dir11:'customer.tbl.43',
data_dir11:'customer.tbl.44',
data_dir12:'customer.tbl.45',
data_dir12:'customer.tbl.46',
data_dir12:'customer.tbl.47',
data_dir12:'customer.tbl.48',
data_dir13:'customer.tbl.49',
data_dir13:'customer.tbl.50',
data_dir13:'customer.tbl.51',
data_dir13:'customer.tbl.52',
data_dir14:'customer.tbl.53',
data_dir14:'customer.tbl.54',
data_dir14:'customer.tbl.55',
data_dir14:'customer.tbl.56',
data_dir15:'customer.tbl.57',
data_dir15:'customer.tbl.58',
data_dir15:'customer.tbl.59',
data_dir15:'customer.tbl.60',
data_dir16:'customer.tbl.61',
data_dir16:'customer.tbl.62',
data_dir16:'customer.tbl.63',
data_dir16:'customer.tbl.64'
))
reject limit unlimited parallel;

drop table s_et;
create table s_et(
  s_suppkey      number ,
  s_name         char(25) ,
  s_address      varchar(40) ,
  s_nationkey    number ,
  s_phone        char(15) ,
  s_acctbal      number ,
  s_comment       varchar(101)
)
organization external (
type ORACLE_LOADER
default directory data_dir1
access parameters
(
      records delimited by newline
  nobadfile
  nologfile
      fields terminated by '|'
      missing field values are null
)
location (
data_dir1:'supplier.tbl.1',
data_dir1:'supplier.tbl.2',
data_dir1:'supplier.tbl.3',
data_dir1:'supplier.tbl.4',
data_dir2:'supplier.tbl.5',
data_dir2:'supplier.tbl.6',
data_dir2:'supplier.tbl.7',
data_dir2:'supplier.tbl.8',
data_dir3:'supplier.tbl.9',
data_dir3:'supplier.tbl.10',
data_dir3:'supplier.tbl.11',
data_dir3:'supplier.tbl.12',
data_dir4:'supplier.tbl.13',
data_dir4:'supplier.tbl.14',
data_dir4:'supplier.tbl.15',
data_dir4:'supplier.tbl.16',
data_dir5:'supplier.tbl.17',
data_dir5:'supplier.tbl.18',
data_dir5:'supplier.tbl.19',
data_dir5:'supplier.tbl.20',
data_dir6:'supplier.tbl.21',
data_dir6:'supplier.tbl.22',
data_dir6:'supplier.tbl.23',
data_dir6:'supplier.tbl.24',
data_dir7:'supplier.tbl.25',
data_dir7:'supplier.tbl.26',
data_dir7:'supplier.tbl.27',
data_dir7:'supplier.tbl.28',
data_dir8:'supplier.tbl.29',
data_dir8:'supplier.tbl.30',
data_dir8:'supplier.tbl.31',
data_dir8:'supplier.tbl.32',
data_dir9:'supplier.tbl.33',
data_dir9:'supplier.tbl.34',

```

```

data_dir9:'supplier.tbl.35',
data_dir9:'supplier.tbl.36',
data_dir10:'supplier.tbl.37',
data_dir10:'supplier.tbl.38',
data_dir10:'supplier.tbl.39',
data_dir10:'supplier.tbl.40',
data_dir11:'supplier.tbl.41',
data_dir11:'supplier.tbl.42',
data_dir11:'supplier.tbl.43',
data_dir11:'supplier.tbl.44',
data_dir12:'supplier.tbl.45',
data_dir12:'supplier.tbl.46',
data_dir12:'supplier.tbl.47',
data_dir12:'supplier.tbl.48',
data_dir13:'supplier.tbl.49',
data_dir13:'supplier.tbl.50',
data_dir13:'supplier.tbl.51',
data_dir13:'supplier.tbl.52',
data_dir14:'supplier.tbl.53',
data_dir14:'supplier.tbl.54',
data_dir14:'supplier.tbl.55',
data_dir14:'supplier.tbl.56',
data_dir15:'supplier.tbl.57',
data_dir15:'supplier.tbl.58',
data_dir15:'supplier.tbl.59',
data_dir15:'supplier.tbl.60',
data_dir16:'supplier.tbl.61',
data_dir16:'supplier.tbl.62',
data_dir16:'supplier.tbl.63',
data_dir16:'supplier.tbl.64'
))
)
reject limit unlimited parallel;

drop table n_et;
create table n_et(
  n_nationkey      number ,
  n_name            char(25) ,
  n_regionkey       number ,
  n_comment          varchar(152)
)
organization external (
type ORACLE_LOADER
default directory data_dir1
access parameters
(
  records delimited by newline
  nobadfile
  nologfile
    fields terminated by '|'
    missing field values are null
  )
  location (
    data_dir9:'nation.tbl'))
reject limit unlimited;

drop table r_et;
create table r_et(
  r_regionkey      number ,
  r_name            char(25) ,
  r_comment          varchar(152)
)
organization external (
type ORACLE_LOADER
default directory data_dir1
access parameters
(
  records delimited by newline
  nobadfile
  nologfile
    fields terminated by '|'
    missing field values are null
  )
  location (
    data_dir9:'region.tbl'))
reject limit unlimited;

)
location (
  data_dir9:'region.tbl'))
reject limit unlimited;

drop table lineitem;
create table lineitem(
  l_shipdate        ,
  l_orderkey      NOT NULL,
  l_discount       NOT NULL,
  l_extendedprice  NOT NULL,
  l_suppkey        NOT NULL,
  l_quantity        NOT NULL,
  l_returnflag     ,
  l_partkey        NOT NULL,
  l_linenumber     ,
  l_shipinstruct   ,
  l_comment         )
pctfree 1
pctused 99
initrans 10
storage (freelist groups 4 freelists 84)
parallel
nologging
partition by range (l_shipdate)
subpartition by hash(l_partkey)
subpartitions 128
(
  partition item1 values less than (to_date('1992-01-01','YYYY-MM-DD'))
  tablespace ts_11
  ,
  partition item2 values less than (to_date('1992-02-01','YYYY-MM-DD'))
  tablespace ts_12
  ,
  partition item3 values less than (to_date('1992-03-01','YYYY-MM-DD'))
  tablespace ts_13
  ,
  partition item4 values less than (to_date('1992-04-01','YYYY-MM-DD'))
  tablespace ts_14
  ,
  partition item5 values less than (to_date('1992-05-01','YYYY-MM-DD'))
  tablespace ts_15
  ,
  partition item6 values less than (to_date('1992-06-01','YYYY-MM-DD'))
  tablespace ts_16
  ,
  partition item7 values less than (to_date('1992-07-01','YYYY-MM-DD'))
  tablespace ts_17
  ,
  partition item8 values less than (to_date('1992-08-01','YYYY-MM-DD'))
  tablespace ts_18
  ,
  partition item9 values less than (to_date('1992-09-01','YYYY-MM-DD'))
  tablespace ts_19
  ,
)

```

```

partition item10 values less than (to_date('1992-10-01','YYYY-MM-  
DD'))  
tablespace ts_110  
,
```

```

partition item11 values less than (to_date('1992-11-01','YYYY-MM-  
DD'))  
tablespace ts_111  
,
```

```

partition item12 values less than (to_date('1992-12-01','YYYY-MM-  
DD'))  
tablespace ts_112  
,
```

```

partition item13 values less than (to_date('1993-01-01','YYYY-MM-  
DD'))  
tablespace ts_113  
,
```

```

partition item14 values less than (to_date('1993-02-01','YYYY-MM-  
DD'))  
tablespace ts_114  
,
```

```

partition item15 values less than (to_date('1993-03-01','YYYY-MM-  
DD'))  
tablespace ts_115  
,
```

```

partition item16 values less than (to_date('1993-04-01','YYYY-MM-  
DD'))  
tablespace ts_116  
,
```

```

partition item17 values less than (to_date('1993-05-01','YYYY-MM-  
DD'))  
tablespace ts_117  
,
```

```

partition item18 values less than (to_date('1993-06-01','YYYY-MM-  
DD'))  
tablespace ts_118  
,
```

```

partition item19 values less than (to_date('1993-07-01','YYYY-MM-  
DD'))  
tablespace ts_119  
,
```

```

partition item20 values less than (to_date('1993-08-01','YYYY-MM-  
DD'))  
tablespace ts_120  
,
```

```

partition item21 values less than (to_date('1993-09-01','YYYY-MM-  
DD'))  
tablespace ts_121  
,
```

```

partition item22 values less than (to_date('1993-10-01','YYYY-MM-  
DD'))  
tablespace ts_122  
,
```

```

partition item23 values less than (to_date('1993-11-01','YYYY-MM-  
DD'))  
tablespace ts_123  
,
```

```

partition item24 values less than (to_date('1993-12-01','YYYY-MM-  
DD'))  
tablespace ts_124  
,
```

```

partition item25 values less than (to_date('1994-01-01','YYYY-MM-  
DD'))  
tablespace ts_125  
,
```

```

partition item26 values less than (to_date('1994-02-01','YYYY-MM-  
DD'))  
tablespace ts_126  
,
```

```

partition item27 values less than (to_date('1994-03-01','YYYY-MM-  
DD'))  
tablespace ts_127  
,
```

```

partition item28 values less than (to_date('1994-04-01','YYYY-MM-  
DD'))  
tablespace ts_128  
,
```

```

partition item29 values less than (to_date('1994-05-01','YYYY-MM-  
DD'))  
tablespace ts_129  
,
```

```

partition item30 values less than (to_date('1994-06-01','YYYY-MM-  
DD'))  
tablespace ts_130  
,
```

```

partition item31 values less than (to_date('1994-07-01','YYYY-MM-  
DD'))  
tablespace ts_131  
,
```

```

partition item32 values less than (to_date('1994-08-01','YYYY-MM-  
DD'))  
tablespace ts_132  
,
```

```

partition item33 values less than (to_date('1994-09-01','YYYY-MM-  
DD'))  
tablespace ts_133  
,
```

```

partition item34 values less than (to_date('1994-10-01','YYYY-MM-  
DD'))  
tablespace ts_134  
,
```

```

partition item35 values less than (to_date('1994-11-01','YYYY-MM-  
DD'))  
tablespace ts_135  
,
```

```

partition item36 values less than (to_date('1994-12-01','YYYY-MM-  
DD'))  
tablespace ts_136  
,
```

```

partition item37 values less than (to_date('1995-01-01','YYYY-MM-  
DD'))  
tablespace ts_137  
,
```

```

partition item38 values less than (to_date('1995-02-01','YYYY-MM-  
DD'))  
tablespace ts_138  
,
```

```

partition item39 values less than (to_date('1995-03-01','YYYY-MM-  
DD'))  
tablespace ts_139  
,
```

```

partition item40 values less than (to_date('1995-04-01','YYYY-MM-  
DD'))  
tablespace ts_140  
,
```

```

partition item41 values less than (to_date('1995-05-01','YYYY-MM-  
DD'))  
tablespace ts_141  
,
```

```

partition item42 values less than (to_date('1995-06-01','YYYY-MM-  
DD'))  
tablespace ts_142  
,
```

```

partition item43 values less than (to_date('1995-07-01','YYYY-MM-  
DD'))  
tablespace ts_143  
,
```

```

partition item44 values less than (to_date('1995-08-01','YYYY-MM-  
DD'))  
tablespace ts_144  
,
```

```

partition item45 values less than (to_date('1995-09-01','YYYY-MM-  
DD'))  


```

```

tablespace ts_145
,
partition item46 values less than (to_date('1995-10-01','YYYY-MM-DD'))
tablespace ts_146
,
partition item47 values less than (to_date('1995-11-01','YYYY-MM-DD'))
tablespace ts_147
,
partition item48 values less than (to_date('1995-12-01','YYYY-MM-DD'))
tablespace ts_148
,
partition item49 values less than (to_date('1996-01-01','YYYY-MM-DD'))
tablespace ts_149
,
partition item50 values less than (to_date('1996-02-01','YYYY-MM-DD'))
tablespace ts_150
,
partition item51 values less than (to_date('1996-03-01','YYYY-MM-DD'))
tablespace ts_151
,
partition item52 values less than (to_date('1996-04-01','YYYY-MM-DD'))
tablespace ts_152
,
partition item53 values less than (to_date('1996-05-01','YYYY-MM-DD'))
tablespace ts_153
,
partition item54 values less than (to_date('1996-06-01','YYYY-MM-DD'))
tablespace ts_154
,
partition item55 values less than (to_date('1996-07-01','YYYY-MM-DD'))
tablespace ts_155
,
partition item56 values less than (to_date('1996-08-01','YYYY-MM-DD'))
tablespace ts_156
,
partition item57 values less than (to_date('1996-09-01','YYYY-MM-DD'))
tablespace ts_157
,
partition item58 values less than (to_date('1996-10-01','YYYY-MM-DD'))
tablespace ts_158
,
partition item59 values less than (to_date('1996-11-01','YYYY-MM-DD'))
tablespace ts_159
,
partition item60 values less than (to_date('1996-12-01','YYYY-MM-DD'))
tablespace ts_160
,
partition item61 values less than (to_date('1997-01-01','YYYY-MM-DD'))
tablespace ts_161
,
partition item62 values less than (to_date('1997-02-01','YYYY-MM-DD'))
tablespace ts_162
,
partition item63 values less than (to_date('1997-03-01','YYYY-MM-DD'))
tablespace ts_163
,
partition item64 values less than (to_date('1997-04-01','YYYY-MM-DD'))
tablespace ts_164
,
partition item65 values less than (to_date('1997-05-01','YYYY-MM-DD'))
tablespace ts_165
,
partition item66 values less than (to_date('1997-06-01','YYYY-MM-DD'))
tablespace ts_166
,
partition item67 values less than (to_date('1997-07-01','YYYY-MM-DD'))
tablespace ts_167
,
partition item68 values less than (to_date('1997-08-01','YYYY-MM-DD'))
tablespace ts_168
,
partition item69 values less than (to_date('1997-09-01','YYYY-MM-DD'))
tablespace ts_169
,
partition item70 values less than (to_date('1997-10-01','YYYY-MM-DD'))
tablespace ts_170
,
partition item71 values less than (to_date('1997-11-01','YYYY-MM-DD'))
tablespace ts_171
,
partition item72 values less than (to_date('1997-12-01','YYYY-MM-DD'))
tablespace ts_172
,
partition item73 values less than (to_date('1998-01-01','YYYY-MM-DD'))
tablespace ts_173
,
partition item74 values less than (to_date('1998-02-01','YYYY-MM-DD'))
tablespace ts_174
,
partition item75 values less than (to_date('1998-03-01','YYYY-MM-DD'))
tablespace ts_175
,
partition item76 values less than (to_date('1998-04-01','YYYY-MM-DD'))
tablespace ts_176
,
partition item77 values less than (to_date('1998-05-01','YYYY-MM-DD'))
tablespace ts_177
,
partition item78 values less than (to_date('1998-06-01','YYYY-MM-DD'))
tablespace ts_178
,
partition item79 values less than (to_date('1998-07-01','YYYY-MM-DD'))
tablespace ts_179
,
partition item80 values less than (to_date('1998-08-01','YYYY-MM-DD'))
tablespace ts_180

```

```

partition item81 values less than (to_date('1998-09-01','YYYY-MM-  
DD'))  
tablespace ts_l81  
,
```

```

partition item82 values less than (to_date('1998-10-01','YYYY-MM-  
DD'))  
tablespace ts_l82  
,
```

```

partition item83 values less than (to_date('1998-11-01','YYYY-MM-  
DD'))  
tablespace ts_l83  
,
```

```

partition item84 values less than (MAXVALUE)  
tablespace ts_l84 )  
as select  

l_shipdate      ,  

l_orderkey      ,  

l_discount      ,  

l_extendedprice ,  

l_suppkey       ,  

l_quantity      ,  

l_returnflag    ,  

l_partkey       ,  

l_linestatus    ,  

l_tax           ,  

l_commitdate    ,  

l_receiptdate   ,  

l_shipmode      ,  

l_linenumber    ,  

l_shipinstruct  ,  

l_comment        ,  
from l_et ORDER BY l_orderkey;  
  

drop table orders;  
create table orders(  

o_orderdate      ,  

o_orderkey      NOT NULL,  

o_custkey       NOT NULL,  

o_orderpriority ,  

o_shippriority  ,  

o_clerk         ,  

o_orderstatus   ,  

o_totalprice    ,  

o_comment        ,  
)  
pctfree 1  
pctused 99  
initrans 10  
storage (freelist groups 4 freelists 99)  
parallel  
nologging  
partition by range (o_orderdate)  
subpartition by hash(o_custkey)  
subpartitions 128  
(  
partition ord1 values less than (to_date('1992-01-01','YYYY-MM-  
DD'))  
tablespace ts_o1  
,
```

```

partition ord2 values less than (to_date('1992-02-01','YYYY-MM-  
DD'))  
tablespace ts_o2  
,
```

```

partition ord3 values less than (to_date('1992-03-01','YYYY-MM-  
DD'))  
tablespace ts_o3  
,
```

```

partition ord4 values less than (to_date('1992-04-01','YYYY-MM-  
DD'))  
tablespace ts_o4  
,
```

```

partition ord5 values less than (to_date('1992-05-01','YYYY-MM-  
DD'))  
tablespace ts_o5  
,
```

```

partition ord6 values less than (to_date('1992-06-01','YYYY-MM-  
DD'))  
tablespace ts_o6  
,
```

```

partition ord7 values less than (to_date('1992-07-01','YYYY-MM-  
DD'))  
tablespace ts_o7  
,
```

```

partition ord8 values less than (to_date('1992-08-01','YYYY-MM-  
DD'))  
tablespace ts_o8  
,
```

```

partition ord9 values less than (to_date('1992-09-01','YYYY-MM-  
DD'))  
tablespace ts_o9  
,
```

```

partition ord10 values less than (to_date('1992-10-01','YYYY-MM-  
DD'))  
tablespace ts_o10  
,
```

```

partition ord11 values less than (to_date('1992-11-01','YYYY-MM-  
DD'))  
tablespace ts_o11  
,
```

```

partition ord12 values less than (to_date('1992-12-01','YYYY-MM-  
DD'))  
tablespace ts_o12  
,
```

```

partition ord13 values less than (to_date('1993-01-01','YYYY-MM-  
DD'))  
tablespace ts_o13  
,
```

```

partition ord14 values less than (to_date('1993-02-01','YYYY-MM-  
DD'))  
tablespace ts_o14  
,
```

```

partition ord15 values less than (to_date('1993-03-01','YYYY-MM-  
DD'))  
tablespace ts_o15  
,
```

```

partition ord16 values less than (to_date('1993-04-01','YYYY-MM-  
DD'))  
tablespace ts_o16  
,
```

```

partition ord17 values less than (to_date('1993-05-01','YYYY-MM-  
DD'))  
tablespace ts_o17  
,
```

```

partition ord18 values less than (to_date('1993-06-01','YYYY-MM-  
DD'))  
tablespace ts_o18  
,
```

```

partition ord19 values less than (to_date('1993-07-01','YYYY-MM-  
DD'))  
tablespace ts_o19  
,
```

```

partition ord20 values less than (to_date('1993-08-01','YYYY-MM-  
DD'))  
tablespace ts_o20  
,
```

```

partition ord21 values less than (to_date('1993-09-01','YYYY-MM-  
DD'))  
tablespace ts_o21  
,
```

```

partition ord22 values less than (to_date('1993-10-01','YYYY-MM-  
DD'))  
tablespace ts_o22  
,
```

```

partition ord23 values less than (to_date('1993-11-01','YYYY-MM-  
DD'))  
tablespace ts_o23  
,
```

```

partition ord24 values less than (to_date('1993-12-01','YYYY-MM-  
DD'))  
tablespace ts_o24

```

```

tablespace ts_o24
,
partition ord25 values less than (to_date('1994-01-01','YYYY-MM-DD'))
tablespace ts_o25
,
partition ord26 values less than (to_date('1994-02-01','YYYY-MM-DD'))
tablespace ts_o26
,
partition ord27 values less than (to_date('1994-03-01','YYYY-MM-DD'))
tablespace ts_o27
,
partition ord28 values less than (to_date('1994-04-01','YYYY-MM-DD'))
tablespace ts_o28
,
partition ord29 values less than (to_date('1994-05-01','YYYY-MM-DD'))
tablespace ts_o29
,
partition ord30 values less than (to_date('1994-06-01','YYYY-MM-DD'))
tablespace ts_o30
,
partition ord31 values less than (to_date('1994-07-01','YYYY-MM-DD'))
tablespace ts_o31
,
partition ord32 values less than (to_date('1994-08-01','YYYY-MM-DD'))
tablespace ts_o32
,
partition ord33 values less than (to_date('1994-09-01','YYYY-MM-DD'))
tablespace ts_o33
,
partition ord34 values less than (to_date('1994-10-01','YYYY-MM-DD'))
tablespace ts_o34
,
partition ord35 values less than (to_date('1994-11-01','YYYY-MM-DD'))
tablespace ts_o35
,
partition ord36 values less than (to_date('1994-12-01','YYYY-MM-DD'))
tablespace ts_o36
,
partition ord37 values less than (to_date('1995-01-01','YYYY-MM-DD'))
tablespace ts_o37
,
partition ord38 values less than (to_date('1995-02-01','YYYY-MM-DD'))
tablespace ts_o38
,
partition ord39 values less than (to_date('1995-03-01','YYYY-MM-DD'))
tablespace ts_o39
,
partition ord40 values less than (to_date('1995-04-01','YYYY-MM-DD'))
tablespace ts_o40
,
partition ord41 values less than (to_date('1995-05-01','YYYY-MM-DD'))
tablespace ts_o41
,
partition ord42 values less than (to_date('1995-06-01','YYYY-MM-DD'))
tablespace ts_o42
,
partition ord43 values less than (to_date('1995-07-01','YYYY-MM-DD'))
tablespace ts_o43
,
partition ord44 values less than (to_date('1995-08-01','YYYY-MM-DD'))
tablespace ts_o44
,
partition ord45 values less than (to_date('1995-09-01','YYYY-MM-DD'))
tablespace ts_o45
,
partition ord46 values less than (to_date('1995-10-01','YYYY-MM-DD'))
tablespace ts_o46
,
partition ord47 values less than (to_date('1995-11-01','YYYY-MM-DD'))
tablespace ts_o47
,
partition ord48 values less than (to_date('1995-12-01','YYYY-MM-DD'))
tablespace ts_o48
,
partition ord49 values less than (to_date('1996-01-01','YYYY-MM-DD'))
tablespace ts_o49
,
partition ord50 values less than (to_date('1996-02-01','YYYY-MM-DD'))
tablespace ts_o50
,
partition ord51 values less than (to_date('1996-03-01','YYYY-MM-DD'))
tablespace ts_o51
,
partition ord52 values less than (to_date('1996-04-01','YYYY-MM-DD'))
tablespace ts_o52
,
partition ord53 values less than (to_date('1996-05-01','YYYY-MM-DD'))
tablespace ts_o53
,
partition ord54 values less than (to_date('1996-06-01','YYYY-MM-DD'))
tablespace ts_o54
,
partition ord55 values less than (to_date('1996-07-01','YYYY-MM-DD'))
tablespace ts_o55
,
partition ord56 values less than (to_date('1996-08-01','YYYY-MM-DD'))
tablespace ts_o56
,
partition ord57 values less than (to_date('1996-09-01','YYYY-MM-DD'))
tablespace ts_o57
,
partition ord58 values less than (to_date('1996-10-01','YYYY-MM-DD'))
tablespace ts_o58
,
partition ord59 values less than (to_date('1996-11-01','YYYY-MM-DD'))
tablespace ts_o59

```

```

,
partition ord60 values less than (to_date('1996-12-01','YYYY-MM-
DD'))
tablespace ts_060
,
partition ord61 values less than (to_date('1997-01-01','YYYY-MM-
DD'))
tablespace ts_061
,
partition ord62 values less than (to_date('1997-02-01','YYYY-MM-
DD'))
tablespace ts_062
,
partition ord63 values less than (to_date('1997-03-01','YYYY-MM-
DD'))
tablespace ts_063
,
partition ord64 values less than (to_date('1997-04-01','YYYY-MM-
DD'))
tablespace ts_064
,
partition ord65 values less than (to_date('1997-05-01','YYYY-MM-
DD'))
tablespace ts_065
,
partition ord66 values less than (to_date('1997-06-01','YYYY-MM-
DD'))
tablespace ts_066
,
partition ord67 values less than (to_date('1997-07-01','YYYY-MM-
DD'))
tablespace ts_067
,
partition ord68 values less than (to_date('1997-08-01','YYYY-MM-
DD'))
tablespace ts_068
,
partition ord69 values less than (to_date('1997-09-01','YYYY-MM-
DD'))
tablespace ts_069
,
partition ord70 values less than (to_date('1997-10-01','YYYY-MM-
DD'))
tablespace ts_070
,
partition ord71 values less than (to_date('1997-11-01','YYYY-MM-
DD'))
tablespace ts_071
,
partition ord72 values less than (to_date('1997-12-01','YYYY-MM-
DD'))
tablespace ts_072
,
partition ord73 values less than (to_date('1998-01-01','YYYY-MM-
DD'))
tablespace ts_073
,
partition ord74 values less than (to_date('1998-02-01','YYYY-MM-
DD'))
tablespace ts_074
,
partition ord75 values less than (to_date('1998-03-01','YYYY-MM-
DD'))
tablespace ts_075
,
partition ord76 values less than (to_date('1998-04-01','YYYY-MM-
DD'))
tablespace ts_076
,
partition ord77 values less than (to_date('1998-05-01','YYYY-MM-
DD'))

```

```

tablespace ts_077
,
partition ord78 values less than (to_date('1998-06-01','YYYY-MM-
DD'))
tablespace ts_078
,
partition ord79 values less than (to_date('1998-07-01','YYYY-MM-
DD'))
tablespace ts_079
,
partition ord80 values less than (to_date('1998-08-01','YYYY-MM-
DD'))
tablespace ts_080
,
partition ord81 values less than (to_date('1998-09-01','YYYY-MM-
DD'))
tablespace ts_081
,
partition ord82 values less than (to_date('1998-10-01','YYYY-MM-
DD'))
tablespace ts_082
,
partition ord83 values less than (to_date('1998-11-01','YYYY-MM-
DD'))
tablespace ts_083
,
partition ord84 values less than (MAXVALUE)
tablespace ts_084 )
as select
    o_orderdate      ,
    o_orderkey       ,
    o_custkey        ,
    o_orderpriority  ,
    o_shipppriority  ,
    o_clerk          ,
    o_orderstatus    ,
    o_totalprice    ,
    o_comment        ,
from o_et ORDER BY o_orderkey ;
```

```

drop table partsupp;
create table partsupp(
    ps_partkey      NOT NULL,
    ps_suppkey      NOT NULL,
    ps_supplycost   NOT NULL,
    ps_availqty     ,
    ps_comment      )
parallel
nologging
partition by hash(ps_partkey)
partitions 128
tablespace ts_pspp
as select
    ps_partkey      ,
    ps_suppkey      ,
    ps_supplycost   ,
    ps_availqty     ,
    ps_comment      from ps_et;
```

```

drop table customer;
create table customer(
    c_custkey      NOT NULL,
    c_mktsegment   ,
    c_nationkey    ,
    c_name         ,
    c_address      ,
    c_phone        ,
```

```

c_acctbal      ,
c_comment      ,
)
pctfree 0
pctused 99
parallel
nologging
partition by hash (c_custkey)
partitions 128
tablespace ts_c
storage (initial 100m)
as select
  c_custkey      ,
  c_mktsegment   ,
  c_nationkey    ,
  c_name         ,
  c_address      ,
  c_phone        ,
  c_acctbal      ,
  c_comment      ,
from c_et;

drop table part;

create table part(
  p_partkey      NOT NULL,
  p_type         ,
  p_size         ,
  p_brand        ,
  p_name         ,
  p_container    ,
  p_mfgr         ,
  p_retailprice  ,
  p_comment      )
)
pctfree 0
pctused 99
parallel
nologging
partition by hash (p_partkey)
partitions 128
tablespace ts_p
storage (initial 100m)
as select
  p_partkey      ,
  p_type         ,
  p_size         ,
  p_brand        ,
  p_name         ,
  p_container    ,
  p_mfgr         ,
  p_retailprice  ,
  p_comment      ,
from p_et;

drop table supplier;
create table supplier(
  s_suppkey      NOT NULL,
  s_nationkey    ,
  s_comment      ,
  s_name         ,
  s_address      ,
  s_phone        ,
  s_acctbal      )
)
pctfree 0
pctused 99
parallel
nologging
partition by hash (s_suppkey)
partitions 128
tablespace ts_s
as select
  s_suppkey      ,
  s_nationkey    ,
  s_comment      ,
  s_name         ,
  s_address      ,
  s_phone        ,
  s_acctbal      ,
from s_et;

drop table nation;
create table nation(
  n_nationkey    NOT NULL,
  n_name         ,
  n_regionkey    ,
  n_comment      )
tablespace ts_default
as select * from n_et;

drop table region;
create table region(
  r_regionkey    ,
  r_name         ,
  r_comment      )
tablespace ts_default
as select * from r_et;

drop table l_et;
drop table o_et;
drop table ps_et;
drop table p_et;
drop table c_et;
drop table s_et;
drop table n_et;
drop table r_et;
!

echo DONE TABLE CREATION at `date`


B.4 ixcre.sh
#!/bin/ksh

echo START INDEX at `date`
export ORACLE_SID=tpch

sqlplus tpch/tpch <<!
set echo on
set timing on
set termout on

drop index i_l_orderkey;
create index i_l_orderkey
on lineitem (l_orderkey)
global partition by hash (l_orderkey)
partitions 128
pctfree 10
initrans 10
tablespace ts_lokey
storage (freelist groups 4 freelists 99)
parallel
compute statistics

```

```

nologging;

drop index i_o_orderkey;
create unique index i_o_orderkey
on orders (o_orderkey)
global partition by hash (o_orderkey)
partitions 128
pctfree 10
initrans 10
tablespace ts_okey
storage (freelist groups 4 freelists 99 )
parallel
compute statistics
nologging;

drop index i_c_custkey;
create unique index i_c_custkey
on customer (c_custkey)
pctfree 2
initrans 10
tablespace ts_custkey
storage (freelists 99)
parallel
compute statistics
nologging;

drop index i_ps_pkey_skey;
create index i_ps_pkey_skey
on partsupp (ps_partkey,ps_suppkey)
global partition by hash (ps_partkey)
partitions 128
pctfree 5
initrans 10
tablespace ts_lokey
storage (freelist groups 4 freelists 99)
parallel
compute statistics
nologging;
!

echo DONE INDEX at `date`


B.5 anl.sh
#!/bin/ksh

echo START ANALYZE at `date`
export ORACLE_SID=tpch;

sqlplus tpch/tpch <<!
set timing on
set echo on
set termout on

execute dbms_stats.gather_schema_stats('TPCH', estimate_percent =>
1, degree => 64, granularity => 'GLOBAL', method_opt => 'for all
columns size 1');
connect / as sysdba
execute dbms_stats.gather_system_stats;
exec dbms_scheduler.disable('GATHER_STATS_JOB');
alter system switch logfile;
!

/dbms/oracle10i/frame/bin/tshut
/dbms/oracle10i/frame/bin/tshut.asm

/dbms/oracle10i/frame/bin/tstart.asm
/dbms/oracle10i/frame/bin/tstart

echo END ANALYZE at `date`


B.6 loadasm
#!/bin/ksh

echo START LOADASM at `date`
export ORACLE_SID=ASM

sqlplus /NOLOG <<!
connect / as sysdba;
shutdown abort;
startup pfile=/oracle/dbs/initasm.ora ;
alter diskgroup all mount;
drop diskgroup dg1 including contents;
create diskgroup dg1 External REDUNDANCY
DISK
'/dbms/links/roradsk1' SIZE 450000M,
'/dbms/links/roradsk2' SIZE 450000M,
'/dbms/links/roradsk3' SIZE 450000M,
'/dbms/links/roradsk4' SIZE 450000M,
'/dbms/links/roradsk5' SIZE 450000M,
'/dbms/links/roradsk6' SIZE 450000M,
'/dbms/links/roradsk7' SIZE 450000M,
'/dbms/links/roradsk8' SIZE 450000M,
'/dbms/links/roradsk9' SIZE 450000M,
'/dbms/links/roradsk10' SIZE 450000M,
'/dbms/links/roradsk11' SIZE 450000M,
'/dbms/links/roradsk12' SIZE 450000M,
'/dbms/links/roradsk13' SIZE 450000M,
'/dbms/links/roradsk14' SIZE 450000M,
'/dbms/links/roradsk15' SIZE 450000M,
'/dbms/links/roradsk16' SIZE 450000M,
'/dbms/links/roradsk17' SIZE 450000M,
'/dbms/links/roradsk18' SIZE 450000M,
'/dbms/links/roradsk19' SIZE 450000M,
'/dbms/links/roradsk20' SIZE 450000M,
'/dbms/links/roradsk21' SIZE 450000M,
'/dbms/links/roradsk22' SIZE 450000M,
'/dbms/links/roradsk23' SIZE 450000M,
'/dbms/links/roradsk24' SIZE 450000M,
'/dbms/links/roradsk25' SIZE 450000M,
'/dbms/links/roradsk26' SIZE 450000M,
'/dbms/links/roradsk27' SIZE 450000M,
'/dbms/links/roradsk28' SIZE 450000M,
'/dbms/links/roradsk29' SIZE 450000M,
'/dbms/links/roradsk30' SIZE 450000M,
'/dbms/links/roradsk31' SIZE 450000M,
'/dbms/links/roradsk32' SIZE 450000M,
'/dbms/links/roradsk33' SIZE 450000M,
'/dbms/links/roradsk34' SIZE 450000M,
'/dbms/links/roradsk35' SIZE 450000M,
'/dbms/links/roradsk36' SIZE 450000M,
'/dbms/links/roradsk37' SIZE 450000M,
'/dbms/links/roradsk38' SIZE 450000M,
'/dbms/links/roradsk39' SIZE 450000M,
'/dbms/links/roradsk40' SIZE 450000M,
'/dbms/links/roradsk41' SIZE 450000M,
'/dbms/links/roradsk42' SIZE 450000M,
'/dbms/links/roradsk43' SIZE 450000M,
'/dbms/links/roradsk44' SIZE 450000M,
'/dbms/links/roradsk45' SIZE 450000M,
'/dbms/links/roradsk46' SIZE 450000M,

```



```

'./dbms/links/roradsk189' SIZE 450000M,
'./dbms/links/roradsk190' SIZE 450000M,
'./dbms/links/roradsk191' SIZE 450000M,
'./dbms/links/roradsk192' SIZE 450000M,
'./dbms/links/roradsk193' SIZE 450000M,
'./dbms/links/roradsk194' SIZE 450000M,
'./dbms/links/roradsk195' SIZE 450000M,
'./dbms/links/roradsk196' SIZE 450000M,
'./dbms/links/roradsk197' SIZE 450000M,
'./dbms/links/roradsk198' SIZE 450000M,
'./dbms/links/roradsk199' SIZE 450000M,
'./dbms/links/roradsk200' SIZE 450000M,
'./dbms/links/roradsk201' SIZE 450000M,
'./dbms/links/roradsk202' SIZE 450000M,
'./dbms/links/roradsk203' SIZE 450000M,
'./dbms/links/roradsk204' SIZE 450000M,
'./dbms/links/roradsk205' SIZE 450000M,
'./dbms/links/roradsk206' SIZE 450000M,
'./dbms/links/roradsk207' SIZE 450000M,
'./dbms/links/roradsk208' SIZE 450000M,
'./dbms/links/roradsk209' SIZE 450000M,
'./dbms/links/roradsk210' SIZE 450000M,
'./dbms/links/roradsk211' SIZE 450000M,
'./dbms/links/roradsk212' SIZE 450000M,
'./dbms/links/roradsk213' SIZE 450000M,
'./dbms/links/roradsk214' SIZE 450000M,
'./dbms/links/roradsk215' SIZE 450000M,
'./dbms/links/roradsk216' SIZE 450000M,
'./dbms/links/roradsk217' SIZE 450000M,
'./dbms/links/roradsk218' SIZE 450000M,
'./dbms/links/roradsk219' SIZE 450000M,
'./dbms/links/roradsk220' SIZE 450000M,
'./dbms/links/roradsk221' SIZE 450000M,
'./dbms/links/roradsk222' SIZE 450000M,
'./dbms/links/roradsk223' SIZE 450000M,
'./dbms/links/roradsk224' SIZE 450000M,
'./dbms/links/roradsk225' SIZE 450000M,
'./dbms/links/roradsk226' SIZE 450000M,
'./dbms/links/roradsk227' SIZE 450000M,
'./dbms/links/roradsk228' SIZE 450000M,
'./dbms/links/roradsk229' SIZE 450000M,
'./dbms/links/roradsk230' SIZE 450000M,
'./dbms/links/roradsk231' SIZE 450000M,
'./dbms/links/roradsk232' SIZE 450000M,
'./dbms/links/roradsk233' SIZE 450000M,
'./dbms/links/roradsk234' SIZE 450000M,
'./dbms/links/roradsk235' SIZE 450000M,
'./dbms/links/roradsk236' SIZE 450000M,
'./dbms/links/roradsk237' SIZE 450000M,
'./dbms/links/roradsk238' SIZE 450000M,
'./dbms/links/roradsk239' SIZE 450000M,
'./dbms/links/roradsk240' SIZE 450000M,
'./dbms/links/roradsk241' SIZE 450000M,
'./dbms/links/roradsk242' SIZE 450000M,
'./dbms/links/roradsk243' SIZE 450000M,
'./dbms/links/roradsk244' SIZE 450000M,
'./dbms/links/roradsk245' SIZE 450000M,
'./dbms/links/roradsk246' SIZE 450000M,
'./dbms/links/roradsk247' SIZE 450000M,
'./dbms/links/roradsk248' SIZE 450000M,
'./dbms/links/roradsk249' SIZE 450000M,
'./dbms/links/roradsk250' SIZE 450000M,
'./dbms/links/roradsk251' SIZE 450000M,
'./dbms/links/roradsk252' SIZE 450000M,
'./dbms/links/roradsk253' SIZE 450000M,
'./dbms/links/roradsk254' SIZE 450000M,
'./dbms/links/roradsk255' SIZE 450000M,
'./dbms/links/roradsk256' SIZE 450000M;
alter diskgroup dg1 rebalance power 0;
!

sqlplus /NOLOG <<!
connect / as sysdba;
shutdown normal;
!

export ORACLE_SID=ASM
sqlplus /NOLOG <<!
connect / as sysdba
startup pfile=/oracle/dbs/initasm.ora mount
!
echo END LOADASM at `date`
```

C.1 Acid Scripts

C.1 a_query.sql

```
Rem
Rem $Header: a_query.sql 06-aug-99.10:51:10 mpoess Exp $
Rem
Rem a_query.sql
Rem
Rem Copyright (c) Oracle Corporation 1999. All Rights Reserved.
Rem
Rem NAME
Rem a_query.sql - <one-line expansion of the name>
Rem
rem DESCRIPTION
Rem Performs ACID Query for TPC-D benchmark.
Rem Asks user to input values for o_key
Rem The range of okey is 1 to 600000
Rem
=====
=====
Rem
Rem Usage: sqlplus tpcd/tpcd @a_query <o_key>
Rem
Rem
Rem MODIFIED (MM/DD/YY)
Rem mpoess 08/06/99 - Creation
Rem mpoess 08/06/99 - Created
Rem

set serverout on;

select
'BEFORE ACID QUERY' as STAGE,
substr(TO_CHAR(sysdate,'YYYY-MM-DD HH:MI:SS'),1,20) as
CURRENT_TIME
from dual;

select SUM(trunc(trunc(l_extendedprice * (1-l_discount),2) *
(1+l_tax),2)) AS RESULT
from lineitem
where l_orderkey = &&1;

select
'AFTER ACID QUERY' as STAGE,
substr(TO_CHAR(sysdate,'YYYY-MM-DD HH:MI:SS'),1,20) as
CURRENT_TIME
from dual;

exit;
```

C.2 a_query2.sql

```
Rem
Rem $Header: aquery2.sql 07-aug-99.23:54:47 mpoess Exp $
Rem
Rem aquery2.sql
Rem
Rem Copyright (c) Oracle Corporation 1999. All Rights Reserved.
Rem
Rem NAME
Rem aquery2.sql - <one-line expansion of the name>
Rem
Rem DESCRIPTION
Rem Performs query on PARTSUPP for TPC-D benchmark
Rem Isolation Test 5.
```

```
Rem Asks user to input values for ps_partkey and ps_suppkey
Rem The range for ps_partkey is 1 to 20000
Rem The range for ps_suppkey is 1 to 1000
Rem A valid combination is 46 and 47
Rem Usage: sqlplus tpcd/tpcd @a_query2 <ps_partkey>
<ps_suppkey>
Rem
Rem MODIFIED (MM/DD/YY)
Rem mpoess 08/07/99 - Creation
Rem mpoess 08/07/99 - Created
Rem
rem DESCRIPTION
rem Performs query on PARTSUPP for TPC-D benchmark
rem Isolation Test 5.
rem Asks user to input values for ps_partkey and ps_suppkey
rem The range for ps_partkey is 1 to 20000
rem The range for ps_suppkey is 1 to 1000
rem A valid combination is 46 and 47

set serverout on;

select
'BEFORE PARTSUPP QUERY' as STAGE,
substr(TO_CHAR(sysdate,'YYYY-MM-DD HH:MI:SS'),1,20) as
CURRENT_TIME
from dual;

select *
from partsupp
where ps_partkey = &&1
and ps_suppkey = &&2;

select
'AFTER PARTSUPP QUERY' as STAGE,
substr(TO_CHAR(sysdate,'YYYY-MM-DD HH:MI:SS'),1,20) as
CURRENT_TIME
from dual;

exit;
```

C.3 atom.sh

```
#!/bin/ksh
#
# $Header: atom.sh 08-aug-99.13:48:02 mpoess Exp $
#
# atom.sh
#
# Copyright (c) Oracle Corporation 1999. All Rights Reserved.
#
# NAME
# atom.sh - <one-line expansion of the name>
#
# DESCRIPTION
# Performs atomicity tests.
# Usage: atom.sh [-n iter] [-p prog] [-u usr/pswd] -h
#
# Options: See usage below
#
# NOTES
# <other useful comments, qualifications, etc.>
#
# MODIFIED (MM/DD/YY)
# mpoess 08/08/99 - Creation
# mpoess 08/08/99 - Creation
#
. $KIT_DIR/env
```

```

OH=$ORACLE_HOME
# ACID_DIR=$TPCD_KIT_DIR/audit set in env
OUT_DIR=$ACID_OUT
DURA_DIR=$ACID_DIR/dura

usage() {
    echo ""
    echo "Usage: $0 [-n iter] [-p prog] [-u usr/pwd] -h"
    echo ""
    echo "-n iter : number of iterations, default is 100"
    echo "-p prog : program to run, default is atranspl.ott"
    echo "-u usr/pwd : user/password combo for database access, default
is tpcd/tpcd"
    echo "-h      : print this usage summary"
    exit 1;
}

ITER=3
SF=1
PROG=$KIT_DIR/utils/atranspl
OUT=${OUT_DIR}/atom
USER=${DATABASE_USER}

set -- ` getopt "n:p:u:h" "$@"` || usage

while :
do
    case "$1" in
        -n) shift; ITER=$1;;
        -p) shift; PROG=$1;;
        -u) shift; USER=$1;;
        -h) usage; exit 0;;
        --) break;;
        esac
        shift
done

echo "Starting Atomicity Test at `date`..."
echo ""
echo "Performing $ITER ACID transactions with COMMIT"
echo ""

$KIT_DIR/utils/randkey $ITER $SF u$USER | $PROG 1 1 1 0 u$USER
> ${OUT}c 2>&1

echo "ACID transactions with COMMIT ended. Output in ${OUT}c"
echo ""
echo "Performing $ITER ACID transactions with ROLLBACK"
echo ""

$KIT_DIR/utils/randkey $ITER $SF u$USER | $PROG 1 1 0 0 u$USER
> ${OUT}r 2>&1

echo "ACID transactions with ROLLBACK ended. Output in ${OUT}r"
echo ""
echo "Ending Atomicity Test at `date`..."

```

C.4 atrans.sql

```

Rem
Rem $Header: atrans.sql 07-aug-99.21:27:13 mpoess Exp $
Rem
Rem atrans.sql
Rem
Rem Copyright (c) Oracle Corporation 1999. All Rights Reserved.
Rem
Rem NAME
Rem atrans.sql - <one-line expansion of the name>

```

```

Rem
Rem DESCRIPTION
Rem     Creates ACID Transaction Package for TPC-D benchmark.
Rem     Asks user to input values for o_key, delta and output file.
Rem
Rem NOTES
Rem     <other useful comments, qualifications, etc.>
Rem
Rem MODIFIED (MM/DD/YY)
Rem mpoess 08/07/99 - Creation
Rem mpoess 08/07/99 - Created
Rem

set serverout on;
set termout on;
set echo on;

CREATE OR REPLACE PACKAGE d_atrans
IS
PROCEDURE doatrans
(
    l_key          IN OUT integer,
    o_key          IN OUT integer,
    delta          IN OUT integer,
    l_pkey         IN OUT integer,
    l_skey         IN OUT integer,
    l_quan         IN OUT integer,
    l_newquan     IN OUT integer,
    l_tax          IN OUT number,
    l_disc         IN OUT number,
    l_eprice       IN OUT number,
    l_neweprice   IN OUT number,
    o_tprice       IN OUT number,
    o_newtprice   IN OUT number,
    rprice         IN OUT number,
    cost           IN OUT number
);
END;
/

CREATE OR REPLACE PACKAGE BODY d_atrans
IS
PROCEDURE doatrans
(
    l_key          IN OUT integer,
    o_key          IN OUT integer,
    delta          IN OUT integer,
    l_pkey         IN OUT integer,
    l_skey         IN OUT integer,
    l_quan         IN OUT integer,
    l_newquan     IN OUT integer,
    l_tax          IN OUT number,
    l_disc         IN OUT number,
    l_eprice       IN OUT number,
    l_neweprice   IN OUT number,
    o_tprice       IN OUT number,
    o_newtprice   IN OUT number,
    rprice         IN OUT number,
    cost           IN OUT number
)
IS
    ototal number;
    not_serializable EXCEPTION;
    PRAGMA EXCEPTION_INIT(not_serializable,-8177);
BEGIN
    -- EXECUTE IMMEDIATE 'ALTER SESSION SET
    ISOLATION_LEVEL = SERIALIZABLE';
    LOOP BEGIN
        select o_totalprice

```

```

into o_tprice
from orders
where o_orderkey = o_key;

select l_quantity, l_extendedprice, l_partkey, l_suppkey, l_tax,
l_discount
into l_quan, l_eprice, l_pkey, l_skey, l_tax, l_disc
from lineitem
where l_orderkey = o_key
and l_linenumber = l_key;

ototal := o_tprice - trunc((trunc(l_eprice * (1.0-l_disc)),2) *
(1.0+l_tax)),2);
rprice := trunc((l_eprice/l_quan), 2);
cost := trunc((rprice * delta), 2);
l_neweprice := l_eprice + cost;
o_newtprice := trunc((l_neweprice * (1.0 - l_disc)), 2);
o_newtprice := ototal + trunc((o_newtprice * (1.0 + l_tax)), 2);
l_newquan := l_quan + delta;

update lineitem
set l_extendedprice = l_neweprice,
l_quantity = l_newquan
where l_orderkey = o_key
and l_linenumber = l_key;

update orders
set o_totalprice = o_newtprice
where o_orderkey = o_key;

insert into history (h_p_key, h_s_key, h_o_key, h_l_key, h_delta,
h_date_t)
values (l_pkey, l_skey, o_key, l_key, delta, sysdate);

-- dbms_lock.sleep(30);
-- commit;
EXIT;

EXCEPTION
WHEN not_serializable THEN
ROLLBACK;
END;

END LOOP;

END doatrans;
END;
/
exit;

/* Copyright (c) 2001, 2002, Oracle Corporation. All rights reserved. */

/*
NAME
atranspl.c - <one-line expansion of the name>

DESCRIPTION
TPC-HR benchmark ACID transaction driver, OCI version 8

NOTES
<other useful comments, qualifications, etc.>

MODIFIED (MM/DD/YY)
mpoess 10/23/02 - mpoess_update_from_visa

mpoess 10/17/01 - add parameter in ACIDinit
mpoess 02/22/01 - enlarge timing array
mpoess 01/04/01 - Creation

*/
#include <stdio.h>
#include <stdlib.h>
#include <sys/types.h>
#include <sys/stat.h>
#include <fcntl.h>
#include "atranspl.h"

/* Declare error handling functions */

double gettime();
void sql_error();
void usage();
void ACIDinit();
void ACIDexit();
int atoi();
void srand48();
long lrand48();

/* declarations for ORDERS */

int o_key = 0;
double o_tprice = 0.0;
double o_newtprice = 0.0;

/* declarations for LINEITEM */

int l_key = 0;
int l_pkey = 0;
int l_skey = 0;

int l_quan = 0;
int l_newquan = 0;
double l_eprice = 0.0;
double l_neweprice = 0.0;
double l_disc = 0.0;
double l_tax = 0.0;

sb2 l_npricei;

/* other declarations */

int delta = 0;
double rprice;
double cost;

int proc_no = 1; /* process number, global */
int num_streams = 1; /* number of transaction streams */
int trig = 0; /* Trigger Time */
int slp = 0; /* Sleep Time */

int logfile; /* fdes for logfile for durability (optional) */
int outfile = 1; /* output file (optional) */
#ifndef LINUX
FILE *infile; /* input file (optional) */
#else
FILE *infile = stdin; /* input file (optional) */
/* in the format of <o_key> <delta> */
#endif
char lname[UNAME_LEN]; /* username/passwd combo */
char *passwd; /* pointer to password */
char buf[WRITE_BUF_LEN]; /* buffer to write */
unsigned flag = (unsigned) 0; /* flag to store all sorts of options */

```

C.5 atranspl.c

/* Copyright (c) 2001, 2002, Oracle Corporation. All rights reserved. */

/*

NAME

atranspl.c - <one-line expansion of the name>

DESCRIPTION

TPC-HR benchmark ACID transaction driver, OCI version 8

NOTES

<other useful comments, qualifications, etc.>

MODIFIED (MM/DD/YY)

mpoess 10/23/02 - mpoess_update_from_visa

```

#define INFILE 0x01u
#define OUTFILE 0x02u
#define LOGFILE 0x04u
#define COMMIT 0x08u
#define DELTA 0x10u

double tr_end = 0.0; /* transaction end time */ 
double tr_start = 0.0; /* transaction start time */ 

int num_iter = 0; /* number of iterations */ 
time_t curr_time; /* Current Time */ 

/* OCI handles */

OCIEnv *tpcenv = NULL;
OCIServer *tpcsrv = NULL;
OCIError *errhp = NULL;
OCISvcCtx *tpcsvc = NULL;
OCISession *tpcusr = NULL;
OCISql *curi = NULL;
OCISql *curr = NULL;
OCISql *cure1 = NULL;
OCISql *cure2 = NULL;

/* OCI bind handles */

#ifndef NOLKEY
OCIBind *l_key_bp = NULL;
OCIBind *o_key_bp = NULL;
#endif /* NOLKEY */

OCIBind *l_key_bp = NULL;
OCIBind *o_key_bp = NULL;
OCIBind *delta_bp = NULL;
OCIBind *l_pkey_bp = NULL;
OCIBind *l_skey_bp = NULL;
OCIBind *l_quan_bp = NULL;
OCIBind *l_newquan_bp = NULL;
OCIBind *l_tax_bp = NULL;
OCIBind *l_disc_bp = NULL;
OCIBind *l_eprice_bp = NULL;
OCIBind *l_neweprice_bp = NULL;
OCIBind *o_tprice_bp = NULL;
OCIBind *o_newtprice_bp = NULL;
OCIBind *rprice_bp = NULL;
OCIBind *cost_bp = NULL;

OCIBind *l_neweprice1_bp = NULL;
OCIBind *l_newquan1_bp = NULL;
OCIBind *o_key1_bp = NULL;
OCIBind *l_key1_bp = NULL;

OCIBind *o_newtprice2_bp = NULL;
OCIBind *o_key2_bp = NULL;

sword status = OCI_SUCCESS; /* OCI return value */

char sqlstmt[1024];

/* usage: prints the usage of the program */

void usage()
{
    fprintf(stderr, "\nUsage: atrans.o[st]t <proc_no> <num_streams>\n<commit> <delta>\n[i<pathname for input>] [o<pathname for output>]\n[d<pathname for durability file>] [u<uid/passwd>] \n\n");
    fprintf(stderr, " proc_no :the process number within this ACID\n");
}

printf(stderr, " num_streams :the total number of ACID transaction streams\n");
printf(stderr, " commit :1 to commit transaction, abort otherwise\n");
printf(stderr, " delta :1 to generate new random delta, otherwise obtain delta from input\n");
printf(stderr, " OPTIONAL PARAMETERS:\n");
printf(stderr, " i<pathname for input> :full path name for input file - default is stdin\n");
printf(stderr, " o<pathname for output> :full path name for output file - default is stdout\n");
printf(stderr, " d<pathname for durability> :full path name for durability success file - must specify for durability test\n");
printf(stderr, " u<uid/passwd> :Username/Password string - default is tcpd/tcpd\n");
printf(stderr, " t<trigger> :Trigger Time - sleep <trigger> seconds before start\n");
printf(stderr, " s<sleep> :Sleep Time - sleep <sleep> seconds before commit or rollback\n");
exit(-1);
}

void ACIDexit()
{
    OCILogoff(tpcsvc,errhp);
    OCIhfree(tpcenv,OCI_HTYPE_STMT);
    OCIhfree(tpcsvc,OCI_HTYPE_SVCCTX);
    OCIhfree(tpcsrv,OCI_HTYPE_SERVER);
    OCIhfree(tpcusr,OCI_HTYPE_SESSION);
}

/* type: 0 if environment handle is passed, 1 if error handle is passwd */

void sql_error(errhp,status,type)
    OCIError *errhp;
    sword status;
    sword type;
{
    char msg[2048];
    ub4 errcode;
    ub4 msglen;
    int i,j;

    switch(status) {
    case OCI_SUCCESS_WITH_INFO:
        fprintf(stderr, "Error: Statement returned with info.\n");
        if (type)
            (void) OCIErrorGet(errhp,1,NULL,(sb4*)&errcode, (text*) msg,
                2048, OCI_HTYPE_ERROR);
        else
            (void) OCIErrorGet(errhp,1,NULL,(sb4*)&errcode, (text*) msg,
                2048, OCI_HTYPE_ENV);
        fprintf(stderr,"%s\n",msg);
        break;
    case OCI_ERROR:
        fprintf(stderr, "Error: OCI call error.\n");
        if (type)
            (void) OCIErrorGet(errhp,1,NULL, (sb4 *) &errcode, (text*) msg,
                2048, OCI_HTYPE_ERROR);
        else
            (void) OCIErrorGet(errhp,1,NULL, (sb4 *) &errcode, (text*) msg,
                2048, OCI_HTYPE_ENV);
        fprintf(stderr,"%s\n",msg);
        break;
    case OCI_INVALID_HANDLE:
        fprintf(stderr, "Error: Invalid Handle.\n");
    }
}

```

```

if (type)
    (void) OCIErrorGet(errhp,1,NULL, (sb4 *) &errcode, (text*) msg,
                      2048,OCI_HTYPE_ERROR);
else
    (void) OCIErrorGet(errhp,1,NULL, (sb4 *) &errcode, (text*) msg,
                      2048,OCI_HTYPE_ENV);
fprintf(stderr,"%s\n",msg);
break;
}
/* Rollback just in case */

(void) OCITransRollback(tpcsvc,errhp,OCI_DEFAULT);

fprintf(stderr, "Exiting Oracle...\n");
fflush(stderr);

ACIDexit();

exit(1);
}

#endif LINUX
int main(argc,argv)
#else
void main(argc,argv)
#endif
{
    int argc;
    char *argv[];

int i;
char line[64];
ub4 errcode;
char msg[2048];
int need_commit = 0;

/* Initialize some variables */
#ifndef LINUX
infile=fopen("/dev/stdin","r");
#endif
strcpy((char *) lname, "tpcd/tpcd");

if ((argc > 10) || (argc < 5)) {
    usage();
}

/* argv[1] -- Process Number */
proc_no = atoi(argv[1]);

/* argv[2] -- Number of Streams */
num_streams = atoi(argv[2]);

/* argv[3] -- Commit? */
if (atoi(argv[3]) == 1)
    BIS(flag, COMMIT);

/* argv[4] -- Delta? */
if (atoi(argv[4]) == 1)
    BIS(flag, DELTA);

/* Process optional parameters */

argc -= 4;
argv += 4;

while(--argc) {
    ++argv;

switch(argv[0][0]) {
case 'u':
    strncpy((char *) lname, ++(argv[0]), UNAME_LEN);
    if (strchr((char *) lname, '/') == NULL) {
        fprintf(stderr, "Login name must be in the format of
user@passwd\n");
        usage();
        exit(-1);
    }
    break;
case 'i':
    if ((infile = fopen(++(argv[0]), "r")) == NULL) {
        fprintf(stderr,"Cannot open input file %s\n", argv[0]);
        fprintf(stderr,"%s\n",strerror(errno));
        exit(-1);
    }
    BIS(flag, INFILE);
    break;
case 'o':
    if ((outfile = open(++(argv[0]), (O_RDWR | O_SYNC | O_CREAT),
S_IRWXU)) == -1) {
        fprintf(stderr,"Cannot open output file %s\n", argv[0]);
        fprintf(stderr,"%s\n",strerror(errno));
        exit(-1);
    }
    BIS(flag, OUTFILE);
    break;
case 'd':
    if ((logfile = open(++(argv[0]), (O_RDWR | O_SYNC | O_CREAT),
S_IRWXU)) == -1) {
        fprintf(stderr,"Cannot open durability success file %s\n",
argv[0]);
        fprintf(stderr,"%s\n",strerror(errno));
        exit(-1);
    }
    BIS(flag, LOGFILE);
    break;
case 'b':
    num_iter = atoi(++(argv[0]));
    break;
case 't':
    trig = atoi(++(argv[0]));
    break;
case 's':
    slp = atoi(++(argv[0]));
    break;
default:
    fprintf(stderr, "Unknown argument %s\n", argv[0]);
    usage();
    break;
}

FPRTF(outfile,"-----\n");

/* Initialize the cursors etc. */

(void) ACIDinit();

/* sleep for some time (triggering) */

sleep(trig);

/* start doing the ACID transactions */

tr_start = gettime();

/* The number of iteration we will run depends on the number of */
/* input lines */

while (fgets(line, 64, infile) != NULL) {

```

```

#endif NOLKEY
sscanf(line, "%d %d\n", &o_key, &delta);

/* Obtain l_key from l_key query */

OCIexec(tpcsvc,curi,errhp,1);

/* l_key is the highest l_linenumber available. We need to pick */
/* at random a number between 1..l_key. */

l_key = (int) ((lrand48() % l_key) + 1);
#else
sscanf(line, "%d %d %d\n", &o_key, &l_key, &delta);
#endif /* NOLKEY */

/* Generate delta if necessary */

if (BIT(flag, DELTA))
    delta = (int) (floor((drand48() * 100)) + 1);

/* Now, we are ready to run the ACID transaction. */

curr_time = time(NULL);

FPRTF2(outfile, "Starting ACID transaction %d at %s...\n",
(++num_iter),
ctime(&curr_time));

FPRTF1(outfile, "o_key: %d\n", (int) o_key);
FPRTF1(outfile, "l_key: %d\n", (int) l_key);
FPRTF1(outfile, "delta: %d\n", (int) delta);

OCIexec(tpcsvc,curr,errhp,1);

curr_time = time(NULL);

if (!BIT(flag, LOGFILE)) {
    FPRTF1(outfile, "BEFORE COMMIT/ROLLBACK
TRANSACTION at %s\n", ctime(&curr_time));
    FPRTF1(outfile, "l_extendedprice: %.2f\n", l_eprice);
    FPRTF1(outfile, "l_quantity:   %d\n", (int) l_quan);
    FPRTF1(outfile, "o_totalprice:  %.2f\n", o_tprice);
}

FPRTF1(outfile, "Sleep %d seconds before
COMMIT/ROLLBACK...\n\n", slp);
sleep(slp);

/* Shall we commit? */

if (BIT(flag, COMMIT)) {
    need_commit = 1;
    while (need_commit) {
        if((status=OCITransCommit(tpcsvc,errhp,OCI_DEFAULT)) !=
        OCI_SUCCESS) {
            OCIrol(tpcsvc,errhp);
            OCIexec(tpcsvc,curr,errhp,1);
        } else {
            need_commit = 0;
            curr_time = time(NULL);
            FPRTF2(outfile, "ACID Transaction iteration %d COMMITTED
at %s\n",
                num_iter, ctime(&curr_time));
        }
    }
} else {
    OCIrol(tpcsvc,errhp);
    curr_time = time(NULL);
    FPRTF2(outfile, "ACID Transaction iteration %d ROLLBACK at
%s\n",
        num_iter, ctime(&curr_time));
}
}

}

/* Report all results to outfile and if necessary, to success file. */

/* Report initial and new values for o_totalprice, l_extendedprice, */
/* l_quantity. */

/*
curr_time = time(NULL);
FPRTF1(outfile, "Transaction Completed at %s\n",
ctime(&curr_time));
*/
}

/* Get the values in LINEITEM and ORDERS after the transaction */

if (BIT(flag, LOGFILE)) {
    FPRTF1(logfile, "p_key:   %d\n", (int) l_pkey);
    FPRTF1(logfile, "s_key:   %d\n", (int) l_skey);
    FPRTF1(logfile, "o_key:   %d\n", (int) o_key);
    FPRTF1(logfile, "l_key:   %d\n", (int) l_key);
    FPRTF1(logfile, "delta:  %d\n", (int) delta);
    FPRTF1(logfile, "Transaction Completed at %s\n",
ctime(&curr_time));
    FPRTF(logfile, "-----\n");
} else {
    OCIexec(tpcsvc,cure1,errhp,1);
    OCIexec(tpcsvc,cure2,errhp,1);

    FPRTF(outfile, "AFTER TRANSACTION:\n");
    FPRTF1(outfile, "l_extendedprice: %.2lf\n", l_neweprice);
    FPRTF1(outfile, "l_quantity:   %d\n", (int) l_newquan);
    FPRTF1(outfile, "o_totalprice:  %.2lf\n", o_newtprice);
    FPRTF1(outfile, "l_tax:      %.2lf\n", l_tax);
    FPRTF1(outfile, "l_discount:  %.2lf\n", l_disc);
    FPRTF1(outfile, "rprice:     %.2lf\n", rprice);
    FPRTF1(outfile, "cost:       %.2lf\n", cost);
    FPRTF(outfile, "-----\n");
}

tr_end = gettime();

if (!BIT(flag, LOGFILE)) {
    FPRTF1(outfile, "Start Time: %.2f\n", tr_start);
    FPRTF1(outfile, "End Time: %.2f\n", tr_end);
    FPRTF1(outfile, "Elapsed Time: %.2f\n", (tr_end - tr_start));
    FPRTF1(outfile, "Transaction Count: %d\n", num_iter);
    FPRTF1(outfile, "Transaction Rate: %.2f\n", num_iter/(tr_end -
tr_start));
} else {
    FPRTF1(logfile, "Start Time: %.2f\n", tr_start);
    FPRTF1(logfile, "End Time: %.2f\n", tr_end);
    FPRTF1(logfile, "Elapsed Time: %.2f\n", (tr_end - tr_start));
    FPRTF1(logfile, "Transaction Count: %d\n", num_iter);
}

/* Disconnect from ORACLE. */

if (BIT(flag, INFIL))
    fclose(infile);
if (BIT(flag, OUTFILE))
    close(outfile);
if (BIT(flag, LOGFILE))
    close(logfile);

ACIDexit();

exit(0);
}

```

```

void ACIDinit()
{
/* run random seed */

    srand48(getpid());

/* Connect to ORACLE. Program will call sql_error()
   if an error occurs in connecting to the default database. */

    (void) OCIInitialize(OCI_DEFAULT,(dvoid *)0,0,0);
    if((status=OCIEnvInit((OCIEnv **)&tpcenv,OCI_DEFAULT,0,(dvoid
    ***)0)) !=

        OCI_SUCCESS)
        sql_error(tpcenv, status, 0);

    OCIalloc(tpcenv,&errhp,OCI_HTYPE_ERROR);
    OCIalloc(tpcenv,&curi,OCI_HTYPE_STMT);
    OCIalloc(tpcenv,&curr,OCI_HTYPE_STMT);
    OCIalloc(tpcenv,&curr1,OCI_HTYPE_STMT);
    OCIalloc(tpcenv,&curr2,OCI_HTYPE_STMT);
    OCIalloc(tpcenv,&tpcsvc,OCI_HTYPE_SVCCTX);
    OCIalloc(tpcenv,&tpcsrv,OCI_HTYPE_SERVER);
    OCIalloc(tpcenv,&tpcusr,OCI_HTYPE_SESSION);

/* Disables auto commit */
/*
if (ocof(&tpclda))
    sql_error(&tpclda, &tpclda);
ologof(&tpclda);
exit(-1);
*/
/* get username and password */

passwd = strchr(lname, '/');
*passwd = '\0';
passwd++;

if ((status = OCIServerAttach(tpcsrv,errhp,(text
*)0,OCI_DEFAULT)) != OCI_SUCCESS)
    sql_error(errhp,status,1);

OCIaset(tpcsvc,OCI_HTYPE_SVCCTX,tpcsrv,0,OCI_ATTR_SERVER
,errhp);

OCIaset(tpcusr,OCI_HTYPE_SESSION,lname,strlen(lname),OCI_ATT
R_USERNAME,
errhp);

OCIaset(tpcusr,OCI_HTYPE_SESSION,passwd,strlen(passwd),OCI_A
TTR_PASSWORD,
errhp);

if ((status = OCISessionBegin(tpcsvc, errhp, tpcusr,
OCI_CRED_RDBMS,
        OCI_DEFAULT)) != OCI_SUCCESS)
    sql_error(errhp,status,1);

OCIaset(tpcsvc,OCI_HTYPE_SVCCTX,tpcusr,0,OCI_ATTR_SESSIO
N,errhp);

/* Enable session parallel dml */

sprintf((char *) sqlstmt, PDMLTXT);
OCIStmtPrepare(curi,errhp,(text *)sqlstmt,strlen((char *)sqlstmt),
        OCI_NTV_SYNTAX,OCI_DEFAULT);

```

```

    OCIexec(tpcsvc,curi,errhp,1);

/* Enable session parallel ddl */

/*sprintf((char *) sqlstmt, PDDLTXT);
OCIStmtPrepare(curi,errhp,(text *)sqlstmt,strlen((char *)sqlstmt),
        OCI_NTV_SYNTAX,OCI_DEFAULT);
OCIexec(tpcsvc,curi,errhp,1);*/

/* Make session serializable */

sprintf ((char *) sqlstmt, ISOTXT);
OCIStmtPrepare(curi,errhp,(text *)sqlstmt,strlen((char *)sqlstmt),
        OCI_NTV_SYNTAX,OCI_DEFAULT);
OCIexec(tpcsvc,curi,errhp,1);

/* Set optimizer_index_cost_adj = 25 */

sprintf ((char *) sqlstmt, OICATXT);
OCIStmtPrepare(curi,errhp,(text *)sqlstmt,strlen((char *)sqlstmt),
        OCI_NTV_SYNTAX,OCI_DEFAULT);
OCIexec(tpcsvc,curi,errhp,1);

curr_time = time(NULL);
printf("\nConnected to ORACLE as user: %s at %s\n\n", lname,
ctime(&curr_time));

#endif NOLKEY
/* Open and Parse cursor for query to choose determine l_key. */
/* Binds l_key to :l_key. */

sprintf((char *) sqlstmt,SQLTXT1);
OCIStmtPrepare(curi,errhp,sqlstmt,strlen((char
*)sqlstmt),OCI_NTV_SYNTAX,OCI_DEFAULT);

OCIBbname(curi,&l_keyi_bp,errhp,:l_key",ADR(l_key),SIZ(l_key),SQ
LT_INT);

OCIBbname(curi,&o_keyi_bp,errhp,:o_key",ADR(o_key),SIZ(o_key),
SQLT_INT);

#endif /* NOLKEY */

/* Open and Parse cursor for the ACID transaction. */

sprintf((char *) sqlstmt,SQLTXT2);
OCIStmtPrepare(curr,errhp,(text *)sqlstmt,strlen((char *)sqlstmt),
        OCI_NTV_SYNTAX,OCI_DEFAULT);

/* bind variables */

OCIBbname(curr,l_key_bp,errhp,:l_key",ADR(l_key),SIZ(l_key),SQL
T_INT);

OCIBbname(curr,o_key_bp,errhp,:o_key",ADR(o_key),SIZ(o_key),SQ
LT_INT);

OCIBbname(curr,delta_bp,errhp,:delta",ADR(delta),SIZ(delta),SQLT_I
NT);

OCIBbname(curr,l_pkey_bp,errhp,:l_pkey",ADR(l_pkey),SIZ(l_pkey),
SQLT_INT);

OCIBbname(curr,l_skey_bp,errhp,:l_skey",ADR(l_skey),SIZ(l_skey),S
QLT_INT);

```

```

OCIbbname(curr,l_quan_bp,errhp,:l_quan",ADR(l_quan),SIZ(l_quan),
SQLT_INT);
OCIbbname(curr,l_newquan_bp,errhp,:l_newquan",ADR(l_newquan),
SIZ(l_newquan),SQLT_INT);

OCIbbname(curr,l_tax_bp,errhp,:l_tax",ADR(l_tax),SIZ(l_tax),SQLT_
FLT);

OCIbbname(curr,l_disc_bp,errhp,:l_disc",ADR(l_disc),SIZ(l_disc),SQ
LT_FLT);

OCIbbname(curr,l_eprice_bp,errhp,:l_eprice",ADR(l_eprice),SIZ(l_epr
ice),
SQLT_FLT);

OCIbbname(curr,l_neweprice_bp,errhp,:l_neweprice",ADR(l_newepric
e),
SIZ(l_neweprice),SQLT_FLT);

OCIbbname(curr,o_tprice_bp,errhp,:o_tprice",ADR(o_tprice),SIZ(o_tp
rice),
SQLT_FLT);

OCIbbname(curr,o_newtprice_bp,errhp,:o_newtprice",ADR(o_newtpri
ce),
SIZ(o_newtprice), SQLT_FLT);
OCIbbname(curr,rprice_bp,errhp,:rprice",ADR(rprice),SIZ(rprice),
SQLT_FLT);
OCIbbname(curr,cost_bp,errhp,:cost",ADR(cost),SIZ(cost),
SQLT_FLT);

/* Open & Parse cursor for end values query */

sprintf((char *) sqlstmt,SQLTXT3);
OCIStmtPrepare(cure1,errhp,(text *)sqlstmt,strlen((char *)sqlstmt),
 OCI_NTV_SYNTAX,OCI_DEFAULT);

sprintf((char *) sqlstmt,SQLTXT4);
OCIStmtPrepare(cure2,errhp,(text *)sqlstmt,strlen((char *)sqlstmt),
 OCI_NTV_SYNTAX,OCI_DEFAULT);

/* bind variables */

OCIbbname(cure1,l_neweprice1_bp,errhp,:l_neweprice",ADR(l_newep
rice),
SIZ(l_neweprice),SQLT_FLT);

OCIbbname(cure1,l_newquan1_bp,errhp,:l_newquan",ADR(l_newqua
n),
SIZ(l_newquan),SQLT_INT);

OCIbbname(cure1,o_key1_bp,errhp,:o_key",ADR(o_key),SIZ(o_key),
SQLT_INT);

OCIbbname(cure1,l_key1_bp,errhp,:l_key",ADR(l_key),SIZ(l_key),S
QLT_INT);

OCIbbname(cure2,o_newtprice2_bp,errhp,:o_newtprice",ADR(o_newt
price),
SIZ(o_newtprice),SQLT_FLT);

OCIbbname(cure2,o_key2_bp,errhp,:o_key",ADR(o_key),SIZ(o_key),
SQLT_INT);

}

```

C.6 atranspl.h

```

/* Copyright (c) 2001, 2002, Oracle Corporation. All rights reserved. */

/*
NAME
atranspl.h - <one-line expansion of the name>

DESCRIPTION

MODIFIED (MM/DD/YY)
mpoess 10/23/02 - mpoess_update_from_visa
mpoess 10/17/01 - add TXT parameter
mpoess 04/09/01 - add hint to find max linenumber
mpoess 01/04/01 - Creation

*/
#ifndef ATRANSPL_H

#define ATRANSPL_H

#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <sys/param.h>
#include <sys/types.h>
#include <time.h>
#include <errno.h>
#include <math.h>

#include <oratypes.h>
#ifndef OCIDFN
#include <ocidfn.h>
#endif /* OCIDFN */

#ifndef OCI_ORACLE
#include <oci.h>
#endif /* OCI_ORACLE */

/*
#ifndef __STDC__
#include <ociapr.h>
#else
#include <ocikpr.h>
#endif /* __STDC__ */

extern int errno;

#ifndef NULL
#define NULL 0
#endif

#ifndef NULLP
#define NULLP (void *)NULL
#endif /* NULLP */

#ifndef DISCARD
#define DISCARD (void)
#endif

#ifndef sword
#define sword int
#endif

#ifndef ub1
#define ub1 unsigned char
#endif

#define UNAME_LEN 64

```

```

#define WRITE_BUF_LEN 1024
#define NA -1 /* ANSI SQL NULL */
#define VER7 2
#define NOT_SERIALIZABLE 8177 /* ORA-08177: transaction not
serializable */
#define WRITE_BUF_LEN 1024

#define ADR(object) ((ub1 *)&(object))
#define SIZ(object) ((sword)sizeof(object))
#define BIS(flg,mask) (unsigned) (flg |= (unsigned) mask)
#define BIT(flg,mask) (unsigned) ((unsigned) flg & (unsigned) mask)

#define FPRTF(fd,s) \
{sprintf(buf,s); write(fd, buf, strlen(s));}
#define FPRTF1(fd,s,p) \
{sprintf(buf,s,p); write(fd, buf, strlen(buf));}
#define FPRTF2(fd,s,p1,p2) \
{sprintf(buf,s,p1,p2); write(fd, buf, strlen(buf));}

#define OCIalloc(envh,hndl,htyp) \
if((status=OCIAHandleAlloc((dvoid *)envh,(dvoid
**)hndl,htyp,0,(dvoid **)0))!=OCI_SUCCESS) \
    sql_error(envh,status,0); \
else \
    DISCARD 0

#define OCIhfree(hndl,htyp) \
if((status=OCIAHandleFree((dvoid *)hndl,htyp)) == OCI_SUCCESS) \
    fprintf(stderr, "Error freeing handle of type %d\n", htyp)

#define OCIaget(hndl,htyp,attp,size,atyp,errh) \
if((status=OCIAttrGet((dvoid *)hndl,htyp,(dvoid *)attp,(dvoid
*)size,atyp,errh)) != OCI_SUCCESS) \
    sql_error(errh,status,1); \
else \
    DISCARD 0

#define OCIsset(hndl,htyp,attp,size,atyp,errh) \
if((status=OCIAttrSet((dvoid *)hndl,htyp,(dvoid
*)attp,size,atyp,errh)) != OCI_SUCCESS) \
    sql_error(errh,status,1); \
else \
    DISCARD 0

#define OCIsexec(svch,stmh,errh,iter) \
if((status=OCIStmtExecute(svch,stmh,errh,iter,0,NULL,NULL,OCI_DE
FAULT)) != OCI_SUCCESS) \
    sql_error(errh,status,1); \
else \
    DISCARD 0

#define OCIBbname(stmh,bndp,errh,sqlvar,progv,progvl,ftype) \
if((status=OCIBindByName(stmh,&bndp,errh,(text
*)sqlvar,strlen(sqlvar), \
    progv,progvl,ftype,0,0,0,0,OCI_DEFAULT)) != \
OCI_SUCCESS) \
    sql_error(errh,status,1); \
else \
    DISCARD 0

#define OCIBbnamei(stmh,bndp,errh,sqlvar,progv,progvl,ftype,indp) \
if((status=OCIAHandleAlloc((dvoid *)stmh,(dvoid
**)&bndp,OCI_HTYPE_BIND, \
    0,(dvoid **)0))!=OCI_SUCCESS) \
    sql_error(stmh,status,0); \
if((status=OCIBindByName(stmh,&bndp,errh,(text
*)sqlvar,strlen(sqlvar), \
    progv,progvl,ftype,indp,0,0,0,0,OCI_DEFAULT)) != \
OCI_SUCCESS) \
    sql_error(errh,status,1); \
else \
    DISCARD 0

sql_error(errh,status,1); \
else \
    DISCARD 0

#define OCIcom(svcp,errh) \
if((status=OCITransCommit(svcp,errh,OCI_DEFAULT)) != \
OCI_SUCCESS) \
    sql_error(errh,status,1); \
else \
    DISCARD 0

#define OCItrol(svcp,errh) \
if((status=OCITransRollback(svcp,errh,OCI_DEFAULT)) != \
OCI_SUCCESS) \
    sql_error(errh,status,1); \
else \
    DISCARD 0

#define ISOTXT "alter session set isolation_level = serializable"
#define PDMLTXT "alter session force parallel dml parallel (degree 4)"
#define PDDLTXT "alter session force parallel ddl parallel (degree 4)"
#define OICATXT "alter session set optimizer_index_cost_adj=25"

#define SQLTXT1 "BEGIN SELECT /*+ index(lineitem,i_l_orderkey)
/* MAX(l_linenumber) INTO :l_key FROM lineitem \
WHERE l_orderkey = :o_key; END;" \
#define SQLTXT2 "BEGIN d_atrans.doatrans(:l_key, :o_key, :delta,
:l_pkey, \
:l_skey, :l_quan, :l_newquan, :l_tax, :l_disc, :l_eprice, :l_neweprice, \
:o_tprice, :o_newtprice, :rprice, :cost); END;" \
#define SQLTXT3 "BEGIN SELECT l_extendedprice, l_quantity \
INTO :l_neweprice, :l_newquan \
FROM lineitem \
WHERE l_orderkey = :o_key \
AND l_linenumber = :l_key; END;" \
#define SQLTXT4 "BEGIN SELECT o_totalprice INTO :o_newtprice \
FROM orders \
WHERE o_orderkey = :o_key; END;" \
#define SQLTXT5 "BEGIN SELECT l_extendedprice, l_quantity \
INTO :l_eprice, :l_quan \
FROM lineitem \
WHERE l_orderkey = :o_key \
AND l_linenumber = :l_key; END;" \
#define SQLTXT6 "BEGIN SELECT o_totalprice INTO :o_tprice \
FROM orders \
WHERE o_orderkey = :o_key; END;" \
#endif /* ATRANSPL_H */


```

C.7 ckpt.sh

```

#!/bin/ksh
#
# $Header: ckpt.sh 08-aug-99.17:37:07 mpoess Exp $
#
# ckpt.sh
#
# Copyright (c) Oracle Corporation 1999. All Rights Reserved.
#
# NAME
#   ckpt.sh - <one-line expansion of the name>
#
# DESCRIPTION
#   Usage: ckpt.sh

```

```

# Start database checkpoint
#
# NOTES
# <other useful comments, qualifications, etc.>
#
# MODIFIED (MM/DD/YY)
# mpoess 08/08/99 - Creation
# mpoess 08/08/99 - Creation
#
# . $KIT_DIR/env
sqlplus -s /NOLOG << !
connect / as sysdba;
alter system switch logfile;
alter system switch logfile;
exit;
!
```

C.8 cnt_hist.sql

```
select count(*) from history;
exit;
```

```

/bin/rm -rf ${KEY}* $CON1 $CON2 $OUTFILE $CHK
trap "/bin/rm -rf ${KEY}*; exit 1" 1 2 3 15
STREAM=${NUM_STREAMS}
let STREAM="$STREAM + 1" # add one for the update stream
ITER=100
PROG=atranspl
USER=${DATABASE_USER}
CK=10

usage() {
echo ""
echo "Usage: $0 [-n iter] [-s number of stream] [-p prog] [-u usr/pwd]"
-h"
echo ""
echo "-n iter      : number of iterations, default is 100"
echo "-s number of stream : number of streams, default is 2"
echo "-p prog      : program to run, default is atranspl.ott"
echo "-u usr/pwd    : user/password for database access, default is
tpcd/tpcd"
echo "-t chkpt     : time after the start of ACID transaction to
perform the checkpoint"
echo "           default is 10 seconds"
echo "-h          : print this usage summary"
exit 1;
}

set -- `getopt "n:p:u:s:h" "$@"` || usage

while :
do
  case "$1" in
    -s) shift; STREAM=$1;;
    -n) shift; ITER=$1;;
    -p) shift; PROG=$1;;
    -u) shift; USER=$1;;
    -t) shift; CK=$1;;
    -h) usage; exit 0;;
    -) break;;
  esac
  shift
done

if [ $ITER -lt 100 ]
then
echo "Error: Must at least run 100 iterations!"
echo "Exiting..."
exit 1
fi

if [ $STREAM -lt 2 ]
then
echo "Error: Must at least run 2 streams!"
echo "Exiting..."
exit 1
fi

echo "Starting Consistency Test at `date`..."
echo ""
echo "Generate some keys first"
echo ""

i=0

while [ $i -lt $STREAM ]
do
  echo randkey $ITER 1 u$USER
  randkey $ITER 1 u$USER > ${KEY}$i

```

C.9 consist.sh

```
#!/bin/ksh
#
# $Header: consist.sh 08-aug-99.14:20:51 mpoess Exp $
#
# consist.sh
#
# Copyright (c) Oracle Corporation 1999. All Rights Reserved.
#
# NAME
#   consist.sh - <one-line expansion of the name>
#
# DESCRIPTION
#   Performs consistency tests.
#   Usage: consist.sh [-n iter] [-s number of stream] [-p prog]
#           [-u usr/pwd] -h
#
#   Options: See usage below
#
# NOTES
#   <other useful comments, qualifications, etc.>
#
# MODIFIED (MM/DD/YY)
# mpoess 08/08/99 - Creation
# mpoess 08/08/99 - Creation
#
# . $KIT_DIR/env

OH=$ORACLE_HOME
# ACID_DIR=$TPCD_KIT_DIR/audit set in env
OUT_DIR=$ACID_OUT

KEY=${OUT_DIR}/key$$_
OUTFILE=${OUT_DIR}/consrte
CON1=${OUT_DIR}/conb
CON2=${OUT_DIR}/cona
CHK=${OUT_DIR}/consckpt
```

```

i=`expr $i + 1`
done

echo "Check consistency before Submitting Transactions `date`"
echo "Check consistency before Submitting Transactions `date`" >>
$CON1

echo "Obtain 10 keys from the each key file to check consistency"

i=0
while [ $i -lt $STREAM ]
do
KEYS=`head -10 ${KEY}${i} | awk '{printf "%d ", $1}'`
echo "The 10 Keys for file $i are: $KEYS"
#for j in `head -10 ${KEY}${i} | awk '{printf "%d ", $1}'` 
for j in $KEYS
do
    sqlplus $USER @/dbms/oracle10i/kit/acid/consistency/consist $j >>
$CON1
    echo "-----" >> $CON1
done
i=`expr $i + 1`
done

echo ""
echo "Starting ACID transactions at `date`"
echo ""

i=0
while [ $i -lt $STREAM ]
do
    $PROG $i $STREAM 1 0 u${USER} i${KEY}${i}
o${OUTFILE}${i} s1 &
    i=`expr $i + 1`
done

echo "Schedule a Checkpoint"
echo "Checkpoint scheduled at $CK seconds after `date`"
(sleep $CK; $ACID_DIR/ckpt.sh) &

wait

echo ""
echo "Ending ACID transactions at `date`"
echo ""

echo "Completed $STREAM transaction streams with $ITER iterations"
each"
echo ""

echo "Check consistency after Submitting Transactions `date`"
echo "Check consistency after Submitting Transactions `date`" >>
$CON2

cat ${ORACLE_HOME}/rdbms/log/alert_${ORACLE_SID}.log >>
$CHK

i=0
while [ $i -lt $STREAM ]
do
KEYS=`head -10 ${KEY}$i | awk '{printf "%d ", $1}'`
#for j in `head -10 ${KEY}$i | awk '{printf "%d ", $1}'` 
echo "The keys to check for consistency after the test from file $i are:" 
echo "$KEYS"
for j in $KEYS
do
    sqlplus $USER @/dbms/oracle10i/kit/acid/consistency/consist $j >>
$CON2
    echo "-----" >> $CON2

```

```

done
i=`expr $i + 1`
done

C.10 consist.sql
Rem
Rem $Header: consist.sql 08-aug-99.16:59:17 mpoess Exp $
Rem
Rem consist.sql
Rem
Rem Copyright (c) Oracle Corporation 1999. All Rights Reserved.
Rem
Rem NAME
Rem   consist.sql - <one-line expansion of the name>
Rem
Rem DESCRIPTION
Rem   Verifies the consistency of TPC-D database using the
Rem   consistency condition.
Rem
Rem Usage: sqlplus tpcd/tpcd @consist
Rem
Rem NOTE
Rem REQUIRES PACKAGES prvtotpt and dbmsotpt
rem
Rem MODIFIED (MM/DD/YY)
Rem   mpoess 08/08/99 - Creation
Rem   mpoess 08/08/99 - Created
Rem

set verify off
rem set termout on
rem set echo on

REM
REM Get today's date.
REM

select
substr(TO_CHAR(sysdate,'YYYY-MM-DD HH:MI:SS'),1,20) as
CURRENT_TIME
from dual;

set serverout on;

DECLARE
    o_okey      number;
    o_tprice    number;
    l_tprice    number;
    diff         number;
BEGIN
    select o_totalprice
    into o_tprice
    from orders
    where o_orderkey = &&1;

    select sum(trunc((trunc((l_extendedprice * (1-l_discount)), 2)
    * (1+l_tax)), 2))
    into l_tprice
    from lineitem
    where l_orderkey = &&1;

    diff := l_tprice - o_tprice;

    dbms_output.put_line('O_TOTALPRICE: ' ||
TO_CHAR(trunc(o_tprice,2)));

```

```

    dbms_output.put_line('L_TOTALPRICE: ' ||
TO_CHAR(trunc(l_tprice,2)));
    dbms_output.put_line('Difference: ' || TO_CHAR(trunc(diff,2)));
END;
/
spool off
exit

```

C.11 count_tx.sh

```
#!/bin/ksh

STEM=$1
ITER=$2
OUT=$3
FIN=FALSE
while [ "$FIN" = "FALSE" ]
do
s=0
FIN=TRUE
while [ $s -lt $STEM ]
do
nt=`grep "Transaction Completed" $OUT/dura${s} | wc -l`
if [ $nt -lt $ITER ];then
    FIN=FALSE
fi
s=`expr $s + 1`
done
sleep 5
done
echo all streams have committed $ITER transactions
```

C.12 d_hist.sql

```

Rem
Rem $Header: d_hist.sql 07-aug-99.21:33:08 mpoess Exp $
Rem
Rem d_hist.sql
Rem
Rem Copyright (c) Oracle Corporation 1999. All Rights Reserved.
Rem
Rem NAME
Rem   d_hist.sql - <one-line expansion of the name>
Rem
Rem DESCRIPTION
Rem   Creates a history table for ACID test purpose.
Rem
Rem NOTES
Rem   <other useful comments, qualifications, etc.>
Rem
Rem MODIFIED (MM/DD/YY)
Rem   mpoess 08/07/99 - Creation
Rem   mpoess 08/07/99 - Created
Rem

set termout on;
set serverout on;
set echo on;

drop table history;
```

```

create table history
(
    h_p_key number,
    h_s_key number,
    h_o_key number,
    h_l_key number,
    h_delta number,
    h_date_t date
);
exit;
```

C.13 end_acid.sh

```
#!/bin/ksh
#
# $Header: end_acid.sh 08-aug-99.17:06:20 mpoess Exp $
#
# end_acid.sh
#
# Copyright (c) Oracle Corporation 1999. All Rights Reserved.
#
# NAME
#   end_acid.sh - <one-line expansion of the name>
#
# DESCRIPTION
#   end_cons.sh <pid of the durability run>
#   Options: See usage below
#
# NOTES
#   <other useful comments, qualifications, etc.>
#
# MODIFIED (MM/DD/YY)
#   mpoess 08/08/99 - Creation
#   mpoess 08/08/99 - Creation
#
. $KIT_DIR/env

OH=$ORACLE_HOME
# ACID_DIR=$OH/tpcd/audit set in env
OUT_DIR=$ACID_OUT/
DURA_DIR=$ACID_OUT/dura
RUN_ID_FILE=$ACID_DIR/run_id

SHELL_PID=`cat ${DURA_DIR}/shellpid`
ITER=100
STEM=${NUM_STREAMS}
let STEM="$STEM + 1" # add one for the update stream
PROG=${ACID_DIR}/transpl.ott
IN=${ACID_DIR}/acid_in
DURA=${DURA_DIR}/drate
OUT=${DURA_DIR}/drate
DSMPL=${DURA_DIR}/durasmpl
KEY=${DURA_DIR}/key${SHELL_PID}_KEY
USER=tpch/tpch
TRIG=1
HCNT=duracnta

# get history count
sqlplus $USER @cnt_hist > $DURA_DIR/$HCNT 2>&1

# perform the consistency
i=0
while [ $i -lt $STEM ]
do
for j in `head -10 ${KEY}${i} | awk '{printf "%d ",$1}'`
```

```

do
  sqlplus tpch/tpch @consist $j >> $DURA_DIR/duraconsa
done
i=`expr $i + 1`
done

i=0
while [ $i -lt $STEM ]
do
sample.sh ${DURA_DIR}${i} > ${DSMPL}${i} 2>&1
i=`expr $i + 1`
done

cat $ORACLE_HOME/rdbms/log/alert_qual.log >
${DURA_DIR}/alert_qual.log.post_dura 2>&1
cat $ORACLE_HOME/rdbms/log/alert_ASM.log >
${DURA_DIR}/alert_ASM.log.post_dura 2>&1

```

C.14 iso.sh

```

#!/bin/ksh
#
# $Header: iso.sh 17-aug-99.15:44:51 mpoess Exp $
#
# iso.sh
#
# Copyright (c) Oracle Corporation 1999. All Rights Reserved.
#
# NAME
# iso.sh
#
# DESCRIPTION
# This script triggers all 6 isolation tests. In addition,
# it creates more readable formats of the isolation test output.
# NOTES
# <other useful comments, qualifications, etc.>
#
# MODIFIED (MM/DD/YY)
# mpoess 08/17/99 - Creation
# mpoess 08/17/99 - Creation
#
for iso in iso1 iso2 iso3 iso4 iso5 iso6;do
  echo Running isolation test $iso
  /dbms/oracle10i/kit/acid/isolation/${iso}.sh
#  echo Creating nicely formated output of ACID test $iso
#  /dbms/oracle10i/kit/acid/isolation/xiso.pl -o
${ACID_OUT}/${iso}
done

```

C.15 iso1.sh

```

#!/bin/ksh
#
# $Header: iso1.sh 29-jul-98.17:00:11 akarasik Exp $
#
# iso1.sh
#
# Copyright (c) Oracle Corporation 1998. All Rights Reserved.
#
# NAME
# iso1.sh
#
# DESCRIPTION

```

```

# Usage: iso1.sh [-u user/password] [-n remote_node] -h
# Options: See usage below
# NOTES
# For a cross node isolation test, assume the local node is
# one of the participating nodes. The other node can be
# specified by the -n option.
# You need to set the environment variable TPCD_KIT_DIR
#
# MODIFIED (MM/DD/YY)
# mpoess 12/16/98 - update to version 8.1.6
# mpoess 09/25/98 - update audit
# akarasik 07/29/98 -
# akarasik 07/29/98 - Creation
#
. $KIT_DIR/env

# May need to change the following:
RSH=rsh

OH=$ORACLE_HOME
#ACID_DIR=$KIT_DIR/acid is set in env
OUT_DIR=$ACID_OUT

TXN1FILE=$OUT_DIR/txn1$$.$out
TXN2FILE=$OUT_DIR/txn2$$.$out
KEYFILE=$OUT_DIR/key$$.$out
ISOFILE=$OUT_DIR/iso1

USER=$DATABASE_USER
PROG=atranspl

/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE
trap "/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE; exit 1" 1 2 3 15

usage() {
  echo ""
  echo "Usage: $0 [-u user/passwd] [-n remote_node] -h"
  echo ""
  exit 1;
}

set -- `getopt "u:n:h" "$@"` || usage

while :
do
  case "$1" in
    -u) shift; USER=$1;;
    -n) shift; HOST="$1";;
    -h) usage; exit 0;;
    --) break;;
    esac
    shift;
done

```

```

de=`direxists.sh $ACID_OUT` # I am not using $de afterward, but I
want to avoid the output of direxists

# generate key files

randkey 1 0.1 u"$USER" > $KEYFILE

OKEY=`cat $KEYFILE | awk '{print $1}'`
echo "o_key is \"$OKEY"

# before the ACID transaction, let's run a ACID query to record the
# initial state of lineitem

```

```

echo "Running ACID query BEFORE the start of Isolation Test 1" >>
$TXN2FILE
echo "">> $TXN2FILE
echo "" >> $TXN2FILE
sqlplus $USER @$ACID_DIR/isolation/a_query $OKEY >>
$TXN2FILE
echo "" >> $TXN2FILE
echo "-----" >> $TXN2FILE

sleep 1

# start ACID transaction, Sleep for 60 second before COMMIT
$PROG 1 1 1 0 i$KEYFILE u$USER s60 b0 >> $TXN1FILE &

# let's sleep 10 seconds before starting ACID query

sleep 10

# start ACID query with the same OKEY

echo "Running ACID query 10 seconds AFTER the start of ACID
Transaction" \
>> $TXN2FILE
echo "date" >> $TXN2FILE
if [ "$HOST" != "" ]
then
echo "Starting ACID query on node $HOST" >> $TXN2FILE
${RSH} -n ${HOST} sqlplus $USER @$ACID_DIR/isolation/a_query
$OKEY >> $TXN2FILE
else
sqlplus $USER @$ACID_DIR/isolation/a_query $OKEY >>
$TXN2FILE
fi

echo "-----" >> $TXN2FILE
wait
echo "-----" >> $TXN1FILE

cat $TXN1FILE $TXN2FILE >> $ISOFILE

/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE

```

C.16 iso2.sh

```

#!/bin/ksh
#
# $Header: iso2.sh 04-aug-99.09:19:54 mpoess Exp $
#
# iso2.sh
#
# Copyright (c) Oracle Corporation 1999. All Rights Reserved.
#
# NAME
# iso2.sh - <one-line expansion of the name>
#
# DESCRIPTION
# Usage: iso2.sh [-u user/password] [-n remote_node] -h
# Options: See usage below
#
# NOTES
# For a cross node isolation test, assume the local node is
# one of the participating nodes. The other node can be
# specified by the -n option.
# You need to set the environment variable TPCD_KIT_DIR
#
# MODIFIED (MM/DD/YY)
# mpoess 08/04/99 - Creation

```

```

# mpoess 08/04/99 - Creation
#
#
#
=====
# May need to change the following:
.
. $KIT_DIR/env

RSH=rsh

OH=$ORACLE_HOME
# ACID_DIR=$TPCD_KIT_DIR/audit is set in env
OUT_DIR=$ACID_OUT

DURA_DIR=$ACID_DIR/dura

TXN1FILE=$OUT_DIR/txn1$$.$out
TXN2FILE=$OUT_DIR/txn2$$.$out
KEYFILE=$OUT_DIR/key$$.$out
ISOFILE=$OUT_DIR/iso2

USER=$DATABASE_USER
PROG=atranspl

/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE

trap "/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE; exit 1" 1 2 3 15

usage() {

echo ""
echo "Usage: $0 [-u user/password] [-n remote_node] -h"
echo ""
exit 1;
}

set -- `getopt "u:n:h" "$@"` || usage

while :
do
case "$1" in
-u) shift; USER=$1;;
-n) shift; HOST="$1";;
-h) usage; exit 0;;
--) break;;
esac
shift;
done

# generate key files

randkey 1 0.1 u"$USER" > $KEYFILE

OKEY=`cat $KEYFILE | awk '{print $1}'`
echo "o_key is \"$OKEY"

# before the ACID transaction, let's run a ACID query to record the
# initial state of lineitem

echo "Running ACID query BEFORE the start of Isolation Test 1" >>
$TXN2FILE
echo "">> $TXN2FILE
echo "" >> $TXN2FILE
sqlplus "$USER" @$ACID_DIR/isolation/a_query $OKEY >>
$TXN2FILE
echo "" >> $TXN2FILE
echo "-----" >> $TXN2FILE

```

```

sleep 1

# start ACID transaction, Sleep for 30 second before ROLLBACK
$PROG 1 1 0 0 i$KEYFILE u$USER s30 >> $TXN1FILE &

# let's sleep 10 seconds before starting ACID query
sleep 10

# start ACID query with the same OKEY

echo "Running ACID query 10 seconds AFTER the start of ACID
transaction" \
>> $TXN2FILE
echo ``date`` >> $TXN2FILE
if [ "$HOST" != "" ]
then
echo "Starting ACID query on node $HOST" >> $TXN2FILE
${RSH} -n ${HOST} sqlplus "$USER"
@$ACID_DIR/isolation/a_query $OKEY >> $TXN2FILE
else
sqlplus $USER @$ACID_DIR/isolation/a_query $OKEY >
$TXN2FILE
fi

echo "-----" >> $TXN2FILE
wait
echo "-----" >> $TXN1FILE

cat $TXN1FILE $TXN2FILE >> $ISOFILE

/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE

```

C.17 iso3.sh

```

#!/bin/ksh
#
# $Header: iso3.sh 04-aug-99.09:20:35 mpoess Exp $
#
# iso3.sh
#
# Copyright (c) Oracle Corporation 1999. All Rights Reserved.
#
# NAME
#   iso3.sh - <one-line expansion of the name>
#
# DESCRIPTION
#   Usage: iso3.sh [-u user/password] [-n remote_node] -h
#   Options: See usage below
#
# NOTES
#   For a cross node isolation test, assume the local node is
#   one of the participating nodes. The other node can be
#   specified by the -n option.
#   We need to make sure the remote node has access to the
#   file system on the local node. Otherwise, we need to rcp
#   the keyfile to the remote system.
#   You need to set the environment variable TPCD_KIT_DIR
#
# MODIFIED (MM/DD/YY)
#   mpoess 08/04/99 - Creation
#   mpoess 08/04/99 - Creation
#
. $KIT_DIR/env

# May need to change the following:
RSH=rsh

```

```

OH=$ORACLE_HOME
#ACID_DIR=$TPCD_KIT_DIR/audit is set in env
OUT_DIR=$ACID_OUT

DURA_DIR=$ACID_DIR/dura

TXN1FILE=$OUT_DIR/txn1$$$.out
TXN2FILE=$OUT_DIR/txn2$$$.out
KEYFILE=$OUT_DIR/key$$.out
ISOFILE=$OUT_DIR/iso3

USER=$DATABASE_USER
PROG=atranspl

/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE

trap '/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE; exit 1' 1 2 3 15

usage() {
    echo ""
    echo "Usage: $0 [-u user/passwd] [-n remote_node] -h"
    echo ""
    echo "-----"
    exit 1;
}

set -- `getopt "u:n:h" "$@"` || usage

while :
do
    case "$1" in
        -u) shift; USER=$1;;
        -n) shift; HOST="$1";;
        -h) usage; exit 0;;
        --) break;;
        esac
    shift
done

# generate key files

randkey 1 0.1 u"$USER" > $KEYFILE
if [ "$HOST" != "" ]
then
    rcp $KEYFILE ${HOST}:$KEYFILE
fi

sleep 1

# start ACID transaction, Sleep for 30 second before COMMIT
$PROG 1 2 1 0 i$KEYFILE u$USER s30 b0 >> $TXN1FILE &

# let's sleep 10 seconds before starting second ACID transaction
sleep 10

# start another ACID transaction with the same LKEY and OKEY
# but different DELTA

# Do not sleep before COMMIT so that we can see TXN2 has waited.

if [ "$HOST" != "" ]
then
echo "Starting TXN2 on node $HOST" >> $TXN2FILE
${RSH} -n ${HOST} $PROG 2 2 1 1 i$KEYFILE u$USER s1 b1 >> $TXN2FILE &
else
$PROG 2 2 1 1 i$KEYFILE u$USER s1 b1 >> $TXN2FILE &
fi

```

```

wait
echo "-----" >> $TXN2FILE
echo "-----" >> $TXN1FILE

cat $TXN1FILE $TXN2FILE >> $ISOFILE

/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE

```

C.18 iso4.sh

```

#!/bin/ksh
#
# $Header: iso4.sh 04-aug-99.09:21:12 mpoess Exp $
#
# iso4.sh
#
# Copyright (c) Oracle Corporation 1999. All Rights Reserved.
#
# NAME
#   iso4.sh - <one-line expansion of the name>
#
# DESCRIPTION
#   Usage: iso4.sh [-u user/password] [-n remote_node] -h
#   Options: See usage below
# NOTES
#   For a cross node isolation test, assume the local node is
#   one of the participating nodes. The other node can be
#   specified by the -n option.
#   We need to make sure the remote node has access to the
#   file system on the local node. Otherwise, we need to rcp
#   the keyfile to the remote system.
#   You need to set the environment variable TPCD_KIT_DIR
#
# MODIFIED (MM/DD/YY)
#   mpoess 08/04/99 - Creation
#   mpoess 08/04/99 - Creation
#
. $KIT_DIR/env

# May need to change the following:
RSH=rsh

OH=$ORACLE_HOME
# ACID_DIR=$TPCD_KIT_DIR/audit is set in env
OUT_DIR=$ACID_OUT

DURA_DIR=$ACID_DIR/dura

TXN1FILE=$OUT_DIR/txn1$$.out
TXN2FILE=$OUT_DIR/txn2$$.out
KEYFILE=$OUT_DIR/key$$.out
ISOFILE=$OUT_DIR/iso4

USER=$DATABASE_USER
PROG=atransl

/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE

trap "/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE; exit 1" 1 2 3 15

usage() {

echo ""
echo "Usage: $0 [-u user/password] [-n remote_node] -h"
echo ""
exit 1;
}

```

```

set -- `getopt "u:n:h" "$@"` || usage

while :
do
  case "$1" in
    -u) shift; USER=$1;;
    -n) shift; HOST="$1";;
    -h) usage; exit 0;;
    --) break;;
  esac
  shift
done

# generate key files

randkey 1 0.1 u"$USER" > $KEYFILE

if [ "$HOST" != "" ]
then
  rcp $KEYFILE ${HOST}:$KEYFILE
fi

sleep 1

# start ACID transaction, Sleep for 30 second before ROLLBACK

$PROG 1 2 0 0 i$KEYFILE u$USER s30 b0 >> $TXN1FILE &

# let's sleep 10 seconds before starting second ACID transaction

sleep 10

# start another ACID transaction with the same LKEY and OKEY
# but different DELTA

# Do not sleep before COMMIT so that we can see TXN2 has waited.

if [ "$HOST" != "" ]
then
  echo "Starting TXN2 on node $HOST" >> $TXN2FILE
  ${RSH} -n ${HOST} $PROG 2 2 1 1 i$KEYFILE u$USER s1 b1 >> $TXN2FILE &
else
  $PROG 2 2 1 1 i$KEYFILE u$USER s1 b1 >> $TXN2FILE &
fi

wait
echo "-----" >> $TXN2FILE
echo "-----" >> $TXN1FILE

cat $TXN1FILE $TXN2FILE >> $ISOFILE

/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE

```

C.19 iso5.sh

```

#!/bin/ksh
#
# $Header: iso5.sh 04-aug-99.09:21:45 mpoess Exp $
#
# iso5.sh
#
# Copyright (c) Oracle Corporation 1999. All Rights Reserved.
#
# NAME
#   iso5.sh - <one-line expansion of the name>
#

```

```

# DESCRIPTION
# Usage: iso5.sh [-u user/password] [-n remote_node] -h
# Options: See usage below
# NOTES
#   For a cross node isolation test, assume the local node is
#   one of the participating nodes. The other node can be
#   specified by the -n option.
#   You need to set the environment variable TPCD_KIT_DIR
#
# MODIFIED (MM/DD/YY)
# mpoess 08/04/99 - Creation
# mpoess 08/04/99 - Creation
#
# $KIT_DIR/env

# May need to change the following:
RSH=rsh

OH=$ORACLE_HOME
# ACID_DIR=$TPCD_KIT_DIR/audit is set in env
OUT_DIR=$ACID_OUT
DURA_DIR=$ACID_DIR/dura

TXN1FILE=$OUT_DIR/txn1$$out
TXN2FILE=$OUT_DIR/txn2$$out
KEYFILE=$OUT_DIR/key$$out
ISOFILE=$OUT_DIR/iso5

USER=$DATABASE_USER
PROG=atranspl

/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE

trap "/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE; exit 1" 1 2 3 15

usage() {
    echo ""
    echo "Usage: $0 [-u user/passwd] [-n remote_node] -h"
    echo ""
    exit 1;
}

set -- ` getopt "u:n:h" "$@"` || usage

while :
do
    case "$1" in
        -u) shift; USER=$1;;
        -n) shift; HOST="$1";;
        -h) usage; exit 0;;
        --) break;;
        esac
        shift;
done

# generate key files
randkey 1 0.1 u"$USER" > $KEYFILE

if [ "$HOST" != "" ]
then
    rcp $KEYFILE ${HOST}:$KEYFILE
fi

sleep 1

OKEY=`cat $KEYFILE | awk '{print $1}'`


echo "o_key is \"$OKEY"

# before the ACID transaction, let's run a ACID query to record the
# initial state of lineitem

echo "Running ACID query BEFORE the start of Isolation Test 5" >>
$TXN1FILE
echo ""`date` >> $TXN1FILE
echo "" >> $TXN1FILE
sqlplus $USER @$ACID_DIR/isolation/a_query $OKEY >>
$TXN1FILE
echo "" >> $TXN1FILE
echo "-----" >> $TXN1FILE

sleep 1

# start ACID transaction, Sleep for 60 second before COMMIT

$PROG 1 1 10 i$KEYFILE u$USER s60 >> $TXN1FILE &

# let's sleep 5 seconds before starting PARTSUPP query

sleep 5

# First generate PS_PARTKEY and PS_SUPPKEY

PSKEY=`randpsup 1` 

echo "Running PARTSUPP query 5 seconds AFTER the start of ACID
Transaction" \
>> $TXN2FILE
echo ""`date` >> $TXN2FILE
echo "PS_PARTKEY and PS_SUPPKEY are: $PSKEY" >>
$TXN2FILE

if [ "$HOST" != "" ]
then
    echo "Starting PARTSUPP query on node $HOST" >> $TXN2FILE
    ${RSH} -n ${HOST} sqlplus $USER
    @$ACID_DIR/isolation/a_query2 ${PSKEY} >> $TXN2FILE &
else
    sqlplus $USER @$ACID_DIR/isolation/a_query2 ${PSKEY} >>
$TXN2FILE &
fi

wait

echo "-----" >> $TXN2FILE
echo "-----" >> $TXN1FILE

cat $TXN1FILE $TXN2FILE >> $ISOFILE

/bin/rm -rf $TXN1FILE $TXN2FILE $KEYFILE

```

C.20 iso6.sh

```

#!/bin/ksh
#
# $Header: iso6.sh 04-aug-99.09:22:12 mpoess Exp $
#
# iso6.sh
#
# Copyright (c) Oracle Corporation 1999. All Rights Reserved.
#
# NAME
#   iso6.sh - <one-line expansion of the name>
#
# DESCRIPTION
#   Usage: iso6.sh [-u user/password] [-n remote_node] -h
#   Options: See usage below
# NOTES
#   For a cross node isolation test, assume the local node is
#   one of the participating nodes. The other node can be

```

```

# specified by the -n option.
# We need to make sure the remote node has access to the
# file system on the local node. Otherwise, we need to rpc
# the keyfile to the remote system.
# You need to set the environment variable TPCD_KIT_DIR
#
# MODIFIED (MM/DD/YY)
# mpoess 08/04/99 - Creation
# mpoess 08/04/99 - Creation
#
# $KIT_DIR/env

# May need to change the following:
RSH=rsh

#OH=/private/tpcd
# ACID_DIR=$TPCD_KIT_DIR/audit is set in env
OUT_DIR=$ACID_OUT

DURA_DIR=$ACID_DIR/dura

TXN1FILE=$OUT_DIR/txn1$.out
TXN2FILE=$OUT_DIR/txn2$.out
TXN3FILE=$OUT_DIR/txn3$.out
KEYFILE=$OUT_DIR/key$.out
ISOFILE=$OUT_DIR/iso6

USER=$DATABASE_USER
PROG=atranspl

/bin/rm -rf $TXN1FILE $TXN2FILE $TXN3FILE $KEYFILE

trap "/bin/rm -rf $TXN1FILE $TXN2FILE $TXN3FILE $KEYFILE; exit 1" 1 2 3 15

usage() {

echo ""
echo "Usage: $0 [-u user/passwd] [-n remote_node] -h"
echo ""
exit 1;
}

set -- `getopt "u:n:h" "$@"` || usage

while :
do
  case "$1" in
  -u) shift; USER=$1;;
  -n) shift; HOST="$1";;
  -h) usage; exit 0;;
  -) break;;
  esac
  shift;
done

# generate key files

randkey 1.0.1 u"$USER" > $KEYFILE
#rcp $KEYFILE ${HOST}:$KEYFILE

OKEY=`cat $KEYFILE | awk '{print $1}'`
echo "o_key is \"$OKEY"

# before the any transaction, let's run a ACID query to record the
# initial state of lineitem

echo "Running ACID query BEFORE the start of Isolation Test 6" >> $TXN2FILE
echo "'date'" >> $TXN2FILE
echo "" >> $TXN2FILE
sqlplus $USER @$ACID_DIR/isolation/a_query $OKEY >> $TXN2FILE
echo "" >> $TXN2FILE
echo "-----" >> $TXN2FILE

sleep 1

# start Query 1, use 0 as the delta

echo "Running Query 21 at `date`" >> $TXN1FILE
sqlplus $USER @$KIT_DIR/acid/isolation/q21 >> $TXN1FILE &

# sleep 2 seconds before starting ACID transaction

sleep 2

# start ACID transaction, COMMIT after one second

echo "Starting ACID transaction at `date`" >> $TXN2FILE

if [ "$HOST" != "" ]
then
echo "Starting ACID transaction on node $HOST" >> $TXN2FILE
${RSH} -n ${HOST} $PROG 1 1 1 0 i$KEYFILE u$USER s1 >> $TXN2FILE &
else

```

```

SPROG 1 1 1 0 i$KEYFILE u$USER s1 >> $TXN2FILE &
fi

# start Query 1

sleep 2

echo "Running 2nd Query 21 at `date`" >> $TXN3FILE
sqlplus $USER @$KIT_DIR/acid/isolation/q21 >> $TXN3FILE &
# wait for everyone to finish

wait

echo "-----" >> $TXN3FILE
echo "-----" >> $TXN2FILE
echo "-----" >> $TXN1FILE

cat $TXN1FILE $TXN2FILE $TXN3FILE >> $ISOFILE

/bin/rm -rf $TXN1FILE $TXN2FILE $TXN3FILE $KEYFILE

```

C.21 q1.sql

```

Rem
Rem $Header: template.sql 06-feb-96.13:23:14 mpoess Exp $
Rem
Rem q1.sql
Rem
Rem Copyright (c) Oracle Corporation 2001. All Rights Reserved.
Rem
Rem NAME
Rem q1.sql - <one-line expansion of the name>
Rem
Rem DESCRIPTION
Rem used in isolation test 6
Rem
Rem NOTES
Rem <other useful comments, qualifications, etc.>
Rem
Rem MODIFIED (MM/DD/YY)
Rem mpoess 02/13/01 - Created
Rem

set serverout on;

select
'BEFORE ACID QUERY' as STAGE,
substr(TO_CHAR(sysdate,'YYYY-MM-DD HH:MI:SS'),1,20) as
CURRENT_TIME
from dual;

select
l_returnflag,
l_linestatus,
sum(l_quantity) as sum_qty,
sum(l_extendedprice) as sum_base_price,
sum(l_extendedprice * (1 - l_discount)) as sum_disc_price,
sum(l_extendedprice * (1 - l_discount) * (1 + l_tax)) as
sum_charge,
avg(l_quantity) as avg_qty,
avg(l_extendedprice) as avg_price,
avg(l_discount) as avg_disc,
count(*) as count_order
from
lineitem
where
l_shipdate <= to_date ('1998-12-01','YYYY-MM-DD') - 0
group by
l_returnflag,
l_linestatus
order by
l_returnflag,
l_linestatus;

```

```

select
'AFTER ACID QUERY' as STAGE,
substr(TO_CHAR(sysdate,'YYYY-MM-DD HH:MI:SS'),1,20) as
CURRENT_TIME
from dual;

```

```
exit;
```

C.22 q21.sql

```

set serverout on;

select
'BEFORE ACID QUERY' as STAGE,
substr(TO_CHAR(sysdate,'YYYY-MM-DD HH:MI:SS'),1,20) as
CURRENT_TIME
from dual;

select * from (
select
    s_name,
    count(*) numwait
from
    supplier,
    lineitem l1,
    orders,
    nation
where
    s_suppkey = l1.l_suppkey
    and o_orderkey = l1.l_orderkey
    and o_orderstatus = 'F'
    and l1.l_receiptdate > l1.l_commitdate
    and exists (
        select
            *
        from
            lineitem l2
        where
            l2.l_orderkey = l1.l_orderkey
            and l2.l_suppkey <> l1.l_suppkey
    )
    and not exists (
        select
            *
        from
            lineitem l3
        where
            l3.l_orderkey = l1.l_orderkey
            and l3.l_suppkey <> l1.l_suppkey
            and l3.l_receiptdate > l3.l_commitdate
    )
    and s_nationkey = n_nationkey
    and n_name = 'SAUDI ARABIA'
group by
    s_name
order by
    numwait desc,
    s_name)
where rownum <= 10;

select
'AFTER ACID QUERY' as STAGE,
substr(TO_CHAR(sysdate,'YYYY-MM-DD HH:MI:SS'),1,20) as
CURRENT_TIME
from dual;

```

```
exit;
```

C.23 randkey.c

```

/* Copyright (c) 2001, 2002, Oracle Corporation. All rights reserved. */

/*
NAME
randkey.c - <one-line expansion of the name>

DESCRIPTION
Generate random keys for ACID transactions:
O_ORDERKEY unique random (1..SF*150000*4) and only
first 8 keys out of every 32 are populated.
and
L_ORDERKEY based on Clause 3.1.6.2
DELTA random (1..100)
*/

#include <stdio.h>
#include <stdlib.h>
#include <math.h>
#include "atranspl.h"

#define ORDERCNT 150000.0

/* MK_SPARSE adopted from dss.h */

#define MK_SPARSE(key, seq) \
    (((((key>>3)<<2)|(seq & 0x0003))<<3)|(key & 0x0007))

void sql_error();
void usage();
void ACIDinit();
long atol();
void srand48();
long lrand48();

/* Not really used here, but retained it for future purposes. */

typedef struct aciddef {
    long okey;
    long lkey;
    int delta;
} adef;

long l_key = 0;
long o_key = 0;
char lname[UNAME_LEN];
char *passwd;

/* OCI handles */

OCIEnv *tpcenv;
OCIServer *tpcsrv;
OCIError *errhp;
OCISvcCtx *tpcsvc;
OCISession *tpcusr;
OCISStmt *curi;

OCIBind *l_key_bp;
OCIBind *o_key_bp;

sword status = OCI_SUCCESS; /* OCI return value */

char sqlstmt[1024];

```

```

void ACIDexit() {
    OCILogoff(tpcsvc,errhp);
    OCIIfree(tpcenv,OCI_HTYPE_STMT);
    OCIIfree(tpcsvc,OCI_HTYPE_SVCCTX);
    OCIIfree(tpcsvr,OCI_HTYPE_SERVER);
    OCIIfree(tpcusr,OCI_HTYPE_SESSION);
}

/* type: 0 if environment handle is passed, 1 if error handle is passwd */

void sql_error(errhp,status,type)
    OCIErr *errhp;
    sword status;
    sword type;
{
    char msg[2048];
    sb4 errcode;
    ub4 msglen;
    int i,j;

    switch(status) {
    case OCI_SUCCESS_WITH_INFO:
        fprintf(stderr, "Error: Statement returned with info.\n");
        if (type)
            (void) OCIErrorGet(errhp,1,NULL,(sb4 *) &errcode,(text *)msg,
                               2048,OCI_HTYPE_ERROR);
        else
            (void) OCIErrorGet(errhp,1,NULL,(sb4 *) &errcode,(text *)msg,
                               2048,OCI_HTYPE_ENV);
        fprintf(stderr,"%s\n",msg);
        break;
    case OCI_ERROR:
        fprintf(stderr, "Error: OCI call error.\n");
        if (type)
            (void) OCIErrorGet(errhp,1,NULL,(sb4 *) &errcode,(text *)msg,
                               2048,OCI_HTYPE_ERROR);
        else
            (void) OCIErrorGet(errhp,1,NULL,(sb4 *) &errcode,(text *)msg,
                               2048,OCI_HTYPE_ENV);
        fprintf(stderr,"%s\n",msg);
        break;
    case OCI_INVALID_HANDLE:
        fprintf(stderr, "Error: Invalid Handle.\n");
        if (type)
            (void) OCIErrorGet(errhp,1,NULL,(sb4 *) &errcode,(text *)msg,
                               2048,OCI_HTYPE_ERROR);
        else
            (void) OCIErrorGet(errhp,1,NULL,(sb4 *) &errcode,(text *)msg,
                               2048,OCI_HTYPE_ENV);
        fprintf(stderr,"%s\n",msg);
        break;
    }
    /* Rollback just in case */

    (void) OCITransRollback(tpcsvc,errhp,OCI_DEFAULT);

    sprintf(stderr, "Exiting Oracle...\n");
    fflush(stderr);

    ACIDexit();
}

main(argc, argv)
    int argc;
    char **argv;
{
    long count;
    long i;
    double sf;      /* need to accomodate sf 0.1 */
    double random;
    double ordcnt;
    adef *res;

    if ((argc < 3) || (argc > 4)) {
        usage();
        exit(-1);
    }

    strcpy((char *) lname, "tpcd/tpcd");

    count = atol(argv[1]);
    sf = atof(argv[2]);

    argc -= 2;
    argv += 2;

    while (--argc) {
        ++argv;
        switch(argv[0][0]) {
        case 'u':
            strncpy((char *) lname, ++(argv[0]), UNAME_LEN);
            if (strchr((char *) lname, '/') == NULL) {
                usage();
                exit(-1);
            }
            break;
        default:
            fprintf(stderr, "Unknown argument %s\n", argv[0]);
            usage();
            break;
        }
    }

    ACIDinit();

    /* initialize array for random numbers */

    res = (adef *) malloc(count*sizeof(adef));
    ordcnt = (double) ORDERCNT * (double) sf;

    for (i=0; i<count; i++) {
        /* The algorithm: */
        /* Assumes drand's output is 'unique', first get a number within */
        /* the range of [0..sf*ORDERCNT) and then maps the different   */
        /* ranges to generate the real output.                         */
        random = floor(drand48() * (double) ordcnt) + 1;
        res[i].okey = o_key = (long) MK_SPARSE((long) random, 0);
        res[i].delta = (long) floor(drand48() * 100) + 1;

        /* Obtain l_key from l_key query */

        OCIexec(tpcsvc,curi,errhp,1);

        /* l_key is the highest l_linenumber available. We need to pick */
        /* at random a number between 1..l_key.                           */
        res[i].lkey = (lrand48() % l_key) + 1;

        printf("%ld %ld %d\n", res[i].okey, res[i].lkey, res[i].delta);
    }

    ACIDexit();
    free(res);
}

```

```

}

void usage() {
    fprintf(stderr, "Usage: randkey <number of random keys to generate>
<SF> u<user/password>\n");
    fprintf(stderr, "\n");
}

void ACIDinit()
{
    /* run random seed */

    srand48(getpid());

    /* Connect to ORACLE. Program will call sql_error()
     * if an error occurs in connecting to the default database. */

    (void) OCIInitialize(OCI_DEFAULT,(dvoid *)0,0,0,0);
    if((status=OCIEnvInit((OCIEnv **)&tpcenv,OCI_DEFAULT,0,(dvoid
**))!=
        OCI_SUCCESS)
        sql_error(tpcenv, status, 0);

    OCIalloc(tpcenv,&errhp,OCI_HTYPE_ERROR);
    OCIalloc(tpcenv,&curi,OCI_HTYPE_STMT);
    OCIalloc(tpcenv,&tpcsvc,OCI_HTYPE_SVCCTX);
    OCIalloc(tpcenv,&tpcsrv,OCI_HTYPE_SERVER);
    OCIalloc(tpcenv,&tpcusr,OCI_HTYPE_SESSION);

    /* get username and password */

    passwd = strchr(lname, '/');
    *passwd = '\0';
    passwd++;

    if ((status=OCIServerAttach(tpcsrv,errhp,(text
*)0,OCI_DEFAULT))!=OCI_SUCCESS)
        sql_error(errhp,status,1);

    OCIaset(tpcsvc,OCI_HTYPE_SVCCTX,tpcsrv,0,OCI_ATTR_SERVER
,errhp);

    OCIaset(tpcusr,OCI_HTYPE_SESSION,lname,strlen(lname),OCI_ATT
R_USERNAME,
        errhp);

    OCIaset(tpcusr,OCI_HTYPE_SESSION,passwd,strlen(passwd),OCI_A
TTR_PASSWORD,
        errhp);

    if ((status = OCISessionBegin(tpcsvc, errhp, tpcusr,
OCI_CRED_RDBMS,
        OCI_DEFAULT)) != OCI_SUCCESS)
        sql_error(errhp,status,1);

    OCIaset(tpcsvc,OCI_HTYPE_SVCCTX,tpcusr,0,OCI_ATTR_SESSIO
N,errhp);

    /* Open and Parse cursor for query to choose determine l_key.
     * Binds l_key to :l_key. */
    sprintf((char *) sqlstmt,SQLTXT1);
    OCISmtPrepare(curi,errhp,(text *)sqlstmt,strlen((char *)sqlstmt),
        OCI_NTV_SYNTAX,OCI_DEFAULT);
}

```

```

OCIbbname(curi,l_key_bp,errhp,:l_key",ADR(l_key),SIZ(l_key),SQL
T_INT);

```

```

OCIbbname(curi,o_key_bp,errhp,:o_key",ADR(o_key),SIZ(o_key),SQ
LT_INT);
}

```

C.24 randpsup.c

```

/* Copyright (c) 2001, 2002, Oracle Corporation. All rights reserved. */

```

```

/*

```

NAME

```

randpsup.c - <one-line expansion of the name>

```

DESCRIPTION

```

Generate random keys for ACID PARTSUPP transactions:

```

```

(Clause 4.2.3)

```

```

PS_PARTKEY random within [SF*200000]
and
PS_SUPPKEY = (PS_PARTKEY + (i * ((S/4) +
(int)(PS_PARTKEY - 1)
/S))) % S + 1
where i random within [0..3] and S = SF * 10000

```

MODIFIED

```

mpoess 10/23/02 - mpoess_update_from_visa
mpoess 01/04/01 - Creation

```

```

*/

```

```

#include <stdio.h>
#include <stdlib.h>
#include <math.h>

```

```

#define PS_PER_SF 200000.0
#define S_PER_SF 10000.0
#define SUPP_PER_PART 4

```

```

/* borrowed from build.c in the dbgen distribution */

```

```

#define PART_SUPP_BRIDGE(tgt, p, s) \
{ \
    long tot_scnt = (long) (S_PER_SF * sf); \
    tgt = (p + s * (tot_scnt / SUPP_PER_PART + \
    (long) ((p - 1) / tot_scnt))) % tot_scnt + 1; \
}

```

```

void usage();
double atof();
void srand48();
long lrand48();

```

```

main(argc, argv)

```

```

    int argc;
    char **argv;
{

```

```

    double sf = 0.1;           /* scale factor */
    long supp;                /* the i-th supplier */
    long pkey;                /* partkey */
    long maxpkey;             /* highest partkey */
    long ps_skey;              /* ps_suppkey */

```

```

if (argc < 2) {

```

```

usage();
exit(-1);
}

/* seed the random number generator */

srand48(getpid());

sf = atof(argv[1]);
maxpkey = (long) (sf * PS_PER_SF);
supp = lrand48() % 4;
pkey = lrand48() % maxpkey + 1;

PART_SUPP_BRIDGE(ps_skey, pkey, supp);

fprintf(stdout, "%ld %ld", pkey, ps_skey);

exit(0);
}

void usage()
{
    fprintf(stderr, "Usage: randpsup <SF>\n\n");
}

```

ITER=1000
STEM=\${NUM_STREAMS}
let STEM="\$STEM + 1" # add one for the update stream
SF=1
PROG=atranspl
IN=\${ACID_DIR}/acid_in
DURA_DIR=\${ACID_OUT}/dura
OUT=\$DURA_DIR/drdate
DURA=\$DURA_DIR/dura
KEY=\${DURA_DIR}/key\$\$
echo \$\$ > \${DURA_DIR}/shellpid
USER=tpch/tpch
TRIG=1
HCNT=duracntb

set -- ` getopt "n:s:p:i:o:d:u:ht:f:" "\$@"` || usage

get all the options

C.25 run_acid.sh

```

#!/bin/ksh
#
# $Header: run_acid.sh 08-aug-99.15:30:10 mpoess Exp $
#
# run_acid.sh
#
# Copyright (c) Oracle Corporation 1999. All Rights Reserved.
#
# NAME
#   run_acid.sh - <one-line expansion of the name>
#
# DESCRIPTION
#   Usage: run_acid.sh [-n iter] [-s stream] [-p prog] [-i infile]
#                      [-o outfile] [-d durafile] [-u usr/pswd]
#                      [-t trigger] [-f scale factor] -h
#
#   Options: See usage below
#
# MODIFIED (MM/DD/YY)
# mpoess 08/08/99 - Creation
# mpoess 08/08/99 - Creation
#
. $KIT_DIR/env

OH=$ORACLE_HOME
ACID_DIR=$ACID_DIR
OUT_DIR=$ACID_OUT

usage() {

echo ""
echo "Usage: $0 [-n iter] [-s stream] [-p prog] [-i infile] [-o outfile]"
echo "           [-d durafile] [-u usr/pswd] -h"
echo ""
echo "-n iter : number of iterations, default is 100"
echo "-s stream : number of streams, default is 2"
echo "-p prog : program to run, default is atranspl.ott"
}

while :
do
    case "$1" in
        -n) shift; ITER=$1;;
        -s) shift; STEM=$1;;
        -p) shift; PROG=$1;;
        -i) shift; IN=$1;;
        -o) shift; OUT=$1;;
        -d) shift; DURA=$1;;
        -u) shift; USER=$1;;
        -h) usage; exit 0;;
        -t) shift; TRIG=$1;;
        -f) shift; SF=$1;;
        --) break;;
        esac
    shift;
done

#collect system info before durability start
cat /var/adm/syslog/syslog.log > ${DURA_DIR}/syslog_pre_dura 2>&1
ps -ef > ${DURA_DIR}/ps.out.pre_dura 2>&1
cat $ORACLE_HOME/rdbms/log/alert_qual.log >
${DURA_DIR}/alert_qual.log.pre_dura 2>&1
cat $ORACLE_HOME/rdbms/log/alert_ASM.log >
${DURA_DIR}/alert_ASM.log.pre_dura 2>&1

echo "Starting ACID run..."

i=0
T=`expr $STEM \* $TRIG + 6`

# Get history count before the run
sqlplus $USER @cnt_hist > $DURA_DIR/$HCNT 2>&1

while [ $i -lt $STEM ]
do
    randkey $ITER ${SF} u${USER} > ${KEY}${i} &

```

```

i=`expr $i + 1`
done

wait
# perform the consistency

i=0
while [ $i -lt $STEM ]
do
  for j in `head -10 ${KEY}${i} | awk '{printf "%d ",$1}'` 
  do
    sqlplus tpch/tpch @consist $j >> $DURA_DIR/duraconsb
  done
  i=`expr $i + 1`
done

echo "Starting Transaction Counting Program"
count_tx.sh $STEM 100 $DURA_DIR &

i=0
while [ $i -lt $STEM ]
do

  $PROG $i $STEM 1 0 ${KEY}${i} ${OUT}${i} ${DURA}${i}
u$USER s1 &
  T=`expr $T - $TRIG` 
  i=`expr $i + 1` 

done

echo "ACID run completed"

```

C.26 sample.sh

```

#!/bin/ksh
#
# $Header: sample.sh 08-aug-99.17:10:00 mpoess Exp $
#
# sample.sh
#
# Copyright (c) Oracle Corporation 1999. All Rights Reserved.
#
# NAME
#   sample.sh - <one-line expansion of the name>
#
# DESCRIPTION
#   <short description of component this file declares/defines>
#
# NOTES
#   <other useful comments, qualifications, etc.>
#
# MODIFIED (MM/DD/YY)
#   mpoess 08/08/99 - Creation
#   mpoess 08/08/99 - Creation
#
# $1 durability output file

```

```

. $KIT_DIR/env

cat $1 | grep o_key | awk '{printf "%d \n", $2}' | head -106 >
/tmp/okey$$
cat $1 | grep l_key | awk '{printf "%d \n", $2}' | head -106 > /tmp/lkey$$

paste /tmp/okey$$ /tmp/lkey$$ > /tmp/keys$$
tail -6 /tmp/keys$$ > /tmp/6keys$$

echo "Keys chosen are:"
cat /tmp/6keys$$

i=1
while [ $i -le 6 ]
do

j=`cat /tmp/6keys$$ | tail -$i | head -1` 
sqlplus tpch/tpch @sample $j
i=`expr $i + 1` 
done

#/bin/rm -f /tmp/*key*

```

C.27 sample.sql

```

Rem
Rem $Header: sample.sql 08-aug-99.17:10:34 mpoess Exp $
Rem
Rem sample.sql
Rem
Rem Copyright (c) Oracle Corporation 1999. All Rights Reserved.
Rem
Rem NAME
Rem   sample.sql - <one-line expansion of the name>
Rem
Rem DESCRIPTION
Rem   <short description of component this file declares/defines>
Rem
Rem NOTES
Rem   <other useful comments, qualifications, etc.>
Rem
Rem MODIFIED (MM/DD/YY)
Rem   mpoess 08/08/99 - Creation
Rem   mpoess 08/08/99 - Created
Rem

alter session set nls_date_format = 'YYYY-MM-DD HH:MI:SS';
select * from history where h_o_key = &&1 and h_l_key = &&2;
exit;

```

Appendix D Query text and Output

D.1 qryqual

Begin Execution at Mon Apr 23 16:25:45 2007

```
-- using default substitutions
-- @(#1.sql      2.1.6.2
-- TPC-H/TPC-R Pricing Summary Report Query (Q1)
-- Functional Query Definition
-- Approved February 1998

select
l_returnflag,
l_linenstatus,
sum(l_quantity) as sum_qty,
sum(l_extendedprice) as sum_base_price,
sum(l_extendedprice * (1 - l_discount)) as sum_disc_price,
sum(l_extendedprice * (1 - l_discount) * (1 + l_tax)) as sum_charge,
avg(l_quantity) as avg_qty,
avg(l_extendedprice) as avg_price,
avg(l_discount) as avg_disc,
count(*) as count_order
from
lineitem
where
l_shipdate <= to_date ('1998-12-01','YYYY-MM-DD') - 90
group by
l_returnflag,
l_linenstatus
order by
l_returnflag,
l_linenstatus

L_RETURNFLAG L_LINENSTATUS SUM_QTY
SUM_BASE_PRICE
SUM_DISC_PRICE      SUM_CHARGE      AVG_QTY
AVG_PRICE          AVG_DISC        COUNT_ORDER
A     F    37734107.00      56586554400.73
53758257134.87    55909065222.83      25.52
38273.13          0.05          1478493.00
N     F    991417.00       1487504710.38
1413082168.05    1469649223.19      25.52
38284.47          0.05          38854.00
N     O    74476040.00      111701729697.74
106118230307.61   110367043872.50      25.50
38249.12          0.05          2920374.00
R     F    37719753.00      56568041380.90
53741292684.60    55889619119.83      25.51
38250.85          0.05          1478870.00
```

4 rows processed.
Query Processed in 1.30 seconds.

```
-- @(#2.sql      2.1.6.2
-- TPC-H/TPC-R Minimum Cost Supplier Query (Q2)
-- Functional Query Definition
-- Approved February 1998
```

```
select * from (
select
```

```
s_acctbal,
s_name,
n_name,
p_partkey,
p_mfgr,
s_address,
s_phone,
s_comment
from
part,
supplier,
partsupp,
nation,
region
where
p_partkey = ps_partkey
and s_suppkey = ps_suppkey
and p_size = 15
and p_type like '%BRASS'
and s_nationkey = n_nationkey
and n_regionkey = r_regionkey
and r_name = 'EUROPE'
and ps_supplycost =
(select
min(ps_supplycost)
from
partsupp,
supplier,
nation,
region
where
p_partkey = ps_partkey
and s_suppkey = ps_suppkey
and s_nationkey = n_nationkey
and n_regionkey = r_regionkey
and r_name = 'EUROPE'
)
order by
s_acctbal desc,
n_name,
s_name,
p_partkey
)
where rownum <= 100
```

S_ACCTBAL	S_NAME	N_NAME
P_PARTKEY	P_MFGR	
S_ADDRESS		S_PHONE
S_COMMENT		
9938.53	Supplier#000005359	UNITED KINGDOM
185358.00	Manufacturer#4	
QKuHYh,vZGiwu2FWEJoLDx04		33-429-790-6131
uriously regular requests hag		
9937.84	Supplier#000005969	ROMANIA
108438.00	Manufacturer#1	
ANDENSOSSmk,miq23Xfb5RWt6dvUcvvt6Qa		29-520-692-3537
efully express instructions. regular requests against the slyly fin		
9936.22	Supplier#000005250	UNITED KINGDOM
249.00	Manufacturer#4	
B3rqp0xbSEim4Mpy2RH J		33-320-228-2957
eect about the furiously final accounts. slyly ironic pinto beans sleep		
inside the furiously		
9923.77	Supplier#000002324	GERMANY
29821.00	Manufacturer#4	
y3OD9UywSTOK		17-779-299-1839
ackages boost blithely. blithely regular deposits c		
9871.22	Supplier#000006373	GERMANY
43868.00	Manufacturer#5	

<deleted>

```

7850.66      Supplier#000001518    UNITED KINGDOM
86501.00     Manufacturer#1
ONDa3YJiHJKJOC          33-730-383-3892
ifts haggle fluffly pending pai
7843.52      Supplier#000006683    FRANCE
11680.00     Manufacturer#4
2Z0JGkiv01Y00oCFwUGfvilbhzCdy          16-464-517-8943
express, final pinto beans x-ray slyly asymptotes. unusual, unusual

```

100 rows processed.
Query Processed in 1.33 seconds.

```

-- @(#3.sql      2.1.6.2
-- TPC-H/TPC-R Shipping Priority Query (Q3)
-- Functional Query Definition
-- Approved February 1998

```

```

select * from (
select
l_orderkey,
sum(l_extendedprice * (1 - l_discount)) as revenue,
o_orderdate,
o_shippriority
from
customer,
orders,
lineitem
where
c_mktsegment = 'BUILDING'
and c_custkey = o_custkey
and l_orderkey = o_orderkey
and o_orderdate < to_date('1995-03-15', 'YYYY-MM-DD')
and l_shipdate > to_date('1995-03-15', 'YYYY-MM-DD')
group by
l_orderkey,
o_orderdate,
o_shippriority
order by
revenue desc,
o_orderdate)
where rownum <= 10

```

L_ORDERKEY	REVENUE	O_ORDERDATE
O_SHIPPRIORITY		
2456423.00	406181.01	1995-03-05 0.00
3459808.00	405838.70	1995-03-04 0.00
492164.00	390324.06	1995-02-19 0.00
1188320.00	384537.94	1995-03-09 0.00
2435712.00	378673.06	1995-02-26 0.00
4878020.00	378376.80	1995-03-12 0.00
5521732.00	375153.92	1995-03-13 0.00
2628192.00	373133.31	1995-02-22 0.00
993600.00	371407.46	1995-03-05 0.00
2300070.00	367371.15	1995-03-13 0.00

10 rows processed.
Query Processed in 1.69 seconds.

```

-- @(#4.sql      2.1.6.2
-- TPC-H/TPC-R Order Priority Checking Query (Q4)
-- Functional Query Definition
-- Approved February 1998

```

```

select
o_orderpriority,

```

```

count(*) as order_count
from
orders
where
o_orderdate >= to_date('1993-07-01', 'YYYY-MM-DD')
and o_orderdate < add_months(to_date('1993-07-01', 'YYYY-MM-
DD'), 3)
and exists (
select
*
```

```

from
lineitem
where
l_orderkey = o_orderkey
and l_commitdate < l_receiptdate
)
group by
o_orderpriority
order by
o_orderpriority
```

O_ORDERPRIORITY	ORDER_COUNT
1-URGENT	10594.00
2-HIGH	10476.00
3-MEDIUM	10410.00
4-NOT SPECIFIED	10556.00
5-LOW	10487.00

5 rows processed.
Query Processed in 1.53 seconds.

```

-- @(#5.sql      2.1.6.2
-- TPC-H/TPC-R Local Supplier Volume Query (Q5)
-- Functional Query Definition
-- Approved February 1998

```

```

select
n_name,
sum(l_extendedprice * (1 - l_discount)) as revenue
from
customer,
orders,
lineitem,
supplier,
nation,
region
where
c_custkey = o_custkey
and l_orderkey = o_orderkey
and l_suppkey = s_suppkey
and c_nationkey = s_nationkey
and s_nationkey = n_nationkey
and n_regionkey = r_regionkey
and r_name = 'ASIA'
and o_orderdate >= to_date('1994-01-01', 'YYYY-MM-DD')
and o_orderdate < add_months(to_date('1994-01-01', 'YYYY-MM-
DD'), 12)
group by
n_name
order by
revenue desc
```

N_NAME	REVENUE
INDONESIA	55502041.17
VIETNAM	55295087.00
CHINA	53724494.26
INDIA	52035512.00
JAPAN	45410175.70

5 rows processed.
Query Processed in 4.11 seconds.

```
-- @(#6.sql      2.1.6.2
-- TPC-H/TPC-R Forecasting Revenue Change Query (Q6)
-- Functional Query Definition
-- Approved February 1998

select
sum(l_extendedprice * l_discount) as revenue
from
lineitem
where
l_shipdate >= to_date('1994-01-01', 'YYYY-MM-DD')
and l_shipdate < add_months(to_date('1994-01-01', 'YYYY-MM-DD'), 12)
and l_discount between .06 - 0.01 and .06 + 0.01
and l_quantity < 24
```

REVENUE
123141078.23

1 row processed.
Query Processed in 0.27 seconds.

```
-- @(#7.sql      2.1.6.2
-- TPC-H/TPC-R Volume Shipping Query (Q7)
-- Functional Query Definition
-- Approved February 1998

select
supp_nation,
cust_nation,
l_year,
sum(volume) as revenue
from
(
select
n1.n_name as supp_nation,
n2.n_name as cust_nation,
to_number(to_char
(l_shipdate,'yyyy')) as l_year,
l_extendedprice * (1 - l_discount) as volume
from
supplier,
lineitem,
orders,
customer,
nation n1,
nation n2
where
s_suppkey = l_suppkey
and o_orderkey = l_orderkey
and c_custkey = o_custkey
and s_nationkey = n1.n_nationkey
and c_nationkey = n2.n_nationkey
and (
(n1.n_name = 'FRANCE' and n2.n_name = 'GERMANY')
or (n1.n_name = 'GERMANY' and n2.n_name = 'FRANCE')
)
and l_shipdate between to_date('1995-01-01', 'YYYY-MM-DD') and
to_date('1996-12-31', 'YYYY-MM-DD')
) shipping
group by
```

SUPP_NATION	CUST_NATION	L_YEAR
FRANCE	GERMANY	1995.00
FRANCE	GERMANY	1996.00
GERMANY	FRANCE	1995.00
GERMANY	FRANCE	1996.00
		52520549.02

4 rows processed.
Query Processed in 3.82 seconds.

```
-- @(#8a.sql      2.1.6.2
-- TPC-H/TPC-R National Market Share Query (Q8)
-- Approved February 1998
```

O_YEAR	MKT_SHARE
1995.00	0.03
1996.00	0.04

2 rows processed.
Query Processed in 2.68 seconds.

```
-- @(#9.sql      2.1.6.2
-- TPC-H/TPC-R Product Type Profit Measure Query (Q9)
-- Functional Query Definition
-- Approved February 1998
```

```
select
nation,
o_year,
sum(amount) as sum_profit
from
(
select
n_name as nation,
to_number(to_char(o_orderdate, 'yyyy')) as o_year,
l_extendedprice * (1 - l_discount) - ps_supplycost * l_quantity as
amount
from
part,
supplier,
lineitem,
partsupp,
orders,
nation
where
s_suppkey = l_suppkey
and ps_suppkey = l_suppkey
and ps_partkey = l_partkey
and p_partkey = l_partkey
and o_orderkey = l_orderkey
and s_nationkey = n_nationkey
and p_name like '%green%'
) profit
group by
nation,
o_year
order by
nation,
o_year desc
```

NATION	O_YEAR	SUM_PROFIT
ALGERIA	1998.00	31342867.23
ALGERIA	1997.00	57138193.02
ALGERIA	1996.00	56140140.13
ALGERIA	1995.00	53051469.65
ALGERIA	1994.00	53867582.13
ALGERIA	1993.00	54942718.13
ALGERIA	1992.00	54628034.71
ARGENTINA	1998.00	30211185.71
ARGENTINA	1997.00	50805741.75
ARGENTINA	1996.00	51923746.58
ARGENTINA	1995.00	49298625.77
ARGENTINA	1994.00	50835610.11
ARGENTINA	1993.00	51646079.18
ARGENTINA	1992.00	50410314.99
BRAZIL	1998.00	27217924.38
BRAZIL	1997.00	48378669.20
BRAZIL	1996.00	50482870.36
BRAZIL	1995.00	47623383.63
BRAZIL	1994.00	47840165.73
BRAZIL	1993.00	49054694.04
BRAZIL	1992.00	48667639.08
CANADA	1998.00	30379833.77
CANADA	1997.00	50465052.31
CANADA	1996.00	52560501.39
CANADA	1995.00	52375332.81

CANADA	1994.00	52600364.66	
CANADA	1993.00	52644504.07	
CANADA	1992.00	53932871.70	
CHINA	1998.00	31075466.16	
CHINA	1997.00	50551874.45	
CHINA	1996.00	51039293.88	

<deleted>

175 rows processed.
Query Processed in 2.73 seconds.

```
-- @(#10.sql      2.1.6.2
-- TPC-H/TPC-R Returned Item Reporting Query (Q10)
-- Functional Query Definition
-- Approved February 1998
```

```
select * from (
select
c_custkey,
c_name,
sum(l_extendedprice * (1 - l_discount)) as revenue,
c_acctbal,
n_name,
c_address,
c_phone,
c_comment
from
customer,
orders,
lineitem,
nation
where
c_custkey = o_custkey
and l_orderkey = o_orderkey
and o_orderdate >= to_date ('1993-10-01', 'YYYY-MM-DD')
and o_orderdate < add_months( to_date('1993-10-01', 'YYYY-MM-
DD'), 3)
and l_returnflag = 'R'
and c_nationkey = n_nationkey
group by
c_custkey,
c_name,
c_acctbal,
c_phone,
n_name,
c_address,
c_comment
order by
revenue desc)
where rownum <= 20
```

C_CUSTKEY	C_NAME	REVENUE
57040.00	Customer#000057040	734235.25
632.87	JAPAN	
Eioyzjf4pp	22-895-641-3466	
sits. slyly regular requests sleep alongside of the regular inst		
143347.00	Customer#000143347	721002.69
2557.47	EGYPT	
1aReFYv,Kw4	14-742-935-3718	
ggle carefully enticing requests. final deposits use bold, bold pinto		
beans. ironic, idle re		
60838.00	Customer#000060838	679127.31
2454.77	BRAZIL	

64EaJ5vMAHWJlBOxJkIpNc2RJiWE 12-913-494-9813
need to boost against the slyly regular account
101998.00 Customer#000101998 637029.57
3790.89 UNITED KINGDOM
01c9CILnNtfOQYmZj 33-593-865-6378
ress foxes wake slyly after the bold excuses. ironic platelets are furiously
carefully bold theodolites
125341.00 Customer#000125341 633508.09
4983.51 GERMANY
S29ODD6bceU8QSuuEJznkNaK 17-582-695-5962
arefully even depths. blithely even excuses sleep furiously. foxes use
except the dependencies. ca
25501.00 Customer#000025501 620269.78
7725.04 ETHIOPIA
W556MXuoiaYCCZamJI,Rn0B4ACUGdkQ8DZ 15-874-808-6793
he pending instructions wake carefully at the pinto beans. regular, final
instructions along the slyly fina
115831.00 Customer#000115831 596423.87
5098.10 FRANCE
rFeBbEEyk dl ne7zV5fDrmiq1oK09wV7pxqCgIc 16-715-386-3788
l somas sleep. furiously final deposits wake blithely regular pinto b
84223.00 Customer#000084223 594998.02
528.65 UNITED KINGDOM
nAVZCs6BaWap rrM27N 2qBnzc5WBauxbA 33-442-824-8191
slyly final deposits haggle regular, pending dependencies. pending
escapades wake
54289.00 Customer#000054289 585603.39
5583.02 IRAN
vXCxoCsU0Bad5JQI ,oobkZ 20-834-292-4707
ely special foxes are quickly finally ironic p
39922.00 Customer#000039922 584878.11
7321.11 GERMANY
Zgy4s50l2GKN4pLDPBU8m342gIw6R 17-147-757-8036
y final requests. furiously final foxes cajole blithely special platelets. f
6226.00 Customer#000006226 576783.76
2230.09 UNITED KINGDOM
8gPu8,NPGkfYQQ0hcIYUGPIBWc,ybP5g, 33-657-701-3391
ending platelets along the express deposits cajole carefully final
922.00 Customer#00000922 576767.53
3869.25 GERMANY
Az9RFaut7NkPnc5zSD2PwHgVwr4jRzq 17-945-916-9648
luffily fluffy deposits. packages c
147946.00 Customer#000147946 576455.13
2030.13 ALGERIA
iANyZHjqhyy7Ajah0pTrYyhJ 10-886-956-3143
ithely ironic deposits haggle blithely ironic requests. quickly regu
115640.00 Customer#000115640 569341.19
6436.10 ARGENTINA
Vtgfia9ql7EpHgecU1X 11-411-543-4901
ost slyly along the patterns; pinto be
73606.00 Customer#000073606 568656.86
1785.67 JAPAN
xuR0Tro5yChDfOCrjk20l 22-437-653-6966
he furiously regular ideas. slowly
110246.00 Customer#000110246 566842.98
7763.35 VIETNAM
7KzflgX MDOq7sOKl 31-943-426-9837
egular deposits serve blithely above the fl
142549.00 Customer#000142549 563537.24
5085.99 INDONESIA
ChqEoK43OysjdHbtKCp6dKqjNyvvi9 19-955-562-2398
sleep pending courts. ironic deposits against the carefully unusual
platelets cajole carefully express accounts.
146149.00 Customer#000146149 557254.99
1791.55 ROMANIA
s87fvzFQpU 29-744-164-6487
of the slyly silent accounts. quickly final accounts across the
52528.00 Customer#000052528 556397.35
551.79 ARGENTINA
NFztyTOR10UOJ 11-208-192-3205
deposits hinder. blithely pending asymptotes breach slyly regular re

23431.00 Customer#000023431 554269.54
3381.86 ROMANIA
HgiV0phqhaIa9aydNoIlb 29-915-458-2654
nusual, even instructions: furiously stealthy n

20 rows processed.
Query Processed in 1.98 seconds.

-- @(#)11.sql 2.1.6.2
-- TPC-H/TPC-R Important Stock Identification Query (Q11)
-- Functional Query Definition
-- Approved February 1998

select
ps_partkey,
sum(ps_supplycost * ps_availqty) as value
from
partsupp,
supplier,
nation
where
ps_suppkey = s_suppkey
and s_nationkey = n_nationkey
and n_name = 'GERMANY'
group by
ps_partkey having
sum(ps_supplycost * ps_availqty) > (
select
sum(ps_supplycost * ps_availqty) * 0.0001000000
from
partsupp,
supplier,
nation
where
ps_suppkey = s_suppkey
and s_nationkey = n_nationkey
and n_name = 'GERMANY'
)
order by
value desc

PS_PARTKEY	VALUE
129760.00	17538456.86
166726.00	16503353.92
191287.00	16474801.97
161758.00	16101755.54
34452.00	15983844.72
139035.00	15907078.34
9403.00	15451755.62
154358.00	15212937.88
38823.00	15064802.86
85606.00	15053957.15
33354.00	14408297.40
154747.00	14407580.68
82865.00	14235489.78
76094.00	14094247.04
222.00	13937777.74
121271.00	13908336.00
<deleted>	

1048 rows processed.
Query Processed in 5.76 seconds.

-- @(#)12.sql 2.1.6.2
-- TPC-H/TPC-R Shipping Modes and Order Priority Query (Q12)
-- Functional Query Definition
-- Approved February 1998

```

select
    l_shipmode,
    sum(case
        when o_orderpriority = '1-URGENT'
            or o_orderpriority = '2-HIGH'
            then 1
        else 0
    end) as high_line_count,
    sum(case
        when o_orderpriority <> '1-URGENT'
            and o_orderpriority <> '2-HIGH'
            then 1
        else 0
    end) as low_line_count
from
    orders,
    lineitem
where
    o_orderkey = l_orderkey
    and l_shipmode in ('MAIL', 'SHIP')
    and l_commitdate < l_receiptdate
    and l_shipdate < l_commitdate
    and l_receiptdate >= to_date('1994-01-01', 'YYYY-MM-DD')
    and l_receiptdate < add_months(to_date('1994-01-01', 'YYYY-MM-DD'), 12)
group by
    l_shipmode
order by
    l_shipmode
L_SHIPMODE HIGH_LINE_COUNT    LOW_LINE_COUNT
MAIL      6202.00          9324.00
SHIP      6200.00          9262.00

```

2 rows processed.
Query Processed in 1.18 seconds.

	10.00	6532.00
11.00	6014.00	
8.00	5937.00	
12.00	5639.00	
13.00	5024.00	
19.00	4793.00	
7.00	4687.00	
17.00	4587.00	
18.00	4529.00	
20.00	4516.00	
15.00	4505.00	
14.00	4446.00	
16.00	4273.00	
21.00	4190.00	
22.00	3623.00	
6.00	3265.00	
23.00	3225.00	
24.00	2742.00	
25.00	2086.00	
5.00	1948.00	
26.00	1612.00	
27.00	1179.00	
4.00	1007.00	
28.00	893.00	
29.00	593.00	
3.00	415.00	
30.00	376.00	
31.00	226.00	
32.00	148.00	
2.00	134.00	
33.00	75.00	
34.00	50.00	
35.00	37.00	
1.00	17.00	
36.00	14.00	
38.00	5.00	
37.00	5.00	
40.00	4.00	
41.00	2.00	
39.00	1.00	

```

-- @(#)13.sql      2.1.6.2
-- TPC-H/TPC-R Customer Distribution Query (Q13)
-- Functional Query Definition
-- Approved February 1998

```

```

select
    c_count,
    count(*) as custdist
from
    (
select
    c_custkey,
    count(o_orderkey) as c_count
from
    customer, orders where
    c_custkey = o_custkey(+)
    and o_comment(+) not like '%special%requests%'
group by
    c_custkey
) c_orders
group by
    c_count
order by
    custdist desc,
    c_count desc
C_COUNT      CUSTDIST
0.00          50005.00
9.00          6641.00

```

```

42 rows processed.
Query Processed in 1.30 seconds.

```

```

-- @(#)14.sql      2.1.6.2
-- TPC-H/TPC-R Promotion Effect Query (Q14)
-- Functional Query Definition
-- Approved February 1998
select
    100.00 * sum(case
        when p_type like 'PROMO%'
            then l_extendedprice * (1 - l_discount)
        else 0
    end) / sum(l_extendedprice * (1 - l_discount)) as
    promo_revenue
from
    lineitem,
    part
where
    l_partkey = p_partkey
    and l_shipdate >= date '1995-09-01'
    and l_shipdate < date '1995-09-01' + interval '1' month
PROMO_REVENUE
16.38

```

1 row• processed.
Query Processed in 1.07 seconds.

```
-- @(#15.sql 2.1.6.2
-- TPC-H/TPC-R Top Supplier Query (Q15)
-- Functional Query Definition
-- Approved February 1998

with revenue
as (select
l_suppkey supplier_no,
sum(l_extendedprice * (1 - l_discount)) total_revenue
from
lineitem
where
l_shipdate >= to_date('1996-01-01', 'YYYY-MM-DD')
and l_shipdate < add_months(to_date('1996-01-01', 'YYYY-MM-DD'), 3)
group by
l_suppkey)
select
s_suppkey,
s_name,
s_address,
s_phone,
total_revenue
from
supplier,
revenue
where
s_suppkey = supplier_no
and total_revenue = (
select
max(total_revenue)
from
revenue )
order by
s_suppkey

S_SUPPKEY      S_NAME
S_ADDRESS          S_PHONE      TOTAL_REVENUE
8449.00    Supplier#000008449
Wp34zim9qYFbVctdW           20-469-856-8873 1772627.21
```

1 row• processed.
Query Processed in 7.95 seconds.

```
-- @(#16.sql      2.1.6.2
-- TPC-H/TPC-R Parts/Supplier Relationship Query (Q16)
-- Functional Query Definition
-- Approved February 1998
```

```
select
p_brand,
p_type,
p_size,
count(distinct ps_suppkey) as supplier_cnt
from
partsupp,
part
where
p_partkey = ps_partkey
and p_brand <> 'Brand#45'
and p_type not like 'MEDIUM POLISHED%'
and p_size in (49, 14, 23, 45, 19, 3, 36, 9)
and ps_suppkey not in (
```

```
select
s_suppkey
from
supplier
where
s_comment like '%Customer%Complaints%'
)
group by
p_brand,
p_type,
p_size
order by
supplier_cnt desc,
p_brand,
p_type,
p_size
```

P_BRAND	P_TYPE	P_SIZE	SUPPLIER_CNT
Brand#41	MEDIUM BRUSHED TIN	3.00	28.00
Brand#54	STANDARD BRUSHED COPPER	14.00	27.00
Brand#11	STANDARD BRUSHED TIN	23.00	24.00
Brand#11	STANDARD BURNISHED BRASS	36.00	24.00
Brand#15	MEDIUM ANODIZED NICKEL	3.00	24.00
Brand#15	SMALL ANODIZED BRASS	45.00	24.00
Brand#15	SMALL BURNISHED NICKEL	19.00	24.00
Brand#21	MEDIUM ANODIZED COPPER	3.00	24.00
Brand#22	SMALL BRUSHED NICKEL	3.00	24.00
Brand#22	SMALL BURNISHED BRASS	19.00	24.00
Brand#25	MEDIUM BURNISHED COPPER	36.00	24.00
Brand#31	PROMO POLISHED COPPER	36.00	24.00
Brand#33	LARGE POLISHED TIN	23.00	24.00
Brand#33	PROMO POLISHED STEEL	14.00	24.00
Brand#35	PROMO BRUSHED NICKEL	14.00	24.00
Brand#41	ECONOMY BRUSHED STEEL	9.00	24.00
Brand#41	ECONOMY POLISHED TIN	19.00	24.00
Brand#41	LARGE PLATED COPPER	36.00	24.00
Brand#42	ECONOMY PLATED BRASS	3.00	24.00
Brand#42	STANDARD POLISHED TIN	49.00	24.00
Brand#43	PROMO BRUSHED TIN	3.00	24.00
Brand#43	SMALL ANODIZED COPPER	36.00	24.00
Brand#44	STANDARD POLISHED NICKEL	3.00	24.00
Brand#52	ECONOMY PLATED TIN	14.00	24.00
Brand#52	STANDARD BURNISHED NICKEL	3.00	24.00
Brand#53	MEDIUM ANODIZED STEEL	14.00	24.00
Brand#14	PROMO ANODIZED NICKEL	45.00	23.00
Brand#32	ECONOMY PLATED BRASS	9.00	23.00
Brand#52	SMALL ANODIZED COPPER	3.00	23.00
Brand#11	ECONOMY BRUSHED COPPER	45.00	20.00
Brand#11	ECONOMY PLATED BRASS	23.00	20.00
Brand#11	LARGE BRUSHED COPPER	49.00	20.00
Brand#11	LARGE POLISHED COPPER	49.00	20.00
Brand#12	STANDARD ANODIZED TIN	49.00	20.00
Brand#12	STANDARD PLATED BRASS	19.00	20.00

<deleted>

18314 rows processed.
Query Processed in 1.55 seconds.

```
-- @(#17.sql      2.1.6.2
-- TPC-H/TPC-R Small-Quantity-Order Revenue Query (Q17)
-- Functional Query Definition
-- Approved February 1998
```

```
select
sum(l_extendedprice) / 7.0 as avg_yearly
from
lineitem,
```

```

part
where
p_partkey = l_partkey
and p_brand = 'Brand#23'
and p_container = 'MED BOX'
and l_quantity < (
select
0.2 * avg(l_quantity)
from
lineitem
where
l_partkey = p_partkey
)

AVG_YEARLY
348406.05

1 row processed.
Query Processed in 2.35 seconds.

-- @(#)18.sql      2.1.6.2
-- TPC-H/TPC-R Large Volume Customer Query (Q18)
-- Function Query Definition
-- Approved February 1998

select * from (
select
c_name,
c_custkey,
o_orderkey,
o_orderdate,
o_totalprice,
sum(l_quantity)
from
customer,
orders,
lineitem
where
o_orderkey in (
select
l_orderkey
from
lineitem
group by
l_orderkey having
sum(l_quantity) > 300
)
and c_custkey = o_custkey
and o_orderkey = l_orderkey
group by
c_name,
c_custkey,
o_orderkey,
o_orderdate,
o_totalprice
order by
o_totalprice desc,
o_orderdate
)
where rownum <= 100

C_NAME      C_CUSTKEY      O_ORDERKEY
O_ORDERDATE
O_TOTALPRICE      SUM(L_QUANTITY)
Customer#000128120      128120.00      4722021.00      1994-
04-07
544089.09      323.00

Customer#000144617    144617.00      3043270.00      1997-
02-12
530604.44      317.00
Customer#000013940    13940.00      2232932.00      1997-
04-13
522720.61      304.00
Customer#000066790    66790.00      2199712.00      1996-
09-30
515531.82      327.00
Customer#000046435    46435.00      4745607.00      1997-
07-03
508047.99      309.00
Customer#000015272    15272.00      3883783.00      1993-
07-28
500241.33      302.00
Customer#000146608    146608.00      3342468.00      1994-
06-12
499794.58      303.00
Customer#000096103    96103.00      5984582.00      1992-
03-16
494398.79      312.00
Customer#000024341    24341.00      1474818.00      1992-
11-
<deleted>

57 rows processed.
Query Processed in 1.50 seconds.

-- @(#)19.sql      2.1.6.2
-- TPC-H/TPC-R Discounted Revenue Query (Q19)
-- Functional Query Definition
-- Approved February 1998

select
sum(l_extendedprice* (1 - l_discount)) as revenue
from
lineitem,
part
where
(
p_partkey = l_partkey
and p_brand = 'Brand#12'
and p_container in ('SM CASE', 'SM BOX', 'SM PACK', 'SM PKG')
and l_quantity >= 1 and l_quantity <= 1 + 10
and p_size between 1 and 5
and l_shipmode in ('AIR', 'AIR REG')
and l_shipinstruct = 'DELIVER IN PERSON'
)
or
(
p_partkey = l_partkey
and p_brand = 'Brand#23'
and p_container in ('MED BAG', 'MED BOX', 'MED PKG', 'MED
PACK')
and l_quantity >= 10 and l_quantity <= 10 + 10
and p_size between 1 and 10
and l_shipmode in ('AIR', 'AIR REG')
and l_shipinstruct = 'DELIVER IN PERSON'
)
or
(
p_partkey = l_partkey
and p_brand = 'Brand#34'
and p_container in ('LG CASE', 'LG BOX', 'LG PACK', 'LG PKG')
and l_quantity >= 20 and l_quantity <= 20 + 10
and p_size between 1 and 15
and l_shipmode in ('AIR', 'AIR REG')
and l_shipinstruct = 'DELIVER IN PERSON'
)

```

)
REVENUE
3083843.06

1 row processed.
Query Processed in 2.38 seconds.

```
-- @(#)20.sql      2.1.6.2
-- TPC-H/TPC-R Potential Part Promotion Query (Q20)
-- Function Query Definition
-- Approved February 1998
```

```
select
s_name,
s_address
from
supplier,
nation
where
s_suppkey in (
select
ps_suppkey
from
partsupp
where
ps_partkey in (
select
p_partkey
from
part
where
p_name like 'forest%'
)
and ps_availqty > (
select
0.5 * sum(l_quantity)
from
lineitem
where
l_partkey = ps_partkey
and l_suppkey = ps_suppkey
and l_shipdate >= to_date ('1994-01-01', 'YYYY-MM-DD')
and l_shipdate < add_months( to_date ('1994-01-01', 'YYYY-MM-DD'),
12)
)
)
and s_nationkey = n_nationkey
and n_name = 'CANADA'
order by
s_name
```

S_NAME	S_ADDRESS
Supplier#000000020	iybAE,RmTymrZVYaFZva2SH,j
Supplier#000000091	YV45D7KfdQanOOZ7q9QxkyGUapU1oOWU6q3
Supplier#000000197	YC2Acon6kjY3zj3Fbxs2k4Vdf7X0cd2F
Supplier#000000226	83qOdU2EYRdPQAQhEtn GRZEd
Supplier#000000285	Br7e1nn1lyxrw6ImgpJ7YdhFDjuBf
Supplier#000000378	FfbhyCxWvcPrO8ltp9
Supplier#000000402	i9Sw4DoyMhzKXCH9By,AYSgmD
Supplier#000000530	0qwCMwobKY OcmLyfRXlagA8ukENJv,
Supplier#000000688	D fw5ocppmZpYBBIPi718hCihLDZ5KhKX
Supplier#000000710	f19YPvOyb QoYwjKC,oPycpGfieBAcwKJo
Supplier#000000736	l6i2nMwVuovfKnuVgaSGK2rDy65DIAFLegiL7
Supplier#000000761	zlSLelQuj2XrvTTFnv7WAcYZGvvMTx882d4

Supplier#000000884 bmhEShejaS

<deleted>

204 rows processed.
Query Processed in 2.13 seconds.

```
-- @(#)21.sql      2.1.6.2
-- TPC-H/TPC-R Suppliers Who Kept Orders Waiting Query (Q21)
-- Functional Query Definition
-- Approved February 1998
```

```
select * from (
select
s_name,
count(*) numwait
from
supplier,
lineitem l1,
orders,
nation
where
s_suppkey = l1.l_suppkey
and o_orderkey = l1.l_orderkey
and o_orderstatus = 'F'
and l1.l_receiptdate > l1.l_commitdate
and exists (
select
*
from
lineitem l2
where
l2.l_orderkey = l1.l_orderkey
and l2.l_suppkey <> l1.l_suppkey
)
and not exists (
select
*
from
lineitem l3
where
l3.l_orderkey = l1.l_orderkey
and l3.l_suppkey <> l1.l_suppkey
and l3.l_receiptdate > l3.l_commitdate
)
and s_nationkey = n_nationkey
and n_name = 'SAUDI ARABIA'
group by
s_name
order by
numwait desc,
s_name)
where rownum <= 100
```

S_NAME	NUMWAIT
Supplier#000002829	20.00
Supplier#000005808	18.00
Supplier#00000262	17.00
Supplier#00000496	17.00
Supplier#000002160	17.00
Supplier#000002301	17.00
Supplier#000002540	17.00
Supplier#000003063	17.00
Supplier#000005178	17.00
Supplier#000008331	17.00
Supplier#000002005	16.00
Supplier#000002095	16.00
Supplier#000005799	16.00
Supplier#000005842	16.00

```
Supplier#000006450    16.00
Supplier#000006939    16.00
```

```
<deleted>
```

```
100 rows processed.
Query Processed in 5.43 seconds.
```

```
-- @(#22.sql 2.1.4.2
-- TPC-H/TPC-R Global Sales Opportunity Query (Q22)
-- Functional Query Definition
-- Approved February 1998
```

```
select
entrycode,
count(*) as numcust,
sum(c_acctbal) as totacctbal
from
(
select
substr(c_phone, 1, 2) as entrycode,
c_acctbal
from
customer
where
substr(c_phone,1, 2) in
('13', '31', '23', '29', '30', '18', '17')
and c_acctbal > (
select
avg(c_acctbal)
from
customer
where
c_acctbal > 0.00
and substr(c_phone, 1, 2) in
('13', '31', '23', '29', '30', '18', '17')
)
```

```
and not exists (
select
*
from
orders
where
o_custkey = c_custkey
)
) custsale
group by
entrycode
order by
entrycode
```

CNTRYCODE	NUMCUST	TOTACCTBAL
13	888.00	6737713.99
17	861.00	6460573.72
18	964.00	7236687.40
23	892.00	6701457.95
29	948.00	7158866.63
30	909.00	6808436.13
31	922.00	6806670.18

```
7 rows processed.
Query Processed in 1.35 seconds.
```

```
Ended Executing this Stream at Mon Apr 23 16:26:41 2007
```

```
Stream Started at 1177370745.79
Stream Ended at 1177370801.15
Stream Processed in 55.37 seconds
```

```
SQL statements processed: 22
```

Appendix E Seed and Input Parameters

E.1 Seed

0525095659

E.2 qp1.0

14	1995-01-01					
2	31	TIN	EUROPE			
9	chiffon					
20	snow	1997-01-01		IRAN		
6	1996-01-01		0.09	25		
17	Brand#15	JUMBO CAN				
18	315					
8	VIETNAM		ASIA	STANDARD BRUSHED		
STEEL						
21	UNITED STATES					
13	special requests					
3	BUILDING		1995-03-20			
22	20	29	15	27	32	21
	23					
16	Brand#11	ECONOMY BRUSHED			8	45
	9	19	18	15	37	46
4	1996-02-01					
11	EGYPT	0.0000000033				
15	1993-01-01					
1	93					
10	1993-04-01					
19	Brand#45	Brand#53	Brand#25	8	20	24
5	AMERICA		1996-01-01			
7	VIETNAM		CANADA			
12	REG AIR	AIR	1995-01-01			

E.3 qp1.1

21	MOZAMBIQUE					
3	HOUSEHOLD	1995-03-05				
18	312					
5	ASIA	1997-01-01				
11	PERU	0.0000000033				
7	JORDAN	BRAZIL				
6	1997-01-01	0.06	25			
20	floral	1996-01-01		ALGERIA		
17	Brand#11	WRAP BOX				
12	FOB	AIR	1995-01-01			
16	Brand#41	SMALL ANODIZED	26		23	
	42	17	24	12		7
15	1996-01-01					
13	special	accounts				
10	1994-01-01					
2	18	COPPER	AFRICA			
8	JORDAN	MIDDLE EAST		STANDARD PLATED		
STEEL						
14	1995-01-01					
19	Brand#52	Brand#41	Brand#25	3	10	
9	blue					
22	32	26	30	21	11	
	12					
1	101					
4	1993-11-01					

E.4 qp1.2

6	1997-01-01	0.03	24			
17	Brand#13 WRAP JAR					
14	1996-01-01					
16	Brand#31 LARGE PLATED	23	6	32		
	30 11 2 1		35			
19	Brand#54 Brand#23 Brand#24	8	11	28		
10	1994-10-01					
9	aquamarine					
2	6 STEEL EUROPE					
15	1993-01-01					
8	ETHIOPIA AFRICA STANDARD ANODIZED					
STEEL						
5	EUROPE 1997-01-01					
22	12 15 25 31		19	18		
	16					
12	MAIL AIR 1995-01-01					
7	ETHIOPIA ALGERIA					
13	special accounts					
18	314					
1	109					
4	1996-05-01					
20	plum 1994-01-01 KENYA					
3	AUTOMOBILE 1995-03-22					
11	ETHIOPIA 0.0000000033					
21	INDIA					

E.5 qp1.3

8	RUSSIA	EUROPE	PROMO	POLISHED	COPPER
5	MIDDLE EAST		1997-01-01		
4	1994-02-01				
6	1997-01-01	0.09	25		
17	Brand#15	WRAP CAN			
7	RUSSIA	UNITED STATES			
1	117				
18	315				
22	16	13	18	27	28
	12				11
14	1996-01-01				
9	violet				
10	1993-08-01				
15	1996-01-01				
11	CHINA	0.0000000033			
20	burnished	1993-01-01	EGYPT		
2	44	BRASS	AMERICA		
21	ARGENTINA				
19	Brand#51	Brand#11	Brand#13	3	12
13	pending	accounts			24
16	Brand#11	PROMO	POLISHED	48	40
	10	8	12	15	36
12	TRUCK	AIR	1996-01-01		
3	HOUSEHOLD		1995-03-07		

E.6 apl.4

5 AFRICA 1997-01-01
21 CHINA
14 1996-01-01
19 Brand#13 Brand#44 Brand#12 9 13 20
15 1994-01-01
17 Brand#12 SM BOX

12	RAIL	MAIL	1994-01-01			1	80				
6			1997-01-01	0.06	25	5	ASIA	1993-01-01			
4			1996-09-01			16	Brand#12	STANDARD POLISHED	4	20	
9			spring			27	3	7	33	37	11
8	KENYA	AFRICA	PROMO BURNISHED COPPER			2	STEEL	MIDDLE EAST			
16	Brand#51	MEDIUM ANODIZED		6	12	14	1997-01-01				
9	1	10	20	42	15	19	Brand#12	Brand#15	Brand#51	9	15
11	FRANCE	0.0000000033				20	honeydew	1993-01-01		UNITED KINGDOM	
2	32	NICKEL	EUROPE			17	Brand#21	SM CAN			
10			1994-05-01			21	BRAZIL				
18			313								
1			64								
13			pending accounts								
7	KENYA	RUSSIA									
22	26	32	16	30	17	22					
3	AUTOMOBILE	1995-03-24									
20	metallic	1996-01-01	ROMANIA								

E.7 qp1.5

21		IRAN					22				
15		1996-01-01					15	31	11	10	
4		1994-06-01					8	MOROCCO	AFRICA		
6		1997-01-01	0.04	24			20	ECONOMY ANODIZED COPPER			
7	FRANCE	SAUDI ARABIA					21	saddle	1996-01-01		
16	Brand#32	ECONOMY BURNISHED					2	JORDAN			
	20	49	21	3			4	ROMANIA			
	5	12	22	24			45	BRASS	AMERICA		
19	Brand#15	Brand#32	Brand#12	4			18	1994-10-01			
	14	27					8				
18	314						2				
14	1996-01-01						4				
22	26	19	15	18			22	15	31	11	10
	10	27	22				17	16	23	19	
11	ROMANIA	0.0000000033					Brand#23	LG BOX			
13	pending deposits						88	SAUDI ARABIA	0.0000000033		
3	FURNITURE	1995-03-09					11	pink			
1	72						9	Brand#25	Brand#43	Brand#55	5
2	19	COPPER	AMERICA				19	16	20		
5	AMERICA	1997-01-01					3	FURNITURE	1995-03-11		
8	FRANCE	EUROPE	ECONOMY				14	pending deposits			
	BRUSHED COPPER						5	EUROPE	1993-01-01		
20	wheat	1995-01-01					7	MOROCCO	PERU		
	INDONESIA						10	1994-09-01			
12	AIR	RAIL	1996-01-01				16	Brand#52	MEDIUM BRUSHED		
17	Brand#24	SM JAR					42	41	20	27	
10		1993-02-01					44	4	21	10	
9	seashell						6	1993-01-01	0.07	25	

qpl.6

10		1993-11-01					19	Brand#22	Brand#31	Brand#54	10	17	27
3	AUTOMOBILE	1995-03-26					1	96					
15		1994-01-01					15	1994-01-01					
13	pending deposits						17	Brand#25	LG JAR				
6	1993-01-01	0.09	25				5	MIDDLE EAST	1993-01-01				
8	UNITED KINGDOM	EUROPE	ECONOMY PLATED				8	GERMANY	EUROPE	LARGE BRUSHED TIN			
COPPER							9	orange					
9	rose						12	MAIL	TRUCK	1997-01-01			
7	UNITED KINGDOM	ROMANIA					14	1997-01-01					
4		1997-01-01					7	GERMANY	MOROCCO				
11	GERMANY	0.0000000033					4	1997-05-01					
22	33	29	10	18	21	20	3	MACHINERY	1995-03-28				
	28						20	cyan	1995-01-01	CANADA			
18	312						16	Brand#32	PROMO BURNISHED	44	30		
12	REG AIR	RAIL	1997-01-01				24	7	41	39	28	3	
							1993-01-01	0.04	24				
							22	19	30	29	11	10	14
							2	1993-01-01	0.04	24			
							10	1993-06-01					
							13	pending deposits					
							2	33	NICKEL	MIDDLE EAST			
							28	IRAQ					
							21	315					
							18						

E.8 qp1.7

							18						
							8						
							20						
							21						
							2						
							4						

E.9 qp1.8

							19						
							1						
							15						
							17						
							5						
							8						
							9						
							12						
							14						
							7						
							4						
							3						
							20						
							16						
							24						
							7						
							22						
							19						
							30						
							29						
							11						
							10						
							28						
							10						
							13						
							2						
							33						
							NICKEL	MIDDLE EAST					
							IRAQ						
							315						

E.10**qp1.9**

8 UNITED STATES AMERICA
13 LARGE PLATED TIN
2 pending deposits
21 TIN ASIA
20 orange 1993-01-01
PERU
17 Brand#22 LG CAN
3 FURNITURE 1995-03-13
6 1993-01-01 0.09 25
21 EGYPT
18 313
11 VIETNAM 0.0000000033
19 Brand#24 Brand#14 Brand#44 5
18 23
10 1994-03-01
15 1997-01-01
4 1995-02-01
22 20 28 25 21
16 1993-01-01
1 104
7 UNITED STATES KENYA
12 TRUCK SHIP 1997-01-01
9 mint
14 1997-01-01
5 AMERICA 1993-01-01
16 Brand#12 SMALL PLATED 19
41 20 36 29
31 23 38

E.11**qp1.10**

6 1994-01-01 0.07 25
15 1994-01-01
18 314
17 Brand#24 MED BOX
12 RAIL TRUCK 1993-01-01
1 112
7 MOZAMBIQUE JAPAN
2 8 STEEL MIDDLE EAST
22 17 12 21 18
29 13 24
13 unusual packages
VIETNAM
10 1994-12-01
14 1993-01-01
9 linen
3 MACHINERY 1995-03-30
16 Brand#52 LARGE BRUSHED 24
3 17 2 41
23 20 19
20 bisque 1997-01-01
GERMANY
19 Brand#31 Brand#52 Brand#43 10
19 30
11 INDONESIA 0.0000000033
4 1997-09-01
8 MOZAMBIQUE AFRICA
LARGE ANODIZED TIN
5 ASIA 1994-01-01

E.12**qp2.0**

14 1995-01-01
2 31 TIN EUROPE
9 chiffon
20 snow 1997-01-01 IRAN
6 1996-01-01 0.09 25
17 Brand#15 JUMBO CAN
18 315
8 VIETNAM ASIA STANDARD BRUSHED
STEEL
21 UNITED STATES
13 special requests
3 BUILDING 1995-03-20
22 20 29 15 27 32 21
23
16 Brand#11 ECONOMY BRUSHED 8 45
9 19 18 15 37 46
4 1996-02-01
11 EGYPT 0.0000000033
15 1993-01-01
1 93
10 1993-04-01
19 Brand#45 Brand#53 Brand#25 8 20 24
5 AMERICA 1996-01-01
7 VIETNAM CANADA
12 REG AIR AIR 1995-01-01

E.13**qp2.1**

21 MOZAMBIQUE
3 HOUSEHOLD 1995-03-05
18 312
5 ASIA 1997-01-01
11 PERU 0.0000000033
7 JORDAN BRAZIL
6 1997-01-01 0.06 25
20 floral 1996-01-01 ALGERIA
17 Brand#11 WRAP BOX
12 FOB AIR 1995-01-01
16 Brand#41 SMALL ANODIZED 26 23 20
42 17 24 12 7
15 1996-01-01
13 special accounts
10 1994-01-01
2 18 COPPER AFRICA
8 JORDAN MIDDLE EAST STANDARD PLATED
STEEL
14 1995-01-01
19 Brand#52 Brand#41 Brand#25 3 10 21
9 blue
22 32 26 30 21 11 31
12
1 101
4 1993-11-01

E.14**qp2.2**

6 1997-01-01 0.03 24
17 Brand#13 WRAP JAR
14 1996-01-01
16 Brand#31 LARGE PLATED 23 6 32
30 11 2 1 35

19	Brand#54	Brand#23	Brand#24	8	11	28	18	313
10	1994-10-01						1	64
9	aquamarine						13	pending accounts
2	6 STEEL	EUROPE					7	KENYA RUSSIA
15	1993-01-01						22	26 32 16 30 17 22
8	ETHIOPIA	AFRICA	STANDARD ANODIZED					13
STEEL							3	AUTOMOBILE 1995-03-24
5	EUROPE	1997-01-01					20	metallic 1996-01-01 ROMANIA
22	12 15 25 31	19	18					16
12	MAIL AIR	1995-01-01						
7	ETHIOPIA	ALGERIA						
13	special accounts							
18	314							
1	109						21	IRAN
4	1996-05-01						15	1996-01-01
20	plum	1994-01-01	KENYA				4	1994-06-01
3	AUTOMOBILE	1995-03-22					6	1997-01-01 0.04 24
11	ETHIOPIA	0.000000033					7	FRANCE SAUDI ARABIA
21	INDIA						16	Brand#32 ECONOMY BURNISHED
								20 49 21 3
								5 12 22 24
							19	Brand#15 Brand#32 Brand#12 4
								14 27
								314
								1996-01-01
							22	26 19 15 18
								10 27 22
								ROMANIA 0.000000033
								pending deposits
								FURNITURE 1995-03-09
								72
								19 COPPER AMERICA
								AMERICA 1997-01-01
								FRANCE EUROPE ECONOMY
								BRUSHED COPPER
								wheat 1995-01-01
								INDONESIA
								AIR RAIL 1996-01-01
								Brand#24 SM JAR
								1993-02-01
								seashell

E.15 qp2.3

8	RUSSIA	EUROPE	PROMO POLISHED COPPER				22	
5	MIDDLE EAST	1997-01-01						26 19 15 18
4	1994-02-01							10 27 22
6	1997-01-01	0.09	25					ROMANIA 0.000000033
17	Brand#15 WRAP CAN							pending deposits
7	RUSSIA	UNITED STATES						FURNITURE 1995-03-09
1	117							72
18	315							19 COPPER AMERICA
22	16 13 18 27	28	11					AMERICA 1997-01-01
								FRANCE EUROPE ECONOMY
	12							BRUSHED COPPER
14	1996-01-01							wheat 1995-01-01
9	violet							INDONESIA
10	1993-08-01							AIR RAIL 1996-01-01
15	1996-01-01							Brand#24 SM JAR
11	CHINA	0.000000033						1993-02-01
20	burnished	1993-01-01	EGYPT					seashell
2	44 BRASS	AMERICA						
21	ARGENTINA							
19	Brand#51	Brand#11	Brand#13 3		12	24		
13	pending accounts							
16	Brand#11	PROMO POLISHED	48		40	3		
10	8 12 15				36			
12	TRUCK AIR	1996-01-01						
3	HOUSEHOLD	1995-03-07						

E.17 qp2.5

							21	IRAN
							15	1996-01-01
							4	1994-06-01
							6	1997-01-01 0.04 24
							7	FRANCE SAUDI ARABIA
							16	Brand#32 ECONOMY BURNISHED
								20 49 21 3
								5 12 22 24
							19	Brand#15 Brand#32 Brand#12 4
								14 27
								314
								1996-01-01
							22	26 19 15 18
								10 27 22
								ROMANIA 0.000000033
								pending deposits
								FURNITURE 1995-03-09
								72
								19 COPPER AMERICA
								AMERICA 1997-01-01
								FRANCE EUROPE ECONOMY
								BRUSHED COPPER
								wheat 1995-01-01
								INDONESIA
								AIR RAIL 1996-01-01
								Brand#24 SM JAR
								1993-02-01
								seashell

E.18 qp2.6

							10	1993-11-01
							3	AUTOMOBILE 1995-03-26
							15	1994-01-01
							13	pending deposits
							6	1993-01-01 0.09 25
							8	UNITED KINGDOM EUROPE ECONOMY PLATED
								COPPER
								9 rose
								7 UNITED KINGDOM ROMANIA
								4 1997-01-01
								11 GERMANY 0.000000033
								22 33 29 10 18 21 20
								28
								312
								12 REG AIR RAIL 1997-01-01
								18 80
								5 ASIA 1993-01-01
								16 Brand#12 STANDARD POLISHED 4 20
								27 3 7 33 37 11
								2 STEEL MIDDLE EAST
								14 1997-01-01
								19 Brand#12 Brand#15 Brand#51 9 15 24

E.16 qp2.4

5	AFRICA	1997-01-01						
21	CHINA							
14	1996-01-01							
19	Brand#13	Brand#44	Brand#12 9		13	20		
15	1994-01-01							
17	Brand#12	SM BOX						
12	RAIL	MAIL	1994-01-01					
6	1997-01-01	0.06	25					
4	1996-09-01							
9	spring							
8	KENYA	AFRICA	PROMO BURNISHED COPPER					
16	Brand#51	MEDIUM ANODIZED		6	12			
9	1	10	20	42	15			
11	FRANCE	0.000000033						
2	32	NICKEL	EUROPE					
10	1994-05-01							

20 honeydew 1993-01-01 UNITED KINGDOM
 17 Brand#21 SM CAN
 21 BRAZIL

E.19 qp2.7

18 313
 8 MOROCCO AFRICA ECONOMY ANODIZED
 COPPER
 20 saddle 1996-01-01 JORDAN
 21 ROMANIA
 2 45 BRASS AMERICA
 4 1994-10-01
 22 15 31 11 10 16 23
 19
 17 Brand#23 LG BOX
 1 88
 11 SAUDI ARABIA 0.000000033
 9 pink
 19 Brand#25 Brand#43 Brand#55 5 16 20
 3 FURNITURE 1995-03-11
 13 pending deposits
 5 EUROPE 1993-01-01
 7 MOROCCO PERU
 10 1994-09-01
 16 Brand#52 MEDIUM BRUSHED 42 41
 20 27 44 4 21 10
 6 1993-01-01 0.07 25
 14 1997-01-01
 15 1996-01-01
 12 FOB RAIL 1997-01-01

E.21
 8
 13
 2
 20
 17
 3
 6
 21
 18
 11
 19
 15
 4
 22
 1
 7
 12
 9
 14
 5
 16
 41
 31

qp2.9
 UNITED STATES AMERICA
 LARGE PLATED TIN
 pending deposits
 21 TIN ASIA
 orange 1993-01-01
 PERU
 Brand#22 LG CAN
 FURNITURE 1995-03-13
 1993-01-01 0.09 25
 EGYPT
 313
 VIETNAM 0.000000033
 Brand#24 Brand#14 Brand#44 5
 18 23
 1994-03-01
 1997-01-01
 1995-02-01
 20 28 25 21
 16 26 33
 104
 UNITED STATES KENYA
 TRUCK SHIP 1997-01-01
 mint
 1997-01-01
 AMERICA 1993-01-01
 Brand#12 SMALL PLATED 19
 41 20 36 29
 31 23 38

E.20 qp2.8

19 Brand#22 Brand#31 Brand#54 10 17 27
 1 96
 15 1994-01-01
 17 Brand#25 LG JAR
 5 MIDDLE EAST 1993-01-01
 8 GERMANY EUROPE LARGE BRUSHED TIN
 9 orange
 12 MAIL TRUCK 1997-01-01
 14 1997-01-01
 7 GERMANY MOROCCO
 4 1997-05-01
 3 MACHINERY 1995-03-28
 20 cyan 1995-01-01 CANADA
 16 Brand#32 PROMO BURNISHED 44 30
 24 7 41 39 28 3
 6 1993-01-01 0.04 24
 22 19 30 29 11 10 14
 28
 10 1993-06-01
 13 pending deposits
 2 33 NICKEL MIDDLE EAST
 21 IRAQ
 18 315
 11 INDIA 0.000000033

E.22 qp2.10
 6 1994-01-01 0.07 25
 15 1994-01-01
 18 314
 17 Brand#24 MED BOX
 12 RAIL TRUCK 1993-01-01
 1 112
 7 MOZAMBIQUE JAPAN
 2 STEEL MIDDLE EAST
 22 17 12 21 18 29 13
 24
 13 unusual packages
 21 VIETNAM
 10 1994-12-01
 14 1993-01-01
 9 linen
 3 MACHINERY 1995-03-30
 16 Brand#52 LARGE BRUSHED 24 3 17
 2 41 23 20 19
 20 bisque 1997-01-01 GERMANY
 19 Brand#31 Brand#52 Brand#43 10 19 30
 11 INDONESIA 0.000000033
 4 1997-09-01
 8 MOZAMBIQUE AFRICA LARGE ANODIZED TIN
 5 ASIA 1994-01-01

Appendix F Benchmark Scripts

F.1 dbtables.sql

```
set echo on
set numwidth 30
spool rdbtablest
SELECT /*+ full(A) */ COUNT(*) FROM LINEITEM A;

SELECT * FROM LINEITEM
WHERE L_ORDERKEY IN
( 4, 26598, 148577, 387431, 56704, 517442, 600000)
AND L_LINENUMBER = 1
ORDER BY L_ORDERKEY;

SELECT * FROM REGION;

SELECT COUNT(*) FROM NATION;

SELECT * FROM NATION
WHERE N_NATIONKEY IN (3,10,14,20)
ORDER BY N_NATIONKEY;

SELECT /*+ full(A) */ COUNT(*) FROM ORDERS A;

SELECT * FROM ORDERS
WHERE O_ORDERKEY IN ( 7, 44065, 287590, 411111, 483876,
599942 )
ORDER BY O_ORDERKEY;

SELECT COUNT(*) FROM PART;

SELECT * FROM PART
WHERE P_PARTKEY IN (1,984,8743,9028,13876,17899,20000)
ORDER BY P_PARTKEY;

SELECT COUNT(*) FROM PARTSUPP;

SELECT* FROM PARTSUPP
WHERE PS_PARTKEY = 3398
AND PS_SUPPKEY = (SELECT MIN(PS_SUPPKEY)
FROM PARTSUPP WHERE PS_PARTKEY = 3398);

SELECT* FROM PARTSUPP
WHERE PS_PARTKEY = 15873
AND PS_SUPPKEY = (SELECT MIN(PS_SUPPKEY)
FROM PARTSUPP WHERE PS_PARTKEY = 15873);

SELECT* FROM PARTSUPP
WHERE PS_PARTKEY = 11394
AND PS_SUPPKEY = (SELECT MIN(PS_SUPPKEY)
FROM PARTSUPP WHERE PS_PARTKEY = 11394);

SELECT* FROM PARTSUPP
WHERE PS_PARTKEY = 6743
AND PS_SUPPKEY = (SELECT MIN(PS_SUPPKEY)
FROM PARTSUPP WHERE PS_PARTKEY = 6743);

SELECT* FROM PARTSUPP
WHERE PS_PARTKEY = 19763
```

```
AND PS_SUPPKEY = (SELECT MIN(PS_SUPPKEY)
FROM PARTSUPP WHERE PS_PARTKEY = 19763);

SELECT COUNT(*) FROM SUPPLIER;

SELECT * FROM SUPPLIER
WHERE S_SUPPKEY IN (83,265,492,784,901,1000)
ORDER BY S_SUPPKEY;

DROP TABLE MINMAX;

CREATE TABLE MINMAX
(TNAME CHAR(15),
KEYMIN INTEGER,
KEYMAX INTEGER);

INSERT INTO MINMAX
SELECT
'LINEITEM_ORD',MIN(L_ORDERKEY),MAX(L_ORDERKEY)
FROM LINEITEM ;

INSERT INTO MINMAX
SELECT
'LINEITEM_NBR',MIN(L_LINENUMBER),MAX(L_LINENUMBER)
FROM LINEITEM;

INSERT INTO MINMAX
SELECT 'ORDERTBL',MIN(O_ORDERKEY),MAX(O_ORDERKEY)
FROM ORDERS;

INSERT INTO MINMAX
SELECT 'CUSTOMER',MIN(C_CUSTKEY),MAX(C_CUSTKEY)
FROM CUSTOMER;

INSERT INTO MINMAX
SELECT 'PART',MIN(P_PARTKEY),MAX(P_PARTKEY)
FROM PART;

INSERT INTO MINMAX
SELECT 'SUPPLIER',MIN(S_SUPPKEY),MAX(S_SUPPKEY)
FROM SUPPLIER;

INSERT INTO MINMAX
SELECT
'PARTSUPP_PART',MIN(PS_PARTKEY),MAX(PS_PARTKEY)
FROM PARTSUPP;

INSERT INTO MINMAX
SELECT
'PARTSUPP_SUPP',MIN(PS_SUPPKEY),MAX(PS_SUPPKEY)
FROM PARTSUPP;

INSERT INTO MINMAX
SELECT 'NATION',MIN(N_NATIONKEY),MAX(N_NATIONKEY)
FROM NATION;

INSERT INTO MINMAX
SELECT 'REGION',MIN(R_REGIONKEY),MAX(R_REGIONKEY)
FROM REGION;

SELECT * FROM MINMAX;
spool off
exit;
```

F.2 firstten.sql

```
set echo on
set numwidth 25
spool count.out
select * from lineitem where rownum < 11;
select * from orders where rownum < 11;
select * from part where rownum < 11;
select * from partsupp where rownum < 11;
select * from supplier where rownum < 11;
select * from customer where rownum < 11;
select * from nation where rownum < 11;
select * from region where rownum < 11;
spool off
exit;
```

F.3 gen_seed.sh

```
#!/bin/ksh

SEED_FILE=$1

#Generate the seed
echo "Setting the random number seed"
PSEED=`date +%m:%d:%H:%M:%S | sed -e 's://g'`
echo "Using ${PSEED} as seed0"
echo ${PSEED} > $SEED_FILE
echo "Done setting the random number seed"
```

F.4 gtime.c

```
/* Copyright (c) 2001, 2002, Oracle Corporation. All rights reserved. */

/*
NAME
  gtime.c - <one-line expansion of the name>

DESCRIPTION
  <short description of facility this file declares/defines>

EXPORT FUNCTION(S)
  <external functions defined for use outside package - one-line
descriptions>

INTERNAL FUNCTION(S)
  <other external functions defined - one-line descriptions>

STATIC FUNCTION(S)
  <static functions defined - one-line descriptions>

NOTES
  <other useful comments, qualifications, etc.>

MODIFIED (MM/DD/YY)
  mpoess 10/17/01 - add serialization level in SQLInit
  mpoess 02/22/01 - add linux changes
  mpoess 08/05/99 - make compile
  mpoess 11/13/98 - fix pdll statement
  pswong 02/19/97 - migrating to version 8
  pswong 04/02/96 - more polishing
  pswong 03/25/96 - polish up
  pswong 03/06/96 - created

*/
#include<stdio.h>
#include<string.h>
#include<setjmp.h>
#include<sys/param.h>
#include<errno.h>
#include<math.h>
#include<string.h>
#include<sys/types.h>
#include<time.h>
#include<stdlib.h>

#include "qexecpl.h"

/* Function Prototypes */

extern double gettime();

/* function prototypes from gen.c */

int get_statement();

/* Declare error handling functions */

void sql_error();
```

```
struct timeval tv;
(void) gettimeofday (&tv, (struct timezone *) 0);
printf ("%-.2f\n", ((double) tv.tv_sec + (1.0e-6 * (double) tv.tv_usec)) )
;
}

/* end of file gtime.c */
```

F.5 qexecpl.c

```
#ifdef RCSID
static char *RCSid =
"$Header: qexecpl.c 17-oct-2001.09:29:47 mpoess Exp $ ";
#endif /* RCSID */

/* Copyright (c) 1999, 2001, Oracle Corporation. All rights reserved. */

/*
NAME
  qexecpl.c - <one-line expansion of the name>

DESCRIPTION
  SQL Execution Engine, Oracle v8, OCI version

PRIVATE FUNCTION(S)
  <list of static functions defined in .c file - with one-line descriptions>
```

```
MODIFIED (MM/DD/YY)
  mpoess 10/17/01 - add serialization level in SQLInit
  mpoess 02/22/01 - add linux changes
  mpoess 08/05/99 - make compile
  mpoess 11/13/98 - fix pdll statement
  pswong 02/19/97 - migrating to version 8
  pswong 04/02/96 - more polishing
  pswong 03/25/96 - polish up
  pswong 03/06/96 - created
```

```
/*
#include <stdio.h>
#include <string.h>
#include <setjmp.h>
#include <sys/param.h>
#include <errno.h>
#include <math.h>
#include <string.h>
#include <sys/types.h>
#include <time.h>
#include <stdlib.h>

#include "qexecpl.h"

/* Function Prototypes */

extern double gettime();

/* function prototypes from gen.c */

int get_statement();

/* Declare error handling functions */

void sql_error();
```

```

/* Other prototypes */

int define_output_variables();
void process_select_list();
void usage();
void SQLInit();
void SQLexec();
void SQLexit();
void *memalloc();
void print_header();
void print_rows();
int OFEN();
void remove_newline();

char logname[UNAME_LEN]; /* username/passwd combo */
char *passwd;

double tr_start = 0.0; /* query start time */ 
double tr_end = 0.0; /* query end time */ 

double s_tr_start = 0.0; /* statement start time */ 
double s_tr_end = 0.0; /* statement end time */ 

/* For our purpose of timing, we will treat comments as delimiters */
/* for queries. Thus, we will collect query timings whenever we */
/* encounter a comment (of course not for the first comment in a */
/* file). */ */

int end_flag = 0; /* flag to indicate that we have reached */
/* the end of a query */

int stmt_cnt = 0; /* Number of statements processed. */
int qry_cnt = 0; /* Number of query processed. */

double product = 1.0; /* cumulative product of query times */
int rows_ret = 0; /* the number of rows fetched */
int num_sel_list = 0; /* the number of select list item */

long num_to_fetch = -1; /* Number of rows to fetch. -1 means fetch all
*/
sltype slist[MAX_SEL_LIST]; /* Array for describing Select List */
*/
dltype *dlist[MAX_SEL_LIST]; /* Array of ptrs for Defining Select
List */

char stmt[SQL_LEN]; /* The SQL statement or comment line. */
char qn[3]; /* Number of the query being executed */
char qnp[3]; /* Number of the previous query executed */
char cmnt[5000]; /* Buffer to save the comment. */
#endif LINUX
FILE *qtemp; /* fd for query template */
FILE *logfile; /* log and report files */
FILE *rep;
#else
FILE *qtemp = stdin; /* fd for query template */
FILE *logfile = stdout; /* log and report files */
FILE *rep = stdout;
#endif
void *defbuf; /* Buffer pointer for ODEFIN */
int deflen = 0; /* Size of data type for ODEFIN */
int deftype = 1; /* Oracle type number for ODEFIN */

int pfmem = PFMEMSIZE; /* Memory to prefetch rows */

time_t tim; /* To get wall clock time */

/* OCI handles */

OCIEnv *tpcenv = NULL;

OCIServer *tpcsrv = NULL;
OCIError *errhp = NULL;
OCISvcCtx *tpcsvc = NULL;
OCISession *tpcusr = NULL;
OCISStmt *curq = NULL;
OCISStmt *cur_dml = NULL;
OCISStmt *cur_ddl = NULL;
OCIParam *tpcpar = NULL;

sword status = OCI_SUCCESS; /* OCI return value */

/* usage: prints the usage of the program */

void usage() {

    fprintf(stderr, "Usage: qexec username/password [q<path name for
query template file>]\n");
    fprintf(stderr, " [l<path name for log>] [r<path name for
reports>]\n\n");
    fprintf(stderr, "Options:\n");
    fprintf(stderr, "q<path for query> : full path name for the query
template file.\n");
    fprintf(stderr, " (default is stdin)\n");
    fprintf(stderr, "l<path name for log> : full path name for log
files\n");
    fprintf(stderr, " (default is stdout)\n");
    fprintf(stderr, "r<path name for reports> : full path name for
reports\n");
    fprintf(stderr, " (default is stdout)\n");
    exit(-1);
}

/* type: 0 if environment handle is passed, 1 if error handle is passwd */

void sql_error(errhp,status,type)
    OCIError *errhp;
    sword status;
    sword type;
{
    char msg[2048];
    ub4 errcode;
    ub4 msglen;
    int i,j;

    switch(status) {
    case OCI_SUCCESS_WITH_INFO:
        fprintf(stderr, "Error: Statement returned with info.\n");
        if (type)
            (void) OCIErrorGet(errhp,1,NULL,(sb4*)&errcode,(text*)msg,
                2048,OCI_HTYPE_ERROR);
        else
            (void) OCIErrorGet(errhp,1,NULL,(sb4*)&errcode,(text*)msg,
                2048,OCI_HTYPE_ENV);
        fprintf(stderr,"%s\n",msg);
        break;
    case OCI_ERROR:
        fprintf(stderr, "Error: OCI call error.\n");
        if (type)
            (void) OCIErrorGet(errhp,1,NULL,(sb4*)&errcode,(text*)msg,
                2048,OCI_HTYPE_ERROR);
        else
            (void) OCIErrorGet(errhp,1,NULL,(sb4*)&errcode,(text*)msg,
                2048,OCI_HTYPE_ENV);
        fprintf(stderr,"%s\n",msg);
        break;
    case OCI_INVALID_HANDLE:
        fprintf(stderr, "Error: Invalid Handle.\n");
        if (type)
            (void) OCIErrorGet(errhp,1,NULL,(sb4*)&errcode,(text*)msg,

```

```

2048,OCI_HTYPE_ERROR);
else
(void) OCIErrorGet(errhp,1,NULL,(sb4*)&errcode,(text*)msg,
2048,OCI_HTYPE_ENV);
fprintf(stderr,"%s\n",msg);
break;
}

/* Rollback just in case */
(void) OCITransRollback(tpcsvc,errhp,OCI_DEFAULT);

fprintf(stderr, "Exiting Oracle...\n");
fflush(stderr);

SQLexit();

exit(1);
}

#endif LINUX
int main(argc,argv)
#else
void main(argc,argv)
#endif
{
    int argc;
    char *argv[];
{

int i,pos,pos2;
int retcode; /* Return code for get_statement */
#ifndef LINUX
logfile=fopen("/dev/stdout","w");
qtemp=fopen("/dev/stdin","rw");
rep=fopen("/dev/stdout","w");
#endif
/* Initialize some variables */

if ((argc > 5) || (argc < 2)) {
    usage();
}

/* argv[1] -- User and Password for Database */

strcpy(logname, argv[1]);

/* Process optional parameters */

argc -= 1;
argv += 1;

while(--argc) {
    ++argv;
    switch(argv[0][0]) {
    case 'q':
        if ((qtemp = fopen(++(argv[0]),"r")) == NULL) {
            fprintf(stderr,"Unable to open file \"%s\n", argv[0]);
            fprintf(stderr,"%s: %s\n", argv[0], strerror(errno));
            exit(-1);
        }
        break;
    case 'r':
        if ((rep = fopen(++(argv[0]),"a")) == NULL) {
            fprintf(stderr,"Unable to open file \"%s\n", argv[0]);
            fprintf(stderr,"%s: %s\n", argv[0], strerror(errno));
            exit(-1);
        }
        break;
    case 'T':
        if ((logfile = fopen(++(argv[0]),"a")) == NULL) {
            fprintf(stderr,"Unable to open file \"%s\n", argv[0]);
            fprintf(stderr,"%s: %s\n", argv[0], strerror(errno));
            exit(-1);
        }
        break;
    }

    /* Do some initialization and establish connection with the database */
    SQLInit();

    /* May want to add some triggering mechanism here */

    time(&tim);
    fprintf(logfile, "Begin Execution at %s\n", ctime(&tim));
    fprintf(rep, "Begin Executing this Stream at %s\n", ctime(&tim));
    /* Get the next statement and start processing it */

    while ((retcode = get_statement()) > 0) {

        switch (retcode) {

        /* If this is a comment, skips it */
        case COMMENT:
            /*if (end_flag) {
                end_flag = 0; /* reset query end flag */
                /* save the comment so that we can print it out later on */
                /* strcpy(cmnt, stmt);
                break;
            } */
            if (stmt[3]== '@') {
                pos=4;
                strcpy(qnp,qn);
                while (stmt[pos] != ')') {
                    pos++;
                }
                pos2=0;
                pos++;
                while (stmt[pos] != '.') {
                    /*printf ("qn %d %c \n",pos2,stmt[pos]);*/
                    qn[pos2]=stmt[pos];
                    pos2++;
                    pos++;
                }
                qn[pos2] = 0;
                /*printf("found a new query: %s\n",qn); */
            }
            /* save the comment so that we can print it out later on */
            strcat(cmnt, stmt);
            break;

        /* if this is a set_row_fetch command */
        case SET_FETCHROW:
            fprintf(logfile,"Setting the number of rows to fetch to: %ld\n",
num_to_fetch);
            break;

        /* if this is a SQL statement */
        case SQL_STMT:

            /* Executes the query */
            SQLexec();

            stmt_cnt++;
            qry_cnt++;
            fflush(rep);
            fflush(logfile);
        }
    }
}

```

```

/*
fprintf(logfile,"\\nStatement Started at %.2f\\n", s_tr_start);
fprintf(logfile,"Statement Ended at %.2f\\n", s_tr_end);

fprintf(logfile,"Statement Processed in %.2f seconds.\\n",
        (s_tr_end - s_tr_start));
fprintf(rep, "Query %s: Execution Time: %.2f started %.2f ended
%.2f\\n",
        qn,(s_tr_end - s_tr_start)s_tr_start,s_tr_end);
fflush(rep);
fflush(logfile);*/
break;

/* Should never reach here */
default:
    fprintf(stderr, "Invalid statement type!!\\n");
    SQLexit();
    break;
}

/* Get Timing for the last query */

tr_end = gettime();

fprintf(logfile,"Query Processed in %.2f seconds.\\n\\n", (tr_end -
s_tr_start));

/* print comments for this query that we have saved */

/* fprintf(logfile, "%s\\n", cmnt); */

/* fprintf(rep, "Query %s : Execution time %.2f\\n", qn,(tr_end -
s_tr_start));*/
fprintf(rep, "Query %s: Execution Time: %.2f started %.2f ended
%.2f\\n",
        qn,(tr_end - s_tr_start),s_tr_start,tr_end);

time(&tim);
fprintf(logfile,"\\nEnded Executing this Stream at %s\\n", ctime(&tim));
fprintf(logfile,"\\nStream Started at %.2f\\n", tr_start);
fprintf(logfile,"Stream Ended at %.2f\\n", tr_end);
fprintf(logfile,"Stream Processed in %.2f seconds\\n\\n", (tr_end -
tr_start));

fprintf(rep,"\\nEnded Executing this Stream at %s\\n", ctime(&tim));
fprintf(rep,"\\nStream Started at %.2f\\n", tr_start);
fprintf(rep,"Stream Ended at %.2f\\n", tr_end);
fprintf(rep,"Stream Processed in %.2f seconds\\n\\n",
        (tr_end - tr_start));

fprintf(logfile, "\\nSQL statements processed: %d\\n", stmt_cnt);
/*fprintf(logfile, "Queries processed: %d\\n", qry_cnt);*/

fflush(rep);
fflush(logfile);

/* Close the query template file */

fclose(qtemp);

/* Disconnect from ORACLE. */

SQLexit();
exit(0);
}

/* SQLinit(): Perform initialization tasks. */
/*      Logs on to Oracle, opens some files and open a cursor for */
/*      later use. */
void SQLinit() {
    int i;

    /* preallocate MAX_PREALLOC members of the dlist array */
    /*
    /* initializes others to NULL so that we can determine who to free later
    */

    for (i=0; i<MAX_SEL_LIST; i++) {
        if (i < MAX_PREALLOC) {
            dlist[i] = (dltype *) memalloc (sizeof(dltype));
            dlist[i]->defhdl = NULL;
            /* OCIalloc(curq,&(dlist[i]->defhdl),OCI_HTYPE_DEFINE); */
        }
        else
            dlist[i] = NULL;
    }

    /* Connect to ORACLE. Program will call sql_error()
     * if an error occurs in connecting to the default database. */
    (void) OCIInitialize(OCI_DEFAULT,(dvoid *)0,0,0,0);

    if((status=OCIEnvInit((OCIEnv **)&tpcenv,OCI_DEFAULT,0,(dvoid
    **))!=
    OCI_SUCCESS)
    sql_error(tpcenv, status, 0);

    OCIalloc(tpcenv,&errhp,OCI_HTYPE_ERROR);
    OCIalloc(tpcenv,&curq,OCI_HTYPE_STMT);
    OCIalloc(tpcenv,&cur_dml,OCI_HTYPE_STMT);
    OCIalloc(tpcenv,&cur_ddl,OCI_HTYPE_STMT);
    OCIalloc(tpcenv,&tpcsvc,OCI_HTYPE_SVCCTX);
    OCIalloc(tpcenv,&tpcsrv,OCI_HTYPE_SERVER);
    OCIalloc(tpcenv,&tpcusr,OCI_HTYPE_SESSION);

    /* get username and password */

    passwd = strchr(logname, '/');
    *passwd = '\\0';
    passwd++;

    if ((status = OCIServerAttach(tpcsrv,errhp,(text
    *0,0,OCI_DEFAULT)) != OCI_SUCCESS)
    sql_error(errhp,status,1);

    OCIaset(tpcsvc,OCI_HTYPE_SVCCTX,tpcsrv,0,OCI_ATTR_SERVER
    ,errhp);

    OCIaset(tpcsrv,OCI_HTYPE_SESSION,logname,strlen(logname),OCI_
    ATTR_USERNAME,
    errhp);

    OCIaset(tpcusr,OCI_HTYPE_SESSION,passwd,strlen(passwd),OCI_A
    TTR_PASSWORD,
    errhp);

    if ((status = OCISessionBegin(tpcsvc, errhp, tpcusr,
    OCI_CRED_RDBMS,
    OCI_DEFAULT)) !=
    OCI_SUCCESS)
    sql_error(errhp,status,1);

    OCIaset(tpcusr,OCI_HTYPE_SESSION,passwd,strlen(passwd),OCI_A
    TTR_PASSWORD,
    errhp);

    if ((status = OCISessionBegin(tpcsvc, errhp, tpcusr,
    OCI_CRED_RDBMS,
    OCI_DEFAULT)) !=
    OCI_SUCCESS)
    sql_error(errhp,status,1);

    OCIaset(tpcsvc,OCI_HTYPE_SVCCTX,tpcusr,0,OCI_ATTR_SESSIO
    N,errhp);

    /*

```

```

if ((status=OCILogon((OCIEnv *)tpcenv,(OCIError
*)errhp,(OCISvcCtx *)tpcsvc,
(text *)logname, strlen(logname), (text
*)passwd,
strlen(passwd), (text *) 0, 0)) !=

OCI_SUCCESS)
    sql_error(errhp, status, 1);
*/
printf("\nConnected to ORACLE as user: %s\n\n", logname);

}

/* SQLexec() Executes the SQL statement.
/* Parse the SQL statement. */
/* If DDL or DML statements, execute right away. */
/* Else describe and define select list outputs,
execute and fetch results. */

void SQLexec()
{
int i;
ub2 stmttyp = OCI_STMT_SELECT; /* default is a SELECT
statement */

/* Clause 5.3.6.2: QI(i,s) is the time between the first character */
/* of this query text is submitted and the first */
/* character of the next query text is submitted. */

if (qry_cnt) {
    time(&tim);
    s_tr_end = gettime();
    fprintf(logfile,"Query Processed in %.2f seconds.\n\n",
(s_tr_end - s_tr_start));

/* print comments for this query that we have saved */

/* fprintf(logfile, "%s\n", cmnt); */

/*fprintf(rep, "Query %s : Execution time %.2f\n", qnp,(s_tr_end -
s_tr_start));*/
    fprintf(rep, "Query %s: Execution Time: %.2f started %.2f ended
%.2f\n",
qnp,(s_tr_end - s_tr_start),s_tr_start,s_tr_end);

/* Let's fflush stuff so that we can see what's going on */

fflush(logfile);
fflush(rep);
}
else
    tr_start = gettime();

s_tr_start = gettime();

/* prepare the statement */

if ((status = OCIStmtPrepare(curq, errhp, (text*) stmt, (ub4)
strlen(stmt),
OCI_NTV_SYNTAX,
OCI_DEFAULT)) != OCI_SUCCESS)
    sql_error(errhp,status,1);

/* Prints the query text and comment to the logfile */

sprintf(logfile, "\n%$s\n", cmnt);
cmnt[0]=0;
printf(logfile, "\n%$s\n", stmt);

/*
/* if this is a DDL or DML statement, execute it right away */
/* only worries about SELECT statements right now, cannot */
/* execute a stored PL/SQL procedure in thiie version */
*/

OCIaget(curq,OCI_HTYPE_STMT,&stmttyp,NULL,OCI_ATTR_STM
T_TYPE,errhp);

if (stmttyp != OCI_STMT_SELECT) {
    OCIsexec(tpcsvc,curq,errhp,1);
    return;
}

/* otherwise, this is a select statement */
/* Describe and define output variables */

/* first let's execute it to get the select-list definition */

OCIaset(curq, OCI_HTYPE_STMT, &pfmem, 0,
OCI_ATTR_PREFETCH_MEMORY, errhp);

OCIsexec(tpcsvc,curq,errhp,0);

num_sel_list = define_output_variables();

/* Executes the query and fetches the rows */

(void) process_select_list(num_sel_list);

/* Need to get the number of rows fetched first */
/* since the following statments will screw it up */

OCIaget(curq,OCI_HTYPE_STMT,&rows_ret,NULL,OCI_ATTR_RO
W_COUNT,errhp);

/* To control memory usage, let's free up the extra dlist entries */
/* that we have allocated. */

i=MAX_PREALLOC;
while(dlist[i] != NULL) {
    free(dlist[i]);
    dlist[i+1] = NULL;
}

/* reset set_fetchrows */

num_to_fetch = -1;

}

void SQLexit() {

int i;

OCILogoff(tpcsvc,errhp);
OCIhfree(tpcenv,OCI_HTYPE_STMT);
OCIhfree(tpcsvc,OCI_HTYPE_SVCCTX);
OCIhfree(tpcsrv,OCI_HTYPE_SERVER);
OCIhfree(tpcusr,OCI_HTYPE_SESSION);

/* free all memory */

for (i=0; i<MAX_SEL_LIST; i++) {
    if (dlist[i] != NULL) {
        free(dlist[i]);
    }
}

/* Flush all output */

```

```

fflush(rep);
fflush(logfile);

}

/* define_output_variables(): Describe and define select-list items for */
/*          a query statement.                                     */
/*          Returns the number of select-list items   */
/*          for this query.           */

int define_output_variables()
{
    int i;
    int retflag = 0;

    for (i=0; i<MAX_SEL_LIST; i++) {
        slist[i].buflen = MAX_COLNAME_SIZE;

        if (OCIParamGet(curq, OCI_HTYPE_STMT, errhp, (dvoid **) &tpepar,
                        POS(i)) != OCI_SUCCESS)
            break;

        /* dszie and nullok fields of dlist not used */

        OCIaget(tpepar, OCI_DTYPE_PARAM, &(slist[i].dbsize),
                NULL, OCI_ATTR_DATA_SIZE, errhp);
        OCIaget(tpepar, OCI_DTYPE_PARAM, &(slist[i].dtype),
                NULL, OCI_ATTR_DATA_TYPE, errhp);
        OCIaget(tpepar, OCI_DTYPE_PARAM, &(slist[i].buf),
                &(slist[i].buflen), OCI_ATTR_NAME, errhp);
        OCIaget(tpepar, OCI_DTYPE_PARAM, &(slist[i].precision),
                NULL, OCI_ATTR_PRECISION, errhp);
        OCIaget(tpepar, OCI_DTYPE_PARAM, &(slist[i].scale),
                NULL, OCI_ATTR_SCALE, errhp);

        /* For formatting purpose, remove trailing blanks in select-list name.
        */
    }

    /* if (slist[i].buflen < MAX_COLNAME_SIZE)
       (slist[i].buf)[slist[i].buflen] = '\0';
    */

    /* Well, we need to allocate for entries for dlist */

    if (i >= MAX_PREALLOC) {
        dlist[i] = (dltype *) memalloc(sizeof(dltype));
        dlist[i]->defhdl = NULL;
    }

    /* Let's check the sizes and types for this select list item */

    switch (slist[i].dtype) {

        case OCI_TYPECODE_NUMBER:
            /* The odesc will not give a good estimate to the scale if */
            /* no scale was given in the Oracle table definition.      */

# ifdef HAVE_SCALE
            if (slist[i].scale != 0) {
                defbuf = (double *) dlist[i]->fbuf;
                deflen = FLT;
                dtype = OCI_TYPECODE_DOUBLE;
                slist[i].dtype = OCI_TYPECODE_DOUBLE;
            } else {
                defbuf = (int *) dlist[i]->ibuf;
                deflen = INT;
                dtype = OCI_TYPECODE_INTEGER;
                slist[i].dtype = OCI_TYPECODE_INTEGER;
            }
# else
                defbuf = (double *) dlist[i]->fbuf;
                deflen = FLT;
                dtype = OCI_TYPECODE_FLOAT;
                slist[i].dtype = OCI_TYPECODE_FLOAT;
# endif /* HAVE_SCALE */

                break;
            default:
                /* default is character string */

                defbuf = (char **) dlist[i]->sbuf;
                deflen = MAX_STR_LEN;
                dtype = SQLT_STR;
                /* deftype = OCI_TYPECODE_CHAR; */
                break;
            }

            /* Define the column */

            if ((status=OCIDefineByPos(curq,&(dlist[i]->defhdl),errhp,POS(i),
                                      defbuf,deflen,dtype,NULL,
                                      dlist[i]->rlen,NULL,OCI_DEFAULT))!=OCI_SUCCESS)
                sql_error(errhp,status,1);
        }
        return i;
    }

    /* process_select_list(): Fetch rows from a query.           */
    /* process_select_list(num)
       int num;          /* number of select list items */
    {
        int i,j;
        int ntf;
        int num_so_far;
        sword stats = OCI_SUCCESS;

        /* Print the headers for the query execution result */

        print_header(num);

        /* See if we need to limit the rows to fetch */

        ntf = (num_to_fetch >= 0) ? num_to_fetch : MAX_ARRAY;

        /* Fetch the rows and print them out */

        if ((ntf > MAX_ARRAY) || (num_to_fetch == -1)) {
            stats = OCISmtFetch(curq, errhp, MAX_ARRAY,
                                OCI_FETCH_NEXT, OCI_DEFAULT);

            OCIaget(curq,OCI_HTYPE_STMT,&rows_ret,NULL,OCI_ATTR_RO
                    W_COUNT,errhp);

            print_rows(num,rows_ret);

            /* To avoid 1022 from OFEN */
            /* More rows to fetch... */
        }
    }
}

```

```

if (stats != OCI_NO_DATA) {
    if (num_to_fetch == -1) {
        while ((stats =
OCISStmtFetch(curq,errhp,MAX_ARRAY,OCI_FETCH_NEXT,
                OCI_DEFAULT)) ==
OCI_SUCCESS) {
            OCIaget(curq,OCI_HTYPE_STMT,&num_so_far,NULL,
                    OCI_ATTR_ROW_COUNT,errhp);
            print_rows(num,(num_so_far-rows_ret));
            rows_ret = num_so_far;
        }
        /* Print the final rows */
        OCIaget(curq,OCI_HTYPE_STMT,&num_so_far,NULL,
                OCI_ATTR_ROW_COUNT,errhp);
        print_rows(num,(num_so_far-rows_ret));
        rows_ret = num_so_far;
    } else {
        ntf := MAX_ARRAY;

        while ((stats = OCISStmtFetch(curq,errhp,
                ((ntf>MAX_ARRAY) ?
MAX_ARRAY:ntf),
                OCI_FETCH_NEXT,
                OCI_DEFAULT)) ==
OCI_SUCCESS) {
            ntf := MAX_ARRAY;
            OCIaget(curq,OCI_HTYPE_STMT,&num_so_far,NULL,
                    OCI_ATTR_ROW_COUNT,errhp);
            print_rows(num,(num_so_far-rows_ret));
            rows_ret = num_so_far;
            if (ntf <= 0) break;
        }
        OCIaget(curq,OCI_HTYPE_STMT,&num_so_far,NULL,
                OCI_ATTR_ROW_COUNT,errhp);
        print_rows(num,(num_so_far-rows_ret));
        rows_ret = num_so_far;
    }
}
} else {
    OCISStmtFetch(curq,errhp,ntf,OCI_FETCH_NEXT,
    OCI_DEFAULT);

    OCIaget(curq,OCI_HTYPE_STMT,&rows_ret,NULL,OCI_ATTR_RO
W_COUNT,errhp);
    print_rows(num,rows_ret);
}

fprintf(logfile,"\\n\\n%d row%c processed.\\n",rows_ret,
    rows_ret == 1 ? '\\0' : '\\s');

}

int get_statement()
{
    char line[128];
    char *pos, *str;

    /* Reset statement buffer */
    stmt[0] = '\\0';

    while (fgets(line, 127, qtemp) != NULL) {

        /* skip blank lines */
        if (line[0] == '\\n')
            continue;

        /* remove blanks */

```

```

        str = line;
        while (*str == ' ') str++;
        /* Let's get the line together first */
        strcat(stmt, str);

        /* if this is a comment line */
        if ((str[0] == '-') && (str[1] == '-'))
            return COMMENT;

        /* see if this is a set_fetchrows line */
        if (strncmp(str, "set_fetchrows", 13) == 0) {
            pos = strchr(str, ':');
            *pos = '\\0';
            pos = strchr(str, '=');
            num_to_fetch = atol(++pos);
            return SET_FETCHROW;
        }

        /* if this is the end of the current statement */
        if ((pos = strchr(stmt, ';')) != NULL) {
            *pos = '\\0';
            return SQL_STMT;
        }
    }
    return END_OF_FILE;
}

/* memalloc(): Allocates memory, exit program if we have a problem. */

void *memalloc(size)
    int size;
{
    void *tmp;

    if ((tmp = (void *) malloc(size)) == NULL) {
        fprintf(stderr, "Error in malloc\\n");
        SQLexit();
        return NULL; /* should never reach here */
    } else {
        return tmp;
    }
}

void print_header(nsel)
    int nsel; /* Number of select list items */
{
    int i, diff;
    char colname[MAX_COLNAME_SIZE];
    int len = 0; /* Running column length */
    int cwid = 0;

    printf(logfile, "\\n");

    for (i=0; i<nsl; i++) {

        /* extract the column name */
        strncpy((char *)colname, (char *)slist[i].buf, slist[i].buflen);
        colname[slist[i].buflen] = '\\0';

        /* format the output a little */

```

```

cwid = MAX(slist[i].dbsize, slist[i].buflen);

/* do a little bit of formatting */

if (cwid > 80) {
    fprintf(logfile, "\n");
    len = 0;
} else if ((len += cwid) > 80) {
    fprintf(logfile, "\n");
    len = cwid;
}
#endifdef FORMAT1
if ((slist[i].dbtype == INT_TYPE) || (slist[i].dbtype == FLT_TYPE))
    fprintf(logfile, "%*s ", cwid, slist[i].buf);
else /* string type */
    fprintf(logfile, "%*s ", -cwid, slist[i].buf);
#else
    fprintf(logfile, "%*s ", -cwid, colname);
#endif /* FORMAT1 */
}

fprintf(logfile, "\n");
}

```

```

void print_rows(ncol, nrow)
    int ncol;
    int nrow;
{
    int i,j;
    int len;
    int diff;
    int cwid;

    for (i=0;i<nrow;i++) {
        len = 0;
        for (j=0;j<ncol;j++) {
            cwid = MAX(slist[j].dbsize, slist[j].buflen);

            /* do a little bit of formatting */

            if (cwid > 80) {
                fprintf(logfile, "\n");
                len = 0;
            } else if ((len += cwid) > 80) {
                fprintf(logfile, "\n");
                len = cwid;
            }

            switch(slist[j].dbtype) {
                case INT_TYPE:
#endifdef HAVE_SCALE
                fprintf(logfile, "%*ld|", cwid, (dlist[j]->ibuf)[i]);
                break;
#endif /* HAVE_SCALE */
                case FLT_TYPE:
#endifdef FORMAT1
                fprintf(logfile, "%*.2f ", cwid, (dlist[j]->fbuf)[i]);
#endif /* FORMAT1 */
                break;
            default:
                fprintf(logfile, "%*s ", -(cwid), (dlist[j]->sbuf)[i]);
                break;
        }
    }
}

```

```

        fprintf(logfile, "\n");
    }
}

/* remove_newline(): Remove newline character from str. */

void remove_newline(str)
    char *str;
{
    char *p;

    while ((p = strchr(str, '\n')) != NULL)
        *p = ' ';
}

```

F.6 qexecpl.h

```

/*
 * $Header: qexecpl.h 13-nov-2001.17:52:35 mpoess Exp $
 */

/* Copyright (c) 1999, 2001, Oracle Corporation. All rights reserved. */

/* NOTE: See 'header_template.doc' in the 'doc' dve under the 'forms' directory for the header file template that includes instructions.
 */

/*
 NAME
 qexecpl.h

DESCRIPTION
 SQL statement execution front-end header file.

PUBLIC FUNCTION(S)
 <list of external functions declared/defined - with one-line descriptions>

PRIVATE FUNCTION(S)
 <list of static functions defined in .c file - with one-line descriptions>

EXAMPLES

NOTES
 <other useful comments, qualifications, etc.>

MODIFIED (MM/DD/YY)
mpoess 11/13/01 - change DOP to 84 for DML and DDL
mpoess 02/22/01 - add linux changes
mpoess 08/05/99 - make compile
mpoess 07/15/99 - Creation
mpoess 07/15/99 - Creation
 */

#ifndef S_ORACLE
# include <s.h>
#endif
#ifndef QSTREAMPL_H
#define QSTREAMPL_H

#include <stdio.h>
#include <string.h>

```

```

#include <sys/param.h>
#include <sys/types.h>
#include <time.h>
#include <errno.h>
#include <math.h>

#include <oratypes.h>
#include <oratypes.h>

#ifndef OCIDFN
#include <ocidfn.h>
#endif /* OCIDFN */

#ifndef OCI_ORACLE
#include <oci.h>
#endif /* OCI_ORACLE */
/*
#ifndef __STDC__
#include <ociapr.h>
#else
#include <ocikpr.h>
#endif /* __STDC__ */

/* some basic definitions */

#define UNAME_LEN 64
#define MAX_FILE_PATH_LEN 128

#ifndef TRUE
#define TRUE 1
#endif /* TRUE */

#ifndef FALSE
#define FALSE 1
#endif /* FALSE */
#ifndef LINUX
#define MAX(x,y) ((x >= y) ? x : y)
#define MIN(x,y) ((x <= y) ? x : y)
#endif
/* defines and typedefs for parsing */

#define CRT_TBL 1
#define INS_STMT 3
#define SEL_STMT 4
#define UPD_STMT 5
#define DRP_VIEW 7
#define DRP_TBL 8
#define DEL_STMT 9
#define CRT_VIEW 10

/* defines and typedefs for query description */

#define MAX_COLNAME_SIZE 32 /* Maximum length of Column name */
#define MAX_SEL_LIST 16 /* Maximum items on a select list */

#define END_OF_LIST 1007 /* Error code when we reach the end of the */
/* select list. */

/* types for describe */

#define CHAR_TYPE 1
#define NUM_TYPE 2
#define INT_TYPE 3
#define FLT_TYPE 4
#define STR_TYPE 5
#define DATE_TYPE 12

#define NUMWIDTH 16 /* Width of the numeric fields */
#define POS(i) (i+1) /* The position is 1...n instead */
#define IND(i) (i-1) /* of 0..n-1 as in an array. */

typedef struct des
{
    ub2 dbsize;
    ub4 buflen;
    /* sb2 dszie; */
    sb4 scale;
    /* sb2 nullok; */
    OCITypeCode dbtype;
    /* text buf[MAX_COLNAME_SIZE]; */
    text *buf;
    ub1 precision;
} sltype;

/* defines and typedefs for query select list definition */

#define MAX_ARRAY 50 /* Maximum array size for array fetch */
#define PFMEMSIZE 65536 /* Memory size of prefetch buffer */

#define MAX_STR_LEN 256 /* Maximum size for string variables */
#define MAX_PREALLOC 8 /* Maximum number of preallocated select list */

/* definitions. */

#define INT sizeof(long)
#define STR sizeof(char)
#define FLT sizeof(double)

#define FLTP (double *)
#define INTP (long *)
#define STRP (char **)

typedef struct def
{
    long ibuf[MAX_ARRAY];
    double fbuf[MAX_ARRAY];
    char sbuf[MAX_ARRAY][MAX_STR_LEN];
    ub2 rlen[MAX_ARRAY]; /* return length */
    OCIDefine *defhdl;
} dltype;

extern int errno;

#define SQL_LEN 2048

#ifndef NULL
#define NULL 0
#endif

#ifndef NULLP
#define NULLP (void *)NULL
#endif /* NULLP */

#ifndef DISCARD
#define DISCARD (void)
#endif

#ifndef sword
#define sword int
#endif

#ifndef ub1
#define ub1 unsigned char
#endif

#define NA -1 /* ANSI SQL NULL */

```

```

#define VER7      2
#define NOT_SERIALIZABLE 8177 /* ORA-08177: transaction not
serializable */

#define ADR(object) ((ub1 *)&(object))
#define SIZ(object) ((sword)sizeof(object))
#define SID(sid) ((sid == -1) ? 0 : sid)

/* For get_statement */

#define END_OF_FILE -1
#define COMMENT 1
#define SQL_STMT 2
#define SET_FETCHROW 3

#define OCIalloc(envh,hndl,htyp) \
if((status=OCIHandleAlloc((dvoid *)envh,(dvoid \
**)hndl,htyp,0,(dvoid **)0))!=OCI_SUCCESS) \
    sql_error(envh,status,0); \
else \
    DISCARD 0

#define OCIhfree(hndl,htyp) \
if((status=OCIHandleFree((dvoid *)hndl,htyp)) == OCI_SUCCESS) \
    fprintf(stderr, "Error freeing handle of type %d\n", htyp)

#define OCIaget(hndl,htyp,attp,size,atyp,errh) \
if((status=OCIAttrGet((dvoid *)hndl,htyp,(dvoid \
*)size,atyp,errh)) != OCI_SUCCESS) \
    sql_error(errh,status,1); \
else \
    DISCARD 0

#define OCIAset(hndl,htyp,attp,size,atyp,errh) \
if((status=OCIAttrSet((dvoid *)hndl,htyp,(dvoid \
*)attp,size,atyp,errh)) != OCI_SUCCESS) \
    sql_error(errh,status,1); \
else \
    DISCARD 0

#define OCIsexec(svch,stmh,errh,iter) \
if((status=OCIStmtExecute(svch,stmh,errh,iter,0,NULL,NULL,NULL,OCI_DE \
FAULT)) != OCI_SUCCESS) \
    sql_error(errh,status,1); \
else \
    DISCARD 0

#define ISOTXT "alter session set isolation_level = serializable"
#define PDMLTXT "alter session force parallel dml parallel (degree \
84)"
#define PDDLTXT "alter session force parallel ddl parallel (degree 84)"

#endif /* QSTREAMPL_H */

```

```

sqlplus=$ORACLE_HOME/bin/sqlplus
GTIME=${KIT_DIR}/utils/gtime

RUN_ID_FILE=${KIT_DIR}/audit/r_id
if [ ! -f $RUN_ID_FILE ]
then
    echo "0" > $RUN_ID_FILE
fi

RUN_ID=`cat $RUN_ID_FILE`
RUN_ID=`expr $RUN_ID + 1`
echo $RUN_ID > $RUN_ID_FILE

OUT_DIR=${KIT_DIR}/audit/tests/${RUN_ID}
if [ ! -d $OUT_DIR ]
then
    mkdir $OUT_DIR
fi

SCRIPT_LOG_FILE=${OUT_DIR}/main.out
RDB_TABLES=${OUT_DIR}/rdbtablest
RI_CHECK=${OUT_DIR}/ri_check
FIRST_TEN=${OUT_DIR}/firstten

LD0LOADASM=${OUT_DIR}/Ld0loadasm
LD1DBCRE=${OUT_DIR}/Ld1dbcre
LD2SCTSO=${OUT_DIR}/Ld2sctso
LD3DAPOP=${OUT_DIR}/Ld3dapop
LD4IXCRE=${OUT_DIR}/Ld4ixcre
LD5ANLYZ=${OUT_DIR}/Ld5anlyz

echo Start TPC-H Benchmark SEQUENCE NUMBER: $RUN_ID >
$SCRIPT_LOG_FILE
echo >> $SCRIPT_LOG_FILE
echo "Starting a new Oracle log file:
$ORACLE_HOME/rdbms/log/alert_${ORACLE_SID}.log" >>
$SCRIPT_LOG_FILE
echo >> $SCRIPT_LOG_FILE

mv $ORACLE_HOME/rdbms/log/alert_${ORACLE_SID}.log
$ORACLE_HOME/rdbms/log/alert_${ORACLE_SID}.log.preAudit.$R \
UN_ID
mv $ORACLE_HOME/rdbms/log/alert_ASM.log
$ORACLE_HOME/rdbms/log/alert_ASM.log.preAudit.$RUN_ID
touch $ORACLE_HOME/rdbms/log/alert_${ORACLE_SID}.log
touch $ORACLE_HOME/rdbms/log/alert_ASM.log

echo "Start: load database `date`" >> $SCRIPT_LOG_FILE
loadasm > $LD0LOADASM
dbcre.sh > $LD1DBCRE
sctso.sh > $LD2SCTSO
STIME=$GTIME
echo "Start: timed load portion `date`" >> $SCRIPT_LOG_FILE
dapop.sh > $LD3DAPOP
ixcre.sh > $LD4IXCRE
anl.sh > $LD5ANLYZ
echo "End: timed load portion `date`" >> $SCRIPT_LOG_FILE

$KIT_DIR/audit/gen_seed.sh $KIT_DIR/audit/seed
echo Generated seed: `cat $KIT_DIR/audit/seed` >>
$SCRIPT_LOG_FILE

$Sqlplus ${DATABASE_USER} @${KIT_DIR}/audit/ri_check >
${RL_CHECK} 2>&1
echo "Start: dbtables.sql and count.sql" >> $SCRIPT_LOG_FILE
$Sqlplus ${DATABASE_USER} @${KIT_DIR}/audit/dbtables >
${RDB_TABLES} 2>&1

```

```

$sqlplus ${DATABASE_USER} @${KIT_DIR}/audit/firstten >
${FIRST_TEN} 2>&1
echo "End: dbtables.sql and count.sql `date`" >> $SCRIPT_LOG_FILE

runTPCHpt ${SCALE_FACTOR} 1 ${RUN_ID}

/dbms/oracle10i/frame/bin/tshut
/dbms/oracle10i/frame/bin/tshut.asm
/dbms/oracle10i/frame/bin/tstart.asm
/dbms/oracle10i/frame/bin/tstart

runTPCHpt ${SCALE_FACTOR} 2 ${RUN_ID}

sleep 600
# call the auditor: don't tshut >> $SCRIPT_LOG_FILE

cp $ORACLE_HOME/rdbms/log/alert_${ORACLE_SID}.log
$OUT_DIR

echo "End TPC-H Benchmark SEQUENCE NUMBER: ${RUN_ID}
`date`" >> $SCRIPT_LOG_FILE

```

F.8 runTPCHpt

```

#!/bin/ksh
. ${KIT_DIR}/env
#set -x
#ECHO=/bin/echo
SCRIPT_DIR=${KIT_DIR}/scripts
UPD_DIR=${KIT_DIR}/update
SRC_DIR=${KIT_DIR}/utils
QRY_DIR=${KIT_DIR}/queries # this is the location of the query
template file
QGEN_DIR=${KIT_DIR}/dbgen
QGEN=${QGEN_DIR}/qgen
QEXEC=${SRC_DIR}

DSS_QUERY=${KIT_DIR}/queries
export DSS_QUERY

UPD_SQL=${UPD_DIR}/sql
UPD_SPT=${UPD_DIR}/scripts
UPD_SRC=${UPD_DIR}/source
UPD_DAT=${UPD_DIR}/data

TPCD_BIN=${KIT_DIR}/audit/bin

GTIME=${SRC_DIR}/gtime
SEED_FILE=${KIT_DIR}/audit/seed

DF=/dev/null
HID=1
INTERVAL=60
COUNT=1200

# The defaults

QPROG=${QEXEC}/qexec

usage () {

echo "
echo "Usage: $0 [-p <program for query stream>] [-u1 <program for
UF1>]""
echo "      [-u2 <program for UF2>] [-o] [-s] [-h] [-u
<user/password>]"
echo "      <scale factor> <run_number>""
echo ""
echo "scale factor : The scale factor of the run."
}

echo "update ||ism : The parallelism to use for the UFs."
echo ""
echo "-p <program> : Program for Query Stream."
echo "           Default is $QPROG."
echo "-u1 <program> : Program for UF1."
echo "           Default is $U1PROG."
echo "-u2 <program> : Program for UF2."
echo "           Default is $U2PROG."
echo "-o : Collect Oracle statistics."
echo "-s : Collect System statistics."
echo "-u <user/passwd> : User/Password. Default is tpch/tpch."
echo "-h : Displays this message."
}

set -- ` getopt "p:u1:u2:osu:h" "$@" || usage

while :
do
  case "$1" in
    -u1) shift; U1PROG=$1;;
    -u2) shift; U2PROG=$1;;
    -p) shift; QPROG=$1;;
    # not needed ? -o) OSTAT=1;;
    # not needed ? -s) SSTAT=1;;
    -h) usage; exit 0;;
    --) shift; break;;
    esac
    shift;
done

if [ "$#" -ne "3" ]
then
  usage
  exit 1
fi

SF=$1
PARA=$2
RUN_ID=$3

OUT_DIR=${KIT_DIR}/audit/tests/${RUN_ID}
if [ ! -d $OUT_DIR ]
then
  mkdir $OUT_DIR
fi

TPCD_LOG=${OUT_DIR}
TPCD_RPT=${OUT_DIR}
OUT=${OUT_DIR}

let UF_SET="($PARA-1)*($NUM_STREAMS+1)+1"
START_SET=1
let STOP_SET=$NUM_STREAMS
let START_SET_UPDATE="($PARA-1)*($NUM_STREAMS+1)+2"
let
STOP_SET_UPDATE="$START_SET_UPDATE+$NUM_STREAMS
-1"

TPCD_LOG_FILE=${TPCD_LOG}/m${PARA}s0
TPCD_RPT_FILE=${TPCD_RPT}/m${PARA}s0inter
QRY_FILE=${TPCD_RPT}/qtemp.${PARA}s0
QUERY_PARAMETER=${TPCD_LOG}/qp${PARA}.0
SCRIPT_LOG_FILE=${TPCD_LOG}/m${PARA}timing
UF1_LOG=${TPCD_LOG}/m${PARA}s0rf1
UF2_LOG=${TPCD_LOG}/m${PARA}s0rf2
STREAM_COUNT_LOG=${TPCD_LOG}/m${PARA}tstrcnt

echo "TPC-H Test - RUN:${PARA} SEQUENCE:${RUN_ID} `date`"
> $SCRIPT_LOG_FILE
echo "TPC-H Test - RUN:${PARA} SEQUENCE:${RUN_ID} `date`"
> $TPCD_RPT_FILE

```

```

echo "Generates query template file with seed: `cat $SEED_FILE` for
stream 0" >> $SCRIPT_LOG_FILE
echo >> $SCRIPT_LOG_FILE

${QGEN} -c -r `cat $SEED_FILE` -p 0 -s ${SF} -l
$QUERY_PARAMETER > ${QRY_FILE}

START=`$GTIME`
echo "Start Power Test - RUN:${PARA} SEQUENCE:${RUN_ID}"
Execution Starts $START, `date` >> $SCRIPT_LOG_FILE
echo "" >> $SCRIPT_LOG_FILE

# Execute UF1

SDATE=`date`
UF1_START=`$GTIME`
echo "Start UF1 $UF1_START, `date`" >> $SCRIPT_LOG_FILE

${ECHO} ${UPD_SPT}/runuf1.sh ${UF_SET} >> $UF1_LOG 2>&1
# Execute Query Stream

UF1_END=`$GTIME`
E1DATE=`date`

UF1_TIME=`echo $UF1_END - $UF1_START | bc`
echo UF1: Execution Time: $UF1_TIME >> ${TPCD_RPT_FILE}
echo Start Time: $UF1_START, $SDATE >> ${TPCD_RPT_FILE}
echo End Time: $UF1_END, $E1DATE >> ${TPCD_RPT_FILE}
echo "" >> ${TPCD_RPT_FILE}

echo "End UF1 $UF1_END, ${E1DATE}" >> $SCRIPT_LOG_FILE
echo UF1: Execution Time: $UF1_TIME >> $SCRIPT_LOG_FILE
echo >> $SCRIPT_LOG_FILE

echo "Start Query Part `$GTIME`, `date`" >> $SCRIPT_LOG_FILE

${QPROG} ${DATABASE_USER} q${QRY_FILE}
I${TPCD_LOG_FILE} r${TPCD_RPT_FILE} > $DF 2>&1

# Execute UF2

UF2_START=`$GTIME`
E2DATE=`date`

echo "End Query Part `$GTIME`, ${E2DATE}" >>
$SCRIPT_LOG_FILE
echo "" >> $SCRIPT_LOG_FILE

echo "Start UF2 $UF2_START, `date`" >> $SCRIPT_LOG_FILE
${ECHO} ${UPD_SPT}/runuf2.sh ${UF_SET} >> $UF2_LOG 2>&1
UF2_END=`$GTIME`
END=`$GTIME`
EDATE=`date`

UF2_TIME=`echo $UF2_END - $UF2_START | bc`
echo UF2: Execution Time: $UF2_TIME >> ${TPCD_RPT_FILE}
echo Start Time: $UF2_START, $E2DATE >> ${TPCD_RPT_FILE}
echo End Time: $UF2_END, $EDATE >> ${TPCD_RPT_FILE}

echo "End UF2 $UF2_END, $EDATE" >> $SCRIPT_LOG_FILE
echo UF2: Execution Time: $UF2_TIME >> $SCRIPT_LOG_FILE
echo >> $SCRIPT_LOG_FILE

echo "End TPC-H Power Test - RUN:${PARA}"
SEQUENCE:${RUN_ID}, $END, $EDATE" >> $SCRIPT_LOG_FILE
MEA_INT` echo $END - $START | bc`
echo "Elapsed Time for TPC-H Power Test - RUN:${PARA}"
SEQUENCE:${RUN_ID} is $MEA_INT" >> $SCRIPT_LOG_FILE
echo >> $SCRIPT_LOG_FILE

#${KIT_DIR}/audit/abridge.pl ${TPCD_LOG_FILE}

i=$START_SET
PSEED=`cat $SEED_FILE`

while [ $i -le $STOP_SET ]; do
  TPCD_LOG_FILE=${TPCD_LOG}/mt${RUN_ID}_${i}.log
  TPCD_RPT_FILE=${TPCD_RPT}/mt${RUN_ID}_${i}.rpt
    QUERY_PARAMETER=${TPCD_LOG}/qp${PARA}.${i}
  QRY_FILE=${TPCD_RPT}/qtemp.${PARA}s${i}

  PSEED=`expr $PSEED + 1` 
  ${QGEN} -c -r ${PSEED} -p ${i} -s ${SF} -l
  $QUERY_PARAMETER > ${QRY_FILE}

  i=`expr $i + 1`
done

TH_START_D=`date`
TH_START_T=`$GTIME`
echo >> $SCRIPT_LOG_FILE

rm -f /tmp/th_pipe1
mknod /tmp/th_pipe1 p
rm -f /tmp/th_pipe2
mknod /tmp/th_pipe2 p
i=$START_SET

echo "Start Throughput Test - RUN:${PARA}"
SEQUENCE:${RUN_ID} $TH_START_T, $TH_START_D" >>
$SCRIPT_LOG_FILE

# starts a script to count the streams during the throughput run
(scnt.sh ${PARA} ${RUN_ID} > ${STREAM_COUNT_LOG} &

while [ $i -le $STOP_SET ]; do
  M_SDATE=`date`
  M_STIME=`$GTIME`
    TPCD_LOG_FILE=${TPCD_LOG}/m${PARA}s${i}
    TPCD_RPT_FILE=${TPCD_RPT}/m${PARA}s${i}inter
  echo "Start Query Stream $i $M_STIME, ${M_SDATE}" >>
$SCRIPT_LOG_FILE
    QRY_FILE=${TPCD_RPT}/qtemp.${PARA}s${i}
  ${QPROG} ${DATABASE_USER} q${QRY_FILE}
I${TPCD_LOG_FILE} r${TPCD_RPT_FILE} | grep -v "Connected to
ORACLE" >> $SCRIPT_LOG_FILE &
  i=`expr $i + 1`
done

(${KIT_DIR}/audit/runTPCHus ${RUN_ID} $START_SET_UPDATE
$STOP_SET_UPDATE ${SF} ${PARA} >> $SCRIPT_LOG_FILE 2>&1
&

wait
THQ_END_T=`$GTIME`
THQ_END_D=`date`
echo End all Query Streams $THQ_END_T, $THQ_END_D >>
$SCRIPT_LOG_FILE
print > /tmp/th_pipe1
read < /tmp/th_pipe2

TH_END_D=`date`
TH_END_T=`$GTIME`
echo End Update Stream ${TH_END_T}, ${TH_END_D} >>
$SCRIPT_LOG_FILE
echo >> $SCRIPT_LOG_FILE
echo "End Throughput Test ${TH_END_T}, ${TH_END_D}" >>
$SCRIPT_LOG_FILE
echo Execution Time Throughput Test: `echo ${TH_END_T} -
${TH_START_T} | bc` >> $SCRIPT_LOG_FILE

```

```

i=$START_SET
while [ $i -le $STOP_SET ]; do
    TPCD_LOG_FILE=${TPCD_LOG}/m${PARA}s${i}
    ${KIT_DIR}/audit/abridge.pl ${TPCD_LOG_FILE}
    i=`expr $i + 1`
done
PIDS=`ps -fu oracle | grep scnt.sh | grep -v grep | awk '{print $2}'`^
kill -9 $PIDS
#calculate the metric
#analyze_streams.pl -f p -n $RUN_ID >
${TPCD_RPT}/tpch_metric.${RUN_ID}.${HID}.rpt

SDATE=`date`
UF1_START=`$GTIME`
echo "Start UF1-${j} at ${UF1_START}, ${SDATE}" >>
${RPT_FILE}

$UPD_SPT/runuf1.sh ${i} >> ${UF1_LOG} 2>&1
UF1_END=`$GTIME`
EDATE=`date`
echo "End UF1-${j} at ${UF1_END}, ${EDATE}" >> ${RPT_FILE}
echo UF1-${j} Execution Time: `echo ${UF1_END} - ${UF1_START} | bc` >> ${RPT_FILE}

# Execute UF2

SDATE=`date`
UF2_START=`$GTIME`
echo "Start UF2-${j} ${UF2_START}, ${SDATE}" >>
${RPT_FILE}

$UPD_SPT/runuf2.sh ${i} >> ${UF2_LOG} 2>&1
UF2_END=`$GTIME`
EDATE=`date`
echo "End UF2-${j} at ${UF2_END}, ${EDATE}" >> ${RPT_FILE}
echo UF2-${j} Execution Time: `echo ${UF2_END} - ${UF2_START} | bc` >> ${RPT_FILE}

i=`expr $i + 1`^
j=`expr $j + 1`^
done

print > /tmp/th_pipe2

# Execute UF1

# $Header: runuf1.sh 25-oct-2001.15:56:04 mpoess Exp $
# runuf1.sh
# Copyright (c) 1999, 2001, Oracle Corporation. All rights reserved.
#
# NAME
#   runuf1.sh - <one-line expansion of the name>
#
# DESCRIPTION
#   runuf1.sh -l [<path name for reports>] -u [<uid/passwd>]
#           -p [<program>] <run_id> <scale factor> <pair number>
#           <parallelism>
#
# USAGE
#   To execute UF1.
#
# NOTES
#   <other useful comments, qualifications, etc.>
#
# MODIFIED (MM/DD/YY)
#
# .${KIT_DIR}/env
O=${ORACLE_HOME}
UPDATE_DIR=${KIT_DIR}/update
SCRIPT_DIR=${UPDATE_DIR}/scripts
UTILS_DIR=${KIT_DIR}/utils
LOG_DIR=${UPDATE_DIR}/log
GTIME=${UTILS_DIR}/gtme
SF=${SCALE_FACTOR}
PAR_HINT=${UPDATE_1_DOP}

```

```

LOGPATH=.
PASSWD=${DATABASE_USER}

if [ $# -lt 1 ];
then
  echo runuf1.sh setnum
  exit 1
fi
SETNUM=$1
i=1
PID=""

# perform the update function 1

START=`$GTIME`

# first create the temp tables

sqlplus /NOLOG << !
connect $PASSWD;
set timing on
set serveroutput on
set echo on

drop directory data_dir;
create directory data_dir as '/flat15/updates';

drop table temp_l_et;
create table temp_l_et(
  l_orderkey      number ,
  l_partkey       number ,
  l_suppkey       number ,
  l_linenumber    number ,
  l_quantity      number ,
  l_extendedprice number ,
  l_discount      number ,
  l_tax           number ,
  l_returnflag    char(1) ,
  l_linestatus    char(1) ,
  l_shipdate      date ,
  l_commitdate    date ,
  l_receiptdate   date ,
  l_shipinstruct  char(25) ,
  l_shipmode      char(10) ,
  l_comment       varchar(44)
)
organization external (
type ORACLE_LOADER
default directory data_dir
access parameters
(
  records delimited by newline
  nobadfile
  nologfile
  fields terminated by '|'
  missing field values are null
)
location (
  'lineitem.tbl.u${SETNUM}'
))
reject limit unlimited parallel ${PAR_HINT};

alter session force parallel dml parallel (degree ${PAR_HINT});
alter session set isolation_level = serializable;
alter session set optimizer_index_cost_adj=10;

insert into orders
select
  o_orderdate      ,
  o_orderkey       ,
  o_custkey        ,
  o_orderpriority  ,
  o_shippriority   ,
  o_clerk          ,
  o_orderstatus    ,
  o_totalprice    ,
  o_comment        ,
from temp_o_et;

insert into lineitem
select
  l_shipdate      ,
  l_orderkey       ,
  l_discount       ,
  l_extendedprice  ,
  l_suppkey        ,
  l_quantity       ,
  l_returnflag     ,
  l_partkey        ,
  l_linestatus     ,
  l_tax            ,
  l_commitdate    ,
  l_receiptdate   ,
  l_shipmode       ,
  l_linenumber    ,
  l_shipinstruct  ,
  l_comment        ,
from temp_l_et;

commit;

rem drop table temp_l_et;
rem drop table temp_o_et;

exit;
!

END=`$GTIME`
```

```

# Done

echo ""
echo "Update Function 1 Set $SETNUM done!"
echo "Elapsed Time is `echo $END - $START | bc`"
echo ""

)
organization external (
type ORACLE_LOADER
default directory data_dir
access parameters
(
  records delimited by newline
  nobadfile
  nologfile
  fields terminated by '|'
  missing field values are null
)
location (
  'delete.${SETNUM}')
reject limit unlimited parallel 16;

create table temp_okey (t_orderkey, constraint tokey1 primary
key(t_orderkey))
organization index parallel 16 nologging as select * from
temp_okey_et;
execute dbms_stats.gather_table_stats('tpch', 'temp_okey',
estimate_percent => 1, degree => 16)

alter session force parallel dml parallel ${PAR_HINT};
alter session set isolation_level=serializable;
alter session set optimizer_index_cost_adj=1;

delete from (select /*+ use_nl(t o) */ o.rowid from orders o, temp_okey t
where o.o_orderkey = t.t_orderkey order by 1);

delete from (select /*+ use_nl(l) */ l.rowid from lineitem l,temp_okey t
where l.l_orderkey = t.t_orderkey order by 1);

commit;

drop table temp_okey;
drop table temp_okey_et;
exit;
!

END=`$GTIME`


# Done

echo ""
echo "Update Function 2 Set $SETNUM done!"
echo "Elapsed Time is `echo $END - $START | bc`"
echo ""



F.11 runuf2.sh

#!/bin/ksh
#
# $Header: runuf2.sh 25-oct-2001.15:56:05 mpoess Exp $
#
# runuf2.sh
#
# Copyright (c) 1999, 2001, Oracle Corporation. All rights reserved.
#
# NAME
#   runuf2.sh - <one-line expansion of the name>
#
# DESCRIPTION
#   runuf2.sh [-u <uid/passwd to login>] [-p <program>] <run_id>
#             <scale factor> <pair number> <parallelism>
#
# USAGE
#   To execute UF2.
#
# NOTES
#   <other useful comments, qualifications, etc.>
#
# . $KIT_DIR/env
UPDATE_DIR=${KIT_DIR}/update
SCRIPT_DIR=${UPDATE_DIR}/scripts
UTILS_DIR=${KIT_DIR}/utils
GTIME=${UTILS_DIR}/gtime
LOG_DIR=${UPDATE_DIR}/log
PAR_HINT=${UPDATE_2_DOP}
SF=${SCALE_FACTOR}
PASSWD=${DATABASE_USER}

if [ $# -lt 1 ]
then
  usage
  exit 1
fi

SETNUM=$1

i=1
PID=""

START=`$GTIME`
# first create the temp tables

sqlplus /NOLOG << !
connect $PASSWD;
set timing on
set serveroutput on
set echo on

drop directory data_dir;
create directory data_dir as '/flat15/updates';

drop table temp_okey_et;
drop table temp_okey;

create table temp_okey_et(
  t_orderkey      number
)
organization external (
type ORACLE_LOADER
default directory data_dir
access parameters
(
  records delimited by newline
  nobadfile
  nologfile
  fields terminated by '|'
  missing field values are null
)
location (
  'delete.${SETNUM}')
reject limit unlimited parallel 16;

create table temp_okey (t_orderkey, constraint tokey1 primary
key(t_orderkey))
organization index parallel 16 nologging as select * from
temp_okey_et;
execute dbms_stats.gather_table_stats('tpch', 'temp_okey',
estimate_percent => 1, degree => 16)

alter session force parallel dml parallel ${PAR_HINT};
alter session set isolation_level=serializable;
alter session set optimizer_index_cost_adj=1;

delete from (select /*+ use_nl(t o) */ o.rowid from orders o, temp_okey t
where o.o_orderkey = t.t_orderkey order by 1);

delete from (select /*+ use_nl(l) */ l.rowid from lineitem l,temp_okey t
where l.l_orderkey = t.t_orderkey order by 1);

commit;

drop table temp_okey;
drop table temp_okey_et;
exit;
!

END=`$GTIME`


# Done

echo ""
echo "Update Function 2 Set $SETNUM done!"
echo "Elapsed Time is `echo $END - $START | bc`"
echo ""



F.12 scnt.sh

#!/bin/ksh

echo Process count for TPC-H RUN:$1 SEQUENCE:$2
while [ 1 = 1 ]; do
  cnt=`ps -ef | egrep "qexec|runTPCHus" | grep -v grep | wc -l`
  echo
  echo `date` : $cnt
  ps -ef | egrep "qexec|runTPCHus" | grep -v grep
  sleep 30
done

```

F.13 set_queue

```
#!/sbin/sh

#set -x

#
# set queue_depth
#

for i in `ls -1 /dev/rdisk/*`
do
  #scsimgr set_attr -C disk -I $i -a max_q_depth=128
  #scsimgr set_attr -D $i -a max_q_depth=128
  scsimgr set_attr -D $i -a max_q_depth=128 > /dev/null 2>&1

done

exit
```

```
sleep 5
```

```
exit
```

F.14 tshut

```
#!/bin/ksh

export ORACLE_SID=tpch

if [ "$1" = "abort" ]; then
  sqlplus /NOLOG<< !
  connect / as sysdba
  shutdown abort
  exit
!
else
  sqlplus /NOLOG<< !
  connect / as sysdba
  shutdown abort
  exit
!
fi

sleep 5

exit
```

F.15 tshut.asm

```
#!/bin/ksh

export ORACLE_SID=ASM

sqlplus /NOLOG<< !
connect / as sysdba;
shutdown normal;
exit
!
```

F.16 tstart

```
#!/bin/ksh

export ORACLE_SID=tpch

sqlplus /NOLOG << !
connect / as sysdba
startup pfile=/oracle/dbs/30TB_init.ora
execute dbms_scheduler.disable('AUTO_TASKS_JOB_CLASS');
!
sleep 5
/Lvm/set_queue;
exit
```

F.17 tstart.asm

```
#!/bin/ksh

export ORACLE_SID=ASM

sqlplus /NOLOG << !
connect / as sysdba
startup pfile=/oracle/dbs/initasm.ora mount
!
exit
```

F.18 ri_check.sql

```
set echo on
set numwidth 30
spool ri_check

select count(*) from partsupp left outer join part on
(ps_partkey=p_partkey) where p_partkey is null;

select count(*) from partsupp left outer join supplier on
(ps_suppkey=s_suppkey) where s_suppkey is null;

select count(*) from customer left outer join nation on
(c_nationkey=n_nationkey) where n_nationkey is null;

select count(*) from supplier left outer join nation on
(s_nationkey=n_nationkey) where n_nationkey is null;

select count(*) from region left outer join nation on
(r_regionkey=n_regionkey) where n_nationkey is null;
```

```
select count(*) from lineitem left outer join partsupp on  
(l_partkey=ps_partkey and l_suppkey=ps_suppkey) where ps_partkey is  
null and l_suppkey is null;
```

```
select count(*) from lineitem left outer join orders on  
(l_orderkey=o_orderkey) where o_orderkey is null;
```

```
select count(*) from orders left outer join customer on  
(o_custkey=c_custkey) where c_custkey is null;
```

```
spool off
```

```
exit;
```

Appendix G Price Quotes

The following pages contain the price quotes for the hardware included in this FDR.

Sharada Bose
HP
June 14, 2007



HP Unix Sales Development
19111 Pruneridge Avenue
Cupertino, CA 95014
(408) 447-2320

Description	Part Number	Source	Reference Price	Qty	Extended Price	3 yr. Maint. Price
Server Hardware						
Superdome left chassis	A9834A, Opt 429	1	235,950	1	235,950	
Superdome right chassis	A9835A, Opt 429	1	249,950	1	249,950	
Superdome sx2000 Cell Board	A9837A	1	19,250	16	308,000	
24x7x4hr - 3 Year Svc & Support Price (Hardware and Software)						\$1,379,874
512GB Memory Bundle (128x4GB dimms)	A9857A	1	1,299,950	2	2,599,900	
12-Slot PCI-X I/O Chassis	A9836A	1	16,950	16	271,200	
Dual-Core Intel Itanium2 9040/1.6GHz/18MB L3	AB406A	1	23,000	64	1,472,000	
PCI 1000BT Lan Adapter	A6847A	1	1,325	1	1,325	
PCI-X 4GB Fibre Channel Adapter (dual port)	AB379B	1	3,495	128	447,360	
PCI Dual Channel Ultra320 SCSI Adapter	A7173A	1	795	1	795	
HPDisk System 2120	A7382A	1	995	1	995	
1-36GB LP 15K HDD	A7527A	1	966	4	3,864	
HP Universal Rack 10642 G2 Pallet Rack	AF001A	1	1,249	1	1,249	
Modular Power Dist Unit for std racks	A5137AZ	1	145	1	145	
200-240 volts North America	A5137AZ, Opt AW4	1	94	1	94	
HP Tape Array 5300 (DVD and DAT tape)	C7508B	1	729	1	729	
HP rx2620 Server (inc mem/disk/monitor/keyboard/mou	AB333A	1	5,315	1	5,315	
I/O Chassis Enclsoure for 12-Slot PCI-X Chassis	A9852A	1	25,750	4	103,000	
Graphite I/O expansion power subsystem	A5861D	1	34,860	2	69,720	
				Subtotal	5,771,591	1,379,874
Server Software						
HPUX 11i v3 Foundation Operating Environment	B9429AC	1	2,370	128	303,360	
HP-UX 11i v3 HP9000/Integrity FOE Media	BA489AA, Opt AJR	1	565	1	565	
				Subtotal	303,925	0
Storage						
5m Fibre Channel Cables	221692-B22	1	82	256	20,992	
HP StorageWorks MSA 1000 (256 + 26 spares)	201723-B22	1	6,499	282	1,832,718	
3 Yr Support Price for MSA1000 and disks						Included
146GB 15K Ultra320 Hard Drive (3072 + 308 spares)	347708-B22	1	689	3,380	2,328,820	
HP Universal Rack 10642 G2 Pallet Rack	AF001A	1	1,249	28	35,222	
Modular Power Dist Unit for std racks	A5137AZ	1	145	113	16,356	
200-240 volts North America	A5137AZ, Opt AW4	1	94	113	10,603	
ProLiant Cluster HA/200 for MSA1000	252409-B22	1	4,007	1	4,007	
				Subtotal	4,248,718	0
45.3% Large Configuration Discount and Support Prepayment*						
				Total	10,324,234	1,379,874
					(4,555,394)	(745,132)
				Grand Total	5,768,840	634,742

Maintenance support price is for 24 hours, 7 days with 4 hour response time.

This quote is valid for 90 days

From: MaryBeth Pierantoni [mailto:mary.beth.pierantoni@oracle.com]
Sent: Tuesday, June 12, 2007 6:49 PM
To: Boushey, Lucille
Subject: Oracle Pricing

Product	Price	Qty	Extended Price
Oracle Database 10g Release 2 Enterprise Edition, Named User Plus for 3 years	\$10,000	64*	\$640,000
Partitioning, Named User Plus for 3 years	\$2,500	64*	\$160,000
Database Server Support Package for 3 years	\$6,000	1	\$6,000
Oracle Mandatory E-Business Discount			<\$161,200>
Oracle TOTAL			\$644,800

(* 64 = 0.50 * 128). Explanation: For the purposes of counting the number of processors which require licensing, an Intel multicore chip with "n" cores shall be determined by multiplying "n" cores by a factor of 0.50).

Contact: MaryBeth Pierantoni, mary.beth.pierantoni@oracle.com, 916-315-5081