

**TPC Benchmark™ H Full Disclosure Report**  
**for**  
**IBM® @server™ 325**  
**using**  
**IBM DB2® Universal Database 8.1**

**Submitted for Review**

**July 29, 2003**



## **Second Edition – August 10, 2003**

THE INFORMATION CONTAINED IN THIS DOCUMENT IS DISTRIBUTED ON AN AS IS BASIS WITHOUT ANY WARRANTY EITHER EXPRESSED OR IMPLIED. The use of this information or the implementation of any of these techniques is the customer's responsibility and depends on the customer's ability to evaluate and integrate them into the customer's operational environment. While each item has been reviewed by IBM for accuracy in a specific situation, there is no guarantee that the same or similar results will be obtained elsewhere. Customers attempting to adapt these techniques to their own environment do so at their own risk.

In this document, any references made to an IBM licensed program are not intended to state or imply that only IBM's licensed program may be used; any functionally equivalent program may be used.

This publication was produced in the United States. IBM may not offer the products, services, or features discussed in this document in other countries, and the information is subject to change without notice. Consult your local IBM representative for information on products and services available in your area.

© Copyright International Business Machines Corporation 2003. All rights reserved.

Permission is hereby granted to reproduce this document in whole or in part, provided the copyright notice as printed above is set forth in full text on the title page of each item reproduced.

U.S. Government Users - Documentation related to restricted rights: Use, duplication, or disclosure is subject to restrictions set forth in GSA ADP Schedule Contract with IBM Corp.

### ***Trademarks***



IBM, the IBM e-business logo, DB2 are trademarks or registered trademarks of International Business Machines Corporation.

The following terms used in this publication are trademarks of other companies as follows: TPC Benchmark, TPC-H, QppH QthH and QphH are trademarks of Transaction Processing Performance Council; AMD and Opteron are trademarks or registered trademarks of AMD Corporation; Other company, product, or service names, which may be denoted by two asterisks (\*\*), may be trademarks or service marks of others.

### ***Notes***

<sup>1</sup> GHz only measures microprocessor internal clock speed, not application performance. Many factors affect application performance.

<sup>2</sup> When referring to hard disk capacity, one GB equals one billion bytes. Total user-accessible capacity may be less.

		<b>IBM® @server™ 325</b> with <b>IBM DB2® UDB 8.1</b>		<b>TPC-H Revision 2.0</b>	
				Report Date: <b>July 29, 2003</b>	
Total System Cost		Composite Query-per-hour Metric		Price/Performance	
<b>863,410</b>		<b>12,216.1</b> <b>QphH@100GB</b>		<b>\$ 71</b> <b>per QphH@100GB</b>	
Database Size	Database Manager	Operating System		Availability Date	
<b>100GB</b>	<b>IBM DB2 UDB 8.1</b>	<b>SuSE Linux</b> <b>Enterprise Server 8</b>		<b>November 8, 2003</b>	
					
<b>Database Load Time: 00:37:30</b>		<b>Load Included Backup: N</b>		<b>Total Data Storage / Database Size: 58.31</b>	
<b>RAID (Base Table): Y</b>		<b>RAID (Base Tables and Auxiliary Data Structures): Y</b>		<b>RAID (ALL): Y</b>	
<b>System Configuration: 8 nodes</b> Processors: <b>2 x 2GHz AMD 64-bit Opteron Model 246 processor</b> Memory: <b>6 x DIMMS 1GB ECC 2700 2.5 CL</b> Disk Controllers: <b>1 x QLA2342 HBA (2 ports x 2G bps FC)</b> <b>1 x IBM FC2-133 HBA (1 ports x 2G bps FC)</b> Disk Drives: <b>3 (IBM TotalStorage FASTT EXP700 cases) x 14 (15K FC Hot-Swap Drive) x 18.2 GB</b> <b>1 x 18.2GB 15K Ultra160 SCSI Hot-Swap Drive</b> <b>Total Disk Storage: 5831.06 GB</b>					



**IBM<sup>®</sup> @server<sup>™</sup> 325**  
**with**  
**IBM DB2<sup>®</sup> UDB 8.1**

**TPC-H Revision 2.0**

**Report Date:**  
**July 29, 2003**

Description	Part #	Source	Unit Price	Qty	Extended Price	3-Yr. Maint. Price
					Price	Price
<b>Server Hardware</b>						
IBM e(logo)server 325 w/2GHz AMD 246	8835-51X		1 3,039	8	24,312	6968
2GHz Opteron Processor Upgrade	13N0700		1 1,399	8	11,192	0
DIMMS 1GB ECC 2700 2.5 CL	73P2267		1 659	48	31,632	0
Cisco Catalyst 3508G XL Enterprise edition	184837		3 3,600	1	3,600	1,223
Cisco 1000BASE-T Gigabit GBIC Module	372656		3 299	8	2,393	
18.2GB 15K Ultra160 SCSI Hot-Swap Drive	06P5767		1 329	8	2,632	0
IBM FC2-133 Host Bus Adapter	24P0960		1 1,485	8	11,880	0
Qlogic QLA 2342 Host Bus Adapter	408082		3 2,291	8	18,328	0
IBM USB Keyboard w/2 port USB Hub	22P5185		1 45	1	45	
IBM USB Optical Wheel Mouse	06P4069		1 20	1	20	
APC Smart-UPS Model 1400	32P1020		1 855	1	855	0
E54 15" (13.8" Viewable) Color Monitor	633147N		1 129	1	129	90
NetBAY42S Enterprise Rack	9306421		1 1,439	4	5,756	300
				<b>Subtotal</b>	<b>112,774</b>	<b>8581</b>
<b>Server Storage</b>						
IBM TOTALSTORAGE FASTT EXP700	1740-1RU		1 3,000	24	72,000	17,280
18.2GB 15K FC Hot-Swap Drive	5211		1 681	336	228,816	
Short Wave SFP	2210		1 499	24	11,976	
1M LC-LC FIBRE OPTIC CABLE	5601		1 79	24	1,896	
				<b>Subtotal</b>	<b>300,816</b>	<b>17,280</b>
<b>Server Software</b>						
DB2 UDB ESE V8.1 License/1-yr. Maint.	D518GLL		1 20,451	16	327,216	
DB2 UDB ESE V8.1 Support – 1Yr/Proc	E00BILL		1 974	32		31,168
DB2 UDB ESE V8.1 DPF License/1-yr. Maint.	D518JLL		1 6,143	16	98,288	
DB2 UDB ESE V8.1 DPF Support – 1Yr/Proc	E00BJLL		1 293	32		9,376
SuSE SLES8 8 proc + 1 yr maint.	2119-3INT-8		2 2,585	1	2,585	
SuSE SLES 8 Main. 1 yr/8proc	2119-MFJ-8		2 2,456	4		9,824
				<b>Subtotal</b>	<b>428,089</b>	<b>50,368</b>
Large volume discount on IBM hardware of 14%; prices vary if purchased separately.14%				<b>Discount</b>	<b>54,498</b>	
				<b>Total</b>	<b>787,181</b>	<b>76,229</b>
<b>Three-Year Cost of Ownership:</b>						<b>863,410</b>
Pricing: 1 - IBM Business Partner; 2 - SuSE, 3 - CDW shop online Warranty and Maintenance: The standard warranty has been upgraded to 3 years of 24x7x4 coverage.					<b>QphH:</b>	12216.1
					<b>\$/QphH:</b>	\$71
Prices used in TPC benchmarks reflect the actual prices a customer would pay for a one-time purchase of the stated components. Individually negotiated discounts are not permitted. Special prices based on assumptions about past or future purchases are not permitted. All discounts reflect standard pricing policies for the listed components. For complete details, see the pricing sections of the TPC benchmark specifications. If you find that stated prices are not available according to these terms, please inform the TPC at pricing@tpc.org. Thank you.						



IBM® @server™ 325  
with IBM DB2® UDB 8.1

TPC-H Revision 2.0  
Report Date: July 29, 2003

Measurement Results:

Database Scale Factor	100
Total Data Storage/Database Size	58.31
Start of Database Load	21:44:56
End of Database Load	22:22:26
Database Load Time	00:37:30
Query Streams for Throughput Test	5
TPC-H Power	12941.2
TPC-H Throughput	11531.7
TPC-H Composite Query-per-Hour (QphH@100GB)	12216.1
Total System Price over 3 Years	863,410
TPC-H Price/Performance Metric (\$/QphH@100GB)	71

Measurement Interval:

Measurement Interval in Throughput Test (Ts) = 3435 seconds

Duration of Stream Execution:

	Seed	Query Start Date/Time Query End Date/Time	RF1 Start Date/Time RF1 End Date/Time	RF2 Start Date/Time RF2 End Date/Time	Duration
<b>Stream 00</b>	722222226	07/22/03 23:04:03	07/22/03 23:03:14	07/22/03 23:18:59	00:16:27
		07/22/03 23:18:59	07/22/03 23:04:03	07/22/03 23:19:41	
<b>Stream 01</b>	722222227	07/22/03 23:19:47	07/23/03 00:10:05	07/23/03 00:10:55	00:47:42
		07/23/03 00:07:29	07/23/03 00:10:55	07/23/03 00:11:35	
<b>Stream 02</b>	722222228	07/22/03 23:19:48	07/23/03 00:11:35	07/23/03 00:12:17	00:48:54
		07/23/03 00:08:42	07/23/03 00:12:17	07/23/03 00:12:56	
<b>Stream 03</b>	722222229	07/22/03 23:19:47	07/23/03 00:12:56	07/23/03 00:13:39	00:48:46
		07/23/03 00:08:33	07/23/03 00:13:39	07/23/03 00:14:19	
<b>Stream 04</b>	722222230	07/22/03 23:19:47	07/23/03 00:14:19	07/23/03 00:15:01	00:50:18
		07/23/03 00:10:05	07/23/03 00:15:01	07/23/03 00:15:41	
<b>Stream 05</b>	722222231	07/22/03 23:19:48	07/23/03 00:15:41	07/23/03 00:16:23	00:49:53
		07/23/03 00:09:41	07/23/03 00:16:23	07/23/03 00:17:02	



IBM<sup>®</sup> @server<sup>™</sup> 325  
with IBM DB2<sup>®</sup> UDB 8.1

TPC-H Revision 2.0

Report Date: July 29, 2003

TPC-H Timing Intervals (in seconds):

Query	Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12
Stream 00	46.9	9.7	9.8	5.3	54.7	6.0	47.3	30.8	110.4	22.8	8.9	10.1
Stream 01	140.8	14.0	32.5	12.8	72.0	11.8	156.1	93.3	393.6	54.4	64.7	33.7
Stream 02	119.4	12.6	25.2	10.8	74.6	16.9	112.8	116.7	453.6	56.6	33.6	26.2
Stream 03	104.1	27.1	20.9	16.0	107.3	8.5	119.0	121.5	460.6	92.0	63.2	27.7
Stream 04	154.7	15.1	10.1	13.0	122.1	16.5	81.0	109.3	559.6	64.8	36.0	21.6
Stream 05	137.2	17.1	27.4	15.5	76.3	17.9	169.3	112.9	506.0	41.8	36.6	29.7
Minimum	104.1	12.6	10.1	10.8	72.0	8.5	81.0	93.3	393.6	41.8	33.6	21.6
Average	117.2	15.9	21.0	12.2	84.5	12.9	114.3	97.4	414.0	55.4	40.5	24.8
Maximum	154.7	27.1	32.5	16.0	122.1	17.9	169.3	121.5	559.6	92.0	64.7	33.7

Stream ID	Q13	Q14	Q15a	Q16	Q17	Q18	Q19	Q20	Q21	Q22	RF1	RF2
Stream 00	77.6	10.7	31.9	29.0	34.4	125.7	36.9	13.1	133.3	40.7	49.2	42.1
Stream 01	247.0	20.9	56.5	80.3	106.8	458.8	161.9	34.8	529.4	86.0	50.0	39.5
Stream 02	198.4	17.9	60.5	82.6	198.7	619.5	167.0	41.8	438.0	51.1	42.4	39.3
Stream 03	296.0	16.0	69.8	82.5	146.0	450.5	99.3	34.6	508.8	54.7	42.8	39.8
Stream 04	235.1	15.1	61.2	94.0	123.8	564.3	137.9	12.7	527.2	43.3	42.0	39.6
Stream 05	259.5	17.8	93.5	69.7	131.9	480.0	104.2	50.0	533.0	65.7	42.2	39.5
Minimum	198.4	15.1	56.5	69.7	106.8	450.5	99.3	12.7	438.0	43.3	42.0	39.3
Average	218.9	16.4	62.2	73.0	123.6	449.8	117.9	31.2	445.0	56.9	44.8	40.0
Maximum	296.0	20.9	93.5	94.0	198.7	619.5	167.0	50.0	533.0	86.0	50.0	42.1

Benchmark Sponsor: Haider Rizvi  
 Mgr., DB2 Data Warehouse  
 Performance  
 IBM Canada Ltd;  
 8200 Warden Avenue  
 Markham, Ontario L6G 1C7

July 25, 2003

I verified the TPC Benchmark™ H performance of the following configuration:

Platform: **IBM eServer 325 8-node cluster**  
 Database Manager: **IBM DB2 UDB 8.1 ESE with DPF**  
 Operating System: **SuSE Linux 8.1**

The results were:

CPU (Speed)	Memory	Disks	QphH@100GB
<b>IBM eServer 325 (each node with)</b>			
2 x AMD 64-bit Opteron (2.0 GHz)	1 MB Cache 6 GB Main	42 x 18.2 GB FASTt 1 x 18.2 GB SCSI	<b>12,216.1</b>

In my opinion, this performance result was produced in compliance with the TPC's requirements for the benchmark. The following verification items were given special attention:

- The database records were defined with the proper layout and size
- The database population was generated using DBGEN
- The database was properly scaled to 100GB and populated accordingly
- The compliance of the database auxiliary data structures was verified
- The database load time was correctly measured and reported

- The required ACID properties were verified and met
- The query input variables were generated by QGEN
- The query text was produced using minor modifications and an approved query variant
- The execution of the queries against the SF1 database produced compliant answers
- A compliant implementation specific layer was used to drive the tests
- The throughput tests involved 5 query streams
- The ratio between the longest and the shortest query was such that no query timing was adjusted
- The execution times for queries and refresh functions were correctly measured and reported
- The repeatability of the measured results was verified
- The required amount of database log was configured
- The system pricing was verified for major components and maintenance
- The major pages from the FDR were verified for accuracy

Additional Audit Notes:

None.

Respectfully Yours,

A handwritten signature in black ink, appearing to read "François Raab", with a long horizontal flourish extending to the right.

François Raab  
President



## *Table of Contents*

<b>Preface</b>	12
<b>1 General Items</b>	14
1.1 Benchmark Sponsor	14
1.2 Parameter Settings	14
1.3 Configuration Diagrams	14
1.3.1 Measured and Priced Configurations	15
<b>2 Clause 1: Logical Database Design Related Items</b>	16
2.1 Database Table Definitions	16
2.2 Database Organization	16
2.3 Horizontal Partitioning	16
2.4 Replication	16
<b>3 Clause 2: Queries and Update Functions Related Items</b>	17
3.1 Query Language	17
3.2 Random Number Generation	17
3.3 Substitution Parameters Generation	17
3.4 Query Text and Output Data from Database	17
3.5 Query Substitution Parameters and Seeds Used	17
3.6 Query Isolation Level	17
3.7 Refresh Function Implementation	18
<b>4 Clause 3: Database System Properties Related Items</b>	19
4.1 Atomicity Requirements	19
4.1.1 Atomicity of Completed Transactions	19
4.1.2 Atomicity of Aborted Transactions	19
4.2 Consistency Requirements	19
4.2.1 Consistency Condition	19
4.2.2 Consistency Tests	20
4.3 Isolation Requirements	20
4.3.1 Isolation Test 1	20
4.3.2 Isolation Test 2	20
4.3.3 Isolation Test 3	20
4.3.4 Isolation Test 4	21
4.3.5 Isolation Test 5	21

4.3.6 Isolation Test 6	22
4.4 Durability Requirements	22
4.4.1 Failure of Durable Medium Containing Recovery Log Data, and Loss of System Power/Memory	22
4.4.2 Loss of Switch Power	23
<b>5 Clause 4: Scaling and Database Population Related Items</b>	<b>24</b>
5.1 Cardinality of Tables	24
5.2 Distribution of Tables and Logs	24
5.3 Database Partition / Replication Mapping	25
5.4 RAID Implementation	25
5.5 DBGEN Modifications	25
5.6 Database Load Time	25
5.7 Data Storage Ratio	25
5.8 Database Load Mechanism Details and Illustration	25
5.9 Qualification Database Configuration	26
<b>6 Clause 5: Performance Metrics and Execution Rules Related Items</b>	<b>27</b>
6.1 System Activity between Load and Performance Tests	27
6.2 Steps in the Power Test	27
6.3 Timing Intervals for Each Query and Refresh Function	27
6.4 Number of Streams for the Throughput Test	27
6.5 Start and End Date/Times for Each Query Stream	27
6.6 Total Elapsed Time for the Measurement Interval	27
6.7 Refresh Function Start Date/Time and Finish Date/Time	27
6.8 Timing Intervals for Each Query and Each Refresh Function for Each Stream	28
6.9 Performance Metrics	28
6.10 Performance Metric and Numerical Quantities from Both Runs	28
6.11 System Activity between Tests	28
<b>7 Clause 6: SUT and Driver Implementation Related Items</b>	<b>29</b>
7.1 Driver	29
7.2 Implementation-Specific Layer	29
7.3 Profile-Directed Optimization	29
<b>8 Clause 7: Pricing Related Items</b>	<b>30</b>
8.1 Hardware and Software Components	30
8.2 Three-Year Cost of System Configuration	30
8.3 Availability Dates	30

8.4 Country-Specific Pricing	30
<b>9 Clause 8: Audit Related Items</b>	31
9.1 Auditor's Report	31
<b>Appendix A: Tunable Parameters and System Configuration</b>	32
DB2 UDB 8.1 Database and Database Manager Configuration	32
<i>Database Configuration for Node 0</i>	32
<i>Database Configuration for Node 1</i>	33
<i>Database Configuration for Node 2</i>	35
<i>Database Configuration for Node 3</i>	37
<i>Database Configuration for Node 4</i>	38
<i>Database Configuration for Node 5</i>	40
<i>Database Configuration for Node 6</i>	41
<i>Database Configuration for Node 7</i>	43
<i>Database Configuration for Node 8</i>	45
<i>Database Configuration for Node 9</i>	46
<i>Database Configuration for Node 10</i>	48
<i>Database Configuration for Node 11</i>	50
<i>Database Configuration for Node 12</i>	51
<i>Database Configuration for Node 13</i>	53
<i>Database Configuration for Node 14</i>	54
<i>Database Configuration for Node 15</i>	56
DB2 Database Manager Configuration	58
DB2 Registry Variables	59
Linux Parameters	59
<b>Appendix B: Database Build Scripts</b>	60
buildtpcd	60
create_bufferpools	74
create_indexes	74
create_nodegroups	75
create_tables	75
create_tablespaces	77
createuftbls	82
db2nodes.cfg	83
Load_db2set.ksh	83

run_db2set.ksh	83
runstats.ddl	83
load_tables.ksh	84
load_tb_customer.ddl	85
load_tb_lineitem.ddl	85
load_tb_orders.ddl	85
load_tb_part.ddl	85
load_tb_partsupp.ddl	85
load_tb_supplier.ddl	86
Load_dbcfg.ddl	86
load_dbmcfg.ddl	86
run_dbcfg.ddl	86
run_dbmcfg.ddl	86
Change_logs.ksh	86
tpcd.setup	87
<b>Appendix C: Qualification Query Output</b>	92
Qualification Queries	92
<i>Query 1</i>	92
<i>Query 2</i>	92
<i>Query 3</i>	97
<i>Query 4</i>	98
<i>Query 5</i>	98
<i>Query 6</i>	99
<i>Query 7</i>	99
<i>Query 8</i>	100
<i>Query 9</i>	100
<i>Query 10</i>	103
<i>Query 11</i>	105
<i>Query 12</i>	105
<i>Query 13</i>	106
<i>Query 14</i>	107
<i>Query 15a</i>	107
<i>Query 16</i>	108
<i>Query 17</i>	108

<i>Query 18</i>	109
<i>Query 19</i>	110
<i>Query 20</i>	111
<i>Query 21</i>	115
<i>Query 22</i>	116
First 10 Rows of the Database	117
Query Substitution Parameters	121
<b>Appendix D: Driver Source Code</b>	125
ploaduf1	125
ploaduf2	125
load_line_uf	125
load_orders_uf	125
preload_uf.ksh	125
runpower	125
runthroughput	130
tpcdbatch.h	134
tpcdbatch.sqc	136
tpcdUF.sqc	181
<b>Appendix E: ACID Transaction Source Code</b>	190
acid.h	190
acid.sqc	190
makefile	205
<b>Appendix F: Price Quotations</b>	206

## Preface

TPC Benchmark H Standard Specification was developed by the Transaction Processing Performance Council (TPC). It was released on February 26, 1999, and most recently revised (Revision 2.0) October 29, 2002. This is the full disclosure report for benchmark testing of IBM **@server** 325 according to the TPC Benchmark H Standard Specification.

The TPC Benchmark H is a decision support benchmark. It consists of a suite of business-oriented ad hoc queries and concurrent data modifications. The queries and the data populating the database have been chosen to have broad industry-wide relevance while maintaining a sufficient degree of ease of implementation. This benchmark illustrates decision support systems that:

- Examine large volumes of data;
- Execute queries with a high degree of complexity;
- Give answers to critical business questions.

TPC-H evaluates the performance of various decision support systems by the execution of set of queries against a standard database under controlled conditions. The TPC-H queries:

- Give answers to real-world business questions;
- Simulate generated ad-hoc queries (e.g., via a point-and-click GUI interface);
- Are far more complex than most OLTP transactions;
- Include a rich breadth of operators and selectivity constraints;
- Generate intensive activity on the part of the database server component of the system under test;
- Are executed against a database complying with specific population and scaling requirements;
- Are implemented with constraints derived from staying closely synchronized with an on-line production database.

The TPC-H operations are modeled as follows:

- The database is continuously available 24 hours a day, 7 days a week, for ad-hoc queries from multiple end users and data modifications against all tables, except possibly during infrequent (e.g., once a month) maintenance sessions.
- The TPC-H database tracks, possibly with some delay, the state of the OLTP database through ongoing refresh functions, which batch together a number of modifications impacting some part of the decision support database.
- Due to the worldwide nature of the business data stored in the TPC-H database, the queries and the refresh functions may be executed against the database at any time, especially in relation to each other. In addition, this mix of queries and refresh functions is subject to specific ACIDity requirements, since queries and refresh functions may execute concurrently.
- To achieve the optimal compromise between performance and operational requirements, the database administrator can set, once and for all, the locking levels and the concurrent scheduling rules for queries and refresh functions.

The minimum database required to run the benchmark holds business data from 10,000 suppliers. It contains almost 10 million rows representing a raw storage capacity of about 1 gigabyte. Compliant benchmark implementations may also use one of the larger permissible database populations (e.g., 100 gigabytes), as defined in Clause 4.1.3).

The performance metrics reported by TPC-H is called the TPC-H Composite Query-per-Hour Performance Metric (QphH@Size), and reflects multiple aspects of the capability of the system to process queries. These aspects include the selected database size against which the queries are executed, the query processing power when queries are submitted by a single stream, and the query throughput when queries are submitted by multiple concurrent users. The TPC-H Price/Performance metric is expressed as  $\$/\text{QphH@Size}$ . To be compliant with the TPC-H standard, all references to TPC-H results for a given configuration must include all required reporting components (see Clause 5.4.6). The TPC believes that comparisons of TPC-H results measured against different database sizes are misleading and discourages such comparisons.

The TPC-H database must be implemented using a commercially available database management system (DBMS), and the queries executed via an interface using dynamic SQL. The specification provides for variants of SQL, as implementers are not required to have implemented a specific SQL standard in full.

Benchmarks results are highly dependent upon workload, specific application requirements, and systems design and implementation. Relative system performance will vary as a result of these and other factors. Therefore, TPC-H should not be used as a substitute for specific customer application benchmarking when critical capacity planning and/or product evaluation decisions are contemplated.

# 1 General Items

## 1.1 Benchmark Sponsor

*A statement identifying the benchmark sponsor(s) and other participating companies must be provided.*

IBM Corporation sponsored this TPC-H benchmark.

## 1.2 Parameter Settings

*Settings must be provided for all customer-tunable parameters and options that have been changed from the defaults found in actual products, including but not limited to:*

- *Database tuning options*
- *Optimizer/Query execution options*
- *Query Processing tool/language configuration parameters*
- *Recovery/commit options*
- *Consistency/locking options*
- *Operating system and configuration parameters*
- *Configuration parameters and options for any other software component incorporated into the pricing structure*
- *Compiler optimization options.*

Appendix A, “Tunable Parameters,” contains a list of all DB2 parameters and operating system parameters. Session initialization parameters can be set during or immediately after establishing the connection to the database within the tpcdbatch program documented in Appendix D, “Driver Source Code.” This result uses the default session initialization parameters established during preprocessing/binding of the tpcdbatch program.

## 1.3 Configuration Diagrams


*Diagrams of both measured and priced configurations must be provided, accompanied by a description of the differences. This includes, but is not limited to:*

- *Number and type of processors*
- *Size of allocated memory and any specific mapping/partitioning of memory unique to the test and type of disk units (and controllers, if applicable)*
- *Number and type of disk units (and controllers, if applicable)*
- *Number of channels or bus connections to disk units, including their protocol type*
- *Number of LAN (e.g., Ethernet) connections, including routers, workstations, terminals, etc., that were physically used in the test or are incorporated into the pricing structure*
- *Type and run-time execution location of software components (e.g., DBMS, query processing tools/languages, middleware components, software drivers, etc.).*

The configuration diagram for the tested and priced system is provided on the following page.



### 1.3.1 Priced and Measured Configurations



The priced configuration was an 8 x IBM **e**server 325 each with

- Two 2GHz AMD 64-bit Opteron Model 246 processors
- 6 GB of memory
- One QLA2342 HBA (2 ports x 2G bps FC)
- One IBM FC2-133 HBA (1 port x 2G bps FC)
- One 18.2GB 15K Ultra160 SCSI disk drive
- Forty-two 18.2GB 15K FC Hot-swap Drives
- Three IBM TotalStorage FAStT EXP700 drive cases

For full details of the priced configuration see the pricing spreadsheet in the Executive Summary.

## **2 Clause 1: Logical Database Design Related Items**

### ***2.1 Database Table Definitions***

*Listings must be provided for all table definition statements and all other statements used to set up the test and qualification databases. (8.1.2.1)*

Appendix B contains the scripts that were used to set up the TPC-H test and qualification databases.

### ***2.2 Database Organization***

*The physical organization of tables and indexes within the test and qualification databases must be disclosed. If the column ordering of any table is different from that specified in Clause 1.4, it must be noted.*

Appendix B contains the scripts that were used to create the indexes on the test and qualification databases.

### ***2.3 Horizontal Partitioning***

*Horizontal partitioning of tables and rows in the test and qualification databases must be disclosed (see Clause 1.5.4).*

Horizontal partitioning was used for all tables except for the nation and region tables. See Appendix B, "Database Build Scripts."

### ***2.4 Replication***

*Any replication of physical objects must be disclosed and must conform to the requirements of Clause 1.5.6).*

No replication was used.

## **3 Clause 2: Queries and Update Functions Related Items**

### ***3.1 Query Language***

*The query language used to implement the queries must be identified.*

SQL was the query language used.

### ***3.2 Random Number Generation***

*The method of verification for the random number generation must be described unless the supplied DBGEN and QGEN were used.*

The TPC-supplied DBGEN version 1.3.0 and QGEN version 1.3.0 were used to generate all database populations.

### ***3.3 Substitution Parameters Generation***

*The method used to generate values for substitution parameters must be disclosed. If QGEN is not used for this purpose, then the source code of any non-commercial tool used must be disclosed. If QGEN is used, the version number, release number, modification number and patch level of QGEN must be disclosed.*

The supplied QGEN version 1.3.0 was used to generate the substitution parameters.

### ***3.4 Query Text and Output Data from Database***

*The executable query text used for query validation must be disclosed along with the corresponding output data generated during the execution of the query text against the qualification database. If minor modifications (see Clause 2.2.3) have been applied to any functional query definitions or approved variants in order to obtain executable query text, these modifications must be disclosed and justified. The justification for a particular minor query modification can apply collectively to all queries for which it has been used. The output data for the power and throughput tests must be made available electronically upon request.*

Appendix C.1, “Qualification Queries,” contains the output for each of the queries. The functional query definitions and variants used in this disclosure use the following minor query modifications:

- Table names and view names are fully qualified. For example, the nation table is referred to as “TPCD.NATION.”
- The standard IBM SQL date syntax is used for date arithmetic. For example, DATE(‘1996-01-01’)+3 MONTHS.
- The semicolon (;) is used as a command delimiter.

### ***3.5 Query Substitution Parameters and Seeds Used***

*All query substitution parameters used for all performance tests must be disclosed in tabular format, along with the seeds used to generate these parameters.*

Appendix C contains the seed and query substitution parameters used.

### ***3.6 Query Isolation Level***

*The isolation level used to run the queries must be disclosed. If the isolation level does not map closely to one of the isolation levels defined in Clause 3.4, additional descriptive detail must be provided.*

The isolation level used to run the queries was “repeatable read.”

### **3.7 Refresh Function Implementation**

*The details of how the refresh functions were implemented must be disclosed (including source code of any non-commercial program used).*

The refresh functions are part of the implementation-specific layer/driver code included in Appendix D, "Driver Source Code."

## 4 Clause 3: Database System Properties Related Items

*The results of the ACID tests must be disclosed, along with a description of how the ACID requirements were met. This includes disclosing the code written to implement the ACID Transaction and Query.*

All ACID tests were conducted according to specifications. The Atomicity, Isolation, Consistency and Durability tests were performed on the IBM **@server** 325. Appendix E contains the ACID transaction source code.

### 4.1 Atomicity Requirements

*The system under test must guarantee that transactions are atomic; the system will either perform all individual operations on the data, or will assure that no partially completed operations leave any effects on the data.*

#### 4.1.1 Atomicity of Completed Transactions

*Perform the ACID transactions for a randomly selected set of input data and verify that the appropriate rows have been changed in the ORDER, LINEITEM and HISTORY tables.*

The following steps were performed to verify the Atomicity of completed transactions.

1. The total price from the ORDER table and the extended price from the LINEITEM table were retrieved for a randomly selected order key. The number of records in the HISTORY table was also retrieved.
2. The ACID Transaction T1 was executed for the order key used in step 1.
3. The total price and extended price were retrieved for the same order key used in step 1 and step 2.

It was verified that:

$$T1.EXTENDEDPRICE=OLD.EXTENDEDPRICE+((T1.DELTA)*$$
$$(OLD.EXTENDEDPRICE/OLD.QUANTITY)),T1.TOTALPRICE=OLD.TOTALPRICE+$$
$$((T1.EXTENDEDPRICE-OLD.EXTENDEDPRICE)*(1-DISCOUNT)*(1+TAX)),$$
 and that

the number of records in the History table had increased by 1.

#### 4.1.2 Atomicity of Aborted Transactions

*Perform the ACID transactions for a randomly selected set of input data, and verify that the appropriate rows have been changed in the ORDER, LINEITEM and HISTORY tables.*

The following steps were performed to verify the Atomicity of the aborted ACID transaction:

1. The ACID application is passed a parameter to execute a rollback of the transaction instead of performing the commit.
2. The total price from the ORDER table and the extended price from the LINEITEM table were retrieved for a random order key. The number of records in the HISTORY table was also retrieved.
3. The ACID transaction was executed for the orderkey used in step 2. The transaction was rolled back.
4. The total price and the extended price were retrieved for the same orderkey used in step 2 and step 3. It was verified that the extended price and the total price were the same as in step 2.

### 4.2 Consistency Requirements

*Consistency is the property of the application that requires any execution of transactions to take the database from one consistent state to another.*

#### 4.2.1 Consistency Condition

*A consistent state for the TPC-H database is defined to exist when:*

$$O\_TOTALPRICE=SUM(L\_EXTENDEDPRICE*(1-L\_DISCOUNT)*(1+L\_TAX)$$

for each ORDER and LINEITEM defined by (O\_ORDERKEY=L\_ORDERKEY)

The following queries were executed before and after a measurement to show that the database was always in a consistent state both initially and after a measurement.

```
SELECT DECIMAL(SUM(DECIMAL(INTEGER(INTEGER(DECIMAL
(INTEGER(100*DECIMAL(L_EXTENDEDPRICE,20,2)),20,3)*
(1-L_DISCOUNT))*(1+L_TAX)),20,3)/100.0),20,3)
FROM TPCD.LINEITEM WHERE L_ORDEYKEY=okey
SELECT DECIMAL(SUM(O_TOTALPRICE,20,3)) from TPCD.ORDERS WHERE
O_ORDERKEY = okey
```

## **4.2.2 Consistency Tests**

*Verify that the ORDER and LINEITEM tables are initially consistent as defined in Clause 3.3.2.1, based on a random sample of at least 10 distinct values of O\_ORDERKEY.*

The queries defined in 4.2.1, “Consistency Condition,” were run after initial database build and prior to executing the ACID transaction. The queries showed that the database was in a consistent condition.

After executing 7 streams of 100 ACID transactions each, the queries defined in 4.2.1, “Consistency Condition,” were run again. The queries showed that the database was still in a consistent state.

## **4.3 Isolation Requirements**

### **4.3.1 Isolation Test 1**

*This test demonstrates isolation for the read-write conflict of a read-write transaction and a read-only transaction when the read-write transaction is committed.*

The following steps were performed to satisfy the test of isolation for a read-only and a read-write committed transaction:

1. First session: Start an ACID transaction with a randomly selected O\_KEY, L\_KEY and DELTA. The transaction is delayed for 60 seconds just prior to the Commit.
2. Second session: Start an ACID query for the same O\_KEY as in the ACID transaction.
3. Second session: The ACID query attempts to read the file but is locked out by the ACID transaction waiting to complete.
4. First session: The ACID transaction is released and the Commit is executed releasing the record. With the LINEITEM record now released, the ACID query can now complete.
5. Second session: Verify that the ACID query delays for approximately 60 seconds and that the results displayed for the ACID query match the input for the ACID transaction.

### **4.3.2 Isolation Test 2**

*This test demonstrates isolation for the read-write conflict of read-write transaction and read-only transaction when the read-write transaction is rolled back.*

The following steps were performed to satisfy the test of isolation for read-only and a rolled back read-write transaction:

1. First session: Perform the ACID transaction for a random O\_KEY, L\_KEY and DELTA. The transaction is delayed for 60 seconds just prior to the Rollback.
2. Second session: Start an ACID query for the same O\_KEY as in the ACID transaction. The ACID query attempts to read the LINEITEM table but is locked out by the ACID transaction.
3. First session: The ACID transaction is released and the Rollback is executed, releasing the read.
4. Second session: With the LINEITEM record now released, the ACID query completes.

### **4.3.3 Isolation Test 3**

*This test demonstrates isolation for the write-write conflict of two refresh transactions when the first transaction is committed.*

The following steps were performed to verify isolation of two refresh transactions:

1. First session: Start an ACID transaction T1 for a randomly selected O\_KEY, L\_KEY and DELTA. The transaction is delayed for 60 seconds just prior to the COMMIT.
2. Second session: Start a second ACID transaction T2 for the same O\_KEY, L\_KEY, and for a randomly selected DELTA2. This transaction is forced to wait while the 1st session holds a lock on the LINEITEM record requested by the second session.
3. First session: The ACID transaction T1 is released and the Commit is executed, releasing the record. With the LINEITEM record now released, the ACID transaction T2 can now complete.
4. Verify that:
 
$$T2.L\_EXTENDEDPRICE = T1.L\_EXTENDEDPRICE + DELTA * (T1.L\_EXTENDEDPRICE / T1.L\_QUANTITY)$$

#### **4.3.4 Isolation Test 4**

*This test demonstrates isolation for write-write conflict of two ACID transactions when the first transaction is rolled back.*

The following steps were performed to verify the isolation of two ACID transactions after the first one is rolled back:

1. First session: Start an ACID transaction T1 for a randomly selected O\_KEY, L\_KEY, and DELTA. The transaction is delayed for 60 seconds just prior to the rollback.
2. Second session: Start a second ACID transaction T2 for the same O\_KEY, L\_KEY used by the 1st session. This transaction is forced to wait while the 1st session holds a lock on the LINEITEM record requested by the second session.
3. First session: Rollback the ACID transaction T1. With the LINEITEM record now released, the ACID transaction T2 completes.
4. Verify that  $T2.L\_EXTENDEDPRICE = T1.L\_EXTENDEDPRICE$

#### **4.3.5 Isolation Test 5**

*This test demonstrates the ability of read and write transactions affecting different database tables to make progress concurrently.*

1. First session: Start an ACID transaction, T1, for a randomly selected O\_KEY, L\_KEY and DELTA. The ACID transaction was suspended prior to COMMIT.
2. First session: Start a second ACID transaction, T2, which selects random values of PS\_PARTKEY and PS\_SUPPKEY and returns all columns of the PARTSUPP table for which PS\_PARTKEY and PS\_SUPPKEY are equal to the selected values.
3. T2 completed.
4. T1 was allowed to complete.
5. It was verified that the appropriate rows in the ORDERS, LINEITEM and HISTORY tables have been changed.

### **4.3.6 Isolation Test 6**

*This test demonstrates that the continuous submission of arbitrary (read-only) queries against one or more tables of the database does not indefinitely delay refresh transactions affecting those tables from making progress.*

1. First session: A transaction T1, which executes modified TPC-H query 1 with DELTA=0, was started.
2. Second session: Before T1 completed, an ACID transaction T2, with randomly selected values of O\_KEY, L\_KEY and DELTA, was started.
3. Third session: Before T1 completed, a transaction T3, which executes modified TPC-H query 1 with a randomly selected value of DELTA (not equal to 0), was started.
4. T1 completed.
5. T2 completed.
6. T3 completed.
7. It was verified that the appropriate rows in the ORDERS, LINEITEM and HISTORY tables were changed.

### **4.4 Durability Requirements**

*The SUT must guarantee durability: the ability to preserve the effects of committed transactions and ensure database consistency after recovery from any one of the failures listed in Clause 3.5.3.*

#### **4.4.1 Failure of Durable Medium Containing Recovery Log Data, and Loss of System Power/Memory**

*Guarantee the database and committed updates are preserved across a permanent irrecoverable failure of any single durable medium containing TPC-H database tables or recovery log tables.*

The database log was stored on RAID-1 protected storage. The tables for the database were stored on RAID-1 protected storage. A backup of the database was taken to a separate array for drives than those used for the database.

The tests were conducted on the qualification database. The steps performed are shown below.

1. The consistency test described in section 4.2.1 was verified.
2. The current count of the total number of records in the HISTORY table was determined giving hist1.
3. A test to run 200 ACID transactions on each of 7 execution streams was started such that each stream executes a different set of transactions.
4. One of the disks containing the DB2 transaction log recovery data was powered off after at least 30 ACID transactions had completed from each of the execution streams.
5. Because the disks were in RAID 1 configuration the applications continued running the ACID transactions.
6. One of the disks containing the DB2 database tables was powered off after at least 30 additional ACID transactions had completed from each of the execution streams.
7. Because the disks were in RAID 1 configuration the applications continued running the ACID transactions.
8. The system was shutdown by switching off circuit breakers on the power rail connected to all system component cabinets, after at least a total of 100 transactions had completed for each stream.
9. The system was powered back on and rebooted.
10. All volumes were re-established and mirrored volumes were synchronized.
11. Step 2 was performed giving hist2. It was verified that hist2 - hist1 was greater than or equal to the number of records in the success file.
12. Consistency condition described in 4.2.1 was verified.



#### ***4.4.2. Loss of Switch Power***

This test was conducted on the qualification database. The following steps were performed:

1. The consistency test described in section 4.2.1 was verified.
2. The current count of the total number of records in the HISTORY table was determined giving hist1.
3. A test to run 200 ACID transactions on each of 10 execution streams was started such that each stream executes a different set of transactions.
4. The Gigabit switch was disconnected from the system.
5. Database detected the network loss and terminated processing.
6. Network connections were reestablished and the database was restarted.
7. Step 2 was performed giving hist2. It was verified that  $hist2 - hist1$  was greater than or equal to the number of records in the success file.
8. Consistency condition described in 4.2.1 was verified.

## 5 Clause 4: Scaling and Database Population Related Items

### 5.1 Cardinality of Tables

The cardinality (e.g., the number of rows) of each table of the test database, as it existed at the completion of the database load (see Clause 4.2.5), must be disclosed.

Table Name	Rows
Order	150,000,000
Lineitem	600,037,902
Customer	15,000,000
Part	20,000,000
Supplier	1,000,000
Partsupp	80,000,000
Nation	25
Region	5

### 5.2 Distribution of Tables and Logs

The distribution of tables and logs across all media must be explicitly described.

DB2 was configured on an 8 node IBM eServer 325 test system. Each node had:

- 1 IBM FC2-133 Host Bus Adapter and 1 Qlogic QLA 2342 Host Bus Adapter.
- 3 (IBM TotalStorage FAStT EXP700 enclosures) × 14 (15K FC Hot-Swap Drive) × 18.2 GB and 1 18.2GB 15K Ultra160 SCSI Hot-Swap Drive internal disk drive.

Each e325 had 22 RAID 1 volumes. 20 of these volumes were created using linux software raid provided in SuSE Linux Enterprise Server 8 on 40 partitions across the 3 EXP700 enclosures so that there were 7 volumes on the first 2 enclosures and 6 volumes on the third enclosure. 2 addition RAID 1 volumes were created on the third enclosure by mirroring 4 partitions that were created on the remaining 2 drives.

The tablespace for NATION and REGION were stored on a single RAID volume only on node 1.

For each node, 20 RAID volumes were used for the table and index data tablespace(DATA\_INDEX), the temp space tablespaces (TEMPSPACE)were placed on the same 40 disks on separate partitions shared by the table and index tablespace , database logs were placed on the remaining 2 RAID devices.

The Operating System resided on an internal disk on each node. The benchmark executing programs resided on a shared home directory NFS mounted from node 1. The database software resided on an internal disk on each node along with staging data for RF functions.

### 5.3 Database Partition / Replication Mapping

*The mapping of database partitions/replications must be explicitly described.*

The database was not replicated. The database was logically partitioned into 16 logical nodes, 2 nodes on each physical server.

### 5.4 RAID Implementation

*Implementations may use some form of RAID to ensure high availability. If used for data, auxiliary storage (e.g., indexes) or temporary space, the level of RAID must be disclosed for each device.*

RAID level 1 was used across all database tables, indexes, and recovery logs through linux software raid provided with SuSE Linux Enterprise Server 8.

### 5.5 DBGEN Modifications

*Any modifications to the DBGEN (see Clause 4.2.1) source code must be disclosed. In the event that a program other than DBGEN was used to populate the database, it must be disclosed in its entirety.*

The standard distribution DBGEN version 1.3.0 was used for database population. No modifications were made.

### 5.6 Database Load Time

*The database load time for the test database (see Clause 4.3) must be disclosed.*

See the Executive Summary at the beginning of this report.

### 5.7 Data Storage Ratio

*The data storage ratio must be disclosed. It is computed as the ratio between the total amount of priced disk space and the chosen test database size as defined in Clause 4.1.3.*

The calculation of the data storage ratio is shown in the following table.

Disk Type	Number of Disks	Formatted Space per Disk	Total Disk Space	Scale Factor	Storage Ratio
18.2GB 15K Ultra160 SCSI Drive	336	16.95GB	5695.45GB		
18.2GB 15K Ultra160 SCSI Hot-Swap Drive	8	16.95GB	135.61GB		
Total			5831.06GB	100	58.31

The data storage ratio is 58.31, derived by dividing 5831.06GB by the database size of 100GB.


### 5.8 Database Load Mechanism Details and Illustration

*The details of the database load must be disclosed, including a block diagram illustrating the overall process. Disclosure of the load procedure includes all steps, scripts, input and configuration files required to completely reproduce the test and qualification databases.*

Flat files for each of the tables were created using DBGEN.

The NATION and REGION tables were created on node 0 and then loaded from dbgen output. The other tables were loaded on 16 logical nodes.

The tables were loaded as depicted in Figure 4-1.



**Figure 4-1. Database Load Procedure**

### ***5.9 Qualification Database Configuration***

*Any differences between the configuration of the qualification database and the test database must be disclosed.*

The qualification database used identical scripts and same set of disks to create and load the data. There was no difference between the configuration of the qualification database and the test database. See Section 5.2 for details.

## **6 Clause 5: Performance Metrics and Execution Rules Related Items**

### ***6.1 System Activity between Load and Performance Tests***

*Any system activity on the SUT that takes place between the conclusion of the load test and the beginning of the performance test must be fully disclosed.*

The auditor requested that queries be run against the database to verify the correctness of the database load.

### ***6.2 Steps in the Power Test***

*The details of the steps followed to implement the power test (e.g., system reboot, database restart) must be disclosed.*

The following steps were used to implement the power test:

1. RF1 Refresh Transaction
2. Stream 00 Execution
3. RF2 Refresh Transaction

### ***6.3 Timing Intervals for Each Query and Refresh Function***

*The timing intervals for each query of the measured set and for both update functions must be reported for the power test.*

See the Numerical Quantities Summary in the Executive Summary at the beginning of this report.

### ***6.4 Number of Streams for the Throughput Test***

*The number of execution streams used for the throughput test must be disclosed.*

Five streams were used for the throughput test.

### ***6.5 Start and End Date/Times for Each Query Stream***

*The start time and finish time for each query execution stream must be reported for the throughput test.*

See the Numerical Quantities Summary in the Executive Summary at the beginning of this report.

### ***6.6 Total Elapsed Time for the Measurement Interval***

*The total elapsed time for the measurement interval must be reported for the throughput test.*

See the Numerical Quantities Summary in the Executive Summary at the beginning of this report..

### ***6.7 Refresh Function Start Date/Time and Finish Date/Time***

*The start time and finish time for each update function in the update stream must be reported for the throughput test.*

See the Numerical Quantities Summary in the Executive Summary at the beginning of this report.

### **6.8 Timing Intervals for Each Query and Each Refresh Function for Each Stream**

*The timing intervals for each query of each stream and for each update function must be reported for the throughput test.*

See the Numerical Quantities Summary in the Executive Summary at the beginning of this report.

### **6.9 Performance Metrics**

*The computed performance metrics, related numerical quantities, and the price/performance metric must be reported.*

See the Numerical Quantities Summary in the Executive Summary at the beginning of this report.

### **6.10 Performance Metric and Numerical Quantities from Both Runs**

*The performance metric and numerical quantities from both runs must be disclosed.*

Two consecutive runs of the TPC-H benchmark were performed. The following table contains the results for both runs.

	<b>QppH @ 100GB</b>	<b>QthH @ 100GB</b>	<b>QphH @ 100GB</b>
<b>Run1</b>	12941.2	11531.7	12216.1
<b>Run2</b>	12996.2	11494.9	12222.5

### **6.11 System Activity between Tests**

*Any activity on the SUT that takes place between the conclusion of Run1 and the beginning of Run2 must be disclosed.*

DB2 was restarted between runs.

## 7 Clause 6: SUT and Driver Implementation Related Items

### 7.1 Driver

*A detailed textual description of how the driver performs its functions, how its various components interact and any product functionality or environmental setting on which it relies must be provided. All related source code, scripts and configurations must be disclosed. The information provided should be sufficient for an independent reconstruction of the driver.*

Appendix D, “Driver Source Code,” contains the source code used for the driver and all scripts used in connection with it.

The Power test is invoked by calling `tpcdbatch` with the stream number 0 specified, an indication that the refresh functions must be run, and the SQL file that contains the power stream queries.

The Throughput test is invoked by initiating a call to `tpcdbatch` for every query stream that will be run. `tpcdbatch` gets the stream number for each of the streams, and the SQL file specific to that stream number as the queries to execute. The refresh function is initiated as a separate call to `tpcdbatch` with the SQL script for the refresh functions and the total number of query streams specified.

### 7.2 Implementation-Specific Layer

*If an implementation-specific layer is used, then a detailed description of how it performs its functions must be supplied, including any related source code or scripts. This description should allow an independent reconstruction of the implementation-specific layer.*

The implementation specific layer is a single executable SQL application that uses embedded dynamic SQL to process the EQT generated by QGEN. The application is called `tpcdbatch` to indicate that it processes a batch of TPC-H queries, although it is completely capable of processing any arbitrary SQL statement (both DML and DDL).

A separate instance of `tpcdbatch` is invoked for each stream. Each instance establishes a distinct connection to the database server through which the EQT is transmitted to the database and the results are returned through the implementation specific layer to the driver. When an instance of `tpcdbatch` is invoked, it is provided with a context of whether it is running a power test, query stream or refresh stream, as well as an input file containing the 22 queries and/or refresh functions. `tpcdbatch` then connects to the database, performs any session initialization as well as preparing output files required by the auditor. Then it proceeds to read from the input file and processes each query or refresh function in turn.

For queries, each query is prepared, described, and a cursor is opened and used to fetch the required number of rows. After the last row has been retrieved a commit is issued. For the refresh functions, during the database build all data is first split for each node using the `db2split` utility. For RF1, the data for each node is further split into  $n$  equal portions for both the `lineitem` and `orders` tables taking care that the records for the same orderkey remain in the same set. For RF2, the data for each node is further split into  $m$  equal portions. During the run, when `tpcdbatch` encounters a call to execute RF1, it first calls a shell script which loads these  $n$  sets of data into  $n$  sets of temporary tables (one each for `lineitem` and `orders`). Then `tpcdbatch` forks off  $n$  children to do an insert with `subselect` into the original `lineitem` and `orders` tables. When `tpcdbatch` encounters a call to execute RF2, it calls a shell script that loads these data into a single staging table. Then `tpcdbatch` forks off  $p$  children (where  $p * x = m$ ) to do  $x$  sets of deletes from the `orders` and `lineitem` tables with a `subselect` from the staging table.

### 7.3 Profile-Directed Optimization

Profile-directed optimization was not used.

## **8 Clause 7: Pricing Related Items**

### ***8.1 Hardware and Software Components***

*A detailed list of the hardware and software used in the priced system must be reported. Each item must have a vendor part number, description and release/revision level, and either general availability status or committed delivery date. If package-pricing is used, contents of the package must be disclosed. Pricing source(s) and effective date(s) must also be reported.*

A detailed list of all hardware and software, including the 3-year price, is provided in the Executive Summary at the front of this report. The price quotations are included in Appendix F.

### ***8.2 Three-Year Cost of System Configuration***

*The total 3-year price of the entire configuration must be reported, including hardware, software and maintenance charges. Separate component pricing is recommended. The basis of all discounts must be disclosed.*

A detailed list of all hardware and software, including the 3-year price, is provided in the Executive Summary at the front of this report. The price quotations are included in Appendix F.

### ***8.3 Availability Dates***

*The committed delivery date for general availability (availability date) of products used in the price calculations must be reported. When the priced system includes products with different availability dates, availability date reported on the Executive Summary must be the date by which all components are committed to being available. The Full Disclosure Report must report availability dates individually for at least each of the categories for which a pricing subtotal must be provided (see Clause 7.3.1.3).*

The system as priced will be generally available November 8, 2003.

### ***8.4 Country-Specific Pricing***

*Additional Clause 7 related items may be included in the Full Disclosure Report for each country-specific priced configuration. Country-specific pricing is subject to Clause 7.1.7.*

The configuration is priced for the United States of America.



## **9 Clause 8: Audit Related Items**

### ***9.1 Auditor's Report***

*The auditor's agency name, address, phone number, and Attestation letter with a brief audit summary report indicating compliance must be included in the Full Disclosure Report. A statement should be included specifying who to contact in order to obtain further information regarding the audit process.*

This implementation of the TPC Benchmark H was audited by Francois Raab of InfoSizing, Inc. Further information can be downloaded from [www.tpc.org](http://www.tpc.org).

## Appendix A: Tunable Parameters and System Configuration

### DB2 UDB 8.1 Database and Database Manager Configuration

#### Database Configuration for Node 0

Database Configuration for Database TPCD		
Database configuration release level	=	Database heap (4KB) (DBHEAP)
0x0a00		= 10000
Database release level	=	Size of database shared memory (4KB)
0x0a00		(DATABASE_MEMORY) = AUTOMATIC
		Catalog cache size (4KB)
		(CATALOGCACHE_SZ) = (MAXAPPLS*4)
Database territory	= US	Log buffer size (4KB) (LOGBUFSZ)
Database code page	= 819	= 2048
Database code set	=	Utilities heap size (4KB)
ISO8859-1		(UTIL_HEAP_SZ) = 5000
Database country/region code	= 1	Buffer pool size (pages) (BUFFPAGE)
		= 1000
Dynamic SQL Query management		Extended storage segments size (4KB)
(DYN_QUERY_MGMT) = DISABLE		(ESTORE_SEG_SZ) = 16000
		Number of extended storage segments
Discovery support for this database		(NUM_ESTORE_SEGS) = 0
(DISCOVER_DB) = ENABLE		Max storage for lock list (4KB)
Default query optimization class		(LOCKLIST) = 40000
(DFT_QUERYOPT) = 7		
Degree of parallelism		Max size of appl. group mem set (4KB)
(DFT_DEGREE) = 1		(APPGROUP_MEM_SZ) = 2000
Continue upon arithmetic exceptions		Percent of mem for appl. group heap
(DFT_SQLMATHWARN) = NO		(GROUPHEAP_RATIO) = 70
Default refresh age		Max appl. control heap size (4KB)
(DFT_REFRESH_AGE) = 0		(APP_CTL_HEAP_SZ) = 512
Number of frequent values retained		
(NUM_FREQVALUES) = 0		Sort heap thres for shared sorts (4KB)
Number of quantiles retained		(SHEAPTHRES_SHR) = 250
(NUM_QUANTILES) = 300		Sort list heap (4KB) (SORTHEAP) =
		20000
Backup pending	= NO	SQL statement heap (4KB)
		(STMTHEAP) = 10000
Database is consistent	= YES	Default application heap (4KB)
Rollforward pending	= NO	(APPLHEAPSZ) = 1024
Restore pending	= NO	Package cache size (4KB)
		(PCKCACHESZ) = (MAXAPPLS*8)
Multi-page file allocation enabled	=	Statistics heap size (4KB)
NO		(STAT_HEAP_SZ) = 4384
		Interval for checking deadlock (ms)
Log retain for recovery status	= NO	(DLCHKTIME) = 10000
User exit for logging status	= NO	Percent. of lock lists per application
		(MAXLOCKS) = 20
Data Links Token Expiry Interval (sec)		Lock timeout (sec)
(DL_EXPINT) = 60		(LOCKTIMEOUT) = -1

Changed pages threshold (CHNGPGS_THRESH) = 60		User exit for logging enabled (USEREXIT) = OFF
Number of asynchronous page cleaners (NUM_IOCLEANERS) = 4		Auto restart enabled (AUTORESTART) = ON
Number of I/O servers (NUM_IOSERVERS) = 4		Index re-creation time (INDEXREC) = SYSTEM (RESTART)
Index sort flag (INDEXSORT) = YES		Default number of loadrec sessions (DFT_LOADREC_SES) = 1
Sequential detect flag (SEQDETECT) = YES		Number of database backups to retain (NUM_DB_BACKUPS) = 12
Default prefetch size (pages) (DFT_PREFETCH_SZ) = 32		Recovery history retention (days) (REC_HIS_RETENTN) = 366
Track modified pages (TRACKMOD) = OFF		TSM management class (TSM_MGMTCLASS) =
Default number of containers = 1		TSM node name (TSM_NODENAME) =
Default tablespace extentsize (pages) (DFT_EXTENT_SZ) = 32		TSM owner (TSM_OWNER) =
Max number of active applications (MAXAPPLS) = AUTOMATIC		TSM password (TSM_PASSWORD) =
Average number of active applications (AVG_APPLS) = 1		
Max DB files open per application (MAXFILOP) = 1024		
Log file size (4KB) (LOGFILSIZ) = 50000		
Number of primary log files (LOGPRIMARY) = 4		
Number of secondary log files (LOGSECOND) = 1		
Changed path to log files (NEWLOGPATH) =		
Path to log files = /dev/raw/raw61		
Overflow log path (OVERFLOWLOGPATH) =		
Mirror log path (MIRRORLOGPATH) =		
First active log file =		
Block log on disk full (BLK_LOG_DSK_FUL) = NO		
Percent of max active log space by transaction (MAX_LOG) = 0		
Num. of active log files for 1 active UOW (NUM_LOG_SPAN) = 0		
Group commit count (MINCOMMIT) = 2		
Percent log file reclaimed before soft chckpt (SOFTMAX) = 360		
Log retain for recovery enabled (LOGRETAIN) = OFF		
		<b>Database Configuration for Node 1</b>
		Database Configuration for Database TPCD
		Database configuration release level = 0x0a00
		Database release level = 0x0a00
		Database territory = US
		Database code page = 819
		Database code set = ISO8859-1
		Database country/region code = 1
		Dynamic SQL Query management (DYN_QUERY_MGMT) = DISABLE
		Discovery support for this database (DISCOVER_DB) = ENABLE
		Default query optimization class (DFT_QUERYOPT) = 7
		Degree of parallelism (DFT_DEGREE) = 1
		Continue upon arithmetic exceptions (DFT_SQLMATHWARN) = NO
		Default refresh age (DFT_REFRESH_AGE) = 0
		Number of frequent values retained (NUM_FREQVALUES) = 0
		Number of quantiles retained (NUM_QUANTILES) = 300

Backup pending	= NO	SQL statement heap (4KB) (STMTHEAP) = 10000
Database is consistent	= YES	Default application heap (4KB) (APPLHEAPSZ) = 1024
Rollforward pending	= NO	Package cache size (4KB)
Restore pending	= NO	(PCKCACHESZ) = (MAXAPPLS*8)
Multi-page file allocation enabled	=	Statistics heap size (4KB) (STAT_HEAP_SZ) = 4384
NO		Interval for checking deadlock (ms) (DLCHKTIME) = 10000
Log retain for recovery status	= NO	Percent. of lock lists per application
User exit for logging status	= NO	(MAXLOCKS) = 20
		Lock timeout (sec) (LOCKTIMEOUT) = -1
Data Links Token Expiry Interval (sec) (DL_EXPINT) = 60		Changed pages threshold (CHNGPGS_THRESH) = 60
Data Links Write Token Init Expiry Interval(DL_WT_IEXPINT) = 60		Number of asynchronous page cleaners (NUM_IOCLEANERS) = 4
Data Links Number of Copies (DL_NUM_COPIES) = 1		Number of I/O servers (NUM_IOSERVERS) = 4
Data Links Time after Drop (days) (DL_TIME_DROP) = 1		Index sort flag (INDEXSORT) =
Data Links Token in Uppercase (DL_UPPER) = NO		YES
Data Links Token Algorithm (DL_TOKEN) = MAC0		Sequential detect flag (SEQDETECT) = YES
Database heap (4KB) (DBHEAP) = 10000		Default prefetch size (pages) (DFT_PREFETCH_SZ) = 32
Size of database shared memory (4KB) (DATABASE_MEMORY) = AUTOMATIC		Track modified pages (TRACKMOD) = OFF
Catalog cache size (4KB) (CATALOGCACHE_SZ) = (MAXAPPLS*4)		Default number of containers = 1
Log buffer size (4KB) (LOGBUFSZ) = 2048		Default tablespace extentsize (pages) (DFT_EXTENT_SZ) = 32
Utilities heap size (4KB) (UTIL_HEAP_SZ) = 5000		Max number of active applications (MAXAPPLS) = AUTOMATIC
Buffer pool size (pages) (BUFFPAGE) = 1000		Average number of active applications (AVG_APPLS) = 1
Extended storage segments size (4KB) (ESTORE_SEG_SZ) = 16000		Max DB files open per application (MAXFILOP) = 1024
Number of extended storage segments (NUM_ESTORE_SEGS) = 0		Log file size (4KB) (LOGFILSIZ) =
Max storage for lock list (4KB) (LOCKLIST) = 40000		50000
Max size of appl. group mem set (4KB) (APPGROUP_MEM_SZ) = 2000		Number of primary log files (LOGPRIMARY) = 4
Percent of mem for appl. group heap (GROUPHEAP_RATIO) = 70		Number of secondary log files (LOGSECOND) = 1
Max appl. control heap size (4KB) (APP_CTL_HEAP_SZ) = 512		Changed path to log files (NEWLOGPATH) =
Sort heap thres for shared sorts (4KB) (SHEAPTHRES_SHR) = 250		Path to log files =
Sort list heap (4KB) (SORTHEAP) =		/dev/raw/raw62
20000		Overflow log path (OVERFLOWLOGPATH) =
		Mirror log path (MIRRORLOGPATH) =

First active log file	=	Discovery support for this database	
Block log on disk full		(DISCOVER_DB) = ENABLE	
(BLK_LOG_DSK_FUL) = NO		Default query optimization class	
Percent of max active log space by		(DFT_QUERYOPT) = 7	
transaction(MAX_LOG) = 0		Degree of parallelism	
Num. of active log files for 1 active		(DFT_DEGREE) = 1	
UOW(NUM_LOG_SPAN) = 0		Continue upon arithmetic exceptions	
Group commit count		(DFT_SQLMATHWARN) = NO	
(MINCOMMIT) = 2		Default refresh age	
Percent log file reclaimed before soft ckcpt		(DFT_REFRESH_AGE) = 0	
(SOFTMAX) = 360		Number of frequent values retained	
Log retain for recovery enabled		(NUM_FREQVALUES) = 0	
(LOGRETAIN) = OFF		Number of quantiles retained	
User exit for logging enabled		(NUM_QUANTILES) = 300	
(USEREXIT) = OFF		Backup pending	= NO
Auto restart enabled		Database is consistent	= YES
(AUORESTART) = ON		Rollforward pending	= NO
Index re-creation time	(INDEXREC)	Restore pending	= NO
= SYSTEM (RESTART)		Multi-page file allocation enabled	=
Default number of loadrec sessions		NO	
(DFT_LOADREC_SES) = 1		Log retain for recovery status	= NO
Number of database backups to retain		User exit for logging status	= NO
(NUM_DB_BACKUPS) = 12		Data Links Token Expiry Interval (sec)	
Recovery history retention (days)		(DL_EXPINT) = 60	
(REC_HIS_RETENTN) = 366		Data Links Write Token Init Expiry	
TSM management class		Intvl(DL_WT_IEXPINT) = 60	
(TSM_MGMTCLASS) =		Data Links Number of Copies	
TSM node name		(DL_NUM_COPIES) = 1	
(TSM_NODENAME) =		Data Links Time after Drop (days)	
TSM owner	(TSM_OWNER)	(DL_TIME_DROP) = 1	
=		Data Links Token in Uppercase	
TSM password		(DL_UPPER) = NO	
(TSM_PASSWORD) =		Data Links Token Algorithm	
		(DL_TOKEN) = MAC0	
<b>Database Configuration for Node 2</b>		Database heap (4KB)	(DBHEAP)
Database Configuration for Database TPCD		= 10000	
Database configuration release level	=	Size of database shared memory (4KB)	
0x0a00		(DATABASE_MEMORY) = AUTOMATIC	
Database release level	=	Catalog cache size (4KB)	
0x0a00		(CATALOGCACHE_SZ) = (MAXAPPLS*4)	
Database territory	= US	Log buffer size (4KB)	(LOGBUFSZ)
Database code page	= 819	= 2048	
Database code set	=	Utilities heap size (4KB)	
ISO8859-1		(UTIL_HEAP_SZ) = 5000	
Database country/region code	= 1	Buffer pool size (pages)	(BUFFPAGE)
		= 1000	
Dynamic SQL Query management		Extended storage segments size (4KB)	
(DYN_QUERY_MGMT) = DISABLE		(ESTORE_SEG_SZ) = 16000	

Number of extended storage segments (NUM_ESTORE_SEGS) = 0	Max DB files open per application (MAXFILOP) = 1024
Max storage for lock list (4KB) (LOCKLIST) = 40000	Log file size (4KB) (LOGFILSIZ) = 50000
Max size of appl. group mem set (4KB) (APPGROUP_MEM_SZ) = 2000	Number of primary log files (LOGPRIMARY) = 4
Percent of mem for appl. group heap (GROUPHEAP_RATIO) = 70	Number of secondary log files (LOGSECOND) = 1
Max appl. control heap size (4KB) (APP_CTL_HEAP_SZ) = 512	Changed path to log files (NEWLOGPATH) =
Sort heap thres for shared sorts (4KB) (SHEAPTHRES_SHR) = 250	Path to log files =
Sort list heap (4KB) (SORTHEAP) = 20000	/dev/raw/raw61
SQL statement heap (4KB) (STMTHEAP) = 10000	Overflow log path (OVERFLOWLOGPATH) =
Default application heap (4KB) (APPLHEAPSZ) = 1024	Mirror log path (MIRRORLOGPATH) =
Package cache size (4KB) (PCKCACHESZ) = (MAXAPPLS*8)	First active log file =
Statistics heap size (4KB) (STAT_HEAP_SZ) = 4384	Block log on disk full (BLK_LOG_DSK_FUL) = NO
Interval for checking deadlock (ms) (DLCHKTIME) = 10000	Percent of max active log space by transaction(MAX_LOG) = 0
Percent. of lock lists per application (MAXLOCKS) = 20	Num. of active log files for 1 active UOW(NUM_LOG_SPAN) = 0
Lock timeout (sec) (LOCKTIMEOUT) = -1	Group commit count (MINCOMMIT) = 2
Changed pages threshold (CHNGPGS_THRESH) = 60	Percent log file reclaimed before soft ckcpt (SOFTMAX) = 360
Number of asynchronous page cleaners (NUM_IOCLEANERS) = 4	Log retain for recovery enabled (LOGRETAIN) = OFF
Number of I/O servers (NUM_IOSERVERS) = 4	User exit for logging enabled (USEREXIT) = OFF
Index sort flag (INDEXSORT) = YES	Auto restart enabled (AUTORESTART) = ON
Sequential detect flag (SEQDETECT) = YES	Index re-creation time (INDEXREC) = SYSTEM (RESTART)
Default prefetch size (pages) (DFT_PREFETCH_SZ) = 32	Default number of loadrec sessions (DFT_LOADREC_SES) = 1
Track modified pages (TRACKMOD) = OFF	Number of database backups to retain (NUM_DB_BACKUPS) = 12
Default number of containers = 1	Recovery history retention (days) (REC_HIS_RETENTN) = 366
Default tablespace extentsize (pages) (DFT_EXTENT_SZ) = 32	TSM management class (TSM_MGMTCLASS) =
Max number of active applications (MAXAPPLS) = AUTOMATIC	TSM node name (TSM_NODENAME) =
Average number of active applications (AVG_APPLS) = 1	TSM owner (TSM_OWNER) =
	TSM password (TSM_PASSWORD) =

**Database Configuration for Node 3**

Database Configuration for Database TPCD		Database heap (4KB) (DBHEAP)
Database configuration release level	=	= 10000
0x0a00		Size of database shared memory (4KB)
Database release level	=	(DATABASE_MEMORY) = AUTOMATIC
0x0a00		Catalog cache size (4KB)
Database territory	= US	(CATALOGCACHE_SZ) = (MAXAPPLS*4)
Database code page	= 819	Log buffer size (4KB) (LOGBUFSZ)
Database code set	=	= 2048
ISO8859-1		Utilities heap size (4KB)
Database country/region code	= 1	(UTIL_HEAP_SZ) = 5000
Dynamic SQL Query management		Buffer pool size (pages) (BUFFPAGE)
(DYN_QUERY_MGMT) = DISABLE		= 1000
Discovery support for this database		Extended storage segments size (4KB)
(DISCOVER_DB) = ENABLE		(ESTORE_SEG_SZ) = 16000
Default query optimization class		Number of extended storage segments
(DFT_QUERYOPT) = 7		(NUM_ESTORE_SEGS) = 0
Degree of parallelism		Max storage for lock list (4KB)
(DFT_DEGREE) = 1		(LOCKLIST) = 40000
Continue upon arithmetic exceptions		Max size of appl. group mem set (4KB)
(DFT_SQLMATHWARN) = NO		(APPGROUP_MEM_SZ) = 2000
Default refresh age		Percent of mem for appl. group heap
(DFT_REFRESH_AGE) = 0		(GROUPHEAP_RATIO) = 70
Number of frequent values retained		Max appl. control heap size (4KB)
(NUM_FREQVALUES) = 0		(APP_CTL_HEAP_SZ) = 512
Number of quantiles retained		Sort heap thres for shared sorts (4KB)
(NUM_QUANTILES) = 300		(SHEAPTHRES_SHR) = 250
Backup pending	= NO	Sort list heap (4KB) (SORTHEAP) =
Database is consistent	= YES	20000
Rollforward pending	= NO	SQL statement heap (4KB)
Restore pending	= NO	(STMTHEAP) = 10000
Multi-page file allocation enabled	=	Default application heap (4KB)
NO		(APPLHEAPSZ) = 1024
Log retain for recovery status	= NO	Package cache size (4KB)
User exit for logging status	= NO	(PCKCACHESZ) = (MAXAPPLS*8)
Data Links Token Expiry Interval (sec)		Statistics heap size (4KB)
(DL_EXPINT) = 60		(STAT_HEAP_SZ) = 4384
Data Links Write Token Init Expiry		Interval for checking deadlock (ms)
Intvl(DL_WT_IEXPINT) = 60		(DLCHKTIME) = 10000
Data Links Number of Copies		Percent. of lock lists per application
(DL_NUM_COPIES) = 1		(MAXLOCKS) = 20
Data Links Time after Drop (days)		Lock timeout (sec)
(DL_TIME_DROP) = 1		(LOCKTIMEOUT) = -1
Data Links Token in Uppercase		Changed pages threshold
(DL_UPPER) = NO		(CHNGPGS_THRESH) = 60
Data Links Token Algorithm		Number of asynchronous page cleaners
(DL_TOKEN) = MAC0		(NUM_IOCLEANERS) = 4
		Number of I/O servers
		(NUM_IOSERVERS) = 4
		Index sort flag (INDEXSORT) =
		YES
		Sequential detect flag (SEQDETECT)
		= YES

Default prefetch size (pages) (DFT_PREFETCH_SZ) = 32		Recovery history retention (days) (REC_HIS_RETENTN) = 366
Track modified pages (TRACKMOD) = OFF		TSM management class (TSM_MGMTCLASS) =
Default number of containers Default tablespace extentsize (pages) (DFT_EXTENT_SZ) = 32	= 1	TSM node name (TSM_NODENAME) =
Max number of active applications (MAXAPPLS) = AUTOMATIC		TSM owner (TSM_OWNER)
Average number of active applications (AVG_APPLS) = 1		=
Max DB files open per application (MAXFILOP) = 1024		TSM password (TSM_PASSWORD) =
		<b>Database Configuration for Node 4</b>
		Database Configuration for Database TPCD
Log file size (4KB) (LOGFILSIZ) = 50000		Database configuration release level = 0x0a00
Number of primary log files (LOGPRIMARY) = 4		Database release level = 0x0a00
Number of secondary log files (LOGSECOND) = 1		Database territory = US
Changed path to log files (NEWLOGPATH) =		Database code page = 819
Path to log files = /dev/raw/raw62	=	Database code set = ISO8859-1
Overflow log path (OVERFLOWLOGPATH) =		Database country/region code = 1
Mirror log path (MIRRORLOGPATH) =		Dynamic SQL Query management (DYN_QUERY_MGMT) = DISABLE
First active log file =	=	Discovery support for this database (DISCOVER_DB) = ENABLE
Block log on disk full (BLK_LOG_DSK_FUL) = NO		Default query optimization class (DFT_QUERYOPT) = 7
Percent of max active log space by transaction (MAX_LOG) = 0		Degree of parallelism (DFT_DEGREE) = 1
Num. of active log files for 1 active UOW (NUM_LOG_SPAN) = 0		Continue upon arithmetic exceptions (DFT_SQLMATHWARN) = NO
Group commit count (MINCOMMIT) = 2		Default refresh age (DFT_REFRESH_AGE) = 0
Percent log file reclaimed before soft ckcpt (SOFTMAX) = 360		Number of frequent values retained (NUM_FREQVALUES) = 0
Log retain for recovery enabled (LOGRETAIN) = OFF		Number of quantiles retained (NUM_QUANTILES) = 300
User exit for logging enabled (USEREXIT) = OFF		Backup pending = NO
Auto restart enabled (AUTORESTART) = ON		Database is consistent = YES
Index re-creation time (INDEXREC) = SYSTEM (RESTART)		Rollforward pending = NO
Default number of loadrec sessions (DFT_LOADREC_SES) = 1		Restore pending = NO
Number of database backups to retain (NUM_DB_BACKUPS) = 12		Multi-page file allocation enabled = NO



Log retain for recovery status	= NO	Percent. of lock lists per application	
User exit for logging status	= NO	(MAXLOCKS) = 20	
Data Links Token Expiry Interval (sec)		Lock timeout (sec)	
(DL_EXPINT) = 60		(LOCKTIMEOUT) = -1	
Data Links Write Token Init Expiry		Changed pages threshold	
Intvl(DL_WT_IEXPINT) = 60		(CHNGPGS_THRESH) = 60	
Data Links Number of Copies		Number of asynchronous page cleaners	
(DL_NUM_COPIES) = 1		(NUM_IOCLEANERS) = 4	
Data Links Time after Drop (days)		Number of I/O servers	
(DL_TIME_DROP) = 1		(NUM_IOSERVERS) = 4	
Data Links Token in Uppercase		Index sort flag	(INDEXSORT) =
(DL_UPPER) = NO		YES	
Data Links Token Algorithm		Sequential detect flag	(SEQDETECT)
(DL_TOKEN) = MAC0		= YES	
Database heap (4KB)	(DBHEAP)	Default prefetch size (pages)	
= 10000		(DFT_PREFETCH_SZ) = 32	
Size of database shared memory (4KB)		Track modified pages	
(DATABASE_MEMORY) = AUTOMATIC		(TRACKMOD) = OFF	
Catalog cache size (4KB)		Default number of containers	= 1
(CATALOGCACHE_SZ) = (MAXAPPLS*4)		Default tablespace extentsize (pages)	
Log buffer size (4KB)	(LOGBUFSZ)	(DFT_EXTENT_SZ) = 32	
= 2048		Max number of active applications	
Utilities heap size (4KB)		(MAXAPPLS) = AUTOMATIC	
(UTIL_HEAP_SZ) = 5000		Average number of active applications	
Buffer pool size (pages)	(BUFFPAGE)	(AVG_APPLS) = 1	
= 1000		Max DB files open per application	
Extended storage segments size (4KB)		(MAXFILOP) = 1024	
(ESTORE_SEG_SZ) = 16000		Log file size (4KB)	(LOGFILSIZ) =
Number of extended storage segments		50000	
(NUM_ESTORE_SEGS) = 0		Number of primary log files	
Max storage for lock list (4KB)		(LOGPRIMARY) = 4	
(LOCKLIST) = 40000		Number of secondary log files	
Max size of appl. group mem set (4KB)		(LOGSECOND) = 1	
(APPGROUP_MEM_SZ) = 2000		Changed path to log files	
Percent of mem for appl. group heap		(NEWLOGPATH) =	
(GROUPHEAP_RATIO) = 70		Path to log files	=
Max appl. control heap size (4KB)		/dev/raw/raw61	
(APP_CTL_HEAP_SZ) = 512		Overflow log path	
Sort heap thres for shared sorts (4KB)		(OVERFLOWLOGPATH) =	
(SHEAPTHRES_SHR) = 250		Mirror log path	
Sort list heap (4KB)	(SORTHEAP) =	(MIRRORLOGPATH) =	
20000		First active log file	=
SQL statement heap (4KB)		Block log on disk full	
(STMTHEAP) = 10000		(BLK_LOG_DSK_FUL) = NO	
Default application heap (4KB)		Percent of max active log space by	
(APPLHEAPSZ) = 1024		transaction(MAX_LOG) = 0	
Package cache size (4KB)		Num. of active log files for 1 active	
(PCKCACHESZ) = (MAXAPPLS*8)		UOW(NUM_LOG_SPAN) = 0	
Statistics heap size (4KB)		Group commit count	
(STAT_HEAP_SZ) = 4384		(MINCOMMIT) = 2	
Interval for checking deadlock (ms)			
(DLCHKTIME) = 10000			

Percent log file reclaimed before soft ckcpt  
(SOFTMAX) = 360  
Log retain for recovery enabled  
(LOGRETAIN) = OFF  
User exit for logging enabled  
(USEREXIT) = OFF

Auto restart enabled  
(AUTORESTART) = ON  
Index re-creation time (INDEXREC)  
= SYSTEM (RESTART)  
Default number of loadrec sessions  
(DFT\_LOADREC\_SES) = 1  
Number of database backups to retain  
(NUM\_DB\_BACKUPS) = 12  
Recovery history retention (days)  
(REC\_HIS\_RETENTN) = 366

TSM management class  
(TSM\_MGMTCLASS) =  
TSM node name  
(TSM\_NODENAME) =  
TSM owner (TSM\_OWNER)  
=  
TSM password  
(TSM\_PASSWORD) =

### Database Configuration for Node 5

#### Database Configuration for Database TPCD

Database configuration release level =  
0x0a00  
Database release level =  
0x0a00

Database territory = US  
Database code page = 819  
Database code set =  
ISO8859-1  
Database country/region code = 1

Dynamic SQL Query management  
(DYN\_QUERY\_MGMT) = DISABLE

Discovery support for this database  
(DISCOVER\_DB) = ENABLE  
Default query optimization class  
(DFT\_QUERYOPT) = 7  
Degree of parallelism  
(DFT\_DEGREE) = 1  
Continue upon arithmetic exceptions  
(DFT\_SQLMATHWARN) = NO  
Default refresh age  
(DFT\_REFRESH\_AGE) = 0

Number of frequent values retained  
(NUM\_FREQVALUES) = 0  
Number of quantiles retained  
(NUM\_QUANTILES) = 300

Backup pending = NO

Database is consistent = YES  
Rollforward pending = NO  
Restore pending = NO

Multi-page file allocation enabled =  
NO

Log retain for recovery status = NO  
User exit for logging status = NO

Data Links Token Expiry Interval (sec)  
(DL\_EXPINT) = 60  
Data Links Write Token Init Expiry  
Intvl(DL\_WT\_IEXPINT) = 60  
Data Links Number of Copies  
(DL\_NUM\_COPIES) = 1  
Data Links Time after Drop (days)  
(DL\_TIME\_DROP) = 1  
Data Links Token in Uppercase  
(DL\_UPPER) = NO  
Data Links Token Algorithm  
(DL\_TOKEN) = MAC0

Database heap (4KB) (DBHEAP)  
= 10000  
Size of database shared memory (4KB)  
(DATABASE\_MEMORY) = AUTOMATIC  
Catalog cache size (4KB)  
(CATALOGCACHE\_SZ) = (MAXAPPLS\*4)  
Log buffer size (4KB) (LOGBUFSZ)  
= 2048  
Utilities heap size (4KB)  
(UTIL\_HEAP\_SZ) = 5000  
Buffer pool size (pages) (BUFFPAGE)  
= 1000  
Extended storage segments size (4KB)  
(ESTORE\_SEG\_SZ) = 16000  
Number of extended storage segments  
(NUM\_ESTORE\_SEGS) = 0  
Max storage for lock list (4KB)  
(LOCKLIST) = 40000

Max size of appl. group mem set (4KB)  
(APPGROUP\_MEM\_SZ) = 2000  
Percent of mem for appl. group heap  
(GROUPHEAP\_RATIO) = 70  
Max appl. control heap size (4KB)  
(APP\_CTL\_HEAP\_SZ) = 512

Sort heap thres for shared sorts (4KB) (SHEAPTHRES_SHR) = 250		Overflow log path (OVERFLOWLOGPATH) =	
Sort list heap (4KB) 20000	(SORTHEAP) =	Mirror log path (MIRRORLOGPATH) =	
SQL statement heap (4KB) (STMTHEAP) = 10000		First active log file	=
Default application heap (4KB) (APPLHEAPSZ) = 1024		Block log on disk full (BLK_LOG_DSK_FUL) = NO	
Package cache size (4KB) (PCKCACHESZ) = (MAXAPPLS*8)		Percent of max active log space by transaction(MAX_LOG) = 0	
Statistics heap size (4KB) (STAT_HEAP_SZ) = 4384		Num. of active log files for 1 active UOW(NUM_LOG_SPAN) = 0	
Interval for checking deadlock (ms) (DLCHKTIME) = 10000		Group commit count (MINCOMMIT) = 2	
Percent. of lock lists per application (MAXLOCKS) = 20		Percent log file reclaimed before soft ckcpt (SOFTMAX) = 360	
Lock timeout (sec) (LOCKTIMEOUT) = -1		Log retain for recovery enabled (LOGRETAIN) = OFF	
Changed pages threshold (CHNGPGS_THRESH) = 60		User exit for logging enabled (USEREXIT) = OFF	
Number of asynchronous page cleaners (NUM_IOCLEANERS) = 4		Auto restart enabled (AUTORESTART) = ON	
Number of I/O servers (NUM_IOSERVERS) = 4		Index re-creation time (INDEXREC)	
Index sort flag YES	(INDEXSORT) =	= SYSTEM (RESTART)	
Sequential detect flag = YES	(SEQDETECT)	Default number of loadrec sessions (DFT_LOADREC_SES) = 1	
Default prefetch size (pages) (DFT_PREFETCH_SZ) = 32		Number of database backups to retain (NUM_DB_BACKUPS) = 12	
Track modified pages (TRACKMOD) = OFF		Recovery history retention (days) (REC_HIS_RETENTN) = 366	
Default number of containers = 1		TSM management class (TSM_MGMTCLASS) =	
Default tablespace extentsize (pages) (DFT_EXTENT_SZ) = 32		TSM node name (TSM_NODENAME) =	
Max number of active applications (MAXAPPLS) = AUTOMATIC		TSM owner (TSM_OWNER)	
Average number of active applications (AVG_APPLS) = 1		=	
Max DB files open per application (MAXFILOP) = 1024		TSM password (TSM_PASSWORD) =	
Log file size (4KB) 50000	(LOGFILSIZ) =	<b>Database Configuration for Node 6</b>	
Number of primary log files (LOGPRIMARY) = 4		Database Configuration for Database TPCD	
Number of secondary log files (LOGSECOND) = 1		Database configuration release level	=
Changed path to log files (NEWLOGPATH) =		0x0a00	
Path to log files /dev/raw/raw62	=	Database release level	=
		0x0a00	
		Database territory	= US
		Database code page	= 819
		Database code set	=
		ISO8859-1	

Database country/region code	= 1	Buffer pool size (pages) (BUFFPAGE) = 1000
Dynamic SQL Query management (DYN_QUERY_MGMT) = DISABLE		Extended storage segments size (4KB) (ESTORE_SEG_SZ) = 16000 Number of extended storage segments (NUM_ESTORE_SEGS) = 0 Max storage for lock list (4KB) (LOCKLIST) = 40000
Discovery support for this database (DISCOVER_DB) = ENABLE		Max size of appl. group mem set (4KB) (APPGROUP_MEM_SZ) = 2000
Default query optimization class (DFT_QUERYOPT) = 7		Percent of mem for appl. group heap (GROUPHEAP_RATIO) = 70
Degree of parallelism (DFT_DEGREE) = 1		Max appl. control heap size (4KB) (APP_CTL_HEAP_SZ) = 512
Continue upon arithmetic exceptions (DFT_SQLMATHWARN) = NO		Sort heap thres for shared sorts (4KB) (SHEAPTHRES_SHR) = 250
Default refresh age (DFT_REFRESH_AGE) = 0		Sort list heap (4KB) (SORTHEAP) = 20000
Number of frequent values retained (NUM_FREQVALUES) = 0		SQL statement heap (4KB) (STMTHEAP) = 10000
Number of quantiles retained (NUM_QUANTILES) = 300		Default application heap (4KB) (APPLHEAPSZ) = 1024
Backup pending	= NO	Package cache size (4KB) (PCKCACHESZ) = (MAXAPPLS*8)
Database is consistent	= YES	Statistics heap size (4KB) (STAT_HEAP_SZ) = 4384
Rollforward pending	= NO	Interval for checking deadlock (ms) (DLCHKTIME) = 10000
Restore pending	= NO	Percent. of lock lists per application (MAXLOCKS) = 20
Multi-page file allocation enabled NO	=	Lock timeout (sec) (LOCKTIMEOUT) = -1
Log retain for recovery status	= NO	Changed pages threshold (CHNGPGS_THRESH) = 60
User exit for logging status	= NO	Number of asynchronous page cleaners (NUM_IOCLEANERS) = 4
Data Links Token Expiry Interval (sec) (DL_EXPINT) = 60		Number of I/O servers (NUM_IOSERVERS) = 4
Data Links Write Token Init Expiry Intvl(DL_WT_IEXPINT) = 60		Index sort flag (INDEXSORT) = YES
Data Links Number of Copies (DL_NUM_COPIES) = 1		Sequential detect flag (SEQDETECT) = YES
Data Links Time after Drop (days) (DL_TIME_DROP) = 1		Default prefetch size (pages) (DFT_PREFETCH_SZ) = 32
Data Links Token in Uppercase (DL_UPPER) = NO		Track modified pages (TRACKMOD) = OFF
Data Links Token Algorithm (DL_TOKEN) = MAC0		Default number of containers = 1
Database heap (4KB) (DBHEAP) = 10000		Default tablespace extentsize (pages) (DFT_EXTENT_SZ) = 32
Size of database shared memory (4KB) (DATABASE_MEMORY) = AUTOMATIC		
Catalog cache size (4KB) (CATALOGCACHE_SZ) = (MAXAPPLS*4)		
Log buffer size (4KB) (LOGBUFSZ) = 2048		
Utilities heap size (4KB) (UTIL_HEAP_SZ) = 5000		

Max number of active applications  
 (MAXAPPLS) = AUTOMATIC  
 Average number of active applications  
 (AVG\_APPLS) = 1  
 Max DB files open per application  
 (MAXFILOP) = 1024

Log file size (4KB) (LOGFILSIZ) =  
 50000  
 Number of primary log files  
 (LOGPRIMARY) = 4  
 Number of secondary log files  
 (LOGSECOND) = 1  
 Changed path to log files  
 (NEWLOGPATH) =  
 Path to log files =  
 /dev/raw/raw61  
 Overflow log path  
 (OVERFLOWLOGPATH) =  
 Mirror log path  
 (MIRRORLOGPATH) =  
 First active log file =  
 Block log on disk full  
 (BLK\_LOG\_DSK\_FUL) = NO  
 Percent of max active log space by  
 transaction(MAX\_LOG) = 0  
 Num. of active log files for 1 active  
 UOW(NUM\_LOG\_SPAN) = 0

Group commit count  
 (MINCOMMIT) = 2  
 Percent log file reclaimed before soft chkpt  
 (SOFTMAX) = 360  
 Log retain for recovery enabled  
 (LOGRETAIN) = OFF  
 User exit for logging enabled  
 (USEREXIT) = OFF

Auto restart enabled  
 (AUTORESTART) = ON  
 Index re-creation time (INDEXREC)  
 = SYSTEM (RESTART)  
 Default number of loadrec sessions  
 (DFT\_LOADREC\_SES) = 1  
 Number of database backups to retain  
 (NUM\_DB\_BACKUPS) = 12  
 Recovery history retention (days)  
 (REC\_HIS\_RETENTN) = 366

TSM management class  
 (TSM\_MGMTCLASS) =  
 TSM node name  
 (TSM\_NODENAME) =  
 TSM owner (TSM\_OWNER)  
 =

TSM password  
 (TSM\_PASSWORD) =

### Database Configuration for Node 7

#### Database Configuration for Database TPCD

Database configuration release level =  
 0x0a00  
 Database release level =  
 0x0a00

Database territory = US  
 Database code page = 819  
 Database code set =  
 ISO8859-1  
 Database country/region code = 1

Dynamic SQL Query management  
 (DYN\_QUERY\_MGMT) = DISABLE

Discovery support for this database  
 (DISCOVER\_DB) = ENABLE  
 Default query optimization class  
 (DFT\_QUERYOPT) = 7  
 Degree of parallelism  
 (DFT\_DEGREE) = 1  
 Continue upon arithmetic exceptions  
 (DFT\_SQLMATHWARN) = NO  
 Default refresh age  
 (DFT\_REFRESH\_AGE) = 0  
 Number of frequent values retained  
 (NUM\_FREQVALUES) = 0  
 Number of quantiles retained  
 (NUM\_QUANTILES) = 300

Backup pending = NO

Database is consistent = YES  
 Rollforward pending = NO  
 Restore pending = NO

Multi-page file allocation enabled =  
 NO

Log retain for recovery status = NO  
 User exit for logging status = NO

Data Links Token Expiry Interval (sec)  
 (DL\_EXPINT) = 60  
 Data Links Write Token Init Expiry  
 Intvl(DL\_WT\_IEXPINT) = 60  
 Data Links Number of Copies  
 (DL\_NUM\_COPIES) = 1

Data Links Time after Drop (days) (DL_TIME_DROP) = 1	Number of I/O servers (NUM_IOSERVERS) = 4
Data Links Token in Uppercase (DL_UPPER) = NO	Index sort flag (INDEXSORT) = YES
Data Links Token Algorithm (DL_TOKEN) = MAC0	Sequential detect flag (SEQDETECT) = YES
Database heap (4KB) (DBHEAP) = 10000	Default prefetch size (pages) (DFT_PREFETCH_SZ) = 32
Size of database shared memory (4KB) (DATABASE_MEMORY) = AUTOMATIC	Track modified pages (TRACKMOD) = OFF
Catalog cache size (4KB) (CATALOGCACHE_SZ) = (MAXAPPLS*4)	Default number of containers = 1
Log buffer size (4KB) (LOGBUFSZ) = 2048	Default tablespace extentsize (pages) (DFT_EXTENT_SZ) = 32
Utilities heap size (4KB) (UTIL_HEAP_SZ) = 5000	Max number of active applications (MAXAPPLS) = AUTOMATIC
Buffer pool size (pages) (BUFFPAGE) = 1000	Average number of active applications (AVG_APPLS) = 1
Extended storage segments size (4KB) (ESTORE_SEG_SZ) = 16000	Max DB files open per application (MAXFILOP) = 1024
Number of extended storage segments (NUM_ESTORE_SEGS) = 0	Log file size (4KB) (LOGFILSIZ) = 50000
Max storage for lock list (4KB) (LOCKLIST) = 40000	Number of primary log files (LOGPRIMARY) = 4
Max size of appl. group mem set (4KB) (APPGROUP_MEM_SZ) = 2000	Number of secondary log files (LOGSECOND) = 1
Percent of mem for appl. group heap (GROUPHEAP_RATIO) = 70	Changed path to log files (NEWLOGPATH) =
Max appl. control heap size (4KB) (APP_CTL_HEAP_SZ) = 512	Path to log files = /dev/raw/raw62
Sort heap thres for shared sorts (4KB) (SHEAPTHRES_SHR) = 250	Overflow log path (OVERFLOWLOGPATH) =
Sort list heap (4KB) (SORTHEAP) = 20000	Mirror log path (MIRRORLOGPATH) =
SQL statement heap (4KB) (STMTHEAP) = 10000	First active log file =
Default application heap (4KB) (APPLHEAPSZ) = 1024	Block log on disk full (BLK_LOG_DSK_FUL) = NO
Package cache size (4KB) (PCKCACHESZ) = (MAXAPPLS*8)	Percent of max active log space by transaction(MAX_LOG) = 0
Statistics heap size (4KB) (STAT_HEAP_SZ) = 4384	Num. of active log files for 1 active UOW(NUM_LOG_SPAN) = 0
Interval for checking deadlock (ms) (DLCHKTIME) = 10000	Group commit count (MINCOMMIT) = 2
Percent. of lock lists per application (MAXLOCKS) = 20	Percent log file reclaimed before soft ckcpt (SOFTMAX) = 360
Lock timeout (sec) (LOCKTIMEOUT) = -1	Log retain for recovery enabled (LOGRETAIN) = OFF
Changed pages threshold (CHNGPGS_THRESH) = 60	User exit for logging enabled (USEREXIT) = OFF
Number of asynchronous page cleaners (NUM_IOCLEANERS) = 4	Auto restart enabled (AUTORESTART) = ON

Index re-creation time = SYSTEM (RESTART)	(INDEXREC)	Rollforward pending	= NO
Default number of loadrec sessions (DFT_LOADREC_SES) = 1		Restore pending	= NO
Number of database backups to retain (NUM_DB_BACKUPS) = 12		Multi-page file allocation enabled	=
Recovery history retention (days) (REC_HIS_RETENTN) = 366		NO	
TSM management class (TSM_MGMTCLASS) =		Log retain for recovery status	= NO
TSM node name (TSM_NODENAME) =		User exit for logging status	= NO
TSM owner (TSM_OWNER)		Data Links Token Expiry Interval (sec) (DL_EXPINT) = 60	
=		Data Links Write Token Init Expiry Intvl(DL_WT_IEXPINT) = 60	
TSM password (TSM_PASSWORD) =		Data Links Number of Copies (DL_NUM_COPIES) = 1	
		Data Links Time after Drop (days) (DL_TIME_DROP) = 1	
		Data Links Token in Uppercase (DL_UPPER) = NO	
		Data Links Token Algorithm (DL_TOKEN) = MAC0	

### Database Configuration for Node 8

Database Configuration for Database TPCD			
Database configuration release level	=	Database heap (4KB)	(DBHEAP)
0x0a00		= 10000	
Database release level	=	Size of database shared memory (4KB) (DATABASE_MEMORY) = AUTOMATIC	
0x0a00		Catalog cache size (4KB) (CATALOGCACHE_SZ) = (MAXAPPLS*4)	
Database territory	= US	Log buffer size (4KB)	(LOGBUFSZ)
Database code page	= 819	= 2048	
Database code set	=	Utilities heap size (4KB) (UTIL_HEAP_SZ) = 5000	
ISO8859-1		Buffer pool size (pages)	(BUFFPAGE)
Database country/region code	= 1	= 1000	
Dynamic SQL Query management (DYN_QUERY_MGMT) = DISABLE		Extended storage segments size (4KB) (ESTORE_SEG_SZ) = 16000	
Discovery support for this database (DISCOVER_DB) = ENABLE		Number of extended storage segments (NUM_ESTORE_SEGS) = 0	
Default query optimization class (DFT_QUERYOPT) = 7		Max storage for lock list (4KB) (LOCKLIST) = 40000	
Degree of parallelism (DFT_DEGREE) = 1		Max size of appl. group mem set (4KB) (APPGROUP_MEM_SZ) = 2000	
Continue upon arithmetic exceptions (DFT_SQLMATHWARN) = NO		Percent of mem for appl. group heap (GROUPHEAP_RATIO) = 70	
Default refresh age (DFT_REFRESH_AGE) = 0		Max appl. control heap size (4KB) (APP_CTL_HEAP_SZ) = 512	
Number of frequent values retained (NUM_FREQVALUES) = 0		Sort heap thres for shared sorts (4KB) (SHEAPTHRES_SHR) = 250	
Number of quantiles retained (NUM_QUANTILES) = 300		Sort list heap (4KB)	(SORTHEAP) =
Backup pending	= NO	20000	
Database is consistent	= YES	SQL statement heap (4KB) (STMTHEAP) = 10000	
		Default application heap (4KB) (APPLHEAPSZ) = 1024	

Package cache size (4KB)  
 (PCKCACHESZ) = (MAXAPPLS\*8)  
 Statistics heap size (4KB)  
 (STAT\_HEAP\_SZ) = 4384  
 Interval for checking deadlock (ms)  
 (DLCHKTIME) = 10000  
 Percent. of lock lists per application  
 (MAXLOCKS) = 20  
 Lock timeout (sec)  
 (LOCKTIMEOUT) = -1  
  
 Changed pages threshold  
 (CHNGPGS\_THRESH) = 60  
 Number of asynchronous page cleaners  
 (NUM\_IOCLEANERS) = 4  
 Number of I/O servers  
 (NUM\_IOSERVERS) = 4  
 Index sort flag (INDEXSORT) =  
 YES  
 Sequential detect flag (SEQDETECT)  
 = YES  
 Default prefetch size (pages)  
 (DFT\_PREFETCH\_SZ) = 32  
  
 Track modified pages  
 (TRACKMOD) = OFF  
  
 Default number of containers = 1  
 Default tablespace extentsize (pages)  
 (DFT\_EXTENT\_SZ) = 32  
  
 Max number of active applications  
 (MAXAPPLS) = AUTOMATIC  
 Average number of active applications  
 (AVG\_APPLS) = 1  
 Max DB files open per application  
 (MAXFILOP) = 1024  
  
 Log file size (4KB) (LOGFILSIZ) =  
 50000  
 Number of primary log files  
 (LOGPRIMARY) = 4  
 Number of secondary log files  
 (LOGSECOND) = 1  
 Changed path to log files  
 (NEWLOGPATH) =  
 Path to log files =  
 /dev/raw/raw61  
 Overflow log path  
 (OVERFLOWLOGPATH) =  
 Mirror log path  
 (MIRRORLOGPATH) =  
 First active log file =  
 Block log on disk full  
 (BLK\_LOG\_DSK\_FUL) = NO

Percent of max active log space by  
 transaction(MAX\_LOG) = 0  
 Num. of active log files for 1 active  
 UOW(NUM\_LOG\_SPAN) = 0  
  
 Group commit count  
 (MINCOMMIT) = 2  
 Percent log file reclaimed before soft ckcpt  
 (SOFTMAX) = 360  
 Log retain for recovery enabled  
 (LOGRETAIN) = OFF  
 User exit for logging enabled  
 (USEREXIT) = OFF  
  
 Auto restart enabled  
 (AUORESTART) = ON  
 Index re-creation time (INDEXREC)  
 = SYSTEM (RESTART)  
 Default number of loadrec sessions  
 (DFT\_LOADREC\_SES) = 1  
 Number of database backups to retain  
 (NUM\_DB\_BACKUPS) = 12  
 Recovery history retention (days)  
 (REC\_HIS\_RETENTN) = 366  
  
 TSM management class  
 (TSM\_MGMTCLASS) =  
 TSM node name  
 (TSM\_NODENAME) =  
 TSM owner (TSM\_OWNER)  
 =  
 TSM password  
 (TSM\_PASSWORD) =

### ***Database Configuration for Node 9***

#### Database Configuration for Database TPCD

Database configuration release level =  
 0x0a00  
 Database release level =  
 0x0a00  
  
 Database territory = US  
 Database code page = 819  
 Database code set =  
 ISO8859-1  
 Database country/region code = 1  
  
 Dynamic SQL Query management  
 (DYN\_QUERY\_MGMT) = DISABLE  
  
 Discovery support for this database  
 (DISCOVER\_DB) = ENABLE



Default query optimization class (DFT_QUERYOPT) = 7		Max size of appl. group mem set (4KB) (APPGROUP_MEM_SZ) = 2000
Degree of parallelism (DFT_DEGREE) = 1		Percent of mem for appl. group heap (GROUPHEAP_RATIO) = 70
Continue upon arithmetic exceptions (DFT_SQLMATHWARN) = NO		Max appl. control heap size (4KB) (APP_CTL_HEAP_SZ) = 512
Default refresh age (DFT_REFRESH_AGE) = 0		
Number of frequent values retained (NUM_FREQVALUES) = 0		Sort heap thres for shared sorts (4KB) (SHEAPTHRES_SHR) = 250
Number of quantiles retained (NUM_QUANTILES) = 300		Sort list heap (4KB) (SORTHEAP) = 20000
Backup pending = NO		SQL statement heap (4KB) (STMTHEAP) = 10000
Database is consistent = YES		Default application heap (4KB) (APPLHEAPSZ) = 1024
Rollforward pending = NO		Package cache size (4KB)
Restore pending = NO		(PCKCACHESZ) = (MAXAPPLS*8)
Multi-page file allocation enabled =		Statistics heap size (4KB) (STAT_HEAP_SZ) = 4384
NO		Interval for checking deadlock (ms) (DLCHKTIME) = 10000
Log retain for recovery status = NO		Percent. of lock lists per application (MAXLOCKS) = 20
User exit for logging status = NO		Lock timeout (sec) (LOCKTIMEOUT) = -1
Data Links Token Expiry Interval (sec) (DL_EXPINT) = 60		
Data Links Write Token Init Expiry Intvl(DL_WT_IEXPINT) = 60		Changed pages threshold (CHNGPGS_THRESH) = 60
Data Links Number of Copies (DL_NUM_COPIES) = 1		Number of asynchronous page cleaners (NUM_IOCLEANERS) = 4
Data Links Time after Drop (days) (DL_TIME_DROP) = 1		Number of I/O servers (NUM_IOSERVERS) = 4
Data Links Token in Uppercase (DL_UPPER) = NO		Index sort flag (INDEXSORT) = YES
Data Links Token Algorithm (DL_TOKEN) = MAC0		Sequential detect flag (SEQDETECT) = YES
Database heap (4KB) (DBHEAP) = 10000		Default prefetch size (pages) (DFT_PREFETCH_SZ) = 32
Size of database shared memory (4KB) (DATABASE_MEMORY) = AUTOMATIC		Track modified pages (TRACKMOD) = OFF
Catalog cache size (4KB) (CATALOGCACHE_SZ) = (MAXAPPLS*4)		Default number of containers = 1
Log buffer size (4KB) (LOGBUFSZ) = 2048		Default tablespace extentsize (pages) (DFT_EXTENT_SZ) = 32
Utilities heap size (4KB) (UTIL_HEAP_SZ) = 5000		
Buffer pool size (pages) (BUFFPAGE) = 1000		Max number of active applications (MAXAPPLS) = AUTOMATIC
Extended storage segments size (4KB) (ESTORE_SEG_SZ) = 16000		Average number of active applications (AVG_APPLS) = 1
Number of extended storage segments (NUM_ESTORE_SEGS) = 0		Max DB files open per application (MAXFILOP) = 1024
Max storage for lock list (4KB) (LOCKLIST) = 40000		Log file size (4KB) (LOGFILSIZ) = 50000

Number of primary log files (LOGPRIMARY) = 4		Database configuration release level	=	0x0a00
Number of secondary log files (LOGSECOND) = 1		Database release level	=	0x0a00
Changed path to log files (NEWLOGPATH) =		Database territory	=	US
Path to log files	=	Database code page	=	819
/dev/raw/raw62		Database code set	=	ISO8859-1
Overflow log path (OVERFLOWLOGPATH) =		Database country/region code	=	1
Mirror log path (MIRRORLOGPATH) =		Dynamic SQL Query management (DYN_QUERY_MGMT) =		DISABLE
First active log file	=	Discovery support for this database (DISCOVER_DB) =		ENABLE
Block log on disk full (BLK_LOG_DSK_FUL) =	NO	Default query optimization class (DFT_QUERYOPT) =		7
Percent of max active log space by transaction(MAX_LOG) =	0	Degree of parallelism (DFT_DEGREE) =		1
Num. of active log files for 1 active UOW(NUM_LOG_SPAN) =	0	Continue upon arithmetic exceptions (DFT_SQLMATHWARN) =		NO
Group commit count (MINCOMMIT) =	2	Default refresh age (DFT_REFRESH_AGE) =		0
Percent log file reclaimed before soft ckcpt (SOFTMAX) =	360	Number of frequent values retained (NUM_FREQVALUES) =		0
Log retain for recovery enabled (LOGRETAIN) =	OFF	Number of quantiles retained (NUM_QUANTILES) =		300
User exit for logging enabled (USEREXIT) =	OFF	Backup pending	=	NO
Auto restart enabled (AUTORESTART) =	ON	Database is consistent	=	YES
Index re-creation time	(INDEXREC)	Rollforward pending	=	NO
= SYSTEM (RESTART)		Restore pending	=	NO
Default number of loadrec sessions (DFT_LOADREC_SES) =	1	Multi-page file allocation enabled	=	NO
Number of database backups to retain (NUM_DB_BACKUPS) =	12	Log retain for recovery status	=	NO
Recovery history retention (days) (REC_HIS_RETENTN) =	366	User exit for logging status	=	NO
TSM management class (TSM_MGMTCLASS) =		Data Links Token Expiry Interval (sec) (DL_EXPINT) =		60
TSM node name (TSM_NODENAME) =		Data Links Write Token Init Expiry Intvl(DL_WT_IEXPINT) =		60
TSM owner	(TSM_OWNER)	Data Links Number of Copies (DL_NUM_COPIES) =		1
=		Data Links Time after Drop (days) (DL_TIME_DROP) =		1
TSM password (TSM_PASSWORD) =		Data Links Token in Uppercase (DL_UPPER) =		NO
		Data Links Token Algorithm (DL_TOKEN) =		MAC0
		Database heap (4KB)	(DBHEAP)	= 10000

### Database Configuration for Node 10

Database Configuration for Database TPCD

Size of database shared memory (4KB) (DATABASE_MEMORY) = AUTOMATIC	Track modified pages (TRACKMOD) = OFF
Catalog cache size (4KB) (CATALOGCACHE_SZ) = (MAXAPPLS*4)	Default number of containers = 1
Log buffer size (4KB) (LOGBUFSZ) = 2048	Default tablespace extentsize (pages) (DFT_EXTENT_SZ) = 32
Utilities heap size (4KB) (UTIL_HEAP_SZ) = 5000	Max number of active applications (MAXAPPLS) = AUTOMATIC
Buffer pool size (pages) (BUFFPAGE) = 1000	Average number of active applications (AVG_APPLS) = 1
Extended storage segments size (4KB) (ESTORE_SEG_SZ) = 16000	Max DB files open per application (MAXFILOP) = 1024
Number of extended storage segments (NUM_ESTORE_SEGS) = 0	Log file size (4KB) (LOGFILSIZ) = 50000
Max storage for lock list (4KB) (LOCKLIST) = 40000	Number of primary log files (LOGPRIMARY) = 4
Max size of appl. group mem set (4KB) (APPGROUP_MEM_SZ) = 2000	Number of secondary log files (LOGSECOND) = 1
Percent of mem for appl. group heap (GROUPHEAP_RATIO) = 70	Changed path to log files (NEWLOGPATH) =
Max appl. control heap size (4KB) (APP_CTL_HEAP_SZ) = 512	Path to log files = /dev/raw/raw61
Sort heap thres for shared sorts (4KB) (SHEAPTHRES_SHR) = 250	Overflow log path (OVERFLOWLOGPATH) =
Sort list heap (4KB) (SORTHEAP) = 20000	Mirror log path (MIRRORLOGPATH) =
SQL statement heap (4KB) (STMTHEAP) = 10000	First active log file =
Default application heap (4KB) (APPLHEAPSZ) = 1024	Block log on disk full (BLK_LOG_DSK_FUL) = NO
Package cache size (4KB) (PCKCACHESZ) = (MAXAPPLS*8)	Percent of max active log space by transaction(MAX_LOG) = 0
Statistics heap size (4KB) (STAT_HEAP_SZ) = 4384	Num. of active log files for 1 active UOW(NUM_LOG_SPAN) = 0
Interval for checking deadlock (ms) (DLCHKTIME) = 10000	Group commit count (MINCOMMIT) = 2
Percent. of lock lists per application (MAXLOCKS) = 20	Percent log file reclaimed before soft ckcpt (SOFTMAX) = 360
Lock timeout (sec) (LOCKTIMEOUT) = -1	Log retain for recovery enabled (LOGRETAIN) = OFF
Changed pages threshold (CHNGPGS_THRESH) = 60	User exit for logging enabled (USEREXIT) = OFF
Number of asynchronous page cleaners (NUM_IOCLEANERS) = 4	Auto restart enabled (AUTORESTART) = ON
Number of I/O servers (NUM_IOSERVERS) = 4	Index re-creation time (INDEXREC) = SYSTEM (RESTART)
Index sort flag (INDEXSORT) = YES	Default number of loadrec sessions (DFT_LOADREC_SES) = 1
Sequential detect flag (SEQDETECT) = YES	Number of database backups to retain (NUM_DB_BACKUPS) = 12
Default prefetch size (pages) (DFT_PREFETCH_SZ) = 32	Recovery history retention (days) (REC_HIS_RETENTN) = 366

TSM management class  
(TSM\_MGMTCLASS) =  
TSM node name  
(TSM\_NODENAME) =  
TSM owner (TSM\_OWNER)  
=  
TSM password  
(TSM\_PASSWORD) =

**Database Configuration for Node 11**

Database Configuration for Database TPCD

Database configuration release level = 0x0a00  
Database release level = 0x0a00  
Database territory = US  
Database code page = 819  
Database code set = ISO8859-1  
Database country/region code = 1  
Dynamic SQL Query management  
(DYN\_QUERY\_MGMT) = DISABLE  
Discovery support for this database  
(DISCOVER\_DB) = ENABLE  
Default query optimization class  
(DFT\_QUERYOPT) = 7  
Degree of parallelism  
(DFT\_DEGREE) = 1  
Continue upon arithmetic exceptions  
(DFT\_SQLMATHWARN) = NO  
Default refresh age  
(DFT\_REFRESH\_AGE) = 0  
Number of frequent values retained  
(NUM\_FREQVALUES) = 0  
Number of quantiles retained  
(NUM\_QUANTILES) = 300  
Backup pending = NO  
Database is consistent = YES  
Rollforward pending = NO  
Restore pending = NO  
Multi-page file allocation enabled = NO  
Log retain for recovery status = NO  
User exit for logging status = NO

Data Links Token Expiry Interval (sec)  
(DL\_EXPINT) = 60  
Data Links Write Token Init Expiry  
Intvl(DL\_WT\_IEXPINT) = 60  
Data Links Number of Copies  
(DL\_NUM\_COPIES) = 1  
Data Links Time after Drop (days)  
(DL\_TIME\_DROP) = 1  
Data Links Token in Uppercase  
(DL\_UPPER) = NO  
Data Links Token Algorithm  
(DL\_TOKEN) = MAC0  
Database heap (4KB) (DBHEAP)  
= 10000  
Size of database shared memory (4KB)  
(DATABASE\_MEMORY) = AUTOMATIC  
Catalog cache size (4KB)  
(CATALOGCACHE\_SZ) = (MAXAPPLS\*4)  
Log buffer size (4KB) (LOGBUFSZ)  
= 2048  
Utilities heap size (4KB)  
(UTIL\_HEAP\_SZ) = 5000  
Buffer pool size (pages) (BUFFPAGE)  
= 1000  
Extended storage segments size (4KB)  
(ESTORE\_SEG\_SZ) = 16000  
Number of extended storage segments  
(NUM\_ESTORE\_SEGS) = 0  
Max storage for lock list (4KB)  
(LOCKLIST) = 40000  
Max size of appl. group mem set (4KB)  
(APPGROUP\_MEM\_SZ) = 2000  
Percent of mem for appl. group heap  
(GROUPHEAP\_RATIO) = 70  
Max appl. control heap size (4KB)  
(APP\_CTL\_HEAP\_SZ) = 512  
Sort heap thres for shared sorts (4KB)  
(SHEAPTHRES\_SHR) = 250  
Sort list heap (4KB) (SORTHEAP) =  
20000  
SQL statement heap (4KB)  
(STMTHEAP) = 10000  
Default application heap (4KB)  
(APPLHEAPSZ) = 1024  
Package cache size (4KB)  
(PCKCACHESZ) = (MAXAPPLS\*8)  
Statistics heap size (4KB)  
(STAT\_HEAP\_SZ) = 4384  
Interval for checking deadlock (ms)  
(DLCHKTIME) = 10000  
Percent. of lock lists per application  
(MAXLOCKS) = 20

Lock timeout (sec)  
 (LOCKTIMEOUT) = -1

Changed pages threshold  
 (CHNGPGS\_THRESH) = 60

Number of asynchronous page cleaners  
 (NUM\_IOCLEANERS) = 4

Number of I/O servers  
 (NUM\_IOSERVERS) = 4

Index sort flag (INDEXSORT) = YES

Sequential detect flag (SEQDETECT) = YES

Default prefetch size (pages)  
 (DFT\_PREFETCH\_SZ) = 32

Track modified pages  
 (TRACKMOD) = OFF

Default number of containers = 1

Default tablespace extentsize (pages)  
 (DFT\_EXTENT\_SZ) = 32

Max number of active applications  
 (MAXAPPLS) = AUTOMATIC

Average number of active applications  
 (AVG\_APPLS) = 1

Max DB files open per application  
 (MAXFILOP) = 1024

Log file size (4KB) (LOGFILSIZ) = 50000

Number of primary log files  
 (LOGPRIMARY) = 4

Number of secondary log files  
 (LOGSECOND) = 1

Changed path to log files  
 (NEWLOGPATH) =

Path to log files = /dev/raw/raw62

Overflow log path  
 (OVERFLOWLOGPATH) =

Mirror log path  
 (MIRRORLOGPATH) =

First active log file =

Block log on disk full  
 (BLK\_LOG\_DSK\_FUL) = NO

Percent of max active log space by transaction  
 (MAX\_LOG) = 0

Num. of active log files for 1 active  
 UOW(NUM\_LOG\_SPAN) = 0

Group commit count  
 (MINCOMMIT) = 2

Percent log file reclaimed before soft ckcpt  
 (SOFTMAX) = 360

Log retain for recovery enabled  
 (LOGRETAIN) = OFF

User exit for logging enabled  
 (USEREXIT) = OFF

Auto restart enabled  
 (AUTORESTART) = ON

Index re-creation time (INDEXREC) = SYSTEM (RESTART)

Default number of loadrec sessions  
 (DFT\_LOADREC\_SES) = 1

Number of database backups to retain  
 (NUM\_DB\_BACKUPS) = 12

Recovery history retention (days)  
 (REC\_HIS\_RETENTN) = 366

TSM management class  
 (TSM\_MGMTCLASS) =

TSM node name  
 (TSM\_NODENAME) =

TSM owner (TSM\_OWNER) =

TSM password  
 (TSM\_PASSWORD) =

### Database Configuration for Node 12

#### Database Configuration for Database TPCD

Database configuration release level = 0x0a00

Database release level = 0x0a00

Database territory = US

Database code page = 819

Database code set = ISO8859-1

Database country/region code = 1

Dynamic SQL Query management  
 (DYN\_QUERY\_MGMT) = DISABLE

Discovery support for this database  
 (DISCOVER\_DB) = ENABLE

Default query optimization class  
 (DFT\_QUERYOPT) = 7

Degree of parallelism  
 (DFT\_DEGREE) = 1

Continue upon arithmetic exceptions  
 (DFT\_SQLMATHWARN) = NO

Default refresh age  
 (DFT\_REFRESH\_AGE) = 0

Number of frequent values retained (NUM_FREQVALUES) = 0		Sort heap thres for shared sorts (4KB) (SHEAPTHRES_SHR) = 250
Number of quantiles retained (NUM_QUANTILES) = 300		Sort list heap (4KB) (SORTHEAP) = 20000
Backup pending = NO		SQL statement heap (4KB) (STMTHEAP) = 10000
Database is consistent = YES		Default application heap (4KB) (APPLHEAPSZ) = 1024
Rollforward pending = NO		Package cache size (4KB) (PCKCACHESZ) = (MAXAPPLS*8)
Restore pending = NO		Statistics heap size (4KB) (STAT_HEAP_SZ) = 4384
Multi-page file allocation enabled = NO		Interval for checking deadlock (ms) (DLCHKTIME) = 10000
Log retain for recovery status = NO		Percent. of lock lists per application (MAXLOCKS) = 20
User exit for logging status = NO		Lock timeout (sec) (LOCKTIMEOUT) = -1
Data Links Token Expiry Interval (sec) (DL_EXPINT) = 60		Changed pages threshold (CHNGPGS_THRESH) = 60
Data Links Write Token Init Expiry Intvl(DL_WT_IEXPINT) = 60		Number of asynchronous page cleaners (NUM_IOCLEANERS) = 4
Data Links Number of Copies (DL_NUM_COPIES) = 1		Number of I/O servers (NUM_IOSERVERS) = 4
Data Links Time after Drop (days) (DL_TIME_DROP) = 1		Index sort flag (INDEXSORT) = YES
Data Links Token in Uppercase (DL_UPPER) = NO		Sequential detect flag (SEQDETECT) = YES
Data Links Token Algorithm (DL_TOKEN) = MAC0		Default prefetch size (pages) (DFT_PREFETCH_SZ) = 32
Database heap (4KB) (DBHEAP) = 10000		Track modified pages (TRACKMOD) = OFF
Size of database shared memory (4KB) (DATABASE_MEMORY) = AUTOMATIC		Default number of containers = 1
Catalog cache size (4KB) (CATALOGCACHE_SZ) = (MAXAPPLS*4)		Default tablespace extentsize (pages) (DFT_EXTENT_SZ) = 32
Log buffer size (4KB) (LOGBUFSZ) = 2048		Max number of active applications (MAXAPPLS) = AUTOMATIC
Utilities heap size (4KB) (UTIL_HEAP_SZ) = 5000		Average number of active applications (AVG_APPLS) = 1
Buffer pool size (pages) (BUFFPAGE) = 1000		Max DB files open per application (MAXFILOP) = 1024
Extended storage segments size (4KB) (ESTORE_SEG_SZ) = 16000		Log file size (4KB) (LOGFILSIZ) = 50000
Number of extended storage segments (NUM_ESTORE_SEGS) = 0		Number of primary log files (LOGPRIMARY) = 4
Max storage for lock list (4KB) (LOCKLIST) = 40000		Number of secondary log files (LOGSECOND) = 1
Max size of appl. group mem set (4KB) (APPGROUP_MEM_SZ) = 2000		Changed path to log files (NEWLOGPATH) =
Percent of mem for appl. group heap (GROUPHEAP_RATIO) = 70		Path to log files =
Max appl. control heap size (4KB) (APP_CTL_HEAP_SZ) = 512		/dev/raw/raw61

Overflow log path  
 (OVERFLOWLOGPATH) =  
 Mirror log path  
 (MIRRORLOGPATH) =  
 First active log file =  
 Block log on disk full  
 (BLK\_LOG\_DSK\_FUL) = NO  
 Percent of max active log space by  
 transaction(MAX\_LOG) = 0  
 Num. of active log files for 1 active  
 UOW(NUM\_LOG\_SPAN) = 0  
  
 Group commit count  
 (MINCOMMIT) = 2  
 Percent log file reclaimed before soft ckcpt  
 (SOFTMAX) = 360  
 Log retain for recovery enabled  
 (LOGRETAIN) = OFF  
 User exit for logging enabled  
 (USEREXIT) = OFF  
  
 Auto restart enabled  
 (AUTORESTART) = ON  
 Index re-creation time (INDEXREC)  
 = SYSTEM (RESTART)  
 Default number of loadrec sessions  
 (DFT\_LOADREC\_SES) = 1  
 Number of database backups to retain  
 (NUM\_DB\_BACKUPS) = 12  
 Recovery history retention (days)  
 (REC\_HIS\_RETENTN) = 366  
  
 TSM management class  
 (TSM\_MGMTCLASS) =  
 TSM node name  
 (TSM\_NODENAME) =  
 TSM owner (TSM\_OWNER)  
 =  
 TSM password  
 (TSM\_PASSWORD) =

### Database Configuration for Node 13

#### Database Configuration for Database TPCD

Database configuration release level =  
 0x0a00  
 Database release level =  
 0x0a00  
  
 Database territory = US  
 Database code page = 819  
 Database code set =  
 ISO8859-1  
 Database country/region code = 1

Dynamic SQL Query management  
 (DYN\_QUERY\_MGMT) = DISABLE  
  
 Discovery support for this database  
 (DISCOVER\_DB) = ENABLE  
 Default query optimization class  
 (DFT\_QUERYOPT) = 7  
 Degree of parallelism  
 (DFT\_DEGREE) = 1  
 Continue upon arithmetic exceptions  
 (DFT\_SQLMATHWARN) = NO  
 Default refresh age  
 (DFT\_REFRESH\_AGE) = 0  
 Number of frequent values retained  
 (NUM\_FREQVALUES) = 0  
 Number of quantiles retained  
 (NUM\_QUANTILES) = 300  
  
 Backup pending = NO  
  
 Database is consistent = YES  
 Rollforward pending = NO  
 Restore pending = NO  
  
 Multi-page file allocation enabled =  
 NO  
  
 Log retain for recovery status = NO  
 User exit for logging status = NO  
  
 Data Links Token Expiry Interval (sec)  
 (DL\_EXPINT) = 60  
 Data Links Write Token Init Expiry  
 Intvl(DL\_WT\_IEXPINT) = 60  
 Data Links Number of Copies  
 (DL\_NUM\_COPIES) = 1  
 Data Links Time after Drop (days)  
 (DL\_TIME\_DROP) = 1  
 Data Links Token in Uppercase  
 (DL\_UPPER) = NO  
 Data Links Token Algorithm  
 (DL\_TOKEN) = MAC0  
  
 Database heap (4KB) (DBHEAP)  
 = 10000  
 Size of database shared memory (4KB)  
 (DATABASE\_MEMORY) = AUTOMATIC  
 Catalog cache size (4KB)  
 (CATALOGCACHE\_SZ) = (MAXAPPLS\*4)  
 Log buffer size (4KB) (LOGBUFSZ)  
 = 2048  
 Utilities heap size (4KB)  
 (UTIL\_HEAP\_SZ) = 5000  
 Buffer pool size (pages) (BUFFPAGE)  
 = 1000

Extended storage segments size (4KB) (ESTORE_SEG_SZ) = 16000	Average number of active applications (AVG_APPLS) = 1
Number of extended storage segments (NUM_ESTORE_SEGS) = 0	Max DB files open per application (MAXFILOP) = 1024
Max storage for lock list (4KB) (LOCKLIST) = 40000	Log file size (4KB) (LOGFILSIZ) = 50000
Max size of appl. group mem set (4KB) (APPGROUP_MEM_SZ) = 2000	Number of primary log files (LOGPRIMARY) = 4
Percent of mem for appl. group heap (GROUPHEAP_RATIO) = 70	Number of secondary log files (LOGSECOND) = 1
Max appl. control heap size (4KB) (APP_CTL_HEAP_SZ) = 512	Changed path to log files (NEWLOGPATH) =
Sort heap thres for shared sorts (4KB) (SHEAPTHRES_SHR) = 250	Path to log files = /dev/raw/raw62
Sort list heap (4KB) (SORTHEAP) = 20000	Overflow log path (OVERFLOWLOGPATH) =
SQL statement heap (4KB) (STMTHEAP) = 10000	Mirror log path (MIRRORLOGPATH) =
Default application heap (4KB) (APPLHEAPSZ) = 1024	First active log file =
Package cache size (4KB) (PCKCACHESZ) = (MAXAPPLS*8)	Block log on disk full (BLK_LOG_DSK_FUL) = NO
Statistics heap size (4KB) (STAT_HEAP_SZ) = 4384	Percent of max active log space by transaction(MAX_LOG) = 0
Interval for checking deadlock (ms) (DLCHKTIME) = 10000	Num. of active log files for 1 active UOW(NUM_LOG_SPAN) = 0
Percent. of lock lists per application (MAXLOCKS) = 20	Group commit count (MINCOMMIT) = 2
Lock timeout (sec) (LOCKTIMEOUT) = -1	Percent log file reclaimed before soft ckcpt (SOFTMAX) = 360
Changed pages threshold (CHNGPGS_THRESH) = 60	Log retain for recovery enabled (LOGRETAIN) = OFF
Number of asynchronous page cleaners (NUM_IOCLEANERS) = 4	User exit for logging enabled (USEREXIT) = OFF
Number of I/O servers (NUM_IOSERVERS) = 4	Auto restart enabled (AUTORESTART) = ON
Index sort flag (INDEXSORT) = YES	Index re-creation time (INDEXREC) = SYSTEM (RESTART)
Sequential detect flag (SEQDETECT) = YES	Default number of loadrec sessions (DFT_LOADREC_SES) = 1
Default prefetch size (pages) (DFT_PREFETCH_SZ) = 32	Number of database backups to retain (NUM_DB_BACKUPS) = 12
Track modified pages (TRACKMOD) = OFF	Recovery history retention (days) (REC_HIS_RETENTN) = 366
Default number of containers = 1	TSM management class (TSM_MGMTCLASS) =
Default tablespace extentsize (pages) (DFT_EXTENT_SZ) = 32	TSM node name (TSM_NODENAME) =
Max number of active applications (MAXAPPLS) = AUTOMATIC	TSM owner (TSM_OWNER) = TSM password (TSM_PASSWORD) =



## Database Configuration for Node 14

Database Configuration for Database TPCD		Data Links Token in Uppercase (DL_UPPER) = NO
Database configuration release level 0x0a00	=	Data Links Token Algorithm (DL_TOKEN) = MAC0
Database release level 0x0a00	=	Database heap (4KB) (DBHEAP) = 10000
Database territory	= US	Size of database shared memory (4KB) (DATABASE_MEMORY) = AUTOMATIC
Database code page	= 819	Catalog cache size (4KB) (CATALOGCACHE_SZ) = (MAXAPPLS*4)
Database code set ISO8859-1	=	Log buffer size (4KB) (LOGBUFSZ) = 2048
Database country/region code	= 1	Utilities heap size (4KB) (UTIL_HEAP_SZ) = 5000
Dynamic SQL Query management (DYN_QUERY_MGMT) = DISABLE		Buffer pool size (pages) (BUFFPAGE) = 1000
Discovery support for this database (DISCOVER_DB) = ENABLE		Extended storage segments size (4KB) (ESTORE_SEG_SZ) = 16000
Default query optimization class (DFT_QUERYOPT) = 7		Number of extended storage segments (NUM_ESTORE_SEGS) = 0
Degree of parallelism (DFT_DEGREE) = 1		Max storage for lock list (4KB) (LOCKLIST) = 40000
Continue upon arithmetic exceptions (DFT_SQLMATHWARN) = NO		Max size of appl. group mem set (4KB) (APPGROUP_MEM_SZ) = 2000
Default refresh age (DFT_REFRESH_AGE) = 0		Percent of mem for appl. group heap (GROUPHEAP_RATIO) = 70
Number of frequent values retained (NUM_FREQVALUES) = 0		Max appl. control heap size (4KB) (APP_CTL_HEAP_SZ) = 512
Number of quantiles retained (NUM_QUANTILES) = 300		Sort heap thres for shared sorts (4KB) (SHEAPTHRES_SHR) = 250
Backup pending	= NO	Sort list heap (4KB) (SORTHEAP) = 20000
Database is consistent	= YES	SQL statement heap (4KB) (STMTHEAP) = 10000
Rollforward pending	= NO	Default application heap (4KB) (APPLHEAPSZ) = 1024
Restore pending	= NO	Package cache size (4KB) (PCKCACHESZ) = (MAXAPPLS*8)
Multi-page file allocation enabled NO	=	Statistics heap size (4KB) (STAT_HEAP_SZ) = 4384
Log retain for recovery status	= NO	Interval for checking deadlock (ms) (DLCHKTIME) = 10000
User exit for logging status	= NO	Percent. of lock lists per application (MAXLOCKS) = 20
Data Links Token Expiry Interval (sec) (DL_EXPINT) = 60		Lock timeout (sec) (LOCKTIMEOUT) = -1
Data Links Write Token Init Expiry Intvl(DL_WT_IEXPINT) = 60		Changed pages threshold (CHNGPGS_THRESH) = 60
Data Links Number of Copies (DL_NUM_COPIES) = 1		Number of asynchronous page cleaners (NUM_IOCLEANERS) = 4
Data Links Time after Drop (days) (DL_TIME_DROP) = 1		Number of I/O servers (NUM_IOSERVERS) = 4

Index sort flag YES	(INDEXSORT) =	Default number of loadrec sessions (DFT_LOADREC_SES) = 1
Sequential detect flag = YES	(SEQDETECT)	Number of database backups to retain (NUM_DB_BACKUPS) = 12
Default prefetch size (pages) (DFT_PREFETCH_SZ) = 32		Recovery history retention (days) (REC_HIS_RETENTN) = 366
Track modified pages (TRACKMOD) = OFF		TSM management class (TSM_MGMTCLASS) =
Default number of containers = 1		TSM node name (TSM_NODENAME) =
Default tablespace extentsize (pages) (DFT_EXTENT_SZ) = 32		TSM owner (TSM_OWNER)
Max number of active applications (MAXAPPLS) = AUTOMATIC		TSM password (TSM_PASSWORD) =
Average number of active applications (AVG_APPLS) = 1		
Max DB files open per application (MAXFILOP) = 1024		
Log file size (4KB) 50000	(LOGFILSIZ) =	
Number of primary log files (LOGPRIMARY) = 4		
Number of secondary log files (LOGSECOND) = 1		
Changed path to log files (NEWLOGPATH) =		
Path to log files /dev/raw/raw61	=	
Overflow log path (OVERFLOWLOGPATH) =		
Mirror log path (MIRRORLOGPATH) =		
First active log file =		
Block log on disk full (BLK_LOG_DSK_FUL) = NO		
Percent of max active log space by transaction(MAX_LOG) = 0		
Num. of active log files for 1 active UOW(NUM_LOG_SPAN) = 0		
Group commit count (MINCOMMIT) = 2		
Percent log file reclaimed before soft chkpt (SOFTMAX) = 360		
Log retain for recovery enabled (LOGRETAIN) = OFF		
User exit for logging enabled (USEREXIT) = OFF		
Auto restart enabled (AUTORESTART) = ON		
Index re-creation time = SYSTEM (RESTART)	(INDEXREC)	
		Database Configuration for Node 15
		Database Configuration for Database TPCD
		Database configuration release level = 0x0a00
		Database release level = 0x0a00
		Database territory = US
		Database code page = 819
		Database code set = ISO8859-1
		Database country/region code = 1
		Dynamic SQL Query management (DYN_QUERY_MGMT) = DISABLE
		Discovery support for this database (DISCOVER_DB) = ENABLE
		Default query optimization class (DFT_QUERYOPT) = 7
		Degree of parallelism (DFT_DEGREE) = 1
		Continue upon arithmetic exceptions (DFT_SQLMATHWARN) = NO
		Default refresh age (DFT_REFRESH_AGE) = 0
		Number of frequent values retained (NUM_FREQVALUES) = 0
		Number of quantiles retained (NUM_QUANTILES) = 300
		Backup pending = NO
		Database is consistent = YES
		Rollforward pending = NO
		Restore pending = NO

Multi-page file allocation enabled NO	=	Statistics heap size (4KB) (STAT_HEAP_SZ) = 4384
Log retain for recovery status	= NO	Interval for checking deadlock (ms) (DLCHKTIME) = 10000
User exit for logging status	= NO	Percent. of lock lists per application (MAXLOCKS) = 20
Data Links Token Expiry Interval (sec) (DL_EXPINT) = 60		Lock timeout (sec) (LOCKTIMEOUT) = -1
Data Links Write Token Init Expiry Intvl(DL_WT_IEXPINT) = 60		Changed pages threshold (CHNGPGS_THRESH) = 60
Data Links Number of Copies (DL_NUM_COPIES) = 1		Number of asynchronous page cleaners (NUM_IOCLEANERS) = 4
Data Links Time after Drop (days) (DL_TIME_DROP) = 1		Number of I/O servers (NUM_IOSERVERS) = 4
Data Links Token in Uppercase (DL_UPPER) = NO		Index sort flag (INDEXSORT) =
Data Links Token Algorithm (DL_TOKEN) = MAC0		YES Sequential detect flag (SEQDETECT) =
Database heap (4KB) (DBHEAP) = 10000		YES Default prefetch size (pages) (DFT_PREFETCH_SZ) = 32
Size of database shared memory (4KB) (DATABASE_MEMORY) = AUTOMATIC		Track modified pages (TRACKMOD) = OFF
Catalog cache size (4KB) (CATALOGCACHE_SZ) = (MAXAPPLS*4)		Default number of containers = 1
Log buffer size (4KB) (LOGBUFSZ) = 2048		Default tablespace extentsize (pages) (DFT_EXTENT_SZ) = 32
Utilities heap size (4KB) (UTIL_HEAP_SZ) = 5000		Max number of active applications (MAXAPPLS) = AUTOMATIC
Buffer pool size (pages) (BUFFPAGE) = 1000		Average number of active applications (AVG_APPLS) = 1
Extended storage segments size (4KB) (ESTORE_SEG_SZ) = 16000		Max DB files open per application (MAXFILOP) = 1024
Number of extended storage segments (NUM_ESTORE_SEGS) = 0		Log file size (4KB) (LOGFILSIZ) =
Max storage for lock list (4KB) (LOCKLIST) = 40000		50000
Max size of appl. group mem set (4KB) (APPGROUP_MEM_SZ) = 2000		Number of primary log files (LOGPRIMARY) = 4
Percent of mem for appl. group heap (GROUPHEAP_RATIO) = 70		Number of secondary log files (LOGSECOND) = 1
Max appl. control heap size (4KB) (APP_CTL_HEAP_SZ) = 512		Changed path to log files (NEWLOGPATH) =
Sort heap thres for shared sorts (4KB) (SHEAPTHRES_SHR) = 250		Path to log files =
Sort list heap (4KB) (SORTHEAP) =		/dev/raw/raw62
20000		Overflow log path (OVERFLOWLOGPATH) =
SQL statement heap (4KB) (STMTHEAP) = 10000		Mirror log path (MIRRORLOGPATH) =
Default application heap (4KB) (APPLHEAPSZ) = 1024		First active log file =
Package cache size (4KB) (PCKCACHESZ) = (MAXAPPLS*8)		Block log on disk full (BLK_LOG_DSK_FUL) = NO
		Percent of max active log space by transaction(MAX_LOG) = 0

Num. of active log files for 1 active  
UOW(NUM\_LOG\_SPAN) = 0

Group commit count  
(MINCOMMIT) = 2  
Percent log file reclaimed before soft ckcpt  
(SOFTMAX) = 360  
Log retain for recovery enabled  
(LOGRETAIN) = OFF  
User exit for logging enabled  
(USEREXIT) = OFF

Auto restart enabled  
(AUTORESTART) = ON  
Index re-creation time (INDEXREC)  
= SYSTEM (RESTART)  
Default number of loadrec sessions  
(DFT\_LOADREC\_SES) = 1  
Number of database backups to retain  
(NUM\_DB\_BACKUPS) = 12  
Recovery history retention (days)  
(REC\_HIS\_RETENTN) = 366

TSM management class  
(TSM\_MGMTCLASS) =  
TSM node name  
(TSM\_NODENAME) =  
TSM owner (TSM\_OWNER)  
=  
TSM password  
(TSM\_PASSWORD) =

## ***DB2 Database Manager Configuration***

### Database Manager Configuration

Node type = Enterprise Server Edition with local  
and remote clients

Database manager configuration release level  
= 0x0a00

CPU speed (millisec/instruction)  
(CPUSPEED) = 2.715979e-07  
Communications bandwidth (MB/sec)  
(COMM\_BANDWIDTH) = 1.000000e+00

Max number of concurrently active databases  
(NUMDB) = 1  
Data Links support (DATALINKS)  
= NO  
Federated Database System Support  
(FEDERATED) = NO  
Transaction processor monitor name  
(TP\_MON\_NAME) =

Default charge-back account  
(DFT\_ACCOUNT\_STR) =

Java Development Kit installation path  
(JDK\_PATH) = /opt/IBMJava2-amd64-131

Diagnostic error capture level  
(DIAGLEVEL) = 0  
Notify Level (NOTIFYLEVEL) =  
0  
Diagnostic data directory path  
(DIAGPATH) =

Default database monitor switches  
Buffer pool  
(DFT\_MON\_BUFPOOL) = OFF  
Lock (DFT\_MON\_LOCK) =  
OFF  
Sort (DFT\_MON\_SORT) =  
OFF  
Statement (DFT\_MON\_STMT)  
= OFF  
Table (DFT\_MON\_TABLE) =  
OFF  
Timestamp  
(DFT\_MON\_TIMESTAMP) = OFF  
Unit of work (DFT\_MON\_UOW)  
= OFF  
Monitor health of instance and databases  
(HEALTH\_MON) = OFF

SYSADM group name  
(SYSADM\_GROUP) =  
SYSCTRL group name  
(SYSCTRL\_GROUP) =  
SYSMAINT group name  
(SYSMAINT\_GROUP) =

Database manager authentication  
(AUTHENTICATION) = SERVER  
Cataloging allowed without authority  
(CATALOG\_NOAUTH) = NO  
Trust all clients  
(TRUST\_ALLCLNTS) = YES  
Trusted client authentication  
(TRUST\_CLNTAUTH) = CLIENT  
Bypass federated authentication  
(FED\_NOAUTH) = NO  
Default database path (DFTDBPATH)  
= /home/tpch

Database monitor heap size (4KB)  
(MON\_HEAP\_SZ) = 90  
Java Virtual Machine heap size (4KB)  
(JAVA\_HEAP\_SZ) = 2048

Audit buffer size (4KB)  
 (AUDIT\_BUF\_SZ) = 0  
 Size of instance shared memory (4KB)  
 (INSTANCE\_MEMORY) = AUTOMATIC  
 Backup buffer default size (4KB)  
 (BACKBUFSZ) = 1024  
 Restore buffer default size (4KB)  
 (RESTBUFSZ) = 1024  
 Sort heap threshold (4KB)  
 (SHEAPTHRES) = 500000  
 Directory cache support  
 (DIR\_CACHE) = YES  
 Application support layer heap size (4KB)  
 (ASLHEAPSZ) = 15  
 Max requester I/O block size (bytes)  
 (RQRIOBLK) = 32767  
 Query heap size (4KB)  
 (QUERY\_HEAP\_SZ) = 1000  
 DRDA services heap size (4KB)  
 (DRDA\_HEAP\_SZ) = 128

Workload impact by throttled  
 utilities(UTIL\_IMPACT\_LIM) = 100  
 Priority of agents (AGENTPRI) =  
 SYSTEM  
 Max number of existing agents  
 (MAXAGENTS) = 400  
 Agent pool size  
 (NUM\_POOLAGENTS) = 64  
 Initial number of agents in pool  
 (NUM\_INITAGENTS) = 4  
 Max number of coordinating agents  
 (MAX\_COORDAGENTS) = (MAXAGENTS -  
 NUM\_INITAGENTS)  
 Max no. of concurrent coordinating agents  
 (MAXCAGENTS) = MAX\_COORDAGENTS  
 Max number of client connections  
 (MAX\_CONNECTIONS) =  
 MAX\_COORDAGENTS

Keep fenced process  
 (KEEPFENCED) = YES  
 Number of pooled fenced processes  
 (FENCED\_POOL) = MAX\_COORDAGENTS  
 Initialize fenced process with JVM  
 (INITFENCED\_JVM) = NO  
 Initial number of fenced processes  
 (NUM\_INITFENCED) = 0

Index re-creation time (INDEXREC)  
 = RESTART

Transaction manager database name  
 (TM\_DATABASE) = 1ST\_CONN  
 Transaction resync interval (sec)  
 (RESYNC\_INTERVAL) = 180

SPM name (SPM\_NAME) =  
 SPM log size  
 (SPM\_LOG\_FILE\_SZ) = 256  
 SPM resync agent limit  
 (SPM\_MAX\_RESYNC) = 20  
 SPM log path  
 (SPM\_LOG\_PATH) =

TCP/IP Service name  
 (SVCENAME) = xtpch  
 Discovery mode (DISCOVER) =  
 SEARCH  
 Discovery mode (DISCOVER) =  
 SEARCH  
 Discover server instance  
 (DISCOVER\_INST) = ENABLE  
 Maximum query degree of parallelism  
 (MAX\_QUERYDEGREE) = ANY  
 Enable intra-partition parallelism  
 (INTRA\_PARALLEL) = NO

No. of int. communication  
 buffers(4KB)(FCM\_NUM\_BUFFERS) = 16384  
 Node connection elapse time (sec)  
 (CONN\_ELAPSE) = 20  
 Max number of node connection retries  
 (MAX\_CONNRETRIES) = 5  
 Max time difference between nodes (min)  
 (MAX\_TIME\_DIFF) = 1440

db2start/db2stop timeout (min)  
 (START\_STOP\_TIME) = 10

### ***DB2 Registry Variables***

DB2\_EXTENDED\_OPTIMIZATION=Y  
 DB2\_ANTIJOIN=Y  
 DB2\_LIKE\_VARCHAR=Y,Y  
 DB2BPVARS=/home/tpch/custom/bpvar.cfg  
 DB2RQTIME=30  
 DB2\_FORCE\_FCM\_BP=ON  
 DB2OPTIONS=-t -v +c  
 DB2BQTRY=120  
 DB2\_PARALLEL\_IO=\*

### ***Linux Parameters***

echo "250 256000 100 1024" >  
 /proc/sys/kernel/sem  
 echo 262143 > /proc/sys/net/core/rmem\_max  
 echo 262143 > /proc/sys/net/core/wmem\_max  
 echo 262143 > /proc/sys/net/core/rmem\_default  
 echo 262143 > /proc/sys/net/core/wmem\_default

## Appendix B: Database Build Scripts

### *buildtpcd*

```
#!/usr/bin/perl
# usage buildtpcd [QUAL]
# ASSUMPTIONS: all ddl files have commits in them!
($myName = $0) =~ s@.*/@@; $usage="
Usage: buildtpcd [QUAL]
    where QUAL is the optional parameter saying to
    build the qualification
        database (sf = .1 = 100MB)\n";

$qual="";
if (@ARGV == 1){
    $qual = $ARGV[0];
}

# get TPC-D specific environment variables
require "getvars";
require "macro.pl";
require "tpcdmacro.pl";
require "version";
$timestamp=`perl gettimestamp "short"`;

# Make output unbuffered.
open(STDOUT, "| tee buildtpcd.out.${timestamp}");
select(STDOUT);
$|= 1 ;
#-----#
# verify that necessary environment variables for
# building the database #
# are present. Default those that aren't necessary
#
#-----#
# variables that must be specified for script to run
@reqVars = ("TPCD_PLATFORM",
            "TPCD_PRODUCT",
            "TPCD_VERSION",
            "TPCD_DBNAME",
            "TPCD_MODE",
            "TPCD_SF",
            "TPCD_DDLPATH",
            "TPCD_AUDIT",
            "TPCD_AUDIT_DIR",
            "TPCD_BUILD_STAGE");

# variables default to 'NULL' if unspecified
@defNullVars = ("TPCD_LOAD_SCRIPT",
```

```
"TPCD_LOAD_SCRIPT_QUAL",
"TPCD_INPUT",
"TPCD_QUAL_INPUT",
"TPCD_DBGEN",
"TPCD_LOGPRIMARY",
    "TPCD_LOGSECOND",
    "TPCD_LOGFILSIZ",
    "TPCD_LOG_DIR",
    "TPCD_MACHINE",
    "TPCD_AGENTPRI",

"TPCD_STAGING_TABLE_DDL",

"TPCD_PRELOAD_STAGING_TABLE_SCRIPT",

"TPCD_DELETE_STAGING_TABLE_SQ
L",
    "TPCD_RUNSTATSHORT",
    "TPCD_ADD_RI",
    "TPCD_AST",
    "TPCD_DBM_CONFIG",
    "TPCD_EXPLAIN_DDL",
    "TPCD_NODEGROUP_DEF",
    "TPCD_BUFFERPOOL_DEF",

"TPCD_LOAD_DB2SET_SCRIPT",
    "TPCD_DB2SET_SCRIPT",

"TPCD_LOG_DIR_SETUP_SCRIPT",
    "TPCD_LOAD_CONFIGFILE",

"TPCD_LOAD_DBM_CONFIGFILE",
    "TPCD_TEMP");

&setVar(@reqVars, "ERROR");
&setVar(@defNullVars, "NULL");

if ( $qual eq "QUAL" ){
    @reqQualVars =
        ("TPCD_QUAL_DBNAME",
         "TPCD_QUAL_DDL",

"TPCD_QUAL_TBSP_DDL",

"TPCD_QUALCONFIGFILE",

"TPCD_DBM_QUALCONFIG",

"TPCD_LOAD_QUALCONFIGFILE",

"TPCD_LOAD_DBM_QUALCONFIGFILE");

    &setVar(@reqQualVars, "ERROR");
```

```

        if ( ($ENV{"TPCD_QUAL_INPUT"} ) eq
"NULL" ){
            if (((($ENV{"TPCD_DBGEN"} ) eq "NULL" ) ||
                (($ENV{"TPCD_TEMP"} ) eq
"NULL"))){
                die "TPCD_DBGEN and TPCD_TEMP
must be set if flatfiles are not provided.\n";
            }
        }
    }
}

$platform=$ENV{"TPCD_PLATFORM"};

if (length($ENV{"TPCD_DBPATH"}) <= 0){
    # if no db pathname specified, build the db in the
home directory
    if ( $platform eq "aix" ||
        $platform eq "sun" ||
        $platform eq "ptx" ||
        $platform eq "hp" ||
        $platform eq "linux"){
        $ENV{"TPCD_DBPATH"} =
$ENV{"HOME"};
    }
    elsif ( $platform eq "nt" ){
        $ENV{"TPCD_DBPATH"} =
$ENV{"HOMEDRIVE"};
    }
    else{
        die "platform '$platform' not supported yet\n";
    }
}
if ( ($ENV{"TPCD_INPUT"} ) eq "NULL" ){
    if (((($ENV{"TPCD_DBGEN"} ) eq "NULL" ) ||
        (($ENV{"TPCD_TEMP"} ) eq "NULL"))){
        die "TPCD_DBGEN and TPCD_TEMP must
be set if flatfiles are not provided.\n";
    }
}
}
#-----#
# ddl script files found under custom directory
#
#-----#
-----#

if (length($ENV{"TPCD_DDL"}) <= 0){
    $ENV{"TPCD_DDL"} = "dss.ddl";
}
if (length($ENV{"TPCD_TBSP_DDL"}) <= 0){
    $ENV{"TPCD_TBSP_DDL"} = "dss.tbsp.ddl";
}
if (length($ENV{"TPCD_INDEXDDL"}) <= 0){
    $ENV{"TPCD_INDEXDDL"} = "dss.index";
}
}
if (length($ENV{"TPCD_RUNSTATS"}) <= 0){
    $ENV{"TPCD_RUNSTATS"} = "dss.runstats";
}
}
if (length($ENV{"TPCD_CONFIGFILE"}) <= 0){
    $ENV{"TPCD_CONFIGFILE"} =
"dss.dbconfig";
}
}

#-----#
-----#
# other settings
#
#-----#
-----#

if (length($ENV{"TPCD_BACKUP_DIR"}) <= 0){
    $ENV{"TPCD_BACKUP_DIR"} =
"${delim}dev${delim}null";
}
}
if (length($ENV{"TPCD_COPY_DIR"}) <= 0){
    $ENV{"TPCD_COPY_DIR"} =
"${delim}dev${delim}null";
}
}
if (length($ENV{"TPCD_TEMP"}) <= 1){
    $ENV{"TPCD_TEMP"} =
"/u/$instance/sql/lib/tmp";
}
}
if (length($ENV{"TPCD_PHYS_NODE"}) <= 0){
    $ENV{"TPCD_NODEGROUP_DEF"}="NULL"
}
}
if
(length($ENV{"TPCD_GENERATE_SEED_FILE"}
) <= 0){
    $ENV{"TPCD_GENERATE_SEED_FILE"} =
"no";
}
}
if (length($ENV{"TPCD_SORTBUF"}) <= 0){
    $ENV{"TPCD_SORTBUF"} = 4096;
}
}
if
(length($ENV{"TPCD_LOAD_PARALLELISM"}
) <= 0){
    $ENV{"TPCD_LOAD_PARALLELISM"} = 0;
}
}
if (length($ENV{"TPCD_LOADSTATS"}) <= 0){
    $ENV{"TPCD_LOADSTATS"} = "no";
}
}
if (length($ENV{"TPCD_FASTPARSE"}) <= 0){
    $ENV{"TPCD_FASTPARSE"} = "no";
}
}
if (length($ENV{"TPCD_LOG"}) <= 0){
    $ENV{"TPCD_LOG"} = "no";
}
}

```

```

}
if (length($ENV{"TPCD_SMPDEGREE"}) <= 0){
    $ENV{"TPCD_SMPDEGREE"} = 1;
}
if (length($ENV{"TPCD_ACTIVATE"}) <= 0){
    $ENV{"TPCD_ACTIVATE"} = "no";
}
if (length($ENV{"TPCD_APPEND_ON"}) <= 0){
    $ENV{"TPCD_APPEND_ON"}="yes"
}
if
(length($ENV{"TPCD_GENERATE_SEED_FILE"
}) <= 0){

$ENV{"TPCD_GENERATE_SEED_FILE"}="no";
}

#setup global variables
$tpcdVersion=
    $ENV{"TPCD_VERSION"};
$buildStage=
    $ENV{"TPCD_BUILD_STAGE"};
$mode=
    $ENV{"TPCD_MODE"};
$delim =
    $ENV{"TPCD_PATH_DELIM"};
$sep =
    $ENV{"COMMAND_SEP"};
$ddlpath=
    $ENV{"TPCD_DDLPATH"};
$extraindex=
    $ENV{"TPCD_EXTRAINDEX"};
$earlyindex=
    $ENV{"TPCD_EARLYINDEX"};
$loadstats=
    $ENV{"TPCD_LOADSTATS"};
$addRI=
    $ENV{"TPCD_ADD_RI"};
$astFile=
    $ENV{"TPCD_AST"};
$genSeed=
    $ENV{"TPCD_GENERATE_SEED_FILE
"};
$log=
    $ENV{"TPCD_LOG"};
$activate=
    $ENV{"TPCD_ACTIVATE"};
$RealAudit=
    $ENV{"TPCD_AUDIT"};
$auditDir=
    $ENV{"TPCD_AUDIT_DIR"};
$loadsetScript=
    $ENV{"TPCD_LOAD_DB2SET_SCRIPT
"};
$user=
    $ENV{"USER"};
$logDirScript=
    $ENV{"TPCD_LOG_DIR_SETUP_SCRIP
T"};

$logprimary=
    $ENV{"TPCD_LOGPRIMARY"};
$logsecond=
    $ENV{"TPCD_LOGSECOND"};
$logfilsiz=
    $ENV{"TPCD_LOGFILSIZ"};
$dbpath =
    $ENV{"TPCD_DBPATH"};
$explainDDL=
    $ENV{"TPCD_EXPLAIN_DDL"};
$platform=
    $ENV{"TPCD_PLATFORM"};
$buffpooldef=
    $ENV{"TPCD_BUFFERPOOL_DEF"};
$stagingTbl =
    $ENV{"TPCD_STAGING_TABLE_DDL"
};
$preloadSampleUF=
    $ENV{"TPCD_PRELOAD_STAGING_T
ABLE_SCRIPT"};
$deleteSampleUF=
    $ENV{"TPCD_DELETE_STAGING_TA
BLE_SQL"};
$machine=
    $ENV{"TPCD_MACHINE"};
$runstatShort =
    $ENV{"TPCD_RUNSTATSHORT"};
$runstats =
    $ENV{"TPCD_RUNSTATS"};
$smpdegree =
    $ENV{"TPCD_SMPDEGREE"};
$agentpri =
    $ENV{"TPCD_AGENTPRI"};
$setScript =
    $ENV{"TPCD_DB2SET_SCRIPT"};
$backupdir =
    $ENV{"TPCD_BACKUP_DIR"};
$nodegroupdef=
    $ENV{"TPCD_NODEGROUP_DEF"};
$dbgen=
    $ENV{"TPCD_DBGEN"};
$appendOn=
    $ENV{"TPCD_APPEND_ON"};
$indexddl=
    $ENV{"TPCD_INDEXDDL"};

if($qual eq "QUAL"){
    $logDir=
        $ENV{"TPCD_LOG_QUAL_DIR"};
    $dbname=
        $ENV{"TPCD_QUAL_DBNAME"};
    $input=
        $ENV{"TPCD_QUAL_INPUT"};
    $sf=
        $ENV{"TPCD_QUAL_SF"};
}

```



```

        $loadconfigfile=$ENV{"TPCD_LOAD_Q
UALCONFIGFILE"};
        $loadDBMconfig=
        $ENV{"TPCD_LOAD_DBM_QUALCON
FIGFILE"};
        $loadscript =
        $ENV{"TPCD_LOAD_SCRIPT_QUAL"};
        $configfile =
        $ENV{"TPCD_QUALCONFIGFILE"};
        $dbmconfig =
        $ENV{"TPCD_DBM_QUALCONFIG"};
        $ddl=
        $ENV{"TPCD_QUAL_DDL"};
        $tbspddl=
        $ENV{"TPCD_QUAL_TBSP_DDL"};
    }else{
        $logDir=
        $ENV{"TPCD_LOG_DIR"};
        $dbname=
        $ENV{"TPCD_DBNAME"};
        $input=
        $ENV{"TPCD_INPUT"};
        $sf=
        $ENV{"TPCD_SF"};
        $loadconfigfile=$ENV{"TPCD_LOAD_C
ONFIGFILE"};
        $loadDBMconfig=
        $ENV{"TPCD_LOAD_DBM_CONFIGFI
LE"};
        $loadscript =
        $ENV{"TPCD_LOAD_SCRIPT"};
        $configfile =
        $ENV{"TPCD_CONFIGFILE"};
        $dbmconfig =
        $ENV{"TPCD_DBM_CONFIG"};
        $ddl=
        $ENV{"TPCD_DDL"};
        $tbspddl=
        $ENV{"TPCD_TBSP_DDL"};
    }

    if (( $mode eq "uni" ) || ( $mode eq "smp" )){
        $all_ln="once";
        $all_pn="once";
        $once="once";
    }
    else{
        $all_ln="all_ln";
        $all_pn="all_pn";
        $once="once";
    }

    #-----#
    # echo parameter settings to acknowledge what is
    # being built      #
    # and set db2set options for database load
    #
    #-----#
    -----#
    &printSummary;
    print "\nSleeping for 15 seconds to give you a
    chance to reconsider...\n";
    sleep 15;
    if ( $platform eq "nt" ){
        if (( $mode eq "uni" ) || ( $mode eq "smp" )){
            #spaces required for NT
            $rc=&doddb_noconn("db2set DB2OPTIONS=\
-t -v +c\";db2set DB2NTNOCACHE=ON",$all_ln);
        }
        else{
            $rc=&doddb_noconn("db2set
            DB2OPTIONS=\\\" -t -v +c\\\";db2set
            DB2NTNOCACHE=ON",$all_ln);
        }
    }
    else{
        if (( $mode eq "uni" ) || ( $mode eq "smp" )){
            $rc=&doddb_noconn("db2set DB2OPTIONS=\
-t -v +c\"",$all_ln);
        }
        else{
            $rc=&doddb_noconn("db2set
            DB2OPTIONS=\\\" -t -v +c\\\"",$all_ln);
        }
    }
    if ( $rc != 0 ){
        die "failure setting db2 environment variable : rc =
        $rc\n";
    }

    #-----#
    -----#
    # set the db2 env vars for loading, from the
    # TPCD_LOAD_DB2SET_SCRIPT script #
    #-----#
    -----#
    if ( $loadsetScript ne "NULL" )
    {
        if ( $platform eq "nt" ){
            if (( $mode eq "uni" ) || ( $mode eq "smp" )){
                $rc=system("${ddlpath}${delim}$loadsetScript");
            }
            else{
                $rc=system("rah \" cd ${ddlpath} &
                $loadsetScript\" ");
            }
        }
    }

```

```

    }
    else{

$rc=system("${ddlpath}${delim}$loadsetScript");
    }
    ($rc == 0) || die "failure loading db2set parms
from $loadsetScript \n";
}

!&stopStart || die;
#-----#
# Begin complete build: TPCD_BUILDSTAGE =
ALL #
#-----#
#-----#

if($buildStage eq "ALL") {
    #create the database
    $rc = &createDb;
    ($rc == 0) || die "ERROR: create database
failed. rc = $rc\n ";
    &setLog;
};

$rc = &setLoadConfig;

#-----#
#-----#
# Begin build from CreateTablespace or early
Indexes #
#-----#
#-----#

if( $buildStage eq "ALL" ||
    $buildStage eq "CRTTBSP" ||
    ($buildStage eq "INDEX" && $earlyindex eq
"yes")){
    !&createNodegroups || print "ERROR:
create nodegroups failed.\n";
    !&createBufferPools || print "ERROR:
create bufferpools failed.\n";
    &outtime("*** Start of audited Load Time
- starting to create tables");
    !&createTablespaces || print "WARNING:
create tablespaces error.\n";
    !&createExplainTbIs || print "ERROR:
create EXPLAIN tables failed.\n";
    !&createTables || print "ERROR: create
tables failed.\n";

    mkdir("${delim}tmp${delim}$instance",07
77);

    # if earlyindex requested, create indexes
if ( $earlyindex eq "yes" ){

```

```

        !&createIndexes("early") || die
"ERROR: create early indexes failed.\n";
    }
    # start the dbgen and load.....call the
specific mode for loading (uni,smp,mln)
    !&loadData || die "ERROR: failure during
load data\n";

    # remove the update.pair.num file so when
setupDir runs, it doesn't
    # hang waiting for an answer on nt
    &rm("${auditDir}${delim}$dbname.$user.up
date.pair.num");
    # verify that the audit directory exists
    $filename="auditDir";
    if (-e $filename){
        # set up the
$auditDir/$dbname.$user.update.pair.num file
        # to start at update pair 1

        $filename="auditDir${delim}$dbname.$u
ser.update.pair.num";
    }else{
        mkdir ("auditDir", 0775) || die
"cannot mkdir $auditDir";
    }
    print "setting update pair num to 1\n";
    system("echo 1 > $filename");
};
#-----#
#-----#
# Begin build from Index or Load
#
#-----#
#-----#

if( $buildStage eq "ALL" ||
    $buildStage eq "CRTTBSP" ||
    $buildStage eq "LOAD" ||
    $buildStage eq "INDEX"){

    # if indexes haven't been created, do so
now
    if ( $earlyindex ne "yes" ){
        !&createIndexes("normal") || die
"ERROR: create indexes failed.\n";
    }
    if ( $extraindex ne "no" ){
        !&createIndexes("extra") || die
"ERROR: create extra indexes failed.\n";
    }
}; # end create/load/index phase of the build
#-----#
#-----#

```

```

# Begin build from runstats
#
#-----#
-----#

if( $buildStage eq "ALL" ||
    $buildStage eq "CRTTBSP" ||
    $buildStage eq "LOAD" ||
    $buildStage eq "INDEX" ||
    $buildStage eq "RUNSTATS"){
    # if statistics not gathered on the load, run
runstats (we have to run the
    # stats at the same time as the index
creation whether it be both during load,
    # or after load)
    # We need to run the runstats as well if we
have specied an extra index file
    # for "after load" indexes
    if (( $loadstats eq "no" ) || ( $earlyindex eq
"no" ) || ( $extraindex ne "no" )){
        &doRunStats;
    }
};

#-----#
-----#
# End build phase: all/load/index/runstats
#
#-----#
-----#
# Add RI/AST, set run configuration
#
#-----#
-----#

if ( $addRI ne "NULL" ){
    &outtime("*** Adding RI constraints started");

&dodb2file($dbname,"$ddlpath${delim}$addRI",,$o
nce);
    &outtime("*** Adding RI constraints completed");
}

#add the AST if it has been requested
if ( $astFile ne "NULL" ){
    &outtime("*** Adding AST started");

&dodb2file($dbname,"$ddlpath${delim}$astFile",,$
once);
    &outtime("*** Adding AST completed");
}

# check tbsp info
&dodb_conn($dbname,"db2 list tablespaces show
detail",,$once);

# set the configuration
&outtime("*** Set Configuration started");
&outtime("*** Setting degree of parallelism");

&setConfiguration;
# if logging is enabled, we must take a backup of the
database
if ( $log eq "yes" ){
    &createBackup;
}

# stop and restart the database to get config parms
recognized
!&stopStart || die;

&outtime("*** Set Configuration completed");
&outtime("*** End of audited Load Time");

#create generated seeds
if ( $genSeed ne "no" ){
    $src = system("perl createmseedme.pl
1000");
    ($src != 0) || warn "createmseedme failed\n";
}

#-----#
-----#
# Call buildtpcdbatch to compile tpcdbatch
#
#-----#
-----#
# - if we are in real audit mode then we have to do a
number of things #
# set up the audit directory structure and the run
directory structure #
# so that once we have completed the buildtpcd,
we are ready to run. #
# first remove any old "update pair number" file so
we won't be prompted #
# doing setupDir.
#
# - before we stop the database for the final time
#
# if we are in the real audit mode then run dbtables
and dbcheck before #
# we print out the notice that we're ready to run
performance tests #
# if we are building the qualification database then
we'll bind to both #
# the dbname database and the qualification
database #
#-----#
-----#
$src = system("perl buildtpcdbatch $qual");

```

```

($rc == 0) || die "buildtpcdbatch failed rc=$rc\n";

if ( $RealAudit eq "yes" ){
    &rm("$auditDir${delim}tools${delim}tpcd
.runsetup");
    system("perl setupRun");
    if ( $qual eq "QUAL" ){
        $verifyType="q";
    }
    else{
        $verifyType="t";
    }
    system("perl tablesdb $verifyType");
    &dodb2file($dbname,"$auditDir${delim}to
ols${delim}first10rows.sql",$once);
}

#-----#
# Create Catalog info
#
#-----#
$rc = system("perl catinfo.pl b");
($rc == 0) || warn "catinfo failed!!! rc = $rc\n";

$rc=system("db2stop");
($rc == 0) || die "failure during db2stop rc = $rc \n";

&outtime("*** Ready to run the performance tests
once the dbm has restarted");

if ( $RealAudit ne "yes" ){
    # if we are not in a real audit, then we can restart
the database manager
    # if we are in a real audit, then we don't want to
do this until the
    # power test starts
    $rc=system("db2start");
    ($rc == 0) || die "failure during db2start rc = $rc
\n";
    if ( $activate eq "yes" ){
        &dodb_noconn("activate database
$dbname",$once);
    }
}

&outtime("*** Finished creating the database");
#-----#
# finished creating the database
#
#-----#

```

```

#-----#
# Function: setLog
#
#-----#
sub setLog{
    # update the log information first
    # set up the log directory before we do any
index creation
    my $rc;
    my $setLogs;
    my $setLogString;

    if ($logDirScript ne "NULL"){
        system ("perl
$dddlpath${delim}$logDirScript");
    }
    elsif ( $logDir ne "NULL" ){
        &dodb_noconn("db2 update
database configuration for $dbname using
newlogpath $logDir",$all_in);
    }
    $setLogs=0;
    $setLogString="";
    if ( $logprimary ne "NULL" ){
        $setLogString.="db2 update db
cfg for $dbname using logprimary $logprimary";
        $setLogs=1;
    }
    if ( $logsecond ne "NULL" ){
        if ( $setLogs != 0 ){
            $setLogString.=" $sep ";
        }
        $setLogString.="db2 update db
cfg for $dbname using logsecond $logsecond";
        $setLogs=1;
    }
    if ( $logfilsiz ne "NULL" ){
        if ( $setLogs != 0 ){
            $setLogString.=" $sep ";
        }
        $setLogString.="db2 update db
cfg for $dbname using logfilsiz $logfilsiz";
        $setLogs=1;
    }
    if ( $setLogs != 0 ){
        $setLogString.=" $sep ";
    }
    $setLogString.="db2 update db cfg for
$dbname using logbufsz 128";
    $rc =
&dodb_noconn("$setLogString",$all_in);
}

```

```

}
#-----#
# Function: createDb
#
#-----#
sub createDb{
    &outtime("*** Starting to create the
database");
    # setup required variables
    my $src;
    $src = &dodb_noconn("db2 \"create
database $dbname on $dbpath collate using identity
with 'TPC-D $sf GB\"",$once);
    ($src == 0) || return($src);
    # reset the db and dbm configuration before
we start
    &dodb_noconn("db2 reset database
configuration for $dbname",$all_in);
    &dodb_conn($dbname,"db2 alter
bufferpool ibmdefaultbp size -1 $sep \
db2 grant connect on database to public
$sep \
db2 grant dbadm on database to
$dbname $sep \
db2 commit",$once);
    &dodb_noconn("db2 reset database
manager configuration",$once);
}
#-----#
# Function: createNodegroups
#
#-----#
sub createNodegroups{
    &outtime("*** Creating the nodegroups.");
    my $src;
    if ( $nodegroupdef ne "NULL"){
        $src =
&dodb2file($dbname,"$ddlpath${delim}$nodegroup
pdef",$once);
    }
}
#-----#
# Function: createExplainTbls
#
#-----#
sub createExplainTbls{
    &outtime("*** Creating the EXPLAIN
tables.");
    my $src;
    my $explnPathFile;
    my $home;
    my $sqlpath;

    if ( $explainDDL ne "NULL" ){
        $explnPathFile="$explainDDL";
    }
    else{
        if ( $platform eq "ptx" ){
            $home=$ENV{"HOME"};
            $sqlpath="$home${delim}sqllib";
        }
        if ( $platform ne "nt" ){
            $home=$ENV{"HOME"};
            $sqlpath="$home${delim}sqllib";
        }
        else{
            $sqlpath=$ENV{"DB2PATH"};
        }

        $explnPathFile="$sqlpath${delim}misc${d
elim}EXPLAIN.DDL";
    }
    $src = &dodb_conn($dbname,
"db2 -tvf $explnPathFile $sep \
db2 alter table explain_instance locksize
table append on $sep \
db2 alter table explain_statement locksize
table append on $sep \
db2 alter table explain_argument locksize
table append on $sep \
db2 alter table explain_object locksize table
append on $sep \
db2 alter table explain_operator locksize
table append on $sep \
db2 alter table explain_predicate locksize
table append on $sep \
db2 alter table explain_stream locksize
table append on",
$once);
}
#-----#
# Function: createBufferPools
#
#-----#
sub createBufferPools{

```



```

                db2 alter table tpcd.orders pctfree 0",
                $once);
        }
}
#-----#
# Function: createIndexes
#
#-----#
sub createIndexes{
    # setup required variables
    local @args = @_;
    my $indexType = @args[0];
    my $src;
    &outtime("*** Starting to create
    $indexType indexes");
    if( $indexType eq "extra"){
        $src =
&dodb2file($dbname,"$ddlpath${delim}$extraindex
", $once);
    }elseif( $indexType eq "early" || $indexType
eq "normal"){
        $src =
&dodb2file($dbname,"$ddlpath${delim}$indexddl",
$once);
    }
    &outtime("*** Create $indexType index
completed");
    return $src;
}

#-----#
# Function: setLoadConfig
#
#-----#
sub setLoadConfig{
    &outtime("*** Setting LOAD
configuration.");
    my $src;
    my $buffpage;
    my $sortheap;
    my $sheapthres;
    my $util_heap_sz;
    my $ioservers;
    my $ioclnrs=      1;
    my $chnngpgs=    60;

    if ($loadconfigfile eq "NULL"){

```

```

        if ( $machine eq "small" ){
            $buffpage = 5000;
            $sortheap = 3000;
            $sheapthres = 8000;
            $util_heap_sz = 5000;
            $ioservers = 6;
        }
        elsif ( $machine eq "medium" ){
            $buffpage = 10000;
            $sortheap = 8000;
            $sheapthres = 20000;
            $util_heap_sz = 10000;
            $ioservers = 10;
        }
        elsif ( $machine eq "big" ){
            $buffpage = 30000;
            $sortheap = 20000;
            $sheapthres = 50000;
            $util_heap_sz = 30000;
            $ioservers = 20;
        }
        else {
            die "Neither a LOAD
            config filename nor a valid machine size has \
            been specified!\n";
        }
        $src = &dodb_noconn("db2 update
        db cfg for $dbname using buffpage $buffpage $sep \
        db2 update db cfg for $dbname
        using sortheap $sortheap $sep \
        db2 update db cfg for $dbname
        using num_iocleaners $ioclnrs $sep \
        db2 update db cfg for $dbname
        using num_ioservers $ioservers $sep \
        db2 update db cfg for $dbname
        using util_heap_sz $util_heap_sz $sep \
        db2 update db cfg for $dbname
        using chngpgs_thresh $chnngpgs", $all_ln);
    }
    else{
        $src =
&dodb2file_noconn("$ddlpath${delim}$loadconfig
file", $all_ln);
    }
    ($src == 0) || return $src;
    if($loadDBMconfig ne "NULL"){
        $src =
&dodb2file_noconn("$ddlpath${delim}$loadDBMc
onfig", $once);
    }
    else{
        $src = &dodb_noconn("db2 update
        dbm cfg using sheapthres $sheapthres", $once);
    }
    ($src == 0) || return $src;

```

```

        &dodb_noconn("db2 terminate", $once);
        $rc = &stopStart;
        return $rc;
    }
#-----#
# Function: loadData
#
#-----#
sub loadData{
    # start the dbgen and load.....call the
    specific mode for loading (uni,smp,mln)
    my $rc;
    if (( $mode eq "uni" ) || ( $mode eq "smp"
))){
        &outtime("*** Starting the load");
        # call the appropriate dbgen/load
for uni/smp
        if ( $loadscript eq "NULL"){
            $rc = system("perl
genloaduni $qual");
            ( $rc == 0 ) || print
"ERROR: genloaduni failed rc = $rc\n";
        }
        else{
            $rc =
&dodb2file_noconn("$ddlpath${delim}$loadscript",
$once);
            ( $rc == 0 ) || print
"ERROR: load script: $loadscript failed. rc = $rc\n";
        }
        elsif (( $mode eq "mln" ) || ( $mode eq
"mpp" )){
            &outtime("*** Starting the load");
            # call the appropriate
dbgen/split/(sort)/load for mln/mpp
            if ( $loadscript eq "NULL"){
                $rc = system("perl
genloadmpp $qual");
                ( $rc == 0 ) || print
"ERROR: genloadmpp failed. rc = $rc\n";
            }
            else{
                system("$ddlpath${delim}$loadscript");
                # $rc =
&dodb2file_noconn("$ddlpath${delim}$loadscript
$sf");
                # ( $rc == 0 ) || print
"ERROR: load script $loadscript failed. rc = $rc\n";
            }
        }
        else{

```

```

        print "TPCD_MODE not set to
one of uni, smp, mln or mpp\n";
        $rc = 1;
    }
    ( $rc == 0 ) || &outtime("*** Load
complete");
    return $rc;
}
#-----#
# Function: doRunStats
#
#-----#
sub doRunStats{
    # if loadstats not gathered, then index stats not
gathered either.
    &outtime("*** Runstats started");
    if ( $runstatShort ne "NULL" ){
        # we've specified a second runstats file...This
runstats file should do
        # runstats for all table except lineitem. The
lineitem runstats command
        # should be left in the main runstats file.
        if ( $platform eq "aix" || $platform eq "sun" ||
$platform eq "ptx" ){
            print "runstats from
$dddlpath${delim}$runstatShort running now\n";
            $rc = system("db2 -tvf
\"$ddlpath${delim}$runstatShort" >
\"$auditDir${delim}tools${delim}runstatShort.out\
& ");
            print "rc from runstatshort=$rc\n";
        }
        elsif ( $platform eq "nt" ){
            system("start db2 -tvf
$dddlpath${delim}$runstatShort");
        }
        else
        {
            print "Don't know how to start in
background on $platform platform\n";
            print "therefore running runstats
serially\n";
        }
    }
    &dodb2file($dbname, "$ddlpath${delim}$runstatSh
ort", $once);
    }
    # run the full runstats, or the remainder of what
wasn't put into the short
    # runstats file. You should be sure that this
runstats will take longer
    # than the short runstats that is running in the
background, otherwise

```



```

# setting the config will happen before this is
done.

&dodb2file($dbname,"$ddlpath${delim}$runstats",
$once);
    &outtime("*** Runstats completed");
}

#-----#
# Function: setConfiguration
#
#-----#
sub setConfiguration{
    my $ret = 0;
    &dodb_noconn("db2 update database
configuration for $dbname using dft_degree
$smpdegree",$all_ln);
    &dodb_noconn("db2 update database
manager configuration using max_querydegree
$smpdegree",$once);
    &dodb2file_noconn("${ddlpath}${delim}$
configfile",$all_ln);
    &dodb2file_noconn("${ddlpath}${delim}$
dbmconfig",$once);

    if ( $agentpri ne "NULL" ){
        &dodb_noconn("db2 update dbm cfg
using AGENTPRI $agentpri",$once);
    }
    # set the db2 environment variables for
running the benchmark
    if ( $setScript ne "NULL" ){
        if ( $platform eq "aix" || $platform eq
"sun" || $platform eq "ptx"){
$ret=system("${ddlpath}${delim}$setScript");
        }
        elsif ( $platform eq "nt" ){
            if (( $mode eq "uni" ) || ( $mode eq
"smp" )){
                $ret = system("perl
${ddlpath}${delim}$setScript");
            }
            else{
                $ret = system(" rah \" cd ${ddlpath}
& $setScript\" ");
            }
        }
        #($ret == 0) || die "failure setting
runtime db2set parms from $setScript \n";
    }
}

```

```

#-----#
# Function: createBackup
#
#-----#
sub createBackup{
    my $rc;
    &dodb_noconn("db2 update database
configuration for $dbname using LOGRETAIN
yes",$all_ln);
    print "\n NOTE: DO NOT RESET THE
DATABASE CONFIGURATION or you will lose
logretain\n";
    # force a connection to the database on all
nodes to ensure LOGRETAIN is
    # set in effect.
    # An error message will print to screen if
the logretain is set properly
    # i.e. SQL116N A connection to or
activation of database <database name>
    # cannot be made.
    # This is expected and the lack of this error
message should be seen as an
    # error in the database build.
    &dodb_conn($dbname,"db2 \"select
count(*) from tpcd.region\"", $all_ln);

    if ( $qual eq "QUAL" ){
        &outtime("*** Starting the
backup");
        if (( $mode eq "mln" ) || ( $mode
eq "mpp")){
            # must back up catalog node
first...assume node 00
            $rc=system("db2_all
\\]<<+000< db2 \"backup database $dbname to
$backupdir without prompting\" ");
            ($rc == 0) || print "ERROR:
backup of catalog node failed rc = $rc\n";
            # back up remaining nodes
            $rc=system("db2_all \\|]<<-
000< db2 backup database $dbname to $backupdir
without prompting\" ");
            ($rc == 0) || print "ERROR:
backup of remaining nodes failed rc = $rc\n";
        }
        else{
            $rc = &dodb_noconn("db2
backup database $dbname to $backupdir",$once);
        }
        ($rc == 0) || &outtime("***
Finished the backup");
    }
    else{

```

```

        # This is the test database. Clause
3.1.4 states that "the test sponsor is
        # not required to make or have
backup copies of the test database; however
        # all other mechanisms that
guarantee durability of the qualification
        # database must be enabled in the
same way for the test database".
        # According to this clause we do
need to keep the backup of the database.
        $src = &dodb_noconn("db2dart
$dbname /CHST /WHAT DBBP OFF",$all_in);
    }
    return $src;
}

#-----#
# Function: printSummary
#
#-----#
sub printSummary{
    if ( $buildStage ne "ALL" ){
        print "***** STARTING the build
process at the $buildStage Stage *****\n";
    }
    print "Building a TPC-D Version
$tpcdVersion $sf GB database on $dbpath with: \n";
    print " Mode = $mode \n";
    print " Tablespace ddl in
$ddlpath${delim}$tbspddl \n";
    if ( $nodegroupdef ne "NULL" ){
        print " Nodegroup ddl in
$ddlpath${delim}$nodegroupdef \n";
    }
    if ( $buffpooldef ne "NULL" ){
        print " Bufferpool ddl in
$ddlpath${delim}$buffpooldef \n";
    }
    print " Table ddl in $ddlpath${delim}$ddl
\n";
    print " Index ddl in
$ddlpath${delim}$indexddl\n";
    if ( $extraindex ne "no" ){
        print " Indices to create after the load
$ddlpath${delim}$extraindex\n";
    }
    if ( $loadscript eq "NULL"){
        if ( $input eq "NULL" ){
            print " Data generated by DBGEN in
$dbgen\n";
        }
        else{
            print " Data loaded from flat files in
$input\n";

```

```

    }
}
if ( $earlyindex eq "yes" ){
    print " Indexes created before loading\n";
}
else{
    print " Indexes created after loading\n";
}
if ( $addRI ne "NULL" ){
    print " RI being used from
$ddlpath${delim}$addRI\n";
}
if ( $astFile ne "NULL" ){
    print " AST being used from
$ddlpath${delim}$astFile\n";
}
if ( $loadstats eq "yes" ){
    if ( $earlyindex eq "yes" ){
        print " Statistics for tables and indexes
gathered during load\n";
    }
    else{
        if ( $runstatShort eq "NULL" ){
            print " Statistics for tables and indexes
gathered after load using $ddlpath${delim}$runstats
\n";
        }
        else{
            print " Statistics for tables and
indexes gathered after load using
$ddlpath${delim}$runstats and
$ddlpath${delim}$runstatShort\n";
        }
    }
}
else{
    if ( $runstatShort eq "NULL" ){
        print " Statistics for tables and indexes
gathered after load using $ddlpath${delim}$runstats
\n";
    }
    else{
        print " Statistics for tables and indexes
gathered after load using $ddlpath${delim}$runstats
and $ddlpath${delim}$runstatShort\n";
    }
}
if ( $loadconfigfile ne "NULL" ){
    print " Database Configuration
parameters for LOAD taken from
$ddlpath${delim}$loadconfigfile\n";
}
if ( $loadDBMconfig ne "NULL" ){
    print " Database manager Configuration
parameters for LOAD taken from
$ddlpath${delim}$loadDBMconfig\n";

```

```

    }
\   if ( $configfile ne "NULL" ){
        print " Database Configuration
parameters taken from
$ddlpath${delim}$configfile\n";
    }
    else{
        print " Database Configuration paramters
taken from
$ddlpath${delim}dss.dbconfig${sfReal}GB\n";
        $configfile="dss.dbconfig${sfReal}GB";
    }
    if ( $dbmconfig ne "NULL" ){
        print " Database Manager Configuration
parameters taken from
$ddlpath${delim}$dbmconfig\n";
    }
    else{
        print " Database Manager Configuration
paramters taken from
$ddlpath${delim}dss.dbmconfig${sfReal}GB\n";

$configfile="dss.dbmconfig${sfReal}GB";
    }
    #print " Copy image for load command
created in $copydir\n";
    if ( $log eq "yes" ){
        print " Backup files placed in
$backupdir\n";
    }
    else{
        print " No backup will be taken.\n";
    }
    print " Log retain set to $log\n";
    if ( $logDir eq "NULL" ){
        print " Log files remain in database
path\n";
    }
    else{
        print " Log file path set to $logDir\n";
    }
    if ( $logprimary eq "NULL" ){
        print " Log Primary left at default\n";
    }
    else{
        print " Log Primary set to
$logprimary\n";
    }
    if ( $logsecond eq "NULL" ){
        print " Log Second left at default\n";
    }
    else{
        print " Log second set to $logsecond\n";
    }
    }
    if ( $logfilsiz eq "NULL" ){
        print " Logfilsiz left at default\n";

```

```

    }
    else{
        print " Logfilsiz set to $logfilsiz\n";
    }
    if (($loadconfigfile eq "") || ($loadconfigfile
eq "NULL")){
        print " Machine size set to $machine so
the following configuration\n";
        print " parameters are used for load,
create index and runstats: \n";
        print " BUFFPAGE = $buffpage \n";
        print " SORTHEAP = $sortheap \n";
        print " SHEAPTHRES =
$sheapthres\n";
        print " NUM_IOSERVERS =
$ioservers\n";
        print " NUM_IOCLEANERS =
$ioclnrs\n";
        print " CHNGPGS_THRESH =
$chnngpgs\n";
        print " UTIL_HEAP_SZ =
$util_heap_sz\n";
        print " Degree of parallelism
(dft_degree and max_querydegree) set to
$smpdegree\n";
        print " Parameters for load are: temp
file = $ldtemp\n";
        print " sort buf =
$sortbuf\n";
        print " ld parallelism =
$load_parallelism\n";
        if ( $fparse eq "yes" ){
            print " FASTPARSE
used on load\n";
        }
    }
    if ( $loadscript ne "NULL"){
        print " Load commands in
$ddlpath${delim}$loadscript\n";
    }
    print " Degree of parallelism (dft_degree
and max_querydegree) set to $smpdegree\n";
    if ( $agentpri ne "NULL" ){
        print " AGENTPRI set to $agentpri\n";
    }
    if ( $activate eq "yes" ){
        print " Database will be activated when
build is complete\n";
    }
    if ( $explainDDL ne "NULL" ){
        print " EXPLAIN DDL being used from
$ddlpath${delim}$explainDDL\n";
    }
    else{
        print " EXPLAIN DDL being used from
default sqllib directory\n";

```

```

    }
}
1;

create_bufferpools

-----
-- Create Bufferpools
-----

ALTER BUFFERPOOL IBMDEFAULTBP SIZE
200;
COMMIT WORK;
CREATE BUFFERPOOL BP32K ALL NODES
SIZE 40000 PAGESIZE 32K;
COMMIT WORK;
ALTER BUFFERPOOL BP32K
NUMBLOCKPAGES 8000 BLOCKSIZE 16;
COMMIT WORK;
CREATE BUFFERPOOL BP8K ALL NODES
SIZE 36000 PAGESIZE 8K;
COMMIT WORK;
ALTER BUFFERPOOL BP8K
NUMBLOCKPAGES 7200 BLOCKSIZE 64;
COMMIT WORK;

create_indexes

-----
-- Create Indexes
-----

values(current timestamp);
ALTER TABLE TPCD.REGION ADD PRIMARY
KEY (R_REGIONKEY);
COMMIT WORK;

values(current timestamp);
ALTER TABLE TPCD.NATION ADD PRIMARY
KEY (N_NATIONKEY);
COMMIT WORK;

values(current timestamp);
ALTER TABLE TPCD.PART ADD PRIMARY
KEY (P_PARTKEY);
COMMIT WORK;

values(current timestamp);
ALTER TABLE TPCD.SUPPLIER ADD
PRIMARY KEY (S_SUPPKEY);
COMMIT WORK;

values(current timestamp);
ALTER TABLE TPCD.PARTSUPP ADD
PRIMARY KEY (PS_PARTKEY,PS_SUPPKEY);
COMMIT WORK;

```

```

values(current timestamp);
ALTER TABLE TPCD.CUSTOMER ADD
PRIMARY KEY (C_CUSTKEY);
COMMIT WORK;

values(current timestamp);
ALTER TABLE TPCD.LINEITEM ADD
PRIMARY KEY
(L_ORDERKEY,L_LINENUMBER);
COMMIT WORK;

values(current timestamp);
ALTER TABLE TPCD.ORDERS ADD PRIMARY
KEY (O_ORDERKEY);
COMMIT WORK;

values(current timestamp);
CREATE INDEX TPCD.N_RK ON
TPCD.NATION (N_REGIONKEY ASC)
PCTFREE 0 ;
commit work;

values(current timestamp);
CREATE INDEX TPCD.S_NK ON
TPCD.SUPPLIER (S_NATIONKEY ASC)
PCTFREE 0 ;
commit work;

values(current timestamp);
CREATE INDEX TPCD.PS_PK ON
TPCD.PARTSUPP (PS_PARTKEY ASC)
PCTFREE 0 ;
commit work;

values(current timestamp);
CREATE UNIQUE INDEX TPCD.PS_SKPK ON
TPCD.PARTSUPP (PS_SUPPKEY ASC,
PS_PARTKEY ASC) PCTFREE 0 ;
commit work;

values(current timestamp);
CREATE INDEX TPCD.PS_SK ON
TPCD.PARTSUPP (PS_SUPPKEY ASC)
PCTFREE 0 ;
commit work;

values(current timestamp);
CREATE INDEX TPCD.C_NK ON
TPCD.CUSTOMER (C_NATIONKEY ASC)
PCTFREE 0 ;
commit work;

values(current timestamp);

```

```

select
substr(tbname,1,10),substr(name,1,18),create_time
from sysibm.sysindexes
where tbcreator='TPCD' order by 3;
select substr(tbname,1,10),
substr(name,1,18),indextype,substr(colnames,1,40)
from sysibm.sysindexes where name like 'SQL%'
and tbcreator ='TPCD' order by 1,2;

```

### ***create\_nodegroups***

```

-----
-- Create Nodegroups
-----

```

```

CREATE NODEGROUP ng_all ON NODES (0 to
15);
CREATE NODEGROUP ng_node0 ON NODE (0);

```

```

COMMIT WORK;

```

### ***create\_tables***

```

-----
-- Create Tables
-----

```

```

CREATE TABLE TPCD.NATION (
N_NATIONKEY INTEGER NOT NULL,

        N_NAME      CHAR(25) NOT
NULL,

        N_REGIONKEY INTEGER NOT
NULL,

        N_COMMENT
VARCHAR(152) NOT NULL)
        IN SMALL_DATA;

```

```

CREATE TABLE TPCD.REGION (
R_REGIONKEY INTEGER NOT NULL,

        R_NAME      CHAR(25) NOT
NULL,

        R_COMMENT
VARCHAR(152) NOT NULL)
        IN SMALL_DATA;

```

```

CREATE TABLE TPCD.PART ( P_PARTKEY
INTEGER NOT NULL,

        P_NAME      VARCHAR(55)
NOT NULL,

        P_MFGR      CHAR(25) NOT
NULL,

        P_BRAND     CHAR(10) NOT
NULL,

        P_TYPE      VARCHAR(25) NOT
NULL,

        P_SIZE      INTEGER NOT
NULL,

        P_CONTAINER CHAR(10) NOT
NULL,

        P_RETAILPRICE FLOAT NOT
NULL,

        P_COMMENT   VARCHAR(23)
NOT NULL )
        IN DATA_INDEX
        PARTITIONING KEY(P_PARTKEY)
USING HASHING;

CREATE TABLE TPCD.SUPPLIER (
S_SUPPKEY  INTEGER NOT NULL,

        S_NAME      CHAR(25) NOT
NULL,

        S_ADDRESS   VARCHAR(40)
NOT NULL,

        S_NATIONKEY INTEGER
NOT NULL,

        S_PHONE     CHAR(15) NOT
NULL,

        S_ACCTBAL   FLOAT NOT
NULL,

        S_COMMENT
VARCHAR(101) NOT NULL)

```

<p>IN DATA_INDEX</p> <p>PARTITIONING KEY(S_SUPPKEY) USING HASHING;</p> <p>CREATE TABLE TPCD.PARTSUPP (  PS_PARTKEY INTEGER NOT NULL,    PS_SUPPKEY INTEGER NOT  NULL,    PS_AVAILQTY INTEGER  NOT NULL,    PS_SUPPLYCOST FLOAT  NOT NULL,    PS_COMMENT  VARCHAR(199) NOT NULL )    IN DATA_INDEX</p> <p>PARTITIONING KEY(PS_PARTKEY)  USING HASHING;</p> <p>CREATE TABLE TPCD.CUSTOMER (  C_CUSTKEY INTEGER NOT NULL,    C_NAME VARCHAR(25)  NOT NULL,    C_ADDRESS VARCHAR(40)  NOT NULL,    C_NATIONKEY INTEGER  NOT NULL,    C_PHONE CHAR(15) NOT  NULL,    C_ACCTBAL FLOAT NOT  NULL,    C_MKTSEGMENT CHAR(10)  NOT NULL,    C_COMMENT  VARCHAR(117) NOT NULL)    IN DATA_INDEX</p>	<p>PARTITIONING KEY(C_CUSTKEY) USING  HASHING;</p> <p>CREATE TABLE TPCD.ORDERS (  O_ORDERKEY INTEGER NOT NULL,    O_CUSTKEY INTEGER NOT  NULL,    O_ORDERSTATUS CHAR(1)  NOT NULL,    O_TOTALPRICE FLOAT NOT  NULL,    O_ORDERDATE DATE NOT  NULL,    O_ORDERPRIORITY CHAR(15)  NOT NULL,    O_CLERK CHAR(15) NOT  NULL,    O_SHIPPRIORITY INTEGER  NOT NULL,    O_COMMENT  VARCHAR(79) NOT NULL)    ORGANIZE BY (O_ORDERDATE)    IN DATA_INDEX</p> <p>PARTITIONING KEY(O_ORDERKEY)  USING HASHING;</p> <p>CREATE TABLE TPCD.LINEITEM (  L_ORDERKEY INTEGER NOT NULL,    L_PARTKEY INTEGER NOT  NULL,    L_SUPPKEY INTEGER NOT  NULL,    L_LINENUMBER INTEGER  NOT NULL,    L_QUANTITY FLOAT NOT  NULL,</p>
--	---

```

NOT NULL,      L_EXTENDEDPRICE FLOAT
NULL,          L_DISCOUNT  FLOAT NOT
NULL,          L_TAX          FLOAT NOT
NOT NULL,      L_RETURNFLAG CHAR(1)
NULL,          L_LINESTATUS CHAR(1) NOT
NULL,          L_SHIPDATE   DATE NOT
NULL,          L_COMMITDATE DATE NOT
NULL,          L_RECEIPTDATE DATE NOT
NOT NULL,      L_SHIPINSTRUCT CHAR(25)
NOT NULL,      L_SHIPMODE   CHAR(10)
VARIABLE L_COMMENT
VARIABLE(44) NOT NULL
ORGANIZE BY (L_SHIPDATE)

IN DATA_INDEX

PARTITIONING KEY(L_ORDERKEY)
USING HASHING;

COMMIT WORK;

```

***create\_tablespace***

-----  
-- Create Tablespaces  
-----

```

CREATE temporary TABLESPACE tempespace
PAGE SIZE 8K
MANAGED BY database
USING (
DEVICE '/dev/raw/raw21' 1000M,

```

```

DEVICE '/dev/raw/raw22' 1000M,
DEVICE '/dev/raw/raw23' 1000M,
DEVICE '/dev/raw/raw24' 1000M,
DEVICE '/dev/raw/raw25' 1000M,
DEVICE '/dev/raw/raw26' 1000M,
DEVICE '/dev/raw/raw27' 1000M,
DEVICE '/dev/raw/raw28' 1000M,
DEVICE '/dev/raw/raw29' 1000M,
DEVICE '/dev/raw/raw30' 1000M,
DEVICE '/dev/raw/raw31' 1000M,
DEVICE '/dev/raw/raw32' 1000M,
DEVICE '/dev/raw/raw33' 1000M,
DEVICE '/dev/raw/raw34' 1000M,
DEVICE '/dev/raw/raw35' 1000M,
DEVICE '/dev/raw/raw36' 1000M,
DEVICE '/dev/raw/raw37' 1000M,
DEVICE '/dev/raw/raw38' 1000M,
DEVICE '/dev/raw/raw39' 1000M,
DEVICE '/dev/raw/raw40' 1000M
) ON NODE (0)
USING (
DEVICE '/dev/raw/raw41' 1000M,
DEVICE '/dev/raw/raw42' 1000M,
DEVICE '/dev/raw/raw43' 1000M,
DEVICE '/dev/raw/raw44' 1000M,
DEVICE '/dev/raw/raw45' 1000M,
DEVICE '/dev/raw/raw46' 1000M,
DEVICE '/dev/raw/raw47' 1000M,
DEVICE '/dev/raw/raw48' 1000M,
DEVICE '/dev/raw/raw49' 1000M,
DEVICE '/dev/raw/raw50' 1000M,
DEVICE '/dev/raw/raw51' 1000M,
DEVICE '/dev/raw/raw52' 1000M,
DEVICE '/dev/raw/raw53' 1000M,
DEVICE '/dev/raw/raw54' 1000M,
DEVICE '/dev/raw/raw55' 1000M,
DEVICE '/dev/raw/raw56' 1000M,
DEVICE '/dev/raw/raw57' 1000M,
DEVICE '/dev/raw/raw58' 1000M,
DEVICE '/dev/raw/raw59' 1000M,
DEVICE '/dev/raw/raw60' 1000M
) ON NODE (1)
USING (
DEVICE '/dev/raw/raw21' 1000M,
DEVICE '/dev/raw/raw22' 1000M,
DEVICE '/dev/raw/raw23' 1000M,
DEVICE '/dev/raw/raw24' 1000M,
DEVICE '/dev/raw/raw25' 1000M,
DEVICE '/dev/raw/raw26' 1000M,
DEVICE '/dev/raw/raw27' 1000M,
DEVICE '/dev/raw/raw28' 1000M,
DEVICE '/dev/raw/raw29' 1000M,
DEVICE '/dev/raw/raw30' 1000M,
DEVICE '/dev/raw/raw31' 1000M,
DEVICE '/dev/raw/raw32' 1000M,
DEVICE '/dev/raw/raw33' 1000M,

```







```

DEVICE '/dev/raw/raw38' 1000M,
DEVICE '/dev/raw/raw39' 1000M,
DEVICE '/dev/raw/raw40' 1000M
) ON NODE (12)
USING (
  DEVICE '/dev/raw/raw41' 1000M,
  DEVICE '/dev/raw/raw42' 1000M,
  DEVICE '/dev/raw/raw43' 1000M,
  DEVICE '/dev/raw/raw44' 1000M,
  DEVICE '/dev/raw/raw45' 1000M,
  DEVICE '/dev/raw/raw46' 1000M,
  DEVICE '/dev/raw/raw47' 1000M,
  DEVICE '/dev/raw/raw48' 1000M,
  DEVICE '/dev/raw/raw49' 1000M,
  DEVICE '/dev/raw/raw50' 1000M,
  DEVICE '/dev/raw/raw51' 1000M,
  DEVICE '/dev/raw/raw52' 1000M,
  DEVICE '/dev/raw/raw53' 1000M,
  DEVICE '/dev/raw/raw54' 1000M,
  DEVICE '/dev/raw/raw55' 1000M,
  DEVICE '/dev/raw/raw56' 1000M,
  DEVICE '/dev/raw/raw57' 1000M,
  DEVICE '/dev/raw/raw58' 1000M,
  DEVICE '/dev/raw/raw59' 1000M,
  DEVICE '/dev/raw/raw60' 1000M
) ON NODE (13)
USING (
  DEVICE '/dev/raw/raw21' 1000M,
  DEVICE '/dev/raw/raw22' 1000M,
  DEVICE '/dev/raw/raw23' 1000M,
  DEVICE '/dev/raw/raw24' 1000M,
  DEVICE '/dev/raw/raw25' 1000M,
  DEVICE '/dev/raw/raw26' 1000M,
  DEVICE '/dev/raw/raw27' 1000M,
  DEVICE '/dev/raw/raw28' 1000M,
  DEVICE '/dev/raw/raw29' 1000M,
  DEVICE '/dev/raw/raw30' 1000M,
  DEVICE '/dev/raw/raw31' 1000M,
  DEVICE '/dev/raw/raw32' 1000M,
  DEVICE '/dev/raw/raw33' 1000M,
  DEVICE '/dev/raw/raw34' 1000M,
  DEVICE '/dev/raw/raw35' 1000M,
  DEVICE '/dev/raw/raw36' 1000M,
  DEVICE '/dev/raw/raw37' 1000M,
  DEVICE '/dev/raw/raw38' 1000M,
  DEVICE '/dev/raw/raw39' 1000M,
  DEVICE '/dev/raw/raw40' 1000M
) ON NODE (14)
USING (
  DEVICE '/dev/raw/raw41' 1000M,
  DEVICE '/dev/raw/raw42' 1000M,
  DEVICE '/dev/raw/raw43' 1000M,
  DEVICE '/dev/raw/raw44' 1000M,
  DEVICE '/dev/raw/raw45' 1000M,
  DEVICE '/dev/raw/raw46' 1000M,
  DEVICE '/dev/raw/raw47' 1000M,

```

```

DEVICE '/dev/raw/raw48' 1000M,
DEVICE '/dev/raw/raw49' 1000M,
DEVICE '/dev/raw/raw50' 1000M,
DEVICE '/dev/raw/raw51' 1000M,
DEVICE '/dev/raw/raw52' 1000M,
DEVICE '/dev/raw/raw53' 1000M,
DEVICE '/dev/raw/raw54' 1000M,
DEVICE '/dev/raw/raw55' 1000M,
DEVICE '/dev/raw/raw56' 1000M,
DEVICE '/dev/raw/raw57' 1000M,
DEVICE '/dev/raw/raw58' 1000M,
DEVICE '/dev/raw/raw59' 1000M,
DEVICE '/dev/raw/raw60' 1000M
) ON NODE (15)
BUFFERPOOL BP8K
EXTENTSIZE 64
PREFETCHSIZE 384
OVERHEAD 5.7
TRANSFERRATE .61;
COMMIT WORK;

CREATE regular TABLESPACE small_data
  IN NODEGROUP ng_node0
  PAGESIZE 4K
  MANAGED BY system
USING (
  '/data/small_data'
)
  BUFFERPOOL ibmdefaultbp
  OVERHEAD 25
  TRANSFERRATE .3;
COMMIT WORK;

CREATE regular TABLESPACE data_index
  IN NODEGROUP ng_all
  PAGESIZE 32K
  MANAGED BY database
USING (
  DEVICE '/dev/raw/raw1' 1000M,
  DEVICE '/dev/raw/raw2' 1000M,
  DEVICE '/dev/raw/raw3' 1000M,
  DEVICE '/dev/raw/raw4' 1000M,
  DEVICE '/dev/raw/raw5' 1000M,
  DEVICE '/dev/raw/raw6' 1000M,
  DEVICE '/dev/raw/raw7' 1000M,
  DEVICE '/dev/raw/raw8' 1000M,
  DEVICE '/dev/raw/raw9' 1000M,
  DEVICE '/dev/raw/raw10' 1000M
) ON NODE (0)
USING (
  DEVICE '/dev/raw/raw11' 1000M,
  DEVICE '/dev/raw/raw12' 1000M,
  DEVICE '/dev/raw/raw13' 1000M,
  DEVICE '/dev/raw/raw14' 1000M,
  DEVICE '/dev/raw/raw15' 1000M,
  DEVICE '/dev/raw/raw16' 1000M,

```



```

) ON NODE (10)
USING (
  DEVICE '/dev/raw/raw11' 1000M,
  DEVICE '/dev/raw/raw12' 1000M,
  DEVICE '/dev/raw/raw13' 1000M,
  DEVICE '/dev/raw/raw14' 1000M,
  DEVICE '/dev/raw/raw15' 1000M,
  DEVICE '/dev/raw/raw16' 1000M,
  DEVICE '/dev/raw/raw17' 1000M,
  DEVICE '/dev/raw/raw18' 1000M,
  DEVICE '/dev/raw/raw19' 1000M,
  DEVICE '/dev/raw/raw20' 1000M
) ON NODE (11)
USING (
  DEVICE '/dev/raw/raw1' 1000M,
  DEVICE '/dev/raw/raw2' 1000M,
  DEVICE '/dev/raw/raw3' 1000M,
  DEVICE '/dev/raw/raw4' 1000M,
  DEVICE '/dev/raw/raw5' 1000M,
  DEVICE '/dev/raw/raw6' 1000M,
  DEVICE '/dev/raw/raw7' 1000M,
  DEVICE '/dev/raw/raw8' 1000M,
  DEVICE '/dev/raw/raw9' 1000M,
  DEVICE '/dev/raw/raw10' 1000M
) ON NODE (12)
USING (
  DEVICE '/dev/raw/raw11' 1000M,
  DEVICE '/dev/raw/raw12' 1000M,
  DEVICE '/dev/raw/raw13' 1000M,
  DEVICE '/dev/raw/raw14' 1000M,
  DEVICE '/dev/raw/raw15' 1000M,
  DEVICE '/dev/raw/raw16' 1000M,
  DEVICE '/dev/raw/raw17' 1000M,
  DEVICE '/dev/raw/raw18' 1000M,
  DEVICE '/dev/raw/raw19' 1000M,
  DEVICE '/dev/raw/raw20' 1000M
) ON NODE (13)
USING (
  DEVICE '/dev/raw/raw1' 1000M,
  DEVICE '/dev/raw/raw2' 1000M,
  DEVICE '/dev/raw/raw3' 1000M,
  DEVICE '/dev/raw/raw4' 1000M,
  DEVICE '/dev/raw/raw5' 1000M,
  DEVICE '/dev/raw/raw6' 1000M,
  DEVICE '/dev/raw/raw7' 1000M,
  DEVICE '/dev/raw/raw8' 1000M,
  DEVICE '/dev/raw/raw9' 1000M,
  DEVICE '/dev/raw/raw10' 1000M
) ON NODE (14)
USING (
  DEVICE '/dev/raw/raw11' 1000M,
  DEVICE '/dev/raw/raw12' 1000M,
  DEVICE '/dev/raw/raw13' 1000M,
  DEVICE '/dev/raw/raw14' 1000M,
  DEVICE '/dev/raw/raw15' 1000M,
  DEVICE '/dev/raw/raw16' 1000M,

```

```

  DEVICE '/dev/raw/raw17' 1000M,
  DEVICE '/dev/raw/raw18' 1000M,
  DEVICE '/dev/raw/raw19' 1000M,
  DEVICE '/dev/raw/raw20' 1000M

```

```

) ON NODE (15)
BUFFERPOOL BP32K
EXTENTSIZ 16
PREFETCHSIZE 160
OVERHEAD 25
TRANSFERRATE .3;
COMMIT WORK;

```

### *createufbtl*

```

-----
-- Create Update Function Tables
-----

```

```

CREATE TABLE TPCDTEMP.ORDERS_NEW (
  APP_ID INTEGER NOT NULL,
                O_ORDERKEY   INTEGER
NOT NULL,
                O_CUSTKEY   INTEGER NOT
NULL,
                O_ORDERSTATUS CHAR(1)
NOT NULL,
                O_TOTALPRICE  FLOAT NOT
NULL,
                O_ORDERDATE   DATE NOT
NULL,
                O_ORDERPRIORITY CHAR(15)
NOT NULL,
                O_CLERK       CHAR(15) NOT
NULL,
                O_SHIPPRIORITY INTEGER
NOT NULL,
                O_COMMENT
VARCHAR(79) NOT NULL WITH DEFAULT)
  PARTITIONING KEY (O_ORDERKEY)
  IN DATA_INDEX;

```

```

CREATE TABLE TPCDTEMP.ORDERS_DEL (
  APP_ID INTEGER NOT NULL,
                O_ORDERKEY   INTEGER
NOT NULL)
  PARTITIONING KEY (O_ORDERKEY)
  IN DATA_INDEX;

```

```

CREATE TABLE TPCDTEMP.LINEITEM_NEW (
  APP_ID INTEGER NOT NULL,
                L_ORDERKEY   INTEGER
NOT NULL,
                L_PARTKEY   INTEGER NOT
NULL,
                L_SUPPKEY   INTEGER NOT
NULL,

```

```

                L_LINENUMBER INTEGER
NOT NULL,
                L_QUANTITY  FLOAT NOT
NULL,
                L_EXTENDEDPRICE FLOAT
NOT NULL,
                L_DISCOUNT  FLOAT NOT
NULL,
                L_TAX        FLOAT NOT
NULL,
                L_RETURNFLAG CHAR(1)
NOT NULL,
                L_LINESTATUS CHAR(1) NOT
NULL,
                L_SHIPDATE   DATE NOT
NULL,
                L_COMMITDATE DATE NOT
NULL,
                L_RECEIPTDATE DATE NOT
NULL,
                L_SHIPINSTRUCT CHAR(25)
NOT NULL,
                L_SHIPMODE   CHAR(10)
NOT NULL,
                L_COMMENT
VARCHAR(44) NOT NULL WITH DEFAULT)
PARTITIONING KEY (L_ORDERKEY)
IN DATA_INDEX;

CREATE INDEX TPCDTEMP.I_ORDERS_NEW
ON TPCDTEMP.ORDERS_NEW
( APP_ID,
O_ORDERKEY,
O_CUSTKEY,
O_ORDERSTATUS,
O_TOTALPRICE,
O_ORDERDATE,
O_ORDERPRIORITY,
O_CLERK,
O_SHIPPRIORITY,
O_COMMENT);

CREATE INDEX
TPCDTEMP.I_LINEITEM_NEW ON
TPCDTEMP.LINEITEM_NEW (APP_ID);

CREATE UNIQUE INDEX
TPCDTEMP.I_ORDERS_DEL ON
TPCDTEMP.ORDERS_DEL
(APP_ID, O_ORDERKEY);

```

COMMIT WORK;

**db2nodes.cfg**

```

0 maguro01 0
1 maguro01 1
2 maguro02 0
3 maguro02 1
4 maguro03 0
5 maguro03 1
6 maguro04 0
7 maguro04 1
8 maguro05 0
9 maguro05 1
10 maguro06 0
11 maguro06 1
12 maguro07 0
13 maguro07 1
14 maguro08 0
15 maguro08 1

```

**load\_db2set.ksh**

```

#!/bin/ksh
db2set DB2OPTIONS="-t -v +c"
db2set DB2_EXTENDED_OPTIMIZATION=Y
db2set DB2_ANTIJOIN=Y
db2set DB2BQTRY=120
db2set DB2RQTIME=30
db2set DB2BPVARS=/home/tpch/custom/bpvar.cfg
db2set DB2_FORCE_FCM_BP=ON
db2set DB2_PARALLEL_IO="*"

```

**run\_db2set.ksh**

```

#!/bin/ksh
db2set DB2OPTIONS="-t -v +c"
db2set DB2_EXTENDED_OPTIMIZATION=Y
db2set DB2_ANTIJOIN=Y
db2set DB2BQTRY=120
db2set DB2RQTIME=30
db2set DB2BPVARS=/home/tpch/custom/bpvar.cfg
db2set DB2_FORCE_FCM_BP=ON
db2set DB2_PARALLEL_IO="*"

```

**runstats.ddl**

```

RUNSTATS ON TABLE TPCD.NATION WITH
DISTRIBUTION on all columns
and columns (
n_name like statistics,
n_comment like statistics )
AND detailed INDEXES ALL;
commit;
RUNSTATS ON TABLE TPCD.REGION WITH
DISTRIBUTION on all columns
and columns (
r_name like statistics,

```

```

    r_comment like statistics )
    AND detailed INDEXES ALL;
commit;
RUNSTATS ON TABLE TPCD.SUPPLIER WITH
DISTRIBUTION on all columns
    and columns (
        s_name like statistics,
        s_address like statistics,
        s_phone like statistics,
        s_comment like statistics)
    AND detailed INDEXES ALL;
commit;
RUNSTATS ON TABLE TPCD.PART    WITH
DISTRIBUTION on all columns
    and columns (
        p_name like statistics,
        p_mfgr like statistics,
        p_brand like statistics,
        p_type like statistics,
        p_container like statistics,
        p_comment like statistics)
    AND detailed INDEXES ALL;
commit;
RUNSTATS ON TABLE TPCD.PARTSUPP
WITH DISTRIBUTION on all columns
    and columns (
        ps_comment like statistics)
    AND detailed INDEXES ALL;
commit;
RUNSTATS ON TABLE TPCD.CUSTOMER
WITH DISTRIBUTION on all columns
    and columns (
        c_name like statistics,
        c_address like statistics,
        c_phone like statistics,
        c_mktsegment like statistics,
        c_comment like statistics)
    AND detailed INDEXES ALL;
commit;
RUNSTATS ON TABLE TPCD.ORDERS    WITH
DISTRIBUTION on all columns
    and columns (
        o_orderstatus like statistics,
        o_orderpriority like statistics,
        o_clerk like statistics,
        o_comment like statistics)
    AND detailed INDEXES ALL;
commit;
RUNSTATS ON TABLE TPCD.LINEITEM WITH
DISTRIBUTION on all columns
    and columns (
        l_returnflag like statistics,
        l_linestatus like statistics,
        l_shipinstruct like statistics,
        l_shipmode like statistics,
        l_comment like statistics)

```

```

    AND detailed INDEXES ALL;
    COMMIT WORK;
load_tables.ksh

#!/bin/ksh
messages=${TPCD_TMP_DIR}
rawdata=${TPCD_INPUT}
custom=${TPCD_DDL_PATH}

echo "Load Summary Time: " >
${messages}/loadstatus.out

# Nation and Region are loaded into the current
node

db2 connect to tpcd;

echo "Loading Nation at "`date` >>
${messages}/loadstatus.out
db2 "load from ${rawdata}/nation.tbl of del
modified by coldel| fastparse nohead
er messages ${messages}/nation.msg replace into
TPCD.NATION nonrecoverable"

echo "Loading Region at "`date` >>
${messages}/loadstatus.out
db2 "load from ${rawdata}/region.tbl of del
modified by coldel| fastparse nohead
er messages ${messages}/region.msg replace into
TPCD.REGION nonrecoverable"

echo "Loading Partsupp at "`date` >>
${messages}/loadstatus.out
db2 -tvf ${custom}/load_tb_partsupp.ddl
#
echo "Loading Orders at "`date` >>
${messages}/loadstatus.out
db2 -tvf ${custom}/load_tb_orders.ddl
#
echo "Loading Lineitem at "`date` >>
${messages}/loadstatus.out
db2 -tvf ${custom}/load_tb_lineitem.ddl
#
echo "Loading Customer at "`date` >>
${messages}/loadstatus.out
db2 -tvf ${custom}/load_tb_customer.ddl
#
echo "Loading Part at "`date` >>
${messages}/loadstatus.out
db2 -tvf ${custom}/load_tb_part.ddl
#
echo "Loading Supplier at "`date` >>
${messages}/loadstatus.out
db2 -tvf ${custom}/load_tb_supplier.ddl

```

```

#
db2 commit;
db2 terminate;

echo "Finished Loading at ``date` >>
${messages}/loadstatus.out
echo "-----" >>
${messages}/loadstatus.out

#echo "Starting Sanity Chequing at ``date` >>
${messages}/loadstatus.out
db2 terminate;

echo "Finished Loading at ``date` >>
${messages}/loadstatus.out
echo "-----" >>
${messages}/loadstatus.out

#echo "Starting Sanity Chequing at ``date` >>
${messages}/loadstatus.out
#db2 connect to tpcd;
#db2 "select count_big(*) as lineitem from
tpcd.lineitem" >> ${messages}/loadsta
tus.out
#db2 "select count_big(*) as orders from
tpcd.orders" >> ${messages}/loadstatus.
out
#db2 "select count_big(*) as partsupp from
tpcd.partsupp" >> ${messages}/loadsta
tus.out
#db2 "select count_big(*) as customer from
tpcd.customer" >> ${messages}/loadsta
tus.out
#db2 "select count_big(*) as part from tpcd.part" >>
${messages}/loadstatus.out
#db2 "select count_big(*) as supplier from
tpcd.supplier" >> ${messages}/loadsta
tus.out
#db2 "select count(*) as nation from tpcd.nation" >>
${messages}/loadstatus.out
#db2 "select count(*) as region from tpcd.region" >>
${messages}/loadstatus.out
#db2 terminate;
#echo "Finish Sanity Chequing at ``date` >>
${messages}/loadstatus.out

```

### ***load\_tb\_customer.ddl***

```

load from
  customer.tbl
of del
modified by coldel|
fastparse

```

```

messages /home/tpch/tmp/customer.msg
replace into TPCD.CUSTOMER
nonrecoverable
partitioned db config mode load_only
part_file_location /data
;

```

### ***load\_tb\_lineitem.ddl***

```

load from
  lineitem.tbl
of del
modified by coldel|
fastparse
  messages /home/tpch/tmp/lineitem.msg
replace into TPCD.LINEITEM
nonrecoverable
partitioned db config mode load_only
part_file_location /data
;

```

### ***load\_tb\_orders.ddl***

```

load from
  orders.tbl
of del
modified by coldel|
fastparse
  messages /home/tpch/tmp/orders.msg
replace into TPCD.ORDERS
nonrecoverable
partitioned db config mode load_only
part_file_location /data
;

```

### ***load\_tb\_part.ddl***

```

load from
  part.tbl
of del
modified by coldel|
fastparse
  messages /home/tpch/tmp/part.msg
replace into TPCD.PART
nonrecoverable
partitioned db config mode load_only
part_file_location /data
;

```

### ***load\_tb\_partsupp.ddl***

```

load from
  partsupp.tbl
of del

```

```

modified by coldel|
    fastparse
    messages /home/tpch/tmp/partsupp.msg
replace into TPCD.PARTSUPP
nonrecoverable
partitioned db config mode load_only
part_file_location /data
;

```

### ***load\_tb\_supplier.ddl***

```

load from /data/supplier.tbl
of del
modified by coldel|
    fastparse
    messages /home/tpch/tmp/supplier.msg
replace into TPCD.SUPPLIER
nonrecoverable
CPU_PARALLELISM 4
;

```

### ***load\_dbcfg.ddl***

```

UPDATE DB CFG FOR TPCD USING DBHEAP
15000 SORTHEAP 25000 SHEAPTHRES_SHR 0
APPGROUP_MEM_SZ 2000 DFT_QUERYOPT 7
DFT_DEGREE 4 NUM_FREQVALUES 0
NUM_QUANTILES 600 LOCKLIST 16384
MAXLOCKS 60 CHNGPGS_THRESH 15
NUM_IOCLEANERS 20 NUM_IOSERVERS 20
MAXFILOP 1024 NEWLOGPATH /home/logs
LOGFILSIZ 10000 LOGPRIMARY 10
LOGSECOND 10 SOFTMAX 750
DATABASE_MEMORY AUTOMATIC
UTIL_HEAP_SZ 50000
;

```

### ***load\_dbmcfg.ddl***

```

UPDATE DBM CFG USING
CPUSPEED -1
SHEAPTHRES 150000
MAX_QUERYDEGREE ANY
INTRA_PARALLEL NO
SVCENAME xtpch
NUMDB 1
MAX_TIME_DIFF 1440
DFT_MON_TIMESTAMP OFF
DIAGLEVEL 0
NOTIFYLEVEL 0
;

```

### ***run\_dbcfg.ddl***

```

UPDATE DB CFG FOR TPCD USING DBHEAP
10000 SORTHEAP 20000 SHEAPTHRES_SHR
250 DATABASE_MEMORY automatic
UTIL_HEAP_SZ 5000 DFT_QUERYOPT 7
DFT_DEGREE 1 NUM_FREQVALUES 0
NUM_QUANTILES 300 LOCKLIST 40000
MAXLOCKS 20 CHNGPGS_THRESH 60
NUM_IOCLEANERS 4 NUM_IOSERVERS 4
MAXFILOP 1024 LOGFILSIZ 50000
LOGPRIMARY 4 LOGSECOND 1 SOFTMAX 360
LOGBUFSZ 2048 MINCOMMIT 2 APPLHEAPSZ
1024 STMTHEAP 10000
;

```

### ***run\_dbmcfg.ddl***

```

UPDATE DBM CFG USING
HEALTH_MON OFF
SHEAPTHRES 500000
MAX_QUERYDEGREE ANY
INTRA_PARALLEL NO
FCM_NUM_BUFFERS 16384
FCM_NUM_RQB 4096
NUM_POOLAGENTS 64
NUM_INITAGENTS 4
JAVA_HEAP_SZ 2048
CONN_ELAPSE 20
DFT_MON_TIMESTAMP OFF
CPUSPEED 2.715979e-07
;

```

### ***change\_logs.ksh***

```

#!/usr/bin/ksh

db2_all "<<<+0< db2 update db cfg for tpcd using
newlogpath /dev/raw/raw61"
db2_all "<<<+1< db2 update db cfg for tpcd using
newlogpath /dev/raw/raw62"
db2_all "<<<+2< db2 update db cfg for tpcd using
newlogpath /dev/raw/raw61"
db2_all "<<<+3< db2 update db cfg for tpcd using
newlogpath /dev/raw/raw62"
db2_all "<<<+4< db2 update db cfg for tpcd using
newlogpath /dev/raw/raw61"
db2_all "<<<+5< db2 update db cfg for tpcd using
newlogpath /dev/raw/raw62"
db2_all "<<<+6< db2 update db cfg for tpcd using
newlogpath /dev/raw/raw61"
db2_all "<<<+7< db2 update db cfg for tpcd using
newlogpath /dev/raw/raw62"
db2_all "<<<+8< db2 update db cfg for tpcd using
newlogpath /dev/raw/raw61"
db2_all "<<<+9< db2 update db cfg for tpcd using
newlogpath /dev/raw/raw62"

```



```

db2_all "<<<+10< db2 update db cfg for tpcd using
newlogpath /dev/raw/raw61"
db2_all "<<<+11< db2 update db cfg for tpcd using
newlogpath /dev/raw/raw62"
db2_all "<<<+12< db2 update db cfg for tpcd using
newlogpath /dev/raw/raw61"
db2_all "<<<+13< db2 update db cfg for tpcd using
newlogpath /dev/raw/raw62"
db2_all "<<<+14< db2 update db cfg for tpcd using
newlogpath /dev/raw/raw61"
db2_all "<<<+15< db2 update db cfg for tpcd using
newlogpath /dev/raw/raw62"

```

### ***tpcd.setup***

```

# NOTE: ALL variable defitions must have a
comment at the end - haven't got
# the getvars script recognizing the
uncommented line yet
TPCD_PLATFORM=linux          # aix, nt, sun
....
TPCD_VERSION=2               # 1 or 2
(Version of tpcd). Default 1
TPCD_DBNAME=TPCD            # name to
create database under
TPCD_WORKLOAD=H              # TPC
version (R for TPCR, H for TPCH)
TPCD_AUDIT_DIR=/home/tpch/tpcd # top
level directory of tar file for
# all the tpcd scripts
TPCD_PRODUCT=v5              # v5 or pe
# Use pe if you really are
using pe v1.2!
# but I won't guarantee that
it will work!
TPCD_MODE=mpp                #
uni/smp/mln/mpp
TPCD_PHYS_NODE=8             # number of
physical nodes
TPCD_LN_PER_PN=2             # number of
logical nodes per physical node
TPCD_SF=100                  # size of the
database (1=1GB,...) to
# get test size databases use:
# 0.012 = 12MB
# 0.1 = 100MB
TPCD_BUILD_STAGE=ALL         # where
to start the build - currently the
# following is possible:
# ALL - do everything
(create,load,
# index,stats,config)
(Default)
# CRTTBSP - start after
create db and

```

```

# config setting. Start
right at
# create tbsp
# LOAD - start from the
load of the tables
# INDEX - start from the
index creation
# (NOTE if earlyindex
is specified,
# then this will do the
create index
# followed by the
load...)
# RUNSTATS - start from
the runstats
# (NOTE Do not use
this option if
# distribution stats are
gathered
# as part of the load,
this will
# start after the load and
indices
# have been created.
# CONFIG - start from the
setting up of
# the benchmark runs
config setup
#
TPCD_DBPATH=/data/dbpath    # path for
database (defaults to home)
TPCD_DDLPATH=/home/tpch/custom # path
for all ddl files and customized
# scripts (load script),
config files,etc
TPCD_BUFFERPOOL_DEF=create_bufferpools.dd
l # name of file with bufferpool definitions
# and sizes
TPCD_NODEGROUP_DEF=create_nodegroups.dd
l # name of file in ddlpath with nodegroup
# definitions
TPCD_EXPLAIN_DDL=NULL       # file
with DDL for explains statments
# if this is NULL then uses
the default
# and puts it in
USERSPACE1 across all
# nodes...nt 1TB found it
was faster if
# just in a single node
nodegroup
TPCD_TBSP_DDL=create_tablespaces.ddl # ddl
file for tablespaces
TPCD_DDL=create_tables.ddl   # ddl file for
tables

```

TPCD_QUAL_TBSP_DDL=create_tablespaces_qual.ddl # ddl file for tablespaces for qual	# work on UNI successfully
TPCD_QUAL_DDL=create_tables.ddl # ddl file for qualification database	# ddl file for short runstats
# tablespaces and tables	
should be identical	# run in the background
# to regular ddl except	# TPCD_RUNSTATS are
container names	# of the build. If this is
TPCD_INDEXDDL=create_indexes.ddl # ddl file for indexes	used, then
TPCD_EXTRAINDEX=no # no = no extra indexes	# TPCD_RUNSTATS
# filename = If you want to	should have the runstats
create some	# command for lineitem and
# indices before	#
# the load, and some indices	TPCD_RUNSTATSHORT should have runstats
after, then	# commands for all other
# use this additional file to	tables.
specify the	TPCD_DBGEN=/home/tpch/tpcd/appendix.v2/dbgen # path name to data generation code
TPCD_ADD_RI=NULL # file name that contains any RI	# Parameters used to specify
# constraints to add after	source of
index creation	# data for load scripts
unused	TPCD_INPUT=/data # NULL - use dbgen generated data OR
load.	# path name - to the pre-generated
TPCD_AST=NULL # file name that contains complete AST	# flat files
# definition including	#
connection to	TPCD_QUAL_INPUT=NULL # NULL - use dbgen generated data OR
table creation,	# path name - to the pre-generated
# population, indexing and	# flat files
runstats.	TPCD_TAILOR_DIR=/home/tpch/tpcd/tailor
TPCD_RUNSTATS=runstats.ddl # ddl file for runstats. If you have	# path name for the directory used to
# created indices before the	# generate split specific
load (ie	config files
#	# only used for partitioned
TPCD_EARLYINDEX=yes), have specified to	environment
# gather stats on the load	TPCD_EARLYINDEX=no # create
command (either	indexes before the load
# through your own load	
script or by using	# LOAD specific
#	parameters follow:
TPCD_LOADSTATS=yes, AND you have	TPCD_LOAD_DB2SET_SCRIPT=NULL #
# specified a file for	Script that contains the db2set commands
TPCD_EXTRAINDEX	# for the load process Use
# then this runstats file	NULL if not
should include	# specified
# the runstats commands	TPCD_LOAD_CONFIGFILE=load_dbcfg.ddl
specifically for	#config file with specific database config
# the extra indices.	# parms for the
TPCD_RUNSTATSHORT=NULL #	load/index/runstats part
NOTE!! THIS IS BUGGY....I can't get it to	# of the build.

	# set to NULL if use	TPCD_BACKUP_DIR=/home/tpch/tpcd/backupdir
defaults		# directory where backup files are placed
TPCD_LOAD_DBM_CONFIGFILE=load_dbmcfg.ddl	# config file with specific database manager	TPCD_LOGPRIMARY=NULL #
config parts for the	# load/index/runstats part	NULL/value = how many primary log files
of the build.		# to configure. If NULL is specified then
	# set to NULL if use	# the default is not changed.
defaults		TPCD_LOGFILSIZ=NULL #
TPCD_LOAD_QUALCONFIGFILE=load_dbcfg.ddl	# config file with specific database config	NULL/value = how 4KB pages to use for
dl # config file with specific database config	# parms for the	# logfilsiz db cfg parameter.
load/index/runstats part	# of the build for	If NULL is
qualification db.		# specified then the default is not changed
	# set to NULL if use	TPCD_LOGSECOND=NULL #
defaults		NULL/value = how many secondary log files
TPCD_LOAD_DBM_QUALCONFIGFILE=load_dbmcfg.ddl	# config file with specific database manager config	# to configure. If NULL is specified then
parts for the	# load/index/runstats part of	# the default is not changed.
the build.		TPCD_LOG_DIR=NULL # directory where log files stored..
	# set to NULL if use	# NULL leaves them in the dbpath
defaults		TPCD_LOG_QUAL_DIR=/home/logs #
TPCD_LOADSTATS=no	# gather	directory where qual log files stored
statistics during load		# NULL leaves them in the dbpath
	# ignored if EARLYINDEX	TPCD_LOG=no # yes/no - whether to turn LOG_RETAIN on
is not set		# i.e. are backups needed to be taken
	# due to runstats limitation	
TPCD_TEMP=/tmp/tpch	# path for LOAD temp files	# CONFIG specific
		parameters
	# used in load script only	TPCD_DB2SET_SCRIPT=run_db2set.ksh #
TPCD_SORTBUF=4096	# sortbuf size for LOAD	Script that contains the db2set commands
		# for the benchmark run.
	# used in load script only	Use NULL if not
TPCD_LOAD_PARALLELISM=0	# degree of parallelism to use on load	# specified
degree of parallelism to use on load	# 0 = use the "intelligent default" that	TPCD_CONFIGFILE=run_dbcfg.ddl # name of configuration file in ddl path
		# that will be used for the benchmark run
	# the load will chose at run time	TPCD_DBM_CONFIG=run_dbmcfg.ddl #
		name of config file for database manager
	# used in load script only	# cfg parms
TPCD_COPY_DIR=NULL	# directory where copy image is created	TPCD_QUALCONFIGFILE=run_dbcfg.ddl #
		name of database cfg file in ddl path
	# used in load script only	# for qualification database
CURRENTLY UNUSED		TPCD_DBM_QUALCONFIG=run_dbmcfg.ddl #
	# used in load script only	name of config file for database
TPCD_FASTPARSE=yes	# use fastparse on load	# manager cfg parms
	# used in load script only	
		TPCD_MACHINE=small # set to NULL if using load config file
	# Backup and logfile specific parameters follow:	

machine used to	# big/medium/small size of	TPCD_QUAL_DBNAME=TPCDQUAL	#
sortheap, sheapthres	# determine buffpage,	TPCD_NUMSTREAM=5	# number of
load, create	# and ioservers parms for	TPCD_FLATFILES=/home/ufdata	# where
is ignored if	# index and runstats		# for update functions
TPCD_LOAD_CONFIGFILE is specified	# NOTE that this parameter	TPCD_STAGING_TABLE_DDL=create_UFtables.ddl	# script that contains the ddl for creating
	# a		# the staging tables if
			they are used for
			# the update functions
TPCD_SMPDEGREE=1	# 1...# of	TPCD_PRELOAD_STAGING_TABLE_SCRIPT=preloadUF.ksh	# file that contains the sql for
degrees of parallelism to run	# with		preloading
TPCD_AGENTPRI=NULL	# set		# and gathering stats
agentpri to this value (default	# is SYSTEM)		on sample UF data
			# Note that the data
TPCD_ACTIVATE=no	# activate the		used is sample data
database upon build	# completion		# and is not data
			from any of the applied
			# update pairs
	# run specific parameters	TPCD_DELETE_STAGING_TABLE_SQL=remove_UFtables.ddl	# file that contains the sql for
TPCD_AUDIT=no	# no/yes		deleting
qualification db stuff	# no - don't set up		# the preloaded
db queries	# yes - set up qualification		data from the staging
function tables	# - build the update		# tables
into the	# and data before we get	TPCD_UPDATE_IMPORT=false	# true =
of the	# timing of the creation		use import for the staging tables
	# tables and the load.		# for UNI/SMP mode only
TPCD_TMP_DIR=/tmp/tpch	# place to		(code change in
put temp working files			# tpcdbatch) (if not uni
			mode then must
			# change load_update)
			# false = use load for
			staging tables
			# The default is false if not
			set.
			# NOTE that this parm is
			only for UNI/SMP
			# it is not for multi node
TPCD_SHARED_TEMP_FULL_PATHNAME=/home/tpch/sql/lib/tmp	# just added		invocation
TPCD_QUERY_TEMPLATE_DIR=standard.V2	# subdirectory in AUDIT_DIR/queries		
query	# to use as the source of the	TPCD_SPLIT_UPDATES=64	# number
are	# templates. Currently there		of chunks to split the update
can make	# v2 ones and pe ones. You		# function into.
following the same	# your own directory	TPCD_CONCURRENT_INSERTS=8	#
using	# form as in the v2 directory		number of insert chunks that are run
	# any variant you wish		# concurrently.
		TPCD_SPLIT_UPDATES	
			# should be evenly divisible
			by this number
		TPCD_CONCURRENT_INSERTS_LOAD=4	
			# number of insert chunks that are loaded

<p>TPCD_SPLIT_UPDATES should number. portion of the partitioned databases TPCD_CONCURRENT_DELETES=8 TPCD_SPLIT_DELETES=64 in UNI/SMP TPCD_GEN_UPDATEPAIRS=12 generation and use this if update functions not yet) TPCD_GENERATE_SEED_FILE=yes substitution values base on audited runs) seeds throughput starting at same node interval for vmstats/iostats interval for vmstats/iostats for TPCD_GATHER_STATS=off only implement for AIX yet around power (vmstat,iostat,netstat)</p>	<p># concurrently. # be evenly divisible by this # this controls the load # insert routine for # function into. # this variable is only valid # mode. # to generate # if 0 the update data # setup will not be done. # you don't want to run the # functions (Update # fully tested in new env't # generating the query # yes - generate a seed file # year/month/day (for # no - use qgen's default # query stream of # different nodes or from # timing # timing # throughput run # on/off - # on = gather statistics # test run</p>
<p>TPCD_UFTEMP=DATA_INDEX name of tablespace(s) where the update functions the tablespaces...eg TPCD_HAVECOMPILER=yes TPCD_SLEEP=5 TPCD_INLISTMAX=default default. TPCD_LOAD_SCRIPT=load_tables.ksh directory under mln/mpp default genloaduni TPCD_LOAD_SCRIPT_QUAL=NULL script to run for loading tables in directory under mln/mpp TPCD_ROOTPRIV=no root privileges to be able schedtune AIX only) information # directory wehre the db2diag.log can tests TPCD_APPEND_ON=no</p>	<p># off = no stats gathered # base # staging tables for the # are created # this name will be used as # basename for the # UFTEMP1 UFTEMP2 .... # rebuild # yes/no # ? # max num # for UF2, use "default" for # script # in TPCD_DDLPTH # leave as NULL if using # TPCD_DDLPTH # for QUAL db # do you have # get values of things like # and vmtune (currently on # acid test specific # be found for the durability # set to no if the cluster indexes are used</p>

## Appendix C: Qualification Query Output

### Qualification Queries

#### Query 1

Start timestamp 07/16/03 21:53:47.750000

-----

-- Query 01 - Var\_0 Rev\_01 - Pricing Summary Report Query

Tag: Q1 Stream: -1 Sequence number: 17

```
select
l_returnflag,
l_linestatus,
sum(l_quantity) as sum_qty,
sum(l_extendedprice) as sum_base_price,
sum(l_extendedprice * (1 - l_discount)) as
sum_disc_price,
sum(l_extendedprice * (1 - l_discount) * (1 + l_tax))
as sum_charge,
avg(l_quantity) as avg_qty,
avg(l_extendedprice) as avg_price,
avg(l_discount) as avg_disc,
count(*) as count_order
from
tpcd.lineitem
where
l_shipdate <= date ('1998-12-01') - 90 day
group by
l_returnflag,
l_linestatus
order by
l_returnflag,
l_linestatus
```

```
L_RETURNFLAG L_LINESTATUS SUM_QTY
SUM_BASE_PRICE SUM_DISC_PRICE
SUM_CHARGE AVG_QTY
AVG_PRICE AVG_DISC
COUNT_ORDER
```

-----

```
-----
A      F      37734107.000
56586554400.730  53758257134.870
55909065222.828      25.522
38273.130      0.050  1478493
```

```
N      F      991417.000
1487504710.380  1413082168.054
1469649223.194      25.516      38284.468
0.050      38854
N      O      74476040.000
111701729697.740  106118230307.605
110367043872.497      25.502
38249.118      0.050  2920374
R      F      37719753.000
56568041380.900  53741292684.604
55889619119.832      25.506
38250.855      0.050  1478870
```

Number of rows retrieved is: 4

-----

Stop timestamp 07/16/03 21:53:50.830000  
Query Time = 3.1 secs

#### Query 2

Start timestamp 07/16/03 21:52:37.100000

-----

-- Query 02 - Var\_0 Rev\_02 - Minimum Cost Supplier Query

Tag: Q2 Stream: -1 Sequence number: 2

```
select
s_acctbal,
s_name,
n_name,
p_partkey,
p_mfgr,
s_address,
s_phone,
s_comment
from
tpcd.part,
tpcd.supplier,
tpcd.partsupp,
tpcd.nation,
tpcd.region
where
p_partkey = ps_partkey
and s_suppkey = ps_suppkey
and p_size = 15
and p_type like '%BRASS'
and s_nationkey = n_nationkey
and n_regionkey = r_regionkey
```

```

and r_name = 'EUROPE'
and ps_supplycost = (
select
min(ps_supplycost)
from
tpcd.partsupp,
tpcd.supplier,
tpcd.nation,
tpcd.region
where
p_partkey = ps_partkey
and s_suppkey = ps_suppkey
and s_nationkey = n_nationkey
and n_regionkey = r_regionkey
and r_name = 'EUROPE'
)
order by
s_acctbal desc,
n_name,
s_name,
p_partkey
fetch first 100 rows only

```

S_ACCTBAL	S_NAME	N_NAME	P_PARTKEY	P_MFGR	S_ADDRESS	S_PHONE
9938.530	Supplier#000005359	UNITED KINGDOM	185358	Manufacturer#4	bgxj2K0w1kJvxYl5mhCfou,W	33-429-790-6131
9937.840	Supplier#000005969	ROMANIA	108438	Manufacturer#1	rdnmd9c8EG1EIAYY3LPVa4yUNx6OwyVaQ	29-520-692-3537
9936.220	Supplier#000005250	UNITED KINGDOM	249	Manufacturer#4	qX AB0vP8mJEWebUY9jri	33-320-228-2957
9923.770	Supplier#000002324	GERMANY	29821	Manufacturer#4	uXcnR7tv87dG	17-779-299-1839
9871.220	Supplier#000006373	GERMANY	43868	Manufacturer#5		

iSLO35z7Ae	17-813-485-8637	never silent deposits integrate furiously blit
9870.780	Supplier#000001286	GERMANY 81285 Manufacturer#2
3gq0mZLHI5OTM6 tBYmLTHZaulCYnECzQ7nj	17-516-924-4574	final theodolites cajole slyly special,
9870.780	Supplier#000001286	GERMANY 181285 Manufacturer#4
3gq0mZLHI5OTM6 tBYmLTHZaulCYnECzQ7nj	17-516-924-4574	final theodolites cajole slyly special,
9852.520	Supplier#000008973	RUSSIA 18972 Manufacturer#2
zVfUT3Np22kUC05tYWHBotAR	32-188-594-7038	quickly regular instructions wake-carefully unusual braids into the expres
9847.830	Supplier#000008097	RUSSIA 130557 Manufacturer#2
veMRTQBmUResNvfd3	32-375-640-3593	slyly regular dependencies sleep slyly furiously express dep
9847.570	Supplier#000006345	FRANCE 86344 Manufacturer#1
68yX tGXAkVRSxUGNSjJdptw 8O878xaFnaoQK	16-886-766-7945	silent pinto beans should have to snooze carefully along the final reques
9847.570	Supplier#000006345	FRANCE 173827 Manufacturer#2
68yX tGXAkVRSxUGNSjJdptw 8O878xaFnaoQK	16-886-766-7945	silent pinto beans should have to snooze carefully along the final reques
9836.930	Supplier#000007342	RUSSIA 4841 Manufacturer#4
icFgTpZ0TuAm188dv	32-399-414-5385	final accounts haggle. bold accounts are furiously dugouts. furiously silent asymptotes are slyly
9817.100	Supplier#000002352	RUSSIA 124815 Manufacturer#2
XfLCj71HKHnPqgvs7KNgPKcOWoWxo2w	32-551-831-1437	blithely pending packages across the ironic accounts grow slyly after the furiously
9817.100	Supplier#000002352	RUSSIA 152351 Manufacturer#3
XfLCj71HKHnPqgvs7KNgPKcOWoWxo2w	32-551-831-1437	blithely pending packages across the ironic accounts grow slyly after the furiously
9739.860	Supplier#000003384	FRANCE 138357 Manufacturer#2
D01XwXbcILNwmrGS6ZPrVhZxO40i	16-494-913-5925	slyly ironic theodolites hag
9721.950	Supplier#000008757	UNITED KINGDOM 156241
Manufacturer#3	ryKUKeeWN7Z	

33-821-407-2995	ironic, even dolphins above the furiously ironic foxes sleep slyly around the caref	9681.330	Supplier#000008406
RUSSIA	78405	Manufacturer#1	
1A6x3PLY6F	32-139-873-8571		
furiously even deposits affix thinly special theodolites. furio		9643.550	Supplier#000005148
ROMANIA	107617	Manufacturer#1	
H7WOI6lzFuSsWzTSBrhzTYV	29-252-617-4850		
doggedly even ideas boost furiously against the furiously express		9624.820	Supplier#000001816
FRANCE	34306	Manufacturer#3	
NTwQPSZwfhc4uu1EMvEDopBnEv2j P	16-392-237-6726		
blithely regular accounts cajole furiously. regular		9624.780	Supplier#000009658
ROMANIA	189657	Manufacturer#1	
DmRxpLmL88XCBIoNB3tq3e0u	29-748-876-2014		
regular deposits haggle. furiously express asympto		9612.940	Supplier#000003228
ROMANIA	120715	Manufacturer#2	
hnNBdhdXO4yT18 QNABTrL8fuv0A4p	29-325-784-8187		
carefully pending accounts serve. furiously close deposits boost slyly. q		9612.940	Supplier#000003228
ROMANIA	198189	Manufacturer#4	
hnNBdhdXO4yT18 QNABTrL8fuv0A4p	29-325-784-8187		
carefully pending accounts serve. furiously close deposits boost slyly. q		9571.830	Supplier#000004305
ROMANIA	179270	Manufacturer#2	
Bdj1T5EostLveb9ocRbz	29-973-481-1831		
furiously final deposits		9558.100	Supplier#000003532
UNITED KINGDOM	88515		
Manufacturer#4			
ncMxIJcDYZd5B7FIKxxLmnlzPeZB,FKBujB			
33-152-301-2164	daring, sly accounts breach about th		
		9492.790	Supplier#000005975
GERMANY	25974	Manufacturer#5	
9UEilp7uSYtTF5	17-992-579-4839		
always pending packages boost slyly.		9461.050	Supplier#000002536
UNITED KINGDOM	20033		
Manufacturer#1			
TEEkPusQ6rU18YvixE7IQtBDOyRBdGoOWl2r			
33-556-973-5522	even foxes are quickly furiously express requests. packages		
		9453.010	Supplier#000000802
ROMANIA	175767	Manufacturer#1	
1Uj23QWxQjj7EyeqHWqGWTbN	29-		
342-882-6463	final, regular packages across the slowly regular packag	9408.650	Supplier#000007772
UNITED KINGDOM	117771		
Manufacturer#4	rIoV2rj0KNy,IT		
33-152-491-1126	blithely final ideas sleep carefully. requests are	9359.610	Supplier#000004856
ROMANIA	62349	Manufacturer#5	
k2CKOmXhPruJZ	29-334-870-9731		
carefully unusual packages sleep carefully even ideas. dogged accoun		9357.450	Supplier#000006188
UNITED KINGDOM	138648		
Manufacturer#1	LS,Z0 zbSvC7GWjF		
33-583-607-1633	carefully regular deposits wake carefully furiously even i	9352.040	Supplier#000003439
GERMANY	170921		
Manufacturer#4	B2bnKDlPkJp2uHKp		
17-128-996-4650	fluffily regular pinto beans wake. unusual, final ideas c	9312.970	Supplier#000007807
RUSSIA	90279	Manufacturer#5	
Dk2ebpGR3jlpYbpMg9Djr	32-673-872-5854		
unusual asymptotes above the		9312.970	Supplier#000007807
RUSSIA	100276	Manufacturer#5	
Dk2ebpGR3jlpYbpMg9Djr	32-673-872-5854		
unusual asymptotes above the		9280.270	Supplier#000007194
ROMANIA	47193	Manufacturer#3	
tJ96aHp8 l3uiq38LiDHswtk9bHMg	29-318-454-2133		
slyly ironic requests despite the unusual ins		9274.800	Supplier#000008854
RUSSIA	76346	Manufacturer#3	
,uJfCd6eTiYE1ZEhDM vsc8ANQPWAPIQ	32-524-148-5221		
ruthlessly ironic instructions along the regular, furious requests integrate car		9249.350	Supplier#000003973
FRANCE	26466	Manufacturer#1	
OZSkIozfU4FYizk4e091MZHozL1qcHe257J89bW	16-722-866-1658		
quickly ironic sauternes use b		9249.350	Supplier#000003973
FRANCE	33972	Manufacturer#1	
OZSkIozfU4FYizk4e091MZHozL1qcHe257J89bW	16-722-866-1658		
quickly ironic sauternes use b		9208.700	Supplier#000007769
ROMANIA	40256	Manufacturer#5	
AzIENtMrVCSbrjyUu8	29-964-424-9649		
furiously ruthless epitaphs among the furiously regular accounts use slowly fluffily ev		9201.470	Supplier#000009690
UNITED KINGDOM	67183		
Manufacturer#5	pprpD77FEIWsNMmGT9T		



33-121-267-9529 blithely unusual accounts  
integrate slyly. platelets  
9192.100 Supplier#000000115  
UNITED KINGDOM 85098  
Manufacturer#3  
EhrYy0MT5M1vfZ0V4skpifdp6pgFz5 33-  
597-248-1220 slyly bold pinto beans boost across  
the furiously regular packages. carefully regu  
9189.980 Supplier#000001226  
GERMANY 21225 Manufacturer#4  
BzfoA9wft1Mx3iBiS 17-725-903-  
1381 final, express instruction  
9128.970 Supplier#000004311  
RUSSIA 146768 Manufacturer#5  
jSiHD4NTd8i9zVRX9uz9a, 32-155-  
440-7120 regular pinto beans sleep ca  
9104.830 Supplier#000008520  
GERMANY 150974  
Manufacturer#4  
aA95nLn,m9shRrPXZw9Y1X 17-728-  
804-1793 deposits sleep carefully e  
9101.000 Supplier#000005791  
ROMANIA 128254 Manufacturer#5  
txPYsp50HJkbaAJ0bYieqHmZtirDUVOcmC4lk  
29-549-251-5384 carefully ironic packages after the  
9094.570 Supplier#000004582  
RUSSIA 39575 Manufacturer#1  
5p,3Gp8kX 1EDarE0JR5juHH Sq9jlxgKenM 32-  
587-577-1351 asymptotes above the slyly even  
requests haggle furiously about the regular accounts  
8996.870 Supplier#000004702  
FRANCE 102191 Manufacturer#5  
T35OahYXQGC 16-811-269-  
8946 stealthy requests haggle c  
8996.140 Supplier#000009814  
ROMANIA 139813 Manufacturer#2  
RL,cVCKSXFc6Win6EmtF415A22as8nG2fqEa  
29-995-571-8781 ironic theodolites are evenly  
unusual requests-- pending pinto beans across the in  
8968.420 Supplier#000010000  
ROMANIA 119999 Manufacturer#5  
R7kfmzyoIfXlrbnqNwUUW3phJctocp0J 29-  
578-432-2146 furiously final ideas believe  
furiously. furiously final ideas  
8936.820 Supplier#000007043  
UNITED KINGDOM 109512  
Manufacturer#1  
m5QHON1iDIOPhmU2R3z97u 6mCIvjnAc3i0,9s  
33-784-177-8208 furiously regular excuses wake  
after the blithely special pinto beans? even  
instructions sl  
8929.420 Supplier#000008770  
FRANCE 173735 Manufacturer#4  
aTokYV7y3 kqbRrkOGJLaI 16-242-  
746-9248 final accounts sleep furiously. blithely  
ironic foxes wake boldly across the furiously s

8920.590 Supplier#000003967  
ROMANIA 26460 Manufacturer#1  
NjCq3NUY82S 29-194-731-3944  
quickly even requests should have to affix blithely--  
fur  
8920.590 Supplier#000003967  
ROMANIA 173966 Manufacturer#2  
NjCq3NUY82S 29-194-731-3944  
quickly even requests should have to affix blithely--  
fur  
8913.960 Supplier#000004603  
UNITED KINGDOM 137063  
Manufacturer#2 d6sFwf6  
TD1xyfuFbdM2h8LX7ZWc3zHupV 33-789-  
255-7342 slyly ironic packages detect furious  
accounts. ironic de  
8877.820 Supplier#000007967  
FRANCE 167966 Manufacturer#5  
rXBIZqq9eWEuU90B vlCab6 16-442-  
147-9345 final deposits after the silent deposits ha  
8862.240 Supplier#000003323  
ROMANIA 73322 Manufacturer#3  
5RrF2PzoRlwpAGXjyf 29-736-951-  
3710 unusual, pending theodolites integrate  
furiously slyly even pinto beans. unusual sheaves  
sleep befor  
8841.590 Supplier#000005750  
ROMANIA 100729 Manufacturer#5  
n uXFrKx,KVYIQjmRuV,yejWmLMdRjnk  
29-344-502-5481 excuses after the blithely regular  
packages mold carefully deposits. regular a  
8781.710 Supplier#000003121  
ROMANIA 13120 Manufacturer#5  
wdA7CLuYXS22oQEmP0V,x0PHrXiPdI5Rpwv,ub  
29-707-291-5144 packages are quickly after the  
final, even packages. furiously regular  
8754.240 Supplier#000009407  
UNITED KINGDOM 179406  
Manufacturer#4 pj9oPHQ4OLWp  
33-903-970-9604 regular dependencies haggle  
across the carefully bold  
8691.060 Supplier#000004429  
UNITED KINGDOM 126892  
Manufacturer#2 H0paE V6JCrIZpYrzIOLgIP  
33-964-337-5038 quickly special foxes against the  
furiously silent platelets wake quickly after t  
8655.990 Supplier#000006330  
RUSSIA 193810 Manufacturer#2  
7CsFQnd ,tzgMYvVoMim514DrJcX8SaQMTcy  
32-561-198-3705 blithely even packages alongside  
8638.360 Supplier#000002920  
RUSSIA 75398 Manufacturer#1  
iMYQSQzsLXg 32-122-621-  
7549 express deposits wake. furiously silent  
requests wake carefully silent instru

8638.360 Supplier#000002920  
 RUSSIA 170402 Manufacturer#3  
 iMYQSQzsLXg 32-122-621-  
 7549 express deposits wake. furiously silent  
 requests wake carefully silent instru  
 8607.690 Supplier#000006003  
 UNITED KINGDOM 76002  
 Manufacturer#2  
 njRvqoOmIxNDe,da,SsnweINv1VY2YatifmJq  
 33-416-807-5206 always special foxes wake slyly  
 bold, ironic accounts. ironic instructions affix  
 careful  
 8569.520 Supplier#000005936  
 RUSSIA 5935 Manufacturer#5  
 I3Qd1VwvDm5hYGzg1hBHzyKy,P3YQXq7  
 32-644-251-7916 packages sleep furiously. special  
 requests about the fluffily even accounts detect  
 8564.120 Supplier#000000033  
 GERMANY 110032  
 Manufacturer#1  
 LLMgB3vXW,0g,8nuv3qU3QZaEBZvU2qRLX9  
 17-138-897-9374 ironic instructions are. special  
 pearls above  
 8553.820 Supplier#000003979  
 ROMANIA 143978 Manufacturer#4  
 qLE5JpqDoe3XHsBI6etWpd4zRsjsBNb9Tidi6  
 29-124-646-4897 express, ironic pinto beans cajole  
 around the express, even packages. qu  
 8517.230 Supplier#000009529  
 RUSSIA 37025 Manufacturer#5  
 NWW9SDThqi9RIeOA 32-565-297-  
 8775 furiously silent requests cajole furiously  
 furiously ironic foxes. slyly express p  
 8517.230 Supplier#000009529  
 RUSSIA 59528 Manufacturer#2  
 NWW9SDThqi9RIeOA 32-565-297-  
 8775 furiously silent requests cajole furiously  
 furiously ironic foxes. slyly express p  
 8503.700 Supplier#000006830  
 RUSSIA 44325 Manufacturer#4  
 qoW4lp2961uQiKOK6rW8 32-147-  
 878-5069 quickly regular excuses detect evenly  
 around  
 8457.090 Supplier#000009456  
 UNITED KINGDOM 19455  
 Manufacturer#1 U8pJ1  
 SKbZPhH7,bLWXX3pG 33-858-440-  
 4349 carefully final accounts sleep blithely special  
 foxes. slyly regular pinto beans alon  
 8441.400 Supplier#000003817  
 FRANCE 141302 Manufacturer#2  
 K6XLsYufTS 16-339-356-5115  
 blithely blithe ideas are  
 8432.890 Supplier#000003990  
 RUSSIA 191470 Manufacturer#1  
 wMJppCZ9aPMuq2nr88TVfztvE gj95OG wdNUE

32-839-509-9301 final requests along the blithely  
 ironic packages kindle against the carefully fina  
 8431.400 Supplier#000002675  
 ROMANIA 5174 Manufacturer#1  
 khl8ydxR9VekbcMLgJKPtpNtwAkYtJTv 29-  
 474-643-1443 express, final deposits cajole  
 carefully. stealthily unusual requests  
 8407.040 Supplier#000005406  
 RUSSIA 162889 Manufacturer#4  
 ITrK2mV94SooV6 Igo 32-626-152-  
 4621 quickly final sheaves boost. car  
 8386.080 Supplier#000008518  
 FRANCE 36014 Manufacturer#3  
 ZHAsABq5MRP  
 e5kc0DRD8za3xGdf763ChHmoOA45 16-618-780-  
 7481 slyly ironic theodolites are slyly. dogged,  
 pendin  
 8376.520 Supplier#000005306  
 UNITED KINGDOM 190267  
 Manufacturer#5 SyS2SsaA8i  
 CqnbzUdfNH07bVtt9uW,Cp6FLCkOR 33-632-  
 514-7931 furiously even instructions integrate  
 during the furiously regular re  
 8348.740 Supplier#000008851  
 FRANCE 66344 Manufacturer#4  
 E4uITlvmPHKvZ 16-796-240-  
 2472 ironic instructions nag slyly against the slyly  
 even theodolites. requests alongside of  
 8338.580 Supplier#000007269  
 FRANCE 17268 Manufacturer#4  
 2vJh8wqp6CJp,W0Y 16-267-277-  
 4365 ruthlessly regular asymptotes a  
 8328.460 Supplier#000001744  
 ROMANIA 69237 Manufacturer#5  
 DfCXL6UWAY1lgjQYB0AjE8T2sx0BzS  
 29-330-728-5873 blithely silent excuses are slyly  
 above the furiously even courts  
 8307.930 Supplier#000003142  
 GERMANY 18139 Manufacturer#1  
 OAPFw6SNodrC kFi 17-595-447-  
 6026 theodolites sleep blithely carefully regular  
 warhorses. slyly regular ins  
 8231.610 Supplier#000009558  
 RUSSIA 192000 Manufacturer#2  
 FONKME0t7ZJhnjn9VL5 32-762-  
 137-5858 slyly regular theodolites sleep fluffily  
 express depos  
 8152.610 Supplier#000002731  
 ROMANIA 15227 Manufacturer#4  
 sDFx3iox2Zzx 29-805-463-2030  
 gifts use. slyly silent ideas are carefully beneath the  
 silent instructions. slyly sil  
 8109.090 Supplier#000009186  
 FRANCE 99185 Manufacturer#1  
 wKLCzA5bMuGRBm35tvQAGpen23L 16-

668-570-1402 quickly pending requests are blithely along the ironic, final requests; instr  
8102.620 Supplier#000003347  
UNITED KINGDOM 18344  
Manufacturer#5 Froy39Y8ZUJ  
33-454-274-8532 packages grow special orbits.  
regular theodolites about the carefully pe  
8046.070 Supplier#000008780  
FRANCE 191222 Manufacturer#3  
rOssxn,6gRDzHr0gu,hEK 16-473-215-  
6395 regular epitaphs integrate slyly.  
8042.090 Supplier#000003245  
RUSSIA 135705 Manufacturer#4  
oJSiGLXRCDAPcfWot7LkwSQRCh63XNS2  
32-836-132-8872 carefully regular instructions  
integrate blithely silent foxes. furiously express  
instructions hagg  
8042.090 Supplier#000003245  
RUSSIA 150729 Manufacturer#1  
oJSiGLXRCDAPcfWot7LkwSQRCh63XNS2  
32-836-132-8872 carefully regular instructions  
integrate blithely silent foxes. furiously express  
instructions hagg  
7992.400 Supplier#000006108  
FRANCE 118574 Manufacturer#1  
TyptNE7nv6BLpLl6WFX 16-974-  
998-8937 regular pinto beans are after  
7980.650 Supplier#000001288  
FRANCE 13784 Manufacturer#4  
tm0TjL5b oE 16-646-464-8247  
unusual pinto beans cajole furiously according t  
7950.370 Supplier#000008101  
GERMANY 33094 Manufacturer#5  
HG2wfVixwCIhK7dIrigGR3an2LuSifDJH 17-  
627-663-8014 quickly regular requests are  
furiously. pending deposits wake  
7937.930 Supplier#000009012  
ROMANIA 83995 Manufacturer#2  
J6I7sJj0mGYIWFv9KxD3fK O7tvNP 29-  
250-925-9690 blithely bold ideas haggle quickly  
final, regular request  
7914.450 Supplier#000001013  
RUSSIA 125988 Manufacturer#2  
AI9ODzBzWgnny28PHBei5M2lUfD9 32-  
194-698-3365 final, ironic theodolites alongside of  
the ironic  
7912.910 Supplier#000004211  
GERMANY 159180  
Manufacturer#5 Zva95Dwj  
EY0w,XjgsL7O0Zb2 l3almck 17-266-947-  
7315 final requests integrate slyly above the silent,  
even  
7912.910 Supplier#000004211  
GERMANY 184210  
Manufacturer#4 Zva95Dwj  
EY0w,XjgsL7O0Zb2 l3almck 17-266-947-

7315 final requests integrate slyly above the silent,  
even  
7894.560 Supplier#000007981  
GERMANY 85472 Manufacturer#4  
e8hRUxe9cqQM3b 17-963-404-  
3760 regular, even theodolites integrate carefully.  
bold, special theodolites are slyly fluffily iron  
7887.080 Supplier#000009792  
GERMANY 164759  
Manufacturer#3 3YSi76M2  
I8XGikO5YgSM81r5Z6A7VkJZcys 17-988-938-  
4296 pending, ironic packages sleep among the  
carefully ironic accounts. quickly final accounts  
7871.500 Supplier#000007206  
RUSSIA 104695 Manufacturer#1  
YvrLdpD 5ExhHmRWzK41tw4 32-432-  
452-7731 furiously dogged pinto beans cajole. bold,  
express notornis until the slyly pending  
7852.450 Supplier#000005864  
RUSSIA 8363 Manufacturer#4  
5odLpc1M83KXJ00 32-454-883-  
3821 blithely regular deposits  
7850.660 Supplier#000001518  
UNITED KINGDOM 86501  
Manufacturer#1 ddNQX3hIjgico  
33-730-383-3892 furiously final accounts wake  
carefully idle requests. even dolphins wake acc  
7843.520 Supplier#000006683  
FRANCE 11680 Manufacturer#4  
Z1,hkHIw,Z3,,Comv6kLxIiPJtoNt 16-464-  
517-8943 carefully bold accounts doub

Number of rows retrieved is: 100

Stop timestamp 07/16/03 21:52:37.930000  
Query Time = 0.8 secs

### Query 3

Start timestamp 07/16/03 21:53:38.280000

-- Query 03 - Var\_0 Rev\_01 - Shipping Priority  
Query

Tag: Q3 Stream: -1 Sequence number: 11

select  
l\_orderkey,  
sum(l\_extendedprice \* (1 - l\_discount)) as revenue,  
o\_orderdate,

```

o_shippriority
from
tpcd.customer,
tpcd.orders,
tpcd.lineitem
where
c_mktsegment = 'BUILDING'
and c_custkey = o_custkey
and l_orderkey = o_orderkey
and o_orderdate < date ('1995-03-15')
and l_shipdate > date ('1995-03-15')
group by
l_orderkey,
o_orderdate,
o_shippriority
order by
revenue desc,
o_orderdate
fetch first 10 rows only

```

```

L_ORDERKEY REVENUE
O_ORDERDATE O_SHIPRIORITY

```

```

-----
-
 2456423      406181.011  1995-03-05
0
 3459808      405838.699  1995-03-04
0
 492164       390324.061  1995-02-19
0
 1188320      384537.936  1995-03-09
0
 2435712      378673.056  1995-02-26
0
 4878020      378376.795  1995-03-12
0
 5521732      375153.922  1995-03-13
0
 2628192      373133.309  1995-02-22
0
 993600       371407.459  1995-03-05
0
 2300070      367371.145  1995-03-13
0

```

Number of rows retrieved is: 10

```

-----
Stop timestamp 07/16/03 21:53:39.870000
Query Time =      1.6 secs

```

### Query 4

Start timestamp 07/16/03 21:53:43.690000

```

-----
-- Query 04 - Var_0 Rev_01 - Order Priority
Checking Query

```

Tag: Q4 Stream: -1 Sequence number: 14

```

select
o_orderpriority,
count(*) as order_count
from
tpcd.orders
where
o_orderdate >= date ('1993-07-01')
and o_orderdate < date ('1993-07-01') + 3 month
and exists (
select
*
from
tpcd.lineitem
where
l_orderkey = o_orderkey
and l_commitdate < l_receiptdate
)
group by
o_orderpriority
order by
o_orderpriority

```

```

O_ORDERPRIORITY ORDER_COUNT

```

```

-----
1-URGENT          10594
2-HIGH            10476
3-MEDIUM         10410
4-NOT SPECIFIED  10556
5-LOW             10487

```

Number of rows retrieved is: 5

```

-----
Stop timestamp 07/16/03 21:53:45.300000
Query Time =      1.6 secs

```

### Query 5

Start timestamp 07/16/03 21:53:55.490000

```

-----
-- Query 05 - Var_0 Rev_02 Local Supplier Volume
Query

```

Tag: Q5 Stream: -1 Sequence number: 20

```

select
n_name,
sum(l_extendedprice * (1 - l_discount)) as revenue
from
tpcd.customer,
tpcd.orders,
tpcd.lineitem,
tpcd.supplier,
tpcd.nation,
tpcd.region
where
c_custkey = o_custkey
and o_orderkey = l_orderkey
and l_suppkey = s_suppkey
and c_nationkey = s_nationkey
and s_nationkey = n_nationkey
and n_regionkey = r_regionkey
and r_name = 'ASIA'
and o_orderdate >= date ('1994-01-01')
and o_orderdate < date ('1994-01-01') + 1 year
group by
n_name
order by
revenue desc

```

N_NAME	REVENUE
INDONESIA	55502041.170
VIETNAM	55295086.997
CHINA	53724494.257
INDIA	52035512.000
JAPAN	45410175.695

Number of rows retrieved is: 5

Stop timestamp 07/16/03 21:54:05.780000  
Query Time = 10.3 secs

### Query 6

Start timestamp 07/16/03 21:52:59.840000

-- Query 06 - Var\_0 Rev\_01 - Forecasting Revenue  
Change Query

Tag: Q6 Stream: -1 Sequence number: 5

```

select
sum(l_extendedprice * l_discount) as revenue
from
tpcd.lineitem
where
l_shipdate >= date ('1994-01-01')
and l_shipdate < date ('1994-01-01') + 1 year
and l_discount between .06 - 0.01 and .06 + 0.01
and l_quantity < 24

```

```

REVENUE
-----
123141078.228

```

Number of rows retrieved is: 1

Stop timestamp 07/16/03 21:53:00.130000  
Query Time = 0.3 secs

### Query 7

Start timestamp 07/16/03 21:54:05.780000

-- Query 07 - Var\_0 Rev\_01 - Volume Shipping  
Query

Tag: Q7 Stream: -1 Sequence number: 21

```

select
supp_nation,
cust_nation,
l_year,
sum(volume) as revenue
from
(
select
n1.n_name as supp_nation,
n2.n_name as cust_nation,
year (l_shipdate) as l_year,
l_extendedprice * (1 - l_discount) as volume
from
tpcd.supplier,
tpcd.lineitem,
tpcd.orders,
tpcd.customer,
tpcd.nation n1,
tpcd.nation n2
where
s_suppkey = l_suppkey

```

```

and o_orderkey = l_orderkey
and c_custkey = o_custkey
and s_nationkey = n1.n_nationkey
and c_nationkey = n2.n_nationkey
and (
(n1.n_name = 'FRANCE' and n2.n_name =
'GERMANY')
or (n1.n_name = 'GERMANY' and n2.n_name =
'FRANCE')
)
and l_shipdate between date('1995-01-01') and
date('1996-12-31')
) as shipping
group by
supp_nation,
cust_nation,
l_year
order by
supp_nation,
cust_nation,
l_year

```

```

SUPP_NATION      CUST_NATION
L_YEAR    REVENUE
-----

```

```

FRANCE      GERMANY
1995      54639732.734
FRANCE      GERMANY
1996      54633083.308
GERMANY      FRANCE
1995      52531746.670
GERMANY      FRANCE
1996      52520549.022

```

Number of rows retrieved is: 4

```

Stop timestamp 07/16/03 21:54:13.020000
Query Time =      7.2 secs

```

### Query 8

Start timestamp 07/16/03 21:53:03.270000

```

-- Query 08 - Var_0 Rev_01 - National Market
Share Query

```

Tag: Q8 Stream: -1 Sequence number: 8

```

select

```

```

o_year,
sum(case
when nation = 'BRAZIL' then volume
else 0
end) / sum(volume) as mkt_share
from
(
select
year(o_orderdate) as o_year,
l_extendedprice * (1 - l_discount) as volume,
n2.n_name as nation
from
tpcd.part,
tpcd.supplier,
tpcd.lineitem,
tpcd.orders,
tpcd.customer,
tpcd.nation n1,
tpcd.nation n2,
tpcd.region
where
p_partkey = l_partkey
and s_suppkey = l_suppkey
and l_orderkey = o_orderkey
and o_custkey = c_custkey
and c_nationkey = n1.n_nationkey
and n1.n_regionkey = r_regionkey
and r_name = 'AMERICA'
and s_nationkey = n2.n_nationkey
and o_orderdate between date('1995-01-01') and
date('1996-12-31')
and p_type = 'ECONOMY ANODIZED STEEL'
) as all_nations
group by
o_year
order by
o_year

```

```

O_YEAR    MKT_SHARE
-----

```

```

1995      0.034
1996      0.041

```

Number of rows retrieved is: 2

```

Stop timestamp 07/16/03 21:53:32.110000
Query Time =      28.8 secs

```

### Query 9

Start timestamp 07/16/03 21:52:37.930000

```

-----
-- Query 09 - Var_0 Rev_01 - Product Type Profit
Measure Query

Tag: Q9 Stream: -1 Sequence number: 3

select
nation,
o_year,
sum(amount) as sum_profit
from
(
select
n_name as nation,
year(o_orderdate) as o_year,
l_extendedprice * (1 - l_discount) - ps_supplycost *
l_quantity as amount
from
tpcd.part,
tpcd.supplier,
tpcd.lineitem,
tpcd.partsupp,
tpcd.orders,
tpcd.nation
where
s_suppkey = l_suppkey
and ps_suppkey = l_suppkey
and ps_partkey = l_partkey
and p_partkey = l_partkey
and o_orderkey = l_orderkey
and s_nationkey = n_nationkey
and p_name like '%green%'
) as profit
group by
nation,
o_year
order by
nation,
o_year desc

```

NATION	O_YEAR	SUM_PROFIT
ALGERIA	1998	31342867.235
ALGERIA	1997	57138193.023
ALGERIA	1996	56140140.133
ALGERIA	1995	53051469.653
ALGERIA	1994	53867582.129
ALGERIA	1993	54942718.132

ALGERIA	1992	54628034.713
ARGENTINA	1998	30211185.708
ARGENTINA	1997	50805741.752
ARGENTINA	1996	51923746.576
ARGENTINA	1995	49298625.767
ARGENTINA	1994	50835610.110
ARGENTINA	1993	51646079.177
ARGENTINA	1992	50410314.995
BRAZIL	1998	27217924.383
BRAZIL	1997	48378669.199
BRAZIL	1996	50482870.357
BRAZIL	1995	47623383.635
BRAZIL	1994	47840165.726
BRAZIL	1993	49054694.035
BRAZIL	1992	48667639.084
CANADA	1998	30379833.769
CANADA	1997	50465052.311
CANADA	1996	52560501.390
CANADA	1995	52375332.809
CANADA	1994	52600364.659
CANADA	1993	52644504.073
CANADA	1992	53932871.697
CHINA	1998	31075466.165
CHINA	1997	50551874.450
CHINA	1996	51039293.875
CHINA	1995	49287534.617
CHINA	1994	50851090.067
CHINA	1993	54229629.833
CHINA	1992	52400529.372
EGYPT	1998	29054433.386
EGYPT	1997	50627611.452
EGYPT	1996	49542212.845
EGYPT	1995	48311550.321
EGYPT	1994	49790644.736
EGYPT	1993	48904292.969
EGYPT	1992	49434932.619
ETHIOPIA	1998	28040717.267
ETHIOPIA	1997	47455009.866

ETHIOPIA	1996		IRAN	1994	50337085.865
46491097.573			IRAN	1993	51730763.490
ETHIOPIA	1995		IRAN	1992	49955856.563
46804449.301			IRAQ	1998	31624551.002
ETHIOPIA	1994		IRAQ	1997	55121749.019
48516143.917			IRAQ	1996	55897663.794
ETHIOPIA	1993		IRAQ	1995	54815472.517
46551891.563			IRAQ	1994	54408516.127
ETHIOPIA	1992		IRAQ	1993	53633167.977
44934648.643			IRAQ	1992	55891939.340
FRANCE	1998	32226407.839	JAPAN	1998	27934179.670
FRANCE	1997	47121485.860	JAPAN	1997	44517162.546
FRANCE	1996	47263135.496	JAPAN	1996	42545606.120
FRANCE	1995	47275997.571	JAPAN	1995	43749356.400
FRANCE	1994	47067209.331	JAPAN	1994	44840243.070
FRANCE	1993	51163370.106	JAPAN	1993	44660015.533
FRANCE	1992	47846235.331	JAPAN	1992	45410249.122
GERMANY	1998		JORDAN	1998	26901488.578
28624942.660			JORDAN	1997	45471878.410
GERMANY	1997		JORDAN	1996	46794325.792
49309074.877			JORDAN	1995	45178828.576
GERMANY	1996		JORDAN	1994	45333636.508
49918683.168			JORDAN	1993	47971496.098
GERMANY	1995		JORDAN	1992	44717239.177
52650718.724			KENYA	1998	28597614.337
GERMANY	1994		KENYA	1997	47949733.727
50346900.423			KENYA	1996	46886924.623
GERMANY	1993		KENYA	1995	46072338.755
50991895.806			KENYA	1994	45772061.171
GERMANY	1992		KENYA	1993	46308728.234
48274126.099			KENYA	1992	47257780.841
INDIA	1998	29943144.354	MOROCCO	1998	
INDIA	1997	50665453.231	26732115.580		
INDIA	1996	50283092.291	MOROCCO	1997	
INDIA	1995	50006774.645	45637304.250		
INDIA	1994	48995190.756	MOROCCO	1996	
INDIA	1993	50286902.853	45558221.745		
INDIA	1992	50850329.402	MOROCCO	1995	
INDONESIA	1998		47851318.887		
27672339.996			MOROCCO	1994	
INDONESIA	1997		46272172.944		
50512145.726			MOROCCO	1993	
INDONESIA	1996		46764326.182		
51653060.117			MOROCCO	1992	
INDONESIA	1995		48122783.583		
51508779.594			MOZAMBIQUE	1998	
INDONESIA	1994		30712392.011		
52817950.322			MOZAMBIQUE	1997	
INDONESIA	1993		50316528.763		
47959994.955			MOZAMBIQUE	1996	
INDONESIA	1992		51640320.251		
51776605.032			MOZAMBIQUE	1995	
IRAN	1998	29065736.238	50693774.506		
IRAN	1997	50042063.054	MOZAMBIQUE	1994	
IRAN	1996	50926653.188	49253277.626		
IRAN	1995	51249667.648			



MOZAMBIQUE	1993		UNITED KINGDOM	1993
49153016.537			49166827.223	
MOZAMBIQUE	1992		UNITED KINGDOM	1992
48247551.850			49349122.083	
PERU	1998	29326102.320	UNITED STATES	1998
PERU	1997	49753780.395	25126238.946	
PERU	1996	50935170.293	UNITED STATES	1997
PERU	1995	53309883.407	50077306.419	
PERU	1994	50643531.797	UNITED STATES	1996
PERU	1993	51584622.002	48048649.470	
PERU	1992	47523899.055	UNITED STATES	1995
ROMANIA	1998		48809032.423	
30368667.400			UNITED STATES	1994
ROMANIA	1997		49296747.183	
50365683.853			UNITED STATES	1993
ROMANIA	1996		48029946.801	
49598999.015			UNITED STATES	1992
ROMANIA	1995		48671944.498	
47537642.870			VIETNAM	1998
ROMANIA	1994		30442736.059	
51455283.010			VIETNAM	1997
ROMANIA	1993		50309179.794	
50407136.892			VIETNAM	1996
ROMANIA	1992		50488161.410	
48185385.129			VIETNAM	1995
RUSSIA	1998	28322384.027	49658284.612	
RUSSIA	1997	50106685.182	VIETNAM	1994
RUSSIA	1996	51753342.430	50596057.261	
RUSSIA	1995	49215820.365	VIETNAM	1993
RUSSIA	1994	52205666.441	50953919.152	
RUSSIA	1993	51860230.034	VIETNAM	1992
RUSSIA	1992	53251677.153	49613838.315	
SAUDI ARABIA	1998			
31541259.810				
SAUDI ARABIA	1997		Number of rows retrieved is: 175	
52438750.808			-----	
SAUDI ARABIA	1996			
52543737.820				
SAUDI ARABIA	1995		Stop timestamp 07/16/03 21:52:57.780000	
52938696.533			Query Time = 19.9 secs	
SAUDI ARABIA	1994			
51389601.967				
SAUDI ARABIA	1993		<b>Query 10</b>	
52937508.882				
SAUDI ARABIA	1992		Start timestamp 07/16/03 21:53:50.830000	
54843459.641			-----	
UNITED KINGDOM	1998			
28494874.004			-- Query 10 - Var_0 Rev_01 - Returned Item	
UNITED KINGDOM	1997		Reporting Query	
49381810.899				
UNITED KINGDOM	1996		Tag: Q10 Stream: -1 Sequence number: 18	
51386853.960				
UNITED KINGDOM	1995		select	
51509586.788			c_custkey,	
UNITED KINGDOM	1994		c_name,	
48086499.711				

```

sum(l_extendedprice * (1 - l_discount)) as revenue,
c_acctbal,
n_name,
c_address,
c_phone,
c_comment
from
tpcd.customer,
tpcd.orders,
tpcd.lineitem,
tpcd.nation
where
c_custkey = o_custkey
and l_orderkey = o_orderkey
and o_orderdate >= date ('1993-10-01')
and o_orderdate < date ('1993-10-01') + 3 month
and l_returnflag = 'R'
and c_nationkey = n_nationkey
group by
c_custkey,
c_name,
c_acctbal,
c_phone,
n_name,
c_address,
c_comment
order by
revenue desc
fetch first 20 rows only

```

C_CUSTKEY	C_NAME	REVENUE
C_ACCTBAL	N_NAME	
C_ADDRESS	C_PHONE	
C_COMMENT		
-----		
-----		
-----		
-----		
57040	Customer#0000057040	
734235.246	632.870 JAPAN	
nICtsILWBB	22-895-641-3466	
requests sleep blithely about the furiously i		
143347	Customer#0000143347	
721002.695	2557.470 EGYPT	
,Q9MI3w0gvX	14-742-935-3718	
fluffily bold excuses haggle finally after the u		
60838	Customer#0000060838	
679127.308	2454.770 BRAZIL	
VWmQhWweqj5hFpcvhGFBeOY9hJ4m		
12-913-494-9813	furiously even pinto beans	
integrate under the ruthless foxes; ironic, even		
dolphins across the slyl		
101998	Customer#0000101998	
637029.567	3790.890 UNITED	
KINGDOM	0,ORojfDdyMca2E2H	

```

33-593-865-6378 accounts doze blithely! enticing,
final deposits sleep blithely special accounts. slyly
express accounts pla
125341 Customer#0000125341
633508.086 4983.510 GERMANY
9YRcnoUPOM7Sa8xymhsDHdQg 17-
582-695-5962 quickly express requests wake
quickly blithely
25501 Customer#0000025501
620269.785 7725.040 ETHIOPIA
sr4VVVe3xCJQ2oo2QEhi19D,pXqo6kOGaSn2
15-874-808-6793 quickly special requests sleep
evenly among the special deposits. special deposi
115831 Customer#0000115831
596423.867 5098.100 FRANCE
AlMpPnmtGrOfRDMUs5VLo
EIA,Cg,Rw5TBuBoKiO 16-715-386-3788
carefully bold excuses sleep alongside of the thinly
idle
84223 Customer#0000084223
594998.024 528.650 UNITED KINGDOM
Eq51o UpQ4RBr fYTdrZApDsPV4pQyuPq
33-442-824-8191 pending, final ideas haggle final
requests. unusual, regular asymptotes affix
according to the even foxes.
54289 Customer#0000054289
585603.392 5583.020 IRAN
x3ouCpz6,pRNVhajn0CCQG1 20-834-
292-4707 express requests sublute blithely regular
requests. regular, even ideas solve.
39922 Customer#0000039922
584878.113 7321.110 GERMANY
2KtWzW,FYkhdWBfobp6SFXWYKjvU9
17-147-757-8036 even pinto beans haggle. slyly
bold accounts inte
6226 Customer#000006226
576783.761 2230.090 UNITED
KINGDOM
TKbxS1dbkGMtaa,KOi26lbip4P0tPbWK0 33-
657-701-3391 quickly final requests against the
regular instructions wake blithely final instructions.
pa
922 Customer#000000922
576767.533 3869.250 GERMANY
rsR9IRxyTdHbDOvt8nYbwjK5vAWH9sB
17-945-916-9648 boldly final requests cajole blith
147946 Customer#0000147946
576455.132 2030.130 ALGERIA
Jqdt1kHAJtuTqHQK,B7 3tJh 10-886-
956-3143 furiously even accounts are blithely
above the furiousl
115640 Customer#0000115640
569341.193 6436.100 ARGENTINA
6yKLIRRAirUmBjKNO6Z3 11-411-
543-4901 final instructions are slyly according to
the

```

73606 Customer#0000073606  
568656.858 1785.670 JAPAN  
vx9,7ACVtoKnLcoAHGNYDF 22-437-  
653-6966 furiously bold orbits about the furiously  
busy requests wake across the furiously quiet  
theodolites. d  
110246 Customer#0000110246  
566842.981 7763.350 VIETNAM  
UgsLFL3rendATzcHi 31-943-426-  
9837 dolphins sleep blithely among the slyly final  
142549 Customer#0000142549  
563537.237 5085.990 INDONESIA  
pJAmChWXct HNjPzgoBUOgAHduwwIR  
19-955-562-2398 regular, unusual dependencies  
boost slyly; ironic attainments nag fluffily into the  
unusual packages?  
146149 Customer#0000146149  
557254.986 1791.550 ROMANIA  
STLwtlaB6 29-744-164-6487  
silent, unusual requests detect quickly slyly regul  
52528 Customer#0000052528  
556397.351 551.790 ARGENTINA  
elsyt8c9Z,7ch 11-208-192-3205  
unusual requests detect. slyly dogged theodolites use  
slyly. deposit  
23431 Customer#0000023431  
554269.536 3381.860 ROMANIA  
kKI5,CJAJQjQRQtOdCiFQ 29-915-  
458-2654 instructions nag quickly. furiously bold  
accounts cajol

Number of rows retrieved is: 20  
-----

Stop timestamp 07/16/03 21:53:52.830000  
Query Time = 2.0 secs

### Query 11

Start timestamp 07/16/03 21:53:45.300000  
-----

-- Query 11 - Var\_0 Rev\_01 - Important Stock  
Identification Query

Tag: Q11 Stream: -1 Sequence number: 15

```
select
ps_partkey,
sum(ps_supplycost * ps_availqty) as value
from
tpcd.partsupp,
```

```
tpcd.supplier,
tpcd.nation
where
ps_suppkey = s_suppkey
and s_nationkey = n_nationkey
and n_name = 'GERMANY'
group by
ps_partkey having
sum(ps_supplycost * ps_availqty) > (
select
sum(ps_supplycost * ps_availqty) * 0.0001000000
from
tpcd.partsupp,
tpcd.supplier,
tpcd.nation
where
ps_suppkey = s_suppkey
and s_nationkey = n_nationkey
and n_name = 'GERMANY'
)
order by
value desc
```

PS_PARTKEY	VALUE
129760	17538456.860
166726	16503353.920
191287	16474801.970
161758	16101755.540
34452	15983844.720
139035	15907078.340
9403	15451755.620
154358	15212937.880
38823	15064802.860

### Rows Deleted

128820	7892882.720
25891	7890511.200
122819	7888881.020
154731	7888301.330
101674	7879324.600
51968	7879102.210
72073	7877736.110
5182	7874521.730

Number of rows retrieved is: 1048  
-----

Stop timestamp 07/16/03 21:53:46.380000  
Query Time = 1.1 secs

### Query 12

Start timestamp 07/16/03 21:54:13.020000

-----

-- Query 12 - Var\_0 Rev\_02 - Shipping Modes and Order Priority Query

Tag: Q12 Stream: -1 Sequence number: 22

```

select
l_shipmode,
sum(case
when o_orderpriority = '1-URGENT'
or o_orderpriority = '2-HIGH'
then 1
else 0
end) as high_line_count,
sum(case
when o_orderpriority <> '1-URGENT'
and o_orderpriority <> '2-HIGH'
then 1
else 0
end) as low_line_count
from
tpcd.orders,
tpcd.lineitem
where
o_orderkey = l_orderkey
and l_shipmode in ('MAIL', 'SHIP')
and l_commitdate < l_receiptdate
and l_shipdate < l_commitdate
and l_receiptdate >= date ('1994-01-01')
and l_receiptdate < date ('1994-01-01') + 1 year
group by
l_shipmode
order by
l_shipmode

```

```

L_SHIPMODE HIGH_LINE_COUNT
LOW_LINE_COUNT

```

```

-----
MAIL          6202      9324
SHIP          6200      9262

```

Number of rows retrieved is: 2

-----

Stop timestamp 07/16/03 21:54:16.190000

Query Time = 3.2 secs

### Query 13

Start timestamp 07/16/03 21:53:36.110000

-----

-- Query 13 - Var\_0 Rev\_01 - Customer Distribution Query

Tag: Q13 Stream: -1 Sequence number: 10

```

select
c_count,
count(*) as custdist
from
(
select
c_custkey,
count(o_orderkey)
from
tpcd.customer left outer join tpcd.orders on
c_custkey = o_custkey
and o_comment not like '%special%requests%'
group by
c_custkey
) as c_orders (c_custkey, c_count)
group by
c_count
order by
custdist desc,
c_count desc

```

```

C_COUNT  CUSTDIST

```

```

-----
0      50004
9      6641
10     6566
11     6058
8      5949
12     5553
13     4989
19     4748
7      4707
18     4625
15     4552
17     4530
14     4484
20     4461
16     4323
21     4217
22     3730
6      3334
23     3129
24     2622
25     2079

```

```

5      1972
26     1593
27     1185
4      1033
28     869
29     559
3      398
30     373
31     235
2      144
32     128
33     71
34     48
35     33
1      23
36     17
37     7
40     4
38     4
39     2
41     1

```

Number of rows retrieved is: 42

Stop timestamp 07/16/03 21:53:38.280000  
Query Time = 2.2 secs

### Query 14

Start timestamp 07/16/03 21:52:13.240000

-----  
--#SET ROWS\_OUT -1 ROWS\_FETCH -1

-- Query 14 - Var\_0 Rev\_01 - Promotion Effect  
Query

Tag: Q14 Stream: -1 Sequence number: 1

```

select
100.00 * sum(case
when p_type like 'PROMO%'
then l_extendedprice * (1 - l_discount)
else 0
end) / sum(l_extendedprice * (1 - l_discount)) as
promo_revenue
from
tpcd.lineitem,
tpcd.part
where
l_partkey = p_partkey

```

```

and l_shipdate >= date ('1995-09-01')
and l_shipdate < date ('1995-09-01') + 1 month

```

PROMO\_REVENUE

-----  
16.381

Number of rows retrieved is: 1

-----  
Stop timestamp 07/16/03 21:52:37.100000  
Query Time = 23.9 secs

### Query 15a

Start timestamp 07/16/03 21:53:46.380000

-----  
-- Query 15 - Var\_a Rev\_01 - Top Supplier Query

Tag: Q15a Stream: -1 Sequence number: 16

```

with revenue (supplier_no, total_revenue) as (
select
l_suppkey,
sum(l_extendedprice * (1-l_discount))
from
tpcd.lineitem
where
l_shipdate >= date ('1996-01-01')
and l_shipdate < date ('1996-01-01') + 3 month
group by
l_suppkey
)
select
s_suppkey,
s_name,
s_address,
s_phone,
total_revenue
from
tpcd.supplier,
revenue
where
s_suppkey = supplier_no
and total_revenue = (
select
max(total_revenue)
from
revenue
)

```

order by  
s\_suppkey

S\_SUPPKEY S\_NAME  
S\_ADDRESS S\_PHONE  
TOTAL\_REVENUE

-----  
-----  
8449 Supplier#000008449  
5BXWsJERA2mP5OyO4 20-469-  
856-8873 1772627.209

Number of rows retrieved is: 1

-----  
Stop timestamp 07/16/03 21:53:47.750000  
Query Time = 1.4 secs

### Query 16

Start timestamp 07/16/03 21:53:41.440000

-----  
-- Query 16 - Var\_0 Rev\_01 - Parts/Supplier  
Relationship Query

Tag: Q16 Stream: -1 Sequence number: 13

```
select
p_brand,
p_type,
p_size,
count(distinct ps_suppkey) as supplier_cnt
from
tpcd.partsupp,
tpcd.part
where
p_partkey = ps_partkey
and p_brand <> 'Brand#45'
and p_type not like 'MEDIUM POLISHED%'
and p_size in (49, 14, 23, 45, 19, 3, 36, 9)
and ps_suppkey not in (
select
s_suppkey
from
tpcd.supplier
where
s_comment like '%Customer%Complaints%'
)
group by
p_brand,
```

p\_type,  
p\_size  
order by  
supplier\_cnt desc,  
p\_brand,  
p\_type,  
p\_size

P\_BRAND P\_TYPE P\_SIZE  
SUPPLIER\_CNT  
-----  
---  
Brand#41 MEDIUM BRUSHED TIN 3  
28  
Brand#54 STANDARD BRUSHED COPPER  
14 27  
Brand#11 STANDARD BRUSHED TIN  
23 24  
Brand#11 STANDARD BURNISHED BRASS  
36 24  
Brand#15 MEDIUM ANODIZED NICKEL  
3 24  
Brand#15 SMALL ANODIZED BRASS  
45 24

Rows Deleted

Brand#51 SMALL PLATED BRASS  
23 3  
Brand#52 MEDIUM BRUSHED BRASS  
45 3  
Brand#53 MEDIUM BRUSHED TIN  
45 3  
Brand#54 ECONOMY POLISHED BRASS  
9 3  
Brand#55 PROMO PLATED BRASS  
19 3  
Brand#55 STANDARD PLATED TIN  
49 3

Number of rows retrieved is: 18314

-----  
Stop timestamp 07/16/03 21:53:43.690000  
Query Time = 2.3 secs

### Query 17

Start timestamp 07/16/03 21:53:00.130000

-- Query 17 - Var\_0 Rev\_01 - Small-Quantity-Order Revenue Query

Tag: Q17 Stream: -1 Sequence number: 6

```
select
sum(l_extendedprice) / 7.0 as avg_yearly
from
tpcd.lineitem,
tpcd.part
where
p_partkey = l_partkey
and p_brand = 'Brand#23'
and p_container = 'MED BOX'
and l_quantity < (
select
0.2 * avg(l_quantity)
from
tpcd.lineitem
where
l_partkey = p_partkey
)
```

AVG\_YEARLY  
-----  
348406.054

Number of rows retrieved is: 1

-----

Stop timestamp 07/16/03 21:53:01.410000  
Query Time = 1.3 secs

### Query 18

Start timestamp 07/16/03 21:53:01.410000

-----

-- Query 18 - Var\_0 Rev\_01 - Large Volume Customer Query

Tag: Q18 Stream: -1 Sequence number: 7

```
select
c_name,
c_custkey,
o_orderkey,
o_orderdate,
o_totalprice,
sum(l_quantity)
from
```

```
tpcd.customer,
tpcd.orders,
tpcd.lineitem
where
o_orderkey in (
select
l_orderkey
from
tpcd.lineitem
group by
l_orderkey having
sum(l_quantity) > 300
)
and c_custkey = o_custkey
and o_orderkey = l_orderkey
group by
c_name,
c_custkey,
o_orderkey,
o_orderdate,
o_totalprice
order by
o_totalprice desc,
o_orderdate
fetch first 100 rows only
```

C\_NAME C\_CUSTKEY  
O\_ORDERKEY O\_ORDERDATE  
O\_TOTALPRICE 6

-----

Customer#0000128120	128120	4722021
1994-04-07	544089.090	323.000
Customer#0000144617	144617	3043270
1997-02-12	530604.440	317.000
Customer#0000013940	13940	2232932
1997-04-13	522720.610	304.000
Customer#0000066790	66790	2199712
1996-09-30	515531.820	327.000
Customer#0000046435	46435	4745607
1997-07-03	508047.990	309.000
Customer#0000015272	15272	3883783
1993-07-28	500241.330	302.000
Customer#0000146608	146608	3342468
1994-06-12	499794.580	303.000
Customer#0000096103	96103	5984582
1992-03-16	494398.790	312.000
Customer#0000024341	24341	1474818
1992-11-15	491348.260	302.000
Customer#0000137446	137446	5489475
1997-05-23	487763.250	311.000
Customer#0000107590	107590	4267751
1994-11-04	485141.380	301.000
Customer#0000050008	50008	2366755
1996-12-09	483891.260	302.000

Customer#0000015619	15619	3767271	Customer#0000081581	81581	4739650
1996-08-07	480083.960	318.000	1995-11-04	435405.900	305.000
Customer#0000077260	77260	1436544	Customer#0000119989	119989	1544643
1992-09-12	479499.430	307.000	1997-09-20	434568.250	320.000
Customer#0000109379	109379	5746311	Customer#0000003680	3680	3861123
1996-10-10	478064.110	302.000	1998-07-03	433525.970	301.000
Customer#0000054602	54602	5832321	Customer#0000113131	113131	967334
1997-02-09	471220.080	307.000	1995-12-15	432957.750	301.000
Customer#0000105995	105995	2096705	Customer#0000141098	141098	565574
1994-07-03	469692.580	307.000	1995-09-24	430986.690	301.000
Customer#0000148885	148885	2942469	Customer#0000093392	93392	5200102
1992-05-31	469630.440	313.000	1997-01-22	425487.510	304.000
Customer#0000114586	114586	551136	Customer#0000015631	15631	1845057
1993-05-19	469605.590	308.000	1994-05-12	419879.590	302.000
Customer#0000105260	105260	5296167	Customer#0000112987	112987	4439686
1996-09-06	469360.570	303.000	1996-09-17	418161.490	305.000
Customer#0000147197	147197	1263015	Customer#0000012599	12599	4259524
1997-02-02	467149.670	320.000	1998-02-12	415200.610	304.000
Customer#0000064483	64483	2745894	Customer#0000105410	105410	4478371
1996-07-04	466991.350	304.000	1996-03-05	412754.510	302.000
Customer#0000136573	136573	2761378	Customer#0000149842	149842	5156581
1996-05-31	461282.730	301.000	1994-05-30	411329.350	302.000
Customer#0000016384	16384	502886	Customer#0000010129	10129	5849444
1994-04-12	458378.920	312.000	1994-03-21	409129.850	309.000
Customer#0000117919	117919	2869152	Customer#0000069904	69904	1742403
1996-06-20	456815.920	317.000	1996-10-19	408513.000	305.000
Customer#0000012251	12251	735366	Customer#0000017746	17746	6882
1993-11-24	455107.260	309.000	1997-04-09	408446.930	303.000
Customer#0000120098	120098	1971680	Customer#0000013072	13072	1481925
1995-06-14	453451.230	308.000	1998-03-15	399195.470	301.000
Customer#0000066098	66098	5007490	Customer#0000082441	82441	857959
1992-08-07	453436.160	304.000	1994-02-07	382579.740	305.000
Customer#0000117076	117076	4290656	Customer#0000088703	88703	2995076
1997-02-05	449545.850	301.000	1994-01-30	363812.120	302.000
Customer#0000129379	129379	4720454			
1997-06-07	448665.790	303.000			
Customer#0000126865	126865	4702759	Number of rows retrieved is: 57		
1994-11-07	447606.650	320.000	-----		
Customer#0000088876	88876	983201			
1993-12-30	446717.460	304.000	Stop timestamp 07/16/03 21:53:03.270000		
Customer#0000036619	36619	4806726	Query Time = 1.9 secs		
1995-01-17	446704.090	328.000			
Customer#0000141823	141823	2806245			
1996-12-29	446269.120	310.000	<b>Query 19</b>		
Customer#0000053029	53029	2662214			
1993-08-13	446144.490	302.000	Start timestamp 07/16/03 21:53:52.830000		
Customer#0000018188	18188	3037414	-----		
1995-01-25	443807.220	308.000			
Customer#0000066533	66533	29158			
1995-10-21	443576.500	305.000	-- Query 19 - Var_0 Rev_01 - Discounted Revenue		
Customer#0000037729	37729	4134341	Query		
1995-06-29	441082.970	309.000			
Customer#0000003566	3566	2329187	Tag: Q19 Stream: -1 Sequence number: 19		
1998-01-04	439803.360	304.000			
Customer#0000045538	45538	4527553			
1994-05-22	436275.310	305.000			



```

select
sum(l_extendedprice* (1 - l_discount)) as revenue
from
tpcd.lineitem,
tpcd.part
where
(
p_partkey = l_partkey
and p_brand = 'Brand#12'
and p_container in ('SM CASE', 'SM BOX', 'SM
PACK', 'SM PKG')
and l_quantity >= 1 and l_quantity <= 1 + 10
and p_size between 1 and 5
and l_shipmode in ('AIR', 'AIR REG')
and l_shipinstruct = 'DELIVER IN PERSON'
)
or
(
p_partkey = l_partkey
and p_brand = 'Brand#23'
and p_container in ('MED BAG', 'MED BOX',
'MED PKG', 'MED PACK')
and l_quantity >= 10 and l_quantity <= 10 + 10
and p_size between 1 and 10
and l_shipmode in ('AIR', 'AIR REG')
and l_shipinstruct = 'DELIVER IN PERSON'
)
or
(
p_partkey = l_partkey
and p_brand = 'Brand#34'
and p_container in ('LG CASE', 'LG BOX', 'LG
PACK', 'LG PKG')
and l_quantity >= 20 and l_quantity <= 20 + 10
and p_size between 1 and 15
and l_shipmode in ('AIR', 'AIR REG')
and l_shipinstruct = 'DELIVER IN PERSON'
)

```

REVENUE

-----  
3083843.058

Number of rows retrieved is: 1

-----

Stop timestamp 07/16/03 21:53:55.490000

Query Time = 2.7 secs

**Query 20**

Start timestamp 07/16/03 21:52:57.780000

-----  
-- Query 20 - Var\_0 Rev\_01 - Potential Part  
Promotion Query

Tag: Q20 Stream: -1 Sequence number: 4

```

select
s_name,
s_address
from
tpcd.supplier,
tpcd.nation
where
s_suppkey in (
select
ps_suppkey
from
tpcd.partsupp
where
ps_partkey in (
select
p_partkey
from
tpcd.part
where
p_name like 'forest%'
)
and ps_availqty > (
select
0.5 * sum(l_quantity)
from
tpcd.lineitem
where
l_partkey = ps_partkey
and l_suppkey = ps_suppkey
and l_shipdate >= date ('1994-01-01')
and l_shipdate < date ('1994-01-01') + 1 year
)
)

```

```

and s_nationkey = n_nationkey
and n_name = 'CANADA'
order by
s_name

```

S\_NAME S\_ADDRESS

-----  
Supplier#000000020 JtPqm19E7tF  
152Rl1wQZ8j0H  
Supplier#000000091  
35WVnU7GLNbQDcc2TARavGtk6RB6ZCd46UA  
Y  
Supplier#000000197  
3oYqODDUGH3XsHXmPuzYHW5NLU3,ONZI

Supplier#00000226  
 TXAcN7Ym29ObaqaKmyDr191mN  
 Supplier#00000285 q TMZEDyZtv  
 vUiFKBhT3NjInIxpL  
 Supplier#00000378 mLpJtpu4wOc cSFzBR  
 Supplier#00000402  
 JR8vWoCteJtJg3okRpt0r28KEo  
 Supplier#00000530  
 0BvoewCPg2scOEFuL93FRKqSxHmdhw1  
 Supplier#00000688  
 orLvVDOBBE2B2ppjbiTZTJoIJgn1VgKg3  
 Supplier#00000710  
 MZR2bxctPrbC2vHho0CbuOBkLJMpqOwghC  
 Supplier#00000736  
 GUIYDfv5xCxLgDx6KQ8khY ntVVnFqmfMKIgt  
 Supplier#00000761 tF8fMGa6HY4  
 w77mDwT4rO21kxwe7uTSYNW  
 Supplier#00000884 QEJm8KMHQ8  
 Supplier#00000887 y mQ7NHjVbdqnbYr9 L  
 Supplier#00000935  
 JHRSOterYgt4MTNo7cupTza,6MoNw 4  
 Supplier#00000975  
 IqorM1ypBdwgPVuf6sMCKuF9D1rJN1iCTXKmal  
 St  
 Supplier#000001263 Aa4  
 UELS1JqY7qIjniwCWic  
 Supplier#000001399 gE COEie8t3c4xqeuT  
 Supplier#000001446  
 GOJRjfd6Z9UQ,fiuPz6CO5GDGV  
 Supplier#000001454 8cBIELxY754iHJjgRXJ0  
 Supplier#000001500 wnEIVvfuyaPJROy6x0  
 Supplier#000001602 ygd4iNQLQeVWW  
 Supplier#000001626 7Jud9t6xZNzIEB,  
 Supplier#000001682 C37Gkv 7a5ujZ9  
 Supplier#000001699 bRoW  
 MhYUCJH5bABOA53N9i  
 Supplier#000001700 UJeFoDLZ2VtflK  
 Supplier#000001726  
 8M92T8y7jYXzmvCANTtqR8GHuT  
 Supplier#000001730 aOSM0,btPDs  
 UsC06himJn,6nswJG  
 Supplier#000001746  
 B4zMDOFcMGbkZQ4XxA,UyaQoEWZzMSGI  
 wTsJp9N  
 Supplier#000001752 m  
 QTCyyuWZ8j2hQa7JNclIpGr  
 Supplier#000001856  
 I3O9Kt2l,QK,V19TBUvV9PhhfP6kt2J69bwmv64e  
 Supplier#000001931  
 mBhPe7YJU1aYmpwTiRdivl  
 Supplier#000001939 e G0hrWPL9N6z  
 Supplier#000001990  
 o8nhGpKphsybKZtye0o6OfDz9GIcuGHjMs7pq  
 Supplier#000002020 IpU ZOTeubVOC  
 Supplier#000002022  
 sNvMPI3TiNZBOYV3w2XX

Supplier#000002036 Z,ty7z5cPHh66iY5op,q  
 Supplier#000002204 y2EF  
 XUo,UyNoAQEH,gIazC7aRG1zmuzzf  
 Supplier#000002243 E8cm5YhMc6UR  
 Supplier#000002245  
 KsYA4445HcugJAb3eCmvtUslGA7Qne  
 Supplier#000002282  
 n8YZgSNuC4,iZ7s5oHTMHNFdv94DwZ2rrUEb0p  
 gD  
 Supplier#000002303  
 EoC4LCPu2cuEPKcKyTFyMGFBGkF  
 Supplier#000002373  
 asj8ud7aEmGoHuiqI5qVZ1rhpWS hJc9tF9  
 Supplier#000002419  
 BtNpaOZWivGVE53RWL22  
 Supplier#000002481  
 Efgj6dDYeFS7cq,V1DARlmeOiGecY  
 Supplier#000002571 i16xKt,WOrJhlf  
 GkzsRdrd04sZ 5jei9MtB  
 Supplier#000002585  
 pzbCgCvYax82Wq5,dG4xzyDMiRW8d  
 Supplier#000002630  
 ZiaqWld62RhjVIwNrsETHr5FbJnFTopCYZ  
 Supplier#000002719  
 XDDsajYoPAama6xjz37p66GQbXEd8X  
 Supplier#000002721 k5NlqeYhheb8BgE  
 Supplier#000002730  
 Gilu9XLsEX,oU0EyshvFTWs  
 Supplier#000002775 unOFQoQpnWJJj  
 Supplier#000002853 A7dqcyj3GQ  
 Supplier#000002875  
 VhKeIsRayU6EvfXgyyZ8aFgvv0HMfa19q1Q  
 Supplier#000002934 F0y pndtv8r vKXoJp  
 Supplier#000002941 eQNNPrRrS27ngMG1ub,  
 Supplier#000002960 hobom  
 9kkCVwuS7uKjJU0Eq2LS 8ya8Y7  
 Supplier#000002980  
 qRGRt6ztQ3x4Gyc9jMsAkIqmBSIN,8hsGv  
 Supplier#000003062  
 g8adKB2ZuDdssRsQoQBtUjvc1b  
 Supplier#000003087 rdvMSbz1W  
 LHZj8B5sRR,M4a  
 Supplier#000003089  
 VPr5pi1Ae915QrArKTf8NOKYskP7mU iZu  
 Supplier#000003095 kucdXIhJ6IYsHy0ArE7n  
 Supplier#000003201 nSTtv  
 Ui0y0BdzWb4T6snuglhEhn14yM  
 Supplier#000003213 Cu 9bXI aZ6CtLa1N7LX  
 Supplier#000003241  
 I,U861f8ReYEvHqfc5IqeMiJP  
 Supplier#000003275 SucWDuhYahP3Uwkm  
 Supplier#000003288  
 nnNLdzTmV6P0uf7yBCiK3fWt2UxHJ0  
 Supplier#000003313 nFYiTwm0,WS8b  
 wDE6EWK1vhCdJ1Gwgufh3L5j

Supplier#000003314	IDIz6TesAcXI6pXtzbO	Supplier#000005100	dLw2b
uzevXon6CH9WATfo		XiC0wmwwfkdQfxp3	
Supplier#000003380		Supplier#000005192	inBW K3Inv0HLU9k
Ibw,51BzsCyx17X3zqAFc0Gu7Yx0K7mImP9z0u		Supplier#000005195	5CIXPZ1QIOcJr18MxZmL4Jm
Supplier#000003403		Supplier#000005283	WLu23vv3t08a30eBnoYJvsta
NX3YC0gokSyZjHJSqr34ouIlZJ14pw		Supplier#000005300	L3kYS3ABu6
Supplier#000003421		Supplier#000005386	7PUqqMjB4f5b
9JXNyS4VCMDLl4CxDIJ L0		Supplier#000005426	SnsYc67ZAr
Supplier#000003441	twlhit80C6y8JjHCO3	PWpgUZFHha,3Hbp39bwc	
Supplier#000003590	tTRoffuAP1oPC	Supplier#000005484	QINcarA4Tri20XRzbAIJqQZZfCYBpCd,pzb gC
Supplier#000003607	GdAljb2Hv8rGL	Supplier#000005505	OYzPHIWXgvfb3
Supplier#000003625		Supplier#000005506	dDrLVuBsC4Lp
B2VSS5,2GVJQ6tZa37KdAmg erHp2jPgZ		Supplier#000005516	4zdRRhzRvmxOCJ6VH9nYfMMPamLTUEoSvCw
Supplier#000003656		y2	
Nm2EEdYKEnshNLkYY3ynLh50NQVU		Supplier#000005536	esCRylGBKPk70m1Xn0TTf2gFWRJZo
Supplier#000003782		Supplier#000005605	U5HUmJF,E7KAGe
J5zb1LTPG,V7AdewI,fgQf6 o,sE K		Supplier#000005631	,W75
Supplier#000003918		IFsCY9hmp2pnKBew7Fwv9Ao	
FM9w9pzhCqQLAN,aMW		Supplier#000005730	W
Supplier#000003941		GP,c8MvzsjuGgShQnXZ6BD9IYOKTjZ	
cEP,VFaLpe9UZScU4gA1irRwtX		Supplier#000005736	ZNAr382Jy258LB
Supplier#000003994	5,,f1CXdHg0	Supplier#000005737	OEm4O9XYoXHuoN0qRVrcF2DWS
Supplier#000004005		Supplier#000005797	1C0cMQv9P8oE5FRLdRLB5boIAqr6CKxF89
6TYXl,votYNqWcKjxS7Hqyc56kB		Supplier#000005836	zuX8HcnY1x5klp9k0
Supplier#000004033	EOzqJxRhM0HI37dILPY	Supplier#000005875	Gg0z2JkspRXJ8tjuRuw82IP5aeo1MYg31xkQ8
Supplier#000004140	0KfTnit2HOkf	Supplier#000005974	amJ9VIm0Ffyza3wMVW8v3t8Kz985IJy
Supplier#000004165		Supplier#000005989	AH120WgKfBqxTO
w7hYN2daqScYcIRSDUn7XTDNju03gnZ		Supplier#000006059	XE,OwTevhRu3YwFwir1
Supplier#000004207		Supplier#000006065	7IiYouX4W7yVzfGsfXw3g9tUgJfKw
zlUWBwIceWjG4HdYE80M0V4xqIfu		Supplier#000006070	8QFoVF,Bn
Supplier#000004236		dUn1PEKLEkFAM	
OF0jzbzhEkICu2z8BDRvEBGx4H y0EoNhScU8		Supplier#000006109	A2VKPMJXNgkDtFOb67bkpvDPM
Supplier#000004246	4JQrQ4alTxXA6Xf jn	Supplier#000006121	9RYtO5vms23vWkzCophd,4exjKC1
Supplier#000004278	QpNNPCpui5CrnIR	Supplier#000006215	IYImP8zF0Vc4NA42TGZtJi8PTByII1GHnibnC
Supplier#000004343	lgXzPDBA anG4fex5plol	Supplier#000006217	a5dYX927RHND6MQ5k36N
Supplier#000004346	9X,TUgmcvC	Supplier#000006274	9Xt715Au7g7ArKrbaKO4SrqaJpGd1z5VZJjyv6
Supplier#000004388	6L1rF,h0EvCWQ8	Supplier#000006435	viKmUS3zs2QDcWmDDTOjkcSt
Supplier#000004406		Supplier#000006463	UrvGNiYmcWSICyFNtYGEjerqnCf8zsl5X9d5H
rJ,1QgxU5vyLb46t0TGP4K21JRxmQjBkiK			
Supplier#000004430			
uw8zge87fVkf3pm8WFxc bdfuhsqeG			
Supplier#000004522			
v3yogwz1nqAuipkoLs3YcKCPk2zpK			
Supplier#000004527			
CrB53pDuKOHF4lUrZCXck2XA4V			
Supplier#000004542	eh8Pfin C2lYtZ Y nIgL		
Supplier#000004574	,jwkvE5xM1WoiDNP		
Supplier#000004655			
VTdApPWryXckXISrcrizB4dAWHkQbCw2f			
Supplier#000004701	VH3WxXT69sjeJL		
Supplier#000004711			
QmsHB,aNaxsFzYmaeuw,HERwDVPxYs4FfZ			
Supplier#000004987	s6luZyBhSexcwKIIqS		
Supplier#000005000	oM3S,Xrv,jTl		
o6xQJKtsIFPxtp3Xdh			

Supplier#000006493	DH5rL1zdQpVjET	Supplier#000007998	
1LGDn67fUXAQhKqI1g		gDq8lqL29ldCRNUO0Qzpx5ARfDYb	
Supplier#000006521	QRrYsIjsu9	Supplier#000008168	RcQSYRS1PgpDLnf4
Supplier#000006607	YlrYMZKAnVyVp	Supplier#000008231	jpgTMkwr2HR0 7NB
Supplier#000006706		b0wOB4ufp	
rGWKQ1MbxZb1UoXBG		Supplier#000008243	
AHDzQ3,LuwA8SwGPM		ZqtMbfGnAEt5sHk8Is3yKlfcSKRmIxOoeucFiik	
Supplier#000006761	EWJuleApVC	Supplier#000008275	qFPdnM4K0KC3gaFgd
nZjKBfwwA48ycgFFQ		Supplier#000008323	UViZS
Supplier#000006808		1Eq8wErbcNJM9eOHRyECtMa0qLo3dWpiqP	
kkNY3DrRDmPjhJ1x3H3u5giBqC7		Supplier#000008366	
Supplier#000006858		KTTSONHZWpy4RcmhFwb75AWIvr89Umqp3dTt	
MDFid8SSVwqpJz4w7kl10DYYyKvk2ZVJrkjiHY		M8S	
Z		Supplier#000008423	aaJgDHqJ9,oq
Supplier#000006872		XivWaZvNeeD,OKdMrhA	
4inIrTbf3p4gU8NmOFN		Supplier#000008480	
Supplier#000006949	Ffu26iJzkOgygMr1kII	Xz8nqXqo9MHFdHmFV7UP	
exZSXrw7		Supplier#000008532	7OYRAX0Vu5OncISU61
Supplier#000006985	c	uK Wu49,IJm73xJ	
66lQCaBt1cyKh0,1Wpvha6tAvROXj		Supplier#000008595	
Supplier#000007072		fj,IpUXkaXtr64XdmPoQAE0	
Zy9t3SeZQrX9OEVUzTTRmZqdkSHFBg		Supplier#000008610	
Supplier#000007098		9K5KbS,wbWWYz6d8KsfRtgv3j4qs5Uz5	
IXHSK0hoWcPPqxYd5CbjA3a4ep6NHATvKojdm		Supplier#000008705	Rm0y
ux		adNbu1WtID8nRcXoMPniC	
Supplier#000007135	GzrnCh5T5VyFLatS5	Supplier#000008742	
Supplier#000007160		kEbFansgobnO76f,W0GgB	
8Ankp7fpXO8Ai7UmgnwESp8WMXw0sv3IabP		Supplier#000008841	jrSVfyZzMGQKYu 9isE,
Supplier#000007169		Supplier#000008895	ZOjWCHLQf8277KS
zmORVoYECdS8SWDOVVc0OFD4		g9PPiauGENlxYm H	
Supplier#000007322	w	Supplier#000008967	
TNKzMVArfqHI20yvEIYetnG9e3Z		ZGvmjuekrTmvCsdjEq6mVEj,J3yA2OyFhe	
Supplier#000007365	WZuJ9dfwaei,VnDOy14y	Supplier#000008972	
Supplier#000007398	6SMmUD1,,cmd60	wYwlUsnV21dXwIzc3zA5Mfqh7h	
Supplier#000007402	X65wVTM tZAHEA8aV	Supplier#000009032	Bg0y qU8NtXnsZpa6ldt
Supplier#000007448	uJJB4JhITmiUaV5pQa	Supplier#000009147	Acqx ujuB1SMcwu
Supplier#000007477		Supplier#000009252	
SERH,wLJ4spw5juH60bBruv8j0K		mTO1Qc6jvJ,r1gtIXuEq64oZ3ObrxM,BVE0J	
Supplier#000007509		Supplier#000009278	
BS05Ugh9CjiHjOcy8kTQg7eK		aA27sLuHRXpf3r,FO2LondcMLO	
Supplier#000007561	AeOIKZVX,5p	Supplier#000009327	
Supplier#000007789	AaTO6Pb yxOoctX	yCAeNMTMTkIRNPaWX	
wd8GJEAjUB L47Z8s		Supplier#000009430	JK9AEEMlyr
Supplier#000007801	VRLI07Z UME6Pr	Supplier#000009567	
Supplier#000007818	uJJOYpaMOri	AW4LuXOXuznqHOkITZjj2ptC EFrnRx sy3GwW	
wOStApISY		Supplier#000009601	
Supplier#000007885		WZEUXUPc09wVnDj5l6wfRO9uR	
yXzIOPJJV1Ct76BeZOhgeOqCQQi4K2		Supplier#000009709	
Supplier#000007918	A0wREqaUfCn2tHZ	A9DoPk2KnKGRb12Et4g53864,xgK	
Supplier#000007926	n solT,gR6u	Supplier#000009753	
Supplier#000007957		wfJ5mP9ENTcGhIWmpDkgU1	
nfvDIDZWzzD6ZrNat1ifscgX5zsP		Supplier#000009796	t0tWiOE ZVocwb6B2k
Supplier#000007965	mT6DVGHtBVKJH	Supplier#000009799	sWvdH4kQWch4F
Supplier#000007968	ozlR6G1YICVj3dRRm	Supplier#000009811	
wtLZIGjDnVSYk8k1Bc		nXlxtBT6D1v6TCb2iMYkyU	

```

Supplier#000009812
rbl9euXFoPLIKQVYDVyRouslbbbKDHAKyXY
Supplier#000009862      AhsvM5MdVS
Supplier#000009868
acHkKvVKwyHED66DMtTx
Supplier#000009869      yOfAut
Bp7aeMvk9eYRy0Ad7eY,KZ7yX3KKYEgQK
Supplier#000009899      U3NBqk s Zz06al2m
Supplier#000009974
Uvh0hWngOu96WgB,OafBQOqwpWqzwg8

```

Number of rows retrieved is: 204

-----

Stop timestamp 07/16/03 21:52:59.840000  
Query Time = 2.1 secs

### Query 21

Start timestamp 07/16/03 21:53:32.110000

-----

-- Query 21 - Var\_0 Rev\_01 - Suppliers Who Kept  
Orders Waiting Query

Tag: Q21 Stream: -1 Sequence number: 9

```

select
s_name,
count(*) as numwait
from
tpcd.supplier,
tpcd.lineitem l1,
tpcd.orders,
tpcd.nation
where
s_suppkey = l1.l_suppkey
and o_orderkey = l1.l_orderkey
and o_orderstatus = 'F'
and l1.l_receiptdate > l1.l_commitdate
and exists (
select
*
from
tpcd.lineitem l2
where
l2.l_orderkey = l1.l_orderkey
and l2.l_suppkey <> l1.l_suppkey
)
and not exists (
select
*

```

```

from
tpcd.lineitem l3
where
l3.l_orderkey = l1.l_orderkey
and l3.l_suppkey <> l1.l_suppkey
and l3.l_receiptdate > l3.l_commitdate
)
and s_nationkey = n_nationkey
and n_name = 'SAUDI ARABIA'
group by
s_name
order by
numwait desc,
s_name
fetch first 100 rows only

```

S_NAME	NUMWAIT
Supplier#000002829	20
Supplier#000005808	18
Supplier#000000262	17
Supplier#000000496	17
Supplier#000002160	17
Supplier#000002301	17
Supplier#000002540	17
Supplier#000003063	17
Supplier#000005178	17
Supplier#000008331	17
Supplier#000002005	16
Supplier#000002095	16
Supplier#000005799	16
Supplier#000005842	16
Supplier#000006450	16
Supplier#000006939	16
Supplier#000009200	16
Supplier#000009727	16
Supplier#000000486	15
Supplier#000000565	15
Supplier#000001046	15
Supplier#000001047	15
Supplier#000001161	15
Supplier#000001336	15
Supplier#000001435	15
Supplier#000003075	15
Supplier#000003335	15
Supplier#000005649	15
Supplier#000006027	15
Supplier#000006795	15
Supplier#000006800	15
Supplier#000006824	15
Supplier#000007131	15
Supplier#000007382	15
Supplier#000008913	15
Supplier#000009787	15
Supplier#000000633	14
Supplier#000001960	14

Supplier#000002323 14  
 Supplier#000002490 14  
 Supplier#000002993 14  
 Supplier#000003101 14  
 Supplier#000004489 14  
 Supplier#000005435 14  
 Supplier#000005583 14  
 Supplier#000005774 14  
 Supplier#000007579 14  
 Supplier#000008180 14  
 Supplier#000008695 14  
 Supplier#000009224 14  
 Supplier#000000357 13  
 Supplier#000000436 13  
 Supplier#000000610 13  
 Supplier#000000788 13  
 Supplier#000000889 13  
 Supplier#000001062 13  
 Supplier#000001498 13  
 Supplier#000002056 13  
 Supplier#000002312 13  
 Supplier#000002344 13  
 Supplier#000002596 13  
 Supplier#000002615 13  
 Supplier#000002978 13  
 Supplier#000003048 13  
 Supplier#000003234 13  
 Supplier#000003727 13  
 Supplier#000003806 13  
 Supplier#000004472 13  
 Supplier#000005236 13  
 Supplier#000005906 13  
 Supplier#000006241 13  
 Supplier#000006326 13  
 Supplier#000006384 13  
 Supplier#000006394 13  
 Supplier#000006624 13  
 Supplier#000006629 13  
 Supplier#000006682 13  
 Supplier#000006737 13  
 Supplier#000006825 13  
 Supplier#000007021 13  
 Supplier#000007417 13  
 Supplier#000007497 13  
 Supplier#000007602 13  
 Supplier#000008134 13  
 Supplier#000008234 13  
 Supplier#000009435 13  
 Supplier#000009436 13  
 Supplier#000009564 13  
 Supplier#000009896 13  
 Supplier#000000379 12  
 Supplier#000000673 12  
 Supplier#000000762 12  
 Supplier#000000811 12  
 Supplier#000000821 12

Supplier#000001337 12  
 Supplier#000001916 12  
 Supplier#000001925 12  
 Supplier#000002039 12  
 Supplier#000002357 12  
 Supplier#000002483 12

Number of rows retrieved is: 100

Stop timestamp 07/16/03 21:53:36.110000

Query Time = 4.0 secs

### Query 22

Start timestamp 07/16/03 21:53:39.870000

-- Query 22 - Var\_0 Rev\_01 - Global Sales Opportunity Query

Tag: Q22 Stream: -1 Sequence number: 12

```

select
  cntrycode,
  count(*) as numcust,
  sum(c_acctbal) as totacctbal
from
  (
    select
      substr(c_phone, 1, 2) as cntrycode,
      c_acctbal
    from
      tpcd.customer
    where
      substr(c_phone, 1, 2) in
      ('13', '31', '23', '29', '30', '18', '17')
    and c_acctbal > (
      select
        avg(c_acctbal)
      from
        tpcd.customer
      where
        c_acctbal > 0.00
        and substr(c_phone, 1, 2) in
        ('13', '31', '23', '29', '30', '18', '17')
    )
    and not exists (
      select
        *
      from
  
```

```

tpcd.orders
where
o_custkey = c_custkey
)
) as custsale
group by
cntrycode
order by
cntrycode

```

CNTRYCODE	NUMCUST	TOTACCTBAL
13	888	6737713.990
17	861	6460573.720
18	964	7236687.400
23	892	6701457.950
29	948	7158866.630
30	909	6808436.130
31	922	6806670.180

Number of rows retrieved is: 7

Stop timestamp 07/16/03 21:53:41.440000  
Query Time = 1.6 secs

**First 10 Rows of the Database**

```

SELECT * FROM TPCD.REGION FETCH FIRST
10 ROWS ONLY

```

```

R_REGIONKEY R_NAME
R_COMMENT

```

```

-----
-----
-----
0 AFRICA          special Tiresias about
the furiously even dolphins are furi
1 AMERICA        even, ironic
theodolites according to the bold platelets wa
2 ASIA           silent, bold requests
sleep slyly across the quickly sly dependencies.
furiously silent instructions alongside
3 EUROPE         special, bold deposits
haggle foxes. platelet
4 MIDDLE EAST    furiously unusual
packages use carefully above the unusual, exp
5 record(s) selected.

```

```

SELECT * FROM TPCD.NATION FETCH FIRST
10 ROWS ONLY

```

```

N_NATIONKEY N_NAME
N_REGIONKEY N_COMMENT

```

```

-----
-----
-----
0 ALGERIA        0 final accounts
wake quickly. special reques
5 ETHIOPIA       0 fluffily
ruthless requests integrate fluffily. pending ideas
wake blithely acco
14 KENYA         0 ironic
requests boost. quickly pending pinto beans cajole
slyly slyly even deposits. ironic packages
15 MOROCCO      0 ideas
according to the fluffily final pinto beans sleep
furiously
16 MOZAMBIQUE   0 ironic
courts wake fluffily even, bold deposi
1 ARGENTINA      1 idly final
instructions cajole stealthily. regular instructions
wake carefully blithely express accounts. fluffi
2 BRAZIL        1 always
pending pinto beans sleep sil
3 CANADA        1 foxes among
the bold requests
17 PERU         1 final, final
accounts sleep slyly across the requests.
24 UNITED STATES 1 blithely
regular deposits serve furiously blithely regular
warthogs! slyly fi
10 record(s) selected.

```

```

SELECT * FROM TPCD.PART FETCH FIRST
10 ROWS ONLY

```

```

P_PARTKEY P_NAME
P_MFGR     P_BRAND P_TYPE
P_SIZE     P_CONTAINER P_RETAILPRICE
P_COMMENT

```

```

-----
-----
-----
43 medium khaki chocolate rosy blush
Manufacturer#4 Brand#44 PROMO
POLISHED STEEL 5 WRAP CASE
+9.430400000000000E+002 carefully iro
47 sky firebrick red linen dim
Manufacturer#4 Brand#45 LARGE

```

BURNISHED BRASS 14 JUMBO PACK  
+9.4704000000000E+002 bold, unusual a  
89 ghost khaki lawn pale dim  
Manufacturer#5 Brand#53 STANDARD  
BURNISHED STEEL 7 MED JAR  
+9.8908000000000E+002 quickly ironi  
98 frosted goldenrod chartreuse dark  
honeydew Manufacturer#5 Brand#54  
STANDARD ANODIZED BRASS 22 MED  
JAR +9.9809000000000E+002 furiou  
119 olive black navajo burlywood ghost  
Manufacturer#4 Brand#43 LARGE  
POLISHED STEEL 30 WRAP CASE  
+1.0191100000000E+003 blithely pendin  
122 ghost royal chocolate peach ivory  
Manufacturer#2 Brand#21 MEDIUM  
ANODIZED TIN 8 LG DRUM  
+1.0221200000000E+003 pinto beans w  
125 metallic indian magenta navy medium  
Manufacturer#1 Brand#12 STANDARD  
BRUSHED BRASS 17 WRAP BAG  
+1.0251200000000E+003 carefully fina  
126 burnished navy indian medium deep  
Manufacturer#4 Brand#45 MEDIUM  
BRUSHED NICKEL 4 LG BAG  
+1.0261200000000E+003 slowly bold pin  
144 wheat brown orange almond aquamarine  
Manufacturer#1 Brand#14 SMALL  
ANODIZED TIN 26 SM BOX  
+1.0441400000000E+003 blithely bold r  
169 tan lime sky almond midnight  
Manufacturer#5 Brand#55 STANDARD  
POLISHED BRASS 10 JUMBO CASE  
+1.0691600000000E+003 blithely

10 record(s) selected.

SELECT \* FROM TPCD.SUPPLIER FETCH  
FIRST 10 ROWS ONLY

S_SUPPKEY	S_NAME	S_ADDRESS
S_NATIONKEY	S_PHONE	S_ACCTBAL
S_COMMENT		

-----  
-----  
-----  
-----

43 Supplier#000000043  
2VEfxrC76mNg2VwZY5DDrWnSTrCUHIZfwe2E  
F3SJ 12 22-421-568-4862  
+7.7734100000000E+003 slyly final accounts  
wake blithely slyly regular requests. sl  
47 Supplier#000000047  
Y3eZu1bOuAw0jgW4dFKPE1ePfkpjfq

14 24-810-354-4471 +2.9580900000000E+003  
regular deposits engage slyly with the  
89 Supplier#000000089 MJys1P8C JyNZ  
9 19-259-876-1014 +1.6380200000000E+003  
bold, even instructions print carefully even courts.  
ironic,  
98 Supplier#000000098 DKjDSOB3pVb  
21 31-914-775-1978 +5.8730700000000E+003  
slyly regular requests mold slyly regular depo  
119 Supplier#000000119 Xoup  
f,CWtzUf2lv1it1TR3DLTf1dDVgO2O 18  
28-558-264-1202 +2.0601300000000E+003  
blithely express theodolites wake furiously within  
the b  
122 Supplier#000000122  
Z968jkzB8Op574oVsrwvZ359 16  
26-432-258-4986 +2.7329500000000E+003  
fluffily silent asymptotes along the accounts ha  
125 Supplier#000000125  
4krMcX3PW79IT  
HX9U49bZwYzN7FtKRXYw12Qo 2 12-419-  
430-3983 +5.1572500000000E+003 quickly final  
excuses wake furiously against the furiously ex  
126 Supplier#000000126  
pQcW2y1rC8HsMED 14 24-  
728-670-3468 +6.8298600000000E+003 carefully  
pending packages sleep slyly.  
144 Supplier#000000144  
MSyNNngBzS,UjjAevzgNEX 20  
30-726-423-7363 +9.8062900000000E+003 even,  
fluffy somas cajole ironically. even instructions are  
after the bold deposits. silent ac  
169 Supplier#000000169 uOtE  
MpVh5,w60zwb3KKry 13 23-698-  
509-1073 -9.2750000000000E+002 even, ironic  
packages boost regularly at the carefully unusual  
inst

10 record(s) selected.

SELECT \* FROM TPCD.PARTSUPP FETCH  
FIRST 10 ROWS ONLY

PS_PARTKEY	PS_SUPPKEY	PS_AVAILQTY
PS_SUPPLYCOST	PS_COMMENT	

-----  
-----  
-----  
-----  
-----

6 7 8851  
+1.3072000000000E+002 carefully regular  
asymptotes wake slyly according to the quickly re  
6 2507 1627  
+4.2425000000000E+002 packages after the



blithely ironic deposits engage quickly around the slyly unusual accounts. quickly pending theodolites boost. requests sleep speci

6 5007 3336

+6.42130000000000E+002 ironic theodolites hang blithe, regular requests. final requests sleep furious

6 7507 6451

+1.75320000000000E+002 regular, ironic accounts sleep ruthlessly around the deposits. slyly final deposits boost about the pending, bold grouches. silent, even theodolites along the final, even ideas cajole blithely

17 18 8555

+9.95350000000000E+002 final deposits among the quickly unusual deposits detect unusual, final dependencies. theodolites cajole blithely. final, express depths wake blithely. slyly regular requests sleep. carefully regu

17 2518 7737

+6.48750000000000E+002 deposits boost slyly. furiously dogged packages wake blithely even attainments. furiously ironic dolphins print bold, even instructions. courts detect. ironic requests accordin

17 5018 3123

+5.55040000000000E+002 quickly final deposits are fluffily. brave packages use slyly. carefull

17 7518 3203

+6.44000000000000E+001 fluffily sly instructions use slyly fluffily even excuses. furiously regular pinto beans among the quickly special

52 53 6533

+5.49200000000000E+001 ironic excuses according to the quickly ironic requests boost regular, express excuses. furiously bold deposits ar

52 2553 1937

+2.10440000000000E+002 carefully special courts about the blithely ironic requests cajole bold

10 record(s) selected.

SELECT \* FROM TPCD.CUSTOMER FETCH FIRST 10 ROWS ONLY

C\_CUSTKEY C\_NAME  
C\_ADDRESS C\_NATIONKEY  
C\_PHONE C\_ACCTBAL  
C\_MKTSEGMENT C\_COMMENT

-----  
-----  
-----  
-----  
-----

43 Customer#0000000043  
Dx8PHkGSFJWLg3XtkzCX28iHRrQXbCRIN

19 29-316-665-2897 +9.90428000000000E+003 MACHINERY idly regular sentiments affix. slyly pending foxes around the deposits haggle according to th

47 Customer#0000000047

Q,6KCP8Am4WrKN5QJd7 2

12-427-271-9466 +2.74580000000000E+002

BUILDING blithely final deposits about the furiously special packages play even idea

89 Customer#0000000089

Oy90ruRha47cUICimutBTvJc6 14

24-394-451-5404 +1.53076000000000E+003

FURNITURE bold accounts cajole furiously after the permanently even excuses. accounts cajole. fluffily even requ

98 Customer#0000000098

UtIJM4d8BxnqvPzwn4 12 22-

885-845-6889 -5.51370000000000E+002

BUILDING blithely final foxes along the unusual realms detect accounts. idle theodolites use pinto beans. ev

119 Customer#0000000119

fZm7cjMOxwkSnye03,D u3L4 7

17-697-919-8406 +3.93035000000000E+003

FURNITURE regular, ironic theodolites alongside of the instructions haggle carefully even requests. packages

122 Customer#0000000122

uBVzFBCdNYVFqmd24XQUUv8L3rUJ7I

3 13-702-694-4520 +7.86546000000000E+003

HOUSEHOLD furiously regular instructions cajole furiously ideas. quickly bold foxes wake careful

125 Customer#0000000125

1v813O59ruviiLESzSi7ufFXGLH7U6p,Tk203

19 29-261-996-3120 -2.34120000000000E+002

FURNITURE special instructions use above the carefully quick packages. closely fi

126 Customer#0000000126

KQWmjFPuXGLrn2o bUnlN6cEQxyaFjKOLQAA

22 32-755-914-7592 +1.00139000000000E+003

HOUSEHOLD carefully special requests after the slyly regular packages sleep furiously slyly final epitaphs.

144 Customer#0000000144

6u21XNPJKPGyDMYRkHdoTAoOOI26,VsLMbdf

DCSt 1 11-717-379-4478

+6.41731000000000E+003 MACHINERY fluffily regular requests at the blithely even theodolites haggle around the requests. special frets x-

169 Customer#0000000169 eHJEjRTu OIm

18 28-362-499-3728 +4.48383000000000E+003

FURNITURE furiously pending dugouts use furiously unusual, regular deposits. carefully regul

10 record(s) selected.

SELECT \* FROM TPCD.ORDERS FETCH FIRST  
10 ROWS ONLY

O\_ORDERKEY O\_CUSTKEY  
O\_ORDERSTATUS O\_TOTALPRICE  
O\_ORDERDATE O\_ORDERPRIORITY  
O\_CLERK O\_SHIPPRIORITY  
O\_COMMENT

-----  
-----  
-----  
-----  
-----  
65 16252 P  
+1.10643600000000E+005 03/18/1995 1-URGENT  
Clerk#000000632 0 furiously even platelets  
boost ironic theodolites. even  
128 73957 F  
+6.61951600000000E+004 06/15/1992 1-URGENT  
Clerk#000000385 0 carefully special e  
320 302 O  
+5.37436000000000E+004 11/21/1997 2-HIGH  
Clerk#000000573 0 carefully silent ideas do  
solve final, express instructions. quickly final p  
326 75986 O  
+3.27413140000000E+005 06/04/1995 2-HIGH  
Clerk#000000466 0 regular theodolites was  
car  
418 94834 P  
+5.33284800000000E+004 04/13/1995 4-NOT  
SPECIFIED Clerk#000000643 0 quiet, bold  
ideas a  
551 89608 O  
+7.10323600000000E+004 05/30/1995 1-URGENT  
Clerk#000000179 0 unusual, final accounts  
use above the special excuses. final depo  
709 36029 O  
+9.07788900000000E+004 04/21/1998 1-URGENT  
Clerk#000000461 0 quickly final excuses  
sleep quickly. sly  
801 117790 F  
+1.84316400000000E+005 02/18/1992 1-URGENT  
Clerk#000000186 0 theodolites sleep above  
the careful  
805 126001 O  
+1.41519400000000E+005 07/05/1995 4-NOT  
SPECIFIED Clerk#000000856 0 busy,  
regular foxes  
836 68782 O  
+1.19120780000000E+005 11/25/1996 4-NOT  
SPECIFIED Clerk#000000729 0 slyly  
unusual deposits affix

10 record(s) selected.

SELECT \* FROM TPCD.LINEITEM FETCH  
FIRST 10 ROWS ONLY

L\_ORDERKEY L\_PARTKEY L\_SUPPKEY  
L\_LINENUMBER L\_QUANTITY  
L\_EXTENDEDPRICE L\_DISCOUNT  
L\_TAX L\_RETURNFLAG  
L\_LINESTATUS L\_SHIPDATE  
L\_COMMITDATE L\_RECEIPTDATE  
L\_SHIPINSTRUCT L\_SHIPMODE  
L\_COMMENT

-----  
-----  
-----  
-----  
-----  
33 61336 8855 1  
+3.10000000000000E+001  
+4.02172300000000E+004 +9.00000000000000E-  
002 +4.00000000000000E-002 A F  
10/29/1993 12/19/1993 11/08/1993 COLLECT  
COD TRUCK slyly even requests are f  
33 60519 5532 2  
+3.20000000000000E+001  
+4.73443200000000E+004 +2.00000000000000E-  
002 +5.00000000000000E-002 A F  
12/09/1993 01/04/1994 12/28/1993 COLLECT  
COD MAIL special theodolites boost  
33 137469 9983 3  
+5.00000000000000E+000  
+7.53230000000000E+003 +5.00000000000000E-  
002 +3.00000000000000E-002 A F  
12/09/1993 12/25/1993 12/23/1993 TAKE  
BACK RETURN AIR bold requests affix  
alongside of the slyly  
33 33918 3919 4  
+4.10000000000000E+001  
+7.59283100000000E+004 +9.00000000000000E-  
002 +0.00000000000000E+000 R F  
11/09/1993 01/24/1994 11/11/1993 TAKE  
BACK RETURN MAIL furiously regular  
deposits are carefully id  
38 175839 874 1  
+4.40000000000000E+001  
+8.42525200000000E+004 +4.00000000000000E-  
002 +2.00000000000000E-002 N O  
09/29/1996 11/17/1996 09/30/1996 COLLECT  
COD MAIL carefully final packages  
229 83580 8597 1  
+2.00000000000000E+001  
+3.12716000000000E+004 +2.00000000000000E-  
002 +3.00000000000000E-002 R F  
01/11/1994 01/31/1994 01/26/1994 DELIVER  
IN PERSON REG AIR final accounts  
integrate. blithe

229 128904 8905 2  
 +2.900000000000000E+001  
 +5.605410000000000E+004 +7.000000000000000E-  
 002 +0.000000000000000E+000 A F  
 03/15/1994 03/02/1994 03/26/1994 COLLECT  
 COD SHIP slyly pending Ti  
 229 78526 8527 3  
 +2.800000000000000E+001  
 +4.212656000000000E+004 +2.000000000000000E-  
 002 +2.000000000000000E-002 R F  
 02/10/1994 02/02/1994 03/10/1994 DELIVER  
 IN PERSON FOB final deposits  
 229 176948 1983 4  
 +3.000000000000000E+000  
 +6.074820000000000E+003 +2.000000000000000E-  
 002 +8.000000000000000E-002 R F  
 03/22/1994 03/24/1994 04/04/1994 DELIVER  
 IN PERSON REG AIR slyly silent deposits  
 sleep carefu  
 229 155180 211 5  
 +3.300000000000000E+001  
 +4.076094000000000E+004 +3.000000000000000E-  
 002 +6.000000000000000E-002 R F  
 03/25/1994 02/11/1994 04/13/1994 NONE  
 FOB asymptotes

10 record(s) selected.

### Query Substitution Parameters

Power stream Seed = 722222226  
 -- TPC TPC-H Parameter Substitution (Version  
 1.3.0)  
 -- using 722222226 as a seed to the RNG  
 Q1 DELTA 69  
 Q2 SIZE 39  
 TYPE COPPER  
 REGION AFRICA  
 Q3 SEGMENT BUILDING  
 DATE 1995-03-05  
 Q4 DATE 1993-10-01  
 Q5 REGION MIDDLE EAST  
 DATE 1995-01-01  
 Q6 DATE 1995-01-01  
 DISCOUNT 0.09  
 QUANTITY 24  
 Q7 NATION1 UNITED STATES  
 NATION2 INDIA  
 Q8 NATION INDIA  
 REGION ASIA  
 TYPE PROMO PLATED COPPER  
 Q9 COLOR thistle  
 Q10 DATE 1993-03-01  
 Q11 NATION IRAQ  
 FRACTION 0.0000010000

Q12 SHIPMODE1 SHIP  
 SHIPMODE2 MAIL  
 DATE 1993-01-01  
 Q13 WORD1 unusual  
 WORD2 packages  
 Q14 DATE 1993-06-01  
 Q15 DATE 1996-09-01  
 Q16 BRAND Brand#11  
 TYPE ECONOMY POLISHED  
 SIZE1 21  
 SIZE2 45  
 SIZE3 4  
 SIZE4 2  
 SIZE5 19  
 SIZE6 31  
 SIZE7 28  
 SIZE8 20  
 Q17 BRAND Brand#14  
 CONTAINER MED CAN  
 Q18 QUANTITY 315  
 Q19 BRAND1 Brand#34  
 BRAND2 Brand#11  
 BRAND3 Brand#22  
 QUANTITY1 7  
 QUANTITY2 11  
 QUANTITY3 26  
 Q20 COLOUR saddle  
 DATE 1993-01-01  
 NATION ARGENTINA  
 Q21 NATION ARGENTINA  
 Q22 I1 13  
 I2 19  
 I3 29  
 I4 17  
 I5 25  
 I6 16  
 I7 22  
 Throughput Stream = 1 Seed = 722222227  
 -- TPC TPC-H Parameter Substitution (Version  
 1.3.0)  
 -- using 722222227 as a seed to the RNG  
 Q1 DELTA 77  
 Q2 SIZE 27  
 TYPE STEEL  
 REGION EUROPE  
 Q3 SEGMENT HOUSEHOLD  
 DATE 1995-03-21  
 Q4 DATE 1996-05-01  
 Q5 REGION AFRICA  
 DATE 1995-01-01  
 Q6 DATE 1995-01-01  
 DISCOUNT 0.07  
 QUANTITY 24  
 Q7 NATION1 MOZAMBIQUE  
 NATION2 ALGERIA

Q8 NATION ALGERIA  
 REGION AFRICA  
 TYPE PROMO BURNISHED TIN  
 Q9 COLOR slate  
 Q10 DATE 1994-01-01  
 Q11 NATION UNITED STATES  
 FRACTION 0.0000010000  
 Q12 SHIPMODE1 FOB  
 SHIPMODE2 MAIL  
 DATE 1993-01-01  
 Q13 WORD1 unusual  
 WORD2 packages  
 Q14 DATE 1993-09-01  
 Q15 DATE 1994-05-01  
 Q16 BRAND Brand#51  
 TYPE STANDARD BRUSHED  
 SIZE1 28  
 SIZE2 11  
 SIZE3 39  
 SIZE4 6  
 SIZE5 37  
 SIZE6 22  
 SIZE7 2  
 SIZE8 7  
 Q17 BRAND Brand#11  
 CONTAINER JUMBO BOX  
 Q18 QUANTITY 312  
 Q19 BRAND1 Brand#42  
 BRAND2 Brand#44  
 BRAND3 Brand#21  
 QUANTITY1 3  
 QUANTITY2 12  
 QUANTITY3 22  
 Q20 COLOUR cream  
 DATE 1996-01-01  
 NATION MOZAMBIQUE  
 Q21 NATION ROMANIA  
 Q22 I1 30  
 I2 12  
 I3 28  
 I4 15  
 I5 13  
 I6 14  
 I7 18  
  
 Throughput Stream = 2 Seed = 722222228  
 -- TPC TPC-H Parameter Substitution (Version  
 1.3.0)  
 -- using 722222228 as a seed to the RNG  
 Q1 DELTA 85  
 Q2 SIZE 15  
 TYPE BRASS  
 REGION AMERICA  
 Q3 SEGMENT AUTOMOBILE  
 DATE 1995-03-07  
 Q4 DATE 1994-02-01

Q5 REGION AMERICA  
 DATE 1995-01-01  
 Q6 DATE 1995-01-01  
 DISCOUNT 0.04  
 QUANTITY 25  
 Q7 NATION1 INDIA  
 NATION2 PERU  
 Q8 NATION PERU  
 REGION AMERICA  
 TYPE ECONOMY BRUSHED TIN  
 Q9 COLOR saddle  
 Q10 DATE 1994-10-01  
 Q11 NATION JAPAN  
 FRACTION 0.0000010000  
 Q12 SHIPMODE1 MAIL  
 SHIPMODE2 AIR  
 DATE 1997-01-01  
 Q13 WORD1 unusual  
 WORD2 packages  
 Q14 DATE 1993-12-01  
 Q15 DATE 1996-12-01  
 Q16 BRAND Brand#31  
 TYPE LARGE BURNISHED  
 SIZE1 6  
 SIZE2 32  
 SIZE3 23  
 SIZE4 13  
 SIZE5 12  
 SIZE6 15  
 SIZE7 38  
 SIZE8 16  
 Q17 BRAND Brand#13  
 CONTAINER JUMBO PACK  
 Q18 QUANTITY 314  
 Q19 BRAND1 Brand#44  
 BRAND2 Brand#32  
 BRAND3 Brand#25  
 QUANTITY1 8  
 QUANTITY2 13  
 QUANTITY3 29  
 Q20 COLOUR orange  
 DATE 1995-01-01  
 NATION FRANCE  
 Q21 NATION IRAQ  
 Q22 I1 24  
 I2 15  
 I3 23  
 I4 28  
 I5 17  
 I6 32  
 I7 18  
  
 Throughput Stream = 3 Seed = 722222229  
 -- TPC TPC-H Parameter Substitution (Version  
 1.3.0)  
 -- using 722222229 as a seed to the RNG

Q1 DELTA 93  
 Q2 SIZE 2  
 TYPE NICKEL  
 REGION EUROPE  
 Q3 SEGMENT HOUSEHOLD  
 DATE 1995-03-24  
 Q4 DATE 1996-09-01  
 Q5 REGION EUROPE  
 DATE 1995-01-01  
 Q6 DATE 1995-01-01  
 DISCOUNT 0.02  
 QUANTITY 24  
 Q7 NATION1 ALGERIA  
 NATION2 INDONESIA  
 Q8 NATION INDONESIA  
 REGION ASIA  
 TYPE ECONOMY PLATED TIN  
 Q9 COLOR puff  
 Q10 DATE 1993-07-01  
 Q11 NATION ALGERIA  
 FRACTION 0.0000010000  
 Q12 SHIPMODE1 TRUCK  
 SHIPMODE2 FOB  
 DATE 1994-01-01  
 Q13 WORD1 unusual  
 WORD2 packages  
 Q14 DATE 1994-03-01  
 Q15 DATE 1994-09-01  
 Q16 BRAND Brand#12  
 TYPE PROMO PLATED  
 SIZE1 39  
 SIZE2 28  
 SIZE3 7  
 SIZE4 30  
 SIZE5 2  
 SIZE6 12  
 SIZE7 14  
 SIZE8 10  
 Q17 BRAND Brand#25  
 CONTAINER JUMBO CAN  
 Q18 QUANTITY 315  
 Q19 BRAND1 Brand#41  
 BRAND2 Brand#15  
 BRAND3 Brand#14  
 QUANTITY1 3  
 QUANTITY2 14  
 QUANTITY3 25  
 Q20 COLOUR beige  
 DATE 1993-01-01  
 NATION SAUDI ARABIA  
 Q21 NATION CANADA  
 Q22 I1 34  
 I2 17  
 I3 27  
 I4 16  
 I5 11

I6 25  
 I7 12  
 Throughput Stream = 4 Seed = 722222230  
 -- TPC TPC-H Parameter Substitution (Version 1.3.0)  
 -- using 722222230 as a seed to the RNG  
 Q1 DELTA 101  
 Q2 SIZE 40  
 TYPE TIN  
 REGION AMERICA  
 Q3 SEGMENT AUTOMOBILE  
 DATE 1995-03-09  
 Q4 DATE 1994-05-01  
 Q5 REGION MIDDLE EAST  
 DATE 1996-01-01  
 Q6 DATE 1996-01-01  
 DISCOUNT 0.07  
 QUANTITY 24  
 Q7 NATION1 PERU  
 NATION2 ARGENTINA  
 Q8 NATION ARGENTINA  
 REGION AMERICA  
 TYPE ECONOMY ANODIZED TIN  
 Q9 COLOR papaya  
 Q10 DATE 1994-04-01  
 Q11 NATION JORDAN  
 FRACTION 0.0000010000  
 Q12 SHIPMODE1 RAIL  
 SHIPMODE2 FOB  
 DATE 1994-01-01  
 Q13 WORD1 express  
 WORD2 requests  
 Q14 DATE 1994-06-01  
 Q15 DATE 1997-03-01  
 Q16 BRAND Brand#52  
 TYPE SMALL BRUSHED  
 SIZE1 42  
 SIZE2 24  
 SIZE3 32  
 SIZE4 22  
 SIZE5 5  
 SIZE6 31  
 SIZE7 15  
 SIZE8 16  
 Q17 BRAND Brand#22  
 CONTAINER WRAP BOX  
 Q18 QUANTITY 313  
 Q19 BRAND1 Brand#53  
 BRAND2 Brand#53  
 BRAND3 Brand#14  
 QUANTITY1 8  
 QUANTITY2 15  
 QUANTITY3 22  
 Q20 COLOUR lawn  
 DATE 1997-01-01

NATION IRAN  
 Q21 NATION SAUDI ARABIA  
 Q22 I1 20  
 I2 12  
 I3 25  
 I4 23  
 I5 30  
 I6 18  
 I7 15  
  
 Throughput Stream = 5 Seed = 722222231  
 -- TPC TPC-H Parameter Substitution (Version  
 1.3.0)  
 -- using 722222231 as a seed to the RNG  
 Q1 DELTA 109  
 Q2 SIZE 28  
 TYPE STEEL  
 REGION MIDDLE EAST  
 Q3 SEGMENT FURNITURE  
 DATE 1995-03-26  
 Q4 DATE 1996-12-01  
 Q5 REGION AFRICA  
 DATE 1996-01-01  
 Q6 DATE 1996-01-01  
 DISCOUNT 0.04  
 QUANTITY 25  
 Q7 NATION1 INDONESIA  
 NATION2 CHINA  
 Q8 NATION CHINA  
 REGION ASIA  
 TYPE LARGE POLISHED TIN  
 Q9 COLOR navajo  
 Q10 DATE 1995-01-01  
 Q11 NATION ARGENTINA  
 FRACTION 0.0000010000  
 Q12 SHIPMODE1 AIR  
 SHIPMODE2 FOB  
 DATE 1994-01-01  
 Q13 WORD1 express  
 WORD2 requests  
 Q14 DATE 1994-10-01  
 Q15 DATE 1994-12-01  
 Q16 BRAND Brand#32  
 TYPE ECONOMY ANODIZED  
 SIZE1 4  
 SIZE2 3  
 SIZE3 26  
 SIZE4 15  
 SIZE5 7  
 SIZE6 22  
 SIZE7 12  
 SIZE8 33  
 Q17 BRAND Brand#24  
 CONTAINER WRAP PACK  
 Q18 QUANTITY 314  
 Q19 BRAND1 Brand#55

BRAND2 Brand#31  
 BRAND3 Brand#13  
 QUANTITY1 4  
 QUANTITY2 16  
 QUANTITY3 29  
 Q20 COLOUR snow  
 DATE 1995-01-01  
 NATION ALGERIA  
 Q21 NATION JAPAN  
 Q22 I1 11  
 I2 10  
 I3 28  
 I4 13  
 I5 24  
 I6 31  
 I7 14

## Appendix D: Driver Source Code

### *ploaduf1*

```
#!/bin/ksh
RFpair=$1
~/tpcd/tools/load_line_uf $RFpair &
~/tpcd/tools/load_orders_uf $RFpair
```

### *ploaduf2*

```
#!/bin/ksh
RFpair=$1;
db2 connect to tpcd
db2 "load from delete.$RFpair of del modified by
coldel| fastparse messages /dev/null replace into
TPCDTEMP.ORDERS_DEL nonrecoverable
partitioned db config mode load_only
part_file_location /home/ufdata;"
db2 commit;
db2 connect reset
db2 terminate
```

### *load\_line\_uf*

```
#!/bin/ksh
RFpair=$1;
db2 connect to tpcd
db2 "load from lineitem.tbl.u$RFpair of del
modified by coldel| fastparse messages /dev/null
replace into TPCDTEMP.LINEITEM_new
nonrecoverable partitioned db config mode
load_only part_file_location /home/ufdata;"
db2 commit;
db2 connect reset
db2 terminate
```

### *load\_orders\_uf*

```
#!/bin/ksh
RFpair=$1;
db2 connect to tpcd
db2 "load from orders.tbl.u$RFpair of del modified
by coldel| fastparse messages /dev/null replace into
TPCDTEMP.ORDERS_new nonrecoverable
partitioned db config mode load_only
part_file_location /home/ufdata;"
db2 commit;
db2 connect reset
db2 terminate
```

### *preload\_uf.ksh*

```
#!/bin/ksh
# Please indicate which pair you want to use for the
preloading of the
# update functions. This pair can NOT be used for
the actual benchmark.
# In general we pre-load the pair which the largest
number. For example
# if we created 12 pairs, we'll preload pair 12. This
number is the parameter
# passed to ploaduf1 and ploaduf2 to load the data.
```

```
toolsDir=/home/tpch/tpcd/tools
```

```
${toolsDir}/ploaduf1 18
${toolsDir}/ploaduf2 18
```

```
db2 "connect to tpcd"
db2 "RUNSTATS ON TABLE
TPCDTEMP.LINEITEM_NEW WITH
DISTRIBUTION AND DETAILED INDEXES
ALL"
db2 "RUNSTATS ON TABLE
TPCDTEMP.ORDERS_NEW WITH
DISTRIBUTION AND DETAILED INDEXES
ALL"
db2 "RUNSTATS ON TABLE
TPCDTEMP.ORDERS_DEL WITH
DISTRIBUTION AND DETAILED INDEXES
ALL"
db2 "terminate"
```

### *runpower*

```
: # -*-Perl-*-
eval 'exec perl5 -S $0 ${1+"$@"}' # Horrible kludge
to convert this
if 0; # into a "portable" perl script
```

```
# usage runpower [UF]
# where UF is the optional parameter that says to run
the power test
# with the update functions. By default, the update
functions are not
# run
```

```
push(@INC, split(':', $ENV{'PATH'}));
```

```
# Get TPC-D specific environment variables
require 'getvars';
```

```
# Use the macros in here so that they can handle the
platform differences.
# macro.pl should be sourced from cmvc, other
people wrote and maintain it.
require "macro.pl";
```

```

require "tpcdmacro.pl";

# Make output unbuffered.
select(STDOUT);
$|= 1 ;

if (@ARGV > 0)
{
    $runUF=$ARGV[0];
}
else
{
    $runUF="no";
}

if (length($ENV{"TPCD_AUDIT_DIR"}) <= 0)
{
    die "TPCD_AUDIT_DIR environment variable not set\n";
}
if (length($ENV{"TPCD_RUN_DIR"}) <= 0)
{
    die "TPCD_RUN_DIR environment variable not set\n";
}
if (length($ENV{"TPCD_DBNAME"}) <= 0)
{
    die "TPCD_DBNAME environment variable not set\n";
}
if (length($ENV{"TPCD_RUNNUMBER"}) <= 0)
{
    die "TPCD_RUNNUMBER environment variable not set\n";
}
if (length($ENV{"TPCD_SF"}) <= 0)
{
    die "TPCD_SF environment variable not set\n";
}
if (length($ENV{"TPCD_PLATFORM"}) <= 0)
{
    die "TPCD_PLATFORM environment variable not set\n";
}
if (length($ENV{"TPCD_PATH_DELIM"}) <= 0)
{
    die "TPCD_PATH_DELIM environment variable not set\n";
}
if (length($ENV{"TPCD_PRODUCT"}) <= 0)
{
    die "TPCD_PRODUCT environment variable not set\n";
}
if (length($ENV{"TPCD_AUDIT"}) <= 0)
{
    die "Must set TPCD_AUDIT env't var. Real audit timing sequence run if yes\n";
}
if (length($ENV{"TPCD_PHYS_NODE"}) <= 0)
{
    die "TPCD_PHYS_NODE env't var not set\n";
}
if (length($ENV{"TPCD_LOG_DIR"}) <= 0)
{
    $ENV{"TPCD_LOG_DIR"} = "NULL";
}
if (length($ENV{"TPCD_MODE"}) <= 0)
{
    die "TPCD_MODE environment variable not set - uni/smp/mln \n";
}
if (length($ENV{"TPCD_ROOTPRIV"}) <= 0)
{
    die "TPCD_ROOTPRIV environment variable not set - yes/no \n";
}

#set up local variables
$runNum=$ENV{"TPCD_RUNNUMBER"};
$runDir=$ENV{"TPCD_RUN_DIR"};
$auditDir=$ENV{"TPCD_AUDIT_DIR"};
$dbname=$ENV{"TPCD_DBNAME"};
$sf=$ENV{"TPCD_SF"};
$platform=$ENV{"TPCD_PLATFORM"};
$delim=$ENV{"TPCD_PATH_DELIM"};
$gatherstats=$ENV{"TPCD_GATHER_STATS"};
$product=$ENV{"TPCD_PRODUCT"};
$RealAudit=$ENV{"TPCD_AUDIT"};
$inlistmax=$ENV{"TPCD_INLISTMAX"};
$pn=$ENV{"TPCD_PHYS_NODE"};
$logDir=$ENV{"TPCD_LOG_DIR"};
$rootPriv=$ENV{"TPCD_ROOTPRIV"};
$mode=$ENV{"TPCD_MODE"};
if (( $mode eq "uni" ) || ( $mode eq "smp" ))
{
    $all_in="once";
    $all_pn="once";
    $once="once";
}
else
{
    $all_in="all_in";
    $all_pn="all_pn";
    $once="once";
}

if ($inlistmax eq "default")
{
    $inlistmax = 400;
}
}

```



```

# the auditruns directory is where we have already
generate the sql files for the
# updates and the power tests

# append isolation level information about tpcdbatch
to the miso file
# the miso file is created here but appended to for
power and throughput
#information

$misofile="$runDir${delim}miso$runNum";
if ( -e $misofile )
{
    &rm("$misofile");
}
# if we are in real audit mode then we must start the
db manager now since
# there must be no activity on the database between
the time the build script
# has finished and the time the power test is started
if ( $RealAudit eq "yes" )
{
    system("db2start");
    system("db2 activate database $dbname");
}

if ( $RealAudit ne "yes" )
{
    system("db2 activate database $dbname");
}

#Report current log info to the run# directory in a
file called startLog.Info
system("perl getLogInfo.pl startLog");

open(MISO, ">$misofile") || die "Can't open
$misofile: $!\n";
$curTs = `perl gettimestamp "long"`;
print MISO "Timestamp and isolation level of
tpcdbatch before power run at : $curTs\n";
close(MISO);
if ( $product eq "pe" )
{
    system("db2 \"connect to $dbname\"; db2 \"select
name,creator,valid,unique_id,isolation from
sysibm.sysplan where name like 'TPCD%'\"; db2
connect reset; db2 terminate >>
$runDir${delim}miso$runNum ");
}
else
{
    &verifyTPCDBatch("$misofile","$dbname");
}

```

```

if ($platform eq "aix")
{
    # Create the sysunused file. This reports what
disks are attached, and which
# ones are being used. Its use spans both the
runpower and runthroughput tests
    system("echo \"The following disks are assigned to
the indicated volume groups\" >
$runDir/sysunused$runNum") && die "cannot
create $runDir/sysunused$runNum";

    system("lspv >> $runDir/sysunused$runNum");
    system("echo \"The following volume groups are
currently online\" >> $runDir/sysunused$runNum");
    $curTs = `perl gettimestamp "long"`;
    system("echo \"$curTs\" >>
$runDir/sysunused$runNum");
    system("lsvg -o >> $runDir/sysunused$runNum");
    # show the disks that are used/unused
    #system("getdisks \"Before the start of the Power
Test\");
}
else
{
    # for all other platforms
    system("echo Assume that all portions of the
system are used >>
$runDir${delim}sysunused$runNum");
}

&getConfig("p");
if ( $rootPriv eq "yes" )
{
    # get the o/s tuning parameters...currently AIX
only and only if your
# user has root privileges to run this
    &getOSTune("p");
}
if ($gatherstats eq "on")
{
    # gather vm io and net stats
    if ($platform eq "aix" || $platform eq "sun" ||
$platform eq "ptx" ||
    $platform eq "hp" || $platform eq "linux")
    {
        # gather vmstats and iostats (and net stats if in
mpp mode)
        system("perl getstats p &");
    }
    else
    {
        print "Stats gather not set up for current
platform $platform\n";
    }
}

```

```

    }
}

# print to screen what type of run is running and set
variables to run
# the query and update streams in parallel
if ($runUF ne "UF")
{
    $semcontrol = "off";
    print "Beginning power stream....no update
functions\n";

    $streamEx = "";
    $streamExNT = "";
}
else
{
    $semcontrol = "on";
    print "Beginning power stream....with update
functions\n";
    if ( $platform eq "nt" )
    {
        $streamExNT = "start /b";
        $streamEx = "";
    }
    else
    {
        $streamExNT = "";
        $streamEx = "&";
    }
}

# bbe This new line (below) runs queries for power
test

print "Starting tpcdbatch...\n";
$ret=system("$streamExNT
$auditDir${delim}auditruns${delim}tpcdbatch -d
$dbname -f $runDir${delim}qtextpow.sql -r on -b
on -s $sf -u p1 -m $inlistmax -n 0 -p $semcontrol
$streamEx");

if ( $runUF eq "UF" )
{
    $ret2 =
system("$auditDir${delim}auditruns${delim}tpcdba
tch -d $dbname -f $runDir${delim}qtextqf.sql -r on
-b on -s $sf -u p2 -m $inlistmax -n 0");
}
else
{
    $ret2 = 0; # If UFs were not running, then the
stream cannot fail
}
}

if (($ret2 == 0) && ($ret == 0))
{
    print "Power stream completed succesfully.\n";
}
else
{
    print "Power stream failed. ret=$ret\n";
}

if ($platform eq "aix")
{
    # show that the same disks are still used or unused
    # system("getdisks \"After completion of the
Power Test\");

    #clean up
}
if ($gatherstats eq "on")
{
    # gather vm io and net stats
    if ($platform eq "aix" || $platform eq "sun" ||
$platform eq "ptx" || $platform eq "linux")
    {
        # kill the stats that were being gathered
        if ($platform eq "ptx")
        {
            $src= `perl5 zap "-f" "sar"`;
            $src= `perl5 zap "-f" "sadc"`;
        }
        else
        {
            $src= `perl5 zap "-f" "vmstat"`;
            $src= `perl5 zap "-f" "iostat"`;
        }
    }
    if ( $pn > 1 )
    {
        $src= `perl5 zap "-f" "netstat"`;
    }
    $src= `perl5 zap "-f" "getstats"`;
}
}

open(MISO, ">>$misofile") || die "Can't open
$misofile: $!\n";
$curTs = `perl gettimestamp "long"`;
print MISO "Timestamp and isolation level of
tpcdbatch after power run at : $curTs\n";
close(MISO);

if ( $product eq "pe" )
{
    system("db2 \"connect to $dbname\"; db2 \"select
name,creator,valid,unique_id,isolation from
sysibm.sysplan where name like 'TPCD%'\";db2

```

```

connect reset;db2 terminate >>
$runDir${delim}miso$runNum");
}
else
{
    &verifyTPCDBatch("$misofile","$dbname");
}
if ( $RealAudit ne "yes" )
{
    $curTs = `perl gettimestamp "short"`;
    # grab the db and dbm snapshot before we
deactivate
    system("db2 get snapshot for all on $dbname >
$runDir${delim}dbrun$runNum.snap.$curTs");
    system("db2 get snapshot for database manager
>> $runDir${delim}dbrun$runNum.snap.$curTs");
}

#####

# now copy the reports from the count of streams
files into one final file
&cat("$runDir${delim}pstrcnt*","$runDir${delim}
mpstrcnt$runNum");
#(NOTE: there is a dependancy that this mpstrcnt
file exist before the
# calcmetrics.pl script is called, both because it is
used as input for
# calcmetrics.pl, and because the output from
calcmetrics is used as
# the trigger for watchstreams to complete, and
watchstreams cats its
# output at the end of the mstrcnt file.

# generate the mpinter?.metrics file in the run
directory
#require 'calcmetricsp.pl';
if ( $runUF eq "UF" )
{
    system("perl calcmetricsp.pl UF");
}
else
{
    system("perl calcmetricsp.pl");
}

# concatenate all the throughput inter files that were
used to
# generate these results into the calcmetrics output
file (mpinterX.metrics)
#cd $TPCD_RUN_DIR
&cat("$runDir${delim}mpqinter*","$runDir${delim}
mpinter$runNum.metrics");

if ($runUF eq "UF" ) {
&cat("$runDir${delim}mpufinter*","$runDir${delim}
mpinter$runNum.metrics");
}
}
}
}
}

#####

# do not stop the database after the power test
#if ( $RealAudit ne "yes" )
#{
#   system("db2stop");
#}

1;

sub getConfig
{
    $stesttype=${_}[0];
    print "Getting database configuration.\n";

    $dbtunefile="$runDir${delim}m${testtype}dbtune$
{runNum}";
    open(DBTUNE, ">$dbtunefile") || die "Can't open
$dbtunefile: ${!}\n";
    $timestamp=`perl gettimestamp "long"`;
    print DBTUNE "Database and Database manager
configuration taken at : $timestamp";
    close(DBTUNE);
    system("db2level >> $dbtunefile");
    system("db2 get database configuration for
$dbname >> $dbtunefile");
    system("db2 get database manager configuration
>> $dbtunefile");
    system("db2set >> $dbtunefile");
    if (( $mode eq "mln" ) || ( $mode eq "mpp" ))
    {
        $cfgfile="$runDir${delim}dbtune${runNum}. ";
        #removed by Alex due to hang
        #system("db2_all |\|" typeset -i ln=##; db2 get db
cfg for $dbname > $cfgfile${ln} ; db2 get dbm cfg
>> $cfgfile${ln}; db2set >> $cfgfile${ln}; db2
terminate """);
    }
}
}
}
}

```

```

sub getOSTune
{
  $stesttype=$_[0];
  if ( $platform eq "aix" )
  {
    print "Getting OS and VMdatabase
configuration.\n";

    $ostunefile="$runDir${delim}m${testtype}ostune$
{runNum}";
    open(OSTUNE, ">$ostunefile") || die "Can't
open $ostunefile: $!\n";
    $timestamp=`perl gettimestamp "long"`;
    print OSTUNE "Operating System and Virtual
Memory configuration taken at : $timestamp";
    close(OSTUNE);

    system("${delim}usr${delim}samples${delim}kern
el${delim}schedtune >> $ostunefile");

    system("${delim}usr${delim}samples${delim}kern
el${delim}vmtune >> $ostunefile");
  }
  else
  {
    print "OS parameters retrieval not supported for
$platform \n";
  }
}

sub verifyTPCDBatch
{
  $logfile=$_[0];
  $dbname=$_[1];
  $file="verifytpcdbatch.clp";
  open(VERTBL, ">$file") || die "Can't open $file:
$!\n";
  print VERTBL "connect to $dbname;\n";
  print VERTBL "select
name,creator,valid,last_bind_time,isolation from
sysibm.sysplan where name like 'TPCD%';\n";
  print VERTBL "connect reset;\n";
  print VERTBL "terminate;\n";
  close(VERTBL);
  system("db2 -vtf $file >> $logfile");
}
-

```

### ***runthroughput***

```
: # -*Perl*-
```

```

eval `exec perl5 -S $0 ${1+"$@"}` # Horrible kludge
to convert this
  if 0;          # into a "portable" perl script

# usage runthroughput [UF]
# where UF is the optional parameter that says to run
the throughput test
# with the update functions. By default, the update
functions are not
# run
# If UF is not supplied and a number is supplied,
then that number is taken
# as the number of concurrent throughput streams to
run. This is also optional

push(@INC, split(':', $ENV{'PATH'}));

# Get TPC-D specific environment variables
require 'getvars';

# Use the macros in here so that they can handle the
platform differences.
# macro.pl should be sourced from cmvc, other
people wrote and maintain it.
require "macro.pl";
require "tpcdmacro.pl";

$runUF="no";
if (@ARGV > 0)
{
  if ($ARGV[0] eq "UF")
  {
    $runUF=$ARGV[0];
  }
}

@reqVars = ("TPCD_AUDIT_DIR",
            "TPCD_RUN_DIR",
            "TPCD_DBNAME",
            "TPCD_RUNNUMBER",
            "TPCD_SF",
            "TPCD_PLATFORM",
            "TPCD_PATH_DELIM",
            "TPCD_PRODUCT",
            "TPCD_AUDIT",
            "TPCD_PHYS_NODE",
            "TPCD_MODE",
            "TPCD_ROOTPRIV",
            "TPCD_NUMSTREAM");

&setVar(@reqVars, "ERROR");

if (length($ENV{"TPCD_LOG_DIR"}) <= 0)
{

```

```

    $ENV{"TPCD_LOG_DIR"} = "NULL";
}

#set up local variables
$runNum=$ENV{"TPCD_RUNNUMBER"};
$numStream=$ENV{"TPCD_NUMSTREAM"};
$runDir=$ENV{"TPCD_RUN_DIR"};
$auditDir=$ENV{"TPCD_AUDIT_DIR"};
$dbname=$ENV{"TPCD_DBNAME"};
$sf=$ENV{"TPCD_SF"};
$product=$ENV{"TPCD_PRODUCT"};
$platform=$ENV{"TPCD_PLATFORM"};
$delim=$ENV{"TPCD_PATH_DELIM"};
$RealAudit=$ENV{"TPCD_AUDIT"};
$inlistmax=$ENV{"TPCD_INLISTMAX"};
$gatherstats=$ENV{"TPCD_GATHER_STATS"};
$logDir=$ENV{"TPCD_LOG_DIR"};
$rootPriv=$ENV{"TPCD_ROOTPRIV"};
$mode=$ENV{"TPCD_MODE"};

$path="$auditDir${delim}auditruns";

if (( $mode eq "uni" ) || ( $mode eq "smp" ))
{
    $all_in="once";
    $all_pn="once";
    $once="once";
}
else
{
    $all_in="all_in";
    $all_pn="all_pn";
    $once="once";
}

# return 1 if the given pattern(parameter $_[0])
matches any file
sub existfile {
    if ($platform eq "aix" || $platform eq "sun" ||
$platform eq "ptx" || $platform eq "linux")
    {
        `ls $_[0] 2> /dev/null | wc -l` + 0 != 0;
    }
    else
    {
        `dir /b $_[0] 2> NUL | wc -l` + 0 != 0;
    }
}

if ($inlistmax eq "default")
{
    $inlistmax = 400;
}

# no longer stop and start the dbm between runs
when not in realaudit mode

```

```

# if ( $RealAudit ne "yes" )
#{
# # if we are not in real audit mode then we must
start the db manager now
# system("db2start");
# # activate the database
# system("db2 activate database $dbname");
#}

$misofile="$runDir${delim}miso$runNum";
# append isolation level information about tpcdbatch
to the miso file
open(MISO, ">>$misofile") || die "Can't open
$misofile: $!\n";
$curTs = `perl gettimestamp "long"`;
print MISO "Timestamp and isolation level of
tpcdbatch before throughput run at : $curTs\n";
close(MISO);

if ( $product eq "pe" )
{
    system("db2 \"connect to $dbname\"; db2 \"select
name,creator,valid,unique_id,isolation from
sysibm.sysplan where name like 'TPCD%'\" >>
$runDir${delim}miso$runNum ");
}
else
{
    &verifyTPCDBatch("$misofile","$dbname");
}

# kick off the script that will monitor for the
database applications during
# the running of the throughput tests. This will quit
when the mtinterX.metrics
# (where X=runnumber) file has been created.

# set variables to run streams in parallel
if ( $platform eq "nt" )
{
    $streamExNT = "start /b";
    $streamEx = "";
}
else
{
    $streamExNT = "";
    $streamEx = "&";
}

if ( $platform eq "aix" || $platform eq "sun" ||
$platform eq "nt" || $platform eq "hp" || $platform eq
"linux")
{
    system("$streamExNT perl watchstreams
$streamEx");
}
else

```

```

{
    die "platform not supported, can't start
watchstreams in background";
}

# show the disks that are used/unused
#if ($platform eq "aix")
#{
#   system("getdisks \"Before the start of the
Throughput Test\");
#}

if ($gatherstats eq "on")
{
    # gather vm io and net stats
    if ($platform eq "aix" || $platform eq "sun" ||
$platform eq "ptx" || $platform eq "hp" || $platform
eq "linux")
    {
        # gather vmstats and iostats (and net stats if in
mpp mode)
        system("perl getstats t &");
    }
    else
    {
        print "Stats gather not set up for current
platform $platform\n";
    }
}

# the auditruns directory is where we have already
generated the sql files
# for the updates and the power tests

$loopStream=1;

for ( $loopStream = 1; $loopStream <=
$numStream; $loopStream++)
{
    print "starting stream $loopStream\n";
    system("echo Executing stream $loopStream out
of $numStream.");
    # run the queries
    if ( $platform eq "aix" || $platform eq "sun" ||
$platform eq "nt" || $platform eq "ptx" ||
$platform eq "hp" || $platform eq "linux")
    {
        system("$streamExNT $path${delim}tpcdbatch
-d $dbname -f
$runDir${delim}qtextt$loopStream.sql -r on -b on -s
$sf -u t1 -m $inlistmax -n $loopStream $streamEx");
    }
    else
    {
        die "platform $platform not supported yet";
    }
}

```

```

}
}

# run the update function stream....this will wait
until the queries have
# completed to kick off the updates
print "starting update stream\n";

if ($runUF eq "no") {

$ret=system("$auditDir${delim}auditruns${delim}t
pcdbatch -d $dbname -f $runDir${delim}quft.sql -r
on -b on -s $sf -u t -m $inlistmax -n $numStream");
}
else {

$ret=system("$auditDir${delim}auditruns${delim}t
pcdbatch -d $dbname -f $runDir${delim}quft.sql -r
on -b on -s $sf -u t2 -m $inlistmax -n $numStream");
}
print "update stream done\n";

&getConfig("t");
if ( $rootPriv eq "yes" )
{
    # get the o/s tuning parameters...currently AIX
only and only if your
# user has root privileges to run this
&getOSTune("t");
}

#if ($platform eq "aix")
#{
# show the disks that are used/unused
#   system("getdisks \"After the completion of the
Throughput Test\");
#}
if ($gatherstats eq "on")
{
    # gather vm io and net stats
    if ($platform eq "aix" || $platform eq "sun" ||
$platform eq "ptx" || $platform eq "linux")
    {
        # kill the stats that were being gathered
        if ($platform eq "ptx")
        {
            $src= `perl5 zap "-f" "sar"`;
            $src= `perl5 zap "-f" "sadc"`;
        }
        else
        {
            $src= `perl5 zap "-f" "vmstat"`;
            $src= `perl5 zap "-f" "iostat"`;
        }
    }
    if ( $pn > 1 )

```

```

        {
            $src= `perl5 zap "-f" "netstat"`;
        }
        $src= `perl5 zap "-f" "getstats"`;
    }
}

open(MISO, ">>$misofile") || die "Can't open
$misofile: $!\n";
$curTs = `perl gettimestamp "long"`;
print MISO "Timestamp and isolation level of
tpcdbatch after throughput run at : $curTs\n";
close(MISO);

if ( $product eq "pe" )
{
    system("db2 \\"connect to $dbname\"; db2 \\"select
name,creator,valid,unique_id,isolation from
sysibm.sysplan where name like 'TPCD%\" >>
$runDir${delim}miso$runNum\"");
}
else
{
    &verifyTPCDBatch("$misofile","$dbname");
}

if ( $RealAudit ne "yes" )
{
    $curTs = `perl gettimestamp "short"`;
    # grab the db and dbm snapshot before we
deactivate
    system("db2 get snapshot for all on $dbname >
$runDir${delim}dbTrun$runNum.snap.$curTs");
    system("db2 get snapshot for database manager
>> $runDir${delim}dbTrun$runNum.snap.$curTs");
}

# now copy the reports from the count of streams
files into one final file
&cat("$runDir${delim}strent*","$runDir${delim}m
strent$runNum");
#(NOTE: there is a dependency that this mstrent file
exist before the
# calcmetrics.pl script is called, both because it is
used as input for
# calcmetrics.pl, and because the output from
calcmetrics is used as
# the trigger for watchstreams to complete, and
watchstreams cats its
# output at the end of the mstrent file.

# generate the mtinter?.metrics file in the run
directory
#require 'calcmetrics.pl';

if ( $runUF ne "no" )
{
    system("perl calcmetrics.pl $numStream UF");
}
else
{
    system("perl calcmetrics.pl $numStream");
}

# concatenate all the throughput inter files that were
used to
# generate these results into the calcmetrics output
file (mtinterX.metrics)
#cd $TPCD_RUN_DIR
&cat("$runDir${delim}mts*inter*","$runDir${deli
m}mtinter$runNum.metrics");

if ($runUF ne "no") {

&cat("$runDir${delim}mtufinter*","$runDir${deli
m}mtinter$runNum.metrics");
}

if (&existfile("$runDir${delim}mp*")) {
    # generate the mplot stuff
    system("perl gen_mplot");

    # generate the mlog information file
    require 'buildmlog';
}

#if ($runUF eq "no") {
# &rm("$runDir${delim}mtuf*");
#}

# deactivate the database this needs to remain at the
end of run throughput so
# asynchronous writing of the log files completes.
system("db2 deactivate database $dbname");
$src=&dodb_noconn("db2 get db cfg for $dbname |
grep -i log >>
$runDir${delim}endLog.Info",$all_in);
if ( $logDir ne "NULL" )
{
    $src=&dodb_noconn("$dircmd $logDir >>
$runDir${delim}endLog.Info",$all_in);
}

#system("db2_all \}]db2 get db cfg for tpcd | grep -i
log >> $runDir${delim}endLog.Info ; db2
terminate\ ");
#system("ls -ltra /node??vg.log/NODE00* >>
$runDir${delim}endLog.Info");

#Create Catalog info
$src = system("perl catinfo.pl p");

```

```

if ( $rc != 0 )
{
    warn "catinfo failed!!!\n";
}

#Report current log info to the run# directory in a
file called endLog.Info
system("perl getLogInfo.pl endLog");

# if we are in audit mode we must do a db2stop at
the end of the power/throughput run
if ( $RealAudit eq "yes" )
{
    system("db2stop");
}

1;

sub getConfig
{
    $testtype=$_[0];
    print "Getting database configuration.\n";

$dbtunefile="$runDir${delim}m${testtype}dbtune$
{runNum}";
    open(DBTUNE, ">$dbtunefile") || die "Can't open
$dbtunefile: $!\n";
    $timestamp=`perl gettimestamp "long"`;
    print DBTUNE "Database and Database manager
configuration taken at : $timestamp";
    close(DBTUNE);
    system("db2level >> $dbtunefile");
    system("db2 get database configuration for
$dbname >> $dbtunefile");
    system("db2 get database manager configuration
>> $dbtunefile");
    system("db2set >> $dbtunefile");
}

sub getOSTune
{
    $testtype=$_[0];
    if ( $platform eq "aix" || $platform eq "linux")
    {
        print "Getting OS and VMdatabase
configuration.\n";

        $ostunefile="$runDir${delim}m${testtype}ostune$
{runNum}";
        open(OSTUNE, ">$ostunefile") || die "Can't
open $ostunefile: $!\n";
        $timestamp=`perl gettimestamp "long"`;
        print OSTUNE "Operating System and Virtual
Memory configuration taken at : $timestamp";

```

```

        close(OSTUNE);

system("${delim}usr${delim}samples${delim}kern
el${delim}schedtune >> $ostunefile");

system("${delim}usr${delim}samples${delim}kern
el${delim}vmtune >> $ostunefile");
    }
    else
    {
        print "OS parameters retrieval not supported for
$platform \n";
    }
}

sub verifyTPCDBatch
{
    $logfile=$_[0];
    $dbname=$_[1];
    $file="verifytpcdbatch.clp";
    open(VERTBL, ">$file") || die "Can't open $file:
$!\n";
    print VERTBL "connect to $dbname;\n";
    print VERTBL "select
name,creator,valid,last_bind_time,isolation from
sysibm.sysplan where name like 'TPCD%';\n";
    print VERTBL "connect reset;\n";
    print VERTBL "terminate;\n";
    close(VERTBL);
    system("db2 -vtf $file >> $logfile");
}
-

```

### ***tpcdbatch.h***

```

/*****
*****
*
*   TPCDBATCH.H
*
*   Revision History:
*
*   27 may 99 bbe from (24 nov 98 jen)
fixNTtimestamp - fixed NT timestamp to print
millisecond correctly
*   27 may 99 bbe from (10 dec 98 jen) SUN - added
Haider's changes necessary for SUN
*   17 jun 99 jen   Increased version to 5.1
*   10 aug 99 bbe  Increased version to 5.2
*   13 aug 99 bbe  Increased version to 5.3
*   18 mar 02 ken  Increased version to 5.7
*****/

```



```

/** Necessary header files */

/** System header files */
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <math.h>
#include <fcntl.h>          /* SUN bbe */

#include <time.h>
#include <ctype.h>
#if (defined(SQLAIX) || defined(SQLPTX) ||
defined(LINUX) || defined(SQLHP))
#include <unistd.h>        /* SUN */
#include <sys/stat.h>      /* SUN */
#endif
#if ((defined(SQLAIX) || defined(SQLPTX)) &&
!defined(LINUX))
#include <sys/vnode.h>     /* SUN */
#endif
#ifndef SQLWINT
#include <sys/time.h>
/*@d33143aha*/
#include <sys/ipc.h>
#include <sys/sem.h>
#if (!defined(SQLPTX) && !defined(LINUX)&&
!defined(SQLHP))
#include <sys/mode.h>
#endif
#include <sys/timeb.h>
#include <sys/types.h>
#else
#include <windows.h>
#include <sys\timeb.h>
#endif
#include <errno.h>

/** External header files */
#include "sqlda.h"
#include "sqlenv.h"
#include "sql.h"
#include "sqlmon.h"
#include "sqlca.h"
#include "sqlutil.h"
#include "sqlcodes.h"

/** Internal header files */
/** #ifdef __cplusplus */
/** #include "sqlz.h" */
/** #include "sqlzcopy.h" */
/** #endif */

```

```

/*****
*****/
/* Define synonyms here
*/
/*****
*****/
#define TPCDBATCH_VERSION "5.7"

#define TPCDBATCH_NONSQL 10
/* @d23684 tjt */
#define TPCDBATCH_SELECT 20
#define TPCDBATCH_NONSELECT 30
#define TPCDBATCH_EOBLOCK 40
/* @d30369 tjt */
#define TPCDBATCH_INSERT 50
#define TPCDBATCH_DELETE 60

#define TPCDBATCH_MAX_COLS 100
/* @d30369 tjt */

#define TPCDBATCH_CHAR char

#define TPCDBATCH_PRINT_FLOAT_WIDTH
20
/* kmw - allow 15 whole digit for %#.3f format */
/* - note: use > 18, size of long indentifier so that
it will */
/* be larger than any column heading
*/
#define TPCDBATCH_PRINT_FLOAT_MAX
1e15 /* kmw */
/* #define TPCD_PREPARETIME 1 */ /* for
separate prep/exec on uf jen 1106 */

#ifndef SQLWINT
#define PATH_DELIM '\\'
#define sleep(a) Sleep((a)*1000)
#else
#define PATH_DELIM '/'
#endif

#define PARALLEL_UPDATES 1

#ifndef PARALLEL_UPDATES
#define UF1OUTSTREAMPATTERN
"%s%cuf1.%02d.%d.out"
#define TPCD_NONPARTITIONED
#define UF2OUTSTREAMPATTERN
"%s%cuf2.%02d.%d.out"
#else
/* kelly add same as NONPART. */
#define UF2OUTSTREAMPATTERN
"%s%cuf2.%02d.%d.out"
/* kelly ... take this out ... should be same name as
for non-partitioned

```

```

#define UF2OUTSTREAMPATTERN
"%s%cuf2.%02d.%d.%d.out" /* /*DELjen add
delchunk*/
#endif
#define BUFSIZE 1024
#endif

#define T_STAMP_FORM_1 1
#define T_STAMP_FORM_2 2
/* jen TIME_ACC start */
#define T_STAMP_FORM_3 3
#define T_STAMP_1LEN 17
#if defined (SQLUNIX) || defined (SQLAIX) ||
defined (SQLHP)
#define T_STAMP_3LEN 24
#elif defined (SQLOS2) || defined (SQLWINT) ||
defined (SQLWIN) || defined (SQLDOS)
#define T_STAMP_3LEN 21 /* WIN NT
timestamp fix bbe */
#else
#error Unknown operating system
#endif
/* jen TIME_ACC start */

#define BLANKS "\0"
#define READMODE "r\0"
#define WRITEMODE "w\0"
#define APPENDMODE "a\0"
#define mem_error(xx)
{ fprintf(stderr, "\n--Out of memory when
%s.\n",xx); }
/* Display out-of-memory and end */

#define TPCDBATCH_MIN(x,y) ((x) < (y) ?
(x) : (y))
/** Returns the smaller of both x and y */
#define TPCDBATCH_MAX(x,y) ((x) > (y)
? (x) : (y)) /* @d22817 tjt */
/** Returns the larger of both x and y */

/** Defines needed for decimal conversion */
#define SQLZ_DYNLINK
#define TRUE 1
#define LEFT 1
#define RIGHT 0
#define FALSE 0
#define sqlrx_get_left_nibble(byte) (((unsigned
char)(byte)) >> 4)

#define sqlrx_get_right_nibble(byte) ((unsigned
char) (byte & '\x0f'))
#define SQL_MAXDECIMAL 31

```

```

#define SQLRX_PREFERRED_PLUS 0x0c
/** Timer-necessary defines for portability */
#if defined (SQLOS2) || defined (SQLWINT) ||
defined (SQLWIN) || defined (SQLDOS)
typedef struct timeb Timer_struct;
#elif defined (SQLUNIX) || defined (SQLAIX) ||
defined (SQLHP) /*TIMER jen*/
typedef struct timeval Timer_struct;
#else
#error Unknown operating system
#endif

/* sleep time between starting subsequent
tpcdbatches running UF1 and UF2 */
#define UF1_SLEEP 1
#define UF2_SLEEP 1
#define UF_DEADLOCK_SLEEP 1 /* sleep
between deadlock retries in UF1,UF2 */

#define MAXWAIT 50 /* maximum retries for
deadlock encounters */

#define DEBUG 0 /* to be set to 1 for diagnostic
purposes if needed */
/* #define UF1DEBUG 1 */
/* #define UF2DEBUG 1 */

```

### ***tpcdbatch.sqc***

```

/*****
*****
*
* TPCDBATCH.SQC
*
* Revision History:
*
* 21 Dec 95 jen Corrected calculation of geometric
mean to include in the
* count of statements the update functions.
* 03 Jan 96 jen Corrected calculation of arithmetic
mean to not include the
* timings for the update functions. (only
want query timings
* as part of arithmetic mean)
* 15 Jan 96 jen Added extra timestamps to the
update functions.
* 22 Jan 96 jen Get rid of checking of
short_time...we always use the long
* timings.
* Fixed timings to print query/uf times
rounded up to 0.1 seconds
* and uses these rounded time values in
subsequent calculations

```

\* Fixed bug where last seed in mseedme file wasn't getting read

\* correctly - EOF processing done too soon.

\* 22 Feb 96 kbs port to NT

\* 26 Mar 96 kbs Fix to avoid counting UFs as queries for min max

\* 27 Jun 97 wlc Temporarily fixed deadlock problems when doing UF1, UF2

\* 30 Jul 97 wlc Add in support for load\_update and TPCD\_SPLIT\_DELETES

\* 13 Aug 97 wlc fixed UF1 log file formatting problem,

\* using TPCD\_TMP\_DIR for temp files instead of /tmp,

\* make summary table fit in 80-column,

\* fixed UF2 # of deleted rows reporting problem

\* 18 Aug 97 wlc added command line support for inlistmax

\* 20 Aug 97 wlc added support for runthroughput without UF

\* 27 Aug 97 aph Replaced hardcoded 'tpcaudit' with getenv("TPCD\_AUDIT\_DIR")

\* 05 Sep 97 wlc fixing free() problem in NT

\* 26 Sep 97 kmw change FLOAT processing in echo\_sqlda and print\_headings

\* 10 Oct 97 jen add lock table in share mode for staging tables

\* 21 Oct 97 jen added explicit rollback on failure of uf1

\* 27 Oct 97 jen don't update TPCD.xxxx.update.pair.num if not running UFs in throughput run

\* 01 Nov 97 jen temp code to do a prep then execute stmt in UFs so we can get timings

\* 03 Nov 97 jen realigned UF code for readability

\* pushed UF2 commit into loop for inlistmax

\* fixed UF2 code so rollback performed

\* 04 Nov 97 jen Added code to handle vldb

\* 06 Nov 97 jen Commented out temp code for prep then execute stmts using

\* TPCD\_PREPARETIME def

\* Updated version number to 2.2

\* send all output during update functions to output files, not

\* stderr

\* 10 Nov 97 jen jenCI Updated version number to 2.3

\* Added handling of TPCD\_CONCURRENT\_INSERTS. Change control of

\* chunk processing to use the concurrent\_inserts value as the control. Now the inserts will be run in TPCD\_CONCURRENT\_INSERTS sets, each having concurrent\_inserts/

\* 13 Nov 97 jen jen DEADLOCK. Fixed bug that Alex found where deadlock count (maxwait) was incremented on every execution of the stmt as opposed to just when deadlock really happened.

\* 14 Nov 97 jen jenSEM - fix up error reporting on semaphore failure

\* sem\_op now returns failure to caller so caller can report where failure has happened.

\* Forced dbname to be upper case, an all other parts of update pair number to be lowercase

\* 15 Nov 97 jen SEED Reworked code to grab the seed from the seed file. Now reusing seeds between runs, so power run will always use first seed, throughput will use the 2nd - #stream+1 seeds

\* 13 Jan 98 jen LONG Increase stmt\_str to be able to hold inlists with larger order key numbers

\* 04 Mar 98 jen IMPORT added support for TPCD\_UPDATE\_IMPORT to choose whether using import or load api's for loading data into the staging tables

\* 04 Mar 98 jen TIMER changed from using gettimer to gettimeofday for unix

\* 01 Apr 98 jen Fixed IMPORT code to do the proper checking on strcmp (ie !strcmp)

\* 01 Apr 98 jen removed code to handle vldb - not needed

\* Upgraded version to 2.4 for ( chunk

\* 01 Apr 98 jen Fixed up import code on NT so the variable is recognized in the children

\* 25 May 98 sks Reworked some of the environment variable code so consolidate as much as possible. Not all complete because of differences in the way nt and AIX calls (and starts stuff in background) for UFs

\* 29 May 98 jen REUSE\_STAGE Changed UF1 so we reuse the same staging tables instead of having a new set for each update pair

\* 06 Jul 98 jen Removed locking of staging tables since they are created with

```

*          locksize table now
* 06 jul 98 jen 912RETRY - added code to retry
query execution on 912 as well
*          as 911
* 07 jul 98 jen Fixed summary_table() so 1000x
adjustment not based on UF (setting
*          of max and min pointers
*          Added generic SleepSome function to
handle NT vs AIX sleep differences
* 01 apr 98 djd Added change to permit the use of
table functions for UF1.
*          to enable this set
TPCD_UPDATE_IMPORT to tf in TPCD.SETUP
file.
*          MERGED this into base copy on Jul 07
* 10 jul 98 jen haider's fix for 'outstream' var for
error processing in
*          runUF1_fn and runUF2_fn
*          Updated version to 2.5
* 25 sep 98 jen Added stream number printing into
mpqry* files and increases
*          accuracy of timestamp in mpqry (and
mts*qry*) files
* 06 oct 98 jen TIME_ACC Added accuracy of
timestamp in mpqry (and mts*qry*)
*          files. Cleaned up misuse of Sleep and
flushed buffers on
*          deadlocks
* 19 oct 98 kbs fix UF2_fn to correctly count rows
deleted in case of deadlock
* 20 oct 98 kbs rewrite UF2 and UF2_fn for static
SQL with staging table
* 23 oct 98 jen Cleaned up retrying of
order/lineitem on lineitem deadlock in UF1
* 24 oct 98 jen Used load_uf1 and load_uf2 instead
of general load_updates
* 26 oct 98 kbs inject the UF1 with a single staging
table
* 02 nov 98 jen Fixed processing of multiple
chunks in uf2 so don't duplicate
* 21 nov 98 kmw Fixed BIGINT
* 05 dec 98 aph Moved runUF1_fn() and
runUF2_fn() into a separate file tpcdUF.sqc
*          so that it can be bound separately with a
different isolation level.
* 21 dec 98 aph Integrated Jennifer's QppD
calculation (rounding & adjustment) fixes.
* 22 dec 98 aph For UFs during Throughput run,
defer CONNECT until children launched.
* 28 dec 98 aph Removed error_check() call after
CONNECT RESET
* 29 dec 98 aph For UFs do not COMMIT in
tpcdbatch.sqc. COMMITs happen in tpcdUF.sqc.
* 18 jan 99 kal replaced header with #include
"tpcdbatch.h"

```

```

* 27 may 99 bbeaton from (03 mar 99 jen) Fixed
SUN fix that wasn't compatible with
*          NT (using %D %T instead of %x %X for
strftime)
* 16 jun 99 jen Added missing LPCTSTR cast of
semaphore file name for NT
* 17 jun 99 jen SEMA Changes semaphore file for
update functions to look for tpcd.setup
*          not for the orders.*** update data file
* 21 jul 99 bbeaton Added semaphore control that
allows runpower to be run as two
*          separate streams (update and query).
This involves the use of
*          two semaphores to be used as it executes
in three different
*          sections. The first is the update inserts.
The next is the query
*          stream which is started with the update
stream, but waits until
*          the inserts are complete. The third
section is the update deletes
*          which execute after the queries are
complete.
* 21 jul 99 bbeaton Added functions to handle
semaphore creation, control, etc.
* 21 jul 99 bbeaton Modified output to mp*inter
files. It now only outputs
*          intermediate data that will be calculated
by calcmetric.pl. This
*          is a result of the runpower being split into
two streams and thus
*          tpcdbatch not having access to all data.
* 21 jul 99 bbeaton The start time for runpower
UF2 now does not start until after
*          the query stream is complete so that its
wait time is not included
*          NOTE: The wait time that the first UF1
in runthroughput still
*          includes the wait period that occurs
waiting on queries.
* 18 mar 02 kentond removed the need for list files.
Instead of using the *.list
*          files to determine the name of the output
files, the tags for the
*          source sql files are used.
*****
*****/
/* included in tpcdbatch.sqc and tpcdUF.sqc */
#include "tpcdbatch.h"
*****
*****/
/* global structure containing elements passed
between different functions */

```

```

/*****
*****/
struct global_struct
{
    struct stmt_info *s_info_ptr; /* ptr to
stmt_info list */
    struct stmt_info *s_info_stop_ptr; /* ptr to
last struct in list */
    struct comm_line_opt *c_l_opt; /* ptr to
comm_line_opt struct */
    struct ctrl_flags *c_flags; /* ptr to
ctrl_flags struct */
    Timer_struct stream_start_time; /* start
time for stream TIME_ACC */
    Timer_struct stream_end_time; /* end
time for stream TIME_ACC */
    char file_time_stamp[50]; /* time
stamp for output files */
    double scale_factor; /* scale factor
of database */
    char run_dir[150]; /* directory for
output files */
    int copy_on_load; /* indication of
whether or not */

    /* to do use a copy
directory */
    /* (equiv to COPY
YES) on load */
    /* default is FALSE */
    long lSeed; /* seed used to
generate the */
    /* queries for this
particular */
    /* run.
*/
    FILE *stream_list; /* ptr to query
list file */
    char update_num_file[150]; /* name of
file that keeps track */
    /* of which update
pairs have run*/
    char sem_file[150]; /* semaphore
name */
    char sem_file2[150]; /* semaphore
name bbe */
    FILE *stream_report_file; /* file to
report start stop */
    /* progress of the
stream */
};

/*****
*****/
/* New type declaration to store details about SQL
statement */

```

```

/*****
*****/
struct stmt_info
{
    long max_rows_fetch;
    long max_rows_out;
    int query_block; /*
@d30369 tjpg */
    unsigned int stmt_num; /*
@d24993 tjpg */
    double elapse_time; /*
@d24993 tjpg */
    double adjusted_time;
    char start_stamp[50]; /* start time
stamp for block */
    char end_stamp[50]; /* end time
stamp for block */
    char tag[50]; /* block tag
*/
    char qry_description[100];
    struct stmt_info *next; /*
@d24993 tjpg */
};

/*****
*****/
/* Structure containing command line options
*/
/*****
*****/
struct comm_line_opt
{
    /* @d22275
tjpg */
    /* kjd715 */
    /* char str_file_name[256]; */ /* output
filename */
    /* kjd715 */
    char infile[256]; /* input filename
*/
    int intStreamNum; /* integer version
of stream number */
    int a_commit; /* auto-commit flag
*/
    int short_time; /* time interval flag
*/
    int update;
    int outfile;
};

/*****
*****/

```

```

/* Structure used to hold precision for decimal
numbers */
/*****
*****/
struct declen
{ /* kmw */
    unsigned char m; /* # of digits left of decimal
*/
    unsigned char n; /* # of digits right of decimal
*/
};

/*****
*****/
/* Structure containing control flags passed between
functions */
/*****
*****/
struct ctrl_flags
{ /* @d25594
tjg */
    int eo_infile;
    int time_stamp;
    int eo_block; /*
@d30369 tjg */
    int select_status;
};

/*****
*****/
/* Function Prototypes
*/
/*****
*****/
int SleepSome( int amount );
int get_env_vars(void);
int Get_SQL_stmt(struct global_struct *g_struct);

void print_headings (struct sqllda *sqllda, int
*col_lengths); /* @d22817 tjg */
void echo_sqllda(struct sqllda *sqllda, int
*col_lengths);
void allocate_sqllda(struct sqllda *sqllda);

void get_start_time(Timer_struct *start_time);
double get_elapsed_time (Timer_struct *start_time);

long error_check(void); /*
@d28763 tjg */
void dumpCa(struct sqlca*); /*kmw*/

void display_usage(void);
char *uppercase(char *string);
char *lowercase(char *string);

void comm_line_parse(int argc, char *argv[], struct
global_struct *g_struct);
int sqlrxd2a(char *decptr,char *asciiptr,short
prec,short scal);
void init_setup(int argc, char *argv[], struct
global_struct *g_struct);
void runUF1( struct global_struct *g_struct, int
updatePair );
void runUF2( struct global_struct *g_struct, int
updatePair );

/* These need to be extern because they're in another
SQC file. aph 981205 */
/*extern void runUF1_fn( int updatePair, int i );*/
/* aph 981205 */
/*extern void runUF2_fn( int updatePair, int i, int
numChunks );*/ /* aph 981205 */
/* Added four new arguments because SQL host
vars can't be global. aph 981205 */
extern void runUF1_fn ( int updatePair, int i, char
*dbname, char *userid, char *passwd );
extern void runUF2_fn ( int updatePair, int
thisConcurrentDelete, int numChunks, char
*dbname, char *userid, char *passwd );

int sem_op (int semid, int semnum, int value);

char *get_time_stamp(int form, Timer_struct
*timer_pointer); /* TIME_ACC jen */
void summary_table (struct global_struct *g_struct);
void free_sqllda (struct sqllda *sqllda, int
select_status); /* @d30369 tjg */
void output_file(struct global_struct *g_struct);
int PreSQLprocess(struct global_struct *g_struct,
Timer_struct *start_time);
void SQLprocess(struct global_struct *g_struct);
int PostSQLprocess(struct global_struct *g_struct,
Timer_struct *start_time);
int cleanup(struct global_struct *g_struct);

/* Semaphore control functions */
void create_semaphore(struct global_struct
*g_struct);
void throughput_wait(struct global_struct
*g_struct);
void runpower_wait(struct global_struct *g_struct,
int sem_num);
void release_semaphore(struct global_struct
*g_struct, int sem_num);
#ifdef SQLWINT
HANDLE open_semaphore(struct global_struct
*g_struct, int num);
#else
int open_semaphore(struct global_struct *g_struct);
#endif

```

```

EXEC SQL INCLUDE SQLCA;

/*****
*****/
/* Declare the SQL host variables.
*/
/*****
*****/
EXEC SQL BEGIN DECLARE SECTION;

char stmt_str1[4000] = "\0"; /* Assume max
SQL statment
of 4000 char */
struct { /* jen LONG */
short len;
char data[32700];
} stmt_str; /* jen LONG */
char dbname[9] = "\0";
char userid[9] = "\0";
char passwd[9] = "\0";
char sourcefile[256]; /* used for
semaphores and table functions?*/
sqlint32 chunk = 0; /* jenCI counter for
within the set of chunks*/

EXEC SQL END DECLARE SECTION;

/*****
*****/
/* Declare the global variables.
*/
/*****
*****/
struct sqlda *sqlda; /* SQL Descriptor
area */

/* Global environment variables (sks May 25 98)*/
char env_tpcd_dbname[100];
char env_user[100];
char env_tpcd_audit_dir[150];
char env_tpcd_path_delim[2];
char env_tpcd_tmp_dir[150];
char env_tpcd_run_on_multiple_nodes[10];
char env_tpcd_copy_dir[150];
char env_tpcd_update_import[10];

/* Other globals */
FILE *instream, *outstream; /* File
pointers */
int verbose = 0; /* Verbose option
flag */
int semcontrol = 1; /*
allows/disallows smaphores usage */

```

```

int updatePairStart; /* update pair to
start at */
int currentUpdatePair; /* update pair
running */
int updatePairStop; /* update pair to
stop before */
char newtime[50]="\0"; /* Des - moved
from get_time_stamp */
char outstreamfilename[256]; /* store
filename of outstream
wlc 081397 */
int inlistmax = 400; /* define # of keys
to delete at a time
wlc 081897 */
int sqlda_allocated = 0; /* fixing free()
problem in NT
wlc 090597 */
int iImportStagingTbl=0; /* IMPORT use
import or load (default) */
char temp_time_stamp[50]; /* holds end
timestamp to be copied into start_time_stamp of
next query bbeaton */
Timer_struct temp_time_struct; /* holds end
time value to be copied into start_time of next query
bbeaton */

/* constants for the semaphores used; 1 for
throughput and 2 for power */
#define INSERT_POWER_SEM 1
#define QUERY_POWER_SEM 2
#define THROUGHPUT_SEM 1

/*****
*****/
/* Start main program processing.
*/
/*****
*****/
int main(int argc, char *argv[])
{
/* kjd715 */
/*struct comm_line_opt c_l_opt = { "\0", "\0", 0, 1,
0, 0, 0 };*/ /* kjd715 */
struct comm_line_opt c_l_opt = { "\0", 0, 1, 0, 0, 0
};
/* kjd715 */
/* command line options */
Timer_struct start_time; /* start point for
elapsed time */

struct stmt_info s_info = { -1, -1, 0, 1, -1, -1,
"\0", "\0", "\0", "\0", NULL };
/* first stmt_info structure */

```

```

struct ctrl_flags c_flags = { 0, 1, 0,
TPCDBATCH_SELECT };
/* structure holding ctrl flags
passed between functions */

/* TIME_ACC jen start */
#if defined (SQLUNIX) || defined (SQLAIX)
struct global_struct g_struct =
{ NULL, NULL, NULL, NULL, {0,0}, {0,0}, "\0",
0.1, "\0", FALSE, 0,
NULL, "\0", "\0", "\0", NULL };

#elif (defined (SQLOS2) || defined (SQLWINT) ||
defined (SQLWIN) || defined (SQLDOS))
struct global_struct g_struct =
{ NULL, NULL, NULL, NULL, {0,0,0,0},
{0,0,0,0}, "\0", 0.1, "\0", FALSE, 0,
NULL, "\0", "\0", "\0", NULL };
#else
#error Unknown operating system
#endif
/* TIME_ACC jen end */

/* Get environment variables */
if (get_env_vars() != 0)
return -1;

/* perform setup and initialization and get process
id of agent */
ostream = stdout;
g_struct.c_flags = &c_flags;

g_struct.s_info_ptr = &s_info;
g_struct.c_l_opt = &c_l_opt;

init_setup(argc,argv,&g_struct); /*
@d22275 tjg */

if ((g_struct.c_l_opt->update == 1) &&
(semcontrol == 1))
/* runpower: wait for insert function to complete */
/* waiting on the INSERT_POWER_SEM
semaphore */
runpower_wait(&g_struct,
INSERT_POWER_SEM);

strcpy(temp_time_stamp, "0");

/*****
*****
*
* This is the transition from the "driver" to the
"SUT"
*
*

```

```

*****
*****/

/*****
*****/
/* Read in each statement, prepare, execute, and
send output to file. */

/*****
*****/

while (!c_flags.eo_infile) { /* Check to see if
there's no more input */

c_flags.eo_block = 0;

if (c_l_opt.outfile)
output_file(&g_struct); /* determine appropriate
name for output files */
if ((g_struct.c_l_opt->update != 3) &&
(g_struct.c_l_opt->update != 4))
{
if (!strcmp(temp_time_stamp, "0")) /* if first
query, get timestamp */
{
get_start_time(&start_time);
strcpy(g_struct.s_info_ptr->start_stamp,

get_time_stamp(T_STAMP_FORM_3,&start_time
)); /* TIME_ACC jen*/
}
else /* else get the end timestamp of previous
query */
{
strcpy(g_struct.s_info_ptr->start_stamp,
temp_time_stamp);
start_time = temp_time_struct;
}
/* write the start timestamp to the file...if this is
not a qualification */
/* run, then write the seed used as well */

fprintf( ostream,"Start timestamp %*.*s \n",
T_STAMP_3LEN,T_STAMP_3LEN,
/* TIME_ACC jen*/
g_struct.s_info_ptr->start_stamp);
if (c_l_opt.intStreamNum >= 0)
{
if (g_struct.lSeed == -1)
{
fprintf( ostream,"Using default qgen seed
file");
}
else

```



```

        fprintf( ostream,"Seed used =
%ld",g_struct.lSeed);

        fprintf( ostream,"\n");
    }
}
do { /* Loop through these statements as long as
we haven't reached
the end of the input file or the end of a block
of statements
*/

/** Read in the next statment **/

c_flags.select_status=Get_SQL_stmt(&g_struct);

if (PreSQLprocess(&g_struct, &start_time) ==
FALSE)
/* if after reading the next statement we see that
we should
exit this loop (i.e. eof, update functions,
etc...), get out
*/
break;

/*****
*****
*
*
* The SQLprocess function implements the
implementation specific layer. *
* It can handle arbitrary SQL statements.
*
*
*
*****
*****

/* If we've got up to here then processing
a regular SQL statement */
SQLprocess(&g_struct);

} while ((!c_flags.eo_block) &&
(!c_flags.eo_infile)); /* @d30369 tjj */

if (PostSQLprocess(&g_struct,&start_time) ==
FALSE)
/* if we've reached the end of the input file, then
get out
of this loop (i.e. no more statements).
Otherwise get
elapsed times and display info about rows */
break;

} /* end of for loop for multiple SQL statements
*/

g_struct.s_info_ptr = &s_info; /* set the global
pointer to start of
linked list */

cleanup(&g_struct); /* finish some semaphore
stuff, cleanup files,
and print out summary table */

/*****
*****
*
* In cleanup we make the transition back from
the "SUT" to the "driver" *
*
*****
*****

return(0);

} /* end of main */

/*****
*****
/* Generic form of Sleep */
int SleepSome( int amount)
{
#ifdef SQLWINT
sleep (amount);
#else
Sleep (amount*1000); /* 10x for NT DJD
Changed "sleep" to "Sleep" */
#endif
return 0;
}

/*****
*****

/*****
*****
/* Get environment variables. (sks May 25 98)
*/
/*****
*****

int get_env_vars(void) {
if (strcpy(env_tpcd_dbname,
getenv("TPCD_DBNAME")) == NULL) {

```

```

    fprintf(stderr, "\n The environment variable
$TPCD_DBNAME is not setup correctly.\n");
    return -1;
}
if (strcpy(env_user, getenv("USER")) == NULL) {
    fprintf(stderr, "\n The environment variable
$USER is not setup correctly.\n");
    return -1;
}
if (strcpy(env_tpcd_audit_dir,
getenv("TPCD_AUDIT_DIR")) == NULL) {
    fprintf(stderr, "\n The environment variable
$TPCD_AUDIT_DIR is not setup correctly.\n");
    return -1;
}
if (strcpy(env_tpcd_tmp_dir,
getenv("TPCD_TMP_DIR")) == NULL) {
    fprintf(stderr, "\n The environment variable
$TPCD_TMP_DIR is not setup correctly.\n");
    return -1;
}
}
#if 0
if (strcpy(env_tpcd_path_delim,
getenv("TPCD_PATH_DELIM")) == NULL ||
    (strcmp(env_tpcd_path_delim, "/") &&
    strcmp(env_tpcd_path_delim, "\\"))){
    fprintf(stderr, "\n The environment variable
$TPCD_PATH_DELIM is not setup correctly ,
env_tpcd_path_delim%s'\n",
env_tpcd_path_delim);

    return -1;
}
#endif
strcpy( env_tpcd_path_delim , "/" ); /*kmw*/
if (strcpy(env_tpcd_run_on_multiple_nodes,
getenv("TPCD_RUN_ON_MULTIPLE_NODES"))
== NULL) {
    fprintf(stderr, "\n The environment variable
$TPCD_RUN_ON_MULTIPLE_NODES");
    fprintf(stderr, "\n is not setup correctly.\n");
    return -1;
}
if (strcpy(env_tpcd_copy_dir,
getenv("TPCD_COPY_DIR")) == NULL) {
    fprintf(stderr, "\n The environment variable
$TPCD_COPY_DIR is not setup correctly.\n");
    return -1;
}
/* If TPCD_UPDATE_IMPORT is not set then,
the default is set to false, */
/* which is done in init_setup subroutine
*/
strcpy(env_tpcd_update_import,
getenv("TPCD_UPDATE_IMPORT"));

```

```

    return 0;
}

/*****
*****/
/* Get the SQL statement and any control statements
from input. */
/*****
*****/
int Get_SQL_stmt(struct global_struct *g_struct)
{
    char input_ln[256] = "\0"; /* buffer for 1 line
of text */
    char temp_str[4000] = "\0"; /* temp string for
SQL stmt */
    char control_str[256] = "\0"; /* control string
*/

    char *test_semi; /* ptr to test for
semicolon */
    char *control_opt; /* ptr used in
control_str parsing */
    char *select_status; /* ptr to first word in
query */
    char *temp_ptr; /* general purpose
temp ptr */

    int good_sql = 0; /* good-sql stmt flag
@d23684 tjt */
    int stmt_num_flag = 1; /* first line of SQL
stmt flag */
    int eostmt = 0; /* flag to signal end of
statement */

    stmt_str.data[0]='\0'; /* Initialize statement
buffer */

    if (verbose)
        fprintf (stderr, "\n-----
-----\n");
    fprintf (outstream, "\n-----
-----\n");

    do {
        /* Read in lines from input one at a time */
        fscanf(instream, "%n[^\n]\n", input_ln);

        if (strstr(input_ln, "--") == input_ln) { /* Skip
all -- comments */

            if (strstr(input_ln, "--SET") == input_ln) {
                /* Store control string but
keep going to find SQL
stmt */

```

```

strcpy(control_str,input_ln);
if (verbose)
    fprintf(stderr,"%s\n",
uppercase(control_str));
    fprintf(outstream,"%s\n",
uppercase(control_str));

/** Start parsing control str. and update
appropriate vars. */
control_opt = strtok(control_str, " ");
while (control_opt != NULL) {
    if (strcmp(control_opt,"--#SET")) { /* Skip
the #SET token */
        if
(!strcmp(control_opt,"ROWS_FETCH"))
            g_struct->s_info_ptr->max_rows_fetch
= atoi(strtok(NULL, " "));

        if (!strcmp(control_opt,"ROWS_OUT"))
            g_struct->s_info_ptr->max_rows_out =
atoi(strtok(NULL, " "));
        }

        control_opt = strtok(NULL, " ");
    }
}

/* if the block option has been set, then check
if we've
reached the end of a block of statements */
if (g_struct->s_info_ptr->query_block)
/* @d30369 tjt */
if (strstr(input_ln,"--#EOBLK") == input_ln)
{
    g_struct->c_flags->eo_block = 1;
    return TPCDBATCH_EOBLOCK;
}
if (strstr(input_ln, "-- Query") == input_ln)
    strcpy(g_struct->s_info_ptr-
>qry_description,input_ln);

if (strstr(input_ln, "--#TAG") == input_ln)
    strcpy(g_struct->s_info_ptr-
>tag,(input_ln+sizeof("--#TAG")));

/* if we're using update functions, return that
info
appropriately */
if (g_struct->c_l_opt->update != 0) {
    if (strstr(input_ln, "--#INSERT") ==
input_ln)
        return TPCDBATCH_INSERT;

    if (strstr(input_ln, "--#DELETE") ==
input_ln)
        return TPCDBATCH_DELETE;
}

```

```

}

if (strstr(input_ln, "--#COMMENT") ==
input_ln) { /* @d25594 tjt */
    temp_ptr = (input_ln + 11); /* User-
specified comments go to
the outfile */

    if (verbose)
        fprintf (stderr,"%s\n",temp_ptr);
        fprintf (outstream,"%s\n",temp_ptr);
    }

    eostmt=0;
}

/* Need this hack here to check if there's any
more empty lines left
in the input file. Continue only if there are
aren't any */
else if (strcmp(input_ln, "\0")) /* HACK */ { /*
A regular SQL statement */
    if (stmt_num_flag) { /* print this out only if
it's the first line
of the SQL statement. We only
want this
line to appear once per
statement */
        if (verbose)
            fprintf(stderr,"\n%s\n", g_struct-
>s_info_ptr->qry_description);
            fprintf(outstream,"\n%s\n", g_struct-
>s_info_ptr->qry_description);

        if (verbose)
            fprintf(stderr,"\nTag: %-5.5s Stream: %d
Sequence number: %d\n",
g_struct->s_info_ptr->tag,g_struct-
>c_l_opt->intStreamNum,
g_struct->s_info_ptr->stmt_num);
/*jen0925*/
            fprintf(outstream,"\nTag: %-5.5s Stream:
%d Sequence number: %d\n",
g_struct->s_info_ptr->tag,g_struct-
>c_l_opt->intStreamNum,
g_struct->s_info_ptr->stmt_num);
/*jen0925*/

        /* Turn off this flag once the number has
been printed */
        stmt_num_flag = 0;

    } /** Print out this heading the first time you
encounter a
non-comment statement */
}

```

```

        /* Test to see if we've reached the end of a
statement */
        good_sql = TRUE;                                /*
@d23684 tjpg */
        test_semi = strstr (input_ln, ";");
        if (test_semi == NULL) { /* if there's no
semi-colon keep on going */
            strcat (stmt_str.data, input_ln);          /*
jen LONG */
            strcat (stmt_str.data, " ");              /* jen
LONG */
            stmt_str.len = strlen (stmt_str.data );   /*
jen LONG */
            eostmt = 0;
        }

        else { /* else replace the ; with a
\0 and continue */
            *test_semi = '\0';
            strcat (stmt_str.data, input_ln);         /*
jen LONG */
            stmt_str.len = strlen (stmt_str.data );   /*
jen LONG */
            eostmt = 1;
        }

        fprintf(outstream, "\n%s", input_ln);
        if (verbose)
            fprintf(stderr, "\n%s", input_ln);
    }

    /** Test to see if we've reached the EOF. Get
out if that's the case */
    if (feof(instream)) {
        eostmt = TRUE;
        g_struct->c_flags->eo_infile = TRUE;
/* @d22275 tjpg */
    }

    } while (!eostmt);

    fprintf(outstream, "\n");
    if (verbose)
        fprintf(stderr, "\n");

    /** erase the old control string */
    strcpy(control_str, "\0");

    /** Determine whether statement is a SELECT or
other SQL */
    if (good_sql) {
        strcpy(temp_str, stmt_str.data);              /*
jen LONG */
        uppercase(temp_str); /* Make sure that select is
made to SELECT */
        select_status=strtok(temp_str, " ");
        if ( (stmt_str.data[0] == '(') ||
(!strcmp(select_status, "SELECT")) ||
        (!strcmp(select_status, "VALUES")) ||
        (!strcmp(select_status, "WITH")) )
            return TPCDBATCH_SELECT;
        else
            return TPCDBATCH_NONSELECT;
    }

    /** If you go through a file with just comments or
control statments
with no SQL, there's nothing to process...Exit
TPCDBATCH */

    else /* @d23684
tjpg */
        return TPCDBATCH_NONSQL;
} /* Get_SQL_stmt */

/*****
*****/
/* allocate_sqlda -- This routine allocates space for
the SQLDA. */
/*****
*****/

void allocate_sqlda(struct sqlda *sqlda)
{
    int loopvar; /* Loop counter
*/

    for (loopvar=0; loopvar<sqlda->sqld; loopvar++)
    {
        switch (sqlda->sqlvar[loopvar].sqltype)
        {
            case SQL_TYP_INTEGER: /*
INTEGER */
            case SQL_TYP_NINTEGER:
                if ((sqlda->sqlvar[loopvar].sqldata=
(TPCDBATCH_CHAR
*)malloc(sizeof(sqlint32))) == NULL)
                    mem_error("allocating INTEGER");
                break;
            case SQL_TYP_BIGINT: /*
BIGINT */ /*kmwBIGINT*/
            case SQL_TYP_NBIGINT:
/*#ifdef SQLWINT */
/* if ((sqlda->sqlvar[loopvar].sqldata=
(TPCDBATCH_CHAR
*)malloc(sizeof(__int64))) == NULL)*/
/* #else */
                if ((sqlda->sqlvar[loopvar].sqldata=

```

```

        (TPCDBATCH_CHAR
*)malloc(sizeof(sqlint64)) == NULL)
/* #endif*/
    mem_error("allocating BIGINT");
    break;
    case SQL_TYP_CHAR: /*
CHAR */
    case SQL_TYP_NCHAR:
    if ((sqlda->sqlvar[loopvar].sqldata=
        (TPCDBATCH_CHAR
*)calloc(256,sizeof(char))) == NULL)
        mem_error("allocating
CHAR/VARCHAR");
        break;
    case SQL_TYP_VARCHAR: /*
VARCHAR */
    case SQL_TYP_NVARCHAR:
    if ((sqlda->sqlvar[loopvar].sqldata=
        (TPCDBATCH_CHAR
*)calloc(4002,sizeof(char))) == NULL)
        mem_error("allocating
CHAR/VARCHAR");
        break;
    case SQL_TYP_LONG: /*
LONG VARCHAR */
    case SQL_TYP_NLONG:
    if ((sqlda->sqlvar[loopvar].sqldata=
        (TPCDBATCH_CHAR
*)calloc(32702,sizeof(char))) == NULL)
        mem_error("allocating VARCHAR/LONG
VARCHAR");
        break;
    case SQL_TYP_FLOAT: /*
FLOAT */
    case SQL_TYP_NFLOAT:
    if ((sqlda->sqlvar[loopvar].sqldata=
        (TPCDBATCH_CHAR
*)malloc(sizeof(double))) == NULL)
        mem_error("allocating FLOAT");
        break;
    case SQL_TYP_SMALL: /*
SMALLINT */
    case SQL_TYP_NSMALL:
    if ((sqlda->sqlvar[loopvar].sqldata=
        (TPCDBATCH_CHAR
*)malloc(sizeof(short))) == NULL)
        mem_error("allocating SMALLINT");
        break;
    case SQL_TYP_DECIMAL: /*
DECIMAL */
    case SQL_TYP_NDECIMAL:
    if ((sqlda->sqlvar[loopvar].sqldata=
        (TPCDBATCH_CHAR *)malloc(20))
== NULL)
        mem_error("allocating DECIMAL");
        break;

```

```

        case SQL_TYP_CSTR: /*
VARCHAR (null terminated) */
        case SQL_TYP_NCSTR:
        if ((sqlda->sqlvar[loopvar].sqldata=
            (TPCDBATCH_CHAR
*)calloc(4001,sizeof(char))) == NULL)
            mem_error("allocating
CHAR/VARCHAR");
            break;
        case SQL_TYP_DATE: /*
DATE */
        case SQL_TYP_NDATE:
        if ((sqlda->sqlvar[loopvar].sqldata=
            (TPCDBATCH_CHAR
*)calloc(13,sizeof(char))) == NULL)
            mem_error("allocating DATE");
            break;
        case SQL_TYP_TIME: /*
TIME */
        case SQL_TYP_NTIME:
        if ((sqlda->sqlvar[loopvar].sqldata=
            (TPCDBATCH_CHAR
*)calloc(11,sizeof(char))) == NULL)
            mem_error("allocating TIME");
            break;
        case SQL_TYP_STAMP: /*
TIMESTAMP */
        case SQL_TYP_NSTAMP:
        if ((sqlda->sqlvar[loopvar].sqldata=
            (TPCDBATCH_CHAR
*)calloc(29,sizeof(char))) == NULL)
            mem_error("allocating TIMESTAMP");
            break;
        }
        if ((sqlda->sqlvar[loopvar].sqlind=
            (short *)calloc(1,sizeof(short))) ==
NULL)
            mem_error("allocating indicator");
        }
        sqlda_allocated = 1; /* fix free() problem on NT
wlc 090597 */
        return; /* allocate_sqlda */
    }

/*****
*****/
/* echo_sqlda -- This routine displays the contents of
an SQLDA. */
/*****
*****/

void echo_sqlda(struct sqlda *sqlda, int
*col_lengths)

```

```

{
    int col;                /* Column counter
*/

    int col_type;          /* Type of column
*/

    char temp_string[100] = "\0"; /* Temporary
string */
    char decimal_string[100] = "\0"; /* String
holding decimals */
    char *temp_ptr;

    TPCDBATCH_CHAR m,n;    /*
precision and accuracy
for decimal conversion
*/

    for (col=0; col<sqlda->sqld; col++) /* Loop
through column count */
    {
        col_type=sqlda->sqlvar[col].sqltype;
/* @d22817 tjc */

        if (*(sqlda->sqlvar[col].sqlind)) /*
@d30369 tjc */
            fprintf(outstream, "%* n/a ",(col_lengths[col]-
3));
        else
            switch (col_type)
            {
                case SQL_TYP_INTEGER:
                case SQL_TYP_NINTEGER:

                    fprintf(outstream, "%*ld ",col_lengths[col],
*(sqlint32 *) (sqlda-
>sqlvar[col].sqldata));
                    break;

                case SQL_TYP_BIGINT: /*kmwBIGINT*/
                case SQL_TYP_NBIGINT:
/*#ifdef SQLWINT*/
/*          fprintf(outstream, "%*I64d
",col_lengths[col],*/
/*          *((__int64 *) (sqlda-
>sqlvar[col].sqldata));*/
/*#else*/
                    fprintf(outstream, "%*lld ",col_lengths[col],
*(sqlint64 *) (sqlda-
>sqlvar[col].sqldata));
/*#endif*/
                    break;

                case SQL_TYP_CHAR:
                case SQL_TYP_NCHAR:

                    fprintf(outstream, "%-*s
",col_lengths[col],sqlda->sqlvar[col].sqldata);
                    break;
                case SQL_TYP_VARCHAR:
                case SQL_TYP_NVARCHAR:
                case SQL_TYP_LONG:
                case SQL_TYP_NLONG:
/* @d30369 tjc */
                    ((struct sqlchar *)sqlda->sqlvar[col].sqldata)-
>
                    data[((struct sqlchar *)sqlda-
>sqlvar[col].sqldata)->length] = '\0';
                    fprintf(outstream, "%-*s ",
col_lengths[col],
((struct sqlchar *)sqlda-
>sqlvar[col].sqldata)->data);
                    break;
                case SQL_TYP_FLOAT:
                case SQL_TYP_NFLOAT:
                { /* kmw */
                    if ( fabs(*(double *) (sqlda-
>sqlvar[col].sqldata))
<
TPCDBATCH_PRINT_FLOAT_MAX )
                        fprintf(outstream, "%#*.3f
",col_lengths[col],
*(double *) (sqlda-
>sqlvar[col].sqldata));
                    else
                        fprintf(outstream, "%*e ",col_lengths[col],
*(double *) (sqlda-
>sqlvar[col].sqldata));
                    break;
                }

                case SQL_TYP_SMALL:
                case SQL_TYP_NSMAIL:

                    fprintf(outstream, "%*hd ",col_lengths[col],
*(short *) (sqlda->sqlvar[col].sqldata));
                    break;
                case SQL_TYP_DECIMAL:
                case SQL_TYP_NDECIMAL:

                    m=*(struct declen *)&sqlda-
>sqlvar[col].sqllen).m;
                    n=*(struct declen *)&sqlda-
>sqlvar[col].sqllen).n;
                    if (sqlrx2a((char *)sqlda-
>sqlvar[col].sqldata,temp_string,m,n) != 0)
                    {
                        fprintf(stderr, "\nThe decimal value could
not be converted.\n");
                        exit (-1);
                    }
            }
    }
}

```

```

else {
    temp_ptr = temp_string;

    if (*temp_ptr == '-')
        strcpy(decimal_string, "-");

    else
        strcpy(decimal_string, " ");

    for (temp_ptr = temp_string + 1; *temp_ptr
        == '0'; temp_ptr++)
        ;

    strcat(decimal_string,temp_ptr);
    fprintf(outstream, "%*s
",col_lengths[col],decimal_string);
}

break;

case SQL_TYP_CSTR:
case SQL_TYP_NCSTR:
case SQL_TYP_DATE:
case SQL_TYP_NDATE:
case SQL_TYP_TIME:
case SQL_TYP_NTIME:
case SQL_TYP_STAMP:
case SQL_TYP_NSTAMP:
    sqlda->sqlvar[col].sqldata[sqlda-
>sqlvar[col].sqlen+1]='\0';
    strcpy(temp_string,(char *)sqlda-
>sqlvar[col].sqldata);
    fprintf(outstream, "%-*s
", (col_lengths[col]),temp_string);
    break;

    default:
        fprintf(stderr,"--Unknown column type (%d).
Aborting.\n",col_type);
        break;
}
}

fprintf(outstream, "\n");

return;
}

/*****
*****/
/* Calculate the elapsed time. */
/*****
*****/

void get_start_time(Timer_struct *start_time)
{
    int rc = 0;

#ifdef SQLLOS2 || defined (SQLWINT) ||
defined (SQLWIN) || defined (SQLDOS)
    /*@d33143aha*/
    ftime (start_time);
#elif defined(SQLSNI)
    rc = gettimeofday(start_time);
#elif defined(SQLPTX)
    gettimeofday_mapped(start_time);
    rc = 0; /* gettimeofday_mapped returns void */
#elif defined (SQLUNIX) || defined (SQLAIX)
    /*TIMER jen*/
    rc = gettimeofday(start_time,NULL);
#else
#error Unknown operating system
#endif

    if (rc != 0) {
        fprintf(stderr,"Timer call failed, aborting
test\nExiting tpcdbatch..\n");
        exit(-1);
    }
}

/*****
*****/
/* Calculate and return the elapsed time given a
starting time. */
/*****
*****/
double get_elapsed_time ( Timer_struct *start_time)
{
    int status = 0;
    Timer_struct end_time;
    double result = -1.0;
#ifdef SQLWINT
    long int result_sec;
    long int result_usec;
#endif
#ifdef SQLSNI
    status = gettimeofday(&end_time);
#elif defined(SQLPTX)
    gettimeofday_mapped(&end_time);
    status = 0; /* gettimeofday_mapped returns void */
#elif defined (SQLUNIX) || defined (SQLAIX)
    status = gettimeofday(&end_time,NULL);
/*TIMER jen*/

```

```

#elif defined (SQLOS2) || defined (SQLWINT) ||
defined (SQLWIN) || defined (SQLDOS)
    ftime(&end_time);
#else
    /** If another operating
system **/
#error Unknown operating system
#endif

    if (status != 0)
        fprintf(stderr, "Bad return from gettimeofday,
don't trust timer results...\n");

    else
    {
#if defined (SQLUNIX) || defined (SQLAIX)
        result_sec = end_time.tv_sec - start_time-
>tv_sec;
        result = (double) result_sec;
        /* TIMER used micro seconds with timeval (not
nanoseconds) */
        if ((start_time->tv_usec > 0) && \
            (start_time->tv_usec < 1000000) && \
            (end_time.tv_usec > 0) && \
            (end_time.tv_usec < 1000000))
        {
            result_usec = end_time.tv_usec - start_time-
>tv_usec;
            result = (double) result_sec + ((double)
result_usec/1000000);
        }
#elif (defined (SQLOS2) || defined (SQLWINT) ||
defined (SQLWIN) || defined (SQLDOS))
        result = (double) (end_time.time - start_time-
>time);
        result = result * 1000 + (end_time.millitm -
start_time->millitm);
        result = result/1000;
#else
#error Unknown operating system
#endif

    }

    /*
    * translate the time to that rounded to the
CLOSEST 0.1 seconds as
    * required by the TPC-D spec. ROUNDING
    */
    /* result = (double)(((long)((result + 0.099999) *
10))/10.0);*/
    result = (double)(((long)((result + 0.05) *
10))/10.0);
    return (result);
}

void dumpCa(struct sqlca *ca)
{
    int i;
    fprintf(outstream, "*****
DUMP OF SQLCA *****\n");
    fprintf(outstream, "SQLCAID : %.8s\n", ca-
>sqlcaid);
    fprintf(outstream, "SQLCABC : %d\n", ca-
>sqlcabc);
    fprintf(outstream, "SQLCODE : %d\n", ca-
>sqlcode);
    fprintf(outstream, "SQLERRML : %d\n", ca-
>sqlerrml);
    fprintf(outstream, "SQLERRMC : %.*s\n", ca-
>sqlerrml, ca->sqlerrmc);
    fprintf(outstream, "SQLERRP : %.8s\n", ca-
>sqlerrp);

    for (i = 0; i < 6; i++)
    {
        fprintf(outstream, "SQLERRD[%d] : %d\n", i, ca-
>sqlerrd[i] );
    }
    fprintf(outstream, "SQLWARN : %.11s\n", ca-
>sqlwarn);
    fprintf(outstream, "SQLSTATE : %.5s\n", ca-
>sqlstate);
    fprintf(outstream, "***** END
OF SQLCA DUMP *****\n");
    return;
}

/*****
*****/
/* error_check
*/
/* This function prints the contents of the sqlca error
information */
/* structure.
*/
/*****
*****/
long error_check(void)
{
    char buffer[512]="\0";
    unsigned short i;
    struct sqlca temp_sqlca; /* temporary sqlca */
    /* @d30369 tjj */

    temp_sqlca.sqlcode = 0; /* initialize the
temporary sqlca to
avoid any memory problems
*/

    if (sqlca.sqlcode != 0) {

```



```

sqlaintp(buffer, sizeof(buffer), 80, &sqlca);
fprintf(stderr, "\n%0.200s\n", buffer);
fprintf(outstream, "\n%0.200s\n", buffer);

/* Decode the SQLCA in more detail KBS
98/09/28 */
if ((sqlca.sqlerrml) /* there's one or more
tokens */
    && (sqlca.sqlerrml < sizeof(sqlca.sqlerrmc))
/* and field not full */
    )
{
    char *tokptr;
    int tokl;
    *(sqlca.sqlerrmc + sqlca.sqlerrml) = '\0'; /*
prevent strtok from scanning beyond end */
    fprintf(stderr, "\n SQLCA: tokens:\n");
    fprintf(outstream, "\n SQLCA: tokens:\n");
    tokptr=strtok(sqlca.sqlerrmc, "\xff");
    while ( tokptr
            &&
            ((tokl = (sizeof(sqlca.sqlerrmc) - (tokptr-
sqlca.sqlerrmc))) > 0)
            )
    {
        fprintf(stderr, "%.*s\n", tokl, tokptr);
        fprintf(outstream, "%.*s\n", tokl, tokptr);
        tokptr=strtok(NULL, "\xff");
    }
    fprintf(stderr, "\n SQLCA: errp= %.8s, errd
1-6= %d %d %d %d %d %d\n",
            sqlca.sqlerrp, sqlca.sqlerrd[0],
sqlca.sqlerrd[1], sqlca.sqlerrd[2],
            sqlca.sqlerrd[3], sqlca.sqlerrd[4],
sqlca.sqlerrd[5]);
    fprintf(outstream, "\n SQLCA: errp= %.8s,
errd 1-6= %d %d %d %d %d %d\n",
            sqlca.sqlerrp, sqlca.sqlerrd[0],
sqlca.sqlerrd[1], sqlca.sqlerrd[2],
            sqlca.sqlerrd[3], sqlca.sqlerrd[4],
sqlca.sqlerrd[5]);

    temp_sqlca = sqlca; /* Make a copy of sqlca in
case it gets changed
in the next statement below */ /*
@d30369 tjj */

    /** Determine if the error is critical or a
connection can be made **/

    EXEC SQL CONNECT ;
/* @d28763 tjj */

    if (sqlca.sqlcode == SQLE_RC_NOSUDB ) { /*
no connection exists */

```

```

/*Print out header for DUMP*/
fprintf(outstream,
"*****\n");
    fprintf(outstream, "** CONTENTS OF
SQLCA *\n");
    fprintf(outstream,
"*****\n\n")
;

/*Print out contents of SQLCA variables*/
fprintf(outstream, "SQLCABC = %ld\n",
temp_sqlca.sqlcabc);
fprintf(outstream, "SQLCODE = %ld\n",
temp_sqlca.sqlcode);
fprintf(outstream, "SQLERRMC = %0.70s\n",
temp_sqlca.sqlerrmc);
fprintf(outstream, "SQLERRP = %0.8s\n",
temp_sqlca.sqlerrp);

    for (i = 0; i < 6; i++)
    {
        fprintf(outstream, "sqlerrd[%d] = %lu \n", i,
temp_sqlca.sqlerrd[i]);
    }

    fprintf(outstream, "SQLWARN = %0.11s\n",
temp_sqlca.sqlwarn);
    fprintf(outstream, "SQLSTATE = %0.5s\n",
temp_sqlca.sqlstate);

    fprintf(stderr, "\nCritical SQLCODE. Exiting
TPCDBATCH\n");
    exit(-1);

}
}
return (temp_sqlca.sqlcode);
} /* error_check */

/*****
*****/
/* Displays a help screen */
/*****
*****/
void display_usage()
{
    printf("\ntpcdbatch -- version
%s", TPCDBATCH_VERSION);
    printf("\n\nSyntax is:\n");
    printf("tpcdbatch [-d dbname] [-f file_name] [-l
file_name] [-r on/off]");
    printf("\n [-v on/off] [-b on/off] [-u
p/t1/t2]");
}

```

```

printf("\n      [-s scale_factor] [-n stream_num] [-
m inlistmax] [-h]\n");
printf("\n where: -d Database name");
printf("\n      Default - dbname set in
$DB2DBDFT");
printf("\n      -f Input file containing SQL
statements");
printf("\n      Default - stdin");
printf("\n      -r Create set of output files
containing query results");
printf("\n      Default - off");
printf("\n      -v Verbose. Sends information to
stderr during");
printf("\n      query processing");
printf("\n      Default - off");
printf("\n      -b Process groups of statements as
blocks ");
printf("\n      instead of individually.");
printf("\n      Default - off");
printf("\n      -u Update streams: p  - for power
test");
printf("\n      t  - for throughput test
without");
printf("\n      UFs (run this
instead of t2)");
printf("\n      t1  - for throughput
test step 1");
printf("\n      only running
queries");
printf("\n      t2  - for throughput
test step 2");
printf("\n      running update
functions");
printf("\n      -s Scale factor");
printf("\n      Default - 0.1");
printf("\n      -n Stream number");
printf("\n      Default - 0");
printf("\n      Qualification - -1");
printf("\n      Power - 0");
printf("\n      Throughput - >= 1 (actual
number depends on the current query stream");
printf("\n      -m Maximum number of keys to
delete at a time");
printf("\n      Default - 400");
printf("\n      -h Display this help screen");
printf("\n      -p turns smeaphores on or off");
printf("\n      Default - off");

printf("\n\nControl statements specifying output
and performance details");
printf("\n can be included before SQL statements;
they will apply for");
printf("\n that and subsequent statements until
updated.");

printf("\n\nSyntax:  --#SET <control option>
<value>");
printf("\n option  value  default");
printf("\nROWS_FETCH  -1 to n  -1 (all rows
fetched from answer set)");
printf("\nROWS_OUT    -1 to n  -1 (all fetched
rows sent to output)");
printf("\n\n--#TAG    tag        (user specified
tag name for sequence#)");
printf("\n\n--#COMMENT  comment    (user
specified comments for output)");
printf("\nNote: All statements executed with
ISOLATION LEVEL RR");
printf("\n and must be terminated with semi-
colons.\n");
exit (1);
}

/*****
*****/
/* Converts a string to upper case characters */
/*****
*****/
char *uppercase( char *string )
{
char *c; /* temp char used to convert word to
upper case */

for ( c = string; *c != '\0'; c++)
*c = (char) toupper( (int) *c );

return (string);
}

/*****
*****/
/* Converts a string to lower case characters */
/*****
*****/
char *lowercase( char *string )
{
char *c; /* temp char used to convert word to
lower case */

for ( c = string; *c != '\0'; c++)
*c = (char) tolower( (int) *c );

return (string);
}

/*****
*****/
/* Parses and processes command line options. */

```

```

/*****
*****/

void comm_line_parse(int argc, char *argv[], struct
global_struct *g_struct)
{
    char authent_info[40] = "\0";
    char *testptr;
    int loopvar = 0;

    int comm_opt = 0;
#ifdef PARALLEL_UPDATES
    int running_updates=0;
    int updatePair=-1;
    int updateStream=-1;
    int function;
    int copyOnOrOff;
    int deleteChunk=0;    /*DELjen */
#endif

    while ((loopvar < argc) && (argc != 1)) {

        if (*argv[loopvar] == '-') {

            switch(*(argv[loopvar]+1)) {

                case 'f' :                /* @d26350
tjg */
                case 'F' :
                    strcpy(g_struct->c_l_opt-
>infile,argv[++loopvar]);
                    break;
                    /* kjd715 */
                case 'l' :
                case 'L' :    loopvar+=1;
                            /*
                            strcpy(g_struct->c_l_opt-
>str_file_name,argv[++loopvar]);
                            */
                            break;
                            /* kjd715 */
                case 'r' :                /* @d26350
tjg */
                case 'R' :
                    if
(!strcmp(uppercase(argv[++loopvar]),"ON"))
                        g_struct->c_l_opt->outfile=1;
                    else
                        g_struct->c_l_opt->outfile=0;
                    break;

                case 'd' :                /*
@d26350 tjg */
                case 'D' :
                    strcpy(dbname,argv[++loopvar]);
                    break;

```

```

                case 'v' :                /*
@d26350 tjg */
                case 'V' :
                    if
(!strcmp(uppercase(argv[++loopvar]),"ON"))
                        verbose=1;
                    else
                        verbose=0;
                    break;

                case 'u' :                /*
@d26350 tjg */
                case 'U' :
                    g_struct->c_l_opt->update=-1; /* init to
invalid number */
                    if
(!strcmp(uppercase(argv[++loopvar]),"P1"))
                        g_struct->c_l_opt->update=1; /* power
query stream*/
                    if (!strcmp(uppercase(argv[loopvar]),"P2"))
                        g_struct->c_l_opt->update=3; /* power
update with updates*/
                    if (!strcmp(uppercase(argv[loopvar]),"P"))
                        g_struct->c_l_opt->update=4; /* power
update without updates*/
                    if (!strcmp(uppercase(argv[loopvar]),"T1"))
                        g_struct->c_l_opt->update=0;
                    /*throughput query stream */
                    if (!strcmp(uppercase(argv[loopvar]),"T2"))
                        g_struct->c_l_opt->update=2; /*
throughput update with updates */
                    if (!strcmp(uppercase(argv[loopvar]),"T"))
                        g_struct->c_l_opt->update=5; /*
throughput update without updates */

                    break;

                case 'b' :                /*
@d26350 tjg */
                case 'B' :
                    if
(!strcmp(uppercase(argv[++loopvar]),"ON"))
                        g_struct->s_info_ptr->query_block=1;
                    else
                        g_struct->s_info_ptr->query_block=0;
                    break;

                case 'n' :                /*
@d26350 tjg */
                case 'N' :
                    g_struct->c_l_opt->intStreamNum =
atoi(argv[++loopvar]);
                    break;

```

```

        case 's':                /* @d26350
tjg */
        case 'S':  g_struct-
>scale_factor=atoi(argv[++loopvar]); break;

        case 'h':
        case 'H':                /*
@d26350 tjg */
            display_usage();
            break;

        case 'm':
        case 'M':
            inlistmax = atoi(argv[++loopvar]); /* wlc
081897 */
            break;

        case 'p':
        case 'P':
            if
(!strcmp(uppercase(argv[++loopvar]),"ON")) /* bbe
072599 */
                semcontrol = 1;
            else
                semcontrol = 0;
            break;

#ifdef PARALLEL_UPDATES
        case 'i':
            updatePair = atoi (argv[++loopvar]);
#ifdef UF2DEBUG
            fprintf (stderr, "updatePair =
%d\n",updatePair);
            fflush(stderr);
#endif
            break;

        case 'j':
            function = atoi (argv[++loopvar]);
#ifdef UF2DEBUG
            fprintf (stderr, "function = %d\n",function);
            fflush(stderr);
#endif
            break;

        case 'k':
            updateStream = atoi (argv [++loopvar]);
#ifdef UF2DEBUG
            fprintf (stderr, "updateStream =
%d\n",updateStream);
            fflush(stderr);
#endif
            break;

        case 'x':                /*DEL jen -x is
chunk*/
            deleteChunk = atoi (argv[++loopvar]); /*
to delete for this */
#ifdef UF2DEBUG
            fprintf (stderr, "DelChunk =
%d\n",deleteChunk);
            fflush(stderr);
#endif
            break;                /* invocation
*/

        case 'z':
            running_updates = 1;
            break;
#endif
        default :
            fprintf(stderr, "An invalid option has been
set\n");
            display_usage();
            break;

    } /** end switch */
} /** end if */

    loopvar ++;
} /** end while */

/* checking if -u option is set */
if (g_struct->c_1_opt->update == -1) {
    fprintf(stderr, "-u option is not set, exiting ...n");
    exit(-1);
}

#ifdef PARALLEL_UPDATES
    if (running_updates) {
        if (updatePair == -1) {
            fprintf (stderr, "The parameters to tpcdbatch
have not been passed correctly\n");
            exit (-1);
        }
        else {
            /* check to see if we are to use copy on for the
load */
            if (( getenv("TPCD_LOG") != NULL ) &&
(!strcmp(uppercase(getenv("TPCD_LOG")), "YES")
))
                {
                    /* okay, we have set LOG_RETAIN on so
we need to use copy directory */
                    copyOnOrOff = TRUE;
                }
            else
                {

```

```

        /* log retain off don't use copy directory */
        copyOnOrOff = FALSE;
    }

    if (function == 1)
        /* runUF1_fn (updatePair, updateStream);
aph 981205 */
        runUF1_fn (updatePair, updateStream,
dbname, userid, passwd);
    else
        if (function == 2) {
            fprintf(stderr, "A-Calling runUF2_fn %d
%d %d ...\\n",
                updatePair, updateStream,
deleteChunk);
            /* runUF2_fn (updatePair, updateStream,
deleteChunk); aph 981205 */
            runUF2_fn (updatePair, updateStream,
deleteChunk, dbname, userid, passwd);
        }
        else {
            fprintf (stderr, "Wrong function to
tpcdbatch\\n");
            exit (-1);
        }
        exit (0);
    }
}
#endif /* PARALLEL_UPDATES */

/* If no database name is given, then use the one
specified in the
environment variable DB2DBDFT, otherwise
error */
if (!strcmp(dbname, "\\0")) {
    testptr = getenv("DB2DBDFT");
    if (testptr == NULL) {
        fprintf(stderr, "\\nNo database name has been
specified on command ");
        fprintf(stderr, "line\\n\\n in environment
variable DB2DBDFT.");
        display_usage();
    }
    else
        strcpy(dbname, testptr);
}
/* kjd715 */
/*
if (g_struct->c_1_opt->outfile) &&
!strcmp(g_struct->c_1_opt->str_file_name, "\\0")
{
    fprintf(stderr, "\\nMust specify input file for
statement list.\\n");
    display_usage();
}

```

```

        */
        /* kjd715 */
    }

    /******
    *****/
    /* Converts DECIMAL values to ASCII text
    */
    /******
    *****/
    int sqlrx_d2a(
        /*kmw*/
        /* C++ *//char
        *decptr,
        /* C++ *//char
        *asciiptr,
        short prec,
        short scal)
    {
        /* */
        int allzero = TRUE;
        /* C++ *//char *srcptr;
        unsigned char sign;
        /* C++ *//char *targptr, decimal_point = '!';
        int rc = 0;
        int tmpint, src_nibble;
        int count, j, limit[3];

        targptr = &asciiptr[ prec + 1];
        *(1 + targptr) = '\\0';
        srcptr = decptr + prec/2;

        /* Validity check sign nibble */
        if (((sign = sqlrx_get_right_nibble( *srcptr )) <
0x0a)
            || (prec > SQL_MAXDECIMAL) || (prec < scal
))
        {
            goto exit;
        }
        /*** end end if invalid sign value **/

        limit[ 0 ] = scal; limit[ 1 ] = prec - scal; limit[ 2 ] =
0;
        src_nibble = LEFT;
        for( j = 0 ; j < 2 ; j++ )
        {
            for( count = limit[ j ] ; count > 0 ; count-- )
            {
                tmpint = ( (src_nibble == LEFT)?
                    sqlrx_get_left_nibble( *srcptr-- ) :
                    sqlrx_get_right_nibble( *srcptr ) );
                if( tmpint > 9 )
                {
                    goto exit;
                }
            }
        }
    }

```

```

    }
    else
        *targptr-- = (/* C++ */char)tmpint + '0';
        src_nibble = ((src_nibble == LEFT) ? RIGHT :
LEFT);
        if ( tmpint != 0 ) allzero = FALSE;
    } /* end for scal > 0 */

    if( j == 0 )
        *targptr-- = decimal_point;
    else
        *targptr = (/* C++ */char)((allzero
                                || (sign ==
SQLRX_PREFERRED_PLUS)
                                || (sign == 0x0a)
                                || (sign == 0x0e)
                                || (sign == 0x0f) ?
                                '+' : '-'));
    } /* end for limit[ j++ ] > 0 */

    exit :
    if( rc < 0 )
    {
        printf ("The decimal conversion has failed\n");
        exit (-1);
    }

    return(rc);
} /* sqlrxd2a */

/*****
*****
*/
/* Does some setup and initialization like parsing
command line */
/* and connecting to database. Returns process id of
agent. */
/*****
*****
*/

void init_setup(int argc, char *argv[], struct
global_struct *g_struct)
{
    int connect=0;
#ifdef SQLWINT
    char *pid;
#endif
    char temparray[256]="\0";
    int loopvar=0;
    FILE *updateFP;
    FILE *fpSeed;
    char file_name[256] = "\0";
    short seedEntry;
    long lSeed;
    int i;

    /* Parse and process command line options */
    comm_line_parse (argc,argv,g_struct);

    /*****
    *****/
    /* Start the mainline report processing.
    */
    /*****
    *****/
    if (!strcmp(g_struct->c_l_opt->infile, "\0")) {
        instream=stdin;
    }
    else {
        instream=NULL;
        if ( (instream = fopen(g_struct->c_l_opt->infile,
READMODE)) == NULL ) {
            /* kjd715 */
            fprintf(outstream, "XXThe input file could not
be opened.\n\n");
            /* kjd715 */
            fprintf(stdout, "Make sure that the filename is
correct.\n");
            fprintf(stdout, "filename = %s\n", g_struct-
>c_l_opt->infile);
            exit(-1);
        } /* open the input file if specified */
    }

    /* IMPORT (begin) - determine whether we
should use the IMPORT api or */
    /* LOAD api for loading into the staging tables,
default is load */
    if (env_tpcd_update_import != NULL)
    {
        if
(!strcmp(uppercase(env_tpcd_update_import), "TRU
E"))
        {
            iImportStagingTbl = 1; /* use import */
        }
        /* DJD */
        else if
(!strcmp(uppercase(env_tpcd_update_import), "TF"))
        )
        {
            iImportStagingTbl = 2; /* Table Functions */
        }
    }

    /* IMPORT (end) */

```

```

/* we want to print the seed in the output files to
show what seed was */
/* used to generate the queries. */
/* if intStreamNum is -1 then we are running a
qualification database */
/* and the default seed has been used so skip this
section */
if (g_struct->c_l_opt->intStreamNum >= 0)
{
/* check to make sure the
TPCD_RUNNUMBER environment variable is set.
We */
/* use this and the stream number to determine
which seed was used to */
/* generate the current set of queries */
if (getenv("TPCD_RUNNUMBER") == NULL)
{
fprintf(stderr, "\nThe TPCD_RUNNUMBER
environment variable is not set");
fprintf(stderr, "....exiting\n");
exit(-1);
}
if (getenv("TPCD_NUMSTREAM") == NULL)
{
fprintf(stderr, "\nThe TPCD_NUMSTREAM
environment variable is not set");
fprintf(stderr, "....exiting\n");
exit(-1);
}

/*****
*****
* SEED jen
* we want to print the seed used in the output
files. For the seed usage
* we can now reuse the seeds from run to run,
therefore all the power runs
* will use the 1st seed in the file, and the
throughput streams will use
* the 2nd to #streams+1 seeds.
* determine the seed to use...e.g. given 3
streams will have the following:
*
* Entry in seed file
* TEST Stream Number Run 1 Run
2
* power 0 1 1
* throughput 1 2 2
* 2 3 3
* 3 4 4

*****
*****
seedEntry = g_struct->c_l_opt->intStreamNum
+ 1;
/* end SEED jen */

```

```

/* open the generated seed file...if not there, try
the default */

sprintf(file_name, "%s%sauditruns%sseedme",
env_tpcd_audit_dir,
env_tpcd_path_delim,
env_tpcd_path_delim);

if ((fpSeed = fopen(file_name, READMODE))
== NULL )
{
fprintf(stderr, "\nCannot open the seed file,
please ensure that\n");
fprintf(stderr, "the file exists. filename =
%s\n", file_name);
exit(-1);
}
for (i = 1; i <= seedEntry; i++)
{
if (feof(fpSeed))
{
lSeed = -1; /* seed not available for some
reason */
}
fscanf(fpSeed, "%ld\n", &lSeed);
}
g_struct->lSeed = lSeed;
fclose(fpSeed);
}

/* check to see if we are to use copy on for the
load */
if ((getenv("TPCD_LOG") != NULL) &&
(!strcmp(uppercase(getenv("TPCD_LOG")), "YES"))
)
{
/* okay, we have set LOG_RETAIN on so we
need to use copy directory */
g_struct->copy_on_load = TRUE;
}
else
{
/* log retain off don't use copy directory */
g_struct->copy_on_load = FALSE;
}

/*****
*****
/* Make sure that DB2 is started.
*/
/* CONNECT now unless this is a UF stream for a
Throughput test. */
/* (aph 98/12/22) */
/*****
*****

```

```

if (g_struct->c_l_opt->update > 1)
{
    /* This is an update function stream in a
throughput run. */
    /* Just make sure that DB2 is started. Each UF
child will CONNECT itself. */
    if (verbose) fprintf(stderr, "\nStarting the DB2
Database Manager Now\n");
    sqlestar ();
}
else
{ /* In all other cases, CONNECT to the target
database. */
    do
    {
        if (!strcmp(userid, "\0")) /** No authentication
provided **/
            EXEC SQL CONNECT TO :dbname;
        else EXEC SQL CONNECT TO :dbname
USER :userid USING :passwd;
        if (sqlca.sqlcode == SQLE_RC_NOSTARTG)
        {
            if (verbose)
                fprintf(stderr, "\nStarting the DB2 Database
Manager Now\n");
            sqlestar ();
            connect=0;
        }
        else connect=1;
    } while (!connect);
    error_check();
}

/*****
*****
* All session initialization is performed at connect
time or immediately *
* following and is complete before starting the
stream. *
*****
*****/

/** Get start timestamp for stream **/
get_start_time(&(g_struct->stream_start_time));
/* TIME_ACC jen*/
strcpy(g_struct->file_time_stamp,

get_time_stamp(T_STAMP_FORM_2, &(g_struct-
>stream_start_time)); /* TIME_ACC jen*/

if (getenv("TPCD_RUN_DIR") != NULL)
    strcpy(g_struct-
>run_dir, getenv("TPCD_RUN_DIR"));

```

```

else
    strcpy(g_struct->run_dir, ".");

/* if we are running a throughput test, then we
must report the */
/* stream count information...we will report one
file per stream */
/* and amalgamate them after all streams have
completed */
/* if the number of streams is greater than 0 then
this is a throughput test*/
switch (g_struct->c_l_opt->update)
{
    case (2):
    case (5):
        /* update throughput function stream */
        sprintf(file_name, "%s%sstrentuf.%s", g_struct-
>run_dir,
                env_tpcd_path_delim, g_struct-
>file_time_stamp);
        break;
    case (3):
    case (4):
        /* update power function stream */
        sprintf(file_name, "%s%spstrentuf.%s", g_struct-
>run_dir,
                env_tpcd_path_delim, g_struct-
>file_time_stamp);
        break;
    case (1):
        /* power query stream */
        sprintf(file_name,
"%s%spstrent%d.%s", g_struct->run_dir,
env_tpcd_path_delim,
                g_struct->c_l_opt-
>intStreamNum, g_struct->file_time_stamp);
        break;
    case (0):
        /* throughput query stream */
        sprintf(file_name,
"%s%sstrent%d.%s", g_struct->run_dir,
env_tpcd_path_delim,
                g_struct->c_l_opt-
>intStreamNum, g_struct->file_time_stamp);
        break;
}

if ( (g_struct->stream_report_file =
fopen(file_name, WRITEMODE)) == NULL )
{
    fprintf(stderr, "\nThe output file for the stream
count information\n");
    fprintf(stderr, "could not be opened, make sure the
filename is correct\n");
}

```



```

    fprintf(stderr,"filename = %s\n",file_name);
    exit(-1);
}

if (g_struct->c_l_opt->update > 1)
{
    /* update function stream */
    fprintf(g_struct->stream_report_file,
        "Update function stream starting at
    %*.*s\n",
        T_STAMP_3LEN,T_STAMP_3LEN, /*
    TIME_ACC jen*/

get_time_stamp(T_STAMP_FORM_3,&(g_struct-
>stream_start_time)); /* TIME_ACC jen*/
}
else
{
    /* query stream */
    fprintf(g_struct->stream_report_file,
        "Stream number %d starting at %*.*s\n",
        g_struct->c_l_opt->intStreamNum,
        T_STAMP_3LEN,T_STAMP_3LEN,
    /* TIME_ACC jen*/

get_time_stamp(T_STAMP_FORM_3,&(g_struct-
>stream_start_time)); /* TIME_ACC jen*/
}

#ifdef LINUX

    fclose(g_struct->stream_report_file);

#endif

    /* set up the update_num_file name so that if we
do use semaphores, */
    /* we will have a filename to generate the semkey
*/

    sprintf(g_struct->update_num_file,
"%s%s%s.%s.update.pair.num", env_tpcd_audit_dir,
    env_tpcd_path_delim,
    uppercase(env_tpcd_dbname),
    lowercase(env_user));
    sprintf(g_struct->sem_file, "%s.%s.semfile",
env_tpcd_dbname, env_user);
    if (g_struct->c_l_opt->intStreamNum == 0)
    {
        sprintf(g_struct->sem_file2, "%s.%s.semfile2",
env_tpcd_dbname, env_user);
    }
    if (verbose) { /* print out the update pair number
file for debugging */
        fprintf(stderr,"\n init_setup: strem %d update pair
numb file = %s\n",

        g_struct->c_l_opt->intStreamNum,g_struct-
>update_num_file);
    }

    /* update the
$TPCD_AUDIT_DIR/$TPCD_DBNAME.$USER.u
pdate.pair.num file */
    /* update pairs have been run */
    if (( g_struct->c_l_opt->update >= 1 ) && (
g_struct->c_l_opt->update < 4 ))
        /* on or onl, but not */ /* bbe or > 1 */
    {
        updateFP = fopen(g_struct-
>update_num_file,"r");
        if (updateFP != NULL )
        {
            fscanf(updateFP,"%d",&updatePairStart);
            fclose(updateFP);
            if (g_struct->c_l_opt->intStreamNum == 0)
/* on, 1 update pair */
                updatePairStop = updatePairStart + 1;
            else /* only, multiple update pairs, stream
number will be total */
                updatePairStop = updatePairStart + g_struct-
>c_l_opt->intStreamNum;
            currentUpdatePair = updatePairStart;

            if (updatePairStart <= 0)
            {
                fprintf(stderr,"updatePairStart is bogus!");
                exit(-1);
            }
        }
        else
        {
            fprintf(stderr,"\n %s not set up, set this
\n",g_struct->update_num_file);
            fprintf(stderr,"file to contain the number of the
update pair to \n");
            fprintf(stderr,"run and resubmit\n");
            exit(-1);
        }
    }

    return ;
}

/*****
*****/
/* A function to print out the column titles for a
returned set */
/*****
*****/
void print_headings (struct sqllda *sqllda, int
*col_lengths)

```

```

{
  int col = 0;          /* Column number
*/
  int col_width = 0;   /* width of column
*/
  int max_col_width = 0; /* maximum
column width */
  int col_name_length = 0; /* sizeof column
name string */
  int col_type = 0;    /* column type
*/

  int total_length = 0; /* accumulator var.
for
                        length of column headings
*/
  int loopvar = 0;

  char col_name[256] = "\0";
  unsigned char m,n;   /* precision and
accuracy
                        for decimal conversion
*/

  fprintf (outstream,"\n");

  /** loop through for each column in solution set
and determine the maximum column width **/

  for (col = 0; col < sqlda->sqlc; col++) {
    col_name_length=sqlda-
>sqlvar[col].sqlname.length;
    col_type = sqlda->sqlvar[col].sqltype;
    col_width = sqlda->sqlvar[col].sqllen;
    strncpy(col_name,(char *)sqlda-
>sqlvar[col].sqlname.data,col_name_length) ;

    switch (col_type)
    {
      case SQL_TYP_SMALL:
      case SQL_TYP_NSMALL:
/* @d30369 tjc */
        col_lengths[col] = TPCDBATCH_MAX
(col_name_length,6);
        break;
      case SQL_TYP_INTEGER:
      case SQL_TYP_NINTEGER:
        col_lengths[col] = TPCDBATCH_MAX
(col_name_length,11);
        break;
      case SQL_TYP_BIGINT: /*kmwBIGINT*/
      case SQL_TYP_NBIGINT:
        col_lengths[col] = TPCDBATCH_MAX
(col_name_length,19);
        break;
      case SQL_TYP_CSTR:

```

```

      case SQL_TYP_NCSTR:
      case SQL_TYP_DATE:
      case SQL_TYP_NDATE:
      case SQL_TYP_TIME:
      case SQL_TYP_NTIME:
      case SQL_TYP_STAMP:
      case SQL_TYP_NSTAMP:
      case SQL_TYP_CHAR:
      case SQL_TYP_NCHAR:
      case SQL_TYP_VARCHAR:
      case SQL_TYP_NVARCHAR:
      case SQL_TYP_LONG:
      case SQL_TYP_NLONG:
        col_lengths[col] = TPCDBATCH_MAX
(col_name_length,col_width);
        break;

      case SQL_TYP_FLOAT:
      case SQL_TYP_NFLOAT:
        /* kmw - note:
TPCDBATCH_PRINT_FLOAT_WIDTH > max
long identifier */
        col_lengths[col] =
TPCDBATCH_PRINT_FLOAT_WIDTH;
        break;

      case SQL_TYP_DECIMAL:
      case SQL_TYP_NDECIMAL:

        m=(*(struct declen *)&sqlda-
>sqlvar[col].sqllen).m;
        n=(*(struct declen *)&sqlda-
>sqlvar[col].sqllen).n;

        col_lengths[col] = TPCDBATCH_MAX
((int)(m+n), col_name_length);
        /* Special handling for DECIMAL */ /*
@d26350 tjc */
        break;

      default:
        fprintf(stderr,"--Unknown column type (%d).
Aborting.\n",col_type);
        break;
    }

    fprintf(outstream,"%-*.s
",col_lengths[col],col_name_length,col_name);

    total_length += (col_lengths[col] + 2); /* 2 is
from padding spaces */
  }

  fprintf(outstream,"\n");
  for (loopvar=0; loopvar < total_length; loopvar++)
    fprintf(outstream,"-");

```

```

    fprintf(outstream,"\n");
}

/*****
*****/
/* Gets the current system time and prints it out
*/
/*****
*****/
char *get_time_stamp(int form, Timer_struct
*time_pointer)
{
    Timer_struct temp_stamp; /* TIME_ACC jen */
    struct tm *tp;
    size_t timeLength = 0;

    /* TIME_ACC jen start */
    if (time_pointer == (Timer_struct *)NULL)
        get_start_time(&temp_stamp);
    else
        temp_stamp = *time_pointer;

#if defined (SQLUNIX) || defined (SQLAIX)
    tp = localtime((time_t *)&(temp_stamp.tv_usec));
#elif defined (SQLOS2) || defined (SQLWINT) ||
defined (SQLWIN) || defined (SQLDOS))
    tp = localtime(&(temp_stamp.time));
#else
#error Unknown operating system
#endif
    /* TIME_ACC jen stop*/

    if ((form == T_STAMP_FORM_1) || (form ==
T_STAMP_FORM_3))
    {
        /* SUN fix bbe start */
#if defined (SQLWINT) || defined (SQLWIN) ||
defined (SQLOS2) || defined (SQLDOS))
            timeLength = strftime(newtime,50,"%x %X",tp);
#elif defined (SQLUNIX) || defined (SQLAIX))
            timeLength = strftime(newtime,50,"%D
%T",tp); /* SUN ...test this */
#else
#error Unknown operating system
#endif
        /* SUN fix bbe stop */
        /* TIME_ACC jen start*/
        if (form == T_STAMP_FORM_3)
        {
            /* concatenate the microsecond/milliseconds
on the end of the */
            /*timestamp jen1006 */
#if defined (SQLUNIX) || defined (SQLAIX)
                sprintf(newtime+timeLength,"%0.6d",temp_stamp.t
v_usec);
                #elif defined (SQLOS2) || defined (SQLWINT) ||
defined (SQLWIN) || defined (SQLDOS))
                sprintf(newtime+timeLength,"%0.3d",temp_stamp.
millitm);
                #else
                #error Unknown operating system
                #endif
                /* TIME_ACC jen stop*/
            }
        }
        else
            if (form == T_STAMP_FORM_2)
                strftime(newtime,50,"%y%m%d-
%H%M%S",tp);

        return (newtime);
    }

/*****
*****/
/* Handle all the processing for the summary table
*/
/*****
*****/

void summary_table (struct global_struct *g_struct)
{
    double arith_mean = 0;
    double geo_mean = 0;
    int num_stmt = 0;
    int num_stmt_for_geo_mean = 0;

    double adjusted_a_mean = 0;
    double adjusted_g_mean = 0;
    double adjusted_g_mean_intern;
    double adjusted_max_time = 0;

    double Ts = 0; /* different TPC-D
metrics */
    double Ts1;
    double Ts2;
    /* double QppD = 0; MARK
double QthD = 0;
double QphD = 0; */

    double db_size_frac_part = 0; /* stores the
fractional part of db size */
    double db_size = 0; /* size in numbers */

```

```

char db_size_qualifier[3] = "\0"; /* MB, GB or
TB */

struct stmt_info
*s_info_ptr,
*s_info_head_ptr,
*max,
*min;

/* Determine the size of the database from the
scale factor (1 SF = 1GB) */
if (g_struct->scale_factor < 1.0) {
db_size = g_struct->scale_factor * 1000;
strcpy(db_size_qualifier, "MB");
} else if (g_struct->scale_factor >= 1000.0) {
db_size = g_struct->scale_factor / 1000;
strcpy(db_size_qualifier, "TB");
} else {
db_size = g_struct->scale_factor;
strcpy(db_size_qualifier, "GB");
}

/* computes the fractional part of db_size */
db_size_frac_part = db_size - (int) db_size;

s_info_ptr = g_struct->s_info_ptr; /* Just use a
local copy */
s_info_head_ptr = s_info_ptr;

max = s_info_head_ptr;
/* ensure that we are not already setting max to the
UF timings */
while ( strstr(max->tag, "UF") != NULL )
max = max->next;
min = max;

if (g_struct->c_l_opt->outfile) /* create the
appropriate output file */
output_file(g_struct);

/* write the seed used for this run unless it is a
qualification run */
/* (qualification runs use the default seed for their
queries) or */
/* unless it is the update function stream (no seeds
used for this) */
/* (this is an update stream iff update is 2) */
if ((g_struct->c_l_opt->intStreamNum >=0) &&
(g_struct->c_l_opt->update != 2) )
{
if (g_struct->lSeed == -1)
{
fprintf( ostream, "\nUsing default qgen seed
file");

```

```

}
else
fprintf (ostream, "\nSeed used for current run
= %ld", g_struct->lSeed);
fprintf( ostream, "\n");
}

/* print out the stream number if we are in a
throughput stream and if */
/* this is not the update stream portion of the
throughput test */
if ( (g_struct->c_l_opt->intStreamNum > 0) &&
(g_struct->c_l_opt->update != 2) )
{
fprintf( ostream, "Stream number =
%d\n", g_struct->c_l_opt->intStreamNum);
}
/* print the stream start timestamp to the inter file
*/
fprintf (ostream, "Stream start time stamp
%*. *s\n",
T_STAMP_3LEN, T_STAMP_3LEN, /*
TIME_ACC jen*/

get_time_stamp(T_STAMP_FORM_3, &(g_struct->
stream_start_time)); /* TIME_ACC jen*/
/* print the stream stop timestamp to the inter file
*/
fprintf (ostream, "Stream stop time stamp
%*. *s\n",
T_STAMP_3LEN, T_STAMP_3LEN, /*
TIME_ACC jen*/

get_time_stamp(T_STAMP_FORM_3, &(g_struct->
stream_end_time)); /* TIME_ACC jen*/

fprintf (ostream, "\n\nSummary of
Results\n=====\n");
fprintf (ostream,
"\nSequence # Elapsed Time Adjusted
Time Start Timestamp End Timestamp\n\n");

/* Go through the linked list and determine which
statement had the
highest and lowest elapsed times */
while ( (s_info_ptr != NULL) && (s_info_ptr !=
g_struct->s_info_stop_ptr) ) {

/* check if we are in an update function...if so,
we do not want to */
/* consider the update function times as the min
or max time */
if ( strstr(s_info_ptr->tag, "UF") == NULL )
{
/* we are not in an update function */

```

```

        if (s_info_ptr->elapse_time > max-
>elapse_time)
            max = s_info_ptr;
        else
            if ((s_info_ptr->elapse_time < min-
>elapse_time)
                && (s_info_ptr->elapse_time > -1))
                min = s_info_ptr;
            }

        s_info_ptr = s_info_ptr->next;

    }

    s_info_ptr = s_info_head_ptr;

    /** Start from the first structure and go through
until the stop
pointer is reached **/
    while ( (s_info_ptr != NULL) && (s_info_ptr !=
g_struct->s_info_stop_ptr) ) {

        if (s_info_ptr->elapse_time != -1) {
            s_info_ptr->adjusted_time = s_info_ptr-
>elapse_time;
            /* determine whether the elapsed times have to
be adjusted or not */
            /* if this is an update function, we do not
adjust the elapsed time*/
            if ( strstr(s_info_ptr->tag,"UF") == NULL )
                {
                    /* this is not an update function, adjust time
if necessary */
                    if (max->elapse_time/min->elapse_time >
1000)
                        {
                            /* jmc fix geo_mean calculation...round
adjusted time properly ROUNDING*/
                            adjusted_max_time = max-
>elapse_time/1000;
                            if (s_info_ptr->elapse_time <
adjusted_max_time)
                                {
                                    s_info_ptr->adjusted_time =
(double)(((long)((adjusted_max_time +
0.05) * 10))/10.0);
                                    if (s_info_ptr->adjusted_time < 0.1)
                                        s_info_ptr->adjusted_time = 0.1;
                                }
                            /*jmc fix geo_mean calculation...round
adjusted time properly ROUNDING end*/
                        }
                    }
                }

            /* a value was calculated
*/

```

```

        fprintf (outstream,
                "%-5d %-5.5s %15.1f %15.1f %*.*s
%*.*s\n",
                s_info_ptr->stmt_num,s_info_ptr->tag,
                s_info_ptr->elapse_time,s_info_ptr-
>adjusted_time,
                T_STAMP_1LEN,T_STAMP_1LEN,s_info_ptr-
>start_stamp, /* TIME_ACC jen*/
                T_STAMP_1LEN,T_STAMP_1LEN,s_info_ptr-
>end_stamp); /* TIME_ACC jen*/

        /* Only update arithmetic mean for queries not
update functions */
        if ( strstr(s_info_ptr->tag,"UF") == NULL )
            {
                arith_mean += s_info_ptr->elapse_time;
                adjusted_a_mean += s_info_ptr-
>adjusted_time;
            }

        if (s_info_ptr->elapse_time > 0) { /* don't
bother finding log of
                numbers < 0 */
                geo_mean += log(s_info_ptr->elapse_time);
                adjusted_g_mean += log(s_info_ptr-
>adjusted_time);
            }

        /* Only update num_stmt for queries not
update functions */
        if ( strstr(s_info_ptr->tag,"UF") == NULL )
            num_stmt ++;
            num_stmt_for_geo_mean++;
        }

        else
            fprintf (outstream,"%-5d %-5.5s %-15s %-
15s\n",
                    s_info_ptr->stmt_num,
                    s_info_ptr->tag,"Not Collected", "Not
Collected");

            if (s_info_ptr != g_struct->s_info_stop_ptr)
                s_info_ptr=s_info_ptr->next;
            }

        fprintf(outstream, "\n\nNumber of statements:
%d\n\n", s_info_ptr->stmt_num - 1);
        /* Calculate the arithmetic and geometric means */

        if (geo_mean != 0) { /*Used to test if
arith_mean != 0

```

```

the
        Don't bother doing any of this if
        elapsed time mean is 0 */
        arith_mean = arith_mean / num_stmt;
        adjusted_a_mean = adjusted_a_mean /
num_stmt;
        geo_mean = exp(geo_mean /
num_stmt_for_geo_mean);
        adjusted_g_mean_intern = adjusted_g_mean;
/*MARK*/
        adjusted_g_mean = exp(adjusted_g_mean /
num_stmt_for_geo_mean);

    }

/* print out all the appropriate information
including the
different TPC-D metrics */
/* do not bother with this if we are in an update
only stream */
fprintf (outstream, "\nGeom. mean queries %7.3f
%15.3f\n",\
        geo_mean,adjusted_g_mean);
if (g_struct->c_1_opt->update < 2)
{
    fprintf (outstream, "Arith. mean queries %7.3f
%15.3f\n",\
        arith_mean,adjusted_a_mean);

    fprintf (outstream,
        "\n\nMax Qry %-3.3s %15.1f %15.1f
%*. *s %*. *s\n",
        max->tag,max->elapse_time,max-
>adjusted_time,
        T_STAMP_1LEN,T_STAMP_1LEN,max-
>start_stamp, /* TIME_ACC jen*/
        T_STAMP_1LEN,T_STAMP_1LEN,max-
>end_stamp); /* TIME_ACC jen*/
    fprintf (outstream,
        "Min Qry %-3.3s %15.1f %15.1f %*. *s
%*. *s\n",
        min->tag,min->elapse_time,min-
>adjusted_time,
        T_STAMP_1LEN,T_STAMP_1LEN,min-
>start_stamp, /* TIME_ACC jen*/
        T_STAMP_1LEN,T_STAMP_1LEN,min-
>end_stamp); /* TIME_ACC jen*/
}

if (g_struct->c_1_opt->intStreamNum == 0) {
    /* fprintf (outstream,
"\n\nMetrics\n===== \n\n"); */

```

```

/* Increase the Ts measurement by one second
since the accuracy of our */
/* timestamps is only to 1 second and if the start
was at 1.01 seconds, */
/* and the end was at 5.99 seconds, we get a free
second ... this will */
/* be made explicit in the upcoming revision of
the spec (after 1.0.1) */
/* TIME_ACC jen start*/
/* NOTE this can probably be better coded by
changing get_elapsed_time */
/* to just calculate the elapsed time give a start
and an end time, and */
/* to also give a precision for the calculation
(sec, 10ths...). The */
/* call then will grab a timestamp before calling.
Then we can get rid */
/* of the if def...and just call get_elapsed_time
(which can handle the */
/* os differences on its own */

#if defined (SQLUNIX) || defined (SQLAIX)
    Ts = g_struct->stream_end_time.tv_sec -
g_struct->stream_start_time.tv_sec + 1;
    Ts1 = (double)g_struct-
>stream_start_time.tv_sec + ((double)g_struct-
>stream_start_time.tv_usec/1000000);
    Ts2 = (double)g_struct-
>stream_end_time.tv_sec + ((double)g_struct-
>stream_end_time.tv_usec/1000000);

#elif defined (SQLOS2) || defined (SQLWINT) ||
defined (SQLWIN) || defined (SQLDOS))
    Ts = g_struct->stream_end_time.time - g_struct-
>stream_start_time.time + 1;
    Ts1 = (double)g_struct->stream_start_time.time
+ ((double)g_struct-
>stream_start_time.millitm/1000);
    Ts2 = (double)g_struct->stream_end_time.time
+ ((double)g_struct-
>stream_end_time.millitm/1000);

#else
#error Unknown operating system
#endif

/* TIME_ACC jen stop*/

/* MARK
##Now do in calcmetricsp.pl##
QppD = (3600 * g_struct->scale_factor) /
adjusted_g_mean;
QthD = (num_stmt * 3600 * g_struct-
>scale_factor) / Ts;
QphD = sqrt(QppD*QthD);
*/

```

```

    /* if the decimal part has some meaningful value
    then print the database size
    with decimal part; otherwise just print the
    integer part */

```

```

    fprintf (outstream,
            "\nGeometric mean interim value =
    %10.3f\n\nStream Ts %11 = %10.0f\n\nStream start
    int representation %11 = %f\n\nStream stop int
    representation %11 = %f",
            adjusted_g_mean_intern,Ts,Ts1,Ts2);
    }
}

```

```

/*****
*****/

```

```

/* free up all the elements of the sqlda after done
processing */
/*****
*****/

```

```

void free_sqlda (struct sqlda *sqlda, int
select_status) /* @d30369 tjc */
{
    int loopvar;

    if (select_status == TPCDBATCH_SELECT)
        for (loopvar=0; loopvar<sqlda->sqld; loopvar++)
        {
            free(sqlda->sqlvar[loopvar].sqldata);
            free(sqlda->sqlvar[loopvar].sqlind);
        }

    free(sqlda);
    sqlda_allocated = 0; /* fix free() problem on NT
        wlc 090597 */
}

```

```

/*****
*****/

```

```

/* processing to run the insert update function */
/*****
*****/

```

```

void runUF1 ( struct global_struct *g_struct, int
updatePair )
{
    char statement[3000];
    char sourcedir[256];

    int split_updates = 2; /* no. of ways update
records are split */

```

```

    int concurrent_inserts = 2; /* jenCI no of
concurrent updates to be */
        /* jenCI run at once*/
    int loop_updates = 1; /* jenCI no of updates to
be run in one */
        /* jenCI "concurrent"
invocation. should*/
        /* jenCI be split_updates /
concurrent_inserts*/
    int i;
    int streamNum;
#endifdef SQLWINT
    /* PROCESS_INFORMATION
childprocess[100]; */
    char commandline[256];
    HANDLE su_hSem;
    char UF1_semfile[256];
#endifelse
    int childpid[100];
    int su_sem; /* semaphore for
controlling split updates*/
    key_t su_semkey; /* key to generate
semid */
#endifif
    if (g_struct->c_l_opt->intStreamNum == 0)
        streamNum = 0;
    else
        streamNum = currentUpdatePair -
updatePairStart + 1;

```

```

    fprintf( outstream,"UF1 for update pair %d, stream
%d, starting\n",updatePair, streamNum);

    /* Start by loading the data into the staging table at
each node */
    /* The orderkeys were split earlier by the
split_updates program */
    if (env_tpcd_audit_dir != NULL)
        strcpy(sourcedir,env_tpcd_audit_dir);
    else
        strcpy(sourcedir,".");

    /* Load the orderkeys into the staging table */
    /* In SMP environments one could use a load
command but by using a */
    /* script we can keep the code common */
#endifdef SQLWINT
    sprintf (statement, "perl %s\\tools\\ploaduf1
%d\n", sourcedir, updatePair);
#endifelse
    sprintf (statement, "perl %s/tools/ploaduf1 %d 1",
sourcedir, updatePair);
#endifif
    if (system(statement))
    {

```

```

    }
}

```

```

}
}

```

```

    fprintf(stderr, "ploaduf1 failed for UF1, examine
UF1.log for cause. Exiting.\n");
    if (verbose)
        fprintf(stderr,
            "ploaduf1 failed for UF1, examine UF1.log
for cause. Exiting.\n");
    exit (-1);
}

fprintf (outstream, "load_update finished for
UF1.\n");

if (getenv ("TPCD_SPLIT_UPDATES") !=
NULL)
    split_updates = atoi (getenv
("TPCD_SPLIT_UPDATES"));
if (getenv ("TPCD_CONCURRENT_INSERTS")
!= NULL)
    /*jenCI*/
    concurrent_inserts = atoi (getenv
("TPCD_CONCURRENT_INSERTS")); /*jenCI*/
loop_updates = split_updates / concurrent_inserts;
/*jenCI*/

#ifdef SQLWINT
/* we will use the tpcd.setup file to generate the
semaphore key */
if (getenv("TPCD_AUDIT_DIR") != NULL)
/*begin SEMA */
{
    /* this is assuming that you will be running this
from 0th node */
    sprintf(sourcefile, "%s%ctools%ctpcd.setup",
getenv("TPCD_AUDIT_DIR"),
PATH_DELIM,PATH_DELIM);
}
else
{
    fprintf (stderr, "runUF1 Can't open UF1
semaphore file,TPCD_AUDIT_DIR is not
defined.\n");
    exit (-1);
}
/*end SEMA */
su_semkey = ftok (sourcefile, 'J');
if ( (su_semid = semget (su_semkey, 1,
IPC_CREAT|S_IRUSR|S_IWUSR)) < 0)
{
    fprintf (stderr, "Cannot get semaphore! semget
failed: errno = %d\n",errno);
    exit (-1);
}
#else /* SQLWINT */
    sprintf (UF1_semfile, "%s.%s.UF1.semfile",
env_tpcd_dbname, env_user);
    su_hSem = CreateSemaphore(NULL, 0,
concurrent_inserts,
(LPCTSTR)(UF1_semfile));
if (su_hSem == NULL)
{
    fprintf(stderr,
        "CreateSemaphore (ready semaphore)
failed, GetLastError: %d, quitting\n",
        GetLastError());
    exit(-1);
}
#endif /* SQLWINT */
if (verbose) fprintf(stderr,"Semaphore created
successfully!\n");

fclose(outstream); /* to prevent multiple header
caused by forking
wlc 081397 */

for (i=0; i < concurrent_inserts; i++)
/*jenCI*/
{
#ifdef SQLWINT
if ((childpid[i] = fork()) == 0)
{
    /* runUF1_fn (updatePair, i); aph 981205 */
    runUF1_fn (updatePair, i, dbname, userid,
passwd);
}
else
{
    /* This is the parent */
    if (verbose)
        fprintf (stderr, "stream # %d started with pid
%d\n", i, childpid[i]);
}
#else /* SQLWINT */
    sprintf (commandline,
        "start /b %s\\auditruns\\tpcdbatch.exe -z -d
%s -i %d -j 1 -k %d",
        env_tpcd_audit_dir, dbname, updatePair, i
); /* aph 082797 */

    system (commandline);
#endif /* SQLWINT */
// sleep (UF1_SLEEP);
}

/* All children have been created, now wait for
them to finish */
#ifdef SQLWINT
if (sem_op (su_semid, 0, concurrent_inserts * -1)
!= 0)
/*jenCI*/
{
/*jenSEM*/
    fprintf(stderr,

```



```

        "Failure to wait on insert semaphore with
%d of children\n",
        concurrent_inserts);
        exit(1);
    }
/*jenSEM*/
    semctl (su_semId, 0, IPC_RMID, 0);
#else
    for (i = 0; i < concurrent_inserts; i++)
/*jenCI*/
    {
        if (verbose)
        {
            fprintf(stderr,"About to wait again ...Sets to
wait for %d\n",
                concurrent_inserts - i);
/*jenCI*/
        }
        if (WaitForSingleObject(su_hSem, INFINITE)
== WAIT_FAILED)
        {
            fprintf(stderr,
                "WaitForSingleObject (su_hSem) failed
in runUF1 on set %d, error: %d, quitting\n",
                i, GetLastError());
            exit(-1);
        }
    }
    if (! CloseHandle(su_hSem))
    {
        fprintf(stderr,
            "RunUF1 Close Sem failed - Last Error:
%d\n", GetLastError());
        /* no exit here */
    }
#endif

    if( (outstream = fopen(outstreamfilename,
APPENDMODE)) == NULL )
    {
        fprintf(stderr, "\n\nThe output file could not be
opened. ");
        fprintf(stderr, "Make sure that the filename is
correct.\n");
        fprintf(stderr, "filename =
%s\n",outstreamfilename);
        exit(-1);
    }

    fprintf( ostream,"UF1 for update pair %d
complete\n",updatePair);
}

/* runUF1_fn() moved to another SQC file
aph 981205 */

```

```

/*****
*****/
/* processing to run the delete update function */
/*****
*****/
void runUF2 ( struct global_struct *g_struct, int
updatePair )
{
    char statement[3000];
    char sourcedir[256];

    int split_deletes = 1; /* no. of ways update
records are split @dxxxxxhar */
    int concurrent_deletes = 1; /* number of
database partitions DELjen */
    int chunks_per_concurrent_delete = 1;

    int i;
    int streamNum;
#ifdef SQLWINT
    char commandline[256];
    HANDLE su_hSem;
    char UF2_semfile[256];
#else
    int childpid[100];
    char sourcefile[256];
    int su_semId; /* semaphore for
controlling split updates*/
    key_t su_semkey; /* key to generate
semid */
#endif
    if (g_struct->c_1_opt->intStreamNum == 0)
        streamNum = 0;
    else
        streamNum = currentUpdatePair -
updatePairStart + 1;

    fprintf( ostream,"UF2 for update pair %d, stream
%d, starting\n",updatePair, streamNum);

    /* We need to know both how many chunks there
are and how many chunks*/
    /* are to be executed by each concurrent UF2
process. More chunks means */
    /* both smaller transactions (less deadlock) and
more potential concurrency */

    /* How many "chunks" have the orderkeys been
divided into? */
    if (getenv ("TPCD_SPLIT_DELETES") !=
NULL)
        split_deletes = atoi (getenv
("TPCD_SPLIT_DELETES"));
    /* How many deletes should run concurrently */

```

```

    if (getenv ("TPCD_CONCURRENT_DELETES")
    != NULL)
        concurrent_deletes = atoi (getenv
("TPCD_CONCURRENT_DELETES"));
        /* How many chunks in each concurrently running
delete process */
        chunks_per_concurrent_delete = split_deletes /
concurrent_deletes;

        /* Start by loading the data into the staging table at
each node */
        /* The orderkeys were split earlier by the
split_updates program */
        if (env_tpcd_audit_dir != NULL)
            strcpy(sourcedir,env_tpcd_audit_dir);
        else
            strcpy(sourcedir, ".");

        /* Load the orderkeys into the staging table */
        /* In SMP environments one could use a load
command but by using a */
        /* script we can keep the code common */

#ifdef SQLWINT
    sprintf (statement, "perl %s\tools\ploaduf2
%d\n", sourcedir, updatePair);
#else
    sprintf (statement, "perl %s/tools/ploaduf2 %d 2",
sourcedir, updatePair);
#endif
    if (system(statement))
    {
        fprintf (stderr, "ploaduf2 failed for UF2, examine
UF2.log for cause. Exiting.\n");
        exit (-1);
    }
    fprintf (outstream, "ploaduf2 finished for
UF2.\n");

    fclose(outstream); /* to prevent multiple header
caused by forking
        wlc 081397 */

    /* Next we need to get ready to launch a bunch of
concurrent processes */
#ifdef SQLWINT
    /* we will use the tpcd.setup file to generate the
semaphore key begin SEMA */
    if (getenv("TPCD_AUDIT_DIR") != NULL)
    {
        sprintf(sourcefile, "%s%ctools%ctpcd.setup",
getenv("TPCD_AUDIT_DIR"),
PATH_DELIM, PATH_DELIM);
    }
else
    {
        fprintf (stderr, "runUF2 Can't open UF2
semaphore file, TPCD_AUDIT_DIR is not
defined.\n");
        exit (-1);
    }

    su_semkey = ftok (sourcefile, 'D'); /* use D for
deletes */
    /* end SEMA */
    if ( (su_semid = semget (su_semkey, 1,
IPC_CREAT|S_IRUSR|S_IWUSR)) < 0)
    {
        fprintf (stderr, "UF2 Can't get semaphore!
semget failed: errno = %d\n",
errno);
        exit (-1);
    }
#else
    sprintf (UF2_semfile, "%s.%s.UF2.semfile",
env_tpcd_dbname, env_user);
    fprintf(stderr,"UF2 semfile = %s\n",UF2_semfile);
    su_hSem = CreateSemaphore(NULL, 0,
concurrent_deletes,
(LPCTSTR)(UF2_semfile));
    if (su_hSem == NULL)
    {
        fprintf(stderr,
"CreateSemaphore (ready semaphore)
failed, GetLastError: %d, quitting\n",
GetLastError());
        exit(-1);
    }
    fprintf(stderr,"Semaphore created
successfully!\n");
#endif

    for (i=0; i < concurrent_deletes; i++)
    {
#ifdef SQLWINT
        if ((childpid[i] = fork()) == 0)
        {
            fprintf(stderr, "B-Calling runUF2_fn %d %d
%d ... \n",
updatePair,
i,chunks_per_concurrent_delete);
            /* runUF2_fn (updatePair, i,
chunks_per_concurrent_delete); aph 981205 */
            runUF2_fn (updatePair, i,
chunks_per_concurrent_delete, dbname, userid,
passwd);
        }
        else
        {
            /* This is the parent */

```

```

        if (verbose)
            fprintf(stderr, "stream #%d started with pid
%d\n", i, childpid[i]);
    }
#else
    {
        /* SECURITY_ATTRIBUTES sec_process;
        SECURITY_ATTRIBUTES sec_thread; */
        /* NEED TO FIX THIS UP - KBS 98/10/20 */

        sprintf (commandline,
            "start /b %s\auditruns\tpcdbatch.exe -z -d
%s -i %d -j 2 -k %d -x %d",
            env_tpcd_audit_dir, dbname, updatePair, i,
            chunks_per_concurrent_delete ); /* aph */
        /* the -x parm should be passed at 0...not
        100% sure of this jen */
        fprintf(stderr, "commandline= %s\n",
            commandline);
        system (commandline);
        // sleep (UF2_SLEEP);
    }
#endif
}

/* All children have been created, now wait for
them to finish */
#ifdef SQLWINT
    fprintf(stderr, "About to wait on the
semaphore...\n");
    if (sem_op (su_semId, 0, concurrent_deletes * -1)
!= 0) /*jenSEM*/
    {
        /*jenSEM*/
        fprintf(stderr,
            "Failure to update wait on delete
semaphone with %d children\n",
            concurrent_deletes);
        exit(1);
    }
    /*jenSEM*/
    semctl (su_semId, 0, IPC_RMID, 0);
#else
    // for (i = 0; i < split_deletes; i++) //DJD Waits
    forever.....
        for (i = 0; i < concurrent_deletes; i++)
        {
            if (verbose)
            {
                // fprintf(stderr, "About to wait again ...Sets to
                wait for %d\n",
                // split_deletes - i);
                fprintf(stderr, "About to wait again ...Sets to
                wait for %d\n",
                concurrent_deletes - i);
            }
        }

```

```

    if (WaitForSingleObject(su_hSem, INFINITE)
== WAIT_FAILED)
    {
        fprintf(stderr,
            "WaitForSingleObject (su_hSem) failed
on set %d, error: %d, quitting\n",
            i, GetLastError());
        exit(-1);
    }
}
if (! CloseHandle(su_hSem))
{
    fprintf(stderr, "Close Sem failed - Last Error:
%d\n", GetLastError());
    /* no exit here */
}
#endif

if( (outstream = fopen(outstreamfilename,
APPENDMODE)) == NULL )
{
    fprintf(stderr, "\nThe output file could not be
opened. ");
    fprintf(stderr, "Make sure that the filename is
correct.\n");
    fprintf(stderr, "filename =
%s\n", outstreamfilename);
    exit(-1);
}

fprintf(ostream, "UF2 for update pair %d
complete\n", updatePair);
}

/* runUF2_fn() moved to another SQC file
aph 981205 */

/*-----
-*/
/*      General semaphore function.
*/
/*-----
-*/
#ifdef SQLWINT
int sem_op (int semid, int semnum, int value)
{
    struct sembuf sembuf; /* = {semnum ,value,0};
*/
    sembuf.sem_num = semnum;
    sembuf.sem_op = value;
    sembuf.sem_flg = 0;

    if (semop(semid, &sembuf, 1) < 0)

```

```

    {
        fprintf(stderr,"ERROR*** sem_op errorno =
%d\n", errno);
        return(-1);
        /* exit(1); */
    }
    return (0); /* successful return jenSEM */
}
#endif

/*****
*****/
/* Determines the proper name for the output file to
be generated for a particular TPC-D query, update
function, or
interval summary */
/*****
*****/
void output_file(struct global_struct *g_struct)
{
    char file_name[256] = "\0";
    char run_dir[150] = "\0";
    char time_stamp[50] = "\0";
    char delim[2] = "\0";
    int qnum=0, found=0; /* kjd715 */
    char input_ln[256] = "\0"; /* kjd715 */
    char tag[128] = "\0"; /* kjd715 */

    strcpy(run_dir,g_struct->run_dir);
    sprintf(delim,"%s",env_tpcd_path_delim);
    strcpy(time_stamp,g_struct->file_time_stamp);
    /* kjd715 */
    if (g_struct->stream_list == NULL)
    {
        if((g_struct->stream_list =
            fopen(g_struct->c_l_opt->infile,
READMODE)) == NULL)
        {
            fprintf(stderr,"\n\nThe input file could not be
opened.");
            fprintf(stderr,"Make sure that the filename is
correct.\n");
            exit(-1);
        }
    }
    found = 0;
    do {
        fscanf(g_struct->stream_list, "\n%[\n]\n",
input_ln);
        if (strstr(input_ln, "--#TAG") == input_ln)
        {
            found = 1;
            strcpy(tag,(input_ln+sizeof("--#TAG")));
            if(strncmp(tag, "UF", 2) == 0)
                qnum = atoi(tag+2)*(-1);
            else if(strncmp(tag, "Q", 1) == 0 )

```

```

        {
            /* for query 15a the 'a' must be
trimmed */
            /* off before converting to integer
*/
            if(strlen(tag)>3)
                tag[3] = '\0';
            qnum = atoi(tag+1);
        }
    }

    if (feof(g_struct->stream_list))
        found = 1;

    }while (!found);
    /*
    if ((g_struct->stream_list =
        fopen(g_struct->c_l_opt-
>str_file_name, READMODE)) == NULL)
    {
        fprintf(stderr, "\n\nThe stream list file could not
be opened.");
        fprintf(stderr, "Make sure that the filename is
correct.\n");
        exit(-1);
    }

    fscanf(g_struct->stream_list,"%d",&qnum);
    /*
    /* kjd715 */

    switch (g_struct->c_l_opt->intStreamNum)
    {
        case -1: /* qualifying */
            sprintf(file_name,
"%s%sqryqual%02d.%s",run_dir,delim,qnum,time_
stamp);
            break;
        case 0: /* power tests */
            if (qnum < 0) /* update functions */
                sprintf(file_name,
"%s%smp00uf%d.%02d.%s",run_dir,delim,abs(qn
um), \
                currentUpdatePair,time_stamp);
            else
                sprintf(file_name,
"%s%smpqry%02d.%s",run_dir,delim,qnum,time_st
amp);
            break;
        default:
            /* if (qnum < 0) - replaced by berni 96/03/26
*/
            if (g_struct->c_l_opt->update == 2 ||
                g_struct->c_l_opt->update == 5)

```

```

        sprintf(file_name,
"%s%smts%02d%f%d.%s",run_dir,delim, \
        currentUpdatePair - updatePairStart +
1,abs(qnum), currentUpdatePair,time_stamp);
        else
            sprintf(file_name,
"%s%smts%dqry%02d.%s",run_dir,delim, \
            g_struct->c_l_opt-
>intStreamNum,qnum,time_stamp);
            break;
    }

    if (g_struct->c_flags->eo_infile)
        if (g_struct->c_l_opt->update == 2 ||
            g_struct->c_l_opt->update == 5)
            sprintf(file_name,
"%s%smtufinter.%s",run_dir,delim,time_stamp);
            else
                switch (g_struct->c_l_opt->intStreamNum) {
                    case -1:
                        sprintf(file_name,
"%s%sqryqualinter.%s",run_dir,delim,time_stamp);
                        break;
                    case 0:
                        /*sprintf(file_name,
"%s%smpinter.%s",run_dir,delim,time_stamp);*/
                        if (g_struct->c_l_opt->update == 1)
                            sprintf(file_name,
"%s%smpqinter.%s",run_dir,delim,time_stamp);
                        else
                            sprintf(file_name,
"%s%smpufinter.%s",run_dir,delim,time_stamp);
                        break;
                    default:
                        if (g_struct->c_l_opt->intStreamNum > 0)
                            sprintf(file_name,
                                "%s%smts%dinter.%s",
                                run_dir,delim,g_struct->c_l_opt-
>intStreamNum,time_stamp);
                            else
                                fprintf(stderr,"Invalid stream number
specified\n");
                                break;
                }

            strcpy(outstreamfilename, file_name); /* wlc
081397 */

            if (!feof(instream) || g_struct->c_flags->eo_infile)
                /* Only create an output file if there are input
statements left to process, or if we're all done
and want to print out the summary table file */
                if( (outstream = fopen(file_name,
WRITEMODE)) == NULL ) {

```

```

        fprintf(stderr,"\nThe output file could not be
opened. ");
        fprintf(stderr,"Make sure that the filename is
correct.\n");
        fprintf(stderr,"filename = %s\n",file_name);
        exit(-1);
    }

    return;
}

/*****
*****/
/* Determine whether or not we should break out of
the block loop
because of an end of file, end of block, or update
function.
Also handle some semaphore stuff for update
functions */
/*****
*****/
int PreSQLprocess(struct global_struct *g_struct,
Timer_struct *start_time)
{
    int rc = 1;
    FILE *updateFP;
#ifdef SQLWINT
    int semid; /* semaphore for
controlling UFs*/
    key_t semkey; /* key to generate
semid */
#else
    int SemTimeout = 60000; /* Des
time out period of 1 minute */
#endif

    switch (g_struct->c_flags->select_status)
    {
        case TPCDBATCH_NONSQL:
            g_struct->s_info_stop_ptr = g_struct-
>s_info_ptr;
            /* if we're at the end of the input file, set the stop
pointer to this structure */
            rc = FALSE;
            break;
        case TPCDBATCH_EOBLOCK:
            rc = FALSE;
            break;
        case TPCDBATCH_INSERT:
            /* we have to check whether or not this is a
throughput */
            /* test, and if it is, we have to set up a semaphore
to */
            /* control when the update functions are run.
We want */

```

```

    /* them to be run after all the query streams have
    finished. */
    /* What we do is set up the semaphore here,
    decrement it */
    /* in the query streams, and wait for it to get
    cleared */
    /* before we allow the UFs to run.
    */
    /* Note: we only set up the semaphore if:
    */
    /* 1. we are running the throughput test
    (num of */
    /* streams > 0) */
    /* 2. we are at the first UF1 (i.e. this is the
    */
    /* case where currentUpdatePair =
    updatePairStart */
    /* we also want to check the sem_on element in
    the global */
    /* structure to see if we want to use semaphores
    or let */
    /* the calling script do the synchronization of the
    update */
    /* stream */
    if ( semcontrol == 1 )
    {
        /* yes we are to be using semaphores */
        /* is this the 1st time into update function 1
        (uf1)? */
        if (currentUpdatePair == updatePairStart )
        {
            /* create the semaphores */
            create_semaphores(g_struct);
            if (g_struct->c_l_opt->intStreamNum !=
            0)
                /* wait period for runthroughput updates
                */
                throughput_wait(g_struct);
        }
        /* otherwise continue to run*/
    }
    if ((g_struct->c_l_opt->update == 3) || (g_struct-
    >c_l_opt->update == 4))
    {
        get_start_time(start_time);
        strcpy(g_struct->s_info_ptr->start_stamp,
        get_time_stamp(T_STAMP_FORM_3,start_time ));
        /* TIME_ACC jen*/
        /* write the start timestamp to the file...if this is
        not a qualification */
        /* run, then write the seed used as well */
        fprintf( outstream,"Start timestamp %*.*s \n",
        T_STAMP_3LEN,T_STAMP_3LEN,
        /* TIME_ACC jen*/
        g_struct->s_info_ptr->start_stamp);
    }

```

```

    if (g_struct->c_l_opt->intStreamNum >= 0)
    {
        if (g_struct->lSeed == -1)
        {
            fprintf( outstream,"Using default qgen seed
            file");
        }
        else
            fprintf( outstream,"Seed used =
            %ld",g_struct->lSeed);
        fprintf( outstream,"\n");
    }
    if (g_struct->c_l_opt->update < 4){
        /* run only if updates are enabled */
        runUF1(g_struct, currentUpdatePair);
    }

    rc = FALSE;
    if ((g_struct->c_l_opt->intStreamNum == 0) &&
    (semcontrol == 1))
        /* RUNPOWER: release first semaphore so the
        queries can run */
        release_semaphore(g_struct,
        INSERT_POWER_SEM);
        break;
    case TPCDBATCH_DELETE:
        if ((g_struct->c_l_opt->intStreamNum == 0) &&
        (semcontrol == 1))
        {
            /* RUNPOWER: wait for queries to finish */
            /* waiting on QUERY_POWER_SEM
            semaphore */
            runpower_wait(g_struct,
            QUERY_POWER_SEM);
        }
        if ((g_struct->c_l_opt->update == 3) || (g_struct-
        >c_l_opt->update == 4))
        {
            get_start_time(start_time);
            strcpy(g_struct->s_info_ptr->start_stamp,
            get_time_stamp(T_STAMP_FORM_3,start_time ));
            /* TIME_ACC jen*/
            /* write the start timestamp to the file...if this is
            not a qualification */
            /* run, then write the seed used as well */
            fprintf( outstream,"Start timestamp %*.*s \n",
            T_STAMP_3LEN,T_STAMP_3LEN,
            /* TIME_ACC jen*/
            g_struct->s_info_ptr->start_stamp);
            if (g_struct->c_l_opt->intStreamNum >= 0)
            {
                if (g_struct->lSeed == -1)
                {

```

```

        fprintf( outstream,"Using default qgen seed
file");
    }
    else
        fprintf( outstream,"Seed used =
%ld",g_struct->lSeed);
        fprintf( outstream,"\n");
    }
}
if (g_struct->c_l_opt->update < 4){
/* run only if updates are enabled */
runUF2(g_struct, currentUpdatePair);
if (g_struct->c_l_opt->intStreamNum == 0)
{ /* RUNPOWER */
    fprintf(stderr, "UF2 completed\n");
}
}
currentUpdatePair += 1;
/* update the update.pair.num file to reflect the
successfully completed */
/* update pair */
if (g_struct->c_l_opt->update < 4)
{ /*jen*/
#endif NO_INCREMENT
/* don't update the pair, only for my testing -
Haider */
    updateFP = fopen(g_struct-
>update_num_file,"w");
    fprintf(updateFP,"%d\n",currentUpdatePair);
    fclose(updateFP);
#endif
} /*jen*/
rc = FALSE;
break;

}
return(rc);
}

```

```

/*****
*****
/* Handles actual processing of SQL statement.
Initializes the SQLDA
for returned rows, does PREPARE, DECLARE,
and OPEN statements and
executed multiple FETCHes as needed. If not a
SELECT statement,
goes into EXECUTE IMMEDIATE section
*/
/*****
*****
void SQLprocess(struct global_struct *g_struct)
{
    int rc = 0; /* 912RETRY */
    int rows_fetch = 0;

```

```

    long sqlcode = SQL_RC_E911; /*
Temporary sqlcode to test
for deadlocks */
    int max_wait = 1; /* Maximum
number of retries
for deadlock scenario
*/
    int col_lengths[TPCDBATCH_MAX_COLS];
/* array containing widths of
columns in returned
set */
    struct stmt_info *s_info_ptr;

    s_info_ptr = g_struct->s_info_ptr;
/*****
*****
/* grab storage for the SQLDA
*/
/*****
*****
    if ((sqlda=(struct sqlda
*)malloc(SQLDASIZE(100))) == NULL)
        mem_error("allocating sqlda");

    sqlda->sqln = TPCDBATCH_MAX_COLS;
/* @d30369 tjpg */

/* Error-recovery code for errors resulting from
multi-stream errors */

    while (((sqlcode == SQL_RC_E911) ||
(sqlcode == SQL_RC_E912) ||
(sqlcode == SQL_RC_E901)) &&
(max_wait < MAXWAIT) &&
(rc==0) )
    {

        sqlcode = 0; /* Re-initialize sqlcode to
avoid infinite-loop */
        if (g_struct->c_flags->select_status ==
TPCDBATCH_SELECT)
        {
            /* Enter this loop if SQL stmt is a SELECT */
            EXEC SQL PREPARE STMT1 INTO :*sqlda
FROM :stmt_str;

            sqlcode = error_check();
            if (sqlcode < 0)
            {
                fprintf (stderr,"\nPrepare failed. Stopping this
query.\n");
                rc = -1;
            }

```

```

        else /* print out the column headings for the
answer set */
        {
            print_headings(sqllda,col_lengths);
/* @d22817 tjpg */

            allocate_sqllda(sqllda); /* This is where we
set storage for the */
                                /* SQLDA based on the
column types in */
                                /* the answer set table.
*/

            EXEC SQL DECLARE DYNCUR
CURSOR FOR STMT1;

            EXEC SQL OPEN DYNCUR;
            sqlcode = error_check();

            if (sqlcode < 0) /* we ran into an error of
some kind KBS 98/09/28 */
            {
                max_wait ++;
                fprintf (stderr, "\nAn error has been
detected on open...Retrying...\n");
                SleepSome(10);
            }
            else
            {

/******
*****
                /* Fetch appropriate number of rows and
determine whether or not to */
                /* send them to file.
*/

/******
*****

                rows_fetch = 0;

                do
                {
                    /* Keep fetching as long as we haven't
finished reading
                    all the rows and we haven't gone past the
limits set
                    in the control string */

                    EXEC SQL FETCH DYNCUR USING
DESCRIPTOR :*sqllda;
                    if (sqlca.sqlcode == 100)
                    {
                        sqlcode = sqlca.sqlcode;
                    }

```

```

        else
        {
            sqlcode = error_check();
        }
        if (sqlcode == 0)
        {
            rows_fetch++;
            if ( (rows_fetch <= s_info_ptr-
>max_rows_out) ||
                (s_info_ptr->max_rows_out == -1) )
                echo_sqllda(sqllda,col_lengths);
        }
        else if (sqlcode < 0)
        {
            max_wait++;
            fprintf (stderr, "\nAn error has been
detected on fetch...Retrying...\n");
            SleepSome(10);
        }
        } while ( (sqlcode == 0) && \
                ( (s_info_ptr->max_rows_fetch == -
1) || \
                (rows_fetch < s_info_ptr-
>max_rows_fetch) ) );
        } /* end of successful open */
        } /* end of successful prepare */
    } /** End of block for handling SELECT
statements **/

    else
    {
        /* SQL statement is not a SELECT */
        EXEC SQL EXECUTE IMMEDIATE
:stmt_str;
        sqlcode = error_check();

        if (sqlcode < 0 )
        {
            max_wait ++;
            fprintf (stderr, "\nAn error has been detected
on execute immediate...Retrying...\n");
            SleepSome(10);
        }
        } /* end of block for handling NON-select
statements */

        if ( (sqlcode >= 0 ) &&
            (g_struct->c_flags->select_status ==
TPCDBATCH_SELECT))
        {
            /* we opened a cursor before */
            EXEC SQL CLOSE DYNCUR;
            sqlcode = error_check();

            if ((s_info_ptr->max_rows_fetch == -1) ||
                (rows_fetch < s_info_ptr-
>max_rows_fetch))

```



```

#ifdef SQLPTX
    fprintf (outstream, "\n\nNumber of rows
retrieved is: %6d",
            rows_fetch);
    else
        fprintf (outstream, "\n\nNumber of rows
retrieved is: %6d",
                s_info_ptr->max_rows_fetch);
#else
    fprintf (outstream, "\n\nNumber of rows
retrieved is: %6d",
            rows_fetch);
    else
        fprintf (outstream, "\n\nNumber of rows
retrieved is: %6d",
                s_info_ptr->max_rows_fetch);
#endif
}
/* @d28763
tjg */

if (s_info_ptr->query_block == FALSE) /* if
block is off don't loop */
    g_struct->c_flags->eo_block = TRUE;

} /* end of while loop to retry if needed */

} /* end of SQLprocess */

/*****
*****
*/
/* performs some operations after a statement has
been processed,
including doing a COMMIT if necessary, and
calculating the
elapsed time. Also initializes a new stmt_info
structure
for the next block of statements
*/
/*****
*****
*/
int PostSQLprocess(struct global_struct *g_struct,
Timer_struct *start_time)
{
    struct stmt_info *s_info_ptr;
    Timer_struct    end_t;    /* end point for
elapsed time */

#ifdef DEBUG
    fprintf (outstream, "In PostSQLprocess\n");
#endif

    s_info_ptr = g_struct->s_info_ptr;

    if (g_struct->c_flags->select_status ==
TPCDBATCH_NONSQL)

```

```

return FALSE; /* get out if we've reached the
end of input file */

if (g_struct->c_l_opt->update > 1)
{
    /* This is an update function stream. There is no
need to COMMIT. */
    /* Each UF child will COMMIT its own
transactions. */
    ;
}
else
{ /* For non-UF cases, COMMIT now. */
    if (g_struct->c_l_opt->a_commit) {
        EXEC SQL COMMIT WORK;
        error_check(); /*
@d22275 tjg */
    }
}

fflush(outstream);

s_info_ptr->elapse_time =
get_elapsed_time(start_time);

if (g_struct->c_flags->time_stamp == TRUE)
/* @d25594 tjg */
    get_start_time(&end_t); /* Get the end time */
    strcpy(s_info_ptr->end_stamp,
get_time_stamp(T_STAMP_FORM_3,&end_t)
);

/*get_time_stamp(T_STAMP_FORM_3,(time_t)NU
LL) */;

/* BBE: Pass on time stamp values for the next
query */
temp_time_struct = end_t;
strcpy(temp_time_stamp, s_info_ptr->end_stamp);

/* write the start timestamp to the file */
fprintf( outstream, "\n\nStop timestamp %*. *s \n",
        T_STAMP_3LEN, T_STAMP_3LEN, /*
TIME_ACC jen*/
        s_info_ptr->end_stamp);

/* DJD print elapsed time in seconds */
fprintf( outstream, "Query Time = %15.1f secs\n",
s_info_ptr->elapse_time);

/** Allocate space for a new stmt_info structure
**/ /* @d24993 tjg */
s_info_ptr->next =
(struct stmt_info *) malloc(sizeof(struct
stmt_info));

```

```

    if (s_info_ptr->next != NULL) {
        memset(s_info_ptr->next, '\0', sizeof(struct
stmt_info));
        /** Transfer details from one structure to another
for
        to apply for the next statement **/
        s_info_ptr->next->stmt_num = s_info_ptr-
>stmt_num + 1;
        s_info_ptr->next->max_rows_fetch =
s_info_ptr->max_rows_fetch;
        s_info_ptr->next->max_rows_out = s_info_ptr-
>max_rows_out;

        s_info_ptr->next->query_block = s_info_ptr-
>query_block;
        s_info_ptr->next->elapsed_time = -1;

        s_info_ptr = s_info_ptr->next;
    }
    else {
        mem_error("allocating next stmt structure.
Exiting\n");
        exit(-1);
    }

    /** Set the stop and travelling pointer to the
current info structure **/
    g_struct->s_info_stop_ptr = g_struct->s_info_ptr
= s_info_ptr;

    if (sqlda_allocated)
        free_sqlda(sqlda,g_struct->c_flags-
>select_status);
        /** fix free() problem on NT
wlc 090597 */

    if (g_struct->c_l_opt->outfile != 0)
        fclose(outstream);

    return (TRUE);
}

/*****
*****/
/** Does some cleaning up once all the statements are
processed. Disconnects
from the database, cleans up some semaphore stuff
from the update functions,
prints out the summary table, and closes all file
handles. */
/*****
*****/
int cleanup(struct global_struct *g_struct)
{
#ifdef SQLWINT

```

```

    int        semid;        /* semaphore for
controlling UFs*/
    key_t      semkey;      /* key to generate
semid */
#endif
    char file_name[256] = "\0";

    /** End timestamp for stream **/
    /**g_struct->stream_end_time = time(NULL);*/
    get_start_time(&(g_struct->stream_end_time)); /*
TIME_ACC jen */

    switch (g_struct->c_l_opt->update)
    {
        case (2):
        case (5):
            /* update throughput function stream */

        sprintf(file_name,"%s%sstcrntuf.%s",g_struct-
>run_dir,
                env_tpcd_path_delim, g_struct-
>file_time_stamp);
            break;
        case (3):
        case (4):
            /* update power function stream */

        sprintf(file_name,"%s%spstrcntuf.%s",g_struct-
>run_dir,
                env_tpcd_path_delim, g_struct-
>file_time_stamp);
            break;
        case (1):
            /* power query stream */
            sprintf(file_name,
"%s%spstrcnt%d.%s",g_struct->run_dir,
env_tpcd_path_delim,
                g_struct->c_l_opt-
>intStreamNum,g_struct->file_time_stamp);
            break;
        case (0):
            /* throughput query stream */
            sprintf(file_name,
"%s%sstcrnt%d.%s",g_struct->run_dir,
env_tpcd_path_delim,
                g_struct->c_l_opt-
>intStreamNum,g_struct->file_time_stamp);
            break;
    }

#ifdef LINUX

    if( (g_struct->stream_report_file =
fopen(file_name, APPENDMODE)) == NULL )
    {

```

```

    fprintf(stderr, "\nThe output file for the stream
count information\n");
    fprintf(stderr, "could not be opened, make sure the
filename is correct\n");
    fprintf(stderr, "filename = %s\n", file_name);
    exit(-1);
}
#endif

/* print out the stream stop time in the stream
count information file*/
if (g_struct->c_l_opt->update > 1)
{
    /* update function stream */
    fprintf(g_struct->stream_report_file,
        "Update function stream stopping at
%*.s\n",
        T_STAMP_3LEN, T_STAMP_3LEN, /*
TIME_ACC jen*/

get_time_stamp(T_STAMP_FORM_3, &(g_struct-
>stream_end_time)); /* TIME_ACC jen*/
}
else
{
    /* query stream(s) */
    fprintf(g_struct->stream_report_file,
        "Stream number %d stopping at %*.s\n",
        g_struct->c_l_opt->intStreamNum,
        T_STAMP_3LEN, T_STAMP_3LEN, /*
TIME_ACC jen*/

get_time_stamp(T_STAMP_FORM_3, &(g_struct-
>stream_end_time)); /* TIME_ACC jen*/
}
fclose(g_struct->stream_report_file);

/* No need to check for errors here.
Also, the UF stream in a Throughput run
has no connection in tpcdbatch.sqc.      aph
98/12/26
error_check();
*/

/* if we are in a query stream AND this is a
throughput test, then need */
/* do to some semaphore stuff (0 implies update
functions are off) */
/* AND we are supposed to be using semaphores
*/

if ( ( semcontrol == 1 ) &&
    ( g_struct->c_l_opt->update < 2))

    /* only queries need to release the semaphore at
this point */
    {
        if (g_struct->c_l_opt->intStreamNum == 0)
            release_semaphore(g_struct,
QUERY_POWER_SEM); /* power stream */
        else
            release_semaphore(g_struct,
THROUGHPUT_SEM); /* throughput stream */

        EXEC SQL CONNECT RESET;
#ifdef SQLWINT
        if (verbose)
        {
            fprintf(stderr,
                "cleanup: semkey = %ld, semid = %d, file
= %s, stream = %d\n",
                semkey, semid, g_struct->update_num_file,
                g_struct->c_l_opt->intStreamNum);
        }
    }
#endif
}

/** Summary table processing **/
/* @d24993 tjpg */
summary_table(g_struct);

fprintf (outstream, "\n\n");

fclose(outstream); /* Close the output data
stream. */
fclose(instream); /* Close the SQL input
stream. */

return (TRUE);
}

void create_semaphores(struct global_struct
*g_struct)
{
#ifdef SQLWINT
    int semid; /* semaphore for
controlling UFs*/
    key_t semkey; /* key to generate
semid */
#else
    HANDLE hSem;
    HANDLE hSem2;
    int SemTimeout = 60000; /* Des
time out period of 1 minute */
#endif
    fprintf(stderr, "numstreams = %d\n", g_struct-
>c_l_opt->intStreamNum);

```

```

    fprintf(stderr,"Update stream creating
semaphore(s) for update and query sequencing\n");
#ifdef SQLWINT

    fprintf(stderr,"semfile = %s\n",g_struct-
>sem_file);
    if (g_struct->c_l_opt->intStreamNum == 0)
        /*RUNPOWER*/
    {
        fprintf(stderr,"semfile2 = %s\n",g_struct-
>sem_file2);
        hSem = CreateSemaphore(NULL,
0,1,(LPCTSTR)(g_struct->sem_file));
        hSem2 = CreateSemaphore(NULL,
0,1,(LPCTSTR)(g_struct->sem_file2));
        if ((hSem == NULL) || (hSem2 ==
NULL))
        {
            fprintf(stderr,
                "CreateSemaphores (ready
semaphore) failed, GetLastError: %d, quitting\n",
                GetLastError());
            exit(-1);
        }
        fprintf(stderr,"Semaphores created
successfully!\n");
    }
    else
    {
        /* RUNTHROUGHPUT creates semaphores
based on the number of query streams while the
number of streams for runpower is constant */
        hSem = CreateSemaphore(NULL, 0,
g_struct->c_l_opt-
>intStreamNum,
(LPCTSTR)(g_struct-
>sem_file));

        if (hSem == NULL)
        {
            fprintf(stderr,
                "CreateSemaphore (ready
semaphore) failed, GetLastError: %d, quitting\n",
                GetLastError());
            exit(-1);
        }
        fprintf(stderr,"Semaphore created
successfully!\n");
    }
#else
    /* AIX, SUN, etc. */
    /* create a semaphore key...use the name of a
file that */
    /* you know exists */
    fprintf(stderr,"semfile = %s\n", g_struct-
>update_num_file);

```

```

semkey = ftok(g_struct->update_num_file,'J');
if (g_struct->c_l_opt->intStreamNum == 0)
    /* RUNPOWER */
    {
        if ( (semid =
semget(semkey,2,IPC_CREAT|S_IRUSR|S_IWUSR
)) < 0)
        {
            fprintf(stderr,
                "Throughput can't get initial
semaphore! semget failed errno = %d\n",
                errno);
            exit(1);
        }
    }
    else
        /* THROUGHPUT */
        {
            if ( (semid =
semget(semkey,1,IPC_CREAT|S_IRUSR|S_IWUSR
)) < 0)
            {
                fprintf(stderr,
                    "Throughput can't get initial
semaphore! semget failed errno = %d\n",
                    errno);
                exit(1);
            }
            if (verbose)
            {
                fprintf(stderr,
                    "insert: semkey = %ld, semid =
%d, file = %s, value = %d\n",
                    semkey,semid,g_struct-
>update_num_file,
                    (g_struct->c_l_opt-
>intStreamNum * -1));
            }
        }
    }
#endif
}

/*throughput update */
void throughput_wait(struct global_struct *g_struct)
{
#ifdef SQLWINT
    int          semid;          /* semaphore for
controlling UFs*/
    key_t        semkey;        /* key to generate
semid */
#else
    HANDLE        hSem;

```

```

    int          j;
    int          SemTimeout = 60000; /* Des
time out period of 1 minute */
#endif

#ifdef SQLWINT
    hSem = open_semaphore(g_struct,
THROUGHPUT_SEM);
    for (j = 0; j < g_struct->c_l_opt-
>intStreamNum; j++)
    {
        if (verbose)
            fprintf(stderr,"About to wait again
...\n");
        if (WaitForSingleObject(hSem,
INFINITE) == WAIT_FAILED)
        {
            fprintf(stderr,
                "WaitForSingleObject (hSem)
failed on stream %d, error: %d, quitting\n",
                j, GetLastError());
            exit(-1);
        }
        if (verbose)
            fprintf(stderr,"Streams to wait for
%d\n", j);
    }
    fprintf(stderr,"finished waiting on stream
semaphore! Ready to run updates!\n");
    /* close the semaphore handle */
    if (! CloseHandle(hSem)) {
        fprintf(stderr, "Close Sem failed - Last Error:
%d\n", GetLastError());
        /* no exit here */
    }
#else
    semid = open_semaphore(g_struct);
    /* call the sem_op routine to decrement the
semaphore by */
    /* however many streams .... by calling this
function with*/
    /* a negative number, this stream is forced to
wait until */
    /* the semaphore gets back to 0 */
    if (sem_op(semid, 0, (g_struct->c_l_opt-
>intStreamNum * -1)) != 0)
    {
        /*jenSEM*/
        fprintf(stderr,
            "Failure to wait on throughput
semaphone for %d streams\n",
            g_struct->c_l_opt->intStreamNum);
        exit(1);
    }
    /*jenSEM*/

```

```

        fprintf(stderr,"finished waiting on stream
semaphore! Ready to run updates!\n");
        semctl(semid,0,IPC_RMID,0); /* we've
finished waiting, now */
        /* remove the semaphore */
    }
#endif
}

void runpower_wait(struct global_struct *g_struct,
int sem_num)
{
    char semfile[150];
#ifdef SQLWINT
    HANDLE hSem;

    if (sem_num == 1)
        strcpy (semfile, g_struct->sem_file);
    else
        strcpy (semfile, g_struct->sem_file2);

#else /* AIX */
    int          semid;          /* semaphore for
controlling UFs*/
    key_t        semkey;        /* key to generate
semid */

    strcpy (semfile, g_struct->update_num_file);
#endif

    if (g_struct->c_l_opt->update == 1)
        fprintf(stderr,"querystream waiting for update
stream (UF1) to signal semaphore based on %s\n",
semfile);
    else
        fprintf(stderr,"updatestream (UF2) waiting on
querystream semaphore to signal semaphore based
on %s\n", semfile);

#ifdef SQLWINT
    hSem = open_semaphore(g_struct, sem_num);
    if (verbose)
        fprintf(stderr,"Runpower queries about to wait
...\n");
    if (WaitForSingleObject(hSem, INFINITE) ==
WAIT_FAILED)
    {
        fprintf(stderr,
            "WaitForSingleObject (hSem) failed on
stream 0, error: %d, quitting\n",
            GetLastError());
        exit(-1);
    }
}

```

```

    if (! CloseHandle(hSem))
    {
        fprintf(stderr, "Close Sem failed - Last
Error: %d\n", GetLastError());
        /* no exit here */
    }
#else

    semid = open_semaphore(g_struct);

    /* call the sem_op routine to decrement the
semaphore by */
    /* however many streams .... by calling this
function with*/
    /* a negative number, this stream is forced to wait
until */
    /* the semaphore gets back to 0 */
    /* aix semaphores start at 0, not 1, so sem_num -1
is used */
    if (sem_op(semid, sem_num - 1, -1) != 0)
    {
        /*jenSEM*/
        fprintf(stderr,
            "Failure to wait on runpower semaphore
for %d streams\n",
            g_struct->c_l_opt->intStreamNum);
        exit(1);
    }
    /*jenSEM*/
#endif
    if (g_struct->c_l_opt->update == 1)
        fprintf(stderr, "querystream finished waiting on
updatestream semaphore\n");
    else
        fprintf(stderr, "updatestream finished waiting on
querystream semaphore\n");
}

void release_semaphore(struct global_struct
*g_struct, int sem_num)
{
#ifdef SQLWINT
    int semid; /* semaphore for
controlling UFs*/
    key_t semkey; /* key to generate
semid */
#else
    HANDLE hSem;
    int SemTimeout = 600000; /* Des
time out period of 1 minute */
#endif

#ifdef SQLWINT
    hSem = open_semaphore(g_struct, sem_num);
/* query */
    if (! ReleaseSemaphore(hSem,
1,

```

```

(LPLONG)(NULL)))
    {
        fprintf(stderr, "ReleaseSemaphore failed,
Sem#: %d LastError: %d, quit\n",
            sem_num, GetLastError());
        exit(-1);
    }
#else
    semid = open_semaphore(g_struct); /* query */
    /* aix semaphores start at 0, not 1, so sem_num
-1 is used */
    if (sem_op(semid, sem_num - 1, 1) != 0)
    /*jenSEM*/
    {
        /*jenSEM*/
        fprintf(stderr,
            "Failed to increment semaphore %d
for throughput stream %d\n",
            sem_num, g_struct->c_l_opt-
>intStreamNum);
        fprintf(stderr,
            "file for generation of semaphore is:
%s\n",
            g_struct->update_num_file);
        exit(1);
    }
#endif
    if (g_struct->c_l_opt->intStreamNum == 0)
    { /* RUNPOWER */
        if (sem_num == 1)
        {
            fprintf(stderr, "UF1 completed.\n");
        }
        else
        {
            fprintf(stderr, "query stream completed.\n");
        }
    }
}

#ifdef SQLWINT /* Compile only in NT */
HANDLE open_semaphore(struct global_struct
*g_struct, int num)
{
    HANDLE hSem;
    LPCTSTR semfile;

    if (num == 1)
        semfile = (LPCTSTR)g_struct->sem_file;
    else
        semfile = (LPCTSTR)g_struct-
>sem_file2;

    while ((hSem =
OpenSemaphore(SEMAPHORE_ALL_ACCESS |

```

```

SEMAPHORE_MODIFY_STATE |
        SYNCHRONIZE,
        TRUE,
        semfile))
    == (HANDLE)(NULL))
{
    /*
    ** if cannot open the semaphore, wait for 0.1
second
    */
    fprintf(stderr,"Retry Open semaphore
%s\n",semfile);

    Sleep(1000);
}
return hSem;
}

#else /* Compile only in non-NT (i.e. AIX) */
int open_semaphore(struct global_struct *g_struct)
{
    int      semid;          /* semaphore for
controlling UFs*/
    key_t    semkey;        /* key to
generate semid */
    int num;

    if (g_struct->c_l_opt->intStreamNum == 0)
        num = 2;
    else
        num = 1;

    semkey = ftok(g_struct->update_num_file,'J');
    while ((semid = semget(semkey,num,0) < 0)
    {
        if (errno == ENOENT)
        {
            sleep(2);
            fprintf(stderr,"cleanUp: looping for
access to semaphore stream %d ",
                g_struct->c_l_opt-
>intStreamNum);
            fprintf(stderr,"semkey=%ld semid =
%d file=%s\n",semkey,semid,
                g_struct->update_num_file);
        }
        else
        {
            fprintf(stderr,"query stream %d
semget failed errno = %d\n",
                g_struct->c_l_opt-
>intStreamNum,errno);
            exit(1);
        }
    }
}

```

```

return semid;
}
#endif
-

tpcdUF.sqc
/*****
*****
*
* TPCDUF.SQC
*
* Revision History:
*
* 05 dec 98 aph Created tpcdUF.sqc containing
runUF1_fn() and runUF2_fn()
* so that it can be bound separately with a
different isolation level.
* 15 may 99 bbe Added cast (short) for type
conversion between a long and a short.
* 16 jun 99 jen Added in proper connect reset code
for UF functions (mistakenly
* removed
* 17 jun 99 jen SEMA Changes semaphore file for
update functions to look for tpcd.setup
* not for the orders.*** update data file
(AIX only )
* 21 jul 99 bbe Commented out conditions in SQL
statments that searched on fields
* other than app_id.
*
*****
*****/

#define UF1DEBUG
#define UF2DEBUG

#if (defined(SQLPTX) && defined(SQLSUN))
#define exit(rc) _exit(rc)
#else
#define exit(rc) exit(rc)
#endif /* SQLPTX & SQLSUN*/

#include "tpcdbatch.h"
/** EXEC SQL INCLUDE SQLCA; **/

#include "sqlca.h"
extern struct sqlca sqlca;

/*****
*****/
/* Function Prototypes
*/

```

```

/*****
*****
extern int SleepSome( int amount );
extern long error_check(void);
/* @d28763 tjg */
extern void dumpCa(struct sqlca*); /*kmw*/
extern int sem_op (int semid, int semnum, int value);
extern char *get_time_stamp(int form, Timer_struct
*timer_pointer); /* TIME_ACC jen */

/*****
*****
/* Declare the SQL host variables.
*/
/*****
*****
EXEC SQL BEGIN DECLARE SECTION;
char UF_dbname[9] = "\0";
char UF_userid[9] = "\0";
char UF_passwd[9] = "\0";
sqlint32 UF_chunk = 0;
short month = 0;
EXEC SQL END DECLARE SECTION;

/*****
*****
/* Declare the global variables.
*/
/*****
*****
extern char env_tpcd_tmp_dir[150];
extern FILE *instream, *outstream; /* File pointers
*/
extern char sourcefile[256]; /* Used for
semaphores and table functions?*/
extern struct { /* jen LONG */
short len;
char data[32700];
} stmt_str; /* jen LONG */

/*****
*****
/* UF1 child */
/* (i is the application number.)
*/
/*****
*****
void runUF1_fn ( int updatePair, int i, char
*dbname, char *userid, char *passwd )
{
int rc = 0;
int split_updates = 2; /* no. of ways update
records are split */
int concurrent_inserts = 2; /* jenCI no of
concurrent updates to be */
/* jenCI run at once*/
int loop_updates = 1; /* jenCI no of updates to
be run in one */
/* jenCI "concurrent"
invocation. should*/
/* jenCI be split_updates /
concurrent_inserts*/
int startChunk = 0; /* jenCI number of first
chunk to insert for */
/* jenCI this child */
int stopChunk = 0; /* jenCI number of last
chunk to insert for */
/* jenCI this child */
long insertedLineitem = 0; /*kmw*/
long insertedOrders = 0; /*kmw*/
long saveInsertedOrders = 0; /*kbs*/

long sqlcode;
int maxwait;

#ifndef SQLWINT
int su_sem;
key_t su_semkey;
#else
HANDLE su_hSem;
char UF1_semfile[256];
#endif

char myoutstreamfile[256];
FILE *myoutstream;

strcpy(UF_dbname, dbname);
strcpy(UF_userid, userid);
strcpy(UF_passwd, passwd);

/* Get ready to start logging diagnostic output */
sprintf (myoutstreamfile,
UF1OUTSTREAMPATTERN, env_tpcd_tmp_dir,
PATH_DELIM,
updatePair, i);
if ( (myoutstream = fopen (myoutstreamfile,
WRITEMODE)) == NULL)
{
fprintf (stderr, "\nThe output file '%s' for update
pair %d set %d could not be opened. runUF1_fn\n",
myoutstreamfile,updatePair,i);
rc=-1;
goto UF1_exit;
}
outstream=myoutstream; /* initialize outstream
for error_check dxxxxhar*/

fprintf( myoutstream, "\nUF1 for update pair %d
set %d starting at %*.s\n",
updatePair, i,

```



```

        T_STAMP_1LEN,T_STAMP_1LEN, /*
TIME_ACC jen*/

get_time_stamp(T_STAMP_FORM_1,(Timer_struct *)NULL)); /* TIME_ACC jen*/

    if (getenv ("TPCD_SPLIT_UPDATES") !=
NULL)
        split_updates = atoi (getenv
("TPCD_SPLIT_UPDATES"));
    if (getenv ("TPCD_CONCURRENT_INSERTS")
!= NULL) /*jenCI*/
        concurrent_inserts = atoi (getenv
("TPCD_CONCURRENT_INSERTS")); /*jenCI*/
    loop_updates = split_updates / concurrent_inserts;
/*jenCI*/

    /* determine the starting and stopping point of the
chunks that this jenCI*/
    /* invocation will apply. i is starting chunk number
with range 0 jenCI*/
    /* through (concurrent_inserts -1)
jenCI*/
    startChunk = i * loop_updates;
/*jenCI*/
    stopChunk = startChunk + (loop_updates - 1);
/*jenCI*/

    /* Establish a connection to the database */
    if (!strcmp(userid, "\0")) /** No authentication
provided **/
        EXEC SQL CONNECT TO :UF_dbname;
    else
        EXEC SQL CONNECT TO :UF_dbname USER
:UF_userid USING :UF_passwd;
    error_check();
    if (sqlca.sqlcode < 0)
    {
        rc=-1;
        goto UF1_exit;
    }

    /* Start processing each chunk in my range */
#ifdef UF1DEBUG
    fprintf (myostream, "Before loop_a startChunk =
%d, stopChunk = %d\n", startChunk, stopChunk);
    fflush(myostream);
#endif
    for ( UF_chunk = startChunk; UF_chunk <=
stopChunk; UF_chunk++ ) /*jenCI*/
    {
/*jenCI*/
        /* wlc 062797 */
        sqlcode = SQL_RC_E911;

```

```

        month = (short)UF_chunk; /* Cast 'short' added
bbe */
        maxwait = 1;
        rc = 0;

#ifdef UF1DEBUG
        fprintf (myostream, "Before While_a Chunk=
%d\n", UF_chunk);
        fflush(myostream);
#endif
        /* Loop to handle any deadlocks */
        while (sqlcode == SQL_RC_E911 && maxwait
<= MAXWAIT && rc==0)
        {
            sqlcode = 0;
#ifdef UF1DEBUG
            fprintf (myostream, "in loop before orders exec
sql\n");
            fflush(myostream);
#endif
            EXEC SQL INSERT INTO TPCD.ORDERS
                SELECT
O_ORDERKEY, O_CUSTKEY, O_ORDERSTATU
S, O_TOTALPRICE,
O_ORDERDATE, O_ORDERPRIORITY, O_CLER
K, O_SHIPPRIORITY, O_COMMENT
                FROM TPCDTEMP.ORDERS_NEW
                WHERE APP_ID = :UF_chunk;
                /*AND 12*(YEAR(O_ORDERDATE)-
1992)+MONTH(O_ORDERDATE)-01 = :month;*/

            if (sqlca.sqlcode < 0)
                sqlcode = error_check();

            if (sqlcode == SQL_RC_E911)
            {
                /* we've hit a deadlock */
                fprintf (myostream,
                    "\nDeadlock detected inserting from
tpcdtemp.orders_new for chunk %d for pair
%d..Retrying...\n", UF_chunk, updatePair);
                SleepSome(UF_DEADLOCK_SLEEP);
                maxwait++; /* jen
DEADLOCK */
            }
            else if (sqlcode < 0)
            {
                fprintf(myostream,
                    "Insert into orders pair %d chunk %d
failed sqlcode=%d\n",
                    updatePair, UF_chunk, sqlcode);
                dumpCa(&sqlca);
                rc = -1;
            }
            else
            {

```

```

/* Everything worked with ORDERS,
proceed with LINEITEM */
saveInsertedOrders = sqlca.sqlerrd[2];

sqlcode = 0;
#ifdef UF1DEBUG
fprintf (myostream, "in lineitem for update
pair number %d set %d chunk %d\n",
updatePair, i,UF_chunk);
fflush(myostream);
#endif

EXEC SQL INSERT INTO
TPCD.LINEITEM
SELECT
L_ORDERKEY,L_PARTKEY,L_SUPPKEY,L_LI
NENUMBER,L_QUANTITY,

L_EXTENDEDPRICE,L_DISCOUNT,L_TAX,

L_RETURNFLAG,L_LINESTATUS,L_SHIPDAT
E,L_COMMITDATE,L_RECEIPTDATE,

L_SHIPINSTRUCT,L_SHIPMODE,L_COMMENT
FROM TPCDTEMP.LINEITEM_NEW
WHERE APP_ID = :UF_chunk;
/*(AND L_ORDERKEY IN
(SELECT O_ORDERKEY FROM
TPCD.ORDERS
WHERE
12*(YEAR(O_ORDERDATE)-
1992)+MONTH(O_ORDERDATE)-01 = :month);*/

if (sqlca.sqlcode < 0)
sqlcode = error_check();

if (sqlcode == SQL_RC_E911)
{ /* we've hit a deadlock */
fprintf (myostream,
"\nA deadlock has been detected
inserting from
tpcdtemp.lineitem%d_%d...Retrying...\n",
updatePair, UF_chunk);
SleepSome(UF_DEADLOCK_SLEEP);
maxwait++; /* jen
DEADLOCK */
}
else if (sqlcode < 0)
{
fprintf(myostream,
"Insert into lineitem pair %d chunk
%d failed sqlcode=%d\n",
updatePair,UF_chunk,sqlcode);
dumpCa(&sqlca);
rc = -1;
}

```

```

else
{
#ifdef UF1DEBUG
fprintf (myostream, "lineitem insert
succeeded\n");
fflush(myostream);
#endif
/* accumulate the number of row inserted
*/
/* Order count ONLY updated if both
orders and lineitem */
/* go through */
insertedOrders += saveInsertedOrders;
/* kbs */
insertedLineitem += sqlca.sqlerrd[2];
rc=0;
EXEC SQL COMMIT WORK;
error_check();

#ifdef UF1DEBUG
/* report the number of row inserted */
fprintf(myostream, " interim %ld rows
for chunk %d into TPCD.ORDERS at %*.s\n",
insertedOrders,UF_chunk,T_STAMP_1LEN,T_ST
AMP_1LEN, /* TIME_ACC jen*/

get_time_stamp(T_STAMP_FORM_1,(Timer_struc
t *)NULL)); /* TIME_ACC jen*/
/* report the number of row deleted *s
inserted */
fprintf(myostream,
" interim %ld rows for chunk %d
into TPCD.LINEITEM at %*.s\n",
insertedLineitem,UF_chunk,
T_STAMP_1LEN,T_STAMP_1LEN,
/* TIME_ACC jen*/

get_time_stamp(T_STAMP_FORM_1,
(Timer_struct *)NULL)); /*
TIME_ACC jen*/

fprintf( myostream,
" inserts for update pair %d chunk
%d complete at %*.s\n\n",
updatePair, UF_chunk,
T_STAMP_1LEN,T_STAMP_1LEN, /*
TIME_ACC jen*/

get_time_stamp(T_STAMP_FORM_1,
(Timer_struct *)NULL)); /*
TIME_ACC jen*/

#endif
}

```

```

        } /* process lineitem INSERTs */
    } /* while loop for deadlocks */
} /* while processing chunks */

/* report the number of row deleted */
fprintf(myostream, "%ld rows inserted into
TPCD.ORDERS at %*.s\n",
insertedOrders,T_STAMP_1LEN,T_STAMP_1LEN
, /* TIME_ACC jen*/

get_time_stamp(T_STAMP_FORM_1,(Timer_struct *)NULL)); /* TIME_ACC jen*/
fprintf(myostream, "%ld rows inserted into
TPCD.LINEITEM at %*.s\n",
insertedLineitem,T_STAMP_1LEN,T_STAMP_1LEN, /* TIME_ACC jen*/

get_time_stamp(T_STAMP_FORM_1,(Timer_struct *)NULL)); /* TIME_ACC jen*/

if (sqlcode < 0)
{
    if (sqlcode == SQL_RC_E911)
    {
        fprintf (myostream,"# of deadlocks exceeds
%i\n", MAXWAIT);
    }
    rc=-1;
    EXEC SQL ROLLBACK WORK;
    error_check(); /* @d22275 tjt */

    goto UF1_exit;
}

/* UF1_conn_reset: */
EXEC SQL CONNECT RESET;
error_check(); /* @d22275 tjt */

UF1_exit:
fclose (myostream);
/* exiting, increment the semaphore */

/* we used the first flat file to generate the
semaphore key */

#ifdef SQLWINT
/* we will use the tpcd.setup file to generate the
semaphore key begin SEMA */
if (getenv("TPCD_AUDIT_DIR") != NULL)
{
    /* this is assuming that you will be running this
from 0th node */
    sprintf(sourcefile, "%s%ctools%ctpcd.setup",
        getenv("TPCD_AUDIT_DIR"),
        PATH_DELIM,PATH_DELIM);
    }
else
{
    fprintf (stderr, "Can't open UF1 semaphore file
TPCD_AUDIT_DIR is not defined.\n");
    exit (-1);
}
/* end SEMA */

su_semkey = ftok (sourcefile, 'J');
while ( (su_semid = semget (su_semkey, 1, 0)) <
0)
{
    if (errno == ENOENT) {
        sleep(2);
    }
    else {
        fprintf(stderr,"update set %d: semget failed
errno = %d\n",
i, errno);
        exit(1);
    }
}
if (sem_op (su_semid, 0, 1) != 0)
/*jen SEM*/
{
    fprintf(stderr,"Failure to increment semaphore
UF1 set %d\n",i);
    fprintf(stderr," semaphore sourcefile = %s
su_semid = su_semid\n",sourcefile);
    exit(1);
}
/*jenSEM*/

#else /* SQLWINT */
    sprintf (UF1_semfile, "%s.%s.UF1.semfile",
        getenv("TPCD_DBNAME"),
        getenv("USER"));
    fprintf(stderr,"UF1 semfile = %s\n",UF1_semfile);
    while ((su_hSem =
OpenSemaphore(SEMAPHORE_ALL_ACCESS |
SEMAPHORE_MODIFY_STATE |
SYNCHRONIZE,
TRUE,
UF1_semfile))
== (HANDLE)NULL)
{
    /*
** if cannot open the semaphore, wait for 0.1
second
*/
    fprintf(stderr,"Retry Open semaphore %s\n",
UF1_semfile);
}
#endif

```

```

        sleep(1);
    }

    if (! ReleaseSemaphore(su_hSem,
                          1,
                          (LPLONG)(NULL)))
    {
        fprintf(stderr, "ReleaseSemaphore failed,
LastError: %d, quit\n",
              GetLastError());
        exit(-1);
    }
#endif /* SQLWINT */
    exit(rc);          /* child exiting after finishing
up */
}

/*****
*****/
/* UF2 child */
/*****
*****/
void runUF2_fn ( int updatePair, int
thisConcurrentDelete, int numChunks, char
*dbname, char *userid, char *passwd )
{
    int rc = 0;
    long sqlcode;
    int maxwait;
    int startChunk =
thisConcurrentDelete*numChunks; /* where do we
start? */
    long deletedLineitems = 0; /*kmw*/
    long deletedOrders = 0; /*kmw*/
    long savedDeletedLineitems = 0; /*kbs*/

#ifdef SQLWINT
    int su_semid; /* semaphore for
controlling split updates*/
    key_t su_semkey; /* key to generate
semid */
#else
    HANDLE su_hSem;
    char UF2_semfile[256];
#endif

    char myoutstreamfile[256];
    FILE *myoutstream, *src_fh=NULL;

    strcpy(UF2_dbname, dbname);
    strcpy(UF2_userid, userid);
    strcpy(UF2_passwd, passwd);

    /* Generate the unique filename for this concurrent
delete process */
    sprintf (myoutstreamfile,
UF2OUTSTREAMPATTERN, env_tpcd_tmp_dir,
PATH_DELIM,
            updatePair, thisConcurrentDelete);
    if ( (myoutstream = fopen (myoutstreamfile,
WRITEMODE)) == NULL)
    {
        fprintf (stderr,
                "\nThe output file '%s' for update pair %d
set %d could not be opened runUF2_fn.\n",
myoutstreamfile,updatePair,thisConcurrentDelete);
        rc=-1;
        goto UF2_exit;
    }

    outstream=myoutstream; /* initialize outstream
for error_check dxxxxhar*/

#ifdef UF2DEBUG
    fprintf (myoutstream, "RunUF2 Called %d %d
%d\n",
            updatePair, thisConcurrentDelete,
numChunks );
    fflush(myoutstream);
#endif
    fprintf( myoutstream,
            "\nUF2 for update pair %d set %d starting at
%*.s\n",
            updatePair, thisConcurrentDelete,
T_STAMP_1LEN,T_STAMP_1LEN, /*
TIME_ACC jen*/

get_time_stamp(T_STAMP_FORM_1,(Timer_struc
t *)NULL)); /* TIME_ACC jen*/

#ifdef UF2DEBUG
    fprintf (myoutstream, "before connect\n");
    fflush(myoutstream);
#endif

    if (!strcmp(userid,"")) /** No authentication
provided **/
        EXEC SQL CONNECT TO :UF2_dbname;
    else
        EXEC SQL CONNECT TO :UF2_dbname USER
:UF2_userid USING :UF2_passwd;
    error_check();

#ifdef UF2DEBUG
    fprintf (myoutstream, "after connect startchunk=
%d, EndChunk = %d\n",

```

```

        startChunk,
startChunk+numChunks);
    fflush(myostream);
#endif

    /* Start processing each chunk in my range */
    for ( UF_chunk = startChunk; UF_chunk <
startChunk+numChunks; UF_chunk++)
    {

        /* Set things up for the loop which will retry if
there is a deadlock */
        sqlcode = SQL_RC_E911;
        month = (short)UF_chunk;
        maxwait = 1;
        rc = 0;

#ifdef UF2DEBUG
        fprintf (myostream, "Chunk = %d\n",
UF_chunk);
        fflush(myostream);
#endif
        while (sqlcode == SQL_RC_E911 && maxwait
<= MAXWAIT && rc == 0)
        {

#ifdef UF2DEBUG
            fprintf (myostream, "in loop before orders exec
sql\n");
            fflush(myostream);
#endif
            sqlcode = 0;

            EXEC SQL DELETE FROM
TPCD.LINEITEM
                WHERE L_ORDERKEY IN
                (SELECT O_ORDERKEY FROM
TPCDTEMP.ORDERS_DEL
                WHERE APP_ID = :UF_chunk);
            /*AND O_ORDERKEY IN
            (SELECT O_ORDERKEY FROM
TPCD.ORDERS
            WHERE
            12*(YEAR(O_ORDERDATE)-
            1992)+MONTH(O_ORDERDATE)-01 =
            :month);*/
            if (sqlca.sqlcode < 0)
                sqlcode = error_check();

            if (sqlcode == SQL_RC_E911)
            {
                /* we've hit a deadlock */
                fprintf (myostream,
                    "\nA deadlock detected while deleting from
LINEITEM: update pair %d set %d chunk %d.
Retrying.\n",

```

```

        updatePair, thisConcurrentDelete,
UF_chunk);
        dumpCa(&sqlca);
        SleepSome(UF_DEADLOCK_SLEEP);
        maxwait++; /* jen DEADLOCK */
    }
    else if (sqlcode < 0)
    {
        fprintf (myostream, "\n%s\n",
stmt_str.data);
        fprintf (myostream, "\nsqlcode %d occurred
deleting from TPCD.LINEITEM\n", sqlca.sqlcode);
        dumpCa(&sqlca);
        fprintf (myostream,
            "for update pair number %d set %d
chunk %d..Exiting\n",
            updatePair,
thisConcurrentDelete,UF_chunk);
        rc=-1;
    }
    else
    {
        /* accumulate the number of row deleted */
        savedDeletedLineitems = sqlca.sqlerrd[2];
        /*kbs*/

#ifdef UF2DEBUG
            fprintf (myostream, "in loop for update pair
number %d set %d chunk %d\n",
            updatePair,
thisConcurrentDelete,UF_chunk);
            fflush(myostream);
#endif

            /* delete the orders now */

            EXEC SQL DELETE FROM
TPCD.ORDERS
                WHERE O_ORDERKEY IN
                (SELECT O_ORDERKEY FROM
TPCDTEMP.ORDERS_DEL WHERE APP_ID =
:UF_chunk);
            /*AND 12*(YEAR(O_ORDERDATE)-
            1992)+MONTH(O_ORDERDATE)-01 = :month;*/

            if (sqlca.sqlcode < 0)
                sqlcode = error_check();

            if (sqlcode == SQL_RC_E911)
            {
                /* we've hit a deadlock */
            }
#ifdef UF2DEBUG
            fprintf (myostream, "orders deadlocked\n");
            fflush(myostream);
#endif
            fprintf (myostream,

```

```

        "\nA deadlock detected while deleting from
ORDERS: update pair %d set %d chunk %d.
Retrying.\n",
        updatePair, thisConcurrentDelete,
UF_chunk);
        dumpCa(&sqlca);
        SleepSome(UF_DEADLOCK_SLEEP);
        maxwait++; /* jen DEADLOCK */
    }
    else if (sqlcode < 0)
    {
#ifdef UF2DEBUG
        fprintf (myostream, "orders failed\n");
        fflush(myostream);
#endif
        fprintf (myostream, "\nAn error %d
occurred deleting from
TPCD.ORDERS\n", sqlca.sqlcode);
        dumpCa(&sqlca);
        fprintf (myostream, "for update pair
number %d set %d chunk %d..Exiting\n",
        updatePair,
thisConcurrentDelete, UF_chunk);
        rc=-1;
    }
    else
    {
#ifdef UF2DEBUG
        fprintf (myostream, "orders succeeded\n");
        fflush(myostream);
#endif
        /* accumulate the number of row deleted */
        /* Order count ONLY updated if both
orders and lineitem */
        /* go through */
        deletedLineitems +=
savedDeletedLineitems; /* kbs */
        deletedOrders += sqlca.sqlerrd[2];
        rc=0;
        EXEC SQL COMMIT WORK;
        error_check();
#ifdef UF2DEBUG
        /* report the number of rows deleted */
        fprintf(myostream, " interim %ld rows
for chunk %d from TPCD.ORDERS at %*.s\n",
        deletedOrders, UF_chunk, T_STAMP_1LEN, T_STA
AMP_1LEN, /* TIME_ACC jen*/

        get_time_stamp(T_STAMP_FORM_1, (Timer_struc
t *)NULL)); /* TIME_ACC jen*/
        fprintf(myostream, " interim %ld rows
for chunk %d from TPCD.LINEITEM at %*.s\n",
        deletedLineitems, UF_chunk, T_STAMP_1LEN, T_S
TAMP_1LEN, /* TIME_ACC jen*/

        get_time_stamp(T_STAMP_FORM_1, (Timer_struc
t *)NULL)); /* TIME_ACC jen*/
        fprintf( myostream,
            " deletes for update pair %d chunk
%d complete at %*.s\n\n",
            updatePair, UF_chunk,
            T_STAMP_1LEN, T_STAMP_1LEN, /*
TIME_ACC jen*/

        get_time_stamp(T_STAMP_FORM_1,
            (Timer_struct *)NULL)); /*
TIME_ACC jen*/
#endif
    }
} /* process orders deletes */
} /* while trying to delete one chunk loop */
} /* while there are more chunks */

#ifdef UF2DEBUG
    fprintf (myostream, "after loop\n");
    fflush(myostream);
#endif
/* report the number of row deleted */
fprintf(myostream, "%ld rows deleted from
TPCD.ORDERS at %*.s\n",
deletedOrders, T_STAMP_1LEN, T_STAMP_1LEN,
/* TIME_ACC jen*/

get_time_stamp(T_STAMP_FORM_1, (Timer_struc
t *)NULL)); /* TIME_ACC jen*/
    fprintf(myostream, "%ld rows deleted from
TPCD.LINEITEM at %*.s\n",
deletedLineitems, T_STAMP_1LEN, T_STAMP_1L
EN, /* TIME_ACC jen*/

get_time_stamp(T_STAMP_FORM_1, (Timer_struc
t *)NULL)); /* TIME_ACC jen*/

    if (sqlca.sqlcode < 0)
    {
        fprintf (myostream, "# of deadlocks %d
exceeds %i\n", maxwait, MAXWAIT);
        rc=-1;
        EXEC SQL ROLLBACK WORK;
        error_check(); /* @d22275 tjt */
    }

/* UF2_conn_reset: */ /*971101jen*/
EXEC SQL CONNECT RESET;
error_check(); /* @d22275 tjt */

```

```

UF2_exit:
    fclose (myostream);

    /* exiting, increment the semaphore */
#ifdef SQLWINT
    /* we used the tpcd.setup file to generate the
    semaphore key begin SEMA */
    if (getenv("TPCD_AUDIT_DIR") != NULL)
    {
        sprintf(sourcefile, "%s%ctools%ctpcd.setup",
            getenv("TPCD_AUDIT_DIR"),
            PATH_DELIM, PATH_DELIM);
    }
    else
    {
        fprintf (stderr, "Can't open UF2 semaphore file
        TPCD_AUDIT_DIR is not defined.\n");
        exit (-1);
    }

    su_semkey = ftok (sourcefile, 'D'); /* use D for
    deletes */
    /* end SEMA */
    while ((su_semid = semget(su_semkey,1,0)) < 0)
    {
        if (errno == ENOENT)
            sleep(2);
        else {
            fprintf(stderr,"UF2 update stream %d: semget
            failed errno = %d\n",
                updatePair, errno);
            exit(1);
        }
    }
    if (sem_op (su_semid, 0, 1) != 0) /*jenSEM*/
    {
        /*jenSEM*/
        fprintf(stderr,"Failure to increment semaphore
        UF2 set %d\n", thisConcurrentDelete);
        exit(1);
    }
    /*jenSEM*/

#else
    sprintf (UF2_semfile, "%s.%s.UF2.semfile",
        getenv("TPCD_DBNAME"),
        getenv("USER"));
    fprintf(stderr,"UF2 semfile = %s\n",UF2_semfile);
    while ((su_hSem =
    OpenSemaphore(SEMAPHORE_ALL_ACCESS |

SEMAPHORE_MODIFY_STATE |
                SYNCHRONIZE,
                TRUE,
                UF2_semfile))
        == (HANDLE) (NULL)) {
        /*
        ** if cannot open the semaphore, wait for 0.1
        second
        */
        fprintf(stderr,"Retry Open semaphore %s\n",
        UF2_semfile);

        SleepSome(1);
    }

    if (! ReleaseSemaphore(su_hSem,
        1,
        (LPLONG)(NULL)))
    {
        fprintf(stderr, "ReleaseSemaphore failed,
        GetLastError: %d, quit\n",
            GetLastError());
        exit(-1);
    }
#endif

    exit(rc); /* child exiting after finishing
    up */
}

```

## Appendix E: ACID Transaction Source Code

### *acid.h*

```
/*
*****
*****
*/
File: acid.h
/*
*****
*****
*/

#include <stdio.h>
#include <stdlib.h>
#include <time.h>

#ifdef SQLWINT
#include <windows.h>
#include <sys\timeb.h>
#include <sys\stat.h>
#include <stdlib.h>
#include <io.h>
#else
#include <unistd.h>
#include <sys/time.h>
#include <sys/timeb.h>
#endif

#include <string.h>
#include <math.h>

#define acidtime(tvsec,tvusec)
tvsec*1000+tvusec/1000
#define TSLEN 20

#if 0 /* needed on NT, not on AIX */
typedef struct timeval {
    long tv_sec; /* seconds */
    long tv_usec; /* and microseconds */
};
#endif

struct update_struct {
    int qnum;
};

struct acidQ_struct {
    int tag;
    long o_key;
    double l_extendedprice;
};

struct acidT_struct {
    int termination;
    int tag;
```

```
int logging;
long o_key;
long l_key;
long delta;
long l_partkey;
long l_suppkey;
double l_quantity;
double l_tax;
double l_discount;
double l_extendedprice;
double o_totalprice;
};

/*
** in acid.sqc
*/

int updateQ (struct update_struct *us);

char del(void);

#ifdef SQLWINT
void sleep (int sec);
#endif

acid.sqc

/*
*****
*****
*/
File: acid.sqc
/*
*****
*****
*/

/* changes:
*
* 961109 jel add EXEC SQL CLOSE for each
cursor in acidT
* to avoid bug in db2pe v1r2
* 980225 gav port to NT
* 981103 kal added ast_acidQ for isolation test
7
* 981103 kal changed ast query to be the same
as that used in
* consistency tests. Fixed so the long
lEprice is
* cast to a double. Changed so uses 3
decimal points of
* precision.
*/

#include "acid.h"
```



```

#if (defined(SQLPTX) || defined(SQLWINT) ||
defined(SQLSUN) || defined(Linux))
double nearest(double);
#endif /* SQLPTX */

#define DEADLOCK -911

/*
#define TRUNC2(d) ((floor((d)*100.0))/100.0)
*/
/*
#define TRUNC2(d)
((floor(nearest((d)*100.0)))*0.01)
*/
/*
#define TRUNC2(d)
((floor(nearest((d)*1000.0)/10.0)/100.0)
*/
#define TRUNC2(d)
((floor(nearest((d)*100000.0)/1000.0)/100.0))

void sqlerror(char * , struct sqlca *);

EXEC SQL INCLUDE SQLCA;
EXEC SQL BEGIN DECLARE SECTION;
char dbname[8]; /* = "tpcd"; */
EXEC SQL END DECLARE SECTION;

#ifdef SQLWINT

/*
** redefine gettimeofday so I don't have to
** change too much aix-specific code
*/
/*#typedef struct timeval { unsigned tv_sec;
unsigned tv_usec; }; */
typedef struct timezone { int dummy; };
struct timeb timer;

void gettimeofday( struct timeval *tv, struct
timezone *tz)
{
ftime(&timer);
tv->tv_sec = timer.time;
tv->tv_usec = timer.millitm * 1000;
tz->dummy = 0;
}
#endif

/*-----
-*/
/*      acidQ                                  */
/*-----
-*/
int acidQ (struct acidQ_struct *acid)

```

```

{
time_t timeT;
FILE *out;
char out_fn[50];
struct timeval tv;
struct timezone tz;
int mypid;
int rc = 0;

EXEC SQL BEGIN DECLARE SECTION;
sqlint32  okey;
sqlint32  lEprice;
double  eprice;
EXEC SQL END DECLARE SECTION;

okey = acid->o_key;

/* mypid = getpid(); */
mypid = acid->tag;

sprintf(out_fn,
"%s%cacidQ.out.%d",getenv("TPCD_TMP_DIR"),
del(),mypid);
out=fopen(out_fn,"a");
if (out == NULL)
{
fprintf(stderr, "ERROR input file %s could not be
appended to!!\n",out_fn);
}

gettimeofday(&tv, &tz);
time(&timeT);
fprintf(out, "\n----- START of acidQ tag: %d --
-----\n\n", mypid);
fprintf(out, "acidQ tag: %d, begin transaction time:
(%us %06uu) %s",
mypid, tv.tv_sec, tv.tv_usec, ctime(&timeT));
fprintf(out, "okey: %d\n", okey);

gettimeofday(&tv, &tz);
time(&timeT);
fprintf(out, "acidQ tag: %d, before read of
LINEITEM: (%us %06uu) %s",
mypid, tv.tv_sec, tv.tv_usec, ctime(&timeT));

/*
** use the same sql code as used in the
consistsql.pl to
** run the consistency acid queries. Note we
assign an long int
** to lEprice (we make it 10s of pennies by *
1000). Then divide
** by 1000.0 and cast it to a double (eprice) for
printing
*/

```

```

EXEC SQL
SELECT

INTEGER(DECIMAL(SUM(DECIMAL(INTEGER
(INTEGER(DECIMAL

(INTEGER(100*DECIMAL(L_EXTENDEDPRICE
,20,3)), 20,3) *
(1-L_DISCOUNT)) *
(1+L_TAX)),20,3)/100.0),20,3) * 1000)
into :IEprice
FROM
TPCD.LINEITEM
WHERE
L_ORDERKEY = :okey;

if (sqlca.sqlcode != 0) {
rc = sqlca.sqlcode;
fprintf(out,"acidQ **ERROR** sqlcode =
%d\n",sqlca.sqlcode);
sqlerror("acidQ: select sum(l_extendedprice)",
&sqlca);
goto Qerror;
}
eprice = (double)IEprice / 1000.0; /* translate to
double for printout*/

gettimeofday(&tv, &tz);
time(&timeT);
fprintf(out,"ACID tag: %d, after read of
LINEITEM: (%us %06uu) %s",
mypid, tv.tv_sec, tv.tv_usec, ctime(&timeT));
fprintf(out, "okey: %d \t sum(l_extendedprice):
%0.3f\n",
okey, eprice);

EXEC SQL COMMIT;
if (sqlca.sqlcode != 0) {
rc = sqlca.sqlcode;
fprintf(out,"acidQ **ERROR** sqlcode =
%d\n",sqlca.sqlcode);
sqlerror("acidQ: COMMIT", &sqlca);
goto Qerror;
}
acid->l_extendedprice = eprice;

rc = 0;
goto Qexit;

Qerror:
EXEC SQL rollback work;
if (sqlca.sqlcode != 0) sqlerror("acidQ:
ROLLBACK FAILED", &sqlca);

Qexit:

```

```

fprintf(out,"\n----- END of acidQ tag: %d ----
-----\n\n",mypid);
fflush(out);fclose(out);
return(rc);
}

/*-----
-*/
/* ast_acidQ */
/*-----
-*/
int ast_acidQ (struct acidQ_struct *acid)
{
time_t timeT;
FILE *out;
char out_fn[50];
struct timeval tv;
struct timezone tz;
int mypid;
int rc = 0;

EXEC SQL BEGIN DECLARE SECTION;
double ast_IEprice;
double ast_eprice;
EXEC SQL END DECLARE SECTION;

/* mypid = getpid(); */
mypid = acid->tag;

sprintf(out_fn,
"%s%cast_acidQ.out.%d",getenv("TPCD_TMP_DI
R"),del(),mypid);
out=fopen(out_fn,"a");
gettimeofday(&tv, &tz);
time(&timeT);
fprintf(out,"\n----- START of ast_acidQ tag:
%d ----- \n\n",mypid);
fprintf(out, "ast_acidQ tag: %d, begin transaction
time: (%us %06uu) %s",
mypid, tv.tv_sec, tv.tv_usec, ctime(&timeT));

gettimeofday(&tv, &tz);
time(&timeT);
fprintf(out,"ast_acidQ tag: %d, before read of
LINEITEM: (%us %06uu) %s",
mypid, tv.tv_sec, tv.tv_usec, ctime(&timeT));

/*
** use the same query acidQ except don't select
for specific okey.
** this ensures that the ast will be used instead of
the base table
** Have to use ast_IEprice as double since this
sum is so big

```

```

*/
EXEC SQL
SELECT
SUM ( L_EXTENDEDPRISE*(1-
L_DISCOUNT)*(1 + L_TAX))
into :ast_IEprice
FROM
TPCD.LINEITEM;

if (sqlca.sqlcode != 0) {
rc = sqlca.sqlcode;
fprintf(out,"ast_acidQ **ERROR** sqlcode =
%d\n",sqlca.sqlcode);
sqlerror("ast_acidQ: select
sum(l_extendedprice)", &sqlca);
goto Qerror;
}
ast_eprice = ast_IEprice; /* use ast_eprice for
printout to be consistent*/

gettimeofday(&tv, &tz);
time(&timeT);
fprintf(out,"AST_ACID tag: %d, after read of
LINEITEM: (%us %06uu) %s",
mypid, tv.tv_sec, tv.tv_usec, ctime(&timeT));
fprintf(out, "sum(l_extendedprice): %0.3f\n",
ast_eprice);

EXEC SQL COMMIT;
if (sqlca.sqlcode != 0) {
rc = sqlca.sqlcode;
fprintf(out,"ast_acidQ **ERROR** sqlcode =
%d\n",sqlca.sqlcode);
sqlerror("ast_acidQ: COMMIT", &sqlca);
goto Qerror;
}
acid->l_extendedprice = ast_eprice;

rc = 0;
goto Qexit;

Qerror:
EXEC SQL rollback work;
if (sqlca.sqlcode != 0) sqlerror("ast_acidQ:
ROLLBACK FAILED", &sqlca);

Qexit:
fprintf(out,"\n----- END of ast_acidQ tag: %d -
-----\n\n",mypid);
fflush(out);fclose(out);
return(rc);
}
/*-----
-*/
/* acidT */
/*-----
-*/
int acidT (struct acidT_struct *acid)
{
time_t timeT;
FILE *out;
char out_fn[50];
struct timeval tv;
struct timezone tz;
int mypid;
int rc = 0;

EXEC SQL BEGIN DECLARE SECTION;
sqlint32 o_key, l_key, delta;
sqlint32 l_partkey, l_suppkey;
double l_quantity, l_tax, l_discount,
l_extendedprice;
double o_totalprice;
double new_quantity, rprice, cost, new_extprice,
new_ototal, ototal;
EXEC SQL END DECLARE SECTION;

EXEC SQL DECLARE l_cursor CURSOR FOR
SELECT l_partkey, l_suppkey, l_quantity,
l_tax, l_discount,
l_extendedprice
FROM tpcd.lineitem
WHERE l_orderkey = :o_key
AND l_linenumber = :l_key
FOR UPDATE OF l_extendedprice,
l_quantity;

EXEC SQL DECLARE o_cursor CURSOR FOR
SELECT o_totalprice
FROM tpcd.orders
WHERE o_orderkey = :o_key
FOR UPDATE OF o_totalprice;

if (acid->termination < 0 || acid->termination > 3)
acid->termination = 0;
o_key = acid->o_key;
l_key = acid->l_key;
delta = acid->delta;

if (acid->logging) {
/* mypid = getpid(); */
mypid = acid->tag;
sprintf(out_fn,
"%s%cacidT.out.%d",getenv("TPCD_TMP_DIR"),d
el(),mypid);
out=fopen(out_fn,"a");
gettimeofday(&tv, &tz);
time(&timeT);
fprintf(out,"\n----- START of acidT tag: %d
-----\n\n",mypid);
}

```

```

    fprintf(out, "acidT tag: %d, begin transaction
time: (%us %06uu) %s",
        mypid, tv.tv_sec, tv.tv_usec,
ctime(&timeT));
    fprintf(out, "o_key: %d\tl_key: %d\tdelta:
%d\n", o_key, l_key, delta);
}
#ifdef DEBUG
    printf("o_key: %d\tl_key: %d\tdelta: %d\n",
o_key, l_key, delta);
#endif

retry_tran:

if (acid->logging) {
    gettimeofday(&tv, &tz);
    time(&timeT);
    fprintf(out, "acidT tag: %d, before read of
LINEITEM: (%us %06uu) %s",
        mypid, tv.tv_sec, tv.tv_usec,
ctime(&timeT));
}

EXEC SQL OPEN l_cursor;
if (sqlca.sqlcode != 0) {
    if (sqlca.sqlcode == DEADLOCK) goto
retry_tran;
    rc = sqlca.sqlcode;
    if (acid->logging) {
        fprintf(out, "acidT **ERROR** sqlcode =
%d\n", sqlca.sqlcode);
    } else {
        fprintf(stderr, "acidT **ERROR** sqlcode =
%d\n", sqlca.sqlcode);
    } /* endif */
    sqlerror("acidT: OPEN l_cursor", &sqlca);
    goto Terror;
}

EXEC SQL FETCH l_cursor INTO
:l_partkey, :l_suppkey, :l_quantity, :l_tax,
:l_discount, :l_extendedprice;
if (sqlca.sqlcode != 0) {
    if (sqlca.sqlcode == DEADLOCK) goto
retry_tran;
    rc = sqlca.sqlcode;
    if (acid->logging) {
        fprintf(out, "acidT **ERROR** sqlcode =
%d\n", sqlca.sqlcode);
    } else {
        fprintf(stderr, "acidT **ERROR** sqlcode =
%d\n", sqlca.sqlcode);
    } /* endif */
    sqlerror("acidT: FETCH l_cursor", &sqlca);
    goto Terror;
}

```

```

#ifdef DEBUG
    printf("l_quantity = %0.3f\n", l_quantity);
    printf("l_tax = %0.3f \n", l_tax);
    printf("l_discount = %0.3f \n", l_discount);
    printf("l_extendedprice = %0.3f \n",
l_extendedprice);
#endif

if (acid->logging) {
    gettimeofday(&tv, &tz);
    time(&timeT);
    fprintf(out, "acidT tag: %d, after read of
LINEITEM: (%us %06uu) %s",
        mypid, tv.tv_sec, tv.tv_usec,
ctime(&timeT));
    fprintf(out, "l_partkey: %d l_suppkey: %d
l_quantity: %0.3f\nl_tax: %0.3f l_discount: %0.3f
l_extendedprice: %0.3f\n",
        l_partkey, l_suppkey, l_quantity, l_tax,
l_discount, l_extendedprice);
}

rprice = TRUNC2( l_extendedprice/l_quantity );
cost = TRUNC2( rprice * delta );
new_extprice = l_extendedprice + cost;
new_quantity = l_quantity + delta;

#ifdef DEBUG
    printf("rprice = %0.3f\n", rprice );
    printf("cost = %0.3f\n", cost );
    printf("new_extprice = %0.3f\n", new_extprice );
    printf("new_quantity = %0.3f\n", new_quantity );
#endif

EXEC SQL UPDATE tpcd.lineitem
SET l_extendedprice = :new_extprice,
l_quantity = :new_quantity
WHERE CURRENT OF l_cursor;

if (sqlca.sqlcode != 0) {
    if (sqlca.sqlcode == DEADLOCK) goto
retry_tran;
    rc = sqlca.sqlcode;
    if (acid->logging) {
        fprintf(out, "acidT **ERROR** sqlcode =
%d\n", sqlca.sqlcode);
    } else {
        fprintf(stderr, "acidT **ERROR** sqlcode =
%d\n", sqlca.sqlcode);
    } /* endif */
    sqlerror("acidT: UPDATE l_cursor", &sqlca);
    goto Terror;
}

if (acid->logging) {

```

```

    gettimeofday(&tv, &tz);
    time(&timeT);
    fprintf(out,"acidT tag: %d, after update of
LINEITEM: (%us %06uu) %s",
        mypid, tv.tv_sec, tv.tv_usec,
ctime(&timeT));
    fprintf(out, "updated l_extendedprice: %0.3f\n",
new_extprice);
    fprintf(out, "updated l_quantity: %0.3f\n",
new_quantity);
}

/* if (acid->termination == 0) {
    EXEC SQL CLOSE L_CURSOR;
    EXEC SQL CLOSE O_CURSOR;
    EXEC SQL COMMIT;
    if (sqlca.sqlcode != 0) {
        if (sqlca.sqlcode == DEADLOCK) goto
retry_tran;
        rc = sqlca.sqlcode;
        if (acid->logging) {
            fprintf(out,"acidT **ERROR** sqlcode =
%d\n",sqlca.sqlcode);
        } else {
            fprintf(stderr,"acidT **ERROR** sqlcode =
%d\n",sqlca.sqlcode);
        }
        sqlerror("acidT: COMMIT", &sqlca);
        goto Terror;
    }
} */

if (acid->logging) {
    gettimeofday(&tv, &tz);
    time(&timeT);
    fprintf(out,"acidT tag: %d, before read of
ORDER: (%us %06uu) %s",
        mypid, tv.tv_sec, tv.tv_usec,
ctime(&timeT));
}

    EXEC SQL OPEN o_cursor;
    if (sqlca.sqlcode != 0) {
        if (sqlca.sqlcode == DEADLOCK) goto
retry_tran;
        rc = sqlca.sqlcode;
        if (acid->logging) {
            fprintf(out,"acidT **ERROR** sqlcode =
%d\n",sqlca.sqlcode);
        } else {
            fprintf(stderr,"acidT **ERROR** sqlcode =
%d\n",sqlca.sqlcode);
        } /* endif */
        sqlerror("acidT: OPEN o_cursor", &sqlca);
        goto Terror;
    }
}

```

```

EXEC SQL FETCH o_cursor INTO :o_totalprice;
if (sqlca.sqlcode != 0) {
    if (sqlca.sqlcode == DEADLOCK) goto
retry_tran;
    rc = sqlca.sqlcode;
    if (acid->logging)
    {
        fprintf(out,"acidT **ERROR** sqlcode =
%d\n",sqlca.sqlcode);
    }
    else
    {
        fprintf(stderr,"acidT **ERROR** sqlcode =
%d\n",sqlca.sqlcode);
    }
    sqlerror("acidT: FETCH o_cursor", &sqlca);
    goto Terror;
}

#ifdef DEBUG
    printf("o_totalprice = %0.3f\n",o_totalprice);
#endif

    if (acid->logging) {
        gettimeofday(&tv, &tz);
        time(&timeT);
        fprintf(out,"acidT tag: %d, after read of ORDER:
(%us %06uu) %s",
            mypid, tv.tv_sec, tv.tv_usec,
ctime(&timeT));
        fprintf(out, "o_totalprice: %0.3f\n",
o_totalprice);
    }

#ifdef DEBUG
    {
        double zeroone= l_extendedprice * (1.0-
l_discount);
        double zeroonetimes= (l_extendedprice * (1.0-
l_discount))*100.0;
        double firststone = TRUNC2(l_extendedprice *
(1.0-l_discount));
        double notone= TRUNC2 ( l_extendedprice *
(1.0-l_discount) ) * (1.0+l_tax);
        double secondone= TRUNC2( TRUNC2(
l_extendedprice * (1.0-l_discount) ) * (1.0+l_tax) );
        printf("firststone= %f\n", firststone);
        printf("zeroone= %f\n", zeroone);
        printf("zeroonetimes= %f\n", zeroonetimes);
        printf("notone= %f\n", notone);
        printf("secondone= %f\n", secondone);
    }
#endif
    ototal = o_totalprice -

```

```

        TRUNC2( TRUNC2( L_extendedprice *
(1-l_discount) ) * (1+l_tax) );
        new_ototal = TRUNC2( new_extprice * (1.0-
l_discount) );
        new_ototal = TRUNC2( new_ototal * (1.0+l_tax)
);
        new_ototal = ototal + new_ototal;

#ifdef DEBUG
        printf("o_totalprice= %f\n",o_totalprice);
        printf("ototal= %0.3f\n",ototal);
        printf("ototal= %f\n",ototal);
        printf("new_ototal= %0.3f\n",new_ototal);
#endif

        EXEC SQL UPDATE tpcd.orders
        SET o_totalprice = :new_ototal
        WHERE CURRENT OF o_cursor;
        if (sqlca.sqlcode != 0) {
            if(sqlca.sqlcode == DEADLOCK) goto
retry_tran;
            rc = sqlca.sqlcode;
            if (acid->logging) {
                fprintf(out,"acidT **ERROR** sqlcode =
%d\n",sqlca.sqlcode);
            } else {
                fprintf(stderr,"acidT **ERROR** sqlcode =
%d\n",sqlca.sqlcode);
            } /* endif */
            sqlerror("acidT: UPDATE o_cursor", &sqlca);
            goto Terror;
        }

        if (acid->logging) {
            gettimeofday(&tv, &tz);
            time(&timeT);
            fprintf(out,"acidT tag: %d, after update of
ORDER: (%us %06uu) %s",
                mypid, tv.tv_sec, tv.tv_usec,
ctime(&timeT));
            fprintf(out, "updated o_totalprice: %0.3f\n",
new_ototal) ;
        }

/*
** why is this code in here? we don't want to
** commit until the history table has been updated
as well
        if (acid->termination == 0) {
            EXEC SQL CLOSE L_CURSOR;
            EXEC SQL CLOSE O_CURSOR;
            EXEC SQL COMMIT;
            if (sqlca.sqlcode != 0) {
                if(sqlca.sqlcode == DEADLOCK) goto
retry_tran;
                rc = sqlca.sqlcode;

```

```

        if (acid->logging) {
            fprintf(out,"acidT **ERROR** sqlcode =
%d\n",sqlca.sqlcode);
        } else {
            fprintf(stderr,"acidT **ERROR** sqlcode =
%d\n",sqlca.sqlcode);
        }
        sqlerror("acidT: COMMIT", &sqlca);
        goto Terror;
    }
}
*/

        if (acid->logging) {
            gettimeofday(&tv, &tz);
            time(&timeT);
            fprintf(out,"acidT tag: %d, before insert into
HISTORY: (%us %06uu) %s",
                mypid, tv.tv_sec, tv.tv_usec,
ctime(&timeT));
        }

        EXEC SQL INSERT INTO tpcd.history values
(:l_partkey, :l_suppkey, :o_key, :l_key, :delta,
CURRENT TIMESTAMP);
        if (sqlca.sqlcode != 0) {
            if(sqlca.sqlcode == DEADLOCK) goto
retry_tran;
            rc = sqlca.sqlcode;
            if (acid->logging) {
                fprintf(out,"acidT **ERROR** sqlcode =
%d\n",sqlca.sqlcode);
            } else {
                fprintf(stderr,"acidT **ERROR** sqlcode =
%d\n",sqlca.sqlcode);
            } /* endif */
            sqlerror("acidT: INSERT INTO history",
&sqlca);
            goto Terror;
        }

        if (acid->logging) {
            gettimeofday(&tv, &tz);
            time(&timeT);
            fprintf(out,"acidT tag: %d, after insert into
HISTORY: (%us %06uu) %s",
                mypid, tv.tv_sec, tv.tv_usec,
ctime(&timeT));
        }

        /* sleep for 1 second for 80% of the transactions */
#ifdef SQLWINT
        if ( ((rand() % (100)) + 1) < 80 ) sleep(1);
#else
        if ( ((random() % (100)) + 1) < 80 ) sleep(1);
#endif
#endif

```

```

switch (acid->termination) {
case 1:
{
if (acid->logging)
{
gettimeofday(&tv, &tz);
time(&timeT);
fprintf(out,"acidT tag: %d, wait before
COMMIT: (%us %06uu) %s",
mypid, tv.tv_sec, tv.tv_usec,
ctime(&timeT));
}
}
sleep(60);
case 0:
if (acid->logging) {
gettimeofday(&tv, &tz);
time(&timeT);
fprintf(out,"acidT tag: %d, immediately before
COMMIT: (%us %06uu) %s",
mypid, tv.tv_sec, tv.tv_usec,
ctime(&timeT));
}
EXEC SQL CLOSE L_CURSOR;
EXEC SQL CLOSE O_CURSOR;
EXEC SQL COMMIT;
if (sqlca.sqlcode != 0) {
if (sqlca.sqlcode == DEADLOCK) goto
retry_tran;
rc = sqlca.sqlcode;
if (acid->logging) {
fprintf(out,"acidT **ERROR** sqlcode =
%d\n",sqlca.sqlcode);
} else {
fprintf(stderr,"acidT **ERROR** sqlcode =
%d\n",sqlca.sqlcode);
} /* endif */
sqlerror("acidT: COMMIT", &sqlca);
goto Terror;
}
if (acid->logging) {
gettimeofday(&tv, &tz);
time(&timeT);
fprintf(out,"acidT tag: %d, after COMMIT:
(%us %06uu) %s",
mypid, tv.tv_sec, tv.tv_usec,
ctime(&timeT));
}
break;
case 3:
if (acid->logging) {
gettimeofday(&tv, &tz);
time(&timeT);
fprintf(out,"acidT tag: %d, wait before
ROLLBACK: (%us %06uu) %s",

```

```

mypid, tv.tv_sec, tv.tv_usec,
ctime(&timeT));
}
sleep(60);
case 2:
if (acid->logging) {
gettimeofday(&tv, &tz);
time(&timeT);
fprintf(out,"acidT tag: %d, immediately before
ROLLBACK: (%us %06uu) %s",
mypid, tv.tv_sec, tv.tv_usec,
ctime(&timeT));
}
EXEC SQL CLOSE L_CURSOR;
EXEC SQL CLOSE O_CURSOR;
EXEC SQL rollback work;
if (sqlca.sqlcode != 0) {
if (sqlca.sqlcode == DEADLOCK) goto
retry_tran;
rc = sqlca.sqlcode;
if (acid->logging) {
fprintf(out,"acidT **ERROR** sqlcode =
%d\n",sqlca.sqlcode);
} else {
fprintf(stderr,"acidT **ERROR** sqlcode =
%d\n",sqlca.sqlcode);
} /* endif */
sqlerror("acidT: ROLLBACK", &sqlca);
goto Terror;
}
if (acid->logging) {
gettimeofday(&tv, &tz);
time(&timeT);
fprintf(out,"acidT tag: %d, after ROLLBACK:
(%us %06uu) %s",
mypid, tv.tv_sec, tv.tv_usec,
ctime(&timeT));
}
break;
}

acid->l_partkey = l_partkey;
acid->l_suppkey = l_suppkey;
acid->l_quantity = l_quantity;
acid->l_tax = l_tax;
acid->l_discount = l_discount;
acid->l_extendedprice = l_extendedprice;
acid->o_totalprice = o_totalprice;

rc = 0;
goto Texit;

Terror:
EXEC SQL CLOSE L_CURSOR;
EXEC SQL CLOSE O_CURSOR;
EXEC SQL rollback work;

```

```

    if (sqlca.sqlcode != 0) sqlerror("acidT:
ROLLBACK FAILED", &sqlca);

Texit:
    if (acid->logging) {
        fprintf(out, "\n----- END of acidT tag: %d ---
-----\n\n", mypid);
        fflush(out); fclose(out);
    }
    return(rc);
}

/*-----
-*/
/*      updateQ                                */
/*-----
-*/

int updateQ (struct update_struct *us)
{
    FILE *out;
    time_t timeT;
    struct timeval tv;
    struct timezone tz;
    int qnum;
    int rc = 0;
    int i;
    int secs2sleep;
    char buff[256];
    struct acidtype {int logging;} a, *acid;

EXEC SQL BEGIN DECLARE SECTION;
double  acctbal;
double  discount;
double  price;
sqlint32  availqty;
sqlint32  size;
EXEC SQL END DECLARE SECTION;

    qnum = us->qnum;

    acid = &a;
    acid->logging= 1;

    sprintf(buff,
"%s%cupdate.out", getenv("TPCD_TMP_DIR"), del(
));
    out=fopen(buff, "a");

    gettimeofday(&tv, &tz);
    time(&timeT);
    fprintf(out, "\n----- START of update -----
\n\n");
    fprintf(out, "update query number: %d, begin
transaction time: (%us %06uu) %s",
        qnum, tv.tv_sec, tv.tv_usec, ctime(&timeT));

```

```

    sqlca.sqlcode = 0;
    discount = 0.25;
    price = 5000.50;
    acctbal = 1000.00;
    availqty = 10;
    size = 5;

    for (i=1; i <= 2; i++) {
        gettimeofday(&tv, &tz);
        time(&timeT);
        fprintf(out, "update query number: %d, pass %d,
immediately before UPDATE: (%us %06uu) %s",
            qnum, i, tv.tv_sec, tv.tv_usec,
            ctime(&timeT));

        switch (qnum)
        {
            case 1:
                {
                    EXEC SQL
                    UPDATE TPCD.LINEITEM set
                    L_DISCOUNT = L_DISCOUNT + :discount
                    WHERE L_ORDERKEY IN
                    (326,512,928,995);
                    if (sqlca.sqlcode != 0) {
                        rc = sqlca.sqlcode;
                        if (acid->logging)
                        {
                            fprintf(out, "update query number: %d, pass
%d, **ERROR** sqlcode = %d\n",
                                qnum, i, sqlca.sqlcode);
                        }
                        else
                        {
                            fprintf(stderr, "update query number: %d,
pass %d, **ERROR** sqlcode = %d\n",
                                qnum, i, sqlca.sqlcode);
                        }
                    }
                    sqlerror("update query number 1", &sqlca);
                    goto Uerror;
                }
            case 2:
                {
                    EXEC SQL
                    UPDATE TPCD.SUPPLIER set
                    S_ACCTBAL = S_ACCTBAL + :acctbal
                    WHERE S_NAME in
                    ('Supplier#000000647', 'Supplier#000000070', 'Suppli
er#000000802');
                    if (sqlca.sqlcode != 0) {
                        rc = sqlca.sqlcode;
                        if (acid->logging)

```



```

        {
            fprintf(out,"update query number: %d, pass
%d, **ERROR** sqlcode = %d\n",
                qnum, i, sqlca.sqlcode);
        }
        else
        {
            fprintf(stderr,"update query number: %d,
pass %d, **ERROR** sqlcode = %d\n",
                qnum, i, sqlca.sqlcode);
        }
        sqlerror("update query number 2", &sqlca);
        goto Uerror;
    }
    acctbal = acctbal * (-1);
    secs2sleep = 90;
    break;
}
case 3:
{
    EXEC SQL
        UPDATE TPCD.LINEITEM set
        L_DISCOUNT = L_DISCOUNT + :discount
        WHERE L_ORDERKEY IN (260930,
        402497, 457859, 509889, 58117,
        538311, 588421, 416167,
        97830, 90276);
    if (sqlca.sqlcode != 0) {
        rc = sqlca.sqlcode;
        if (acid->logging)
        {
            fprintf(out,"update query number: %d, pass
%d, **ERROR** sqlcode = %d\n",
                qnum, i, sqlca.sqlcode);
        }
    }
    else
    {
        fprintf(stderr,"update query number: %d,
pass %d, **ERROR** sqlcode = %d\n",
                qnum, i, sqlca.sqlcode);
    }
    sqlerror("update query number 3", &sqlca);
    goto Uerror;
}
discount = discount * (-1);
secs2sleep = 300;
break;
}
case 4:
{
    if ( i ==1 ) {
        EXEC SQL
            UPDATE TPCD.ORDERS set
            O_ORDERDATE = O_ORDERDATE - 6
            MONTHS
            WHERE O_ORDERKEY = 67461;
        /* WHERE O_ORDERKEY IN
(22400,28515,34338,46596,67461,92644,98307);*/
    }
    else {
        EXEC SQL
            UPDATE TPCD.ORDERS set
            O_ORDERDATE = O_ORDERDATE + 6
            MONTHS
            WHERE O_ORDERKEY = 67461;
    }
    if (sqlca.sqlcode != 0) {
        rc = sqlca.sqlcode;
        if (acid->logging)
        {
            fprintf(out,"update query number: %d, pass
%d, **ERROR** sqlcode = %d\n",
                qnum, i, sqlca.sqlcode);
        }
    }
    else
    {
        fprintf(stderr,"update query number: %d,
pass %d, **ERROR** sqlcode = %d\n",
                qnum, i, sqlca.sqlcode);
    }
    sqlerror("update query number 4", &sqlca);
    goto Uerror;
}
secs2sleep = 300;
break;
}
case 5:
{
    EXEC SQL
        UPDATE TPCD.LINEITEM set
        L_DISCOUNT = L_DISCOUNT + :discount
        WHERE L_ORDERKEY IN
(70976,566279,152897,84226,232483);
    if (sqlca.sqlcode != 0) {
        rc = sqlca.sqlcode;
        if (acid->logging)
        {
            fprintf(out,"update query number: %d, pass
%d, **ERROR** sqlcode = %d\n",
                qnum, i, sqlca.sqlcode);
        }
    }
    else
    {
        fprintf(stderr,"update query number: %d,
pass %d, **ERROR** sqlcode = %d\n",
                qnum, i, sqlca.sqlcode);
    }
    sqlerror("update query number 5", &sqlca);
    goto Uerror;
}
discount = discount * (-1);
secs2sleep = 300;
break;
}

```

```

}
case 6:
{
EXEC SQL
UPDATE TPCD.LINEITEM set
L_DISCOUNT = L_DISCOUNT + :discount
WHERE L_ORDERKEY in
(33,131,161,195,229,230,231,323,353,356);
if (sqlca.sqlcode != 0) {
rc = sqlca.sqlcode;
if (acid->logging)
{
fprintf(out,"update query number: %d, pass
%d, **ERROR** sqlcode = %d\n",
qnum, i, sqlca.sqlcode);
}
else
{
fprintf(stderr,"update query number: %d,
pass %d, **ERROR** sqlcode = %d\n",
qnum, i, sqlca.sqlcode);
}
sqlerror("update query number 6", &sqlca);
goto Uerror;
}
discount = discount * (-1);
secs2sleep = 300;
break;
}
case 7:
{
EXEC SQL
UPDATE TPCD.LINEITEM set
L_DISCOUNT = L_DISCOUNT + :discount
WHERE L_ORDERKEY IN
(562917,410659,16550,398401,157634,429920,454
11);
if (sqlca.sqlcode != 0) {
rc = sqlca.sqlcode;
if (acid->logging)
{
fprintf(out,"update query number: %d, pass
%d, **ERROR** sqlcode = %d\n",
qnum, i, sqlca.sqlcode);
}
else
{
fprintf(stderr,"update query number: %d,
pass %d, **ERROR** sqlcode = %d\n",
qnum, i, sqlca.sqlcode);
}
sqlerror("update query number 7", &sqlca);
goto Uerror;
}
discount = discount * (-1);
secs2sleep = 300;

```

```

break;
}
case 8:
{
EXEC SQL
UPDATE TPCD.LINEITEM set
L_DISCOUNT = L_DISCOUNT + :discount
WHERE L_ORDERKEY IN
(129569,343591,270242,254983,98500,28963);
if (sqlca.sqlcode != 0) {
rc = sqlca.sqlcode;
if (acid->logging)
{
fprintf(out,"update query number: %d, pass
%d, **ERROR** sqlcode = %d\n",
qnum, i, sqlca.sqlcode);
}
else
{
fprintf(stderr,"update query number: %d,
pass %d, **ERROR** sqlcode = %d\n",
qnum, i, sqlca.sqlcode);
}
sqlerror("update query number 8", &sqlca);
goto Uerror;
}
discount = discount * (-1);
secs2sleep = 300;
break;
}
case 9:
{
EXEC SQL
UPDATE TPCD.LINEITEM set
L_DISCOUNT = L_DISCOUNT + :discount
WHERE L_ORDERKEY IN
(113509,232997,246691,379233,448162,32134);
if (sqlca.sqlcode != 0) {
rc = sqlca.sqlcode;
if (acid->logging)
{
fprintf(out,"update query number: %d, pass
%d, **ERROR** sqlcode = %d\n",
qnum, i, sqlca.sqlcode);
}
else
{
fprintf(stderr,"update query number: %d,
pass %d, **ERROR** sqlcode = %d\n",
qnum, i, sqlca.sqlcode);
}
sqlerror("update query number 9", &sqlca);
goto Uerror;
}
discount = discount * (-1);
secs2sleep = 300;

```

```

break;
}
case 10:
{
EXEC SQL
UPDATE TPCD.LINEITEM set
L_DISCOUNT = L_DISCOUNT + :discount
WHERE L_ORDERKEY IN
(516487,245411,265799,253025,6914,562020);
if (sqlca.sqlcode != 0) {
rc = sqlca.sqlcode;
if (acid->logging)
{
fprintf(out,"update query number: %d, pass
%d, **ERROR** sqlcode = %d\n",
qnum, i, sqlca.sqlcode);
}
else
{
fprintf(stderr,"update query number: %d,
pass %d, **ERROR** sqlcode = %d\n",
qnum, i, sqlca.sqlcode);
}
sqlerror("update query number 10", &sqlca);
goto Uerror;
}
discount = discount * (-1);
secs2sleep = 300;
break;
}
case 11:
{
EXEC SQL
UPDATE TPCD.PARTSUPP set
PS_AVAILQTY = PS_AVAILQTY + :availqty
WHERE PS_PARTKEY IN
(12098,5134,13334,17052,3452,12552,1084,5797);
if (sqlca.sqlcode != 0) {
rc = sqlca.sqlcode;
if (acid->logging)
{
fprintf(out,"update query number: %d, pass
%d, **ERROR** sqlcode = %d\n",
qnum, i, sqlca.sqlcode);
}
else
{
fprintf(stderr,"update query number: %d,
pass %d, **ERROR** sqlcode = %d\n",
qnum, i, sqlca.sqlcode);
}
sqlerror("update query number 11", &sqlca);
goto Uerror;
}
availqty = availqty * (-1);
secs2sleep = 180;

```

```

break;
}
case 12:
{
if (i == 1) {
EXEC SQL
UPDATE TPCD.LINEITEM set
L_RECEIPTDATE = L_RECEIPTDATE - 3
YEARS
WHERE L_ORDERKEY IN
(33,70,195,355,677,837,960,962,1028);
} else {
EXEC SQL
UPDATE TPCD.LINEITEM set
L_RECEIPTDATE = L_RECEIPTDATE + 3
YEARS
WHERE L_ORDERKEY IN
(33,70,195,355,677,837,960,962,1028);
}
if (sqlca.sqlcode != 0) {
rc = sqlca.sqlcode;
if (acid->logging)
{
fprintf(out,"update query number: %d, pass
%d, **ERROR** sqlcode = %d\n",
qnum, i, sqlca.sqlcode);
}
else
{
fprintf(stderr,"update query number: %d,
pass %d, **ERROR** sqlcode = %d\n",
qnum, i, sqlca.sqlcode);
}
sqlerror("update query number 12", &sqlca);
goto Uerror;
}
secs2sleep = 300;
break;
}
case 13:
{
EXEC SQL
UPDATE TPCD.LINEITEM set
L_DISCOUNT = L_DISCOUNT + :discount
WHERE L_ORDERKEY IN
(263,9476,32355,34854,53445,56901);
if (sqlca.sqlcode != 0) {
rc = sqlca.sqlcode;
if (acid->logging)
{
fprintf(out,"update query number: %d, pass
%d, **ERROR** sqlcode = %d\n",
qnum, i, sqlca.sqlcode);
}
else
{

```

```

        fprintf(stderr,"update query number: %d,
pass %d, **ERROR** sqlcode = %d\n",
            qnum, i, sqlca.sqlcode);
    }
    sqlerror("update query number 13", &sqlca);
    goto Uerror;
}
discount = discount * (-1);
secs2sleep = 90;
break;
}
case 14:
{
    EXEC SQL
        UPDATE TPCD.LINEITEM set
L_DISCOUNT = L_DISCOUNT + :discount
        WHERE L_ORDERKEY IN
(32,225,326,448,449,483,512);
    if (sqlca.sqlcode != 0) {
        rc = sqlca.sqlcode;
        if (acid->logging)
        {
            fprintf(out,"update query number: %d, pass
%d, **ERROR** sqlcode = %d\n",
                qnum, i, sqlca.sqlcode);
        }
        else
        {
            fprintf(stderr,"update query number: %d,
pass %d, **ERROR** sqlcode = %d\n",
                qnum, i, sqlca.sqlcode);
        }
        sqlerror("update query number 14", &sqlca);
        goto Uerror;
    }
    discount = discount * (-1);
    secs2sleep = 180;
    break;
}
case 15:
{
    EXEC SQL
        UPDATE TPCD.LINEITEM set
L_DISCOUNT = L_DISCOUNT + :discount
        WHERE L_ORDERKEY IN
(1,4,7,35,135,131300);
    if (sqlca.sqlcode != 0) {
        rc = sqlca.sqlcode;
        if (acid->logging)
        {
            fprintf(out,"update query number: %d, pass
%d, **ERROR** sqlcode = %d\n",
                qnum, i, sqlca.sqlcode);
        }
        else
        {

```

```

        fprintf(stderr,"update query number: %d,
pass %d, **ERROR** sqlcode = %d\n",
            qnum, i, sqlca.sqlcode);
    }
    sqlerror("update query number 15", &sqlca);
    goto Uerror;
}
discount = discount * (-1);
secs2sleep = 180;
break;
}
case 16:
{
    EXEC SQL
        UPDATE TPCD.PART set P_SIZE =
P_SIZE + :size
        WHERE P_PARTKEY IN (4,7,15,1313);
    if (sqlca.sqlcode != 0) {
        rc = sqlca.sqlcode;
        if (acid->logging)
        {
            fprintf(out,"update query number: %d, pass
%d, **ERROR** sqlcode = %d\n",
                qnum, i, sqlca.sqlcode);
        }
        else
        {
            fprintf(stderr,"update query number: %d,
pass %d, **ERROR** sqlcode = %d\n",
                qnum, i, sqlca.sqlcode);
        }
        sqlerror("update query number 16", &sqlca);
        goto Uerror;
    }
    size = size * (-1);
    secs2sleep = 180;
    break;
}
case 17:
{
    EXEC SQL
        UPDATE TPCD.LINEITEM set
L_EXTENDEDPRICE = L_EXTENDEDPRICE +
:price
        WHERE L_ORDERKEY IN
(4065,110372,165061,265702,87138);
    if (sqlca.sqlcode != 0) {
        rc = sqlca.sqlcode;
        if (acid->logging)
        {
            fprintf(out,"update query number: %d, pass
%d, **ERROR** sqlcode = %d\n",
                qnum, i, sqlca.sqlcode);
        }
        else
        {

```

```

        fprintf(stderr,"update query number: %d,
pass %d, **ERROR** sqlcode = %d\n",
            qnum, i, sqlca.sqlcode);
    }
    sqlerror("update query number 17", &sqlca);
    goto Uerror;
}
price = price * (-1);
secs2sleep = 90;
break;
}
default:
{
    fprintf(out,"ERROR: Invalid query number
specified %d\n", qnum);
    rc = 1;
    goto Uexit;
}
}

gettimeofday(&tv, &tz);
time(&timeT);

if (acid->logging)
    fprintf(out,"update query number: %d, pass
%d, after UPDATE: (%us %06uu) %s",
        qnum, i, tv.tv_sec, tv.tv_usec,
ctime(&timeT));
else
    fprintf(stderr,"update query number: %d, pass
%d, after UPDATE: (%us %06uu) %s",
        qnum, i, tv.tv_sec, tv.tv_usec,
ctime(&timeT));

if ( i == 2 ) {
    gettimeofday(&tv, &tz);
    time(&timeT);
    fprintf(out,"update query number: %d, pass
%d, sleeping for %d seconds: (%us %06uu) %s",
        qnum, i, secs2sleep, tv.tv_sec, tv.tv_usec,
ctime(&timeT));
    fflush(out);
    system("touch /tmp/tpcd/update.sync.sleep");
    sleep(secs2sleep);
}

gettimeofday(&tv, &tz);
time(&timeT);
fprintf(out,"update query number: %d, pass %d,
immediately before COMMIT: (%us %06uu) %s",
    qnum, i, tv.tv_sec, tv.tv_usec,
ctime(&timeT));

EXEC SQL COMMIT;
if (sqlca.sqlcode != 0) {
    rc = sqlca.sqlcode;
    fprintf(out,"update pass %d, **ERROR**
sqlcode = %d\n", i, sqlca.sqlcode);
    sqlerror("update: COMMIT", &sqlca);
    goto Uerror;
}
gettimeofday(&tv, &tz);
time(&timeT);
if (acid->logging)
    fprintf(out,"update query number: %d, pass
%d, after COMMIT: (%us %06uu) %s",
        qnum, i, tv.tv_sec, tv.tv_usec,
ctime(&timeT));
else
    fprintf(stderr,"update query number: %d, pass
%d, after COMMIT: (%us %06uu) %s",
        qnum, i, tv.tv_sec, tv.tv_usec,
ctime(&timeT));
}

rc = 0;
goto Uexit;

Uerror:
EXEC SQL rollback work;
if (sqlca.sqlcode != 0) sqlerror("update:
ROLLBACK FAILED", &sqlca);
system("touch /tmp/tpcd/update.sync.sleep");

Uexit:
fprintf(out,"\n----- END of update -----
\n\n");
fflush(out);fclose(out);
return(rc);
}

/*-----
-*/
/*    connect_to_TM                                */
/*-----
-*/
void connect_to_TM( void )
{
    char *dbname_ptr;
    if ((dbname_ptr =
getenv("TPCD_QUAL_DBNAME")) != NULL) {
        fprintf(stderr,"***** %s
*****\n",dbname_ptr);
        strcpy (dbname, dbname_ptr);
    }

EXEC SQL CONNECT TO :dbname IN SHARE
MODE;
if (sqlca.sqlcode < 0) {
    fprintf(stderr, "CONNECT TO %s failed
SQLCODE = %d\n", dbname, sqlca.sqlcode);
    exit(-1);
}
}

```

```

    }
    return;
}

/*-----
-*/
/* disconnect_from_TM
*/
/*-----
-*/
void disconnect_from_TM ( void )
{
    EXEC SQL CONNECT RESET;
    if (sqlca.sqlcode < 0) {
        fprintf(stderr, "DISCONNECT failed
SQLCODE = %d\n", sqlca.sqlcode);
        exit(-1);
    }
    return;
}

/*-----
-*/
/* sqlerror */
/*-----
-*/
void sqlerror(char *msg, struct sqlca *psqlca)
{
    FILE *err_fp;

    char err_fn[256];

    int j,k;

    sprintf(err_fn,
"%s%cacid.sqlerrors",getenv("TPCD_TMP_DIR"),d
el());
    err_fp=fopen(err_fn,"a");
    fprintf(err_fp,"acid: sqlcode: %4d %s\n", psqlca-
>sqlcode, msg);
    fprintf(stderr,"acid: sqlcode: %4d %s\n", psqlca-
>sqlcode, msg);
    fflush(stderr);
    if (psqlca->sqlerrmc[0] != ' ' || psqlca->sqlerrmc[1]
!= ' ') {
        fprintf(err_fp,"acid: slerrmc: ");
        for(j = 0; j < 5; j++)
        {
            for(k = 0; k < 14; k++) fprintf(err_fp,"%x ",
psqlca->sqlerrmc[j*10+k]);
            fprintf(err_fp," ");
            for(k = 0; k < 14; k++) fprintf(err_fp,"%c",
psqlca->sqlerrmc[j*10+k]);
            fprintf(err_fp,"\n");
        }
        if (j < 4) fprintf(err_fp," ");
    }
    fprintf(err_fp,"acid: sqlerrp: ");
    for(j = 0; j < 8; j++) fprintf(err_fp,"%c", psqlca-
>sqlerrp[j]);
    fprintf(err_fp,"\n");

    fprintf(err_fp,"acid: sqlerrd: ");
    for(j = 0; j < 6; j++) fprintf(err_fp," %d", psqlca-
>sqlerrd[j]);
    fprintf(err_fp,"\n");

    if (psqlca->sqlwarn[0] != ' ') {
        fprintf(err_fp,"acid: sqlwarn: ");
        for(j = 0; j < 8; j++) fprintf(err_fp,"%c ",
psqlca->sqlwarn[j]);
        fprintf(err_fp,"\n");
    }

    fprintf(err_fp,"\n");
    fflush(err_fp);fclose(err_fp);
}

#ifdef SQLWINT
void sleep(int sec)
{
    Sleep(sec * 1000);
}
#endif

char del(void)
{
#ifdef SQLWINT
    return "\\";
#else
    return '/';
#endif
}

#ifdef defined(SQLPTX) || defined(SQLWINT) ||
defined(SQLSUN) || defined(Linux)
/* added for PTX as this one is not there in libm */
double nearest(double x)
{
    double y, z;

    y = x;
    if (x < 0)
        y = -x;
    z = y - (int)y;
    if (z == 0.5) {
        if ((int)floor(y) % 2) {
            return((x < 0) ? -ceil(y) : ceil(y));
        }
    }
}

```

```

    } else {
        return((x < 0) ? -floor(y) : floor(y));
    }
} else if (z < 0.5)
    return((x < 0) ? -floor(y) : floor(y));
else
    return((x < 0) ? -ceil(y) : ceil(y));
}
#endif /* SQLPTX */

```

-

### **makefile**

```

DBNAME =
    $(TPCD_QUAL_DBNAME)

INCLUDE = $(HOME)/sqllib/include

#CFLAGS = -I$(INCLUDE) -g -
Dpascal= -DLINT_ARGS \
# -Dfar= -D_loadds= -DSQLA_NOLINES
-qflag=i:i -qlanglvl=ansi

#LFLAGS = -lm -lcurses -ls -ll -ly -liconv -lbsd
CFLAGS = -I$(INCLUDE) -
Dpascal= -DLINT_ARGS \
    -DSQLA_NOLINES -DLinux
# .. sun -DSQLA_NOLINES

LFLAGS = -lm
# sun .... LFLAGS = -lm

LIB = -L$(HOME)/sqllib/lib -ldb2

CC = g++

HDR = acid.h
C = mainacid.c
SQC = acid.sqc
SRC = $(HDR) $(C)
    $(SQC)

OBJ = acid.o
EXEC = mainacid

TARGET = $(EXEC) tsec

.SUFFIXES: .o .c .sqc .bnd

.c.o:
    $(CC) -c $< $(CFLAGS)

all: $(TARGET)

mainacid: $(SRC) $(OBJ) mainacid.o

```

```

$(CC) -o $@ $(CFLAGS) $(OBJ)
mainacid.o $(LIB) $(LFLAGS)

acid.c: acid.sqc $(HDR)
    db2 connect to $(DBNAME); \
    db2 prep acid.sqc BINDFILE ISOLATION
RR NOLINEMACRO PACKAGE; \
    db2 bind acid.bnd GRANT PUBLIC; \
    db2 connect reset; \
    db2 terminate

```

```

acid.o: acid.c
    $(CC) $(CFLAGS) -c acid.c -o acid.o

```

```

tsec: tsec.c
    $(CC) $(CFLAGS) $(LFLAGS) -o tsec

```

tsec.c

```

clean:
    rm -f *.o *.bnd $(EXEC) tsec
    rm -f acid.c

```

# Appendix F: Price Quotations

07-25-03 10:10 From-SuSE Inc

+510 628 3381

T-129 P.002/002 F-067

## Quotation

SuSE Inc.  
318 Harrison St.  
Suite 301  
Oakland, CA 94607  
USA

Quote Number:  
183

Quote Date:  
Jul 25, 2003

Page:  
1

**Quoted to:**  
IBM Corporation - Endicott  
Accounts Payable  
P.O.Box 9005  
Endicott, NY 13761  
USA

Customer ID	Good Thru	Payment Terms	Sales Rep
CCIBM02	8/24/03	Net 45 Days	SEHOL01

Quantity	Item	Description	Unit Price	Extension
1.00	2119-3INT-8	SuSE Linux Enterprise Server 8 Opteron for AMD64, Includes Media Kit and 1 Year Maintenance Program for 8 CPUs.	2,585.00	2,585.00
4.00	2119-3-MFJ-8	SuSE Linux Enterprise Server 8 for AMD64 - 1 Year Maintenance Program for 8 CPUs SuSE, Inc. confirms that these are official list prices for the products listed.	2,456.00	9,824.00
			<b>Subtotal</b>	12,409.00
			<b>Sales Tax</b>	
			<b>Freight</b>	
			<b>Total</b>	12,409.00





Home | About CDW | Customer Support | View Cart | Log

SmartSearch™

Brands Hardware Software Networking Accessories Services

800 839 4239

**RESOURCES**

- Order Status
- My Company
- My Account
- Account Team
- New Accounts
- Rebates
- Special Events
- CDW Outlet
- Technical Support
- E-New sletters
- Solutions Library

ONLINEHELP

PRINTABLE VERSION



Image not Available

**Manufacturer**



**Product Links**

- > Similar Products
- > Send to Associate

**QLOGIC 133MHZ PCI-X 2GB DUAL POR**

**Product Information**



**Usually Ships:**

**CDW Part:**

**Mfg. Part:**

**UNSPSC:**

**Sales Rank:**

**Price:**

**ADD**

Copyright 2003 CDW Corporation

[Terms and Conditions of Use](#) | [Terms and Conditions of Sale](#) | [Privacy Pledge](#)

- RESOURCES**
- Order Status
  - My Company
  - My Account
  - Account Team
  - New Accounts
  - Rebates
  - Special Events
  - CDW Outlet
  - Technical Support
  - E-Newsletters
  - Solutions Library
  - Reference Guides

- ONLINEHELP**
- PRINTABLE VERSION**

# SHOPPING CART

- Your Saved Carts
- Save This Cart
- Edit Saved Carts
- Send To An Associate

## YOUR SHOPPING CART :

Quantity	Product	CDW	Usually Ships	Price	Ext. Price
<input type="text" value="8"/>	<a href="#">Cisco 1000BASE-T GBIC Module</a>	372656	Same Day	\$299.09	\$2,392.72
<input type="text" value="1"/>	<a href="#">Cisco Catalyst 3508G XL Enterprise Edition</a>	184837	Same Day	\$3,599.74	\$3,599.74
<input type="text" value="3"/>	<a href="#">Cisco SMARTnet Onsite 1 Year 24x7 4 Hour</a>	183063	1-2 Weeks	\$407.68	\$1,223.04
Click  to remove an item from your cart				Sub-Total	\$7,215.50

**QuickCart:**

Enter a **CDW part number** to quickly add it to your cart.

\* Sample: CDW Part #

Usually Ships:	<input type="text" value="Same Day"/>
CDW Part:	<input type="text" value="XXXXXXX"/>
Mfg. Part:	<input type="text" value="XXXXXX-XXXXXX"/>
UNSPSC:	<input type="text" value="XXXXXXX"/>

**Shipping Calc:**

Enter a postal code to quickly estimate shipping cost.